

NAME

CUTEST_cdimsj – CUTEst tool to determine number of nonzeros to store the matrix of gradients of the objective function and constraints, in sparse format.

SYNOPSIS

CALL CUTEST_cdimsj(status, nnzj)

DESCRIPTION

The CUTEST_cdimsj subroutine determines the number of nonzero elements required to store the matrix of gradients of the objective function and constraint functions for the problem decoded into OUTSDIF.d in the constrained minimization case. The matrix is stored in sparse format.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to general equations $c_i(x) = 0$, ($i \in 1, \dots, m_E$), general inequalities $c_i^l(x) \leq c_i(x) \leq c_i^u(x)$, ($i \in m_E + 1, \dots, m$), and simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable and all constraint functions are partially separable.

ARGUMENTS

The arguments of CUTEST_cdimsj are as follows

status [out] - integer

the output status: 0 for a succesful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

nnzj [out] - integer

the number of nonzero elements in the Jacobian matrix.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

sifdecode(1).

NAME

CUTEST_cdimsj – CUTEst tool to determine number of nonzeros to store the matrix of gradients of the objective function and constraints, in sparse format.

SYNOPSIS

CALL CUTEST_cdimsj(status, nnzj)

DESCRIPTION

The CUTEST_cdimsj subroutine determines the number of nonzero elements required to store the matrix of gradients of the objective function and constraint functions for the problem decoded into OUTSDIF.d in the constrained minimization case. The matrix is stored in sparse format.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to general equations $c_i(x) = 0$, ($i \in 1, \dots, m_E$), general inequalities $c_i^l(x) \leq c_i(x) \leq c_i^u(x)$, ($i \in m_E + 1, \dots, m$), and simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable and all constraint functions are partially separable.

ARGUMENTS

The arguments of CUTEST_cdimsj are as follows

status [out] - integer

the output status: 0 for a succesful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

nnzj [out] - integer

the number of nonzero elements in the Jacobian matrix.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

sifdecode(1).