

NAME

CUTEST_csetup – CUTEst tool to set up the data structures for constrained minimization.

SYNOPSIS

CALL CUTEST_csetup(status, input, out, io_buffer, n, m, X, X_l, X_u, Y, C_l, C_u, EQUATN, LINEAR, efirst, lfirst, nvfirst)

DESCRIPTION

The CUTEST_csetup subroutine sets up the correct data structures for subsequent computations on the problem decoded from a SIF file by the script *sifdecode*. The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to general equations $c_i(x) = 0$, ($i \in 1, \dots, m_E$), general inequalities $c_i^l(x) \leq c_i(x) \leq c_i^u(x)$, ($i \in m_E + 1, \dots, m$), and simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable and all constraint functions are partially separable.

ARGUMENTS

The arguments of CUTEST_csetup are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

input [in] - integer

the unit number for the decoded data; the unit from which OUTSDIF.d is read,

out [in] - integer

the unit number for any error messages,

io_buffer [in] - integer

the unit number for any internal input/output,

n [out] - integer

the number of variables for the problem,

m [out] - integer

the total number of general constraints,

X [out] - real/double precision

an array that gives the initial estimate of the solution of the problem,

X_l [out] - real/double precision

an array that gives lower bounds on the variables,

X_u [out] - real/double precision

an array that gives upper bounds on the variables,

Y [out] - real/double precision

an array that gives the initial estimate of the Lagrange multipliers at the solution of the problem. By convention, the signs of the Lagrange multipliers Y are set so the Lagrangian function can be written as $l(x, y) = f(x) + y^T c(x)$,

C_l [out] - real/double precision

an array that gives lower bounds on the inequality constraints,

C_u [out] - real/double precision

an array that gives upper bounds on the inequality constraints,

EQUATN [out] - logical

a logical array whose i -th component is `.TRUE.` if the i -th constraint is an equation (i in E) and `.FALSE.` if the constraint is an inequality (i in I),

LINEAR [out] - logical

a logical array whose i -th component is `.TRUE.` if the i -th constraint is linear or affine and `.FALSE.` otherwise,

efirst [in] - logical

logical variable that should be set .TRUE. if the user wishes the general equations to occur before the general inequalities in the list of constraints. If the order is unimportant, efirst should be set to .FALSE.,

lfirst [in] - logical

a logical variable that should be set .TRUE. if the user wishes the general linear (or affine) constraints to occur before the general nonlinear ones in the list of constraints. If the order is unimportant, lfirst should be set .FALSE. If both efirst and lfirst are set .TRUE., the linear constraints will occur before the nonlinear ones. The linear constraints will be ordered so that the linear equations occur before the linear inequalities. Likewise, the nonlinear equations will appear before the nonlinear inequalities in the list of nonlinear constraints,

nvfirst [in] - logical

a logical variable that should be set .TRUE. if the user wishes that the nonlinear variables come first. Within the nonlinear variables the smaller set of either the nonlinear objective or nonlinear Jacobian variables appears first.

APPLICATION USAGE

A call to CUTEst_csetup must precede calls to other evaluation tools, except CUTEst_cdimen, for generally-constrained problems.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_usetup(3M), sifdecode(1).

NAME

CUTEST_csetup – CUTEst tool to set up the data structures for constrained minimization.

SYNOPSIS

CALL CUTEST_csetup(status, input, out, io_buffer, n, m, X, X_l, X_u, Y, C_l, C_u, EQUATN, LINEAR, efirst, lfirst, nvfirst)

DESCRIPTION

The CUTEST_csetup subroutine sets up the correct data structures for subsequent computations on the problem decoded from a SIF file by the script *sifdecode*. The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to general equations $c_i(x) = 0$, ($i \in 1, \dots, m_E$), general inequalities $c_i^l(x) \leq c_i(x) \leq c_i^u(x)$, ($i \in m_E + 1, \dots, m$), and simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable and all constraint functions are partially separable.

ARGUMENTS

The arguments of CUTEST_csetup are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

input [in] - integer

the unit number for the decoded data; the unit from which OUTSDIF.d is read,

out [in] - integer

the unit number for any error messages,

io_buffer [in] - integer

the unit number for any internal input/output,

n [out] - integer

the number of variables for the problem,

m [out] - integer

the total number of general constraints,

X [out] - real/double precision

an array that gives the initial estimate of the solution of the problem,

X_l [out] - real/double precision

an array that gives lower bounds on the variables,

X_u [out] - real/double precision

an array that gives upper bounds on the variables,

Y [out] - real/double precision

an array that gives the initial estimate of the Lagrange multipliers at the solution of the problem. By convention, the signs of the Lagrange multipliers Y are set so the Lagrangian function can be written as $l(x, y) = f(x) + y^T c(x)$,

C_l [out] - real/double precision

an array that gives lower bounds on the inequality constraints,

C_u [out] - real/double precision

an array that gives upper bounds on the inequality constraints,

EQUATN [out] - logical

a logical array whose i -th component is `.TRUE.` if the i -th constraint is an equation (i in E) and `.FALSE.` if the constraint is an inequality (i in I),

LINEAR [out] - logical

a logical array whose i -th component is `.TRUE.` if the i -th constraint is linear or affine and `.FALSE.` otherwise,

efirst [in] - logical

logical variable that should be set .TRUE. if the user wishes the general equations to occur before the general inequalities in the list of constraints. If the order is unimportant, efirst should be set to .FALSE.,

lfirst [in] - logical

a logical variable that should be set .TRUE. if the user wishes the general linear (or affine) constraints to occur before the general nonlinear ones in the list of constraints. If the order is unimportant, lfirst should be set .FALSE. If both efirst and lfirst are set .TRUE., the linear constraints will occur before the nonlinear ones. The linear constraints will be ordered so that the linear equations occur before the linear inequalities. Likewise, the nonlinear equations will appear before the nonlinear inequalities in the list of nonlinear constraints,

nvfirst [in] - logical

a logical variable that should be set .TRUE. if the user wishes that the nonlinear variables come first. Within the nonlinear variables the smaller set of either the nonlinear objective or nonlinear Jacobian variables appears first.

APPLICATION USAGE

A call to CUTEst_csetup must precede calls to other evaluation tools, except CUTEst_cdimen, for generally-constrained problems.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_usetup(3M), sifdecode(1).