## **NAME**

CUTEST\_creport\_threaded - CUTEst tool to obtain statistics concerning function evaluation and CPU time used.

## **SYNOPSIS**

CALL CUTEST\_creport\_threaded( status, CALLS, TIME, thread )

#### DESCRIPTION

The CUTEST\_creport\_threaded subroutine obtains statistics concerning function evaluation and CPU time used for constrained optimization in a standardized format.

The problem under consideration is to minimize or maximize an objective function f(x) over all  $x \in \mathbb{R}^n$  subject to general equations  $c_i(x) = 0$ ,  $(i \in 1, ..., m_E)$ , general inequalities  $c_i^l \le c_i(x) \le c_i^u$ ,  $(i \in m_E + 1, ..., m)$ , and simple bounds  $x^l \le x \le x^u$ . The objective function is group-partially separable and all constraint functions are partially separable.

#### **ARGUMENTS**

The arguments of CUTEST\_creport\_threaded are as follows

status [out] - integer

the outputr status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error, 4 for an out-of-range thread,

**CALLS** [out] - real array of length 7

gives the number of calls to the problem functions:

CALLS(1): number of calls to the objective function

CALLS(2): number of calls to the objective gradient

CALLS(3): number of calls to the objective Hessian

CALLS(4): number of Hessian times vector products

CALLS(5): number of calls to the constraint functions

CALLS(6): number of calls to the constraint gradients

CALLS(7): number of calls to the constraint Hessians,

**TIME** [out] - real array of length 2:

TIME(1): CPU time (in seconds) for CUTEST\_csetup\_threaded

TIME(2): CPU time (in seconds) since the end of CUTEST\_csetup\_threaded,

thread [in] - integer

statistics are for the specified thread; threads are numbered from 1 to the value threads set when calling CUTEST usetup threaded.

## **NOTE**

Note that CALLS(4), CALLS(5) and CALLS(6) may account for codes which allow the evaluation of a selection of constraints only and may thus be much smaller than the number of constraints times the number of iterations.

# **AUTHORS**

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

### **SEE ALSO**

CUTEst: a Constrained and Unconstrained Testing Environment with safe threads,

N.I.M. Gould, D. Orban and Ph.L. Toint,

Computational Optimization and Applications **60**:3, pp.545-557, 2014.

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint, ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, ACM TOMS, **21**:1, pp.123-160, 1995.