

NAME

CUTEST_ugrdh – CUTEst tool to evaluate the gradient and Hessian matrix.

SYNOPSIS

CALL CUTEST_ugrdh(status, n, X, G, lh1, H_val)

DESCRIPTION

The CUTEST_ugrdh subroutine evaluates the gradient and Hessian matrix of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X. This Hessian matrix is stored as a dense matrix.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_ugrdh are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

X [in] - real/double precision

an array which gives the current estimate of the solution of the problem,

G [out] - real/double precision

an array which gives the value of the gradient of the objective function evaluated at X,

lh1 [in] - integer

the actual declared size of the leading dimension of H_val (with lh1 no smaller than N),

H_val [out] - real/double precision

a two-dimensional array which gives the value of the Hessian matrix of the objective function evaluated at X.

NOTE

Calling this routine is more efficient than separate calls to CUTEST_ugr and CUTEST_udh.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint,

ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_cgrdh(3M), sifdecode(1).

NAME

CUTEST_ugrdh – CUTEst tool to evaluate the gradient and Hessian matrix.

SYNOPSIS

CALL CUTEST_ugrdh(status, n, X, G, lh1, H_val)

DESCRIPTION

The CUTEST_ugrdh subroutine evaluates the gradient and Hessian matrix of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X. This Hessian matrix is stored as a dense matrix.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_ugrdh are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

X [in] - real/double precision

an array which gives the current estimate of the solution of the problem,

G [out] - real/double precision

an array which gives the value of the gradient of the objective function evaluated at X,

lh1 [in] - integer

the actual declared size of the leading dimension of H_val (with lh1 no smaller than N),

H_val [out] - real/double precision

a two-dimensional array which gives the value of the Hessian matrix of the objective function evaluated at X.

NOTE

Calling this routine is more efficient than separate calls to CUTEST_ugr and CUTEST_udh.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint,

ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_cgrdh(3M), sifdecode(1).