

NAME

CUTEST_ureport – CUTEst tool to obtain statistics concerning function evaluation and CPU time used.

SYNOPSIS

CALL CUTEST_ureport(data, status, CALLS, TIME)

DESCRIPTION

The CUTEST_ureport subroutine obtains statistics concerning function evaluation and CPU time used for unconstrained or bound-constrained optimization in a standardized format.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_ureport are as follows

data [inout] - CUTEST_data_type derived type
problem-specific private data,

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

CALLS [out] - real array of length 4

gives the number of calls to the problem functions:

CALLS(1): number of calls to the objective function

CALLS(2): number of calls to the objective gradient

CALLS(3): number of calls to the objective Hessian

CALLS(4): number of Hessian times vector products

TIME [out] - real array of length 2:

TIME(1): CPU time (in seconds) for CUTEST_usetup

TIME(2): CPU time (in seconds) since the end of CUTEST_usetup.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

NAME

CUTEST_ureport – CUTEst tool to obtain statistics concerning function evaluation and CPU time used.

SYNOPSIS

CALL CUTEST_ureport(data, status, CALLS, TIME)

DESCRIPTION

The CUTEST_ureport subroutine obtains statistics concerning function evaluation and CPU time used for unconstrained or bound-constrained optimization in a standardized format.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_ureport are as follows

data [inout] - CUTEST_data_type derived type
problem-specific private data,

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

CALLS [out] - real array of length 4

gives the number of calls to the problem functions:

CALLS(1): number of calls to the objective function

CALLS(2): number of calls to the objective gradient

CALLS(3): number of calls to the objective Hessian

CALLS(4): number of Hessian times vector products

TIME [out] - real array of length 2:

TIME(1): CPU time (in seconds) for CUTEST_usetup

TIME(2): CPU time (in seconds) since the end of CUTEST_usetup.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.