

NAME

CUTEST_unames – CUTEst tool to obtain the names of the problem and its variables.

SYNOPSIS

CALL CUTEST_unames(status, n, pname, VNAME)

DESCRIPTION

The CUTEST_unames subroutine obtains the names of the problem and its variables.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_unames are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

pname [out] - character

a 10-character string containing the name of the problem,

VNAME [out] - character

an array of 10-character strings containing the names of the variables.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_cnames(3M).

NAME

CUTEST_unames – CUTEst tool to obtain the names of the problem and its variables.

SYNOPSIS

CALL CUTEST_unames(status, n, pname, VNAME)

DESCRIPTION

The CUTEST_unames subroutine obtains the names of the problem and its variables.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_unames are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

pname [out] - character

a 10-character string containing the name of the problem,

VNAME [out] - character

an array of 10-character strings containing the names of the variables.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_cnames(3M).