#### **NAME**

CUTEST\_udimen - CUTEst tool to get the number of variables involved.

#### **SYNOPSIS**

CALL CUTEST\_udimen( status, input, n )

## DESCRIPTION

The CUTEST\_udimen subroutine discovers how many variables are involved in the problem decoded from a SIF file by the script *sifdecoder*.

The problem under consideration is to minimize or maximize an objective function f(x) over all  $x \in \mathbb{R}^n$  subject to the simple bounds  $x^l \le x \le x^u$ . The objective function is group-partially separable.

## **ARGUMENTS**

The arguments of CUTEST\_udimen are as follows

status [out] - integer

the outputr status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

input [in] - integer

the unit number for the decoded data; the unit from which OUTSDIF.d is read,

n [out] - integer

the number of variables for the problem,

# **AUTHORS**

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

## **SEE ALSO**

CUTEst: a Constrained and Unconstrained Testing Environment with safe threads,

N.I.M. Gould, D. Orban and Ph.L. Toint,

Technical Report, Rutherford Appleton Laboratory, 2013.

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint,

ACM TOMS, 29:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, ACM TOMS, 21:1, pp.123-160, 1995.

cutest cdimen(3M), sifdecoder(1).