

**NAME**

CUTEST\_ubandh\_threaded – CUTEst tool to extract a banded matrix from the Hessian matrix.

**SYNOPSIS**

CALL CUTEST\_ubandh\_threaded( status, n, goth, X, nsemib, BANDH, lbandh, thread )

**DESCRIPTION**

The CUTEST\_ubandh\_threaded subroutine extracts the elements which lie within a band of given semi-bandwidth out of the Hessian matrix of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X.

The problem under consideration is to minimize or maximize an objective function  $f(x)$  over all  $x \in R^n$  subject to the simple bounds  $x^l \leq x \leq x^u$ . The objective function is group-partially separable.

**ARGUMENTS**

The arguments of CUTEST\_ubandh\_threaded are as follows

**status** [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error, 4 for an out-of-range thread,

**n** [in] - integer

the number of variables for the problem,

**goth** [in] - integer

a logical variable which specifies whether the second derivatives of the groups and elements have already been set (goth = .TRUE.) or if they should be computed (goth = .FALSE.),

**X** [in] - real/double precision

when GOTH = .FALSE., the derivatives will be evaluated at X. Otherwise X is not used.

**nsemib** [in] - integer

the required semi-bandwidth, i.e., the number of bands directly below the diagonal of the Hessian.

**BANDH** [out] - real/double precision

a two-dimensional array of dimension (0:lbandh,n) which gives the lower triangular part of the band segment of the Hessian. The diagonal entry in column i is returned in location BANDH(0,i), while the entry j places below the diagonal in column i may be found in location BANDH(j,i),

**lbandh** [in] - integer

the actual declared size of the leading dimension of BANDH (with lbandh no smaller than nsemib). N.B. the leading component of BANDH includes the index 0 so strictly, the size of the leading dimension is lbandh + 1.

**NOTE**

goth should be set to .TRUE. whenever

- (1) a call has been made to CUTEST\_udh\_threaded, CUTEST\_ush\_threaded, CUTEST\_ugrdh\_threaded or CUTEST\_ugrsh\_threaded at the current point, or
- (2) a previous call to CUTEST\_ubandh\_threaded, with goth = .FALSE., at the current point has been made.

Otherwise, it should be set .FALSE.,

**thread** [in] - integer

thread chosen for the evaluation; threads are numbered from 1 to the value threads set when calling CUTEST\_usetup\_threaded.

**AUTHORS**

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

**SEE ALSO**

*CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited*,  
N.I.M. Gould, D. Orban and Ph.L. Toint,  
ACM TOMS, **29**:4, pp.373-394, 2003.

*CUTE: Constrained and Unconstrained Testing Environment*, I. Bongartz, A.R. Conn, N.I.M. Gould and  
Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

sifdecode(1).

**NAME**

CUTEST\_ubandh\_threaded – CUTEst tool to extract a banded matrix from the Hessian matrix.

**SYNOPSIS**

CALL CUTEST\_ubandh\_threaded( status, n, goth, X, nsemib, BANDH, lbandh, thread )

**DESCRIPTION**

The CUTEST\_ubandh\_threaded subroutine extracts the elements which lie within a band of given semi-bandwidth out of the Hessian matrix of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X.

The problem under consideration is to minimize or maximize an objective function  $f(x)$  over all  $x \in R^n$  subject to the simple bounds  $x^l \leq x \leq x^u$ . The objective function is group-partially separable.

**ARGUMENTS**

The arguments of CUTEST\_ubandh\_threaded are as follows

**status** [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error, 4 for an out-of-range thread,

**n** [in] - integer

the number of variables for the problem,

**goth** [in] - integer

a logical variable which specifies whether the second derivatives of the groups and elements have already been set (goth = .TRUE.) or if they should be computed (goth = .FALSE.),

**X** [in] - real/double precision

when GOTH = .FALSE., the derivatives will be evaluated at X. Otherwise X is not used.

**nsemib** [in] - integer

the required semi-bandwidth, i.e., the number of bands directly below the diagonal of the Hessian.

**BANDH** [out] - real/double precision

a two-dimensional array of dimension (0:lbandh,n) which gives the lower triangular part of the band segment of the Hessian. The diagonal entry in column i is returned in location BANDH(0,i), while the entry j places below the diagonal in column i may be found in location BANDH(j,i),

**lbandh** [in] - integer

the actual declared size of the leading dimension of BANDH (with lbandh no smaller than nsemib). N.B. the leading component of BANDH includes the index 0 so strictly, the size of the leading dimension is lbandh + 1.

**NOTE**

goth should be set to .TRUE. whenever

- (1) a call has been made to CUTEST\_udh\_threaded, CUTEST\_ush\_threaded, CUTEST\_ugrdh\_threaded or CUTEST\_ugrsh\_threaded at the current point, or
- (2) a previous call to CUTEST\_ubandh\_threaded, with goth = .FALSE., at the current point has been made.

Otherwise, it should be set .FALSE.,

**thread** [in] - integer

thread chosen for the evaluation; threads are numbered from 1 to the value threads set when calling CUTEST\_usetup\_threaded.

**AUTHORS**

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

**SEE ALSO**

*CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited*,  
N.I.M. Gould, D. Orban and Ph.L. Toint,  
ACM TOMS, **29**:4, pp.373-394, 2003.

*CUTE: Constrained and Unconstrained Testing Environment*, I. Bongartz, A.R. Conn, N.I.M. Gould and  
Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

sifdecode(1).