

NAME

CUTEST_cshc – CUTEst tool to evaluate the Hessian of the constraint part of the Lagrangian, in sparse format.

SYNOPSIS

CALL CUTEST_cshc(status, n, m, X, Y, nnzh, lh, H_val, H_row, H_col)

DESCRIPTION

The CUTEST_cshc subroutine evaluates the constraint part of the Hessian of the Lagrangian function $y^T c(x)$ for the problem decoded from a SIF file by the script *sifdecoder* at the point $(x, y) = (X, Y)$. The matrix is stored in sparse format.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to general equations $c_i(x) = 0$, ($i \in 1, \dots, m_E$), general inequalities $c_i^l(x) \leq c_i(x) \leq c_i^u(x)$, ($i \in m_E + 1, \dots, m$), and simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable and all constraint functions are partially separable.

ARGUMENTS

The arguments of CUTEST_cshc are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

m [in] - integer

the total number of general constraints,

X [in] - real/double precision

an array which gives the current estimate of the solution of the problem,

Y [in] - real/double precision

an array which gives the Lagrange multipliers,

nnzh [out] - integer

the number of nonzeros in H_val,

lh [in] - integer

the actual declared dimensions of H_val, H_row and H_col,

H_val [out] - real/double precision

an array which gives the values of the constraint part of the Hessian matrix of the Lagrangian function evaluated at X and Y. The i-th entry of H_val gives the value of the nonzero in row H_row(i) and column H_col(i). Only the upper triangular part of the Hessian is stored,

H_row [out] - integer

an array which gives the row indices of the nonzeros of the Hessian matrix of the constraint part of the Lagrangian function evaluated at X and Y, and

H_col [out] - integer

an array which gives the column indices of the nonzeros of the Hessian matrix of the constraint part of the Lagrangian function evaluated at X and Y.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEst: a Constrained and Unconstrained Testing Environment with safe threads,
N.I.M. Gould, D. Orban and Ph.L. Toint,
Technical Report, Rutherford Appleton Laboratory, 2013.

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and
Ph.L. Toint, ACM TOMS, **21**:1, pp.123-160, 1995.

cutest_csh(3M), cutest_ush(3M), sifdecoder(1).

NAME

CUTEST_cshc – CUTEst tool to evaluate the Hessian of the constraint part of the Lagrangian, in sparse format.

SYNOPSIS

CALL CUTEST_cshc(status, n, m, X, Y, nnzh, lh, H_val, H_row, H_col)

DESCRIPTION

The CUTEST_cshc subroutine evaluates the constraint part of the Hessian of the Lagrangian function $y^T c(x)$ for the problem decoded from a SIF file by the script *sifdecoder* at the point $(x, y) = (X, Y)$. The matrix is stored in sparse format.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to general equations $c_i(x) = 0$, ($i \in 1, \dots, m_E$), general inequalities $c_i^l(x) \leq c_i(x) \leq c_i^u(x)$, ($i \in m_E + 1, \dots, m$), and simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable and all constraint functions are partially separable.

ARGUMENTS

The arguments of CUTEST_cshc are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

m [in] - integer

the total number of general constraints,

X [in] - real/double precision

an array which gives the current estimate of the solution of the problem,

Y [in] - real/double precision

an array which gives the Lagrange multipliers,

nnzh [out] - integer

the number of nonzeros in H_val,

lh [in] - integer

the actual declared dimensions of H_val, H_row and H_col,

H_val [out] - real/double precision

an array which gives the values of the constraint part of the Hessian matrix of the Lagrangian function evaluated at X and Y. The i-th entry of H_val gives the value of the nonzero in row H_row(i) and column H_col(i). Only the upper triangular part of the Hessian is stored,

H_row [out] - integer

an array which gives the row indices of the nonzeros of the Hessian matrix of the constraint part of the Lagrangian function evaluated at X and Y, and

H_col [out] - integer

an array which gives the column indices of the nonzeros of the Hessian matrix of the constraint part of the Lagrangian function evaluated at X and Y.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEst: a Constrained and Unconstrained Testing Environment with safe threads,
N.I.M. Gould, D. Orban and Ph.L. Toint,
Technical Report, Rutherford Appleton Laboratory, 2013.

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and
Ph.L. Toint, ACM TOMS, **21**:1, pp.123-160, 1995.

cutest_csh(3M), cutest_ush(3M), sifdecoder(1).