

NAME

CUTEST_uvartype – CUTEst tool to determine the type of each variable.

SYNOPSIS

CALL CUTEST_uvartype(status, n, X_type)

DESCRIPTION

The CUTEST_uvartype subroutine determines the type (continuous, 0-1, integer) of each variable involved in the problem decoded from a SIF file by the script *sifdecode*.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_uvartype are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

X_type [out] - integer

an integer array whose i-th component indicates the type of variable i. Possible values are 0 (a variable whose value may be any real number), 1 (an integer variable that can only take the values zero or one) and 2 (a variable that can only take integer values).

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint,

ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_cvartype(3M), sifdecode(1).

NAME

CUTEST_uvartype – CUTEst tool to determine the type of each variable.

SYNOPSIS

CALL CUTEST_uvartype(status, n, X_type)

DESCRIPTION

The CUTEST_uvartype subroutine determines the type (continuous, 0-1, integer) of each variable involved in the problem decoded from a SIF file by the script *sifdecode*.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_uvartype are as follows

status [out] - integer

the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

X_type [out] - integer

an integer array whose i-th component indicates the type of variable i. Possible values are 0 (a variable whose value may be any real number), 1 (an integer variable that can only take the values zero or one) and 2 (a variable that can only take integer values).

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint,

ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_cvartype(3M), sifdecode(1).