

NAME

CUTEST_ugr – CUTEst tool to evaluate gradient.

SYNOPSIS

CALL CUTEST_ugr(data, status, n, X, G)

DESCRIPTION

The CUTEST_ugr subroutine evaluates the gradient of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_ugr are as follows

data [inout] - CUTEST_data_type derived type
problem-specific private data,

status [out] - integer
the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer
the number of variables for the problem,

X [in] - real/double precision
an array which gives the current estimate of the solution of the problem,

G [out] - real/double precision
an array which gives the value of the gradient of the objective function evaluated at X.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_cgr(3M), sifdecode(1).

NAME

CUTEST_ugr – CUTEst tool to evaluate gradient.

SYNOPSIS

CALL CUTEST_ugr(data, status, n, X, G)

DESCRIPTION

The CUTEST_ugr subroutine evaluates the gradient of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X.

The problem under consideration is to minimize or maximize an objective function $f(x)$ over all $x \in R^n$ subject to the simple bounds $x^l \leq x \leq x^u$. The objective function is group-partially separable.

ARGUMENTS

The arguments of CUTEST_ugr are as follows

data [inout] - CUTEST_data_type derived type
problem-specific private data,

status [out] - integer
the output status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer
the number of variables for the problem,

X [in] - real/double precision
an array which gives the current estimate of the solution of the problem,

G [out] - real/double precision
an array which gives the value of the gradient of the objective function evaluated at X.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest_cgr(3M), sifdecode(1).