

Rajalakshmi Engineering College

Name: Sunetra B

Email: 241801282@rajalakshmi.edu.in

Roll no: 241801282

Phone: 9150958405

Branch: REC

Department: I AI & DS FD

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 1

Attempt : 3

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Your task is to create a program to manage a playlist of items. Each item is represented as a character, and you need to implement the following operations on the playlist.

Here are the main functionalities of the program:

Insert Item: The program should allow users to add items to the front and end of the playlist. Items are represented as characters. Display Playlist: The program should display the playlist containing the items that were added.

To implement this program, a doubly linked list data structure should be used, where each node contains an item character.

Input Format

The input consists of a sequence of space-separated characters, representing the items to be inserted into the doubly linked list.

The input is terminated by entering - (hyphen).

Output Format

The first line of output prints "Forward Playlist: " followed by the linked list after inserting the items at the end.

The second line prints "Backward Playlist: " followed by the linked list after inserting the items at the front.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: a b c -

Output: Forward Playlist: a b c

Backward Playlist: c b a

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    char item;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
void insertAtEnd(Node** head, char item) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->item = item;  
    newNode->next = NULL;  
    newNode->prev = NULL;
```

```
    if (*head == NULL) {  
        *head = newNode;  
    } else {  
        struct Node* temp = *head;
```

```
        while (temp->next != NULL)
            temp = temp->next;

        temp->next = newNode;
        newNode->prev = temp;
    }
}
```

```
void displayForward(struct Node* head) {
    struct Node* temp = head;
    while (temp != NULL) {
        printf("%c ", temp->item);
        temp = temp->next;
    }
    printf("\n");
}
```

```
void displayBackward(struct Node* head) {
    struct Node* temp = head;
    if (temp == NULL) return;

    while (temp->next != NULL)
        temp = temp->next;

    while (temp != NULL) {
        printf("%c ", temp->item);
        temp = temp->prev;
    }
    printf("\n");
}
```

```
void freePlaylist(struct Node* head) {
    struct Node* temp;
    while (head != NULL) {
        temp = head;
        head = head->next;
        free(temp);
    }
}
```

```
int main() {
    struct Node* playlist = NULL;
    char item;
```

```
while (1) {
    scanf(" %c", &item);
    if (item == '-') {
        break;
    }
    insertAtEnd(&playlist, item);
}

struct Node* tail = playlist;
while (tail->next != NULL) {
    tail = tail->next;
}

printf("Forward Playlist: ");
displayForward(playlist);

printf("Backward Playlist: ");
displayBackward(tail);

freePlaylist(playlist);

return 0;
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Sunetra B
Email: 241801282@rajalakshmi.edu.in
Roll no: 241801282
Phone: 9150958405
Branch: REC
Department: I AI & DS FD
Batch: 2028
Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 2

Attempt : 2
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Moniksha, a chess coach organizing a tournament, needs a program to manage participant IDs efficiently. The program maintains a doubly linked list of IDs and offers two functions: Append to add IDs as students register, and Print Maximum ID to identify the highest ID for administrative tasks.

This tool streamlines tournament organization, allowing Moniksha to focus on coaching her students effectively.

Input Format

The first line consists of an integer n , representing the number of participant IDs to be added.

The second line consists of n space-separated integers representing the participant IDs.

Output Format

The output displays a single integer, representing the maximum participant ID.

If the list is empty, the output prints "Empty list!".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

163 137 155

Output: 163

Answer

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int id;
    struct Node* next;
    struct Node* prev;
};
```

```
struct Node* createNode(int id) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->id = id;
    newNode->next = NULL;
    newNode->prev = NULL;
    return newNode;
}
```

```
void append(struct Node** head, int id) {
    struct Node* newNode = createNode(id);
    if (*head == NULL) {
        *head = newNode;
        return;
    }
    struct Node* temp = *head;
    while (temp->next != NULL) {
```

```
    temp = temp->next;
}
temp->next = newNode;
newNode->prev = temp;
}
```

```
int findMaxID(struct Node* head) {
    if (head == NULL) {
        return -1;
    }
    int maxID = head->id;
    struct Node* temp = head->next;
    while (temp != NULL) {
        if (temp->id > maxID) {
            maxID = temp->id;
        }
        temp = temp->next;
    }
    return maxID;
}
```

```
void freeList(struct Node* head) {
    struct Node* temp;
    while (head != NULL) {
        temp = head;
        head = head->next;
        free(temp);
    }
}
```

```
int main() {
    struct Node* head = NULL;
    int n;

    scanf("%d", &n);

    if (n == 0) {
        printf("Empty list!\n");
        return 0;
    }

    for (int i = 0; i < n; i++) {
```

```
int id;  
scanf("%d", &id);  
append(&head, id);  
}
```

```
int maxID = findMaxID(head);  
if (maxID != -1) {  
    printf("%d\n", maxID);  
} else {  
    printf("Empty list!\n");  
}
```

```
freeList(head);
```

```
return 0;
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Sunetra B

Email: 241801282@rajalakshmi.edu.in

Roll no: 241801282

Phone: 9150958405

Branch: REC

Department: I AI & DS FD

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 3

Attempt : 2

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Bob is tasked with developing a company's employee record management system. The system needs to maintain a list of employee records using a doubly linked list. Each employee is represented by a unique integer ID.

Help Bob to complete a program that adds employee records at the front, traverses the list, and prints the same for each addition of employees to the list.

Input Format

The first line of input consists of an integer N, representing the number of employees.

The second line consists of N space-separated integers, representing the employee IDs.

Output Format

For each employee ID, the program prints "Node Inserted" followed by the current state of the doubly linked list in the next line, with the data values of each node separated by spaces.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4

101 102 103 104

Output: Node Inserted

101

Node Inserted

102 101

Node Inserted

103 102 101

Node Inserted

104 103 102 101

Answer

```
#include <iostream>
using namespace std;
```

```
struct node {
    int info;
    struct node* prev, * next;
};
```

```
struct node* start = NULL;
```

```
void traverse() {
    struct node* temp;
    temp = start;
    while (temp != NULL) {
        printf("%d ", temp->info);
        temp = temp->next;
    }
    printf("\n");
}
```

```
void insertAtFront(int data) {
    struct node* temp;
    temp = (struct node*)malloc(sizeof(struct node));
    temp->info = data;
    temp->prev = NULL;
    temp->next = start;
    if (start != NULL)
        start->prev = temp;
    start = temp;
    printf("Node Inserted\n");
}

int main() {
    int n, data;
    cin >> n;
    for (int i = 0; i < n; ++i) {
        cin >> data;
        insertAtFront(data);
        traverse();
    }
    return 0;
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Sunetra B

Email: 241801282@rajalakshmi.edu.in

Roll no: 241801282

Phone: 9150958405

Branch: REC

Department: I AI & DS FD

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 4

Attempt : 2

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

Input Format

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

Output Format

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

10 20 30 40 50

Output: 10 20 30 40 50

Answer

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct node {  
    int id;  
    struct node* prev;  
    struct node* next;  
};
```

```
struct node* start = NULL;
```

```
void insertAtEnd(int data) {  
    struct node* newNode = (struct node*)malloc(sizeof(struct node));  
    newNode->id = data;  
    newNode->prev = NULL;  
    newNode->next = NULL;
```

```
    if (start == NULL) {  
        start = newNode;  
    } else {  
        struct node* temp = start;  
        while (temp->next != NULL) {  
            temp = temp->next;
```

```
    }  
    temp->next = newNode;  
    newNode->prev = temp;  
}  
}
```

```
void traverse() {  
    struct node* temp = start;  
    while (temp != NULL) {  
        printf("%d ", temp->id);  
        temp = temp->next;  
    }  
    printf("\n");  
}
```

```
int main() {  
    int n, i, id;
```

```
    scanf("%d", &n);
```

```
    for (i = 0; i < n; i++) {  
        scanf("%d", &id);  
        insertAtEnd(id);  
    }
```

```
    traverse();
```

```
    return 0;
```

```
}
```

Status : Correct

Marks : 10/10