DOCUMENTDB

June 17, 2021

```python
[4]: from pathlib import Path
     import json
     import os
     from tinydb import TinyDB
     current_dir = Path(os.getcwd()).absolute()
     results_dir = current_dir.joinpath('results')
     kv_data_dir = results_dir.joinpath('kvdb')
     kv_data_dir.mkdir(parents=True, exist_ok=True)
     def _load_json(json_path):
         with open(json_path) as f:
             return json.load(f)
     class DocumentDB(object):
         def __init__(self, db_path):
             ## You can use the code from the previous exmaple if you would like
             people_json = kv_data_dir.joinpath('people.json')
             visited_json = kv_data_dir.joinpath('visited.json')
             sites_json = kv_data_dir.joinpath('sites.json')
             measurements_json = kv_data_dir.joinpath('measurements.json')
             self._db_path = Path(db_path)
             self._db = None
             self._person_lookup = _load_json(people_json)
             self._visit_lookup = _load_json(visited_json)
             self._site_lookup = _load_json(sites_json)
             self._measurements_lookup = _load_json(measurements_json)
             self._load_db()

         def _get_site(self, site_id):
             return self._site_lookup[str(site_id)]

         def _get_measurements(self, person_id):
             measurements = []
             for values in self._measurements_lookup.values():
                 measurements.extend([value for value in values if
     →str(['person_id']) == str(person_id)])
             return measurements

         def _get_visit(self, visit_id):
```

1

```python
        visit = self._visit_lookup.get(str(visit_id))
        site_id = str(visit['site_id'])
        site = self._site_lookup[site_id]
        visit['site'] = site
        return visit

    def _load_db(self):
        self._db = TinyDB(self._db_path)
        persons = self._person_lookup.items()
        for person_id, record in persons:
            measurements = self._get_measurements(person_id)
            visit_ids = set([measurement['visit_id'] for measurement in
    →measurements])
            visits = []
            for visit_id in visit_ids:
                visit = self._get_visit(visit_id)
                visit['measurements'] = [
                    measurement for measurement in measurements
                    if visit_id == measurement['visit_id']
                ]
                visits.append(visit)
            record['visits'] = visits
            self._db.insert(record)
```

```python
[5]: db_path = results_dir.joinpath('patient-info.json')
    if db_path.exists():
        os.remove(db_path)

    db = DocumentDB(db_path)
```

[ ]: