

# TSKS04 Digital Communication Continuation Course

## Solutions for the exam 2015-06-08

Emil Björnson, emil.bjornson@liu.se

1

**Answer:**

This is a one-dimensional situation in which the PSD is given by

$$R_s(f) = \frac{1}{T} |\Phi_1(f)|^2 R_S[fT]$$

where  $\Phi_1(f)$  is the Fourier transform of the basis function  $\phi_1(t)$  and  $R_S[fT]$  is the PSD of the signal constellation.

The PSD can be computed as

$$R_S[fT] = \sigma_S^2 + m_S^2 \sum_m \delta(fT - m)$$

where the variance is  $\sigma_S^2 = P$  according to the problem formulation. The mean value for on-off keying can be shown to be  $\sqrt{P}$ . This gives

$$R_S[fT] = P + P \sum_m \delta(fT - m).$$

Moreover, direction computation of Fourier transform gives

$$\Phi_1(f) = \frac{T}{2} e^{-j\pi fT} \left( \underbrace{e^{-j\pi f_c T}}_{=j^{-2f_c T}} \text{sinc}((f + f_c)T) + \underbrace{e^{+j\pi f_c T}}_{=j^{2f_c T}} \text{sinc}((f - f_c)T) \right)$$

where we can utilize that  $e^{-j\pi f_c T} = j^{2f_c T}$  since  $2f_c T$  is an integer. (See A.3.1 in the extra course material for details).

By multiplying everything together, according to the formula above, we get

$$\begin{aligned} R_s(f) &= \frac{T}{4} \left| e^{-j\pi fT} \left( j^{-2f_c T} \text{sinc}((f + f_c)T) + j^{2f_c T} \text{sinc}((f - f_c)T) \right) \right|^2 \left( P + P \sum_m \delta(fT - m) \right) \\ &= \frac{PT}{4} \left( \text{sinc}((f + f_c)T) + (-1)^{2f_c T} \text{sinc}((f - f_c)T) \right)^2 \left( 1 + \sum_m \delta(fT - m) \right) \end{aligned}$$

One can continue to simplify this expression by using properties of the  $\delta$  function.

2

**Answer:**

The different questions can be answered independently.

- a) Since we consider proper complex Gaussian random variables, as in Section 4.5.1, the PDF is  $\frac{e^{-|y|^2/(N_0+A^2)}}{\pi(N_0+A^2)}$  for the case “1 sent” and  $\frac{e^{-|y|^2/N_0}}{\pi N_0}$  for the case “0 sent”.

Let us find the interval where “1 sent” is more probable than “0 sent”:

$$\begin{aligned} \frac{e^{-|y|^2/(N_0+A^2)}}{\pi(N_0+A^2)} &\geq \frac{e^{-|y|^2/N_0}}{\pi N_0} \Leftrightarrow \\ e^{|y|^2\left(\frac{1}{N_0} - \frac{1}{N_0+A^2}\right)} &\geq \frac{N_0+A^2}{N_0} \Leftrightarrow \\ |y|^2 \left(\frac{1}{N_0} - \frac{1}{N_0+A^2}\right) &\geq \ln\left(\frac{N_0+A^2}{N_0}\right) \Leftrightarrow \\ |y|^2 &\geq \frac{N_0(N_0+A^2)}{A^2} \ln\left(1 + \frac{A^2}{N_0}\right) \end{aligned}$$

This threshold only depends on  $|y|^2$ .

- c) In this case, “1 sent” corresponds to  $y = 3j/2 + n$  and “0 sent” corresponds to  $y = 0 + n$ , where  $n$  is the noise. The ML detection rule corresponds to finding which of the mean values  $3j/2$  and  $0$  from the hypotheses that is closest to the received signal  $1 + j$  in terms of Euclidean distance. The hypothesis “1 sent” gives  $|3j/2 - (1 + j)| = \sqrt{5}/2 \approx 1.1180$  while the hypothesis “0 sent” gives  $|1 + j| = \sqrt{2} \approx 1.4142$ . Since “1 sent” has the shortest distance, this is the ML estimate.

### 3

**Answer:**

Hypothesis  $H_0$  gives the PDF

$$f_0(z) = \begin{cases} 1/4 & |z| \leq 2 \\ 0 & |z| > 2 \end{cases}$$

and hypothesis  $H_1$  gives the PDF

$$f_1(z) = \frac{e^{-z^2/2}}{\sqrt{2\pi}}$$

of the observed signal.


Hypothesis  $H_1$  is more probable than  $H_0$  when  $f_0(z) \leq f_1(z)$ . This is necessarily the case for  $|z| > 2$ , since  $f_0(z) = 0$ , thus one decision boundary is at  $z = \pm 2$ .

Now looking at the range  $|z| \leq 2$ , direct computation yields

$$\frac{e^{-z^2/2}}{\sqrt{2\pi}} \geq \frac{1}{4} \Leftrightarrow e^{-z^2/2} \geq \frac{\sqrt{2\pi}}{4} \Leftrightarrow z^2 \leq 2 \ln\left(\frac{4}{\sqrt{2\pi}}\right) = \ln\left(\frac{8}{\pi}\right),$$

thus the hypotheses are equal at  $z = \pm \sqrt{\ln\left(\frac{8}{\pi}\right)} \approx 0.9668$ , which are the other two decision boundaries.

The decision boundaries and PDFs are illustrated as follows:



4

**Answer:**

- a. The sampled autocorrelation sequence is defined in (5.6) as

$$h[m] = \int p(t)p^*(t - mT)dt.$$

From the problem formulation we see that  $T = 1$ .

We now get

$$h[0] = \int p(t)p^*(t)dt = 2^2 + (-1)^2 + 1^2 = 6$$

$$h[\pm 1] = \int p(t)p^*(t \mp 1)dt = 2 \cdot (-1) + (-1) \cdot 1 = -3$$

$$h[\pm 2] = \int p(t)p^*(t \mp 2)dt = 2 \cdot 1 = 2$$

$$h[\pm k] = \int p(t)p^*(t \mp 3)dt = 0$$


for  $k \geq 3$ .

- b. The branch metric (5.13) becomes

$$\lambda_n(b[n], (b[n-1], b[n-2])) = b[n]z[n] - 3 + 3b[n]b[n-1] - 2b[n]b[n-2] \quad (1)$$

for the values of  $h[m]$  computed above, since everything is real-valued and  $|b[n]| = 1$  for BPSK.

For simplicity, we neglect the constant  $-3$ . See the finalized Viterbi algorithm below. When we terminate the algorithm by selecting the state with the highest end probability, we pick the red-marked path that ends with "12". The corresponding bit sequence is  $b[1] = 1$ ,  $b[2] = -1$ ,  $b[3] = -1$ ,  $b[4] = -1$ .



5

**Answer:**

Since this is a problem from the book, and none of the students who took the exam tried to solve the problem, we do not provide any detailed solution here.