
Table of Contents

.....	1
Define Constants	1
Import data	1
Plot world map	2
Propagate orbits	2

```
%Megaconstellation Design Code
%By Brian Trybus
%11/29/2021
```

Define Constants

```
MU = 3.986*(10^5);

J2 = 1.087*(10^-3);

Re = 6378;

elevation_limit = 15*(pi/180);
```

Import data

```
%Load in satellites
[num_launches, num_spacecraft, satellite_list] =
    loadConstellation("example_constellation.json");
%Load coast and convert to rad
load("world_coastline_low.txt")
xCoast = world_coastline_low(:,1)*(pi/180);
yCoast = world_coastline_low(:,2)*(pi/180);

%Load citys in
citys = readtable("worldcities.csv");

%Allow for loading less citys if ':' is replaced with a number
citysOfWorthC = (citys(:,3:4));
citysOfWorth = zeros(size(citysOfWorthC));


%Convert city possitions to rad then to 3d cords.
for i = 1:height(citysOfWorthC)
    citysOfWorthX =
        str2double(citysOfWorthC(i,1).lat{1})*(pi/180); %Reading in the csv
        needed lots of handeling and to be casted to double.
        citysOfWorthY = str2double(citysOfWorthC(i,2).lng{1})*(pi/180);
        [Cx(i),Cy(i),Cz(i)]=sph2cart(citysOfWorthY,citysOfWorthX,Re);
end
```

Plot world map

```
%Convert coast to 3d cords
[cx,cy,cz]=sph2cart(xCoast,yCoast,Re);

%Plot a sphere for the earth
[sx,sy,sz] = sphere(40);
s=surf(sx*Re,sy*Re,sz*Re);
%Make it blue for the sea
s.EdgeColor = 'none';
s.FaceColor = '#006994';
hold on %Hold on all parts will be plotted on this figure

%Plot the coast lines in black
plot3(cx,cy,cz,'k')
%Plot the citys as red dots
scatter3(Cx,Cy,Cz,'r.')
title("Constellation Traces over Earth with Major Citys")
```



Propagate orbits

```
t_0=0; %Setting epoch time.

t = 0:30:86400;%We will run every 30 seconds over a day
```

```

lengthT = length(t); %Reduce function calls for speed
satTime = zeros(height(citysOfWorthC),lengthT);
x=zeros(6,lengthT);
for i = 1:length(satellite_list) %Other loop cover each satellite

    oe0 = satellite_list(i).oe0; %orbital info from sat i

    for j = 1:lengthT % second loop covers time

        x(1:6,j) = propagateState(oe0,t(j),t_0,MU,J2,Re); %Propagates
the orbit of satellite i for time j.

        for k = 1:height(citysOfWorthC) %third loop covers citys,

            r_site = [Cx(k);Cy(k);Cz(k)]; %Possition of city k

            if(testLoS(r_site,x(1:3,j),elevation_limit)) %testing if
city k has sight of sat i at time j

                satTime(k,j) = satTime(k,j)+1;%If sat i is over city k
at time j then add 1

            end

        end


    end

    plot3(x(1,:),x(2,:),x(3,:)); % After running the orbit for a day
it will plot the path of the current sat i.

end

%satTime has amount of coverage in terms of satTime(city,time) time
indexes

```



Published with MATLAB® R2019b