

API Reference

BTC Embedded Platform - RESTful API documentation

API Version: 23.1p0

This is the documentation for the BTC Embedded Platform RESTful API.

CONTACT

EMAIL: support@btc-embedded.com

INDEX

| | |
|---|-----------|
| 1. APPLICATION | 8 |
| 1.1 DELETE /ep/application | 8 |
| 2. ARCHITECTURES | 9 |
| 2.1 POST /ep/architectures/ccode | 9 |
| 2.2 POST /ep/architectures/embedded-coder-wrapper-creation | 9 |
| 2.3 POST /ep/architectures/embedded-coder | 10 |
| 2.4 POST /ep/architectures/targetlink-ev | 11 |
| 2.5 POST /ep/architectures/mdf | 12 |
| 2.6 POST /ep/architectures/sdf | 13 |
| 2.7 GET /ep/architectures/{architecture-uid} | 14 |
| 2.8 GET /ep/architectures | 14 |
| 2.9 PUT /ep/architectures | 15 |
| 2.10 PUT /ep/architectures/model-paths | 16 |
| 2.11 POST /ep/architectures/simulink | 17 |
| 2.12 POST /ep/architectures/targetlink | 18 |
| 2.13 POST /ep/architectures/userdefined | 20 |
| 3. BACK-TO-BACK TEST REPORTS | 21 |
| 3.1 POST /ep/b2b/{b2b-test-uid}/b2b-reports | 21 |
| 3.2 GET /ep/b2b-reports | 21 |
| 4. BACK-TO-BACK TESTS | 23 |
| 4.1 GET /ep/b2b/{b2b-uid} | 23 |
| 4.2 PATCH /ep/b2b/{b2b-uid} | 24 |
| 4.3 POST /ep/folders/{folder-uid}/b2b | 24 |
| 4.4 POST /ep/folders/b2b | 25 |
| 4.5 POST /ep/scopes/{scope-uid}/b2b | 26 |
| 4.6 POST /ep/scopes/b2b | 27 |
| 4.7 GET /ep/b2b | 28 |
| 5. CODE ANALYSIS REPORTS B2B | 30 |
| 5.1 POST /ep/folders/{folder-uid}/code-analysis-reports-b2b | 30 |
| 5.2 POST /ep/folders/code-analysis-reports-b2b | 30 |
| 5.3 POST /ep/scopes/{scope-uid}/code-analysis-reports-b2b | 31 |
| 5.4 GET /ep/code-analysis-reports-b2b | 32 |
| 6. CODE ANALYSIS REPORTS RBT | 33 |
| 6.1 POST /ep/folders/{folder-uid}/code-analysis-reports-rbt | 33 |
| 6.2 POST /ep/folders/code-analysis-reports-rbt | 33 |
| 6.3 POST /ep/requirements-sources/{requirements-source-uid}/code-analysis-reports-rbt | 34 |
| 6.4 POST /ep/requirements-sources/code-analysis-reports-rbt | 35 |
| 6.5 POST /ep/scopes/{scope-uid}/code-analysis-reports-rbt | 36 |

| | |
|---|-----------|
| 6.6 GET /ep/code-analysis-reports-rbt | 36 |
| 7. CODE COVERAGE/ROBUSTNESS CHECK B2B | 38 |
| 7.1 GET /ep/scopes/{scope-uid}/coverage-details-b2b | 38 |
| 7.2 GET /ep/scopes/{scope-uid}/coverage-results-b2b | 39 |
| 7.3 POST /ep/coverage-goals/set-comment-b2b | 49 |
| 7.4 POST /ep/coverage-goals/set-justified-b2b | 49 |
| 7.5 POST /ep/scopes/{scope-uid}/set-coverage-overview-comment-b2b | 50 |
| 8. CODE COVERAGE/ROBUSTNESS CHECK RBT | 51 |
| 8.1 GET /ep/requirements-sources/{requirement-source-uid}/coverage-details-rbt | 51 |
| 8.2 GET /ep/scopes/{scope-uid}/coverage-details-rbt | 52 |
| 8.3 GET /ep/requirements-sources/{requirements-source-uid}/coverage-results-rbt | 53 |
| 8.4 GET /ep/scopes/{scope-uid}/coverage-results-rbt | 63 |
| 8.5 POST /ep/coverage-goals/set-comment-rbt | 73 |
| 8.6 POST /ep/coverage-goals/set-justified-rbt | 74 |
| 8.7 POST /ep/scopes/{scope-uid}/set-coverage-overview-comment-rbt | 74 |
| 9. COVERAGE GENERATION | 76 |
| 9.1 POST /ep/coverage-generation | 76 |
| 10. DOMAIN CHECKS | 79 |
| 10.1 POST /ep/domain-checks-ranges | 79 |
| 10.2 POST /ep/domain-checks-export | 79 |
| 10.3 GET /ep/scopes/{scope-uid}/domain-check-details | 80 |
| 10.4 GET /ep/scopes/{scope-uid}/domain-checks-results | 81 |
| 10.5 POST /ep/domain-checks | 83 |
| 10.6 POST /ep/domain-check-comments | 84 |
| 11. EXECUTION CONFIGS | 85 |
| 11.1 GET /ep/execution-configs | 85 |
| 12. EXECUTION RECORDS | 86 |
| 12.1 GET /ep/execution-records/{execution-record-uid} | 86 |
| 12.2 DELETE /ep/execution-records/{execution-record-uid} | 86 |
| 12.3 POST /ep/execution-records-export | 87 |
| 12.4 GET /ep/execution-records | 88 |
| 12.5 POST /ep/execution-records | 88 |
| 12.6 GET /ep/folders/{folder-uid}/execution-records | 89 |
| 12.7 PUT /ep/folders/{folder-uid}/execution-records | 90 |
| 12.8 GET /ep/scopes/{scope-uid}/execution-records | 91 |
| 13. FOLDERS | 93 |
| 13.1 GET /ep/folders | 93 |
| 13.2 POST /ep/folders | 93 |
| 13.3 DELETE /ep/folders/{folder-uid} | 94 |

| | |
|---|------------|
| 14. FORMAL SPECIFICATION REPORTS | 96 |
| 14.1 GET /ep/formal-specification-reports | 96 |
| 14.2 POST /ep/formal-specification-reports | 96 |
| 15. FORMAL SPECIFICATIONS | 98 |
| 15.1 GET /ep/environmental-assumptions | 98 |
| 15.2 GET /ep/formal-requirements | 98 |
| 15.3 GET /ep/formal-requirements/{formal-requirement-uid}/environmental-assumptions | 99 |
| 15.4 POST /ep/specifications-export | 100 |
| 15.5 POST /ep/specifications-import | 101 |
| 16. FORMAL TEST EXECUTION | 102 |
| 16.1 POST /ep/execute-formal-test | 102 |
| 17. FORMAL TEST REPORTS | 103 |
| 17.1 POST /ep/formal-requirements/{formal-requirement-uid}/formal-test-reports | 103 |
| 17.2 POST /ep/formal-requirements/formal-test-reports | 104 |
| 17.3 POST /ep/requirements-sources/{requirements-source-uid}/formal-test-reports | 104 |
| 17.4 POST /ep/requirements-sources/formal-test-reports | 105 |
| 17.5 POST /ep/scopes/{scope-uid}/formal-test-reports | 106 |
| 17.6 POST /ep/scopes/formal-test-reports | 107 |
| 17.7 GET /ep/formal-test-reports | 107 |
| 18. FORMAL VERIFICATION REPORTS | 109 |
| 18.1 POST /ep/scopes/{scope-uid}/formal-verification-reports | 109 |
| 18.2 GET /ep/formal-verification-reports | 110 |
| 19. INPUT RESTRICTIONS | 111 |
| 19.1 POST /ep/input-restrictions-export | 111 |
| 19.2 POST /ep/input-restrictions-import | 111 |
| 20. INTERFACE REPORTS | 113 |
| 20.1 POST /ep/scopes/{scope-uid}/interface-reports | 113 |
| 20.2 GET /ep/interface-reports | 113 |
| 21. MATLAB SCRIPT EXECUTION | 115 |
| 21.1 POST /ep/execute-long-matlab-script | 115 |
| 21.2 POST /ep/execute-short-matlab-script | 115 |
| 22. MESSAGES | 117 |
| 22.1 POST /ep/message-markers | 117 |
| 22.2 GET /ep/message-markers/{marker-date}/messages | 117 |
| 22.3 GET /ep/messages | 118 |
| 22.4 POST /ep/messages | 119 |
| 22.5 DELETE /ep/messages | 119 |

| | | |
|------------|---|------------|
| 22.6 | GET /ep/messages/{message-uid} | 120 |
| 22.7 | DELETE /ep/messages/{message-uid} | 121 |
| 22.8 | POST /ep/messages/message-report | 121 |
| 23. | MODEL COVERAGE REPORTS | 123 |
| 23.1 | POST /ep/folders/{folder-uid}/model-coverage-reports | 123 |
| 23.2 | POST /ep/folders/model-coverage-reports | 124 |
| 23.3 | POST /ep/scopes/{scope-uid}/model-coverage-reports | 124 |
| 23.4 | GET /ep/model-coverage-reports | 125 |
| 24. | PREFERENCES | 127 |
| 24.1 | GET /ep/preferences/{preference-name} | 127 |
| 24.2 | PUT /ep/preferences | 127 |
| 25. | PROFILES | 129 |
| 25.1 | GET /ep/profiles | 129 |
| 25.2 | PUT /ep/profiles | 129 |
| 25.3 | POST /ep/profiles | 130 |
| 25.4 | DELETE /ep/profiles | 130 |
| 25.5 | GET /ep/profiles/{profile-path} | 131 |
| 26. | PROGRESS | 133 |
| 26.1 | GET /ep/progress | 133 |
| 27. | PROJECT REPORTS | 135 |
| 27.1 | POST /ep/scopes/{scope-uid}/project-report | 135 |
| 27.2 | GET /ep/project-reports | 135 |
| 28. | PROOFS | 137 |
| 28.1 | GET /ep/proofs/{proofUID} | 137 |
| 28.2 | PUT /ep/proofs/{proofUID} | 138 |
| 28.3 | POST /ep/proofs/{frUid} | 139 |
| 28.4 | POST /ep/proofs/{proofUID}/execute | 140 |
| 28.5 | GET /ep/proofs | 141 |
| 28.6 | GET /ep/proofs/{proofUID}/detailed-proof-results | 141 |
| 29. | REAL-TIME TESTING | 143 |
| 29.1 | POST /ep/rtt-observers-export | 143 |
| 30. | REGRESSION TEST REPORTS | 144 |
| 30.1 | POST /ep/regression-tests/{regression-test-uid}/regression-test-reports | 144 |
| 30.2 | GET /ep/regression-test-reports | 144 |
| 31. | REGRESSION TESTS | 146 |
| 31.1 | GET /ep/regression-tests/{regression-test-uid} | 146 |
| 31.2 | PATCH /ep/regression-tests/{regression-test-uid} | 147 |
| 31.3 | POST /ep/folders/{folder-uid}/regression-tests | 147 |

| | | |
|------------|--|------------|
| 31.4 | POST /ep/folders/regression-tests | 148 |
| 31.5 | GET /ep/regression-tests | 149 |
| 32. | REPORTS | 151 |
| 32.1 | GET /ep/reports/{report-uid} | 151 |
| 32.2 | POST /ep/reports/{report-uid} | 151 |
| 33. | REQUIREMENT-BASED TEST CASES | 153 |
| 33.1 | GET /ep/test-cases-rbt/{testcase-uid} | 153 |
| 33.2 | DELETE /ep/test-cases-rbt/{testcase-uid} | 153 |
| 33.3 | POST /ep/test-cases-rbt-export | 154 |
| 33.4 | GET /ep/test-cases-rbt | 155 |
| 33.5 | PUT /ep/test-cases-rbt | 155 |
| 33.6 | GET /ep/folders/{folder-uid}/test-cases-rbt | 156 |
| 33.7 | GET /ep/scopes/{scope-uid}/test-cases-rbt | 157 |
| 33.8 | GET /ep/requirements/{requirement-uid}/test-cases-rbt | 158 |
| 33.9 | PUT /ep/requirements/test-cases-rbt | 159 |
| 33.10 | POST /ep/requirements/test-cases-rbt | 159 |
| 33.11 | POST /ep/formal-requirements/test-cases-rbt | 160 |
| 34. | REQUIREMENT-BASED TEST EXECUTION | 162 |
| 34.1 | POST /ep/folders/{folder-uid}/test-execution-rbt | 162 |
| 34.2 | POST /ep/folders/test-execution-rbt | 163 |
| 34.3 | POST /ep/test-cases-rbt/{testcase-uid}/test-execution-rbt | 163 |
| 34.4 | POST /ep/test-cases-rbt/test-execution-rbt | 164 |
| 34.5 | POST /ep/requirements-sources/{requirements-source-uid}/test-execution-rbt | 165 |
| 34.6 | POST /ep/requirements-sources/test-execution-rbt | 166 |
| 34.7 | POST /ep/scopes/{scope-uid}/test-execution-rbt | 167 |
| 34.8 | POST /ep/scopes/test-execution-rbt | 168 |
| 35. | REQUIREMENT-BASED TEST EXECUTION REPORTS | 169 |
| 35.1 | POST /ep/folders/{folder-uid}/test-execution-reports-rbt | 169 |
| 35.2 | POST /ep/folders/test-execution-reports-rbt | 169 |
| 35.3 | POST /ep/requirements-sources/{requirements-source-uid}/test-execution-reports-rbt | 170 |
| 35.4 | POST /ep/requirements-sources/test-execution-reports-rbt | 171 |
| 35.5 | POST /ep/scopes/{scope-uid}/test-execution-reports-rbt | 172 |
| 35.6 | POST /ep/scopes/test-execution-reports-rbt | 173 |
| 35.7 | GET /ep/test-execution-reports-rbt | 173 |
| 36. | REQUIREMENTS | 175 |
| 36.1 | GET /ep/requirements-sources | 175 |
| 36.2 | GET /ep/requirements/{requirement-source-id} | 175 |
| 36.3 | GET /ep/scopes/{scope-id}/linked-requirements | 176 |

| | |
|---|------------|
| 37. REQUIREMENTS IMPORT | 178 |
| 37.1 POST /ep/requirements-import | 178 |
| 37.2 GET /ep/requirements-import/doors | 179 |
| 37.3 GET /ep/requirements-import/excel | 179 |
| 38. SCOPES | 181 |
| 38.1 GET /ep/scopes/{scope-uid} | 181 |
| 38.2 GET /ep/scopes | 181 |
| 39. SIGNALS | 183 |
| 39.1 GET /ep/scopes/{scope-uid}/signals | 183 |
| 40. STIMULI VECTORS | 184 |
| 40.1 GET /ep/stimuli-vectors/{stimuli-vector-uid} | 184 |
| 40.2 DELETE /ep/stimuli-vectors/{stimuli-vector-uid} | 184 |
| 40.3 POST /ep/stimuli-vectors-export | 185 |
| 40.4 GET /ep/stimuli-vectors | 186 |
| 40.5 PUT /ep/stimuli-vectors | 186 |
| 40.6 GET /ep/folders/{folder-uid}/stimuli-vectors | 187 |
| 40.7 GET /ep/scopes/{scope-uid}/stimuli-vectors | 188 |
| 41. TEST | 189 |
| 41.1 GET /ep/test | 189 |
| 42. TEST CASE/STIMULI VECTOR SIMULATION | 190 |
| 42.1 POST /ep/folders/{folder-uid}/testcase-simulation | 190 |
| 42.2 POST /ep/folders/testcase-simulation | 191 |
| 42.3 POST /ep/scopes/{scope-uid}/testcase-simulation | 191 |
| 42.4 POST /ep/scopes/testcase-simulation | 192 |
| 42.5 POST /ep/test-cases/{testcase-uid}/testcase-simulation | 193 |
| 42.6 POST /ep/test-cases/testcase-simulation | 194 |
| 43. TOLERANCES | 195 |
| 43.1 POST /ep/profiles/export-global-tolerances | 195 |
| 43.2 GET /ep/scopes/{scope-id}/global-tolerances | 195 |
| 43.3 PUT /ep/profiles/global-tolerances | 196 |
| 43.4 DELETE /ep/profiles/global-tolerances | 197 |
| 43.5 GET /ep/test-cases/{test-case-id}/local-tolerances | 198 |
| 43.6 PUT /ep/test-cases/{test-case-id}/local-tolerances | 199 |
| 43.7 POST /ep/test-cases/{test-case-id}/local-tolerances | 199 |
| 43.8 DELETE /ep/test-cases/{test-case-id}/local-tolerances | 200 |

API

1. APPLICATION

Handle the EP application itself.

1.1 DELETE /ep/application

Exit EP and save the active profile

After calling the exit method, the current active profile will be saved, if there is one. If the profile has no save path, one is created at a temporary directory and a response containing the path is returned.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|---------|---|
| force-quit | boolean | If set to 'true', the application will force quit without saving the active profile. If set to 'false', the profile is saved at the given location, or at a temporary location if provided none. Default is 'false' |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - text/plain

string

STATUS CODE - 201: Created

RESPONSE MODEL - text/plain

string

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

2. ARCHITECTURES

Import and retrieve architectures.

2.1 POST /ep/architectures/ccode

Import a C-Code architecture

Long running task Import a C-Code architecture. Settings are provided as an import info object.

REQUEST

REQUEST BODY - application/json

```
{
  modelFile*   string  File name of the C-Code XML file
  mappingFile  string  File name of the mapping XML file. The file must be provided if architectures are already available in the
                        profile. The file is used to map the first imported architecture to the new imported C-Code architecture.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                        The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

2.2 POST /ep/architectures/embedded-coder-wrapper-creation

Create an EmbeddedCoder™ wrapper model

Long running task Creating an EmbeddedCoder™ wrapper model. Settings are provided as an import wrapper info object.

REQUEST

REQUEST BODY - application/json

```
{
  ecModelFile* string  The absolute or relative path to the Embedded Coder model.
  ecInitScript string  The absolute or relative path to the init script of the Embedded Coder model.
}
```

```
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

2.3 POST /ep/architectures/embedded-coder

Import an EmbeddedCoder™ architecture

Long running task Import an EmbeddedCoder™ architecture. Settings are provided as an import info object.

REQUEST

REQUEST BODY - application/json

```
{
  ecModelFile*      string  The absolute or relative path to the EmbeddedCoder model.<br>This file is mandatory
                        and may not be undefined.
  ecInitScript       string  The absolute or relative path to the init script of the EmbeddedCoder model.<br>This
                        attribute may be undefined.<br>If the specified file path is invalid, an error is reported.
  parameterHandling  enum    ALLOWED:OFF, EXPLICIT_PARAMETER
                        Specifies how parameter variables are handled. Can be 'OFF' or
                        'EXPLICIT_PARAMETER'.<br>'OFF': Only regular inputs in the interface of subsystems
                        are observed.<br>'EXPLICIT_PARAMETER': Parameter variables are regarded as
                        additional<br>inputs to subsystems.<br>Default is 'EXPLICIT_PARAMETER'.<br>If not
                        specified (undefined or invalid), the default value is used.
  testMode           enum    ALLOWED:BLACK_BOX, GREY_BOX
                        Specifies the test mode. Can be 'BLACK_BOX' or 'GREY_BOX'.<br>If set to 'GreyBox',
                        local variables are regarded as additional outputs of subsystems.<br>For BlackBox-
                        Testing only the regular outputs in the interfaces of subsystems are
                        observed.<br>Default is 'GreyBox'.<br>If not specified (undefined or invalid), the default
                        value is used.
  fixedStepSolver     boolean Handling when a non-fixed-step solver is encountered: If 'true', the solver is automatically
                        set to fixed-step.<br>Otherwise an error is issued.Default is 'false'.
  inDepthCcodeAnalysis boolean true: Simulink model and C-Code model are imported.<br>>false: indicates that a SL SIL
                        simulation is supported.<br>C-Code and mapping are omitted.<br>Default is 'true'
  subsystemMatcher    string  A whitelist of all subsystems you would like to import.<br>Uses the regular expression
                        standard.<br>Each subsystem is identified by its virtual path inside the model.<br>If no
                        value is defined, all subsystems are imported.<br>If the specified regular expression
                        does not produce any match, an error is reported.
  parameterMatcher    string  A whitelist of all parameters you would like to import.<br>Uses the regular expression
```

standard.
Each parameter is identified by its name.
If no value is defined, all calibrations are imported.
If the specified regular expression does not produce any match, no calibration is imported.
The list cannot be applied, if parameterHandling is set to 'OFF'.
Please note, that model workspace parameters have their name extended by the model they
are located in and need to be addressed accordingly in the following way: 'modelname:paramname'

```
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                        The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

2.4 POST /ep/architectures/targetlink-ev

Import a TargetLink™ EV architecture

Long running task Import a TargetLink™ EV architecture. Settings are provided as an import info object.

REQUEST

REQUEST BODY - application/json

```
{
  tlModelFile*      string  The absolute or relativ path to the TargetLink model file (.mdl|.slx).
  tlInitScript       string  The absolute or relativ path to the script defining all parameters needed for initializing the TL-
                             model. If not provided, the TL-model is assumed to be selfcontained.
  fixedStepSolver    boolean 'true': The analyzed models (TargetLink model and Simulink model) will be set to the fixed-step
                             solver type automatically. The usage of the EmbeddedPlatform requires a fixed-step solver. If
                             the model is open and the fixed-step solver is not already set, this might lead to a modified
                             model. <br>'false': The analyzed models (TargetLink model and Simulink model) will not be set
                             to the fixed-step solver automatically. If the fixed-step solver is not already set in the model, an
                             exception is thrown. In order to proceed the user has to set the fixed-step solver manually in
                             the simulation settings. <br>Note: The option is ignored if the model is currently not in an
                             open/loaded state. In this case it has no visible side-effect. <br>Default is 'false'.

  tlSubsystem        string  Name of the Subsystem representing the TL toplevel subsystem for the analysis.<br>Note:
                             Argument is obligatory if there is more than one toplevel system in the model.
  calibrationHandling enum   ALLOWED:OFF, EXPLICIT_PARAMETER, LIMITED_BLOCKSET
                             Determine how calibration variables are being handled.<br>'OFF': Only regular inputs in the
                             interface of subsystems are observed. <br>'EXPLICIT_PARAMETER': Calibration variables are
                             regarded as additional inputs to subsystems. Their value is set once during the initial phase of
                             the simulation and is held constant thereafter. <br>'LIMITED_BLOCKSET': Calibration variables
                             are regarded as additional inputs to subsystems. Their value is set once during the initial
                             phase of the simulation and is held constant thereafter. Enable support for calibration within
```

| | |
|--------------------------------|---|
| subsystemMatcher string | block properties, not using workspace calibrations. Note: The supported Set of calibratable TL-Blocks is different from 'EXPLICIT_PARAMETER'. Default is 'EXPLICIT_PARAMETER'. |
| calibrationMatcher string | A whitelist of all subsystems you would like to import. Uses the regular expression standard. Each subsystem is identified by its virtual path inside the model. If no value is defined, all subsystems are imported. If the specified regular expression does not produce any match, only the toplevel subsystem is imported. The root subsystem is always imported. Please note that the subsystem-path has to include the Targetlink wrapper. |

}

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

2.5 POST /ep/architectures/mdf

Import an MDF™ architecture

Long running task Import an MDF™ architecture. Settings are provided as an import info object.

REQUEST

REQUEST BODY - application/json

```
{
  modelFile* string Absolute or relative path to the execution record (.mf4).
  sampleTime* string Sample time, in seconds.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not acceptable

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

2.6 POST /ep/architectures/sdf

Import a SDF™ architecture

Long running task Import a SDF™ architecture. Settings are provided as an import info object.

REQUEST

REQUEST BODY - application/json

```
{
  sdfFile*          string  The absolute path to the SDF file. This file is mandatory and may not be null! If the specified
                           file path is invalid, an error is reported.
  trcFile*          string  The absolute path to the TRC file. This file is mandatory and may not be null! If the specified
                           file path is invalid, an error is reported.
  sampleTime*       string  The SDF architecture sample time in seconds. The format can be only numbers (e.g. 3) or with
                           the time unit specified (e.g. 3 s). Attempt to use any other format will be reported as an error.
  excludedSubsystems [string] Subsystems names that should not be imported, can be empty. If an invalid subsystem is
                           requested, an error is reported.
  propagateSelection boolean This option allows to configure the excluded subsystems option. If set to true, also the child
                           subsystems of the excluded subsystems are excluded from the import. Default setting is false.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

2.7 GET /ep/architectures/{architecture-uid}

Get a specific architecture

Get an existing architecture by UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------------|--------|---|
| *architecture-uid | string | The UID of the architecture to be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  uid                string READ-ONLY
                    The unique identifier (UID) of this object.
  architectureKind  string READ-ONLY
                    The string representation of the concrete architecture
                    , e.g. 'Simulink', 'C-Code', 'TargetLink'.
  name              string READ-ONLY
                    The architecture name as specified by the model.
  propList {
    The Architecture property List
  }
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

2.8 GET /ep/architectures

Get all architectures

Search for all open architectures.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------------|--------|---|
| architecture-kind | string | Specifies the specific architecture kind to be queried. (e.g. 'Simulink', 'C-Code', 'TargetLink') |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid string READ-ONLY
      The unique identifier (UID) of this object.
    architectureKind string READ-ONLY
      The string representation of the concrete architecture
      , e.g. 'Simulink', 'C-Code', 'TargetLink'.
    name string READ-ONLY
      The architecture name as specified by the model.
    propList {
      The Architecture property List
    }
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

2.9 PUT /ep/architectures

Update architectures

Long running task Perform an architecture update.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
    The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

2.10 PUT /ep/architectures/model-paths

Update model paths for architectures

Update the paths for imported architectures. If the architecture-uid is not specified, the model paths will be updated for the master architecture.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------------|--------|--|
| architecture-uid | string | The UID of the architecture to be updated. If empty, the path will be updated for the master architecture. |

REQUEST BODY - application/json

```
{
  slModelFile    string  The path to the Simulink model(.mdl|.slx).
  slInitScript   string  The path to the init script of the Simulink model.
  addModelInfo   string  The path to additional model information.
  tlModelFile    string  The path to the TargetLink model file (.mdl|.slx).
  tlInitScript   string  The path to the init script of the TargetLink model.
  environment    string  The path to XML file including information about
                           environmental files like additional code.
}
```

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - text/plain

string

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

2.11 POST /ep/architectures/simulink

Import a Simulink™ architecture

Long running task Import a Simulink™ architecture. Settings are provided as an import info object.

REQUEST

REQUEST BODY - application/json

```
{
  slModelFile*      string  The absolute or relative path to the Simulink model.<br>This file is mandatory and may not be
                        undefined!
  slInitScriptFile  string  The absolute or relative path to the init script of the Simulink model.<br>This attribute may be
                        undefined.<br>If the specified file path is invalid, an error is reported.
  parameterHandling enum    ALLOWED:OFF, EXPLICIT_PARAMETER
                        Specifies how parameter variables are handled. Can be 'OFF' or 'EXPLICIT_PARAMETER'.<br>'OFF':
                        Only regular inputs in the interface of subsystems are observed.<br>'EXPLICIT_PARAMETER':
                        Parameter variables are regarded as additional inputs to subsystems.<br>Default is
                        'EXPLICIT_PARAMETER'.<br>If not specified (undefined or invalid), the default value is used.
  testMode          enum    ALLOWED:BLACK_BOX, GREY_BOX
                        Specifies the test mode. Can be 'BLACK_BOX' or 'GREY_BOX'.<br>If set to 'GREY_BOX', local
                        variables are regarded as additional outputs of subsystems.<br>For Black Box-Testing only the
                        regular outputs in the interfaces of subsystems are observed.<br>Default is 'GREY_BOX'.<br>If not
                        specified (undefined or invalid), the default value is used.
  fixedStepSolver   boolean Defines, if the fixed step solver will be set or not. Can be true or false.<br>true: The analyzed
                        Simulink model will be set to the fixed-step solver type automatically.<br>The usage of the
                        EmbeddedPlatform requires a fixed-step solver. If the model is open and<br>the fixed-step solver
                        is not already set, this might lead to a modified model.<br>false: The analyzed Simulink model will
                        not be set to the fixed-step solver automatically.<br>If the fixed-step solver is not already set in the
                        model, the method return with state of<br>a non fixed-step solver. In order to proceed the user has
                        to set the fixed-step solver<br>manually in the Simulink simulation settings.<br>Default is
                        'false'.<br>Note: The option is ignored if the model is currently not in an open/loaded state. In this
                        case it has no visible side-effect.
  mappingFile       string  File name of the mapping XML file. The file must be provided if architectures are already available
                        in the profile. The file is used to map the first imported architecture to the new imported Simulink
                        architecture.<br>This attribute may be undefined.<br>If the specified file path is invalid, an error is
                        reported.
  subsystemMatcher  string  A whitelist of all subsystems you would like to import.<br>Uses the regular expression
                        standard.<br>Each subsystem is identified by its virtual path inside the model.<br>If no value is
                        defined, all subsystems are imported.<br>If the specified regular expression does not produce any
                        match, an error is reported.<br>Keep in mind that having multiple Toplevel-Subsystem will result in
                        an error.
  parameterMatcher  string  A whitelist of all parameters you would like to import.<br>Uses the regular expression
                        standard.<br>Each parameter is identified by its name.<br>If no value is defined, all parameters
                        are imported.<br>If the specified regular expression does not produce any match, no parameter is
                        imported.<br>The list cannot be applied, if parameterHandling is set to 'OFF'.<br>Please note, that
                        model workspace parameters have their name extended by the model they <br>are located in and
                        need to be addressed accordingly in the following way: 'modelname:paramname'
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
```

```
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

2.12 POST /ep/architectures/targetlink

Import a TargetLink™ architecture

Long running task Import a TargetLink™ architecture. Settings are provided as an import info object.

REQUEST

REQUEST BODY - application/json

| | | |
|----------------------|---------|--|
| { | | |
| tlModelFile* | string | The absolute or relative path to the TargetLink model file (.mdl .slx). |
| tlInitScript | string | The absolute or relative path to the script defining all parameters needed for initializing the TL-model. If not provided, the TL-model is assumed to be selfcontained. |
| slModelFile | string | The absolute or relative path to the Simulink model file (.mdl .slx). Note: If a TargetLink model is given, the SL-model is assumed to be equivalent to the TL-model. |
| slInitScript | string | The absolute or relative path to the script defining all parameters needed for initializing the SL-model. If not provided, the SL-model is assumed to be selfcontained. |
| environment | string | The absolute or relative path to XML file including information about environmental files like additional code. (see specifications in CodeGeneration.dtd). |
| useExistingCode | boolean | Determine if code generation needs to be done. 'true': Code generation is not explicitly performed. Instead it is assumed that the required code files are already generated and that the corresponding DataDictionary of the model includes information about the code generation. 'false': Code generation is explicitly performed during the analysis. The resulting code is used for further steps. Default is 'false'. |
| activateModelLinking | boolean | Determine if the source code needs to be linked to the TargetLink model. 'true': A link between the source code and the TargetLink model will be established. This setting may lead to a modified TargetLink model. To accomplish this link relation, the TargetLink option 'ExtendedBlockComments' needs to be enabled with a subsequent TargetLink code generation. 'false': The source code model linking is not explicitly set by EmbeddedPlatform. Default is 'false'. |
| closedLoopModel | boolean | Determine if the SUT environment is analyzed during extraction 'true': The environment of the SUT is also analyzed during the model extraction. Important for analyzing closed-loop models. 'false': Only the SUT is considered during the model extraction. Default is 'false'. |
| fixedStepSolver | boolean | Defines, if the fixed step solver will be set or not. 'true': The analyzed models (TargetLink model and Simulink model) will be set to the fixed-step solver type automatically. The usage of the EmbeddedPlatform requires a fixed-step solver. If the model is open and the fixed-step solver is not already set, this might lead to a modified model. 'false': The analyzed models (TargetLink model and Simulink model) will not be set to the fixed-step solver automatically. If the fixed-step solver is not already set in the model, an exception is thrown. In order to proceed the user has to set the fixed-step solver manually in the simulation settings. Note: The option is ignored if the model is currently not in an open/loaded state. In this case it has no visible side-effect. Default is 'false'. |
| tlSubsystem | string | Name of the Subsystem representing the TL toplevel subsystem for the analysis. Note: Argument is obligatory if there is more than one toplevel system in the model. |
| calibrationHandling | enum | ALLOWED: OFF, EXPLICIT_PARAMETER, LIMITED_BLOCKSET Determine how calibration variables are being handled. 'OFF': Only regular inputs in the interface of subsystems are observed. 'EXPLICIT_PARAMETER': Calibration |

| | | |
|-------------------------|--------|--|
| | | variables are regarded as additional inputs to subsystems. Their value is set once during the initial phase of the simulation and is held constant thereafter. 'LIMITED_BLOCKSET': Calibration variables are regarded as additional inputs to subsystems. Their value is set once during the initial phase of the simulation and is held constant thereafter. Enable support for calibration within block properties, not using workspace calibrations. Note: The supported Set of calibratable TL-Blocks is different from 'EXPLICIT_PARAMETER'.Default is 'EXPLICIT_PARAMETER'. |
| testMode | enum | ALLOWED:BLACK_BOX, GREY_BOX Specifies the test mode. Can be 'BLACK_BOX' or 'GREY_BOX'. If set to 'GREY_BOX', local variables are regarded as additional outputs of subsystems. For Black Box-Testing only the regular outputs in the interfaces of subsystems are observed. Default is 'GREY_BOX'. If not specified (undefined or invalid), the default value is used. |
| mappingFileForTLArch | string | The absolute or relative path to the mapping file for TargetLink architecture mapping. At least one mapping file must be provided if architectures are already available in the profile. The file is used to map the first imported architecture to the new imported TargetLink architecture. If this file is not provided, the mapping to the first imported architecture is derived from the auto-generated mapping between TargetLink, C-Code, and Simulink (if available). For the derivation to work, at least one of these architectures must be mapped to the first imported architecture via a specified mapping file |
| mappingFileForCCodeArch | string | The absolute or relative path to the mapping file for C-Code architecture mapping. At least one mapping must be provided if architectures are already available in the profile. The file is used to map the first imported architecture to the new imported C-Code architecture. If this file is not provided, the mapping to the first imported architecture is derived from the auto-generated mapping between TargetLink, C-Code, and Simulink (if available). For the derivation to work, at least one of these architectures must be mapped to the first imported architecture via a specified mapping file |
| mappingFileForSLArch | string | The absolute or relative path to the mapping file for Simulink architecture mapping. At least one mapping must be provided if a Simulink architecture is additionally imported and architectures are already available in the profile. The file is used to map the first imported architecture to the new imported Simulink architecture. If this file is not provided, the mapping to the first imported architecture is derived from the auto-generated mapping between TargetLink, C-Code, and Simulink (if available). For the derivation to work, at least one of these architectures must be mapped to the first imported architecture via a specified mapping file |
| subsystemMatcher | string | A whitelist of all subsystems you would like to import. Uses the regular expression standard. Each subsystem is identified by its virtual path inside the model. If no value is defined, all subsystems are imported. If the specified regular expression does not produce any match, only the toplevel subsystem is imported. The root subsystem is always imported. Please note that the subsystem-path has to include the Targetlink wrapper. |
| calibrationMatcher | string | A whitelist of all calibrations you would like to import. Uses the regular expression standard. Each calibration is identified by its name. If no value is defined, all calibrations are imported. If the specified regular expression does not produce any match, no calibration is imported. The list cannot be applied, if calibrationHandling is set to 'OFF'. |
| cfileMatcher | string | A whitelist of all c-code files you would like to import. Uses the regular expression standard. Each file is identified by its name. If no value is defined, all files are imported. If the specified regular expression does not produce any match, no file is imported. |
| } | | |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

2.13 POST /ep/architectures/userdefined

Import a User-defined architecture

Long running task Import a User-defined architecture from a XML file that describes the interface of the architecture. It is only possible to have one User-defined architecture imported at all times. Importing a second User-defined architecture will be rejected.

REQUEST

REQUEST BODY - application/json

```
{
  modelFile*   string  Filename (and path) of the xml file that describes the interface of the User-defined architecture to import.
  mappingFile  string  Filename (and path) of the mapping xml file that describes the mapping between the User-defined architecture and the master architecture. This file is only required (and mandatory), if the User-defined architecture is imported into a profile that already contains another architecture.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [RESPONSE MODEL - application/json](#get-/ep/progress>Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.</p></div><div data-bbox=)

```
{
  jobID string READ-ONLY
                The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

3. BACK-TO-BACK TEST REPORTS

3.1 POST /ep/b2b/{b2b-test-uid}/b2b-reports

Create a B2B test report on a B2B test

Creates a Back-to-Back test report on a Back-to-Back test by providing its UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|--|
| *b2b-test-uid | string | The Back-to-Back test UID for which the Back-to-Back test report is created. |

RESPONSE

STATUS CODE - 201: Created

RESPONSE MODEL - application/json

```
{
  uid          string READ-ONLY
                  The unique identifier (UID) of this object.
  reportName   string Name of the report.
  reportType   string Type of the report.
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

3.2 GET /ep/b2b-reports

Get all B2B test reports

Retrieve all the Back-to-Back test reports from the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {
  Array of object:
  uid          string READ-ONLY
                  The unique identifier (UID) of this object.
  reportName   string Name of the report.
}
```

```
    reportType string Type of the report.  
  }]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

```
string
```

4. BACK-TO-BACK TESTS

Create and retrieve Back-to-Back tests.

4.1 GET /ep/b2b/{b2b-uid}

Get a B2B test

Get a Back-to-Back test with the provided UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|----------|--------|--|
| *b2b-uid | string | The UID of the Back-to-Back test to be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

| | | | |
|-----------------------------------|----------|---|--|
| { | | | |
| uid | string | READ-ONLY | The unique identifier (UID) of this object. |
| referenceMode | string | | The reference execution config type. |
| comparisonMode | string | | The comparison execution config type. |
| referenceFolderUIDs | [string] | | Reference folder UIDs |
| comparisonFolderUID | string | | Comparison folder UID |
| executionDate | string | | Execution Date |
| verdictStatus | enum | ALLOWED:PASSED, FAILED, ERROR, FAILED_ACCEPTED | The verdict status |
| verdictState | enum | ALLOWED:VALID, OUTDATED_TOLERANCE_UPDATE, OUTDATED_MISSING_EXECUTIONS | Verdict State |
| failed | integer | | Number of failed comparisons. |
| failedAccepted | integer | | Number of failed accepted comparisons. |
| passed | integer | | Number of passed comparisons. |
| error | integer | | Number of comparisons with error. |
| total | integer | | Total number of comparisons. |
| comparisons [{ | | | |
| Array of object: All comparisons. | | | |
| uid | string | READ-ONLY | The unique identifier (UID) of this object. |
| name | string | | The name of Test Case / Stimuli Vector used in Comparison. |
| verdictStatus | enum | ALLOWED:PASSED, FAILED, ERROR, FAILED_ACCEPTED | The verdict status |
| referenceExecutionRecordUID | string | | UID of reference execution record. |
| comparisonExecutionRecordUID | string | | UID of compared to execution record. |
| comment | string | | Added comment for Comparison. |
| }] | | | |
| name | string | | The name of the Back-To-Back Test. |
| stimuliFolderUIDs | [string] | | Folder UIDs for which Back-To-Back Test was generated. |
| stimuliScopeUIDs | [string] | | Scope UIDs for which Back-To-Back Test was generated. |
| } | | | |

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

4.2 PATCH /ep/b2b/{b2b-uid}

Change a verdict status for a comparison

Changes verdict status for a comparison. If accept is true, the comparison verdict status is changed from 'failed' to 'failed (accepted)'. If accept is false, the comparison verdict status is changed from 'failed (accepted)' to 'failed'.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|----------|--------|---|
| *b2b-uid | string | The Back-to-Back test UID for which to change the comparison verdict. |

REQUEST BODY - application/json

```
{
  comparisonUID* string  UID of the Comparison
  accept*         boolean If accept is true, the comparison verdict status is changed from 'failed' to 'failed (accepted)'. If accept is
                        false, the comparison verdict status is changed from 'failed (accepted)' to 'failed'
}
```

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

4.3 POST /ep/folders/{folder-uid}/b2b

Create a B2B test on a folder

Long running task Generates a Back-to-Back test on a given folder UID for the specified reference and comparison execution kinds. Optionally, the execution can be forced to simulate all contained requirements-based test cases/stimuli-vectors. Optionally, only stimuli vectors can be set to be executed if force execution is activated. Otherwise if there are requirements-based test cases with comparison verdicts, the verdicts will be deleted in order to run the Back-to-Back test.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The folder UID for which the Back-to-Back test is generated. |

REQUEST BODY - application/json

| | | |
|----------------------------|---------|--|
| refMode* | string | Reference execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL'). Not case-sensitive. |
| compMode* | string | Comparison execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL'). Not case-sensitive. |
| forceExecute | boolean | (Optional) If true, simulates all contained test cases/stimuli-vectors, replacing existing execution records. Default is false. |
| simulateStimuliVectorsOnly | boolean | (Optional) This option can be used only when forceExecution is set to true. If true, simulates only stimuli-vectors. If false, and there are Requirements-based Test Cases with comparison verdicts, the verdicts will be deleted in order to run the Back-To-Back Test. Default value is false. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [#get-/ep/progress](#) Progress i.e. GET ['/ep/progress?progress-id={progress-id}'](#) using the id received by this command.

RESPONSE MODEL - application/json

| | | |
|-------|--------|------------------|
| jobID | string | READ-ONLY |
| | | The ID of a job. |

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

4.4 POST /ep/folders/b2b

Create a B2B test on a list of folders

Long running task Generates a Back-to-Back test on a given list of folder UIDs for the specified reference and comparison execution kinds. Optionally, the execution can be forced to simulate all contained requirements-based test cases/stimuli-vectors. Optionally, only stimuli vectors can be set to be executed if force execution is activated. Otherwise if there are requirements-based test cases with comparison verdicts, the verdicts will be deleted in order to run the Back-to-

Back test.

REQUEST

REQUEST BODY - application/json

| | | |
|----------------------------|----------|--|
| refMode* | string | Reference execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL'). Not case-sensitive. |
| compMode* | string | Comparison execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL'). Not case-sensitive. |
| forceExecute | boolean | (Optional) If true, simulates all contained test cases/stimuli-vectors, replacing existing execution records. Default is false. |
| simulateStimuliVectorsOnly | boolean | (Optional) This option can be used only when forceExecution is set to true. If true, simulates only stimuli-vectors. If false, and there are Requirements-based Test Cases with comparison verdicts, the verdicts will be deleted in order to run the Back-To-Back Test. Default value is false. |
| UIDs* | [string] | UIDs list (e.g. scopes, folders) |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.](#get-/ep/progress)

RESPONSE MODEL - application/json

| | | |
|-------|--------|------------------|
| jobID | string | READ-ONLY |
| | | The ID of a job. |

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

4.5 POST /ep/scopes/{scope-uid}/b2b

Create a B2B test on a scope

Long running task Generates a Back-to-Back test on a given scope UID for the specified reference and comparison execution kinds. Optionally, the execution can be forced to simulate all contained requirements-based test cases/stimuli-vectors. Optionally, only stimuli vectors can be set to be executed if force execution is activated. Otherwise if there are requirements-based test cases with comparison verdicts, the verdicts will be deleted in order to run the Back-to-Back test.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The scope UID for which the Back-to-Back test is generated. |

REQUEST BODY - application/json

```
{
  refMode*           string  Reference execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL'). Not
                        case-sensitive.
  compMode*          string  Comparison execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL').
                        Not case-sensitive.
  forceExecute        boolean (Optional) If true, simulates all contained test cases/stimuli-vectors, replacing
                        existing execution records. Default is false.
  simulateStimuliVectorsOnly boolean (Optional) This option can be used only when forceExecution is set to true. If true,
                        simulates only stimuli-vectors. If false, and there are Requirements-based Test Cases
                        with comparison verdicts, the verdicts will be deleted in order to run the Back-To-Back
                        Test. Default value is false.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

4.6 POST /ep/scopes/b2b

Create a B2B test on a list of scopes

Long running task Generates a Back-to-Back test on a given list of scope UIDs for the specified reference and comparison execution kinds. Optionally, the execution can be forced to simulate all contained requirements-based test cases/stimuli-vectors. Optionally, only stimuli vectors can be set to be executed if force execution is activated. Otherwise if there are requirements-based test cases with comparison verdicts, the verdicts will be deleted in order to run the Back-to-Back test.

REQUEST

REQUEST BODY - application/json

```
{
  refMode*           string  Reference execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL').
                        Not case-sensitive.
```

| | | |
|----------------------------|----------|--|
| compMode* | string | Comparison execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL'). Not case-sensitive. |
| forceExecute | boolean | (Optional) If true, simulates all contained test cases/stimuli-vectors, replacing existing execution records. Default is false. |
| simulateStimuliVectorsOnly | boolean | (Optional) This option can be used only when forceExecution is set to true. If true, simulates only stimuli-vectors. If false, and there are Requirements-based Test Cases with comparison verdicts, the verdicts will be deleted in order to run the Back-To-Back Test. Default value is false. |
| UIDs* | [string] | UIDs list (e.g. scopes, folders) |
| } | | |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

4.7 GET /ep/b2b

Get all B2B tests

Get all Back-to-Back tests from active profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {
  Array of object:
    uid string READ-ONLY
                The unique identifier (UID) of this object.
    referenceMode string
                The reference execution config type.
    comparisonMode string
                The comparison execution config type.
    referenceFolderUIDs [string]
                Reference folder UID
    comparisonFolderUID string
                Comparison folder UID
    executionDate string
                Execution Date
  }
```

```

    verdictStatus      enum      ALLOWED:PASSED, FAILED, ERROR, FAILED_ACCEPTED
                                The verdict status
    verdictState       enum      ALLOWED:VALID, OUTDATED_TOLERANCE_UPDATE,
                                OUTDATED_MISSING_EXECUTIONS
                                Verdict State
    failed              integer   Number of failed comparisons.
    failedAccepted      integer   Number of failed accepted comparisons.
    passed              integer   Number of passed comparisons.
    error               integer   Number of comparisons with error.
    total               integer   Total number of comparisons.
    comparisons [{
Array of object: All comparisons.
        uid            string    READ-ONLY
                                The unique identifier (UID) of this object.
        name            string    The name of Test Case / Stimuli Vector used in Comparison.
        verdictStatus   enum      ALLOWED:PASSED, FAILED, ERROR,
                                FAILED_ACCEPTED
                                The verdict status
        referenceExecutionRecordUID string  UID of reference execution record.
        comparisonExecutionRecordUID string  UID of compared to execution record.
        comment          string    Added comment for Comparison.
    }]
    name                string     The name of the Back-To-Back Test.
    stimuliFolderUIDs   [string]   Folder UUIDs for which Back-To-Back Test was generated.
    stimuliScopeUIDs   [string]   Scope UUIDs for which Back-To-Back Test was generated.
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

5. CODE ANALYSIS REPORTS B2B

Handle Back-To-Back code analysis reports.

5.1 POST /ep/folders/{folder-uid}/code-analysis-reports-b2b

Create a report on a folder

Create a B2B code analysis report on given folder.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The folder UID for which to create the B2B code analysis report. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
    The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

5.2 POST /ep/folders/code-analysis-reports-b2b

Create a report on a list of folders

Create B2B Code Analysis Report on given folders.

REQUEST

REQUEST BODY - application/json

```
{
  UUIDs* [string] List with unique identifiers of the objects.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

5.3 POST /ep/scopes/{scope-uid}/code-analysis-reports-b2b

Create a report on a scope

Create a B2B code analysis report on given scope.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The scope UID for which to create the B2B code analysis report. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

```
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

5.4 GET /ep/code-analysis-reports-b2b

Get all reports

Retrieve all B2B code analysis reports from profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
```

Array of object:

| | | |
|------------|--------|---|
| uid | string | READ-ONLY |
| | | The unique identifier (UID) of this object. |
| reportName | string | Name of the report. |
| reportType | string | Type of the report. |

```
}]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

6. CODE ANALYSIS REPORTS RBT

Creates requirement-based code analysis reports.

6.1 POST /ep/folders/{folder-uid}/code-analysis-reports-rbt

Create a report on a folder

Long running task Create an RBT code analysis report on a given folder.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|---|
| *folder-uid | string | The folder UID for which to create an RBT code analysis report. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
    The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

6.2 POST /ep/folders/code-analysis-reports-rbt

Create a report on a list of folders

Create an RBT code analysis report on given folders.

REQUEST

REQUEST BODY - application/json

```
{
  UUIDs* [string] List with unique identifiers of the objects.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

6.3 POST /ep/requirements-sources/{requirements-source-uid}/code-analysis-reports-rbt

Create a report on a requirements source

Create an RBT code analysis report on a given requirements source UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|--------------------------|--------|---|
| *requirements-source-uid | string | The requirements source UID for which to create RBT code analysis report. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
```

```
    jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

6.4 POST /ep/requirements-sources/code-analysis-reports-rbt

Create a report on requirements sources

Create an RBT code analysis report on given requirements sources.

REQUEST

REQUEST BODY - application/json

```
{
  UUIDs* [string] List with unique identifiers of the objects.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

6.5 POST /ep/scopes/{scope-uid}/code-analysis-reports-rbt

Create a report on scope

Create an RBT code analysis report on a given scope.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The scope UID for which to create RBT code analysis report. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
    The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

6.6 GET /ep/code-analysis-reports-rbt

Get all reports

Retrieve all RBT code analysis reports from the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{  
  Array of object:  
    uid          string  READ-ONLY  
                        The unique identifier (UID) of this object.  
    reportName   string  Name of the report.  
    reportType   string  Type of the report.  
}]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

7. CODE COVERAGE/ROBUSTNESS CHECK B2B

Retrieve code coverage/robustness checks details and results in B2B.

7.1 GET /ep/scopes/{scope-uid}/coverage-details-b2b

Get coverage details for a scope

Get all code coverage/robustness checks details for a scope. Some filters can be applied.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|----------------------|
| *scope-uid | string | The UID of the scope |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|---|--|
| statuses | array of string ALLOWED: COVERED, UNKNOWN, UNREACHABLE_INF, UNREACHABLE_N, INCONSISTENT, UNKNOWN_JUSTIFIED, UNREACHABLE_INF_JUSTIFIED, UNREACHABLE_N_JUSTIFIED | The status filter for code coverage/robustness check goals. Possible values: COVERED, UNKNOWN, UNREACHABLE_INF, UNREACHABLE_N, INCONSISTENT, UNKNOWN_JUSTIFIED, UNREACHABLE_INF_JUSTIFIED, UNREACHABLE_N_JUSTIFIED. Can also specify multiple options. Can also be empty, in which case the results are shown for all statuses. |
| goal-types | array of string ALLOWED: STM, D, C, MCDC, F, FC, SC, RO, CDC, DZ, CA | The goal type filter for code coverage/robustness check goals. Possible values for code coverage goals: STM(Statement), C(Condition), D(Decision/Branch), CDC(C/DC), MCDC(C/DC and MC/DC), F(Function), SC(Switch-Case), RO(Relational Operator), FC(Function Call). Possible values for robustness check goals are: DZ(Division by Zero), CA(Downcast). Can also specify multiple options. Can also be empty, in which case the results are shown for all goal types. |
| files | array of string | List of file filters for code coverage/robustness check goals. If list is empty the results are shown for all files. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{  
  Array of object:  
  pll      string    PLL string of the coverage goal.  
  type     string    Goal type of the coverage goal.  
  line     integer   The line number of the location where the coverage goal is located in the file.  
  file     string    The file name where the coverage property can be located.  
  properties [{  
    Array of object: A list with coverage goal properties.  
    pll      string    PLL string of the coverage property.  
    status   string    Status of the coverage property.  
    coveringVectors [string] List of string vector names that cover the property.  
  }]  
}]
```

```

    expression string Expression of the coverage goal.
    blocks      [string] The TargetLink blocks
    comment     string The comment.
    justified   boolean If this goal is justified
  }
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

7.2 GET /ep/scopes/{scope-uid}/coverage-results-b2b

Get coverage results for a scope

Get the code coverage and robustness checks results for a scope. Goal type filters can be applied.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|----------------------|
| *scope-uid | string | The UID of the scope |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|---|--|
| goal-types | array of string ALLOWED: STM, D, C, MCDC, F, FC, SC, RO, CDC, DZ, CA | The goal type filter for code coverage/robustness check goals. Possible values for code coverage goals: STM(Statement), C(Condition), D(Decision/Branch), CDC(C/DC), MCDC(C/DC and MC/DC), F(Function), SC(Switch-Case), RO(Relational Operator), FC(Function Call). Possible values for robustness check goals are: DZ(Division by Zero), CA(Downcast). Can also specify multiple options. Can also be empty, in which case the results are shown for all goal types. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```

{
  CDCCoverage {
    CDC goal coverage information.
    coverageGoal string Name of the goal
    coveredCompletelyCount integer Coverage complete count
    coveredCompletelyPercentage number Coverage complete percentage
    coveredPartiallyCount integer Coverage partial count
    coveredPartiallyPercentage number Coverage partial percentage
    handledCompleteCount number Handled complete count
  }
}
```

```

        handledCompletelyCount      integer
        handledCompletelyPercentage number    Handled complete percentage
        handledPartiallyCount       integer    Handled partial count
        handledPartiallyPercentage  number    Handled partial percentage
        unhandledCount              integer    Unhandled count
        unhandledPercentage          number    Unhandled percentage
        uncoveredCount               integer    Uncovered count
        uncoveredPercentage          number    Uncovered percentage
        justifiedCompletelyCount     integer    Covered completely (justified) count
        justifiedCompletelyPercentage number    Covered completely (justified) percentage
        justifiedPartiallyCount      integer    Covered partially (justified) count
        justifiedPartiallyPercentage number    Covered partially (justified) percentage
        totalCount                   integer    Total count
    }
    CDCPropertyCoverage {
        CDC property coverage information.

        coverageGoal                string     Name of the goal
        coveredCount                  integer    Covered count
        coveredPercentage             number     Covered percentage
        unreachableInfiniteCount      integer    Unreachable Infinite count
        unreachableInfinitePercentage number     Unreachable Infinite percentage
        unreachableNCount             integer    Unreachable N count
        unreachableNPercentage        number     Unreachable N percentage
        unreachableInfiniteJustifiedCount integer    Unreachable Infinite (justified) count
        unreachableInfiniteJustifiedPercentage number    Unreachable Infinite (justified) percentage
        unreachableNJustifiedCount    integer    Unreachable N (justified) count
        unreachableNJustifiedPercentage number    Unreachable N (justified) percentage
        unknownJustifiedCount         integer    Unknown (justified) count
        unknownJustifiedPercentage    number     Unknown (justified) percentage
        unknownCount                  integer    Unknown count
        unknownPercentage             number     Unknown percentage
        handledCount                  integer    Handled count
        handledPercentage             number     Handled percentage
        inconsistentCount             integer    Inconsistent count
        inconsistentPercentage        number     Inconsistent percentage
        unreachableCount             integer    Unreachable count
        unreachablePercentage         number     Unreachable percentage
        totalCount                    integer    Total count
        comment                       string     The comment
    }
    ConditionCoverage {
        Condition goal coverage information.

        coverageGoal                string     Name of the goal
        coveredCompletelyCount       integer    Coverage complete count
        coveredCompletelyPercentage  number     Coverage complete percentage
        coveredPartiallyCount        integer    Coverage partial count
        coveredPartiallyPercentage   number     Coverage partial percentage
        handledCompletelyCount       integer    Handled complete count
        handledCompletelyPercentage  number     Handled complete percentage
        handledPartiallyCount        integer    Handled partial count
        handledPartiallyPercentage   number     Handled partial percentage
        unhandledCount              integer    Unhandled count
        unhandledPercentage          number     Unhandled percentage
        uncoveredCount               integer    Uncovered count
        uncoveredPercentage          number     Uncovered percentage
        justifiedCompletelyCount     integer    Covered completely (justified) count
        justifiedCompletelyPercentage number    Covered completely (justified) percentage

```



```

    justifiedPartiallyCount      integer  Covered partially (justified) count
    justifiedPartiallyPercentage number  Covered partially (justified) percentage
    totalCount                   integer  Total count
}
ConditionPropertyCoverage {
Condition property coverage information.

    coverageGoal                string  Name of the goal
    coveredCount                 integer  Covered count
    coveredPercentage            number  Covered percentage
    unreachableInfiniteCount     integer  Unreachable Infinite count
    unreachableInfinitePercentage number  Unreachable Infinite percentage
    unreachableNCount            integer  Unreachable N count
    unreachableNPercentage       number  Unreachable N percentage
    unreachableInfiniteJustifiedCount integer  Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number  Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount   integer  Unreachable N (justified) count
    unreachableNJustifiedPercentage number  Unreachable N (justified) percentage
    unknownJustifiedCount        integer  Unknown (justified) count
    unknownJustifiedPercentage   number  Unknown (justified) percentage
    unknownCount                 integer  Unknown count
    unknownPercentage            number  Unknown percentage
    handledCount                 integer  Handled count
    handledPercentage            number  Handled percentage
    inconsistentCount            integer  Inconsistent count
    inconsistentPercentage       number  Inconsistent percentage
    unreachableCount             integer  Unreachable count
    unreachablePercentage        number  Unreachable percentage
    totalCount                   integer  Total count
    comment                      string  The comment
}
DecisionCoverage {
Decision goal coverage information.

    coverageGoal                string  Name of the goal
    coveredCompletelyCount       integer  Coverage complete count
    coveredCompletelyPercentage  number  Coverage complete percentage
    coveredPartiallyCount        integer  Coverage partial count
    coveredPartiallyPercentage   number  Coverage partial percentage
    handledCompletelyCount       integer  Handled complete count
    handledCompletelyPercentage  number  Handled complete percentage
    handledPartiallyCount        integer  Handled partial count
    handledPartiallyPercentage   number  Handled partial percentage
    unhandledCount               integer  Unhandled count
    unhandledPercentage          number  Unhandled percentage
    uncoveredCount               integer  Uncovered count
    uncoveredPercentage          number  Uncovered percentage
    justifiedCompletelyCount      integer  Covered completely (justified) count
    justifiedCompletelyPercentage number  Covered completely (justified) percentage
    justifiedPartiallyCount       integer  Covered partially (justified) count
    justifiedPartiallyPercentage  number  Covered partially (justified) percentage
    totalCount                   integer  Total count
}
DecisionPropertyCoverage {
Decision property coverage information.

    coverageGoal                string  Name of the goal
    coveredCount                 integer  Covered count
    coveredPercentage            number  Covered percentage
    unreachableInfiniteCount     integer  Unreachable Infinite count

```

| | | |
|--|---------|---|
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

FunctionCoverage {

Function goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

FunctionPropertyCoverage {

Function property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |

| | | |
|------------------------|---------|-------------------------|
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

FunctionCallCoverage {

Function call goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

FunctionCallPropertyCoverage {

Function call property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

MCDCCoverage {

MCDC goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

MCDCPropertyCoverage {

MCDC property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

RelationalOperatorCoverage {

Relational operation goal coverage information.

| | | |
|-----------------------------|---------|------------------------------|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |

```

    handledPartiallyPercentage    number    Handled partial percentage
    unhandledCount                integer     Unhandled count
    unhandledPercentage           number     Unhandled percentage
    uncoveredCount                integer     Uncovered count
    uncoveredPercentage           number     Uncovered percentage
    justifiedCompletelyCount       integer     Covered completely (justified) count
    justifiedCompletelyPercentage number     Covered completely (justified) percentage
    justifiedPartiallyCount        integer     Covered partially (justified) count
    justifiedPartiallyPercentage   number     Covered partially (justified) percentage
    totalCount                    integer     Total count
}
RelationalOperatorPropertyCoverage {
    Relational operation property coverage information.

    coverageGoal                  string     Name of the goal
    coveredCount                  integer     Covered count
    coveredPercentage              number     Covered percentage
    unreachableInfiniteCount       integer     Unreachable Infinite count
    unreachableInfinitePercentage number     Unreachable Infinite percentage
    unreachableNCount              integer     Unreachable N count
    unreachableNPercentage         number     Unreachable N percentage
    unreachableInfiniteJustifiedCount integer     Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number     Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount     integer     Unreachable N (justified) count
    unreachableNJustifiedPercentage number     Unreachable N (justified) percentage
    unknownJustifiedCount          integer     Unknown (justified) count
    unknownJustifiedPercentage     number     Unknown (justified) percentage
    unknownCount                  integer     Unknown count
    unknownPercentage              number     Unknown percentage
    handledCount                   integer     Handled count
    handledPercentage              number     Handled percentage
    inconsistentCount              integer     Inconsistent count
    inconsistentPercentage          number     Inconsistent percentage
    unreachableCount               integer     Unreachable count
    unreachablePercentage           number     Unreachable percentage
    totalCount                    integer     Total count
    comment                       string      The comment
}
StatementCoverage {
    Statement goal coverage information.

    coverageGoal                  string     Name of the goal
    coveredCompletelyCount         integer     Coverage complete count
    coveredCompletelyPercentage    number     Coverage complete percentage
    coveredPartiallyCount          integer     Coverage partial count
    coveredPartiallyPercentage     number     Coverage partial percentage
    handledCompletelyCount          integer     Handled complete count
    handledCompletelyPercentage    number     Handled complete percentage
    handledPartiallyCount           integer     Handled partial count
    handledPartiallyPercentage     number     Handled partial percentage
    unhandledCount                 integer     Unhandled count
    unhandledPercentage             number     Unhandled percentage
    uncoveredCount                 integer     Uncovered count
    uncoveredPercentage             number     Uncovered percentage
    justifiedCompletelyCount         integer     Covered completely (justified) count
    justifiedCompletelyPercentage   number     Covered completely (justified) percentage
    justifiedPartiallyCount          integer     Covered partially (justified) count
    justifiedPartiallyPercentage    number     Covered partially (justified) percentage
    totalCount                    integer     Total count

```

```

}
StatementPropertyCoverage {
Statement property coverage information.

    coverageGoal                string    Name of the goal
    coveredCount                integer    Covered count
    coveredPercentage            number    Covered percentage
    unreachableInfiniteCount     integer    Unreachable Infinite count
    unreachableInfinitePercentage number    Unreachable Infinite percentage
    unreachableNCount           integer    Unreachable N count
    unreachableNPercentage       number    Unreachable N percentage
    unreachableInfiniteJustifiedCount integer    Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number    Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount   integer    Unreachable N (justified) count
    unreachableNJustifiedPercentage number    Unreachable N (justified) percentage
    unknownJustifiedCount        integer    Unknown (justified) count
    unknownJustifiedPercentage   number    Unknown (justified) percentage
    unknownCount                 integer    Unknown count
    unknownPercentage            number    Unknown percentage
    handledCount                 integer    Handled count
    handledPercentage            number    Handled percentage
    inconsistentCount            integer    Inconsistent count
    inconsistentPercentage       number    Inconsistent percentage
    unreachableCount             integer    Unreachable count
    unreachablePercentage        number    Unreachable percentage
    totalCount                   integer    Total count
    comment                      string    The comment
}

SwitchCaseCoverage {
Switch Case goal coverage information.

    coverageGoal                string    Name of the goal
    coveredCompletelyCount       integer    Coverage complete count
    coveredCompletelyPercentage  number    Coverage complete percentage
    coveredPartiallyCount        integer    Coverage partial count
    coveredPartiallyPercentage   number    Coverage partial percentage
    handledCompletelyCount        integer    Handled complete count
    handledCompletelyPercentage  number    Handled complete percentage
    handledPartiallyCount        integer    Handled partial count
    handledPartiallyPercentage   number    Handled partial percentage
    unhandledCount               integer    Unhandled count
    unhandledPercentage          number    Unhandled percentage
    uncoveredCount               integer    Uncovered count
    uncoveredPercentage          number    Uncovered percentage
    justifiedCompletelyCount      integer    Covered completely (justified) count
    justifiedCompletelyPercentage number    Covered completely (justified) percentage
    justifiedPartiallyCount       integer    Covered partially (justified) count
    justifiedPartiallyPercentage  number    Covered partially (justified) percentage
    totalCount                   integer    Total count
}

SwitchCasePropertyCoverage {
Switch Case property coverage information.

    coverageGoal                string    Name of the goal
    coveredCount                integer    Covered count
    coveredPercentage            number    Covered percentage
    unreachableInfiniteCount     integer    Unreachable Infinite count
    unreachableInfinitePercentage number    Unreachable Infinite percentage
    unreachableNCount           integer    Unreachable N count
    unreachableNPercentage       number    Unreachable N percentage

```

| | | |
|--|---------|---|
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

DivisionByZeroCoverage {
Division By Zero goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

DivisionByZeroPropertyCoverage {
Division By Zero property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |

| | | |
|------------------------|---------|-------------------------|
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

DownCastCoverage {

DownCast goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

DownCastPropertyCoverage {

DownCast property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

codeCoverageComment

string

The code coverage overview comment.

robustnessCoverageComment

string

The robustness coverage overview comment.

}

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

7.3 POST /ep/coverage-goals/set-comment-b2b

Set goal comments

Set comments of code coverage and robustness check goals.

REQUEST

REQUEST BODY - application/json

```
[{  
  Array of object:  
    pll*    string  The PLL of the code coverage or robustness goal for which to set the comment.  
    comment* string  The comment to set on the goal with the given PLL.  
}]
```

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

7.4 POST /ep/coverage-goals/set-justified-b2b

Set goal justified status

Set justified status of code coverage and robustness check goals.

REQUEST

REQUEST BODY - application/json

```
{  
  justified boolean  The desired state of justify for the supplied goals.  
  plls      [string] The PLLs of the goals  
}
```

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

7.5 POST /ep/scopes/{scope-uid}/set-coverage-overview-comment-b2b

Set overview comments

Set the comments of code coverage overview sections.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|----------------------|
| *scope-uid | string | The UID of the scope |

REQUEST BODY - application/json

```
[{
  Array of object:
    type*      enum      ALLOWED:CC_STAT, STM, D, C, MCDC, F, FC, SC, RO, RC_STAT, DZ, CA
                  The type of overview for which to set the comment. Possible values for code coverage goals: CC_STAT(Code Coverage Statistics), STM(Statement), D(Decision/Branch), C(Condition), MCDC(C/DC and MC/DC), F(Function), FC(Function Call). SC(Switch-Case), RO(Relational Operator), Possible values for robustness check goals are: RC_STAT(Robustness Check Statistics),DZ(Division by Zero), CA(Downcast). Can also specify multiple options.
    comment*   string    The comment to set for the overview type.
}]
```

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

8. CODE COVERAGE/ROBUSTNESS CHECK RBT

Retrieve code coverage/robustness checks details and results in RBT.

8.1 GET /ep/requirements-sources/{requirement-source-uid}/coverage-details-rbt

Get coverage details for a requirement source

Get code coverage/robustness checks details for a requirement source. Some filters can be applied.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------------------|--------|-----------------------------------|
| *requirement-source-uid | string | The UID of the requirement source |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|---|---|
| statuses | array of string ALLOWED: COVERED, UNKNOWN, UNREACHABLE_INF, UNREACHABLE_N, INCONSISTENT, UNKNOWN_JUSTIFIED, UNREACHABLE_N_JUSTIFIED, UNREACHABLE_INF_JUSTIFIED | The status filter for code coverage/robustness check goals. Possible values: COVERED, UNKNOWN, UNREACHABLE_INF, UNREACHABLE_N, INCONSISTENT, UNKNOWN_JUSTIFIED, UNREACHABLE_INF_JUSTIFIED, UNREACHABLE_N_JUSTIFIED. Can also specify multiple options. Can also be empty, in which case the results are shown for all statuses. |
| goal-types | array of string ALLOWED: STM, D, C, MCD, F, FC, SC, RO, CDC, DZ, CA | The goal type filter for code coverage/robustness check goals. Possible values for code coverage goals: STM(Statement), C(Condition), D(Decision/Branch), CDC(C/DC), MCD(C/DC and MC/DC), F(Function), SC(Switch-Case), RO(Relational Operator), FC(Function Call). Possible values for robustness check goals are: DZ(Division by Zero), CA(Downcast). Can also specify multiple options. Can also be empty, in which case the results are shown for all goal types. |
| files | array of string | List of file filters for code coverage/robustness check goals. If list is empty the results are shown for all files. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
```

Array of object:

| | | |
|------|---------|---|
| pll | string | PLL string of the coverage goal. |
| type | string | Goal type of the coverage goal. |
| line | integer | The line number of the location where the coverage goal is located in the file. |
| file | string | The file name where the coverage property can be located. |

```
properties [{
```

Array of object: A list with coverage goal properties.

| | | |
|-----------------|----------|--|
| pll | string | PLL string of the coverage property. |
| status | string | Status of the coverage property. |
| coveringVectors | [string] | List of string vector names that cover the property. |

```

    }]
    expression string      Expression of the coverage goal.
    blocks      [string]    The TargetLink blocks
    comment     string      The comment.
    justified   boolean     If this goal is justified
  }]

```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

8.2 GET /ep/scopes/{scope-uid}/coverage-details-rbt

Get coverage details for a scope

Get all code coverage/robustness checks details for a scope. Some filters can be applied.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|----------------------|
| *scope-uid | string | The UID of the scope |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|---|---|
| statuses | array of string ALLOWED: COVERED, UNKNOWN, UNREACHABLE_INF, UNREACHABLE_N, INCONSISTENT, UNKNOWN_JUSTIFIED, UNREACHABLE_INF_JUSTIFIED, UNREACHABLE_N_JUSTIFIED | The status filter for code coverage/robustness check goals. Possible values: COVERED, UNKNOWN, UNREACHABLE_INF, UNREACHABLE_N, INCONSISTENT, UNKNOWN_JUSTIFIED, UNREACHABLE_INF_JUSTIFIED, UNREACHABLE_N_JUSTIFIED. Can also specify multiple options. Can also be empty, in which case the results are shown for all statuses. |
| goal-types | array of string ALLOWED: STM, D, C, MCDC, F, FC, SC, RO, CDC, DZ, CA | The goal type filter for code coverage/robustness check goals. Possible values for code coverage goals: STM(Statement), C(Condition), D(Decision/Branch), CDC(C/DC), MCDC(C/DC and MC/DC), F(Function), SC(Switch-Case), RO(Relational Operator), FC(Function Call). Possible values for robustness check goals are: DZ(Division by Zero), CA(Downcast). Can also specify multiple options. Can also be empty, in which case the results are shown for all goal types. |
| files | array of string | List of file filters for code coverage/robustness check goals. If list is empty the results are shown for all files. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
  pll          string    PLL string of the coverage goal.
  type         string    Goal type of the coverage goal.
  line         integer   The line number of the location where the coverage goal is located in the file.
  file         string    The file name where the coverage property can be located.
  properties   [{
    Array of object: A list with coverage goal properties.
    pll          string    PLL string of the coverage property.
    status       string    Status of the coverage property.
    coveringVectors [string] List of string vector names that cover the property.
  }]
  expression   string    Expression of the coverage goal.
  blocks       [string]   The TargetLink blocks
  comment      string    The comment.
  justified     boolean   If this goal is justified
}]
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

8.3 GET /ep/requirements-sources/{requirements-source-uid}/coverage-results-rbt

Get coverage results for a requirement source

Get the code coverage and robustness checks results for a requirement source. Goal type filters can be applied.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|--------------------------|--------|-----------------------------------|
| *requirements-source-uid | string | The UID of the requirement source |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------|------|-------------|
|------|------|-------------|

| NAME | TYPE | DESCRIPTION |
|------------|---|--|
| goal-types | array of string ALLOWED: STM, D, C, MCDC, F, FC, SC, RO, CDC, DZ, CA | The goal type filter for code coverage/robustness check goals. Possible values for code coverage goals: STM(Statement), C(Condition), D(Decision/Branch), CDC(C/DC), MCDC(C/DC and MC/DC), F(Function), SC(Switch-Case), RO(Relational Operator), FC(Function Call). Possible values for robustness check goals are: DZ(Division by Zero), CA(Downcast). Can also specify multiple options. Can also be empty, in which case the results are shown for all goal types. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  CDCCoverage {
    CDC goal coverage information.
    coverageGoal          string    Name of the goal
    coveredCompletelyCount integer   Coverage complete count
    coveredCompletelyPercentage number  Coverage complete percentage
    coveredPartiallyCount  integer   Coverage partial count
    coveredPartiallyPercentage number  Coverage partial percentage
    handledCompletelyCount integer   Handled complete count
    handledCompletelyPercentage number  Handled complete percentage
    handledPartiallyCount  integer   Handled partial count
    handledPartiallyPercentage number  Handled partial percentage
    unhandledCount         integer   Unhandled count
    unhandledPercentage     number   Unhandled percentage
    uncoveredCount         integer   Uncovered count
    uncoveredPercentage     number   Uncovered percentage
    justifiedCompletelyCount integer   Covered completely (justified) count
    justifiedCompletelyPercentage number  Covered completely (justified) percentage
    justifiedPartiallyCount integer   Covered partially (justified) count
    justifiedPartiallyPercentage number  Covered partially (justified) percentage
    totalCount             integer   Total count
  }
  CDCPropertyCoverage {
    CDC property coverage information.
    coverageGoal          string    Name of the goal
    coveredCount          integer   Covered count
    coveredPercentage     number   Covered percentage
    unreachableInfiniteCount integer  Unreachable Infinite count
    unreachableInfinitePercentage number  Unreachable Infinite percentage
    unreachableNCount     integer   Unreachable N count
    unreachableNPercentage number   Unreachable N percentage
    unreachableInfiniteJustifiedCount integer  Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number  Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount integer  Unreachable N (justified) count
    unreachableNJustifiedPercentage number  Unreachable N (justified) percentage
    unknownJustifiedCount integer   Unknown (justified) count
    unknownJustifiedPercentage number  Unknown (justified) percentage
    unknownCount         integer   Unknown count
    unknownPercentage     number   Unknown percentage
    handledCount         integer   Handled count
    handledPercentage     number   Handled percentage
    inconsistentCount     integer   Inconsistent count
    inconsistentPercentage number   Inconsistent percentage
  }
}
```

| | | |
|-----------------------|---------|------------------------|
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

ConditionCoverage {
Condition goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

ConditionPropertyCoverage {
Condition property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

DecisionCoverage {
Decision goal coverage information.

| | | |
|-----------------------------|---------|------------------------------|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |

```

coveredPartiallyCount      integer Coverage partial count
coveredPartiallyPercentage number Coverage partial percentage
handledCompletelyCount     integer Handled complete count
handledCompletelyPercentage number Handled complete percentage
handledPartiallyCount      integer Handled partial count
handledPartiallyPercentage number Handled partial percentage
unhandledCount             integer Unhandled count
unhandledPercentage        number Unhandled percentage
uncoveredCount             integer Uncovered count
uncoveredPercentage        number Uncovered percentage
justifiedCompletelyCount   integer Covered completely (justified) count
justifiedCompletelyPercentage number Covered completely (justified) percentage
justifiedPartiallyCount    integer Covered partially (justified) count
justifiedPartiallyPercentage number Covered partially (justified) percentage
totalCount                 integer Total count
}
DecisionPropertyCoverage {
Decision property coverage information.

coverageGoal               string Name of the goal
coveredCount               integer Covered count
coveredPercentage          number Covered percentage
unreachableInfiniteCount   integer Unreachable Infinite count
unreachableInfinitePercentage number Unreachable Infinite percentage
unreachableNCount          integer Unreachable N count
unreachableNPercentage     number Unreachable N percentage
unreachableInfiniteJustifiedCount integer Unreachable Infinite (justified) count
unreachableInfiniteJustifiedPercentage number Unreachable Infinite (justified) percentage
unreachableNJustifiedCount integer Unreachable N (justified) count
unreachableNJustifiedPercentage number Unreachable N (justified) percentage
unknownJustifiedCount      integer Unknown (justified) count
unknownJustifiedPercentage number Unknown (justified) percentage
unknownCount              integer Unknown count
unknownPercentage          number Unknown percentage
handledCount              integer Handled count
handledPercentage          number Handled percentage
inconsistentCount          integer Inconsistent count
inconsistentPercentage     number Inconsistent percentage
unreachableCount           integer Unreachable count
unreachablePercentage      number Unreachable percentage
totalCount                 integer Total count
comment                    string The comment
}
FunctionCoverage {
Function goal coverage information.

coverageGoal               string Name of the goal
coveredCompletelyCount     integer Coverage complete count
coveredCompletelyPercentage number Coverage complete percentage
coveredPartiallyCount      integer Coverage partial count
coveredPartiallyPercentage number Coverage partial percentage
handledCompletelyCount     integer Handled complete count
handledCompletelyPercentage number Handled complete percentage
handledPartiallyCount      integer Handled partial count
handledPartiallyPercentage number Handled partial percentage
unhandledCount             integer Unhandled count
unhandledPercentage        number Unhandled percentage
uncoveredCount             integer Uncovered count
uncoveredPercentage        number Uncovered percentage

```



```

    justifiedCompletelyCount      integer  Covered completely (justified) count
    justifiedCompletelyPercentage number  Covered completely (justified) percentage
    justifiedPartiallyCount       integer  Covered partially (justified) count
    justifiedPartiallyPercentage  number  Covered partially (justified) percentage
    totalCount                    integer  Total count
}
FunctionPropertyCoverage {
Function property coverage information.

    coverageGoal                  string  Name of the goal
    coveredCount                  integer  Covered count
    coveredPercentage              number  Covered percentage
    unreachableInfiniteCount       integer  Unreachable Infinite count
    unreachableInfinitePercentage number  Unreachable Infinite percentage
    unreachableNCount              integer  Unreachable N count
    unreachableNPercentage         number  Unreachable N percentage
    unreachableInfiniteJustifiedCount integer  Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number  Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount     integer  Unreachable N (justified) count
    unreachableNJustifiedPercentage number  Unreachable N (justified) percentage
    unknownJustifiedCount          integer  Unknown (justified) count
    unknownJustifiedPercentage     number  Unknown (justified) percentage
    unknownCount                   integer  Unknown count
    unknownPercentage              number  Unknown percentage
    handledCount                   integer  Handled count
    handledPercentage              number  Handled percentage
    inconsistentCount              integer  Inconsistent count
    inconsistentPercentage         number  Inconsistent percentage
    unreachableCount               integer  Unreachable count
    unreachablePercentage          number  Unreachable percentage
    totalCount                     integer  Total count
    comment                        string  The comment
}
FunctionCallCoverage {
Function call goal coverage information.

    coverageGoal                  string  Name of the goal
    coveredCompletelyCount        integer  Coverage complete count
    coveredCompletelyPercentage   number  Coverage complete percentage
    coveredPartiallyCount         integer  Coverage partial count
    coveredPartiallyPercentage    number  Coverage partial percentage
    handledCompletelyCount        integer  Handled complete count
    handledCompletelyPercentage   number  Handled complete percentage
    handledPartiallyCount         integer  Handled partial count
    handledPartiallyPercentage    number  Handled partial percentage
    unhandledCount                integer  Unhandled count
    unhandledPercentage           number  Unhandled percentage
    uncoveredCount                integer  Uncovered count
    uncoveredPercentage           number  Uncovered percentage
    justifiedCompletelyCount       integer  Covered completely (justified) count
    justifiedCompletelyPercentage  number  Covered completely (justified) percentage
    justifiedPartiallyCount        integer  Covered partially (justified) count
    justifiedPartiallyPercentage  number  Covered partially (justified) percentage
    totalCount                     integer  Total count
}
FunctionCallPropertyCoverage {
Function call property coverage information.

    coverageGoal                  string  Name of the goal
    coveredCount                  integer  Covered count

```

| | | |
|--|---------|---|
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

MCDCCoverage {
MCDC goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

MCDCPropertyCoverage {
MCDC property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |

| | | |
|----------------------------|---------|--------------------------------|
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

RelationalOperatorCoverage {
 Relational operation goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

RelationalOperatorPropertyCoverage {
 Relational operation property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |

```

    comment                                string    The comment
}
StatementCoverage {
Statement goal coverage information.

    coverageGoal                          string    Name of the goal
    coveredCompletelyCount                integer   Coverage complete count
    coveredCompletelyPercentage           number    Coverage complete percentage
    coveredPartiallyCount                 integer   Coverage partial count
    coveredPartiallyPercentage            number    Coverage partial percentage
    handledCompletelyCount                integer   Handled complete count
    handledCompletelyPercentage           number    Handled complete percentage
    handledPartiallyCount                 integer   Handled partial count
    handledPartiallyPercentage            number    Handled partial percentage
    unhandledCount                       integer   Unhandled count
    unhandledPercentage                   number    Unhandled percentage
    uncoveredCount                       integer   Uncovered count
    uncoveredPercentage                   number    Uncovered percentage
    justifiedCompletelyCount              integer   Covered completely (justified) count
    justifiedCompletelyPercentage         number    Covered completely (justified) percentage
    justifiedPartiallyCount               integer   Covered partially (justified) count
    justifiedPartiallyPercentage          number    Covered partially (justified) percentage
    totalCount                           integer   Total count
}
StatementPropertyCoverage {
Statement property coverage information.

    coverageGoal                          string    Name of the goal
    coveredCount                         integer   Covered count
    coveredPercentage                     number    Covered percentage
    unreachableInfiniteCount              integer   Unreachable Infinite count
    unreachableInfinitePercentage         number    Unreachable Infinite percentage
    unreachableNCount                    integer   Unreachable N count
    unreachableNPercentage                number    Unreachable N percentage
    unreachableInfiniteJustifiedCount     integer   Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number    Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount            integer   Unreachable N (justified) count
    unreachableNJustifiedPercentage       number    Unreachable N (justified) percentage
    unknownJustifiedCount                 integer   Unknown (justified) count
    unknownJustifiedPercentage            number    Unknown (justified) percentage
    unknownCount                         integer   Unknown count
    unknownPercentage                     number    Unknown percentage
    handledCount                         integer   Handled count
    handledPercentage                     number    Handled percentage
    inconsistentCount                     integer   Inconsistent count
    inconsistentPercentage                 number    Inconsistent percentage
    unreachableCount                      integer   Unreachable count
    unreachablePercentage                  number    Unreachable percentage
    totalCount                           integer   Total count
    comment                              string    The comment
}
SwitchCaseCoverage {
Switch Case goal coverage information.

    coverageGoal                          string    Name of the goal
    coveredCompletelyCount                integer   Coverage complete count
    coveredCompletelyPercentage           number    Coverage complete percentage
    coveredPartiallyCount                 integer   Coverage partial count
    coveredPartiallyPercentage            number    Coverage partial percentage
    handledCompletelyCount                integer   Handled complete count

```

| | | |
|-------------------------------|---------|---|
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

SwitchCasePropertyCoverage {
Switch Case property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

DivisionByZeroCoverage {
Division By Zero goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |

```

    justifiedPartiallyPercentage    number    Covered partially (justified) percentage
    totalCount                      integer    Total count
}
DivisionByZeroPropertyCoverage {
Division By Zero property coverage information.

    coverageGoal                  string     Name of the goal
    coveredCount                  integer    Covered count
    coveredPercentage              number     Covered percentage
    unreachableInfiniteCount       integer    Unreachable Infinite count
    unreachableInfinitePercentage number     Unreachable Infinite percentage
    unreachableNCount              integer    Unreachable N count
    unreachableNPercentage         number     Unreachable N percentage
    unreachableInfiniteJustifiedCount integer    Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number    Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount     integer    Unreachable N (justified) count
    unreachableNJustifiedPercentage number     Unreachable N (justified) percentage
    unknownJustifiedCount          integer    Unknown (justified) count
    unknownJustifiedPercentage     number     Unknown (justified) percentage
    unknownCount                   integer    Unknown count
    unknownPercentage              number     Unknown percentage
    handledCount                   integer    Handled count
    handledPercentage              number     Handled percentage
    inconsistentCount              integer    Inconsistent count
    inconsistentPercentage         number     Inconsistent percentage
    unreachableCount               integer    Unreachable count
    unreachablePercentage          number     Unreachable percentage
    totalCount                     integer    Total count
    comment                        string     The comment
}
DownCastCoverage {
DownCast goal coverage information.

    coverageGoal                  string     Name of the goal
    coveredCompletelyCount         integer    Coverage complete count
    coveredCompletelyPercentage    number     Coverage complete percentage
    coveredPartiallyCount          integer    Coverage partial count
    coveredPartiallyPercentage     number     Coverage partial percentage
    handledCompletelyCount          integer    Handled complete count
    handledCompletelyPercentage    number     Handled complete percentage
    handledPartiallyCount           integer    Handled partial count
    handledPartiallyPercentage     number     Handled partial percentage
    unhandledCount                 integer    Unhandled count
    unhandledPercentage            number     Unhandled percentage
    uncoveredCount                  integer    Uncovered count
    uncoveredPercentage            number     Uncovered percentage
    justifiedCompletelyCount        integer    Covered completely (justified) count
    justifiedCompletelyPercentage  number     Covered completely (justified) percentage
    justifiedPartiallyCount         integer    Covered partially (justified) count
    justifiedPartiallyPercentage   number     Covered partially (justified) percentage
    totalCount                      integer    Total count
}
DownCastPropertyCoverage {
DownCast property coverage information.

    coverageGoal                  string     Name of the goal
    coveredCount                  integer    Covered count
    coveredPercentage              number     Covered percentage
    unreachableInfiniteCount       integer    Unreachable Infinite count
    unreachableInfinitePercentage number     Unreachable Infinite percentage

```

| | | |
|--|---------|---|
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |
| } | | |
| codeCoverageComment | string | The code coverage overview comment. |
| robustnessCoverageComment | string | The robustness coverage overview comment. |
| } | | |

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

8.4 GET /ep/scopes/{scope-uid}/coverage-results-rbt

Get coverage results for a scope

Get the code coverage and robustness checks results for a scope. Goal type filters can be applied.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|----------------------|
| *scope-uid | string | The UID of the scope |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------|------|-------------|
|------|------|-------------|

| NAME | TYPE | DESCRIPTION |
|------------|---|--|
| goal-types | array of string ALLOWED: STM, D, C, MCDC, F, FC, SC, RO, CDC, DZ, CA | The goal type filter for code coverage/robustness check goals. Possible values for code coverage goals: STM(Statement), C(Condition), D(Decision/Branch), CDC(C/DC), MCDC(C/DC and MC/DC), F(Function), SC(Switch-Case), RO(Relational Operator), FC(Function Call). Possible values for robustness check goals are: DZ(Division by Zero), CA(Downcast). Can also specify multiple options. Can also be empty, in which case the results are shown for all goal types. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  CDCCoverage {
    CDC goal coverage information.
    coverageGoal          string    Name of the goal
    coveredCompletelyCount integer    Coverage complete count
    coveredCompletelyPercentage number  Coverage complete percentage
    coveredPartiallyCount integer    Coverage partial count
    coveredPartiallyPercentage number  Coverage partial percentage
    handledCompletelyCount integer    Handled complete count
    handledCompletelyPercentage number  Handled complete percentage
    handledPartiallyCount integer    Handled partial count
    handledPartiallyPercentage number  Handled partial percentage
    unhandledCount        integer    Unhandled count
    unhandledPercentage    number    Unhandled percentage
    uncoveredCount        integer    Uncovered count
    uncoveredPercentage    number    Uncovered percentage
    justifiedCompletelyCount integer    Covered completely (justified) count
    justifiedCompletelyPercentage number  Covered completely (justified) percentage
    justifiedPartiallyCount integer    Covered partially (justified) count
    justifiedPartiallyPercentage number  Covered partially (justified) percentage
    totalCount            integer    Total count
  }
  CDCPropertyCoverage {
    CDC property coverage information.
    coverageGoal          string    Name of the goal
    coveredCount          integer    Covered count
    coveredPercentage      number    Covered percentage
    unreachableInfiniteCount integer    Unreachable Infinite count
    unreachableInfinitePercentage number  Unreachable Infinite percentage
    unreachableNCount      integer    Unreachable N count
    unreachableNPercentage number    Unreachable N percentage
    unreachableInfiniteJustifiedCount integer    Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number  Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount integer    Unreachable N (justified) count
    unreachableNJustifiedPercentage number  Unreachable N (justified) percentage
    unknownJustifiedCount  integer    Unknown (justified) count
    unknownJustifiedPercentage number    Unknown (justified) percentage
    unknownCount          integer    Unknown count
    unknownPercentage      number    Unknown percentage
    handledCount          integer    Handled count
    handledPercentage      number    Handled percentage
    inconsistentCount      integer    Inconsistent count
    inconsistentPercentage number    Inconsistent percentage
  }
}
```


| | | |
|-----------------------|---------|------------------------|
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

ConditionCoverage {
Condition goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

ConditionPropertyCoverage {
Condition property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

DecisionCoverage {
Decision goal coverage information.

| | | |
|-----------------------------|---------|------------------------------|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |

```

coveredPartiallyCount      integer  Coverage partial count
coveredPartiallyPercentage number  Coverage partial percentage
handledCompletelyCount     integer  Handled complete count
handledCompletelyPercentage number  Handled complete percentage
handledPartiallyCount      integer  Handled partial count
handledPartiallyPercentage number  Handled partial percentage
unhandledCount            integer  Unhandled count
unhandledPercentage        number  Unhandled percentage
uncoveredCount            integer  Uncovered count
uncoveredPercentage        number  Uncovered percentage
justifiedCompletelyCount   integer  Covered completely (justified) count
justifiedCompletelyPercentage number  Covered completely (justified) percentage
justifiedPartiallyCount    integer  Covered partially (justified) count
justifiedPartiallyPercentage number  Covered partially (justified) percentage
totalCount                integer  Total count
}
DecisionPropertyCoverage {
Decision property coverage information.

coverageGoal              string  Name of the goal
coveredCount              integer  Covered count
coveredPercentage          number  Covered percentage
unreachableInfiniteCount   integer  Unreachable Infinite count
unreachableInfinitePercentage number  Unreachable Infinite percentage
unreachableNCount         integer  Unreachable N count
unreachableNPercentage     number  Unreachable N percentage
unreachableInfiniteJustifiedCount integer  Unreachable Infinite (justified) count
unreachableInfiniteJustifiedPercentage number  Unreachable Infinite (justified) percentage
unreachableNJustifiedCount integer  Unreachable N (justified) count
unreachableNJustifiedPercentage number  Unreachable N (justified) percentage
unknownJustifiedCount     integer  Unknown (justified) count
unknownJustifiedPercentage number  Unknown (justified) percentage
unknownCount              integer  Unknown count
unknownPercentage         number  Unknown percentage
handledCount              integer  Handled count
handledPercentage          number  Handled percentage
inconsistentCount         integer  Inconsistent count
inconsistentPercentage     number  Inconsistent percentage
unreachableCount          integer  Unreachable count
unreachablePercentage      number  Unreachable percentage
totalCount                integer  Total count
comment                   string  The comment
}
FunctionCoverage {
Function goal coverage information.

coverageGoal              string  Name of the goal
coveredCompletelyCount     integer  Coverage complete count
coveredCompletelyPercentage number  Coverage complete percentage
coveredPartiallyCount      integer  Coverage partial count
coveredPartiallyPercentage number  Coverage partial percentage
handledCompletelyCount     integer  Handled complete count
handledCompletelyPercentage number  Handled complete percentage
handledPartiallyCount      integer  Handled partial count
handledPartiallyPercentage number  Handled partial percentage
unhandledCount            integer  Unhandled count
unhandledPercentage        number  Unhandled percentage
uncoveredCount            integer  Uncovered count
uncoveredPercentage        number  Uncovered percentage

```

```

    justifiedCompletelyCount      integer  Covered completely (justified) count
    justifiedCompletelyPercentage number  Covered completely (justified) percentage
    justifiedPartiallyCount       integer  Covered partially (justified) count
    justifiedPartiallyPercentage  number  Covered partially (justified) percentage
    totalCount                    integer  Total count
}
FunctionPropertyCoverage {
Function property coverage information.

    coverageGoal                  string  Name of the goal
    coveredCount                  integer  Covered count
    coveredPercentage              number  Covered percentage
    unreachableInfiniteCount       integer  Unreachable Infinite count
    unreachableInfinitePercentage number  Unreachable Infinite percentage
    unreachableNCount              integer  Unreachable N count
    unreachableNPercentage         number  Unreachable N percentage
    unreachableInfiniteJustifiedCount integer  Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number  Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount     integer  Unreachable N (justified) count
    unreachableNJustifiedPercentage number  Unreachable N (justified) percentage
    unknownJustifiedCount          integer  Unknown (justified) count
    unknownJustifiedPercentage     number  Unknown (justified) percentage
    unknownCount                   integer  Unknown count
    unknownPercentage              number  Unknown percentage
    handledCount                   integer  Handled count
    handledPercentage              number  Handled percentage
    inconsistentCount              integer  Inconsistent count
    inconsistentPercentage          number  Inconsistent percentage
    unreachableCount               integer  Unreachable count
    unreachablePercentage           number  Unreachable percentage
    totalCount                     integer  Total count
    comment                        string  The comment
}
FunctionCallCoverage {
Function call goal coverage information.

    coverageGoal                  string  Name of the goal
    coveredCompletelyCount        integer  Coverage complete count
    coveredCompletelyPercentage    number  Coverage complete percentage
    coveredPartiallyCount          integer  Coverage partial count
    coveredPartiallyPercentage     number  Coverage partial percentage
    handledCompletelyCount         integer  Handled complete count
    handledCompletelyPercentage    number  Handled complete percentage
    handledPartiallyCount          integer  Handled partial count
    handledPartiallyPercentage     number  Handled partial percentage
    unhandledCount                 integer  Unhandled count
    unhandledPercentage            number  Unhandled percentage
    uncoveredCount                 integer  Uncovered count
    uncoveredPercentage            number  Uncovered percentage
    justifiedCompletelyCount        integer  Covered completely (justified) count
    justifiedCompletelyPercentage  number  Covered completely (justified) percentage
    justifiedPartiallyCount         integer  Covered partially (justified) count
    justifiedPartiallyPercentage   number  Covered partially (justified) percentage
    totalCount                     integer  Total count
}
FunctionCallPropertyCoverage {
Function call property coverage information.

    coverageGoal                  string  Name of the goal
    coveredCount                  integer  Covered count

```

| | | |
|--|---------|---|
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

MCDCCoverage {
MCDC goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

MCDCPropertyCoverage {
MCDC property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |

| | | |
|---|---------|---|
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |
| } | | |
| RelationalOperatorCoverage { | | |
| Relational operation goal coverage information. | | |
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |
| } | | |
| RelationalOperatorPropertyCoverage { | | |
| Relational operation property coverage information. | | |
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |

```

    comment                                string    The comment
}
StatementCoverage {
Statement goal coverage information.

    coverageGoal                          string    Name of the goal
    coveredCompletelyCount                 integer   Coverage complete count
    coveredCompletelyPercentage            number    Coverage complete percentage
    coveredPartiallyCount                  integer   Coverage partial count
    coveredPartiallyPercentage             number    Coverage partial percentage
    handledCompletelyCount                  integer   Handled complete count
    handledCompletelyPercentage            number    Handled complete percentage
    handledPartiallyCount                   integer   Handled partial count
    handledPartiallyPercentage             number    Handled partial percentage
    unhandledCount                         integer   Unhandled count
    unhandledPercentage                     number    Unhandled percentage
    uncoveredCount                         integer   Uncovered count
    uncoveredPercentage                     number    Uncovered percentage
    justifiedCompletelyCount                integer   Covered completely (justified) count
    justifiedCompletelyPercentage           number    Covered completely (justified) percentage
    justifiedPartiallyCount                 integer   Covered partially (justified) count
    justifiedPartiallyPercentage            number    Covered partially (justified) percentage
    totalCount                             integer   Total count
}
StatementPropertyCoverage {
Statement property coverage information.

    coverageGoal                          string    Name of the goal
    coveredCount                           integer   Covered count
    coveredPercentage                       number    Covered percentage
    unreachableInfiniteCount                integer   Unreachable Infinite count
    unreachableInfinitePercentage           number    Unreachable Infinite percentage
    unreachableNCount                       integer   Unreachable N count
    unreachableNPercentage                  number    Unreachable N percentage
    unreachableInfiniteJustifiedCount       integer   Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number    Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount              integer   Unreachable N (justified) count
    unreachableNJustifiedPercentage         number    Unreachable N (justified) percentage
    unknownJustifiedCount                   integer   Unknown (justified) count
    unknownJustifiedPercentage              number    Unknown (justified) percentage
    unknownCount                           integer   Unknown count
    unknownPercentage                       number    Unknown percentage
    handledCount                           integer   Handled count
    handledPercentage                       number    Handled percentage
    inconsistentCount                       integer   Inconsistent count
    inconsistentPercentage                  number    Inconsistent percentage
    unreachableCount                        integer   Unreachable count
    unreachablePercentage                   number    Unreachable percentage
    totalCount                             integer   Total count
    comment                                string    The comment
}
SwitchCaseCoverage {
Switch Case goal coverage information.

    coverageGoal                          string    Name of the goal
    coveredCompletelyCount                 integer   Coverage complete count
    coveredCompletelyPercentage            number    Coverage complete percentage
    coveredPartiallyCount                  integer   Coverage partial count
    coveredPartiallyPercentage             number    Coverage partial percentage
    handledCompletelyCount                  integer   Handled complete count

```

| | | |
|-------------------------------|---------|---|
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |
| justifiedPartiallyPercentage | number | Covered partially (justified) percentage |
| totalCount | integer | Total count |

}

SwitchCasePropertyCoverage {
Switch Case property coverage information.

| | | |
|--|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCount | integer | Covered count |
| coveredPercentage | number | Covered percentage |
| unreachableInfiniteCount | integer | Unreachable Infinite count |
| unreachableInfinitePercentage | number | Unreachable Infinite percentage |
| unreachableNCount | integer | Unreachable N count |
| unreachableNPercentage | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | integer | Unknown (justified) count |
| unknownJustifiedPercentage | number | Unknown (justified) percentage |
| unknownCount | integer | Unknown count |
| unknownPercentage | number | Unknown percentage |
| handledCount | integer | Handled count |
| handledPercentage | number | Handled percentage |
| inconsistentCount | integer | Inconsistent count |
| inconsistentPercentage | number | Inconsistent percentage |
| unreachableCount | integer | Unreachable count |
| unreachablePercentage | number | Unreachable percentage |
| totalCount | integer | Total count |
| comment | string | The comment |

}

DivisionByZeroCoverage {
Division By Zero goal coverage information.

| | | |
|-------------------------------|---------|---|
| coverageGoal | string | Name of the goal |
| coveredCompletelyCount | integer | Coverage complete count |
| coveredCompletelyPercentage | number | Coverage complete percentage |
| coveredPartiallyCount | integer | Coverage partial count |
| coveredPartiallyPercentage | number | Coverage partial percentage |
| handledCompletelyCount | integer | Handled complete count |
| handledCompletelyPercentage | number | Handled complete percentage |
| handledPartiallyCount | integer | Handled partial count |
| handledPartiallyPercentage | number | Handled partial percentage |
| unhandledCount | integer | Unhandled count |
| unhandledPercentage | number | Unhandled percentage |
| uncoveredCount | integer | Uncovered count |
| uncoveredPercentage | number | Uncovered percentage |
| justifiedCompletelyCount | integer | Covered completely (justified) count |
| justifiedCompletelyPercentage | number | Covered completely (justified) percentage |
| justifiedPartiallyCount | integer | Covered partially (justified) count |

```

    justifiedPartiallyPercentage    number    Covered partially (justified) percentage
    totalCount                     integer     Total count
}
DivisionByZeroPropertyCoverage {
Division By Zero property coverage information.

    coverageGoal                  string     Name of the goal
    coveredCount                  integer     Covered count
    coveredPercentage             number     Covered percentage
    unreachableInfiniteCount       integer     Unreachable Infinite count
    unreachableInfinitePercentage number     Unreachable Infinite percentage
    unreachableNCount             integer     Unreachable N count
    unreachableNPercentage        number     Unreachable N percentage
    unreachableInfiniteJustifiedCount integer     Unreachable Infinite (justified) count
    unreachableInfiniteJustifiedPercentage number     Unreachable Infinite (justified) percentage
    unreachableNJustifiedCount     integer     Unreachable N (justified) count
    unreachableNJustifiedPercentage number     Unreachable N (justified) percentage
    unknownJustifiedCount         integer     Unknown (justified) count
    unknownJustifiedPercentage    number     Unknown (justified) percentage
    unknownCount                  integer     Unknown count
    unknownPercentage             number     Unknown percentage
    handledCount                  integer     Handled count
    handledPercentage             number     Handled percentage
    inconsistentCount             integer     Inconsistent count
    inconsistentPercentage        number     Inconsistent percentage
    unreachableCount              integer     Unreachable count
    unreachablePercentage         number     Unreachable percentage
    totalCount                    integer     Total count
    comment                       string     The comment
}
DownCastCoverage {
DownCast goal coverage information.

    coverageGoal                  string     Name of the goal
    coveredCompletelyCount        integer     Coverage complete count
    coveredCompletelyPercentage   number     Coverage complete percentage
    coveredPartiallyCount         integer     Coverage partial count
    coveredPartiallyPercentage    number     Coverage partial percentage
    handledCompletelyCount        integer     Handled complete count
    handledCompletelyPercentage   number     Handled complete percentage
    handledPartiallyCount         integer     Handled partial count
    handledPartiallyPercentage    number     Handled partial percentage
    unhandledCount                integer     Unhandled count
    unhandledPercentage           number     Unhandled percentage
    uncoveredCount                integer     Uncovered count
    uncoveredPercentage           number     Uncovered percentage
    justifiedCompletelyCount       integer     Covered completely (justified) count
    justifiedCompletelyPercentage number     Covered completely (justified) percentage
    justifiedPartiallyCount       integer     Covered partially (justified) count
    justifiedPartiallyPercentage  number     Covered partially (justified) percentage
    totalCount                    integer     Total count
}
DownCastPropertyCoverage {
DownCast property coverage information.

    coverageGoal                  string     Name of the goal
    coveredCount                  integer     Covered count
    coveredPercentage             number     Covered percentage
    unreachableInfiniteCount       integer     Unreachable Infinite count
    unreachableInfinitePercentage number     Unreachable Infinite percentage

```


| | | | |
|--|--------|---------|---|
| unreachableNCount | | integer | Unreachable N count |
| unreachableNPercentage | | number | Unreachable N percentage |
| unreachableInfiniteJustifiedCount | | integer | Unreachable Infinite (justified) count |
| unreachableInfiniteJustifiedPercentage | | number | Unreachable Infinite (justified) percentage |
| unreachableNJustifiedCount | | integer | Unreachable N (justified) count |
| unreachableNJustifiedPercentage | | number | Unreachable N (justified) percentage |
| unknownJustifiedCount | | integer | Unknown (justified) count |
| unknownJustifiedPercentage | | number | Unknown (justified) percentage |
| unknownCount | | integer | Unknown count |
| unknownPercentage | | number | Unknown percentage |
| handledCount | | integer | Handled count |
| handledPercentage | | number | Handled percentage |
| inconsistentCount | | integer | Inconsistent count |
| inconsistentPercentage | | number | Inconsistent percentage |
| unreachableCount | | integer | Unreachable count |
| unreachablePercentage | | number | Unreachable percentage |
| totalCount | | integer | Total count |
| comment | | string | The comment |
| } | | | |
| codeCoverageComment | string | | The code coverage overview comment. |
| robustnessCoverageComment | string | | The robustness coverage overview comment. |
| } | | | |

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

8.5 POST /ep/coverage-goals/set-comment-rbt

Set goal comments

Set comments of code coverage and robustness check goals.

REQUEST

REQUEST BODY - application/json

```
[{
  Array of object:
    pll*    string  The PLL of the code coverage or robustness goal for which to set the comment.
    comment* string  The comment to set on the goal with the given PLL.
}]
```

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

8.6 POST /ep/coverage-goals/set-justified-rbt

Set goal justified status

Set justified status of code coverage and robustness check goals.

REQUEST

REQUEST BODY - application/json

```
{
  justified boolean  The desired state of justify for the supplied goals.
  plls      [string] The PILs of the goals
}
```

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

8.7 POST /ep/scopes/{scope-uid}/set-coverage-overview-comment-rbt

Set overview comments

Set the comments of code coverage overview sections.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|----------------------|
| *scope-uid | string | The UID of the scope |

REQUEST BODY - application/json

```
[{
  Array of object:
    type*          enum      ALLOWED:CC_STAT, STM, D, C, MCDC, F, FC, SC, RO, RC_STAT, DZ, CA
                      The type of overview for which to set the comment. Possible values for code coverage goals: CC_STAT(Code
```

Coverage Statistics), STM(Statement), D(Decision/Branch), C(Condition), MCD(C/DC and MC/DC), F(Function), FC(Function Call). SC(Switch-Case), RO(Relational Operator), Possible values for robustness check goals are: RC_STAT(Robustness Check Statistics) ,DZ(Division by Zero), CA(Downcast). Can also specify multiple options.

```
comment* string The comment to set for the overview type.
}]
```

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

9. COVERAGE GENERATION

For a C-Code function, create stimuli vectors which cover the code function, or mark coverage properties that are unreachable.

9.1 POST /ep/coverage-generation

Execute coverage generation

Long running task Using the provided configuration, execute the coverage generation / stimuli vector generation.

REQUEST

REQUEST BODY - application/json

```
{
  isSubscopesGoalsConsidered  boolean  Whether or not goals from sub scopes should be considered. <br>Default is 'true'
  targetDefinitions [ {
    Array of object: The target definitions to use for this run. <br>If no target definitions are provided, and no PLL is given, the default target
    definitions are used
    label* string  The label of the target definition.
  } ]
  folderName                  string    Name of the folder to store Stimuli Vectors in. If the specified folder doesn't exists,
                                     it will be created with the given name. <br>If no folder is specified the default
                                     folder 'Default Stimuli Vectors' will be used.
  checkUnreachableProperties  boolean   Whether or not unreachable properties should be (re-)checked. <br>Default is
                                     'false'
  pllString                   string    PLL String for specific goals to be reached. Default is ':' which matches all goals.
                                     Use e.g. 'STM;D;CDC' to find stimuli vectors for statement, decision, and condition/
                                     decision coverage. Individual PLLs can be addressed by their specific label (e.g.
                                     'D:4:1'). Multiple PLLs can be concatenated using semicolon, e.g. 'D:4:1;C:2'. See
                                     the user guide for more information about the property location labels. <br>If this
                                     is null or empty, only the selected target definitions will be used. If in that case, the
                                     target definitions are empty, the default target definitions are used.

  engineSettings {
    The engine settings to use for this run.
    timeoutSeconds          integer     Global timeout (seconds) for the execution <br>Default is
                                     '-1' (unlimited)
    handlingRateThreshold   integer     After each scope is analyzed, the 'handled rate' of the entry scope
                                     (potentially including goals from subscopes) is checked against
                                     this threshold and the stimuli vector generation is stopped when it
                                     is reached. Allowed range are integers from [1, 100] (percent of
                                     handled goals). <br>Default: 100
    analyseSubScopesHierarchically  boolean  Enables / disables recursive analysis of subscopes. <br>Default is
                                     'true'

    engineAtg {
      The ATG engine. <br>Note: If neither ATG, nor CV engine is provided, both, ATG and CV are used together, using their default settings!
      name                  string       The name of the engine (heuristic). Currently, only 'ATG' is allowed.
                                     <br>Default is 'ATG'
      searchDepthSteps       integer     The search depth (number of SUT iterations) <br>Default is '20'
      executionMode           enum        ALLOWED:TOP_DOWN, BOTTOM_UP
                                     The search direction, bottom up or top down <br>Default is 'TOP_DOWN'
      mutateExistingVectors  boolean     Defines whether or not the Mutation Based ATG engine shall be used.
                                     <br>MATG requires existing vectors to produce new results. <br>Default
                                     is 'false'
      timeoutSecondsPerSubsystem integer  Timeout (seconds) per scope <br>Default is '300'
    }

    engineCv {
      The CV engine. <br>Note: If neither ATG, nor CV engine is provided, both, ATG and CV are used together, using their default settings!
      name                  string       The name of the engine (heuristic). Currently, only 'CV' is allowed.
                                     <br>Default is 'CV'
      searchDepthSteps       integer     The search depth (number of SUT iterations) <br>Default is '10'
      timeoutSecondsPerSubsystem integer  Timeout (seconds) per scope <br>Default is '-1' (unlimited)
      timeoutSecondsPerProperty integer  Timeout (seconds) per coverage property <br>Default is '60'
    }
  }
}
```

```

memoryLimitMb          integer  The maximum amount of system memory to use (MB) <br>Default is
                             '-1' (unlimited)
loopUnroll             integer  The number of internal loop unwindings for potentially unbounded loops
                             within each SUT iteration. <br>Default is '50'

coreEngines [{
  Array of object: The core engines to use <br>Note: If no core engine is provided, all core engines are used by default!
    name*  enum  ALLOWED:SMIBMC, VIS, AUTOFXP, CBMC, ISAT
              The name of the core engine.If no core engine is provided, all core engines are used by default!
}]
assumptionCheckEnabled  boolean  Whether or not core engines are allowed to explicitly checkthe
                             satisfiability of the selected assumptions. <br>Default is 'true'
searchFocus            enum      ALLOWED:BALANCED, REACHABLE, UNREACHABLE
                             The search focus of the core engines. <br>Default is 'BALANCED'
parallelExecutionMode   enum      ALLOWED:BALANCED, ENGINES, GOALS
                             The mode used for the parallel engine execution.If maximum number of
                             threads used is 1, the value of this parameter is not used (instead the
                             default value BALANCED will be used).

maximumNumberOfThreads  integer  The maximum number of threads available for parallel engine execution
                             for core engines. Valid values are between 1 and available number of
                             cores. It is possible to set this parameter to a value of -1, which will
                             compute the number of threads automatically as half of the available
                             number of cores. <br>Default is '1'

}
allowDenormalizedFloats  boolean  Whether or not the engine may produce denormalized floats.
                             <br>Default is 'true'
}
scopeUid*               string   The UID of the entry scope to use for this run.
assumptions [{
  Array of object: The environmental assumptions to use for this run.
    id*  string  The Assumption UID.
  }]
drivers [{
  Array of object: The drivers to use for this run.
    id*  string  The Driver source UID.
  }]
initializationVectorUID  string   The UID of the RequirementBasedTestCase or B2BStimuliVector which shall be
                             used to initialize the engine
}

```

RESPONSE

STATUS CODE - 202: Accepted

RESPONSE MODEL - application/json

```

{
  jobID  string  READ-ONLY
              The ID of a job.
}

```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

10. DOMAIN CHECKS

Handle domain checks.

10.1 POST /ep/domain-checks-ranges

Create domain checks ranges

Create the domain checks ranges for a scope and a list of signals. If the list of signals is not given, ranges for all signals of the scope will be created by default. The ranges can be created with some convenience functions applied (partitioned by a percent, with boundaries checks included or with invalid ranges checks included). Please note ALL domain checks ranges created via this service will overwrite any existing ranges for the given list of signals or for all signals (if no signal is specified).

REQUEST

REQUEST BODY - application/json

| | | |
|--------------------------|----------|--|
| { | | |
| scopeUid* | string | The scope for which to create the domain checks ranges. |
| signalUids | [string] | The list of signals for which to create the domain checks ranges. If no signal is provided, ranges for all signals from the scope are created by default. |
| applyBoundaryChecks | boolean | Used for applying the boundary checks when creating the range.Can only be used for applying boundary checks on a defined range, so it must be used only together with one of the other options (either apply invalid ranges checks or partition ranges). Default is 'false' |
| applyInvalidRangesChecks | boolean | Used for applying the invalid ranges checks when creating the range. Default is 'false' |
| percentage | integer | Percentage used for partitioning the range interval when creating the range. If no value is provided the domain check ranges will not be partitioned. |
| } | | |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - text/plain

string

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

10.2 POST /ep/domain-checks-export

Export domain check ranges

Export domain check ranges of the given scopeUid.

REQUEST

REQUEST BODY - application/json

| | | |
|-----------|--------|--|
| { | | |
| scopeUid* | string | The scopeUid for which to export/import domain check ranges. |
| filePath* | string | The file path used for exporting/importing domain check ranges. The directory path specified in the filePath must already exist. |

```
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET `/ep/progress?progress-id={progress-id}` using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

10.3 GET /ep/scopes/{scope-uid}/domain-check-details

Get domain check details

Get domain check details for a scope. Some filters can be applied.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The UID of the scope, for which to retrieve the domain check details. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|---|--|
| useCase | enum ALLOWED: B2B, RBT | The use case for which to retrieve the domain check details. Possible values: B2B, RBT. If not provided, details are shown for B2B. |
| signalNames | array of string | The names of the signals for which to retrieve the domain check details. If not provided, the details for all signals are shown. |
| signalKinds | array of string ALLOWED: INPUT, OUTPUT, LOCAL, PARAMETER | The kinds of the signals for which to retrieve the domain check details. Possible values: INPUT, OUTPUT, LOCAL, PARAMETER. If not provided, the details will be shown for all kinds. |
| goalStates | array of string ALLOWED: COVERED, UNREACHABLE, UNKNOWN, ERROR, NOT_DEFINED | The status filter for domain check details. Possible values: COVERED, UNKNOWN, UNREACHABLE, ERROR. If not provided, the details will be shown for all status. |

| NAME | TYPE | DESCRIPTION |
|-----------|--|---|
| goalTypes | array of string ALLOWED: VALID, INVALID | The goal type filter for domain check details. Possible values: VALID, INVALID. If not provided, the details will be shown for all types. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  name          string  READ-ONLY
                  The name of the signal for which domain check goals where created.
  kind          enum    READ-ONLY
                  ALLOWED:INPUT, OUTPUT, LOCAL, PARAMETER
                  The kind of the signal for which domain check goals where created.
  pll           string  PLL string of the domain check goal.
  range         string  The range of the domain check goal.
  goalType      enum    ALLOWED:VALID, INVALID
                  The type of the domain check goal.
  goalStatus    enum    ALLOWED:COVERED, UNREACHABLE, UNKNOWN, ERROR, NOT_DEFINED
                  The status of the domain check goal.
  comment       string  The comment of the domain check goal.
  coveringVectors [string] List of string vector names that cover the property.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

10.4 GET /ep/scopes/{scope-uid}/domain-checks-results

Get domain checks results

Get the domain checks results for a scope. Using the use case option will display the results for SVs and RBTest Cases if B2B is used or only for RBTest Cases if RBT option is used. Also, the results can be requested either only for the invalid goal types and for the valid ones, or for all goal types.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|--|
| *scope-uid | string | The UID of the scope for which to get the domain checks results. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------|--|---|
| useCase | enum ALLOWED: B2B, RBT | The use case for which to retrieve the domain check results. Possible values: B2B, RBT.Can be empty, in which case the results are shown for B2B use case. |
| goalTypes | array of string ALLOWED: VALID, INVALID | The goal type for which to retrieve the domain check results. Possible values: VALID, INVALID.Can be empty, in which case the results are shown for all goal types. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  totalCountValid      string  READ-ONLY
                        The total number of valid range goals.
  coveredCountValid    string  READ-ONLY
                        The number of covered valid range goals.
  unreachableCountValid string  READ-ONLY
                        The number of unreachable valid range goals.
  errorCountValid      string  READ-ONLY
                        The number of erroneous valid range goals.
  handledCountValid    string  READ-ONLY
                        The number of handled valid range goals.
  unhandledCountValid  string  READ-ONLY
                        The number of unhandled valid range goals.
  coveredPercValid     string  READ-ONLY
                        The covered percentage for valid range goals.
  unreachablePercValid string  READ-ONLY
                        The unreachable percentage for valid range goals.
  errorPercValid       string  READ-ONLY
                        The error percentage for valid range goals.
  handledPercValid     string  READ-ONLY
                        The handled percentage for valid range goals.
  unhandledPercValid   string  READ-ONLY
                        The unhandled percentage for valid range goals.
  totalCountInvalid    string  READ-ONLY
                        The total number of invalid range goals.
  coveredCountInvalid  string  READ-ONLY
                        The number of covered invalid range goals.
  unreachableCountInvalid string  READ-ONLY
                        The number of unreachable invalid range goals.
  errorCountInvalid    string  READ-ONLY
                        The number of erroneous invalid range goals.
  handledCountInvalid  string  READ-ONLY
                        The number of handled invalid range goals.
  unhandledCountInvalid string  READ-ONLY
                        The number of unhandled invalid range goals.
  coveredPercInvalid   string  READ-ONLY
                        The covered percentage for invalid range goals.
  unreachablePercInvalid string  READ-ONLY
                        The unreachable percentage for invalid range goals.
  errorPercInvalid     string  READ-ONLY
                        The error percentage for invalid range goals.
  handledPercInvalid   string  READ-ONLY
                        The handled percentage for invalid range goals.
  unhandledPercInvalid string  READ-ONLY
                        The unhandled percentage for invalid range goals.
}
```

```
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

10.5 POST /ep/domain-checks

Import domain check ranges

Import domain check ranges on the given scopeUid.

REQUEST

REQUEST BODY - application/json

```
{
  scopeUid* string The scopeUid for which to export/import domain check ranges.
  filePath* string The file path used for exporting/importing domain check ranges. The directory path specified in the filePath must
                  already exist.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
          The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

10.6 POST /ep/domain-check-comments

Set domain check comments

Set the comments for the domain check ranges specified by the PLL of their corresponding domain check goal. To remove a comment for a given domain check goal, provide an empty string as a comment.

REQUEST

REQUEST BODY - application/json

```
[{
```

Array of object:

```
  pll*      string  The PLL of the domain check goal for which to set the comment.
  comment*  string  The comment to set on the domain check goal with the given PLL.
}]
```

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - text/plain

string

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

11. EXECUTION CONFIGS

11.1 GET /ep/execution-configs

Get all execution configs

Get all execution configs available in the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  execConfigNames [string] List of the available execution kinds
}
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

12. EXECUTION RECORDS

Handle execution records.

12.1 GET /ep/execution-records/{execution-record-uid}

Get an execution record

Get the requested execution record by UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------------------|--------|----------------------|
| *execution-record-uid | string | Execution record UID |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid                string  READ-ONLY
                        The unique identifier (UID) of this object.
    executionConfig*   string
    name*              string  The execution config name
                        The execution record name
    status              enum    ALLOWED:OK, WARNING, ERROR
                        The status of execution record.Possible options: OK, WARNING, or ERROR.
    folderName*        string  The folder name on which this execution record can be found.
    length*             integer The length of execution record source
    scopeName*          string  The scope name of execution record
    sourceName*         string  The name of execution record source
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

12.2 DELETE /ep/execution-records/{execution-record-uid}

Delete an execution record

Deletes the specified execution record.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------|------|-------------|
|------|------|-------------|

| NAME | TYPE | DESCRIPTION |
|-----------------------|--------|--|
| *execution-record-uid | string | The UID of the execution record to be deleted. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 406: Not acceptable

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

12.3 POST /ep/execution-records-export

Export execution records

LONG RUNNING TASK Export single or multiple execution record(s) by providing the list of the execution records which will be exported, the export directory, the export format and a list of additional options for export.

REQUEST

REQUEST BODY - application/json

```
{
  UIDs*           [string] List with the UIDs of the elements which will be exported
  exportDirectory* string   Directory where to export the elements
  exportFormat    enum     ALLOWED:MDF, EXCEL
                           The format of the exported execution records. (Default value: "MDF").
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

12.4 GET /ep/execution-records

Get all execution records

Get all execution records available in the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid string READ-ONLY
              The unique identifier (UID) of this object.
    executionConfig* string
    name* string The execution config name
    status enum   The execution record name
              ALLOWED:OK, WARNING, ERROR
              The status of execution record.Possible options: OK, WARNING, or ERROR.
    folderName* string
              The folder name on which this execution record can be found.
    length* integer
              The length of execution record source
    scopeName* string
              The scope name of execution record
    sourceName* string
              The name of execution record source
}]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

12.5 POST /ep/execution-records

Import execution records

Import multiple execution records by providing the path for each file.

REQUEST

REQUEST BODY - application/json

| | | |
|-----------------------|----------|--|
| paths* | [string] | The path to all execution record files you'd like to import. Supported formats are MDF, MF4 and CSV. |
| kind* | string | The simulation kind that was used for creating the execution records from the given files. Possible values: TL MIL, SL MIL, SIL, PIL or any external simulation kind. If the user defined folder option is not specified, the simulation kind will define the default folder where the execution records will be imported. |
| folderName | string | User defined execution records folder name. If used, folderUID can not be used at the same time. |
| folderUID | string | Existing user defined folder uid to import records. If used, folderName can not be used at the same time. |
| referenceExternalFile | boolean | Relevant only for MF4 and CSV import format. Whether to only reference the external file rather than importing the execution record in the profile. This would be recommended for very big execution records.Default is 'false'. |
| csvDelimiter | enum | ALLOWED:SEMICOLON, COMMA, COLON, PIPE Relevant only for CSV import format. It can have one of the following values: "SEMICOLON", "COMMA", "COLON", "PIPE". Default value is "SEMICOLON". |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.](#get-/ep/progress)

RESPONSE MODEL - application/json

| | | |
|-------|--------|------------------|
| jobID | string | READ-ONLY |
| | | The ID of a job. |

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

12.6 GET /ep/folders/{folder-uid}/execution-records

Get all execution records for a folder

Get all the execution records for a given folder UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The folder UID from which to retrieve all execution records. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid                string  READ-ONLY
                        The unique identifier (UID) of this object.
    executionConfig*   string
    name*              string  The execution config name
                        The execution record name
    status              enum    ALLOWED:OK, WARNING, ERROR
                        The status of execution record.Possible options: OK, WARNING, or ERROR.
    folderName*        string
    length*            integer  The folder name on which this execution record can be found.
                        The length of execution record source
    scopeName*         string  The scope name of execution record
    sourceName*        string  The scope name of execution record
                        The name of execution record source
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

12.7 PUT /ep/folders/{folder-uid}/execution-records

Move a list of execution records to a folder

Moves the list of execution records to the requested user-defined execution record folder.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The UID of user-defined execution record folder. |

REQUEST BODY - application/json

```
{
  UUIDs* [string]  UUIDs of execution records to be moved.
}
```

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid                string  READ-ONLY
                        The unique identifier (UID) of this object.
    executionConfig*   string
    name*              string  The execution config name
                        The execution record name
}]
```

```

    status          enum    ALLOWED:OK, WARNING, ERROR
                                The status of execution record.Possible options: OK, WARNING, or ERROR.
    folderName*     string
    length*         integer  The length of execution record source
    scopeName*      string   The scope name of execution record
    sourceName*     string   The name of execution record source
  }
}

```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

```
string
```

12.8 GET /ep/scopes/{scope-uid}/execution-records

Get all execution records for a scope

Get all the execution records for the given scope UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The scope UID from which to retrieve all execution records. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```

[ {
  Array of object:
    uid          string    READ-ONLY
                                The unique identifier (UID) of this object.
    executionConfig* string
    name*        string    The execution record name
    status       enum      ALLOWED:OK, WARNING, ERROR
                                The status of execution record.Possible options: OK, WARNING, or ERROR.
    folderName*  string
    length*      integer   The length of execution record source
    scopeName*   string    The scope name of execution record
    sourceName*  string    The name of execution record source
  }
]

```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

13. FOLDERS

Handle folders.

13.1 GET /ep/folders

Get a list of folders

Get a list of folders by name and/or kind.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------|---|--|
| name | string | Enter the name of the folder you would like to search for. If null, then all folders will be returned. |
| kind | enum ALLOWED: RB_TEST_CASE, EXECUTION_RECORD, STIMULI_VECTOR | Enter the folder kind. If null, then all folder kinds will be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {  
  Array of object:  
    uid          string  READ-ONLY  
                        The unique identifier (UID) of this object.  
    name*        string  The name of the folder.  
    kind*        string  The folder kind.  
    isDefault*   boolean Set to 'true' if it is a default folder.  
  } ]
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

13.2 POST /ep/folders

Create a folder

Add a folder by providing a folder kind and optionally a folder name. Note that a new UID will be assigned.

REQUEST

REQUEST BODY - application/json

```
{
  folderKind*  string  The folder kind. Possible: "RB_TEST_CASE", "EXECUTION_RECORD", "STIMULI_VECTOR"
  folderName   string  The folder name. This parameter is optional
}
```

RESPONSE

STATUS CODE - 201: Created

RESPONSE MODEL - application/json

```
{
  uid          string  READ-ONLY
                  The unique identifier (UID) of this object.
  name*        string  The name of the folder.
  kind*        string  The folder kind.
  isDefault*   boolean Set to 'true' if it is a default folder.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

13.3 DELETE /ep/folders/{folder-uid}

Delete a folder

Delete a folder by providing its UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|---|
| *folder-uid | string | Enter the UID of the folder you would like to delete. |

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

14. FORMAL SPECIFICATION REPORTS

Formal Specification Reports

14.1 GET /ep/formal-specification-reports

Get all reports

Get all formal specification reports from the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {  
  Array of object:  
    uid          string  READ-ONLY  
                        The unique identifier (UID) of this object.  
    reportName   string  Name of the report.  
    reportType   string  Type of the report.  
  } ]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

14.2 POST /ep/formal-specification-reports

Create a formal specification report

Create a formal specification report on a list of formal specification UID's.

REQUEST

REQUEST BODY - application/json

```
{  
  UUIDs* [string] List with unique identifiers of the objects.  
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.](#get-/ep/progress)

RESPONSE MODEL - application/json

```
{  
  jobID string  READ-ONLY  
          The ID of a job.  
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

15. FORMAL SPECIFICATIONS

Handle Formal Specifications.

15.1 GET /ep/environmental-assumptions

Get all environmental assumptions

Get all environmental assumptions present on active profile, or from the specified scope-uid.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------|--------|---|
| scope-uid | string | The UID of scope from which to get the environmental assumptions. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid          string  READ-ONLY
                    The unique identifier (UID) of this object.
    name*        string
    description*  string  The name of the environmental assumption.
    scopeUID*    string  The description of the environmental assumption.
    draft        string  The unique identifier (UID) of the scope this object belongs to.
    errors       [string] States whether or not the FormalRequirement is in Draft-Mode.
                    List of errors
}]
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

15.2 GET /ep/formal-requirements

Get all formal requirements

Get all formal requirements from the profile, or from the specified scope-uid.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------|--------|---|
| scope-uid | string | The UID of scope from which to get the formal requirements. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid          string    READ-ONLY
                        The unique identifier (UID) of this object.
    name*         string    The name of the formal requirement.
    description*  string    The description of the formal requirement.
    scopeUID*     string    The unique identifier (UID) of the scope this object belongs to.
    draft         string    States whether or not the FormalRequirement is in Draft-Mode.
    errors        [string]  List of errors
}]
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

15.3 GET /ep/formal-requirements/{formal-requirement-uid}/environmental-assumptions

Get all environmental assumptions from a formal requirement

Use this command to retrieve the environmental assumptions from a formal requirement.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------------------|--------|---|
| *formal-requirement-uid | string | The uid of the formal requirement for which all environmental assumptions should be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid          string    READ-ONLY
                        The unique identifier (UID) of this object.
    name*         string    The name of the environmental assumption.
    description*  string    The description of the environmental assumption.
    scopeUID*     string    The unique identifier (UID) of the scope this object belongs to.
    draft         string    States whether or not the FormalRequirement is in Draft-Mode.
    errors        [string]  List of errors
}]
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

15.4 POST /ep/specifications-export

Export a SPEC file

Long running task Exports the given formal specifications belonging to the same scope to the specified SPEC file.

REQUEST

REQUEST BODY - application/json

```
{
  specFile*           string  The file name of the target SPEC file. Should have .spec extension.
  archUid             string  The architecture UID to define the interface names. If specified, the SPEC file will use
                              the interface and expression names based on the interfaces and signals defined in the
                              given architecture.If not specified, the first imported architecture is used for the name
                              space.
  formalSpecificationUids* [string] A list of uids of formal requirements or environmental assumptions to export. Note:
                              The formal requirements / environmental assumptions must reside on the same scope!
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

15.5 POST /ep/specifications-import

Import a SPEC file

Imports formal specifications from the specified SPEC file. **Long running task** Specify artifact existing policy, one of EXTEND_NAME, OVERWRITE, or SKIP. By default it will be used 'EXTEND_NAME'.

REQUEST

REQUEST BODY - application/json

```
{
  specPath*   string  The path of the given SPEC file. Should have .spec extension.
  scopeId     string  The scopeld to use, when scope definition in SPEC file is invalid. This can happed for two reasons, the first is
                      that in the SPEC file, the component(scope) name is invalid and can not be found in the opened profile, or when
                      the given component(scope) name in the SPEC file is not unique within current profile.e.g. a TL architecture
                      scope name is unique to the one in the generated CCode.

  isDraft     boolean The draft status setting for the formal requirements that will be imported. By default its value is false.
  optionParam enum    ALLOWED:EXTEND_NAME, OVERWRITE, SKIP
                      The options of importing a SPEC file, when the artifacts already exists. If no value is provided, 'EXTEND_NAME'
                      is used.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.](#get-/ep/progress)

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

16. FORMAL TEST EXECUTION

Execute Formal Test.

16.1 POST /ep/execute-formal-test

Execute formal tests

Long running task Execute formal test for all not yet existing or outdated results.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

17. FORMAL TEST REPORTS

Create and get formal test reports.

17.1 POST /ep/formal-requirements/{formal-requirement-uid}/formal-test-reports

Create a report on a formal requirement

Create a formal test report on a formal requirement for the given execution configurations.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------------------|--------|---|
| *formal-requirement-uid | string | The formal requirement UID for which the formal test report is created. |

REQUEST BODY - application/json

```
{
  executionConfigNames* [string]
}
```

The comma separated list of execution configurations for which the Formal Test report shall be created. It can include values like "TL MIL", "SIL" etc. Please keep the specified format when you want to introduce a value.

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
  The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

17.2 POST /ep/formal-requirements/formal-test-reports

Create a report on a list of formal requirements

Create a formal test report on on a list of formal requirements for the given execution configurations.

REQUEST

REQUEST BODY - application/json

```
{
  UUIDs* [string]
  executionConfigInfo {
    executionConfigNames* [string]
  }
}
```

List with unique identifiers of the objects.

The comma separated list of execution configurations for which the Formal Test report shall be created. It can include values like "TL MIL", "SIL" etc. Please keep the specified format when you want to introduce a value.

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
}
```

The ID of a job.

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string](#get-/ep/progress)

17.3 POST /ep/requirements-sources/{requirements-source-uid}/formal-test-reports

Create a report on a requirements source

Create a formal test report on a requirements source for the given execution configurations.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|--------------------------|--------|--|
| *requirements-source-uid | string | The requirements source UID for which the formal test report is created. |

REQUEST BODY - application/json

104 of 201


```
{
  executionConfigNames* [string] The comma separated list of execution configurations for which the Formal Test report shall
                             be created. It can include values like "TL MIL", "SIL" etc. Please keep the specified format
                             when you want to introduce a value.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

17.4 POST /ep/requirements-sources/formal-test-reports

Create a report on a list of requirements sources

Create a formal test report on on a list of requirements sources for the given execution configurations.

REQUEST

REQUEST BODY - application/json

```
{
  UIDs* [string] List with unique identifiers of the objects.
  executionConfigInfo {
    executionConfigNames* [string] The comma separated list of execution configurations for which the Formal Test report
                                   shall be created. It can include values like "TL MIL", "SIL" etc. Please keep the specified
                                   format when you want to introduce a value.
  }
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

17.5 POST /ep/scopes/{scope-uid}/formal-test-reports

Create a report on a scope

Create a formal test report on a scope for the given execution configurations.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|--|
| *scope-uid | string | The scope UID for which the formal test report is created. |

REQUEST BODY - application/json

```
{
  executionConfigNames* [string] The comma separated list of execution configurations for which the Formal Test report shall
                             be created. It can include values like "TL MIL", "SIL" etc. Please keep the specified format
                             when you want to introduce a value.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.](#get-/ep/progress)

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

17.6 POST /ep/scopes/formal-test-reports

Create a report for a list of scopes

Create a formal test report on a list of scopes for the given execution configurations.

REQUEST

REQUEST BODY - application/json

```
{
  UUIDs* [string] List with unique identifiers of the objects.
  executionConfigInfo {
    executionConfigNames* [string] The comma separated list of execution configurations for which the Formal Test report
    shall be created. It can include values like "TL MIL", "SIL" etc. Please keep the specified
    format when you want to introduce a value.
  }
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
  The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

17.7 GET /ep/formal-test-reports

Get all reports

Retrieve all the Formal Test reports from the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  uid          string READ-ONLY
                The unique identifier (UID) of this object.
  reportName   string Name of the report.
  reportType   string Type of the report.
}]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

18. FORMAL VERIFICATION REPORTS

Create Formal Verification reports.

18.1 POST /ep/scopes/{scope-uid}/formal-verification-reports

Create a formal verification report on given scopeUid.

Create a formal verification report on given scope-uid which is found on this active profile. If multiple architectures for report creation are preset, the architecture-uid query parameter must be specified.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|-----------------------|
| *scope-uid | string | The UID of the scope. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------------|--------|---|
| architecture-uid | string | The UID of the architecture on which the report to be created. If there are multiple valid architectures, but no architecture is specified, the C-Code architecture is used as a default. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

18.2 GET /ep/formal-verification-reports

Get all reports

Get all formal verification reports from the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {  
  Array of object:  
    uid          string  READ-ONLY  
                        The unique identifier (UID) of this object.  
    reportName   string  Name of the report.  
    reportType   string  Type of the report.  
  } ]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

19. INPUT RESTRICTIONS

19.1 POST /ep/input-restrictions-export

Export input restrictions

Export input restrictions to a file

REQUEST

REQUEST BODY - application/json

```
{
  filePath* string The file containing input restrictions.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

19.2 POST /ep/input-restrictions-import

Import input restrictions

Import input restrictions from a file

REQUEST

REQUEST BODY - application/json

```
{
  filePath* string The file containing input restrictions.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#)

href='#get-/ep/progress'>Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
    The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

20. INTERFACE REPORTS

Handle interface reports.

20.1 POST /ep/scopes/{scope-uid}/interface-reports

Create a report on a scope

Create an interface report on given scope. The interface report will use the interface of the architecture of the provided scope.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|--|
| *scope-uid | string | The scope on which the interface report should be created. The interface report will use the interface of the architecture of the provide scope. |

RESPONSE

STATUS CODE - 201: Created

RESPONSE MODEL - application/json

```
{
  uid          string READ-ONLY
                The unique identifier (UID) of this object.
  reportName   string Name of the report.
  reportType   string Type of the report.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

20.2 GET /ep/interface-reports

Get all reports

Retrieve all interface reports from the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid          string  READ-ONLY
                        The unique identifier (UID) of this object.
    reportName   string  Name of the report.
    reportType   string  Type of the report.
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

21. MATLAB SCRIPT EXECUTION

Execute a MATLAB script.

21.1 POST /ep/execute-long-matlab-script

Execute long-running MATLAB script

Execute a long-running MATLAB script using the given parameters. Should be used when the time it takes for the script to end is longer than the request timeout of your REST client. Otherwise, for ease of use, the **Execute a short-running MATLAB script** method should be utilized.

REQUEST

REQUEST BODY - application/json

```
{
  scriptName*           string           MATLAB script name.
  outArgs*              integer          Number of output arguments to return. Exception will be thrown
                                     if the given m-script returns less arguments.
  inArgs* [ {
    Array of object: Parameters of the MATLAB script. The order in the list can be important, dependent of the executed m-script. The parameters will
    be received in the MATLAB script as follows: primitive types will be converted into their MATLAB equivalents, JSON arrays will be converted into
    cell arrays, JSON objects will be converted into MATLAB structures.
  } ]
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.](#get-/ep/progress)

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                                     The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

21.2 POST /ep/execute-short-matlab-script

Execute short-running MATLAB script

Execute a short-running MATLAB script using the given parameters. If the time it takes for the script to end is longer than the request timeout of your REST client, this request may fail. In this scenario the **Execute a long-running MATLAB script** method should be used.

REQUEST

REQUEST BODY - application/json

```
{
```

| | | |
|--|---------|--|
| scriptName* | string | MATLAB script name. |
| outArgs* | integer | Number of output arguments to return. Exception will be thrown if the given m-script returns less arguments. |
| inArgs* [{ | | |
| Array of object: Parameters of the MATLAB script. The order in the list can be important, dependent of the executed m-script. The parameters will be received in the MATLAB script as follows: primitive types will be converted into their MATLAB equivalents, JSON arrays will be converted into cell arrays, JSON objects will be converted into MATLAB structures. | | |
| }] | | |
| } | | |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  outArgs [{
    Array of object: Output objects of the MATLAB script. The objects returned from the script must be primitive types, cell arrays or structures.
  }]
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

22. MESSAGES

Handle messages and message markers.

22.1 POST /ep/message-markers

Create a message marker

Use this command to create a new message marker at the current time. The response will contain the created message marker time stamp as java Timestamp

REQUEST

No request parameters

RESPONSE

STATUS CODE - 201: Created

RESPONSE MODEL - application/json

```
{
  date string READ-ONLY
    The date when the marker was set.
}
```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

22.2 GET /ep/message-markers/{marker-date}/messages

Get a list of messages from a message marker

Search for messages created after a given message marker.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|--------------|--------|--|
| *marker-date | string | The message marker after which the messages should be queried from the Database. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|---|--|
| search-string | string | Enter the beginning of the messages you would like to search for. If null, then all messages will be returned. |
| severity | enum ALLOWED: INFO, WARNING, ERROR, CRITICAL | Choose any severity you would like to search for. If null, then all severities will be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid      string  READ-ONLY
                  The unique identifier (UID) of this object.
    date      string  READ-ONLY
                  The creation-date of the message.
    message*  string  The message itself.
    hint      string  An additional hint.
    severity* enum    ALLOWED:INFO, WARNING, ERROR, CRITICAL
                  The severity of the message.
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

22.3 GET /ep/messages

Get a list of messages

Search for past messages up until a certain amount you can set yourself.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|---|--|
| search-string | string | Enter the beginning of the messages you would like to search for. If null, then all messages will be returned. Furthermore, you may use the following wildcards: '*' for any string, '?' for any single character. |
| severity | enum ALLOWED: INFO, WARNING, ERROR, CRITICAL | Choose any severity you would like to search for. If null, then all severities will be returned. |
| max-messages | int32 | The maximum number of messages returned. Cannot be > 1000. If > 1000, negative, or null, at most 1000 messages will be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid      string  READ-ONLY
                  The unique identifier (UID) of this object.
    date      string  READ-ONLY
                  The creation-date of the message.
    message*  string  The message itself.
    hint      string  An additional hint.
    severity* enum    ALLOWED:INFO, WARNING, ERROR, CRITICAL
```

The severity of the message.

```
}]
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

22.4 POST /ep/messages

Create a message

Add a message by providing a Message. Note that a new UID will be assigned.

REQUEST

REQUEST BODY - application/json

```
{
  uid          string  READ-ONLY
                  The unique identifier (UID) of this object.
  date         string  READ-ONLY
                  The creation-date of the message.
  message*    string  The message itself.
  hint        string  An additional hint.
  severity*   enum    ALLOWED:INFO, WARNING, ERROR, CRITICAL
                  The severity of the message.
}
```

RESPONSE

STATUS CODE - 201: Created

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

22.5 DELETE /ep/messages

Delete a list of messages

Search for past messages up until a certain amount you can set yourself and delete them.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|---|
| search-string | string | Enter the beginning of the messages you would like to search for. If null, then all messages will be deleted. |

| NAME | TYPE | DESCRIPTION |
|--------------|---|---|
| severity | enum ALLOWED: INFO, WARNING, ERROR, CRITICAL | Choose any severity you would like to search for. If null, then all severities will be deleted. |
| max-messages | int32 | The max number of messages deleted. If negative or null, all messages will be deleted. |

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

22.6 GET /ep/messages/{message-uid}

Get a message

Get the message with the provided UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|--------------|--------|--|
| *message-uid | string | The UID of the message to be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  uid          string  READ-ONLY
                  The unique identifier (UID) of this object.
  date         string  READ-ONLY
                  The creation-date of the message.
  message*    string
  hint        string  An additional hint.
  severity*   enum    ALLOWED:INFO, WARNING, ERROR, CRITICAL
                  The severity of the message.
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

22.7 DELETE /ep/messages/{message-uid}

Delete a message

Delete a message by providing its UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|--------------|--------|--|
| *message-uid | string | Enter the UID of the message you would like to delete. |

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

22.8 POST /ep/messages/message-report

Export messages

Export all messages to the specified report file (in HTML format).

If a [Message Marker](#post-/ep/message-markers) is provided, all messages starting from the marker will be exported.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *file-name | string | The path and file name of the message report file to create. Note: An existing file will be overwritten! |
| marker-date | string | If specified, only messages that were posted after this Message Marker was created will be exported. |

RESPONSE

STATUS CODE - 201: Exported Successfully. Returns exported report location.

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

23. MODEL COVERAGE REPORTS

Creates RBT or B2B model coverage reports.

23.1 POST /ep/folders/{folder-uid}/model-coverage-reports

Create a report for a folder

Long running task Create RBT or B2B model coverage report for given folder.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|---|
| *folder-uid | string | The folder UID for which to create the model coverage report. |

REQUEST BODY - application/json

| | | | |
|----------------------|---------|------------------|---|
| { | | | |
| type* | enum | ALLOWED:RBT, B2B | |
| | | | Specifies the testing use-case for which the model coverage report should be created. Must be 'B2B' or 'RBT' for Back-to-back testing or Requirement based test, respectively. |
| simulationKind* | string | | Specifies the simulation mode: 'SL MIL' or 'TL MIL' |
| useShortCircuitLogic | boolean | | Specifies if short circuit logic should be used for Simulink blocks. The paramter is optional. If not provided, the current setting from EP is used. |
| } | | | |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

| | | |
|-------|--------|------------------|
| { | | |
| jobID | string | READ-ONLY |
| | | The ID of a job. |
| } | | |

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

23.2 POST /ep/folders/model-coverage-reports

Create a report for a list of folders

Long running task Create RBT or B2B model coverage report for a list of folders. In the RBT use-case, RBTTestCases from the folders will be used to generate the report. In the B2B use-case, RBTTestCases and Stimuli-Vectors from the folders will be used to generate the report.

REQUEST

REQUEST BODY - application/json

```
{
  type*           enum      ALLOWED:RBT, B2B
                    Specifies the testing use-case for which the model coverage report should be
                    created. Must be 'B2B' or 'RBT' for Back-to-back testing or Requirement based test,
                    respectively.

  simulationKind* string     Specifies the simulation mode: 'SL MIL' or 'TL MIL'
  folderUIDs*     [string]   The comma separated list of folder UIDs for which the model coverage report shall be
                    created.

  useShortCircuitLogic boolean Specifies if short circuit logic should be used for Simulink blocks. The paramter is
                    optional. If not provided, the current setting from EP is used.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                    The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

23.3 POST /ep/scopes/{scope-uid}/model-coverage-reports

Create a report for a scope

Long running task Create RBT or B2B model coverage report on given scope.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|--|
| *scope-uid | string | The scope UID for which to create the model coverage report. |

REQUEST BODY - application/json

| | | | |
|----------------------|---------|--|---|
| { | | | |
| type* | enum | ALLOWED:RBT, B2B | |
| | | | Specifies the testing use-case for which the model coverage report should be created. Must be 'B2B' or 'RBT' for Back-to-back testing or Requirement based test, respectively. |
| simulationKind* | string | Specifies the simulation mode: 'SL MIL' or 'TL MIL' | |
| useShortCircuitLogic | boolean | Specifies if short circuit logic should be used for Simulink blocks. The paramter is optional. If not provided, the current setting from EP is used. | |
| } | | | |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

| | | |
|-------|--------|-------------------------------|
| { | | |
| jobID | string | READ-ONLY The ID of a job. |
| } | | |

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

23.4 GET /ep/model-coverage-reports

Get a list of reports

Retrieve all model coverage reports of the specified testing use-case from the profile.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|---------------------------|--------------------------------------|
| coverage-type | enum ALLOWED: RBT, B2B | The model coverage testing use-case. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {  
  Array of object:  
    uid          string  READ-ONLY  
                        The unique identifier (UID) of this object.  
    reportName   string  Name of the report.  
    reportType   string  Type of the report.  
  } ]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

24. PREFERENCES

Set and retrieve preferences.

24.1 GET /ep/preferences/{preference-name}

Get a preference

Get the preference with a given name. If the retrieved value is empty, the preference might have its default value.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------------|--------|---|
| *preference-name | string | Enter the name of the preference that you want retrieved. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  preferenceName*  string  The name of the preference.
  preferenceValue* string  The value of the preference.
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

```
string
```

24.2 PUT /ep/preferences

Set a list of preferences

Set new values for a list of given preferences. The preference name and new value must be provided for each of them.

REQUEST

REQUEST BODY - application/json

```
[{
  preferenceName*  string  The name of the preference.
  preferenceValue* string  The value of the preference.
}]
```

RESPONSE

STATUS CODE - 200: Preferences set

RESPONSE MODEL - application/json

```
{  
  messages [string]  
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

25. PROFILES

Create and handle EP Profiles.

25.1 GET /ep/profiles

Get the active profile

Use this command to get the currently active profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  uid    string    READ-ONLY
           The unique identifier (UID) of this object.
  metadata* {
    The metadata containing all relevant info about the profile.
  }
  profilePath {
    path string The location where the profile is stored.
  }
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

25.2 PUT /ep/profiles

Save the profile

Use this command to save your active profile at a given location. Keep in mind to use only legal profile paths.

REQUEST

REQUEST BODY - application/json

```
{
  path string The location where the profile is stored.
}
```

RESPONSE

STATUS CODE - 201: Created

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

25.3 POST /ep/profiles

Create a profile

Use this command to create a new empty profile. It won't contain a path, since it's not stored anywhere yet.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------------------|---------|---|
| discardCurrentProfile | boolean | If 'true' the current profile is discarded and a new profile will be created. Otherwise a new profile will only be created when the current profile is not in a dirty state. Default is 'false' |

RESPONSE

STATUS CODE - 201: Created

RESPONSE MODEL - application/json

```
{
  uid    string    READ-ONLY
           The unique identifier (UID) of this object.
  metadata* {
    The metadata containing all relevant info about the profile.
  }
  profilePath {
    path    string  The location where the profile is stored.
  }
}
```

STATUS CODE - 428: Precondition Required

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

25.4 DELETE /ep/profiles

Discard a profile

Use this command to discard a profile, even if it is dirty. Changes will not be saved!

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

25.5 GET /ep/profiles/{profile-path}

Open a profile

Use this command to open an existing profile. Specify the path to the profile with a name of your choice. Keep in mind to only use legal profile paths of already existing profiles.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|-----------------------------------|
| *profile-path | string | The path to the existing profile. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------------------|---------|--|
| discardCurrentProfile | boolean | If 'true' the current profile is discarded and a new profile will be created. Otherwise a new profile will only be created when the current profile is not in a dirty state.Default is 'false' |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  uid    string    READ-ONLY
              The unique identifier (UID) of this object.
  metadata* {
    The metadata containing all relevant info about the profile.
  }
  profilePath {
    path string    The location where the profile is stored.
  }
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 428: Precondition Required

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

26. PROGRESS

Get the current status of long-running operations.

26.1 GET /ep/progress

Get the status of a long running operation

Get the status of a long running operation. If the operation is on-going, the current progress will be returned. If the operation is complete, the resulted object will be returned if there is one. An error will be returned if it occurred during the long-running operation.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| progress-id | string | The progress id. Can be retrieved by starting a long-running operation. If not specified then last long running operation result will be returned. |

RESPONSE

STATUS CODE - 200: Operation is complete. No resulting object is returned.

RESPONSE MODEL - application/json

```
{
  message string
  progress integer
  result {
  }
}
```

STATUS CODE - 201: Operation is complete. Resulting object is returned as JSON.

RESPONSE MODEL - application/json

```
{
  message string
  progress integer
  result {
  }
}
```

STATUS CODE - 202: Operation is currently in progress

RESPONSE MODEL - application/json

```
{
  message string
  progress integer
  result {
  }
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

`string`

STATUS CODE - 500: Internal server error

27. PROJECT REPORTS

Create and retrieve project reports.

27.1 POST /ep/scopes/{scope-uid}/project-report

Create a project report

Create a project report.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The UID of the scope for which the report shall be created. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|---|
| template-name | string | The name of the template to use for report creation. This can be either the full path and filename of a template file to use, or the name of a template that was provided to EP by setting the template folder via the preference REPORT_TEMPLATE_FOLDER If no template is given, all available data will be included. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
    The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

27.2 GET /ep/project-reports

Get all project reports

Retrieve all project reports from the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid          string  READ-ONLY
                        The unique identifier (UID) of this object.
    reportName    string  Name of the report.
    reportType    string  Type of the report.
}]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

28. PROOFS

Create, verify and execute proofs.

28.1 GET /ep/proofs/{proofUID}

Get a proof based on given proofUID.

Get a proof based on given proofUID found on the active profile.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------|--------|-----------------------|
| *proofUID | string | The UID of the proof. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

| | | | |
|--|---------|--|--|
| { | | | |
| uid | string | READ-ONLY | The unique identifier (UID) of this object. |
| name | string | | Name of the proof. |
| description | string | | Description of the proof. |
| formalRequirementName | string | | Name of the formal requirement used by this proof. |
| proofSettings { | | | |
| The proof settings object. If not provided, default settings will be used. | | | |
| timeoutSeconds | integer | | The timeout in seconds, i.e. the limit on how long this proof execution may run. Non-positive numbers (≤ 0) are interpreted as infinity (i.e. no timeout has been specified). |
| memoryLimit | integer | | The memory limit in MB. Valid values are ≤ 0 (to denote infinity) or any positive integer ≥ 500 to set a positive memory limit. |
| numberOfThreads | integer | | The maximum number of parallel threads for the proof execution. Valid values are between 1 and available number of cores. It is possible to set this parameter to a value of -1, which will compute the number of threads automatically as half of the available number of cores. |
| maximumSearchDepth | integer | | The maximum search depth, which is the number of unwindings of the main function. Non-positive numbers (≤ 0) are interpreted as infinity. |
| maximumLoopUnroll | integer | | The maximum number of unwindings for internal loops. Non-positive numbers (≤ 0) are interpreted as infinity. |
| resultExpectation | enum | ALLOWED:FULFILLED, VIOLATED, UNKNOWN | The expected result for the proof's execution. |
| engines [{ | | | |
| Array of object: The engines of the proof execution. | | | |
| name* | enum | ALLOWED:SMIBMC, VIS, AUTOFXP, CBMC, ISAT | The name of the engine. |
| enabled | boolean | | Whether or not this engine should be considered. Default is true |
| }] | | | |
| isAllowAssumption | boolean | | Set to 'true', if assumption check is allowed. |
| useLocalInputRestriction | boolean | | Whether or not the proof uses local input restrictions. |
| } | | | |
| } | | | |

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

28.2 PUT /ep/proofs/{proofUID}

Apply proof settings.

Apply proof settings on given proofUID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------|--------|----------------------|
| *proofUID | string | The ID of the proof. |

REQUEST BODY - application/json

```
{
  The proof settings object. If not provided, default settings will be used.

  timeoutSeconds      integer  The timeout in seconds, i.e. the limit on how long this proof execution may run. Non-
                           positive numbers (<= 0) are interpreted as infinity (i.e. no timeout has been specified).
  memoryLimit         integer  The memory limit in MB. Valid values are <= 0 (to denote infinity) or any positive integer
                           >= 500 to set a positive memory limit.
  maxNumberOfThreads  integer  The maximum number of parallel threads for the proof execution. Valid values are
                           between 1 and available number of cores. <br>It is possible to set this parameter to a
                           value of -1, which will compute the number of threads automatically as half of the
                           available number of cores.
  maximumSearchDepth  integer  The maximum search depth, which is the number of unwindings of the main function.
                           Non-positive numbers (<= 0) are interpreted as infinity.
  maximumLoopUnroll   integer  The maximum number of unwindings for internal loops. Non-positive numbers (<= 0) are
                           interpreted as infinity.
  resultExpectation    enum    ALLOWED:FULFILLED, VIOLATED, UNKNOWN
                           The expected result for the proof's execution.

  engines [{
    Array of object: The engines of the proof execution.
    name*      enum    ALLOWED:SMIBMC, VIS, AUTOFXP, CBMC, ISAT
                           The name of the engine.
    enabled    boolean  Whether or not this engine should be considered. Default is true
  }]
  isAllowAssumption    boolean  Set to 'true', if assumption check is allowed.
  useLocalInputRestriction boolean  Whether or not the proof uses local input restrictions.
}
```

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

28.3 POST /ep/proofs/{frUid}

Create a proof.

Create a proof based on Formal Requirement Uid.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|--------|--------|------------------------------------|
| *frUid | string | The UID of the formal requirement. |

RESPONSE

STATUS CODE - 201: Created

RESPONSE MODEL - application/json

| | | | |
|--|---------|---|---|
| { | | | |
| uid | string | | READ-ONLY The unique identifier (UID) of this object. |
| name | string | | Name of the proof. |
| description | string | | Description of the proof. |
| formalRequirementName | string | | Name of the formal requirement used by this proof. |
| proofSettings { | | | |
| The proof settings object. If not provided, default settings will be used. | | | |
| timeoutSeconds | integer | The timeout in seconds, i.e. the limit on how long this proof execution may run. Non-positive numbers (<= 0) are interpreted as infinity (i.e. no timeout has been specified). | |
| memoryLimit | integer | The memory limit in MB. Valid values are <= 0 (to denote infinity) or any positive integer >= 500 to set a positive memory limit. | |
| maxNumberOfThreads | integer | The maximum number of parallel threads for the proof execution. Valid values are between 1 and available number of cores. It is possible to set this parameter to a value of -1, which will compute the number of threads automatically as half of the available number of cores. | |
| maximumSearchDepth | integer | The maximum search depth, which is the number of unwindings of the main function. Non-positive numbers (<= 0) are interpreted as infinity. | |
| maximumLoopUnroll | integer | The maximum number of unwindings for internal loops. Non-positive numbers (<= 0) are interpreted as infinity. | |
| resultExpectation | enum | ALLOWED:FULFILLED, VIOLATED, UNKNOWN The expected result for the proof's execution. | |
| engines [{ | | | |
| Array of object: The engines of the proof execution. | | | |
| name* | enum | ALLOWED:SMIBMC, VIS, AUTOFXP, CBMC, ISAT The name of the engine. | |
| enabled | boolean | Whether or not this engine should be considered. Default is true | |
| }] | | | |
| isAllowAssumption | boolean | Set to 'true', if assumption check is allowed. | |
| useLocalInputRestriction | boolean | Whether or not the proof uses local input restrictions. | |
| } | | | |
| } | | | |

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

28.4 POST /ep/proofs/{proofUID}/execute

Execute a proof.

Execute a proof based on the given proofUID. If multiple executable architecture are preset, the architecture-uid query parameter must be specified.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------|--------|-----------------------|
| *proofUID | string | The UID of the proof. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------------|--------|--|
| architecture-uid | string | The UID of the architecture on which this proof to be executed. If there are multiple valid architectures, but no architecture is specified, the C-Code architecture is used as a default. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
  The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

28.5 GET /ep/proofs

Get all proofs.

Get all proofs found on the active profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid                                string                                READ-ONLY
                                         The unique identifier (UID) of this object.
    name                              string                                Name of the proof.
    description                        string                                Description of the proof.
    formalRequirementName              string                                Name of the formal requirement used by this
                                         proof.
    proofSettings {
      The proof settings object. If not provided, default settings will be used.
        timeoutSeconds                 integer    The timeout in seconds, i.e. the limit on how long this proof execution may run.
                                         Non-positive numbers (<= 0) are interpreted as infinity (i.e. no timeout has been
                                         specified).
        memoryLimit                    integer    The memory limit in MB. Valid values are <= 0 (to denote infinity) or any positive
                                         integer >= 500 to set a positive memory limit.
        maxNumberOfThreads              integer    The maximum number of parallel threads for the proof execution. Valid values
                                         are between 1 and available number of cores. <br>It is possible to set this
                                         parameter to a value of -1, which will compute the number of threads
                                         automatically as half of the available number of cores.
        maximumSearchDepth              integer    The maximum search depth, which is the number of unwindings of the main
                                         function. Non-positive numbers (<= 0) are interpreted as infinity.
        maximumLoopUnroll              integer    The maximum number of unwindings for internal loops. Non-positive numbers
                                         (<= 0) are interpreted as infinity.
        resultExpectation               enum      ALLOWED:FULFILLED, VIOLATED, UNKNOWN
                                         The expected result for the proof's execution.
        engines [{
          Array of object: The engines of the proof execution.
            name*                       enum      ALLOWED:SMIBMC, VIS, AUTOFXP, CBMC, ISAT
                                         The name of the engine.
            enabled                      boolean   Whether or not this engine should be considered. Default is true
          }]
        isAllowAssumption               boolean   Set to 'true', if assumption check is allowed.
        useLocalInputRestriction        boolean   Whether or not the proof uses local input restrictions.
      }
    ]
  ]
```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

28.6 GET /ep/proofs/{proofUID}/detailed-proof-results

Get detailed proof results of a proof.

Get detailed proof results of a proof by providing a proofUID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------|--------|-----------------------|
| *proofUID | string | The UID of the proof. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

| | | |
|--|---------|--|
| [{ Array of object: | | |
| proofId | string | The proof UID for which this result was generated. |
| steps | integer | The amount of steps after which the execution was terminated. -1 represents a step number which has no useful meaning. |
| architectureName | string | The architecture name on which the result was executed. |
| proofResult | string | The proof result after the execution. |
| terminationReason | string | Termination reason of the proof execution. |
| timeoutSeconds | integer | The timeout in seconds, i.e. the limit on how long this proof execution may run. Non-positive numbers (<= 0) are interpreted as infinity (i.e. no timeout has been specified). |
| memoryLimit | integer | The memory limit in MB. Valid values are -1 (to denote infinity) or any positive integer >= 500 to set a positive memory limit. |
| maxNumberOfThreads | integer | The maximum number of parallel proof execution threads. Valid values are between 1 and MAX_INT. |
| maximumSearchDepth | integer | The maximum search depth, which is the number of unwindings of the main function. Non-positive numbers (<= 0) are interpreted as infinity. |
| maximumLoopUnroll | integer | The maximum number of unwindings for internal loops. Non-positive numbers (<= 0) are interpreted as infinity. |
| usedEngines | [enum] | ALLOWED: SMIBMC, VIS, AUTOFXP, CBMC, ISAT The engines used in the proof execution. |
| isAllowAssumptionCheck | boolean | Returns true if assumption check was allowed. |
| inputRestrictions { | | |
| A list with the used input restriction for this execution. | | |
| } | | |
| expectedResult | enum | ALLOWED: FULFILLED, VIOLATED, UNKNOWN The expected result for the proof's execution. |
| }] | | |

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

29. REAL-TIME TESTING

Execute operations with Real-Time Testing observers such as export

29.1 POST /ep/rtt-observers-export

Export RTT Observers

Long running task Export RTT Observers at specified folder location, and select which formal requirements to contain the export.

REQUEST

REQUEST BODY - application/json

```
{
  folderPath*           string    The path of the folder to which the RTT Observers should be exported.
  formalRequirementUIDs* [string] Formal requirements UIDs list.
  resetOnFailure         boolean   Set reset on failure flag. Default is false.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

```
string
```

30. REGRESSION TEST REPORTS

Creates a Regression Test Report for a given Regression Test. Retrieves all existing Regression Test reports from the profile.

30.1 POST /ep/regression-tests/{regression-test-uid}/regression-test-reports

Create a report for a regression test

Creates a Regression Test Report on a regression test.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|----------------------|--------|---|
| *regression-test-uid | string | The Regression test UID for which the Regression Report is created. |

RESPONSE

STATUS CODE - 201: Created

RESPONSE MODEL - application/json

```
{
  uid          string READ-ONLY
                  The unique identifier (UID) of this object.
  reportName   string Name of the report.
  reportType   string Type of the report.
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

30.2 GET /ep/regression-test-reports

Get all reports

Retrieve all the Regression Test reports from the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {
  Array of object:
```



```
    uid          string  READ-ONLY
                        The unique identifier (UID) of this object.
    reportName    string  Name of the report.
    reportType    string  Type of the report.
  }]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

```
string
```

31. REGRESSION TESTS

Creates regression tests.

31.1 GET /ep/regression-tests/{regression-test-uid}

Get a test

Get the Regression Test with the provided UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|----------------------|--------|--|
| *regression-test-uid | string | The UID of the Regression Test to be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

| | | |
|-----------------------------------|----------|--|
| { | | |
| uid | string | READ-ONLY The unique identifier (UID) of this object. |
| referenceMode | string | The reference execution config type. |
| comparisonMode | string | The comparison execution config type. |
| referenceFolderUIDs | [string] | Reference folder UIDs |
| comparisonFolderUID | string | Comparison folder UID |
| executionDate | string | Execution Date |
| verdictStatus | enum | ALLOWED:PASSED, FAILED, ERROR, FAILED_ACCEPTED The verdict status |
| verdictState | enum | ALLOWED:VALID, OUTDATED_TOLERANCE_UPDATE, OUTDATED_MISSING_EXECUTIONS Verdict State |
| failed | integer | Number of failed comparisons. |
| failedAccepted | integer | Number of failed accepted comparisons. |
| passed | integer | Number of passed comparisons. |
| error | integer | Number of comparisons with error. |
| total | integer | Total number of comparisons. |
| comparisons [{ | | |
| Array of object: All comparisons. | | |
| uid | string | READ-ONLY The unique identifier (UID) of this object. |
| name | string | The name of Test Case / Stimuli Vector used in Comparison. |
| verdictStatus | enum | ALLOWED:PASSED, FAILED, ERROR, FAILED_ACCEPTED The verdict status |
| referenceExecutionRecordUID | string | UID of reference execution record. |
| comparisonExecutionRecordUID | string | UID of compared to execution record. |
| comment | string | Added comment for Comparison. |
| }] | | |
| name | string | The name of the RegresionTest Test. |
| } | | |

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

31.2 PATCH /ep/regression-tests/{regression-test-uid}

Update verdict status for a comparison

Changes verdict status for a Comparison. If accept is true, the comparison verdict status is changed from 'failed' to 'failed (accepted)'. If accept is false, the comparison verdict status is changed from 'failed (accepted)' to 'failed'

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|----------------------|--------|---|
| *regression-test-uid | string | The Regression Test UID for which to change the Comparison verdict. |

REQUEST BODY - application/json

```
{
  comparisonUID* string  UID of the Comparison
  accept*         boolean If accept is true, the comparison verdict status is changed from 'failed' to 'failed (accepted)'. If accept is
                        false, the comparison verdict status is changed from 'failed (accepted)' to 'failed'
}
```

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

31.3 POST /ep/folders/{folder-uid}/regression-tests

Generate a test on a folder

Long running task Generates a Regression Test on a given folder UID for the specified comparison execution kind. Optionally, the folder where to save the simulated execution records can be provided. If this property is not provided, the execution records are not saved.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The folder UID for which the Regression Test is generated. |

REQUEST BODY - application/json

```
{
  compMode*      string  Comparison execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL')
  compFolderUID  string  (Optional) The folder where to save the simulated ExecutionRecords. If this property is not provided, the
                        ExecutionRecords are not saved.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

31.4 POST /ep/folders/regression-tests

Generate a test on a list of folders

Long running task Generates a Regression Test on a given list of folder UIDs for the specified comparison execution kind. Optionally, the folder where to save the simulated execution records can be provided. If this property is not provided, the execution records are not saved.

REQUEST

REQUEST BODY - application/json

```
{
  compMode*      string  Comparison execution mode (e.g. 'SL MIL', 'TL MIL', 'TL MIL (EV)', 'SIL', 'PIL', 'SL SIL')
  compFolderUID  string  (Optional) The folder where to save the simulated ExecutionRecords. If this property is not provided, the
                        ExecutionRecords are not saved.
  UIDs*          [string] Folder UID list
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

```
string
```

31.5 GET /ep/regression-tests

Get all tests
Get all Regression Tests from active profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  uid string READ-ONLY
           The unique identifier (UID) of this object.
  referenceMode string
           The reference execution config type.
  comparisonMode string
           The comparison execution config type.
  referenceFolderUIDs [string]
           Reference folder UIDs
  comparisonFolderUID string
           Comparison folder UID
  executionDate string
           Execution Date
  verdictStatus enum
           ALLOWED:PASSED, FAILED, ERROR, FAILED_ACCEPTED
           The verdict status
  verdictState enum
           ALLOWED:VALID, OUTDATED_TOLERANCE_UPDATE,
           OUTDATED_MISSING_EXECUTIONS
           Verdict State
  failed integer
           Number of failed comparisons.
  failedAccepted integer
           Number of failed accepted comparisons.
  passed integer
           Number of passed comparisons.
  error integer
           Number of comparisons with error.
}
```

```
total          integer    Total number of comparisons.
comparisons [{
  Array of object: All comparisons.
    uid          string    READ-ONLY
                          The unique identifier (UID) of this object.
    name          string    The name of Test Case / Stimuli Vector used in Comparison.
    verdictStatus enum      ALLOWED:PASSED, FAILED, ERROR, FAILED_ACCEPTED
                          The verdict status
    referenceExecutionRecordUID string  UID of reference execution record.
    comparisonExecutionRecordUID string  UID of compared to execution record.
    comment       string    Added comment for Comparison.
  }]
name           string      The name of the RegresionTest Test.
}]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

32. REPORTS

Retrieve and export Reports.

32.1 GET /ep/reports/{report-uid}

Get a report

Get the report with the provided UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|---------------------------------------|
| *report-uid | string | The UID of the report to be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  uid          string READ-ONLY
                The unique identifier (UID) of this object.
  reportName   string  Name of the report.
  reportType   string  Type of the report.
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

```
string
```

32.2 POST /ep/reports/{report-uid}

Export a report

Use this command export a report to a given location. The exported report corresponds to the given UID inside the command. New name can be set for file. If file exists, will be overwritten. Keep in mind to use only legal profile paths.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|---------------------------------------|
| *report-uid | string | The UID of the report to be returned. |

REQUEST BODY - application/json

```
{
  exportPath* string Path to export report
}
```

```
    newName      string (Optional) New report name.
}
```

RESPONSE

STATUS CODE - 201: Exported Successfully. Returns exported report location.

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

33. REQUIREMENT-BASED TEST CASES

Handle requirement-based Test Cases.

33.1 GET /ep/test-cases-rbt/{testcase-uid}

Get a test case

Get a requirement-based Test Case by providing its UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|--|
| *testcase-uid | string | The UID of the requirement-based Test Case to be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  uid          string  READ-ONLY
                  The unique identifier (UID) of this object.
  name         string
  description   string  An optional description of the RBTTestCase
  kind         string  The datatype or kind of the RBTTestCase. Usually "tc" or "csv".
  length       integer
  draft        boolean States whether or not the RBTTestCase is in Draft-Mode.
  lastModifiedDate string The date of the last modification to the RBTTestCase
  folderUID    string  The unique identifier of the folder the RBTTestCase belongs to.
  scopeUID     string  The unique identifier of the scope the RBTTestCase belongs to.
  requirementUIDs [string] The unique identifiers of the requirements belonging to the RBTTestCase.
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

33.2 DELETE /ep/test-cases-rbt/{testcase-uid}

Delete a test case

Delete a requirement-based Test Case by providing its UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------|------|-------------|
|------|------|-------------|

| NAME | TYPE | DESCRIPTION |
|---------------|--------|---|
| *testcase-uid | string | The UID of the requirement-based Test Case to be deleted. |

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

33.3 POST /ep/test-cases-rbt-export

Export test cases

Long running task Export single or multiple requirement-based Test Case(s) by providing the list of the test cases which will be exported, the export directory, the export format and a list of additional options for export.

REQUEST

REQUEST BODY - application/json

```
{
  UUIDs*           [string] List with the UUIDs of the elements which will be exported
  exportDirectory* string    Directory where to export the elements
  exportFormat      enum      ALLOWED:TC, EXCEL, CSV, JSON
                               The format of the exported test cases. Default value is EXCEL.

  additionalOptions {
    csvDelimiter    enum      ALLOWED:SEMICOLON, COMMA, COLON, PIPE
                               Relevant only for CSV export format. It can have one of the following values: "SEMICOLON",
                               "COMMA", "COLON", "PIPE". Default value is "SEMICOLON".

    singleFile      boolean   Relevant only for CSV export format: false - each vector will be exported in it's own file; true - all
                               vectors will be exported in same file. Default is 'false'

    architectureUid string    Relevant only for Excel export format. It specifies the UUID of the architecture on which the
                               interfaces of the vectors will be exported. Default is the master architecture
  }
  overwritePolicy  enum      ALLOWED:EXTEND_NAME, OVERWRITE, SKIP
                               Overwrite policy: allowed values (not case-sensitive) are: EXTEND_NAME, in which case if the
                               exported file exists on disk, its name will be extended and the original file on disk will be kept,
                               OVERWRITE, in which case the original file on disk is overwritten, if it exists. Default value is
                               EXTEND_NAME
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

33.4 GET /ep/test-cases-rbt

Get all test cases

Get all requirement-based Test Cases.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

| | | |
|------------------|----------|---|
| [{ | | |
| Array of object: | | |
| uid | string | READ-ONLY The unique identifier (UID) of this object. |
| name | string | The name of the RBTestCase. |
| description | string | An optional description of the RBTestCase |
| kind | string | The datatype or kind of the RBTestCase. Usually "tc" or "csv". |
| length | integer | The length of the vector. |
| draft | boolean | States whether or not the RBTestCase is in Draft-Mode. |
| lastModifiedDate | string | The date of the last modification to the RBTestCase |
| folderUID | string | The unique identifier of the folder the RBTestCase belongs to. |
| scopeUID | string | The unique identifier of the scope the RBTestCase belongs to. |
| requirementUIDs | [string] | The unique identifiers of the requirements belonging to the RBTestCase. |
| }] | | |

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

33.5 PUT /ep/test-cases-rbt

Import test cases

LONG RUNNING TASK Import multiple requirement-based Test Cases from external files by providing their Path and an Overwrite Policy.

REQUEST

REQUEST BODY - application/json

```

{
  paths*           [string] The paths to all test cases you would like to import.
  folderUID        string   The UID of the folder you want to import into. If not specified Test Cases will be imported in the
                             default Test Cases folder.
  overwritePolicy  enum     ALLOWED:EXTEND_NAME, OVERWRITE, SKIP
                             Decides what happens in case of duplicate names. Can be "EXTEND_NAME", "OVERWRITE" or
                             "SKIP". Default is "SKIP".
  draft           boolean   Sets the Draft-Mode of the test cases. By default its value is false.
  csvDelimiter     enum     ALLOWED:SEMICOLON, COMMA, COLON, PIPE
                             Relevant only for CSV export format. It can have one of the following values: "SEMICOLON",
                             "COMMA", "COLON", "PIPE". Default value is "SEMICOLON".
  importKind       enum     ALLOWED:TC, EXCEL
                             The kind a file should be imported as. Possible values are: "TC" or "EXCEL". "TC" by default
}

```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET `/ep/progress?progress-id={progress-id}` using the id received by this command.

RESPONSE MODEL - application/json

```

{
  jobID string READ-ONLY
           The ID of a job.
}

```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

33.6 GET /ep/folders/{folder-uid}/test-cases-rbt

Get a list of test cases from a folder

Get all requirement-based Test Cases from a certain Folder by providing its UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The UID of the Folder containing the requirement based Test Cases. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid          string    READ-ONLY
                        The unique identifier (UID) of this object.
    name          string    The name of the RBTestCase.
    description   string    An optional description of the RBTestCase
    kind          string    The datatype or kind of the RBTestCase. Usually "tc" or "csv".
    length        integer   The length of the vector.
    draft         boolean   States whether or not the RBTestCase is in Draft-Mode.
    lastModifiedDate string  The date of the last modification to the RBTestCase
    folderUID     string    The unique identifier of the folder the RBTestCase belongs to.
    scopeUID      string    The unique identifier of the scope the RBTestCase belongs to.
    requirementUIDs [string] The unique identifiers of the requirements belonging to the RBTestCase.
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

33.7 GET /ep/scopes/{scope-uid}/test-cases-rbt

Get a list of test cases from a scope

Get all requirement-based Test Cases from a certain Scope by providing its UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The UID of the Scope containing the requirement based Test Cases. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid          string    READ-ONLY
                        The unique identifier (UID) of this object.
    name          string    The name of the RBTestCase.
    description   string    An optional description of the RBTestCase
    kind          string    The datatype or kind of the RBTestCase. Usually "tc" or "csv".
    length        integer   The length of the vector.
    draft         boolean   States whether or not the RBTestCase is in Draft-Mode.
    lastModifiedDate string  The date of the last modification to the RBTestCase
    folderUID     string    The unique identifier of the folder the RBTestCase belongs to.
    scopeUID      string    The unique identifier of the scope the RBTestCase belongs to.
    requirementUIDs [string] The unique identifiers of the requirements belonging to the RBTestCase.
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

33.8 GET /ep/requirements/{requirement-uid}/test-cases-rbt

Get a list of test cases linked to a requirement

Use this command to retrieve the test cases linked to a given requirement uid.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------------|--------|--|
| *requirement-uid | string | The uid of the requirement for which all linked test cases should be returned. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------------------|---------|---|
| only-indirect-testcases | boolean | The flag used to specify whether to retrieve only test cases which are indirectly linked to a given requirement. This flag has an effect only on non-leaves requirements. If no value is specified, this flag will be set to false. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {
  Array of object:
    uid          string  READ-ONLY
                    The unique identifier (UID) of this object.
    name          string
    description   string  An optional description of the RBTestCase
    kind          string  The datatype or kind of the RBTestCase. Usually "tc" or "csv".
    length        integer
    draft         boolean States whether or not the RBTestCase is in Draft-Mode.
    lastModifiedDate string The date of the last modification to the RBTestCase
    folderUID     string  The unique identifier of the folder the RBTestCase belongs to.
    scopeUID      string  The unique identifier of the scope the RBTestCase belongs to.
    requirementUIDs [string] The unique identifiers of the requirements belonging to the RBTestCase.
  } ]
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

33.9 PUT /ep/requirements/test-cases-rbt

Unlink requirements from test cases

Use this command to unlink requirements from test cases. Only their uids must be specified.

REQUEST

REQUEST BODY - application/json

```
{
  requirementUIDs* [string] The uids of the requirements that need to be linked to test cases.
  testCaseUIDs*   [string] The uids of the test cases that need to be linked to the requirements.
}
```

RESPONSE

STATUS CODE - 200: Requirements unlinked from test cases.

STATUS CODE - 400: Bad request.

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

33.10 POST /ep/requirements/test-cases-rbt

Link requirements to test cases

Use this command to link requirements to test cases. Only their uids must be specified.

REQUEST

REQUEST BODY - application/json

```
{
  requirementUIDs* [string] The uids of the requirements that need to be linked to test cases.
  testCaseUIDs*   [string] The uids of the test cases that need to be linked to the requirements.
}
```

RESPONSE

STATUS CODE - 200: Requirements linked to test cases.

STATUS CODE - 400: Bad request.

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

string

33.11 POST /ep/formal-requirements/test-cases-rbt

Generate test cases based on formal requirements

Long running task Generate test cases based on formal requirements using a specific configuration.

REQUEST

REQUEST BODY - application/json

| | | |
|-------------------------------|----------|--|
| { | | |
| formalRequirements* | [string] | The formal requirements for which the coverage will be generated. |
| behaviour | enum | ALLOWED: IMPLEMENTATION, FORMAL_REQUIREMENTS Specifies if the vector generation shall be based on the behaviour of the SUT or the behaviour specified via formal requirements. 'IMPLEMENTATION' (default, if profile contains SUT): Uses behaviour from SUT 'FORMAL_REQUIREMENTS': Uses behaviour described in formal requirements (see SurroundingFormalRequirements). |
| architecture | string | Architecture uid for which generation is performed. (Only valid for behaviour: FORMAL_REQUIREMENTS). |
| surroundingFormalRequirements | [string] | Specifies the formal requirements that describe the behaviour as array. (only valid for corresponding 'Behaviour' selection) By default all formal requirements of the scope (see first parameter) are taken into account. |
| restrictOutputBehaviour | boolean | Set whether or not values for outputs and locals should keep their values if these are not written by formal requirement (only valid for Behaviour: Formal Requirements). Default is 'true' |
| coverageMetric | enum | ALLOWED: ONCE, LINEAR_CONDITION_COVERAGE, MULTIPLE_CONDITION_COVERAGE Specifies the type of coverage metric. Default is 'ONCE' |
| coverageTarget | enum | ALLOWED: NONE, TRIGGER_EVENT_COVERAGE, TRIGGER_CONDITION_COVERAGE, TRIGGER_EVENT_CONDITION_COVERAGE Specifies the type of coverage target. Allowed values depend on the selected 'coverageMetric': 'NONE' (default) for 'ONCE' coverageMetric, 'TRIGGER_EVENT_COVERAGE' (default), 'TRIGGER_CONDITION_COVERAGE', or 'TRIGGER_EVENT_CONDITION_COVERAGE' (Trigger event/condition coverage) for 'LINEAR_CONDITION_COVERAGE' or 'MULTIPLE_CONDITION_COVERAGE' coverageMetric. |
| onlyFulfillingTestCases | boolean | Specifies if only fulfilling test cases shall be considered. Default is 'true' |
| memoryLimit | string | Defines the memory limit (MB), default: 'inf'. |
| globalTimeout | string | Defines the global timeout (s), default 'inf'. |
| timeoutPerGoal | string | Defines the timeout per goal (s), default 'inf'. |
| searchDepth | string | Defines the search depth (steps), default 'inf'. |
| loopUnroll | string | Defines the loop unroll, default 32. |
| numberOfThreads | integer | Defines the maximum number of parallel proof execution threads. Valid values are between 1 and available number of cores. It is possible to set this parameter to a value of -1, which will compute the number of threads automatically as half of the available number of cores. Default is '1' |
| initializationVectorUID | string | The UID of the RequirementBasedTestCase which shall be used to initialize the engine |
| checkBoundaryCoverageGoals | boolean | Specifies if boundary coverage goals shall be considered. Default is taken from the preferences. |
| relativeEpsilon | string | Relative epsilon used to derive boundary coverage goals. Default is taken from the preferences. |
| minimumEpsilon | string | Minimum epsilon used to derive boundary coverage goals. Default is taken from the preferences. |
| } | | |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
    The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

34. REQUIREMENT-BASED TEST EXECUTION

Executes requirement-based Testing.

34.1 POST /ep/folders/{folder-uid}/test-execution-rbt

Execute all test cases from a folder

Long running task Executes a requirement-based Test on all Test Cases from a given folder for the specified execution kinds. Optionally, also the model coverage report can be generated or the test execution can be forced to not re-use any previous results.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The folder UID for which the requirement-based Test is executed. |

REQUEST BODY - application/json

| | | |
|-----------------------------|----------|---|
| execConfigNames* | [string] | List of execution kinds (example: SIL, TL MIL, SL MIL, etc.). Not case-sensitive. |
| generateModelCoverageReport | boolean | Specify (optional) if the model coverage report should be generated. Default value is false. |
| forceExecute | boolean | Specify (optional) if the test execution should be forced (all previous results will be discarded). Default value is false. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [#get-/ep/progress>Progress](#) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

| | | |
|-------|--------|------------------|
| jobID | string | READ-ONLY |
| | | The ID of a job. |

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

34.2 POST /ep/folders/test-execution-rbt

Execute all test cases from a list of folders

Long running task Executes a requirement-based Test on all Test Cases from a given list of folders for the specified execution kinds. Optionally, also the model coverage report can be generated or the test execution can be forced to not re-use any previous results.

REQUEST

REQUEST BODY - application/json

```
{
  UIDs* [string] List with unique identifiers of the objects.
  data {
    execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.). Not case-sensitive.
    generateModelCoverageReport boolean Specify (optional) if the model coverage report should be generated. Default value is false.
    forceExecute boolean Specify (optional) if the test execution should be forced (all previous results will be discarded). Default value is false.
  }
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
  The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

34.3 POST /ep/test-cases-rbt/{testcase-uid}/test-execution-rbt

Execute a test case

Long running task Executes a requirement-based Test on a requirement-based Test Case for the specified execution kinds. Optionally, also the test execution can be forced to not re-use any previous results.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|--|
| *testcase-uid | string | The requirement-based Test Case UID for which the RBT is executed. |

REQUEST BODY - application/json

```
{
  execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.).
  forceExecute      boolean Specify (optional) if the test execution should be forced (all previous results will be discarded).
                                Default value is false.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

34.4 POST /ep/test-cases-rbt/test-execution-rbt

Execute a list of test cases

Long running task Executes a requirement-based Test on a list of requirement-based Test Cases for the specified execution kinds. Optionally, also the test execution can be forced to not re-use any previous results.

REQUEST

REQUEST BODY - application/json

```
{
  UUIDs* [string] List with unique identifiers of the objects.
  data {
    execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.).
    forceExecute      boolean Specify (optional) if the test execution should be forced (all previous results will be
                                discarded). Default value is false.
  }
}
```

```
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET `/ep/progress?progress-id={progress-id}` using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

34.5 POST /ep/requirements-sources/{requirements-source-uid}/test-execution-rbt

Execute all test cases linked to a requirements source

Long running task Executes a requirement-based Test on all Test Cases linked to the requirements of the given requirements source for the specified execution kinds. Optionally, also the model coverage report can be generated or the test execution can be forced to not re-use any previous results.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|--------------------------|--------|--|
| *requirements-source-uid | string | The requirements source UID for which the RBT is executed. |

REQUEST BODY - application/json

```
{
  execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.). Not case-sensitive.
  generateModelCoverageReport boolean Specify (optional) if the model coverage report should be generated. Default value is false.
  forceExecute boolean Specify (optional) if the test execution should be forced (all previous results will be discarded). Default value is false.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET `/ep/progress?progress-id={progress-id}` using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

34.6 POST /ep/requirements-sources/test-execution-rbt

Execute all test cases linked to a list of requirements sources

Long running task Executes a requirement-based Test on all Test Cases linked to the requirements of the given requirements sources for the specified execution kinds. Optionally, also the model coverage report can be generated or the test execution can be forced to not re-use any previous results.

REQUEST

REQUEST BODY - application/json

```
{
  UIDs* [string] List with unique identifiers of the objects.
  data {
    execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.). Not case-sensitive.
    generateModelCoverageReport boolean Specify (optional) if the model coverage report should be generated. Default value is false.
    forceExecute boolean Specify (optional) if the test execution should be forced (all previous results will be discarded). Default value is false.
  }
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

34.7 POST /ep/scopes/{scope-uid}/test-execution-rbt

Execute all test cases from a scope

Long running task Executes a requirement-based Test on all Test Cases from a given scope for the specified execution kinds. Optionally, also the model coverage report can be generated or the test execution can be forced to not re-use any previous results.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The scope UID for which the requirement-based Test is executed. |

REQUEST BODY - application/json

| | | |
|-----------------------------|----------|---|
| { | | |
| execConfigNames* | [string] | List of execution kinds (example: SIL, TL MIL, SL MIL, etc.). Not case-sensitive. |
| generateModelCoverageReport | boolean | Specify (optional) if the model coverage report should be generated. Default value is false. |
| forceExecute | boolean | Specify (optional) if the test execution should be forced (all previous results will be discarded). Default value is false. |
| } | | |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

| | | |
|-------|--------|-------------------------------|
| { | | |
| jobID | string | READ-ONLY The ID of a job. |
| } | | |

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

34.8 POST /ep/scopes/test-execution-rbt

Execute all test cases from a list of scopes

Long running task Executes a requirement-based Test on all Test Cases from a given list of scopes for the specified execution kinds. Optionally, also the model coverage report can be generated or the test execution can be forced to not re-use any previous results.

REQUEST

REQUEST BODY - application/json

```
{
  UUIDs* [string] List with unique identifiers of the objects.
  data {
    execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.). Not case-sensitive.
    generateModelCoverageReport boolean Specify (optional) if the model coverage report should be generated. Default value is false.
    forceExecute boolean Specify (optional) if the test execution should be forced (all previous results will be discarded). Default value is false.
  }
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
  The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

35. REQUIREMENT-BASED TEST EXECUTION REPORTS

Creates requirement-based Test Execution Reports.

35.1 POST /ep/folders/{folder-uid}/test-execution-reports-rbt

Create a report on a folder

Create a requirement-based Test Execution Report on a given folder.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The folder UID for which the Test Execution Report is created. |

REQUEST BODY - application/json

```
{
  execConfigName* string Execution kind (example: SIL, TL MIL, SL MIL, etc.). Not case-sensitive.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                        The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

35.2 POST /ep/folders/test-execution-reports-rbt

Create a report on a list of folders

Create a requirement-based Test Execution Report on a given list of folders.

REQUEST

REQUEST BODY - application/json

```
{
  UIDs*           [string] List with unique identifiers of the objects.
  execConfigName* string    Execution kind (example: SIL, TL MIL, SL MIL, etc.).
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

```
string
```

35.3 POST /ep/requirements-sources/{requirements-source-uid}/test-execution-reports-rbt

Create a report on a requirements source

Create a requirement-based Test Execution Report on a given requirements source.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|--------------------------|--------|---|
| *requirements-source-uid | string | The requirements source UID for which the Test Execution Report is created. |

REQUEST BODY - application/json

```
{
```

```
    execConfigName* string Execution kind (example: SIL, TL MIL, SL MIL, etc.). Not case-sensitive.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

35.4 POST /ep/requirements-sources/test-execution-reports-rbt

Create a report on a list of requirements sources

Create a requirement-based Test Execution Report on a given list of requirements sources.

REQUEST

REQUEST BODY - application/json

```
{
  UUIDs* [string] List with unique identifiers of the objects.
  execConfigName* string Execution kind (example: SIL, TL MIL, SL MIL, etc.).
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

35.5 POST /ep/scopes/{scope-uid}/test-execution-reports-rbt

Create a report on a scope

Create a requirement-based Test Execution Report on a given scope.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The Scope UID for which the Test Execution Report is created. |

REQUEST BODY - application/json

```
{
  execConfigName* string Execution kind (example: SIL, TL MIL, SL MIL, etc.). Not case-sensitive.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                        The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

35.6 POST /ep/scopes/test-execution-reports-rbt

Create a report on a list of scopes

Create a requirement-based Test Execution Report on a given list of scopes.

REQUEST

REQUEST BODY - application/json

```
{
  UIDs*           [string] List with unique identifiers of the objects.
  execConfigName* string   Execution kind (example: SIL, TL MIL, SL MIL, etc.).
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

35.7 GET /ep/test-execution-reports-rbt

Get all reports

Retrieve all the requirement-based Test Execution reports from the profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid          string  READ-ONLY
                        The unique identifier (UID) of this object.
    reportName    string  Name of the report.
    reportType    string  Type of the report.
}]
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

36. REQUIREMENTS

Retrieve Requirements, Linked Requirements, or Requirement Sources.

36.1 GET /ep/requirements-sources

Get all requirement sources

Get all requirement sources found on the opened profile.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    kind*      string      The kind of this requirement source. The
                        kind identifies this source to be from a
                        specific requirement management tool.

    settings* [{
      Array of object: A list with requirement settings.For EXCEL requirement kind, the following keys can be: name_attr_value, desc_attr_value,
      additional_attr, modification_date, excel_file_path, projectName_attr (or excel_sheet_name), excel_id_attr, excel_start_row,
      excel_parent_id.For DOORS requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date,
      projectName_attr, doors_module_qualifier, doors_baseline_major, doors_baseline_minor, doors_baseline_suffix.

        key*      string      For EXCEL requirement kind, the following keys are mandatory: excel_file_path, projectName_attr, excel_id_attr.
                        The optional setting keys are: excel_start_row, excel_parent_id.For DOORS requirement kind, the following keys
                        are mandatory: projectName_attr, doors_module_qualifier. The optional setting keys are:
                        doors_baseline_major, doors_baseline_minor, doors_baseline_suffix.

        value*    string      Setting value
      }]
    definedAdditionalAttributes      [string]      A list with additional attributes.
    externalUUID*                   string          The unique ID identifying the external
                                                    requirement source.
    name*                           string          The requirement source name.
    uid*                            string          The universally unique identifier of this
                                                    requirement source.
  }]
```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

36.2 GET /ep/requirements/{requirement-source-id}

Get all requirements of a requirement source

Get the requirements of the given requirement source id.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------------------|--------|------------------------------------|
| *requirement-source-id | string | The UID of the requirement source. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

| | | |
|---|----------|--|
| [{ Array of object: | | |
| uid* | string | The universally unique identifier. |
| identifier* | string | The requirement identifier (e.g. a chapter number within DOORS). |
| isRemoved | boolean | Value meaning whether this requirement has been removed within the requirement management tool. |
| additionalAttributes { Map containing all additional attributes. | | |
| } | | |
| scopeId* | string | The scope id this requirement is directly linked to. |
| description* | string | The requirement description. |
| name* | string | The requirement name. |
| dateOfLastUpdate* | string | The requirement last update date. |
| requirementSource* { | | |
| kind* | string | The kind of this requirement source. The kind identifies this source to be from a specific requirement management tool. |
| settings* [{ Array of object: A list with requirement settings. For EXCEL requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date, excel_file_path, projectName_attr (or excel_sheet_name), excel_id_attr, excel_start_row, excel_parent_id. For DOORS requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date, projectName_attr, doors_module_qualifier, doors_baseline_major, doors_baseline_minor, doors_baseline_suffix. | | |
| key* | string | For EXCEL requirement kind, the following keys are mandatory: excel_file_path, projectName_attr, excel_id_attr. The optional setting keys are: excel_start_row, excel_parent_id. For DOORS requirement kind, the following keys are mandatory: projectName_attr, doors_module_qualifier. The optional setting keys are: doors_baseline_major, doors_baseline_minor, doors_baseline_suffix. |
| value* | string | Setting value |
| }] | | |
| definedAdditionalAttributes | [string] | A list with additional attributes. |
| externalUUID* | string | The unique ID identifying the external requirement source. |
| name* | string | The requirement source name. |
| uid* | string | The universally unique identifier of this requirement source. |
| } | | |
| }] | | |

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

36.3 GET /ep/scopes/{scope-id}/linked-requirements

Get all requirements for a scope

Get the linked requirements of this given scope id.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-----------|--------|--------------------------|
| *scope-id | string | The UID of the scope id. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

| | | |
|---|----------|--|
| [{ Array of object: | | |
| uid* | string | The universally unique identifier. |
| identifier* | string | The requirement identifier (e.g. a chapter number within DOORS). |
| isRemoved | boolean | Value meaning whether this requirement has been removed within the requirement management tool. |
| additionalAttributes { Map containing all additional attributes. | | |
| } | | |
| scopeId* | string | The scope id this requirement is directly linked to. |
| description* | string | The requirement description. |
| name* | string | The requirement name. |
| dateOfLastUpdate* | string | The requirement last update date. |
| requirementSource* { | | |
| kind* | string | The kind of this requirement source. The kind identifies this source to be from a specific requirement management tool. |
| settings* [{ Array of object: A list with requirement settings. For EXCEL requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date, excel_file_path, projectName_attr (or excel_sheet_name), excel_id_attr, excel_start_row, excel_parent_id. For DOORS requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date, projectName_attr, doors_module_qualifier, doors_baseline_major, doors_baseline_minor, doors_baseline_suffix. | | |
| key* | string | For EXCEL requirement kind, the following keys are mandatory: excel_file_path, projectName_attr, excel_id_attr. The optional setting keys are: excel_start_row, excel_parent_id. For DOORS requirement kind, the following keys are mandatory: projectName_attr, doors_module_qualifier. The optional setting keys are: doors_baseline_major, doors_baseline_minor, doors_baseline_suffix. |
| value* | string | Setting value |
| }] | | |
| definedAdditionalAttributes | [string] | A list with additional attributes. |
| externalUUID* | string | The unique ID identifying the external requirement source. |
| name* | string | The requirement source name. |
| uid* | string | The universally unique identifier of this requirement source. |
| } | | |
| }] | | |

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

37. REQUIREMENTS IMPORT

Import Requirements.

37.1 POST /ep/requirements-import

Import requirements

Import requirements by specifying the kind of requirements.

REQUEST

REQUEST BODY - application/json

| | | |
|---|-----------------------|---|
| <code>{</code> | | |
| <code> kind*</code> | <code>enum</code> | ALLOWED: EXCEL , DOORS The kind of imported requirements. Allowed types: EXCEL or DOORS. |
| <code> nameAttribute</code> | <code>string</code> | The name of imported requirements. Required for DOORS and EXCEL import. |
| <code> descriptionAttribute</code> | <code>string</code> | The description of imported requirements. Required for DOORS and EXCEL import. |
| <code> additionalAttributes</code> | <code>[string]</code> | A list with additional attributes. |
| <code> settings* [{</code> | | |
| Array of object: A list with requirement settings.For EXCEL requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date, excel_file_path, projectName_attr (or excel_sheet_name), excel_id_attr, excel_start_row, excel_parent_id.For DOORS requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date, projectName_attr, doors_module_qualifier, doors_baseline_major, doors_baseline_minor, doors_baseline_suffix. | | |
| <code> key*</code> | <code>string</code> | For EXCEL requirement kind, the following keys are mandatory: excel_file_path, projectName_attr, excel_id_attr. The optional setting keys are: excel_start_row, excel_parent_id.For DOORS requirement kind, the following keys are mandatory: projectName_attr, doors_module_qualifier. The optional setting keys are: doors_baseline_major, doors_baseline_minor, doors_baseline_suffix. |
| <code> value*</code> | <code>string</code> | Setting value |
| <code> }]</code> | | |
| <code>}</code> | | |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

| | |
|----------------------|---|
| <code>{</code> | |
| <code> jobID</code> | <code>string</code> READ-ONLY The ID of a job. |
| <code>}</code> | |

STATUS CODE - 400: Bad request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

37.2 GET /ep/requirements-import/doors

Get the DOORS™ configuration template

Get the configuration with default settings for importing different kinds of requirements.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

| | | |
|---|----------|---|
| { | | |
| kind* | enum | ALLOWED: EXCEL , DOORS The kind of imported requirements. Allowed types: EXCEL or DOORS. |
| nameAttribute | string | The name of imported requirements. Required for DOORS and EXCEL import. |
| descriptionAttribute | string | The description of imported requirements. Required for DOORS and EXCEL import. |
| additionalAttributes | [string] | A list with additional attributes. |
| settings* [{ | | |
| Array of object: A list with requirement settings.For EXCEL requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date, excel_file_path, projectName_attr (or excel_sheet_name), excel_id_attr, excel_start_row, excel_parent_id.For DOORS requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date, projectName_attr, doors_module_qualifier, doors_baseline_major, doors_baseline_minor, doors_baseline_suffix. | | |
| key* | string | For EXCEL requirement kind, the following keys are mandatory: excel_file_path, projectName_attr, excel_id_attr. The optional setting keys are: excel_start_row, excel_parent_id.For DOORS requirement kind, the following keys are mandatory: projectName_attr, doors_module_qualifier. The optional setting keys are: doors_baseline_major, doors_baseline_minor, doors_baseline_suffix. |
| value* | string | Setting value |
| }] | | |
| } | | |

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

37.3 GET /ep/requirements-import/excel

Get the Excel™ configuration template

Get the configuration with default settings for importing different kinds of requirements.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```

{
  kind*          enum          ALLOWED:EXCEL, DOORS
                                The kind of imported requirements. Allowed
                                types: EXCEL or DOORS.
  nameAttribute  string
                                The name of imported requirements. Required
                                for DOORS and EXCEL import.
  descriptionAttribute string
                                The description of imported requirements.
                                Required for DOORS and EXCEL import.
  additionalAttributes [string]
                                A list with additional attributes.
  settings* [{
    Array of object: A list with requirement settings.For EXCEL requirement kind, the following keys can be: name_attr_value, desc_attr_value,
    additional_attr, modification_date, excel_file_path, projectName_attr (or excel_sheet_name), excel_id_attr, excel_start_row,
    excel_parent_id.For DOORS requirement kind, the following keys can be: name_attr_value, desc_attr_value, additional_attr, modification_date,
    projectName_attr, doors_module_qualifier, doors_baseline_major, doors_baseline_minor, doors_baseline_suffix.
    key*    string  For EXCEL requirement kind, the following keys are mandatory: excel_file_path, projectName_attr, excel_id_attr.
                The optional setting keys are: excel_start_row, excel_parent_id.For DOORS requirement kind, the following keys
                are mandatory: projectName_attr, doors_module_qualifier. The optional setting keys are:
                doors_baseline_major, doors_baseline_minor, doors_baseline_suffix.
    value*  string  Setting value
  }]
}

```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

38. SCOPES

Handle Scopes.

38.1 GET /ep/scopes/{scope-uid}

Get a scope

Get a specific scope by providing its UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|--------------------------------------|
| *scope-uid | string | The UID of the scope to be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  uid          string  The unique identifier (UID) of this object.
  name         string  The scope name.
  topLevel     boolean True if scope is a toplevel scope.
  kind         enum    ALLOWED:SUT, DUMMY, ENVIRONMENT, HIDDEN_INTERNAL, VIRTUAL
                  Scope kind.
  path         string  Scope path.
  architecture string  The corresponding architecture of the scope.
  sampleTime {
    The sample time of the scope.
    uid      string  The unique identifier (UID) of this object.
    seconds  string  The sample time as a value given in seconds.
  }
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

38.2 GET /ep/scopes

Get a list of scopes

Get a list of scopes by a query which filters by path and top-level.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------------|---------|--|
| path | string | Enter the path of the scope you would like to search for. If null, then all scopes will be returned. |
| top-level | boolean | Specifies, if only top level scopes shall be returned. If set to 'true', only top level scopes will be returned. If set to 'false', all scopes will be returned, including the top level. If not specified, then the default value is 'false'. |
| architecture-uid | string | Specifies from which architecture the scopes are being collected. If null, then the first imported architecture will be used. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid      string  The unique identifier (UID) of this object.
    name     string  The scope name.
    topLevel boolean  True if scope is a toplevel scope.
    kind     enum    ALLOWED:SUT, DUMMY, ENVIRONMENT, HIDDEN_INTERNAL, VIRTUAL
                  Scope kind.
    path     string  Scope path.
    architecture string The corresponding architecture of the scope.
    sampleTime {
      The sample time of the scope.
        uid      string  The unique identifier (UID) of this object.
        seconds  string  The sample time as a value given in seconds.
      }
    }
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

39. SIGNALS

Handle signals' operations.

39.1 GET /ep/scopes/{scope-uid}/signals

Get all signals from a scope

Get all signals from the given scope

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The scope for which to get the signals. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid          string READ-ONLY
                  The unique identifier (UID) of this object.
    identifier    string READ-ONLY
                  The signal identifier.
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

40. STIMULI VECTORS

Handle stimuli vectors.

40.1 GET /ep/stimuli-vectors/{stimuli-vector-uid}

Get a stimuli vector

Get a specific stimuli vector by UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------------|--------|---|
| *stimuli-vector-uid | string | The UID of the stimuli vector to be returned. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
{
  uid      string  READ-ONLY
              The unique identifier (UID) of this object.
  name     string
              The name of the StimuliVector.
  length   integer
              The length of the vector.
  folderUID string
              The unique identifier of the folder the StimuliVector belongs to.
  scopeUID string
              The unique identifier of the scope the StimuliVector belongs to.
}
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

```
string
```

40.2 DELETE /ep/stimuli-vectors/{stimuli-vector-uid}

Delete a stimuli vector

Delete a stimuli vector by its UID.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------------|--------|--|
| *stimuli-vector-uid | string | The UID of the stimuli vector to be deleted. |

RESPONSE

STATUS CODE - 200: OK

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

40.3 POST /ep/stimuli-vectors-export

Export Stimuli Vectors

Long running task Export single or multiple Stimuli Vector(s) by providing the list of the stimuli vectors which will be exported, the export directory, the export format and a list of additional options for export.

REQUEST

REQUEST BODY - application/json

```
{
  UIDs*           [string] List with the UIDs of the elements which will be exported
  exportDirectory* string Directory where to export the elements
  exportFormat     enum      ALLOWED:EXCEL, CSV
                                The format of the exported stimuli vectors. It can be: "EXCEL" or "CSV". Default value is EXCEL.

  additionalOptions {
    csvDelimiter     enum      ALLOWED:SEMICOLON, COMMA, COLON, PIPE
                                Relevant only for CSV export format. It can have one of the following values: "SEMICOLON",
                                "COMMA", "COLON", "PIPE". Default value is "SEMICOLON".

    singleFile        boolean Relevant only for CSV export format: false - each vector will be exported in it's own file; true - all
                                vectors will be exported in same file. Default is 'false'

    architectureUid  string   Relevant only for Excel export format. It specifies the UID of the architecture on which the
                                interfaces of the vectors will be exported. Default is the master architecture
  }
  overwritePolicy  enum      ALLOWED:EXTEND_NAME, OVERWRITE, SKIP
                                Overwrite policy: allowed values (not case-sensitive) are: EXTEND_NAME, in which case if the
                                exported file exists on disk, its name will be extended and the original file on disk will be kept,
                                OVERWRITE, in which case the original file on disk is overwritten, if it exists. Default value is
                                EXTEND_NAME
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

40.4 GET /ep/stimuli-vectors

Get all stimuli vectors

Get all stimuli vectors.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[{
```

Array of object:

| | | |
|-----------|---------|---|
| uid | string | READ-ONLY |
| | | The unique identifier (UID) of this object. |
| name | string | The name of the StimuliVector. |
| length | integer | The length of the vector. |
| folderUID | string | The unique identifier of the folder the StimuliVector belongs to. |
| scopeUID | string | The unique identifier of the scope the StimuliVector belongs to. |
| }] | | |

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

40.5 PUT /ep/stimuli-vectors

Import stimuli vectors

Long running task Import multiple stimuli vectors from external files into a Folder by providing their path and the Folders UID. Can either overwrite or skip stimuli vectors that are already imported.

REQUEST

REQUEST BODY - application/json

```
{
```

| | | |
|------------|----------|--|
| paths* | [string] | The paths to all stimuli vectors you'd like to import. |
| vectorKind | enum | ALLOWED:TC, EXCEL The stimuli vector type. Default value is "TC" |
| folderUID | string | The UID of the folder you want to import into. |
| delimiter | enum | ALLOWED:SEMICOLON, COMMA, COLON, PIPE The CSV file delimiter, can be: "SEMICOLON", "COMMA", "COLON", "PIPE". Default value is "SEMICOLON" |

```
}
```

overwritePolicy enum

ALLOWED:EXTEND_NAME, OVERWRITE, SKIP

Decides what happens in case of duplicate names. Can be "EXTEND_NAME", "OVERWRITE" or "SKIP". Default is "SKIP".

}

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

40.6 GET /ep/folders/{folder-uid}/stimuli-vectors

Get all stimuli vectors from a folder

Get all stimuli vectors from the specified folder.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The UID of the folder from which to get stimuli vectors. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {
  Array of object:
    uid      string READ-ONLY
              The unique identifier (UID) of this object.
    name     string
              The name of the StimuliVector.
    length   integer
              The length of the vector.
    folderUID string
              The unique identifier of the folder the StimuliVector belongs to.
    scopeUID string
              The unique identifier of the scope the StimuliVector belongs to.
}]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

40.7 GET /ep/scopes/{scope-uid}/stimuli-vectors

Get all stimuli vectors from a scope

Get all stimuli vectors from the specified scope.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The UID of the scope from which to get stimuli vectors. |

RESPONSE

STATUS CODE - 200: OK

RESPONSE MODEL - application/json

```
[ {
  Array of object:
    uid      string  READ-ONLY
                  The unique identifier (UID) of this object.
    name     string
    length   integer The length of the vector.
    folderUID string  The unique identifier of the folder the StimuliVector belongs to.
    scopeUID string  The unique identifier of the scope the StimuliVector belongs to.
  } ]
```

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

41. TEST

41.1 GET /ep/test

Test the connection to the REST server

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: Request successfully sent.

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

42. TEST CASE/STIMULI VECTOR SIMULATION

Simulate TestCases.

42.1 POST /ep/folders/{folder-uid}/testcase-simulation

Simulates all Test Cases/StimuliVectors from a folder

Long running task Simulates all Test Cases/StimuliVectors from a given folder for the specified execution kinds. Optionally, simulation can be forced to not re-use any previous results.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------|--------|--|
| *folder-uid | string | The Folder UID for which the Test Cases/Stimuli Vectors are simulated. |

REQUEST BODY - application/json

| | | |
|------------------|----------|---|
| execConfigNames* | [string] | List of execution kinds (example: SIL, TL MIL, SL MIL, etc.) for which to simulate. Not case-sensitive. |
| forceExecute | boolean | Specify (optional) if the simulation should be forced (all previous results will be discarded). Default is 'false'. |

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

| | | |
|-------|--------|------------------|
| jobID | string | READ-ONLY |
| | | The ID of a job. |

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

42.2 POST /ep/folders/testcase-simulation

Simulates all Test Cases/StimuliVectors from a list of folders

Long running task Simulates all Test Cases/StimuliVectors from a given list of folders for the specified execution kinds. Optionally, simulation can be forced to not re-use any previous results.

REQUEST

REQUEST BODY - application/json

```
{
  execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.) for which to simulate. Not case-sensitive.
  forceExecute      boolean Specify (optional) if the simulation should be forced (all previous results will be discarded). Default is 'false'.
  UIDs*            [string] List with unique identifiers of the objects.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

42.3 POST /ep/scopes/{scope-uid}/testcase-simulation

Simulates all Test Cases/StimuliVectors from a scope

Long running task Simulates all Test Cases/StimuliVectors from a given scope for the specified execution kinds. Optionally, simulation can be forced to not re-use any previous results.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------------|--------|---|
| *scope-uid | string | The Scope UID for which the Test Cases/Stimuli Vectors are simulated. |

REQUEST BODY - application/json

```
{
```

| | | |
|-------------------------------|-----------------------|---|
| <code>execConfigNames*</code> | <code>[string]</code> | List of execution kinds (example: SIL, TL MIL, SL MIL, etc.) for which to simulate. Not case-sensitive. |
| <code>forceExecute</code> | <code>boolean</code> | Specify (optional) if the simulation should be forced (all previous results will be discarded). Default is 'false'. |

}

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the `Progress` i.e. GET `'/ep/progress?progress-id={progress-id}'` using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

42.4 POST /ep/scopes/testcase-simulation

Simulates all Test Cases/StimuliVectors from a list of scopes

**Long running task ** Simulates all Test Cases/StimuliVectors from a given list of scopes for the specified execution kinds. Optionally, simulation can be forced to not re-use any previous results.

REQUEST

REQUEST BODY - application/json

```
{
  execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.) for which to simulate. Not case-sensitive.
  forceExecute      boolean  Specify (optional) if the simulation should be forced (all previous results will be discarded). Default is 'false'.
  UIDs*            [string] List with unique identifiers of the objects.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the `Progress` i.e. GET `'/ep/progress?progress-id={progress-id}'` using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

42.5 POST /ep/test-cases/{testcase-uid}/testcase-simulation

Simulates a Test Case/Stimuli Vector

Long running task Simulates a Test Case/Stimuli Vector for the specified execution kinds. Optionally, also the test execution can be forced to not re-use any previous results.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|--|
| *testcase-uid | string | The Test Case/Stimuli VectorUID to simulate. |

REQUEST BODY - application/json

```
{
  execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.) for which to simulate. Not case-sensitive.
  forceExecute      boolean  Specify (optional) if the simulation should be forced (all previous results will be discarded). Default is 'false'.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

42.6 POST /ep/test-cases/testcase-simulation

Simulates all Test Cases/StimuliVectors

Long running task Simulates all Test Cases/StimuliVectors on the specified execution kinds. Optionally, simulation can be forced to not re-use any previous results.

REQUEST

REQUEST BODY - application/json

```
{
  execConfigNames* [string] List of execution kinds (example: SIL, TL MIL, SL MIL, etc.) for which to simulate. Not case-sensitive.
  forceExecute      boolean Specify (optional) if the simulation should be forced (all previous results will be discarded). Default is 'false'.
  UUIDs*           [string] List with unique identifiers of the objects.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the [Progress](#get-/ep/progress) i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
           The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

string

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

string

43. TOLERANCES

Import, reset and retrieve global and local tolerances.

43.1 POST /ep/profiles/export-global-tolerances

Export global tolerances

Use this command to export the global tolerances per usecase.

REQUEST

REQUEST BODY - application/json

```
{
  path*           string  The path to the xml file to use for import or export of tolerances.
  toleranceUseCase* enum   ALLOWED:B2B, RBT
                                     The use case of the tolerances for which tolerances should be applied. Allowed values are RBT and B2B.
}
```

RESPONSE

STATUS CODE - 202: Long running operation started. The status of the operation can be reviewed by using the Progress i.e. GET '/ep/progress?progress-id={progress-id}' using the id received by this command.

RESPONSE MODEL - application/json

```
{
  jobID string READ-ONLY
                The ID of a job.
}
```

STATUS CODE - 400: Bad Request

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 403: Forbidden

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 500: Internal server error

RESPONSE MODEL - text/plain

```
string
```

43.2 GET /ep/scopes/{scope-id}/global-tolerances

Get the global tolerances

Use this command to retrieve the global tolerances. A valid scope uid and use case must be specified. The lead-lag-unit can be either Seconds or Steps.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|------|------|-------------|
|------|------|-------------|

| NAME | TYPE | DESCRIPTION |
|-----------|--------|---|
| *scope-id | string | The scope from which to retrieve the global tolerances. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|---------------------------------|--|
| *kind | enum ALLOWED: B2B, RBT | The use case kind. Can be either RBT or B2B. |
| lead-lag-unit | enum ALLOWED: SECONDS, STEPS | For existing tolerances, lead and lag values should be displayed as either SECONDS or STEPS. Default is STEPS. |

RESPONSE

STATUS CODE - 200: Global tolerances retrieved.

RESPONSE MODEL - application/json

```
[{
  Array of object:
    uid      string  READ-ONLY
                  The unique identifier (UID) of this object.
    name     string
    lead     string
    lag      string
    absTol   string
    relTol   string
    kind     string
}]
```

STATUS CODE - 400: Bad request.

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Not found.

RESPONSE MODEL - text/plain

string

STATUS CODE - 406: Not acceptable.

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

43.3 PUT /ep/profiles/global-tolerances

Import the global tolerances

Use this command to import the global tolerances.

REQUEST

REQUEST BODY - application/json

```
{
  path*                string  The path to the xml file to use for import or export of tolerances.
  toleranceUseCase*    enum    ALLOWED:B2B, RBT
                           The use case of the tolerances for which tolerances should be applied. Allowed values are RBT and
                           B2B.
}
```

RESPONSE

STATUS CODE - 200: Global tolerances imported.

STATUS CODE - 400: Bad request.

RESPONSE MODEL - text/plain

string

STATUS CODE - 406: Not acceptable.

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

43.4 DELETE /ep/profiles/global-tolerances

Reset the global tolerances

Use this command to reset the global tolerances for the profile.

REQUEST

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------|---------------------------|--|
| *kind | enum ALLOWED: B2B, RBT | The use case kind. Can be either RBT or B2B. |

RESPONSE

STATUS CODE - 200: Global tolerances reset.

STATUS CODE - 400: Bad request.

RESPONSE MODEL - text/plain

string

STATUS CODE - 406: Not acceptable.

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

43.5 GET /ep/test-cases/{test-case-id}/local-tolerances

Get the local tolerances

Use this command to retrieve the local tolerances. A valid test case uid must be specified. The lead-lag-unit can be either Seconds or Steps. Setting the create-if-missing to true will create local tolerances from the global tolerances.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|--|
| *test-case-id | string | The UID of the test case for which local tolerances will be retrieved. |

QUERY PARAMETERS

| NAME | TYPE | DESCRIPTION |
|-------------------|---------------------------------|--|
| lead-lag-unit | enum ALLOWED: SECONDS, STEPS | For existing tolerances, lead and lag values should be displayed as either SECONDS or STEPS. Default is STEPS. |
| create-if-missing | boolean | If true, the local tolerances will be created if they do not exist yet. Default is: false. |

RESPONSE

STATUS CODE - 200: Local tolerances retrieved.

RESPONSE MODEL - application/json

```
[ {  
  Array of object:  
    uid      string  READ-ONLY  
                The unique identifier (UID) of this object.  
    name     string  
    lead     string  
    lag      string  
    absTol   string  
    relTol   string  
    kind     string  
  } ]
```

STATUS CODE - 400: Bad request.

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 404: Test case not found.

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 406: Not acceptable.

RESPONSE MODEL - text/plain

```
string
```

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

```
string
```

43.6 PUT /ep/test-cases/{test-case-id}/local-tolerances

Import the local tolerances

Import local tolerances for a given test case.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|---|
| *test-case-id | string | The UID of the test case for which local tolerances will be imported. |

REQUEST BODY - application/json

```
{
  path* string The path to the xml file to use for import or export of local tolerances.
}
```

RESPONSE

STATUS CODE - 200: Local tolerances imported.

STATUS CODE - 400: Bad request.

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Test case not found.

RESPONSE MODEL - text/plain

string

STATUS CODE - 406: Not acceptable.

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

43.7 POST /ep/test-cases/{test-case-id}/local-tolerances

Export local tolerances

Export local tolerances for a given test case.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|--|
| *test-case-id | string | The UID of the requirement-based Test Case to export the local tolerances for. |

REQUEST BODY - application/json

```
{
```

```
    path* string The path to the xml file to use for import or export of local tolerances.
}
```

RESPONSE

STATUS CODE - 200: Local tolerances exported.

STATUS CODE - 400: Bad request.

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Test case not found.

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

43.8 DELETE /ep/test-cases/{test-case-id}/local-tolerances

Reset the local tolerances

Remove the local tolerances for a test case.

REQUEST

PATH PARAMETERS

| NAME | TYPE | DESCRIPTION |
|---------------|--------|--|
| *test-case-id | string | The UID of the test case for which local tolerances will be removed. |

RESPONSE

STATUS CODE - 200: Local tolerances removed.

STATUS CODE - 400: Bad request.

RESPONSE MODEL - text/plain

string

STATUS CODE - 404: Test case not found.

RESPONSE MODEL - text/plain

string

STATUS CODE - 406: Not acceptable.

RESPONSE MODEL - text/plain

string

STATUS CODE - 500: Internal server error.

RESPONSE MODEL - text/plain

string

