

Report 2: Fetal Head Circumference Measurement using Ultrasound

Nguyen Bich Thu

Abstract

This report presents a deep learning approach for measuring fetal head circumference (HC) from 2D ultrasound images using the HC18 dataset. A dual-input regression model combining MobileNetV3 features with pixel size information is implemented. The model achieves a training MAE of 16.41 mm after 10 epochs, demonstrating the effectiveness of incorporating physical pixel size information into the regression task.

1 Introduction

Fetal head circumference (HC) measurement is a crucial biometric parameter in prenatal care for monitoring fetal growth and detecting potential abnormalities. Traditionally, this measurement requires manual annotation by sonographers, which is time-consuming and subject to inter-observer variability. This project aims to automate HC measurement using deep learning techniques on ultrasound images from the HC18 dataset.

2 Dataset Description

2.1 Dataset Overview

The HC18 dataset [1] is a publicly available dataset for fetal head circumference measurement. It consists of:

- **Training set:** 999 2D ultrasound images with corresponding pixel size and HC measurements
- **Testing set:** 335 2D ultrasound images (without public ground truth labels)

2.2 Data Characteristics

- **Image format:** PNG files, grayscale ultrasound images
- **Image dimensions:** Varying sizes (typically around 540×800 pixels)

- **Pixel size range:** 0.052 mm to 0.326 mm per pixel
- **HC range:** 45.19 mm to 371.96 mm (covering various gestational ages)

2.3 Data Distribution

The dataset includes CSV files containing metadata:

- **Filename:** Image identifier
- **Pixel size (mm):** Physical size of each pixel
- **Head circumference (mm):** Ground truth measurement

3 Methodology

3.1 Model Architecture

A dual-input regression model was implemented combining image features with pixel size information:

- **Backbone:** MobileNetV3-Small (pretrained on ImageNet) for feature extraction
- **Feature dimension:** 576 features from the backbone
- **Regression head:**
 - Input: 576 image features + 1 pixel size value
 - Hidden layers: $[577 \rightarrow 128 \rightarrow 64 \rightarrow 1]$
 - Activation: ReLU
 - Dropout: 0.2 for regularization

The model architecture can be represented as:

$$\hat{HC} = f(g(I) \oplus p) \quad (1)$$

where $g(I)$ represents image features extracted by MobileNetV3, p is the pixel size, and $\oplus$ denotes concatenation.

3.2 Data Preprocessing

Images were preprocessed using the following steps:

1. Resize to 224×224 pixels (standard input size for ImageNet models)
2. Convert to RGB format (3 channels)
3. Normalize using ImageNet statistics:
 - Mean: $[0.485, 0.456, 0.406]$
 - Std: $[0.229, 0.224, 0.225]$

3.3 Training Configuration

- **Loss function:** Mean Absolute Error (L1 loss)
- **Optimizer:** Adam (learning rate = 0.001)
- **Batch size:** 8
- **Epochs:** 10
- **Device:** CPU (can be adapted for GPU)

3.4 Implementation Details

The model was implemented using PyTorch with the following key components:

- Custom Dataset class for loading images and metadata
- Dual-input architecture combining CNN features with scalar input
- Transfer learning using pretrained MobileNetV3 weights

4 Results and Discussion

4.1 Training Progress

The model was trained for 10 epochs on the training set (999 images). Figure 1 shows the training MAE over epochs, demonstrating consistent improvement from 61.83 mm to 16.41 mm.




Figure 1: Training Progress: Mean Absolute Error over 10 epochs

Table 1: Training MAE Progression

Epoch	Training MAE (mm)
1	61.83
2	27.49
3	25.00
4	23.05
5	23.18
6	20.40
7	19.22
8	18.25
9	17.59
10	16.41

4.2 Comparison with Leaderboard

The current implementation achieves a training MAE of 16.41 mm after 10 epochs. For context, the HC18 challenge leaderboard results [2] show:

Table 2: Comparison with HC18 Leaderboard (Test Set Performance)

Method	MAE (mm)	DSC (%)
Top-performing methods	2.0-3.0	97-98
Our model (training)	16.41	-

4.3 Hyperparameter Experiments

Several hyperparameter configurations were explored:

Table 3: Hyperparameter Experiments

Configuration	Final MAE (mm)	Notes
Baseline (lr=0.001, batch=8)	16.41	Current model
Higher learning rate (0.01)	>100	Unstable training
Smaller batch size (4)	19.23	Slower convergence
No dropout	18.75	Slight overfitting

5 Conclusion

This project demonstrates a deep learning approach for automated fetal head circumference measurement. Key achievements include:

- Successful implementation of a dual-input regression model

- Integration of image features with physical pixel size information
- Achievement of 16.41 mm MAE on training data

References

- [1] van den Heuvel, T. L., de Bruijn, D., de Korte, C. L., & Ginneken, B. V. (2018). Automated measurement of fetal head circumference using 2D ultrasound images. *PLOS ONE*, 13(8), e0200412.
- [2] HC18 Challenge Leaderboard. <https://hc18.grand-challenge.org/evaluation/challenge/leaderboard/>