

Report 4: Pulmonary Nodule Detection from CT Images

Nguyen Bich Thu

Abstract

This report presents a Random Forest model for detecting pulmonary nodules from CT images using the LUNA16 dataset. The model achieves 92.41% accuracy and 93.25% sensitivity using features extracted from nodule coordinates and diameters.

1 Introduction

Early detection of pulmonary nodules (small abnormal growths in the lungs) is crucial for lung cancer diagnosis. This project implements a machine learning approach for automated nodule detection.

2 Dataset Description

2.1 LUNA16 Dataset

- **Total nodules:** 1,186 nodules from 601 CT scans
- **Features:** 3D coordinates (X, Y, Z) and diameter (mm)

coordX	coordY	coordZ	diameter_mm
-128.699	-175.319	-298.387	5.65
103.784	-211.925	-227.121	4.22
69.639	-140.945	876.374	5.79

Table 1: Sample annotations

3 Methodology

3.1 Feature Engineering

Features created from raw data:

- `x_abs`, `y_abs`, `z_abs`: Absolute coordinates
- `distance_from_origin`: $\sqrt{x^2 + y^2 + z^2}$
- `xy_ratio`, `xz_ratio`, `yz_ratio`: Coordinate ratios
- `log_diameter`: $\ln(\text{diameter} + 1)$

3.2 Dataset Composition

- **Positive samples (nodules):** 1,186
- **Negative samples (non-nodules):** 3,558 (generated)
- **Total:** 4,744 samples (80% train, 20% test)

3.3 Random Forest Model

- **Parameters:** 100 trees, max depth=10, class weight='balanced'
- **Input:** 8 features
- **Output:** Binary classification (nodule/non-nodule)

4 Results

Metric	Value
Accuracy	92.41%
AUC-ROC	0.9761
Sensitivity	93.25%
Specificity	92.13%
Precision	79.78%
F1-score	0.8599

Table 2: Performance metrics

Actual	Predicted	
	Negative	Positive
Negative	656	56
Positive	16	221

Table 3: Confusion matrix

4.1 Classification Report

Class	Precision	Recall	F1-score
No Nodule	0.98	0.92	0.95
Nodule	0.80	0.93	0.86

Table 4: Per-class performance

4.2 Feature Importance

- **distance_from_origin:** 0.312 (most important)
- **log_diameter:** 0.285
- **y_abs:** 0.158
- **x_abs:** 0.142
- **z_abs:** 0.103

5 Comparison with Other Methods

Method	Sensitivity	Specificity
Ours (Random Forest)	93.3%	92.1%
2D CNN	85-90%	88-92%
3D CNN (Basic)	90-92%	91-93%
LUNA16 Top 1	95.1%	96.2%

Table 5: Comparison with literature

6 Hyperparameter Experiments

- **Number of trees:** 100 optimal (vs 50: 91.8%, 200: 92.5%)
- **Max depth:** 10 optimal (vs 5: 89.2%, 15: 92.3%)
- **Negative ratio:** 1:3 optimal (vs 1:1: 88.7%, 1:5: 92.1%)

7 Conclusion

Key achievements:

- **92.41% accuracy** in nodule detection

- **93.25% sensitivity** (only 16/237 nodules missed)
- **Resource-efficient** model (no GPU needed)
- **Interpretable** results via feature importance

Future work: Integrate real CT patches, extract texture features, experiment with ensemble methods.