CRUISE PERFORMANCE, RANGE AND ENDURANCE with standard tanks at 1043 kg (2300 lbs)

Conditions:

Take-off weight 1043 kg (2300 lbs)
Flaps Up
Zero wind

Notes:

1. Endurance information is based on standard tanks with 127.4 l (33.6 US gal) usable fuel.
2. The table assumes 4 l (1.1 US gal) for startup and taxi; time, fuel and distance to climb and 45 min. reserve.
3. Increase true airspeed (KTAS) and maximum range (NM) by 1% per 10°C above ISA temperature.
4. Cruise Power above 75% not recommended. For economic cruise set load 70% or less.

Press. Alt.	Load	Speed		Fuel Flow		Distance	Endu-rance Time
[ft]	[%]	[KTAS]	[mph]	[l/h]	[US Gal/h]	[NM]	[Hrs]
SL	100	131	151	33.6	8.9	383	2.9
SL	90	126	145	29.6	7.8	431	3.4
SL	80	120	138	25.8	6.8	484	4.0
SL	70	114	131	22.1	5.8	551	4.8
SL	60	106	122	18.6	4.9	624	5.9
SL	50	97	112	15.3	4.0	710	7.3
2000	100	133	154	33.6	8.9	386	2.8
2000	90	128	147	29.6	7.8	435	3.3
2000	80	122	141	25.8	6.8	489	3.9
2000	70	116	133	22.1	5.8	557	4.7
2000	60	108	124	18.6	4.9	631	5.8
2000	50	99	114	15.3	4.0	718	7.2
4000	100	136	156	33.6	8.9	392	2.8
4000	90	131	150	29.6	7.8	442	3.3
4000	80	124	143	25.8	6.8	493	3.9
4000	70	118	135	22.1	5.8	562	4.6
4000	60	110	126	18.6	4.9	637	5.7
4000	50	100	115	15.3	4.0	720	7.1
6000	100	139	159	33.6	8.9	398	2.7
6000	90	133	153	29.6	7.8	445	3.2
6000	80	127	146	25.8	6.8	501	3.8
6000	70	120	138	22.1	5.8	567	4.5
6000	60	111	128	18.6	4.9	638	5.5
6000	50	102	117	15.3	4.0	728	6.9
8000	100	141	162	33.6	8.9	401	2.6
8000	90	135	156	29.6	7.8	449	3.1
8000	80	129	148	25.8	6.8	505	3.7
8000	70	122	140	22.1	5.8	572	4.4
8000	60	113	130	18.6	4.9	644	5.4
8000	50	103	119	15.3	4.0	729	6.8
10000	90	138	159	29.6	7.8	455	3.0
10000	80	131	151	25.8	6.8	509	3.6

Press. Alt.	Load	Speed		Fuel Flow		Distance	Endu-rance Time
[ft]	[%]	[KTAS]	[mph]	[l/h]	[US Gal/h]	[NM]	[Hrs]
10000	70	124	142	22.1	5.8	576	4.3
10000	60	115	132	18.6	4.9	650	5.3
10000	50	105	120	15.3	4.0	737	6.7
12000	90	140	162	29.6	7.8	458	2.9
12000	80	134	154	25.8	6.8	516	3.5
12000	70	126	145	22.1	5.8	581	4.2
12000	60	117	134	18.6	4.9	655	5.2
12000	50	106	122	15.3	4.0	737	6.5
14000	90	143	165	29.6	7.8	465	2.8
14000	80	136	157	25.8	6.8	520	3.4
14000	70	128	147	22.1	5.8	585	4.1
14000	60	119	137	18.6	4.9	661	5.1
14000	50	108	124	15.3	4.0	744	6.4
16000	80	138	159	25.8	6.8	524	3.2
16000	70	130	150	22.1	5.8	590	4.0
16000	60	121	139	18.6	4.9	666	4.9
16000	50	109	126	15.3	4.0	745	6.2
18000	80	141	162	25.8	6.8	531	3.1
18000	70	132	152	22.1	5.8	594	3.8
18000	60	123	141	18.6	4.9	671	4.8
18000	50	111	127	15.3	4.0	751	6.1

Figure 5-4a Cruise Performance, Range and Endurance with standard tanks, at 1043 kg (2300 lbs)

CRUISE PERFORMANCE, RANGE AND ENDURANCE with long-range tanks (Cessna 172N) at 1043 kg (2300 lbs)

Conditions:

Take-off weight 1043 kg (2300 lbs)
Flaps Up
Zero wind

Notes:

1. Endurance information is based on long-range tanks with 158.6 l (41.9 US gal) usable fuel.
2. The table assumes 4 l (1.1 US gal) for startup and taxi; time, fuel and distance to climb and 45 min. reserve.
3. Increase true airspeed (KTAS) and maximum range (NM) by 1% per 10°C above ISA temperature.
4. Cruise Power above 75% not recommended. For economic cruise set load 70% or less.

Press. Alt.	Load	Speed		Fuel Flow		Distance	Endu-rance Time
[ft]	[%]	[KTAS]	[mph]	[l/h]	[US Gal/h]	[NM]	[Hrs]
SL	100	131	151	33.6	8.9	505	3.9
SL	90	126	145	29.6	7.8	564	4.5
SL	80	120	138	25.8	6.8	629	5.2
SL	70	114	131	22.1	5.8	712	6.2
SL	60	106	122	18.6	4.9	802	7.6
SL	50	97	112	15.3	4.0	907	9.4
2000	100	133	154	33.6	8.9	510	3.8
2000	90	128	147	29.6	7.8	570	4.4
2000	80	122	141	25.8	6.8	636	5.2
2000	70	116	133	22.1	5.8	720	6.1
2000	60	108	124	18.6	4.9	812	7.5
2000	50	99	114	15.3	4.0	920	9.2
4000	100	136	156	33.6	8.9	519	3.7
4000	90	131	150	29.6	7.8	580	4.3
4000	80	124	143	25.8	6.8	643	5.1
4000	70	118	135	22.1	5.8	728	6.0
4000	60	110	126	18.6	4.9	822	7.3
4000	50	100	115	15.3	4.0	924	9.1
6000	100	139	159	33.6	8.9	527	3.6
6000	90	133	153	29.6	7.8	586	4.2
6000	80	127	146	25.8	6.8	655	5.0
6000	70	120	138	22.1	5.8	736	5.9
6000	60	111	128	18.6	4.9	824	7.2
6000	50	102	117	15.3	4.0	936	9.0
8000	100	141	162	33.6	8.9	532	3.5
8000	90	135	156	29.6	7.8	591	4.1
8000	80	129	148	25.8	6.8	661	4.9
8000	70	122	140	22.1	5.8	744	5.8
8000	60	113	130	18.6	4.9	834	7.1
8000	50	103	119	15.3	4.0	939	8.8
10000	90	138	159	29.6	7.8	601	4.0
10000	80	131	151	25.8	6.8	667	4.8

Press. Alt.	Load	Speed		Fuel Flow		Distance	Endu-rance Time
[ft]	[%]	[KTAS]	[mph]	[l/h]	[US Gal/h]	[NM]	[Hrs]
10000	70	124	142	22.1	5.8	751	5.7
10000	60	115	132	18.6	4.9	843	7.0
10000	50	105	120	15.3	4.0	951	8.7
12000	90	140	162	29.6	7.8	606	3.9
12000	80	134	154	25.8	6.8	678	4.7
12000	70	126	145	22.1	5.8	759	5.6
12000	60	117	134	18.6	4.9	852	6.9
12000	50	106	122	15.3	4.0	953	8.6
14000	90	143	165	29.6	7.8	616	3.8
14000	80	136	157	25.8	6.8	685	4.6
14000	70	128	147	22.1	5.8	766	5.5
14000	60	119	137	18.6	4.9	860	6.7
14000	50	108	124	15.3	4.0	964	8.4
16000	80	138	159	25.8	6.8	691	4.4
16000	70	130	150	22.1	5.8	773	5.4
16000	60	121	139	18.6	4.9	869	6.6
16000	50	109	126	15.3	4.0	967	8.3
18000	80	141	162	25.8	6.8	701	4.3
18000	70	132	152	22.1	5.8	780	5.2
18000	60	123	141	18.6	4.9	878	6.4
18000	50	111	127	15.3	4.0	977	8.1

Figure 5-4b Cruise Performance, Range and Endurance with long-range tanks, at 1043 kg (2300 lbs)