

Algol cheat sheet

v0.10.0. Algol governs what gets reviewed and records what was decided. A heuristic is never silently upgraded to verified.

Step	Command	What you get
Compile policy	<code>compile_policy.py .algol/policy.toml</code>	REVIEW.md, scanner-rules.json, routing.json, catalog.json
Route a change	<code>router.py --routing routing.json --changed <paths></code>	A recommendation per matched standard, deep-tier escalation on undo-cost. Recommends; you run it
Collect (brevity)	<code>brevlint.py --rules scanner-rules.json --root .</code>	Deterministic style and brevity evidence rows
Collect (security)	<code>seclint.py --rules scanner-rules.json --root .</code>	CWE-tagged security evidence rows, secrets masked
Policy check	<code>policy_review.py prompt --review REVIEW.md --changed <files></code>	A model-pass prompt; feed it to a model, then ingest the result
Reconcile	<code>reconcile.py --collector rows.json [--gauntlet run.json] --out record.json</code>	One record, verified kept distinct from heuristic
Deep tier	route to gauntlet, then <code>reconcile.py --gauntlet run-record.json</code>	Its verdict and Conflict Ledger fold into the record
Guard and report	wire <code>hooks.py</code> via <code>hooks.example.json</code>	A reversibility guard before a write, a collector report after

All tools are stdlib-only Python 3.11+. Full flags: `--help` on any tool, or the `references/` doc for each component.

Your data: your own repository. Policy and the record are plain files under version control. Algol sends nothing on its own.

The floor: the tool proposes; a human decides and runs the engine. No finding originates in Algol except the deterministic collector rows.