

# Rajalakshmi Engineering College

Name: Nakshatra Pa  
Email: 241901062@rajalakshmi.edu.in  
Roll no: 241901062  
Phone: 8838047354  
Branch: REC  
Department: CSE (CS) - Section 1  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_PAH

Attempt : 1  
Total Mark : 50  
Marks Obtained : 50

#### **Section 1 : Coding**

##### **1. Problem Statement**

Each customer at the bank has an Account Number, Customer Name, and an Initial Balance. The bank allows two types of transactions:

Deposit – Increases the balance. Withdrawal – Decreases the balance, but only if enough funds are available. If the withdrawal amount exceeds the available balance, the transaction should be skipped, and the balance should remain unchanged.

You are required to implement this banking system by:

Creating a class with the necessary attributes to store account details.

Using a constructor to initialize the account details when a new account is created. Providing setter methods to update the details if required. Providing getter methods to retrieve account details. Creating

objects of this class to represent different customers, where each customer can perform deposits and withdrawals.

Instructions:

Implement the class to store account details. Implement the logic for performing deposit and withdrawal transactions. Ensure that withdrawals don't exceed the available balance. After performing the transactions, print the account number, customer name, and final balance.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the account number (integer).
- The following line contains the customer name (string).
- The next line contains the initial balance (double).
- The next line contains the deposit amount (double).
- The next line contains the withdrawal amount (double).

### ***Output Format***

For each customer, print the details in the following format:

1. Account Number: <account\_number>
2. Customer Name: <customer\_name>
3. Final Balance: <final\_balance> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1234

Rahul Sharma

5000

2000

3000

Output: Account Number: 1234

Customer Name: Rahul Sharma  
Final Balance: 4000.0

**Answer**

// You are using Java  
import java.util.Scanner;

```
class Account {  
    private int accountNumber;  
    private String customerName;  
    private double balance;  
  
    public Account(int accountNumber, String customerName, double balance) {  
        this.accountNumber = accountNumber;  
        this.customerName = customerName;  
        this.balance = balance;  
    }  
  
    public void setAccountNumber(int accountNumber) {  
        this.accountNumber = accountNumber;  
    }  
  
    public void setCustomerName(String customerName) {  
        this.customerName = customerName;  
    }  
  
    public void setBalance(double balance) {  
        this.balance = balance;  
    }  
  
    public int getAccountNumber() {  
        return accountNumber;  
    }  
  
    public String getCustomerName() {  
        return customerName;  
    }  
  
    public double getBalance() {  
        return balance;  
    }  
}
```

```

    public void deposit(double amount) {
        if (amount >= 0) balance += amount;
    }

    public void withdraw(double amount) {
        if (amount <= balance) balance -= amount;
    }
}

class CityBankApp {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());
        for (int i = 0; i < n; i++) {
            int accNo = Integer.parseInt(sc.nextLine());
            String name = sc.nextLine();
            double initBal = Double.parseDouble(sc.nextLine());
            double deposit = Double.parseDouble(sc.nextLine());
            double withdraw = Double.parseDouble(sc.nextLine());

            Account acc = new Account(accNo, name, initBal);
            acc.deposit(deposit);
            acc.withdraw(withdraw);

            System.out.println("Account Number: " + acc.getAccountNumber());
            System.out.println("Customer Name: " + acc.getCustomerName());
            System.out.println("Final Balance: " + acc.getBalance());
        }
        sc.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Neha is working as a developer for CityMovie Theatre, which wants to build a system to calculate total ticket cost for movie-goers based on the number of tickets and type of seats booked.

Each customer's booking has:

Booking ID (integer) Customer Name (string) Number of Tickets (integer) Seat Type (string: "Standard", "Premium", "VIP")

The ticket prices are:

Standard – 250 units per ticket Premium – 400 units per ticket VIP – 600 units per ticket

The calculation rules:

Total Amount = Number of Tickets × Seat Price

If a customer books more than 4 tickets, they get a 10% discount on the total amount.

If the booking is for VIP seats and the total amount exceeds 3000 units, a 5% luxury tax is added after any discount.

Neha has been asked to implement this system using:

A class with attributes for booking details. A constructor to initialize booking details. Getter and Setter methods to retrieve and update booking details if required. A method to calculate the final ticket cost. Objects of the class to represent bookings.

Finally, display each customer's details and final ticket amount.

### ***Input Format***

The first line contains an integer N, representing the number of bookings.

For each booking:

- The next line contains the Booking ID (integer).
- The next line contains the Customer Name (string).
- The next line contains Number of Tickets (integer).
- The next line contains Seat Type ("Standard", "Premium", or "VIP").

### ***Output Format***

For each booking, print:

- Booking ID: <booking\_id>
- Customer Name: <customer\_name>
- Final Ticket Amount: <final\_amount> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

1001

Ravi Kumar

3

Standard

Output: Booking ID: 1001

Customer Name: Ravi Kumar

Final Ticket Amount: 750.0

### **Answer**

// You are using Java

```
import java.util.*;
```

```
class movie{
```

```
    int bid;
```

```
    String cname;
```

```
    int tickets;
```

```
    String stype;
```

```
    movie(int bid,String cname,int tickets,String stype){
```

```
        this.bid=bid;
```

```
        this.cname=cname;
```

```
        this.tickets=tickets;
```

```
        this.stype=stype;
```

```
    }
```

```
    public void price_calc(){
```

```
        double price=0;
```

```
        if(stype.equals("Standard")){
```

```
            price=(tickets*250);
```

```
        }
```

```
        else if(stype.equals("Premium")){
```

```
            price=(tickets*400);
```

```
        }
```

```
        else if(stype.equals("VIP")){
```

```

        price=(tickets*600);
    }
    if(tickets>4){
        price=price-(price*0.1);
    }
    if(stype.equals("VIP") && price>3000){
        price=price+(price*0.05);
    }
    System.out.printf("Final Ticket Amount: %.1f",price);
}
public void print(){
    System.out.println("Booking ID: "+bid);
    System.out.println("Customer Name: "+cname);
}
}
}
class main{
    public static void main(String [] args){
        Scanner n=new Scanner(System.in);
        int test=n.nextInt();
        String sq0=n.nextLine();
        for(int i=0;i<test;i++){
            int bid=n.nextInt();
            String sq=n.nextLine();
            String cname=n.nextLine();
            int tickets=n.nextInt();
            String sq1=n.nextLine();
            String stype=n.nextLine();
            movie c1=new movie(bid,cname,tickets,stype);
            c1.print();
            c1.price_calc();}
        }
    }
}

```

**Status :** Correct

**Marks : 10/10**

### 3. Problem Statement

Anjali is working as a developer for CityFitness Gym, which wants to build a system to calculate monthly membership fees for gym members based on the type of membership and the number of personal training sessions

booked.

Each member's record has:

Member ID (integer) Member Name (string) Membership Type (string: "Basic", "Premium", "Elite") Number of Personal Training Sessions (integer)

The monthly fees are:

Basic – 1000 units Premium – 1500 units Elite – 2000 units

The cost of personal training sessions is 500 units per session.

The calculation rules:

Total Amount = Membership Fee + (Number of Personal Training Sessions × 500) If the number of sessions is more than 5, a 10% discount is applied on the total amount. If the member has Elite membership and the total amount exceeds 4000, an additional 5% service tax is added after discount.

Anjali has been asked to implement this system using:

A class with attributes for member details. A constructor to initialize member details. Getter and Setter methods to retrieve and update member details if required. A method to calculate the final monthly fee. Objects of the class to represent members.

Finally, display each member's details and the final monthly fee.

### ***Input Format***

The first line contains an integer N, representing the number of members.

For each member:

- Next line contains Member ID (integer)
- Next line contains Member Name (string)
- Next line contains Membership Type ("Basic", "Premium", "Elite")
- Next line contains Number of Personal Training Sessions (integer)

### ***Output Format***

For each member, print:



- Member ID: <member\_id>
- Member Name: <member\_name>
- Final Monthly Fee: <final\_fee> (The final fee must be rounded to one decimal place)

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1  
1001  
Ravi Kumar  
Basic  
3

Output: Member ID: 1001  
Member Name: Ravi Kumar  
Final Monthly Fee: 2500.0

### **Answer**

// You are using Java  
import java.util.\*;

```
class gym{
    int mid;
    String mname;
    String mtype;
    int sess;
    gym(int a,String b,String c,int d){
        this.mid=a;
        this.mname=b;
        this.mtype=c;
        this.sess=d;
    }
    public void calc_fee(){
        double fee=0;
        if(mtype.equals("Basic"))
            fee=1000+(sess*500);
        else if(mtype.equals("Premium"))
            fee=1500+(sess*500);
    }
}
```

```

        else if(mtype.equals("Elite"))
            fee=2000+(sess*500);

        if(sess>5){
            fee=fee-(fee*0.1);
        }
        if(mtype.equals("Elite") && fee>4000){
            fee=fee+(fee*0.05);
        }
        System.out.printf("Final Monthly Fee: %.1f",fee);

    }
    public void print(){
        System.out.println("Member ID: "+mid);
        System.out.println("Member Name: "+mname);
    }
}

class main{
    public static void main(String[] args){
        Scanner n=new Scanner(System.in);
        int test=n.nextInt();
        for(int i=0;i<test;i++){
            int a=n.nextInt();
            String sq=n.nextLine();
            String b=n.nextLine();
            String c=n.nextLine();
            int d=n.nextInt();
            gym g1=new gym(a,b,c,d);
            g1.print();
            g1.calc_fee();
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Neha is working as a developer for CityQuiz Platform, which wants to build

a system to calculate quiz scores and identify top scorers among participants.

Each participant's record has:

Participant ID (integer) Participant Name (string) An array of scores in 5 quiz rounds (integers, each between 0 and 100)

The system must calculate:

Total Score = sum of scores in all 5 rounds. Average Score = Total Score ÷ 5. If a participant scores above 80 in all rounds, a bonus of 10 points is added to the total score. Identify the Top Scorer among all participants. If two participants have the same total score, the one with the lower Participant ID is considered the top scorer.

Neha has been asked to implement this system using:

A class with attributes for participant details. A constructor to initialize participant details. Getter and setter methods to retrieve or update participant details. A method to calculate total score and average score (including bonus if applicable). Objects of the class to represent participants.

Finally, display each participant's details and announce the Top Scorer.

### ***Input Format***

The first line of input contains an integer N, representing the number of participants.

For each participant:

- Next line: Participant ID (integer)
- Next line: Participant Name (string)
- Next line: 5 integers separated by spaces (scores for 5 quiz rounds)

### ***Output Format***

For each participant:

- Participant ID: <participant\_id>
- Participant Name: <participant\_name>

- Total Score: <total\_score>
- Average Score: <average\_score>

Finally, print "Top Scorer: <participant\_name> with <total\_score> points"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

1001

Ravi Kumar

85 90 88 92 87

Output: Participant ID: 1001

Participant Name: Ravi Kumar

Total Score: 452

Average Score: 90

Top Scorer: Ravi Kumar with 452 points

### **Answer**

// You are using Java

import java.util.\*;

```
class Participant{
    int pid;
    String pname;
    int [] scores;
    int sum;
    int avg;
    Participant(int pid,String pname,int[] scores){
        this.pid=pid;
        this.pname=pname;
        this.scores=scores;
    }
    public int points(){
        int sum=0;
        int f=0;
```

```

        for(int i=0;i<scores.length;i++){
            if(scores[i]>80){
                f+=1;
            }
            sum+=scores[i];
        }
        if(f==5){
            sum+=10;
        }
        return sum;
    }
    public void print(){
        System.out.println("Participant ID: "+pid);
        System.out.println("Participant Name: "+pname);
    }
}

```

```

class main{
    public static void main(String [] args){
        Scanner n=new Scanner(System.in);
        int test=Integer.parseInt(n.nextLine());
        String topper=" ";
        int top_score=0;
        int top_id=0;
        for(int i=0;i<test;i++){
            int pid=Integer.parseInt(n.nextLine());
            String pname=n.nextLine();
            int [] scores=new int[5];
            String [] s=(n.nextLine().split(" "));

            for(int j=0;j<s.length;j++){
                scores[j]=Integer.parseInt(s[j]);
            }
            Participant p1=new Participant(pid,pname,scores);
            p1.print();
            System.out.println("Total Score: "+p1.points());
            System.out.println("Average Score: "+p1.points()/5);
            if(top_score==p1.points()){
                if(top_id>p1.pid){
                    top_score=p1.points();
                    topper=p1.pname;
                }
            }
        }
    }
}

```

```

        top_id=p1.pid;
    }
}
if(top_score<p1.points()){
    top_score=p1.points();
    topper=p1.pname;
    top_id=p1.pid;
}
}
System.out.println("Top Scorer: "+topper+" with "+top_score+" points");
}
}

```

**Status :** Correct

**Marks : 10/10**

## 5. Problem Statement

Ravi is working as a developer for SecureLogin Systems, which wants to build a system to evaluate the strength of user passwords.

Each user record has:

User ID (integer) User Name (string) Password (string)

The system must calculate whether a password is strong or weak.

A password is considered strong if it meets all of the following conditions:

At least 8 characters long. Contains at least one uppercase letter. Contains at least one lowercase letter. Contains at least one digit. Contains at least one special character (from !@#\$%^&\*).

Ravi has been asked to implement this system using:

A class with attributes for user details. A constructor to initialize user details. Getter and setter methods to retrieve or update user details. A method to check whether the password is strong. Objects of the class to represent users.

Finally, display each user's details and indicate whether their password is Strong or Weak.

### ***Input Format***

The first line contains an integer N, representing the number of users.

For each user:

The next line contains the User ID (integer).

The next line contains the User Name (string).

The next line contains the Password (string).

### ***Output Format***

For each user, print the details in the following format:

User ID: <user\_id>

User Name: <user\_name>

Password: <password>

Password Strength: <Strong/Weak>

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1001

Ravi Kumar

Abc@1234

Output: User ID: 1001

User Name: Ravi Kumar

Password: Abc@1234

Password Strength: Strong

### ***Answer***

```
// You are using Java
import java.util.*;
```

```

class User{
    int user_id;
    String name;
    String pass;
    User(int user_id,String name,String pass){
        this.user_id=user_id;
        this.name=name;
        this.pass=pass;
    }
    public void print(){
        System.out.println("User ID: "+user_id);
        System.out.println("User Name: "+name);
        System.out.println("Password: "+pass);
    }
    public void strength(){
        String spl="!@#$%^&*";
        int u=0,l=0,d=0,s=0;
        if(pass.length()>=8){
            for(int i=0;i<pass.length();i++){
                if(pass.charAt(i)>='A'&&pass.charAt(i)<='Z'){
                    u+=1;
                }
                else if(pass.charAt(i)>='a'&&pass.charAt(i)<='z'){
                    l+=1;
                }
                else if(pass.charAt(i)>='0'&&pass.charAt(i)<='9'){
                    d+=1;
                }
                else{
                    for(int j=0;j<spl.length();j++){
                        if(spl.charAt(j)==pass.charAt(i)){
                            s+=1;
                            break;
                        }
                    }
                }
            }
        }
        if(u>0 && l>0 && d>0 && s>0){
            System.out.println("Password Strength : Strong");
        }
    }
}

```



```
        else{
            System.out.println("Password Strength : Weak");
        }
    }
    else{
        System.out.println("Password Strength : Weak");
    }
}
}
```

```
class main{
    public static void main(String [] args){
        Scanner n=new Scanner(System.in);
        int test=Integer.parseInt(n.nextLine());
        for(int i=0;i<test;i++){
            int user_id=Integer.parseInt(n.nextLine());
            String name=n.nextLine();
            String pass=n.nextLine();
            User u1=new User(user_id,name,pass);
            u1.print();
            u1.strength();
        }
    }
}
```

**Status :** Correct

**Marks :** 10/10