

# PlainT<sub>E</sub>X Verbatim

Benjamin T. Shepard

July 9, 2022

An inline verbatim such as `this is \inline` can be made with the code `|...|`. If visible spaces are desired, use `@|...|` instead, which will produce `thisis\inline`. A display verbatim such as

`this is \display`

can be made with `||...||`. If visible spaces are desired, use `@||...||` instead, which will produce

`thisis\display.`

Every normal T<sub>E</sub>X character (except `|`) as well as all of the special characters can be used inside this environment, as shown in the following example:

```
!$@#$%^&*()-+=\ /.,:;`~th@<is$ ]\bye *is{ #a '1\rho > *\tes<t* \undefined .??"
```

Normally, the pipe character `|` can only be used inside the display verbatim `||...||`. However, the macros `\makepipeother` and `\makepipeactive` turn the character `|` into an innocent character and into an active character, respectively. There is also the macro `\pipe` which expands to `\bgroup\string|\egroup`. These commands allow for use of the pipe literal `|` in horizontal mode. For example, both

```
{\tt th\pipe{s is a pipe}}
```

and

```
\makepipeother{\tt th|s is a pipe}\makepipeactive
```

will display `th|s is a pipe`. Of course, these macros cannot be used inside the `|...|` or `||...||` environments. In contrast, the character `@` is able to be used normally, provided that it is not proceeded by the pipe character; T<sub>E</sub>X will recognize the sequence `@|` as the beginning of a verbatim environment.

These verbatim environments obey spaces, lines, and blank lines; this allows for code insertion such as

```
void dfs(int p){
    if(o[p]) return;
    o[p]=1;

    c[p]=t++;
    for(int i=0; i<s[p].size(); ++i){
        dfs(s[p][i]);
    }
}
```

which will compile as expected.

Oops, the very long line of code is here, it does not fit into the line width unfortunately.

As a backup (in case | is needed), the four commands `\bverb...\everb` and `\bverbatim...\verbatim` are provided as substitutes for `|...|` and `||...||`. Furthermore, the commands `\bverb` and `\bverbs` gobble the first space of their argument. However, these environments cannot be used with `@`; instead, use `\bverbs...\everbs` and `\bverbatim...\everbatims`. Use this command in front of either environment for visible spaces. For example, the code

```
\bverbs this is a \test\everbs
```

will display `this is a \test`. These commands can also be used to display the | character: the code

```
\bverb th|s is a pipe\everb
```

will display `th|s is a pipe`, as expected. When the `\bverb` macro is executed,  $\text{\TeX}$  turns every available character innocent until it scans the exact sequence `\everb`.

asdfasdfadsf

asdf

asdfasdfadf

asdfasdfadsf

asdf

asdfasdfadf