

THE HONG KONG POLYTECHNIC UNIVERSITY
DEPARTMENT OF COMPUTING
EXAMINATION

Subject : COMP5112 Data Structures and Database Systems

Session : 2023 / 2024 Semester II

Date : 9 May 2024

Time : 19:00 – 21:00

Time Allowed: 2 Hours

Subject Examiner(s): Dr HUA Wency

This question paper has a total of 5 pages.
(Some pages may be intentionally omitted.)


Instructions to Candidates:

- This is a closed-book exam – no written materials permitted.
- You are allowed to use a calculator.
- Answer ALL questions in the answer book provided.
- All the answers must be written in English.
- Write down your name and student ID in the answer book provided.

Do not turn over the page until you are told to do so!

Question 2. Data Structures**[15 marks]**

- [1] Consider the following AVL tree. Show the running steps of inserting node 27 and rebalancing the AVL tree after the insertion.



- [2] Write an algorithm (pseudocode) to merge two unsorted arrays A and B into a new array C that is sorted in descending order by using max-heaps. For example, given arrays $A = | 4 | 9 | 1 | 7 |$ and $B = | 3 | 8 | 5 |$, the new array $C = | 9 | 8 | 7 | 5 | 4 | 3 | 1 |$.

Question 3. Sorting Algorithms**[10 marks]**

Suppose we need to sort array A with 6 numbers in ascending order by the insertion-sort algorithm.

- [1] Suggest a best-case input for the array A . Calculate the number of comparisons needed.
- [2] Suggest a worst-case input for the array A . Calculate the number of comparisons needed.
- [3] Show the running steps of the insertion-sort algorithm (i.e., the updated array after each swap) for the following array A .

	0	1	2	3	4	5
A	85	91	72	67	80	88

Question 4. SQL and Relational Algebra**[10 marks]**

Consider the following relations in a *Company* database:

Employee (ENO, EName, Email, Salary)
 Department (DNO, DName, Budget, City)
 Job (JNO, JName)
 Work (ENO, DNO, JNO, Duration)

The *ENO*, *DNO*, and *JNO* attributes in the *Work* relation are foreign keys referencing *Employee*, *Department*, and *Job*, respectively.


- [1] Write each of the following queries in SQL:
- Get the maximum and minimum salary for each department.
 - Get the names of employees who have worked in more than one departments.

- (c) Get the names of departments that have no sufficient budget to pay for employee salary.
- [2] Write each of the following queries in relational algebra:
- Get the names of employees who have worked in the department with DNO = 'D1'.
 - Get the names of employees who have not worked for the job with JNO = 'J1'.

Question 5. ERD, Table Design, and Normalization

[20 marks]

- [1] Convert the following ER diagram into a set of relation schemas. Specify the primary key(s) and foreign key(s) for each relation.




- [2] Consider the relation $R = (A, B, C, D, E)$ and the set of functional dependencies $F = \{A \rightarrow BC, BCD \rightarrow E, B \rightarrow D, A \rightarrow D, E \rightarrow A\}$.
- Identify the candidate key(s) for R .
 - Compute the canonical cover for F .
 - Conduct 3NF decomposition for R which is lossless-join and dependency-preserving.

Question 6. Data Storage and Indexing

[10 marks]

- [1] Consider the following B⁺-tree, where the tree order = 4 (i.e., maximum number of pointers in each tree node). Show the updated B⁺-tree after inserting the key "18".



- [2] Consider the following *Employee* relation. Build a hash index based on the *EID* attribute. The hash function is $H(EID) = \text{SUM}(EID) \bmod 4$, where $\text{SUM}(EID)$ adds up all the numbers in the *EID*, e.g., $\text{SUM}(321321321) = 3+2+1+3+2+1+3+2+1 = 18$. Assume that each bucket can store 3 keys, and bucket overflow is handled by overflow chaining.

EID	Name	Salary	DeptNo
554433221	Doug Gilbert	80000	1
543216789	Joyce Pan	70000	1
333445555	Frank Wong	75000	2
987654321	Jennifer Wallace	54000	2
123456789	John Smith	56000	3
666884444	Ramesh Narayan	66000	3
453453453	Joyce Huang	60000	3
888665555	James Borg	83000	3
999887777	Alicia Zelaya	92000	4
123675134	Ahmad Jabbar	85000	4
987987989	Helen Fei	60000	4

Question 7. Query Processing and Optimization**[15 marks]**

Consider the following relations in a *University* database:

Student (SID, SName, SType, Email, DID)


Department (DID, DName, Location, Budget)

The *DID* attribute in the *Student* relation is a foreign key referencing the *Department* relation. *DName* is a unique attribute in the *Department* relation.

[1] Given the following SQL query:

```
SELECT S.SName, S.Email, D.Location
FROM Student S, Department D
WHERE S.DID = D.DID AND S.SType = 'Domestic' AND D.DName = 'CS';
```

The initial query tree is illustrated as follows:



Show the most efficient query tree after applying all the five steps of query tree optimization.

- [2] Suppose the *Student* relation contains 50000 tuples, with each disk block stores 10 tuples; the *Department* relation contains 200 tuples, with each disk block stores 20 tuples. Both relations are stored as sequential files. *Student* is ordered by *SID* and *Department* is ordered by *DID*. The memory size is 40 blocks. What is the cost of *Student* ⋈ *Department* (natural join) using the merge-join algorithm? Show your calculation process and result.