

TopoAna: A generic tool for the topology analysis of inclusive Monte-Carlo samples in high energy physics experiments

Xingyu Zhou^{a,*}, Shuxian Du^b, Gang Li^c, Chengping Shen^{d,*}

^a*School of Physics, Beihang University, Beijing 100191, China*

^b*School of Physics and Microelectronics, Zhengzhou University, Zhengzhou 450000, China*

^c*Institute of High Energy Physics, Chinese Academy of Sciences, Beijing 100049, China*

^d*Key Laboratory of Nuclear Physics and Ion-beam Application (MOE) and Institute of Modern Physics, Fudan University, Shanghai 200443, China*

Abstract

1 Inclusive Monte-Carlo samples are indispensable for signal selection and background suppression in many high energy physics experiments. A clear knowledge of the topology of the samples, including the types of physics processes and the number of processes in each type, is a great help to investigating signals and backgrounds. To help analysts obtain the topology knowledge from the truth information of the samples, we develop a topology analysis program, TopoAna, with C++, ROOT, and LaTeX. The program implements the functionalities of component analysis and signal identification with many kinds of fine, customizable clustering and matching algorithms. It tags physics processes in individual events accurately in the output root files, and exports the obtained topology information at the sample level clearly to the output plain text, tex source, and pdf files. Independent of specific software frameworks, the program is applicable to many experiments. At present, it has come into use in three e^+e^- colliding experiments: the BESIII, Belle, and Belle II experiments. The use of the program in other experiments is also prospective.

13 **Keywords:** event topology; component analysis; signal identification; inclusive Monte-Carlo samples; high energy physics experiments

PROGRAM SUMMARY

17 *Program title:* TopoAna

18 *Licensing provisions:* MIT

19 *Programming language:* C++

20 *Operating system:* Linux

21 *Nature of problem:* A clear knowledge of the topology of inclusive Monte-Carlo samples is a great help to investigating signals and backgrounds in many high energy physics experiments. However, the raw topology truth information of the samples is counter-intuitive, diverse, and overwhelming, which makes it difficult for analysts to check the topology of the samples directly.

25 *Solution method:* Based on accurate pattern recognition, many kinds of fine, customizable clustering and

*Corresponding author.

E-mail address: zhouxu@buaa.edu.cn, shencp@fudan.edu.cn

The program is now available at <https://github.com/buaazhouxingyu/topoana>.

Preprint submitted to Computer Physics Communications

February 11, 2020

26 *matching algorithms are implemented in this program, in order to help analysts obtain the topology knowl-*
 27 *edge of the samples from their raw topology truth information.*
 28 *Unusual features: Besides the C++ Standard Template Library, this program makes use of ROOT [1], a*
 29 *C++ based data analysis software universally used in modern high energy physics experiments. In addition,*
 30 *the program employs the Linux command, pdflatex, to compile the tex source files into the pdf documents.*
 31
 32 [1] ROOT User's Guide, Available online: <https://root.cern/root/html/doc/guides/users-guide/ROOTUsersGuide.html>.

33 1. Introduction

34 One of the most important tasks in the data analysis of high energy physics experiments is
 35 to select signals, or in other words, to suppress backgrounds. As for the task, inclusive/generic
 36 Monte-Carlo (MC) samples are extremely useful, in that they provide basic, though not per-
 37 fect, descriptions of the signals and/or backgrounds involved. However, due to the similarities
 38 between signals and some backgrounds, it usually takes efforts to establish a set of selection
 39 criteria that retain a high signal efficiency and meanwhile keep a low background level. Further
 40 optimization of preliminary criteria is often needed in the process. Under the circumstances, a
 41 comprehensive understanding of the samples is required. In particular, a clear knowledge of the
 42 topology of the samples is quite helpful. To be specific, the topology information includes the
 43 types of physics processes and the number of processes in each type, involved both in the entire
 44 samples and in the individual events. Here, the physics process could be a complete production
 45 and decay process involved in an event, or merely a part of it, such as the decay of an intermediate
 46 resonance. With the information, one can figure out the main backgrounds (especially the peak-
 47 ing ones), and optimize the selection criteria further by analyzing the differences between the
 48 main backgrounds and the signals. Even if it is difficult to further suppress these backgrounds,
 49 the knowledge of their topology is beneficial to estimate the systematic uncertainties associated
 50 with them.

51 The analysis of the topology information described above is a sort of component analysis,
 52 or in technical words, cluster analysis. It is complex since it has to classify physics processes
 53 actively and finely. Another sort of topology analysis often required in practice is signal iden-
 54 tification, which only aims to search for certain processes of interests. It is relatively simple
 55 because its core technique is merely pattern matching. Mostly, signal and background events
 56 coexist in the inclusive MC samples. It is meaningful to differentiate them in such cases. The
 57 identified signal events can be used to make up a signal sample (removed to avoid repetition) in
 58 the absence (presence) of specialized signal samples. Occasionally, we have to pick out some
 59 decay branches in order to re-weight them according to new theoretical predictions or updated
 60 experimental measurements. Signal identification also plays a part in this occasion.

61 However, since the raw topology truth information of inclusive MC samples is counter-
 62 intuitive, diverse, and overwhelming, it is difficult for analysts to check the topology of the
 63 samples directly. To help them do the checks quickly and easily, a topology analysis program
 64 called TopoAna is developed with C++, ROOT [1], and LaTeX. Here, C++ is the programming
 65 language, ROOT is the C++ based data analysis software universally used in modern high energy
 66 physics experiments, and LaTeX is used for generating pdf documents containing the obtained
 67 topology information. The program implements the functionalities of component analysis and
 68 signal identification based on accurate pattern recognition. To meet a variety of practical require-
 69 ments, many kinds of fine, customizable clustering and matching algorithms are implemented in

the program. Generally, the program recognizes, categorizes, and counts physics processes in each event in the samples, and tags them in the corresponding entry of the output root (TFile [2]) files. After processing the events, the program exports the obtained topology information at the sample level to the output plain text, tex source, and pdf files.

The program is applicable to inclusive MC samples at any data analysis stage of high energy physics experiments. In the overwhelming majority of situations, it is run over the samples which have undergone some selections, in order to examine the signals and backgrounds in the selected samples as well as the effect of the imposed selections. In such situations, the results of topology analysis are usually used together with other quantities for physics analysis. In spite of this, applying the program to the samples without undergoing any selection facilitates us to validate the generators and decay cards that produce the samples and helps novices get familiar with the topology of the samples.

Not relying on any specific software frameworks, the program applies to many high energy physics experiments. At first, the program was developed for the BESIII experiment, an experiment in the τ -Charm energy region with abundant research topics under study [3, 4]. Then, it was extended substantially for the Belle II experiment, which is primarily dedicated to search for physics beyond the Standard Model in the flavor sector and has already started data taking in the recent two years [5]. Besides, the program has also been tried and used in the Belle experiment, the predecessor of the Belle II experiment, where some physics studies are still ongoing [6].

This paper gives an essential description of TopoAna. It proceeds as follows: Section 2 introduces the basics of the program; Sections 3 and 4 expatiate the two categories of functionalities of the program — component analysis and signal identification, respectively; Section 5 presents some common settings for the executing of the program; Section 6 summarizes the paper. It is worth mentioning here that, aside from the essential description in the paper, a detailed description of the program can be found in the file “user_guide_v*.pdf” under the directory “share” of the package.

2. Basics of the program

This section introduces the basics of the program, including the package, input, execution, and output of the program. The package implements the program via a C++ class called “topoana” and a main function invoking the class. Compiling the package creates the executable file of the program, that is, “topoana.exe”. To execute the program, we have to first obtain the input data of the program, namely the raw topology truth information of the inclusive MC samples, with some interfaces to the program in the software systems of the corresponding experiments. Normally, the input data contain all the topology information of the samples. With the data, all kinds of the topology analysis presented in the paper can be performed.

To carry out the topology analysis desired in our work, we have to provide some necessary input, functionality, and output information to the program. The information is required to be filled in the setting items designed and implemented in the program, and the items have to be put in a plain text file named with a suffix “.card”. With the card file, one can execute the program with the command line: “topoana.exe cardFileName”, where the argument “cardFileName” is optional and its default value is “topoana.card”. After the execution of the program, we can examine the results of topology analysis in the output files and use them to analyze other experimental quantities. The results help us gain a better understanding of the signals and backgrounds and are conducive to carrying our work forward. In the next four subsections, we will present the package, input, execution, and output of the program in detail, with each part in one subsection.

2.1. Package of the program

The package consists of six directories — “include”, “src”, “bin”, “share”, “examples”, and “utilities” — and five files — “LICENSE”, “README.md”, “Configure”, “Makefile”, and “Setup”. While the directory “include” only includes one header file “topoana.h”, the directory “src” contains sixty source files “*.cpp” as well as a script file “topoana.C”. At present, only one class, namely “topoana”, is defined in the program for all of its functionalities. The class is declared in “topoana.h”, implemented in “*.cpp” files, and invoked in “topoana.C”.

The file “template_topoana.card” under the directory “share” saves all the items which are developed for users to specify information for the execution of the program. One can refer to the file when filling in the cards for their own needs. Some plain text files “pid_3pchrg_txtpnm_texpnm_iccp.dat_*” are also included in the directory “share”. They store the basic information of the particles used in the program. The suffixes of their names indicate the experiments they apply to. One of them will be copied to “pid_3pchrg_txtpnm_texpnm_iccp.dat” when we set up the program. Besides, the directory “share” also contains three LaTeX style files “ geometry.sty”, “ifxetex.sty”, and “makecell.sty”, which are invoked by the program for generating pdf files. The directory “examples” includes plenty of detailed examples. Particularly, all the examples involved in this paper are under its sub-directory “in_the_paper”. The directory “utilities” contains some useful bash scripts.

The program is released under MIT license [7]. The file “README.md” briefly introduces how to install and use the program. To set up the program, one should first set the package path with the command “./Configure”. Standard outputs of the command are the guidelines for manually adding the absolute path of “topoana.exe” to the environment variable “PATH”, in order to execute it without any path. The second step is executing the command “make”. This command compiles the header, source, and script files into the executable file “topoana.exe” under the directory “bin”, according to the rules specified in the “Makefile”. The last step is specifying the experiment name with the command line “./Setup experimentName”. Currently, the supported experiment names are “BESIII”, “Belle”, and “Belle_II”. Besides, “./Setup Example” is required for the execution of the examples in the paper.

2.2. Input of the program

The input of the program is one or more root files including a TTree [8] object which has some TBranch [9] objects containing the raw topology truth information of the inclusive MC samples under study. To be specific, the information in each entry of the TTree object consists of the following three ingredients associated with the particles produced in an event of the samples: the number of particles, PDG [10] codes of particles, and mother indices of particles. Notably, the particles do not include the initial state particles (e^+ and e^- in e^+e^- colliding experiments), which are default and thus omitted. Besides, the indices of particles are integers starting from zero (included) to the number of particles (excluded); they are obvious and hence not taken as an input ingredient for topology analysis. Equation (1) shows an example of the input data.

Number of particles	:	63	
PDG codes of particles	:	300553,	
		-511, 511, -433, 421, 211, 22, -413, 111, 111, 113,	
		211, -431, 22, -323, 213, -421, -211, 22, 22, 22,	
		22, 211, -211, 333, 11, -12, 22, -311, -211, 211,	
		111, 221, 331, 321, -321, 310, 22, 22, 111, 111,	
		111, 111, 111, 221, 111, 111, 22, 22, 22, 22,	
		22, 22, 22, 22, 22, 22, 22, 22, 22, 22,	
		22, 22	(1)
Mother indices of particles	:	-1,	
		0, 0, 1, 1, 1, 1, 2, 2, 2, 2,	
		2, 3, 3, 4, 4, 7, 7, 8, 8, 9,	
		9, 10, 10, 12, 12, 12, 12, 14, 14, 15,	
		15, 16, 16, 24, 24, 28, 31, 31, 32, 32,	
		32, 33, 33, 33, 36, 36, 39, 39, 40, 40,	
		41, 41, 42, 42, 43, 43, 44, 44, 45, 45,	
		46, 46	

The complete physics process contained in the data is displayed as follows.

0	$e^+e^- \rightarrow \Upsilon(4S)$	-1	9	$\rho^+ \rightarrow \pi^0\pi^+$	6
1	$\Upsilon(4S) \rightarrow B^0\bar{B}^0$	0	10	$K^{*-} \rightarrow \pi^- \bar{K}^0$	6
2	$B^0 \rightarrow \pi^0\pi^0\rho^0\pi^+D^{*-}$	1	11	$D_s^- \rightarrow e^- \bar{\nu}_e \phi \gamma$	7
3	$\bar{B}^0 \rightarrow \pi^+ D^0 D_s^{*-} \gamma$	1	12	$\eta \rightarrow \pi^0\pi^0\pi^0$	8
4	$\rho^0 \rightarrow \pi^+\pi^-$	2	13	$\eta' \rightarrow \pi^0\pi^0\eta$	8
5	$D^{*-} \rightarrow \pi^- \bar{D}^0$	2	14	$\bar{K}^0 \rightarrow K_S^0$	10
6	$D^0 \rightarrow \rho^+ K^{*-}$	3	15	$\phi \rightarrow K^+ K^-$	11
7	$D_s^{*-} \rightarrow D_s^- \gamma$	3	16	$\eta \rightarrow \gamma\gamma$	13
8	$\bar{D}^0 \rightarrow \eta\eta'$	5	17	$K_S^0 \rightarrow \pi^0\pi^0$	14

Here, the decay branches in the process are placed into two blocks in order to make full use of the page space. In both blocks, the first, second, and third columns are the indices, textual expressions, and mother indices of the decay branches. Notably, all the decay branches of $\pi^0 \rightarrow \gamma\gamma$ are omitted in Eq. (2) in order to make the process look more concise. Since the topology diagram of such a process looks like a tree, we refer to the complete processes as decay trees. Obviously, the input data do not show the structure automatically. Thus, we need the program to do the topology analysis work.

From the first branch in Eq. (2), only one particle $\Upsilon(4S)$ is produced after the e^+e^- annihilation. Thus, $\Upsilon(4S)$ can be referred to as the root particle of the decay tree. Similarly, many other resonances with the quantum numbers $J^{PC} = 1^{--}$, such as J/ψ , can be solely produced at other proper energy points. Besides the cases with only one root particle, the program can deal with the cases with multiple root particles. For example, the program can recognize the following raw topology truth information

Number of particles	:	25
PDG codes of particles	:	433,
		-321, 223, 211, -413, 431, 111, 211, -211, 111, -411,
		111, 321, 113, 22, 22, 22, 22, 321, -211, -211,
		22, 22, 211, -211
Mother indices of particles	:	-1,
		-1, -1, -1, -1, 0, 0, 2, 2, 2, 4,
		4, 5, 5, 6, 6, 9, 9, 10, 10, 10,
		11, 11, 13, 13

as the following process

$$\begin{array}{llll}
0 & e^+ e^- \rightarrow \pi^+ \omega K^- D^{*-} D_s^{*+} & -1 & 4 \quad D^- \rightarrow \pi^- \pi^- K^+ \quad 2 \\
1 & \omega \rightarrow \pi^0 \pi^+ \pi^- & 0 & 5 \quad D_s^+ \rightarrow \rho^0 K^+ \quad 3 \\
2 & D^{*-} \rightarrow \pi^0 D^- & 0 & 6 \quad \rho^0 \rightarrow \pi^+ \pi^- \quad 5 \\
3 & D_s^{*+} \rightarrow \pi^0 D_s^+ & 0 &
\end{array} \tag{4}$$

Here, the particles $\pi^+ \omega K^- D^{*-} D_s^{*+}$ in the first branch arise from hadronization processes, in which quark pairs produced from initial state particles turn into hadrons. The processes with hadronization ignored have a tree structure and thus are easy to resolve. On the other hand, some hadronization processes, particularly those in high energy regions, contain complicated loop structures that are difficult to resolve without sophisticated algorithms. Resolving these intricate hadronization processes is not involved in the program at present.

The input data are recommended to be saved in the TTree object together with other quantities for physics analysis, in order to facilitate the examination of the distributions of these quantities with the topology information. It is easy to get the input of the program within the software framework of high energy physics experiments. To facilitate its use, we have developed the interfaces of the program to the software systems of the BESIII, Belle, and Belle II experiments. Similar interfaces for other experiments can also be implemented with ease. Beyond the scope of the paper, we will not discuss the details of the interfaces here.

2.3. Execution of the program

To execute the program, we have to first configure some necessary setting items in a card file, and then run the program with the command line: “topoana.exe cardFileName”. This subsection introduces the essential items for the input, basic functionality, and output of the program. More items that can be set in the card file will be described in the following three sections. Sections 3 and 4 expatiate the available items for the functionalities of the program, and Section 5 presents some optional items for the common settings to control the execution of the program.

An example of the card file containing the essential items is shown as follows.

```

# The following five items set the input of the program.

% Names of input root files
{
  ../input/jpsi.1.root
  ../input/jpsi.2.root
}

% TTree name
{
  evt
}

% TBranch name of the number of particles (Default: nMCGen)
{
  Nmcp
}

% TBranch name of the PDG codes of particles (Default: MCGenPDG)
{
  Pid
}

```

```

205
206 % TBranch name of the mother indices of particles (Default: MCGenMothIndex)
207 {
208     Midx
209 }
210
211 # The following item sets the basic functionality of the program.
212
213 % Component analysis — decay trees
214 {
215     Y
216 }
217
218 # The following item sets the output of the program.
219
220 % Main name of output files (Default: Main name of the card file)
221 {
222     jpsi.ta
223 }
224

```

In the card file, “#”, “%”, and the pair of “{” and “}”, are used for commenting, prompting, and grouping, respectively. The first five, sixth, and last items are set for the input, basic functionality, and output of the program, respectively.

The first item sets the names of the input root files. The names ought to be input one per line without tailing characters, such as comma, semicolon, and period. In the names, both the absolute and relative paths are allowed and wildcards “[]?*” are supported, just like those in the root file names input to the method Add() of the class TChain [11]. The second item specifies the TTree name. The following three items set the TBranch names of the three ingredients of the raw topology truth information. Of the first five items, the former two are indispensable, whereas the latter three can be removed or left empty if the input values are identical to the default values indicated in their prompts.

The sixth item sets the basic functionality of the program, namely the component analysis over decay trees. The item can be replaced or co-exist with other functionality items expatiated in Sections 3 and 4. Here, we note that at least one functionality item has to be specified explicitly in the card file, otherwise the program will terminate soon after its start because no topology analysis to be performed is set up.

The last item specifies the main name of the output files. Though in different formats, the files are denominated with the same main name for the sake of uniformity. They will be introduced at length in the next subsection. This item is also optional, with the main name of the card file as its default input value. It is a good practice to first denominate the card file with the desired main name of the output files and then remove this item or leave it empty.

To provide a complete description, we list and explain all the essential items in the paragraphs above. However, in practical uses, we suggest removing the optional items if the input values are identical to the default ones. In this way, the contents of the card file will become much more concise, making the use of the program easier and quicker. For example, unless otherwise stated, only the following two items are used to set the essential information in Sections 3, 4, and 5.

```

251
252 % Names of input root files
253 {
254     ../input/mixed_1.root
255     ../input/mixed_2.root
256 }
257

```

```

258 % TTree name
259 {
260     evt
261 }

```

The processing rate of the program is partly related to the performance of the detailed computing systems. Figure 1 shows the typical trends of the progress of the program, where the blue line displays the trend of running the example in this subsection. From the figure, the number of elapsed seconds grows linearly with the number of processed entries. This linear pattern, rather than a quadratic pattern, is a nice feature. It guarantees the program has a high rate even in the case of processing huge samples. In this example, the program can process one hundred thousand events within five seconds.




Figure 1: Typical trends of the progress of the program. The dots show the timing data from the standard output of the program, and the lines display the results of fitting linear functions to the data. The blue and red lines illustrate the trends of running the J/ψ example in Section 2.3 and the $\Upsilon(4S)$ example in Section 3.1, respectively. It takes more time in the $\Upsilon(4S)$ example than in the J/ψ example, because the decay of the $\Upsilon(4S)$ resonance is more complex than that of the J/ψ resonance.

2.4. Output of the program

The program gains the topology information from input data and saves it to output files. As mentioned in Section 1, the information includes the types of physics processes and the number of processes in each type, involved both in entire samples and in individual events. We refer to the information at the sample level as topology maps. In the topology maps, we assign an integer to each type of physics processes as its index. We term the indices of processes as well as the numbers of processes involved in each type in the individual events as topology tags.

The program outputs topology maps to three different files: one plain text file, one tex source file, and one pdf file, with the same main name specified in the card file. For instance, the three files are “jpsi.ta.txt”, “jpsi.ta.tex”, and “jpsi.ta.pdf” in the example. Although in different formats, the three files have the same information. The pdf file is the easiest to read. It is

converted from the tex source file with the command pdflatex. The tex source file is convenient to us if we want to change the style of the pdf file to our taste and when we need to copy and paste (parts of) the topology maps to our slides, papers, and so on. For example, all of the tables displaying topology maps in this paper are taken from associated tex source files. The plain text file has its own advantage, because the topology maps in it can be checked with text processing commands as well as text editors, and can be used on some occasions as input to the functionality items (see Sections 3 and 4 for details) of another card file.

In addition to the three files for topology maps, one or more root files are output to save topology tags. The root files only include one TTree object, which is entirely the same as that in the input root files, except for the topology tags inserted in all of its entries. The number of root files depends on the size of output data. The program switches to one new root file whenever the size of the TTree object in memory exceeds 3 GB. In the case of the size less than 3 GB, only one root file is output. While the sole or first root file has the same main name as the three files above, more possible root files are denominated with the suffix “_n” (n=1, 2, 3, and so on) appended to the main name. In the example, the first root file is “jpsi.ta.root”, and more possible root files would be “jpsi.ta_1.root”, “jpsi.ta_2.root”, “jpsi.ta_3.root”, and so on.

In the example of the previous subsection, the program conducts its basic functionality, namely the component analysis over decay trees. From the 100000 events of the input sample, the program recognizes 17424 decay trees and outputs all of them to the plain text, tex source, and pdf files. Table 1 only shows the top ten decay trees and their respective final states listed in the output pdf file. With the help of the symbolic expressions, the components of the sample are clearly displayed in the table, which brings great convenience to us in examining the signals and backgrounds involved in the sample.

Table 1: Top ten decay trees and their respective final states.

rowNo	decay tree	decay final state	iDcyTr	nEtr	nCEtr
1	$J/\psi \rightarrow \mu^+ \mu^-$	$\mu^+ \mu^-$	6	5269	5269
2	$J/\psi \rightarrow e^+ e^-$	$e^+ e^-$	4	4513	9782
3	$J/\psi \rightarrow \pi^0 \pi^+ \pi^- \pi^-$	$\pi^0 \pi^+ \pi^- \pi^-$	0	2850	12632
4	$J/\psi \rightarrow \pi^0 \pi^+ \pi^+ \pi^- \pi^-$	$\pi^0 \pi^+ \pi^+ \pi^- \pi^-$	2	1895	14527
5	$J/\psi \rightarrow \pi^0 \pi^+ \pi^- K^+ K^-$	$\pi^0 \pi^+ \pi^- K^+ K^-$	20	1698	16225
6	$J/\psi \rightarrow \rho^+ \rho^- \omega, \rho^+ \rightarrow \pi^0 \pi^+, \rho^- \rightarrow \pi^0 \pi^-, \omega \rightarrow \pi^0 \pi^+ \pi^-$	$\pi^0 \pi^0 \pi^0 \pi^+ \pi^- \pi^-$	19	1453	17678
7	$J/\psi \rightarrow e^+ e^- \gamma^f$	$e^+ e^- \gamma^f$	70	1222	18900
8	$J/\psi \rightarrow \pi^0 \pi^0 \pi^+ \pi^- \pi^-$	$\pi^0 \pi^0 \pi^+ \pi^- \pi^-$	127	1161	20061
9	$J/\psi \rightarrow \pi^0 \pi^+ \pi^+ \pi^+ \pi^- \pi^- \pi^-$	$\pi^0 \pi^+ \pi^+ \pi^+ \pi^- \pi^- \pi^-$	234	836	20897
10	$J/\psi \rightarrow \pi^0 \pi^0 \pi^+ \pi^- \gamma^F$	$\pi^0 \pi^0 \pi^+ \pi^- \gamma^F$	43	792	21689

In the table, “rowNo”, “iDcyTr”, “nEtr”, and “nCEtr” are abbreviations for the row number, index of decay tree, number of entries of decay tree, and number of the cumulative entries from the first to the current decay trees, respectively. The values of “iDcyTr” are assigned from small to large in the program but listed according to the values of “nEtr” from large to small in the table. This is the reason why they are not in natural order like the values of “rowNo”. Since J/ψ is the only root particle for the J/ψ sample, the production branch $e^+ e^- \rightarrow J/\psi$ is omitted to save page space. Similar rules also apply to other samples with only one root particle. Considering π^0 has a very large production rate and approximately 99% of it decays to $\gamma\gamma$, the program is

312 designed to discard the decay $\pi^0 \rightarrow \gamma\gamma$ by default at the early phase of processing the input data.
 313 As a result, $\pi^0 \rightarrow \gamma\gamma$ does not show itself in the table. Besides, the superscripts “ f ” and “ F ” in
 314 γ^f and γ^F indicate the final state radiation effect (see Section 5.3 for their difference).

315 In the table, “iDcyTr” is the topology tag for decay trees. Thus, it is also saved in the TTree
 316 objects of the output root file, together with other quantities for physics analysis. Therefore, it
 317 can be used to pick out the entries of specific decay trees and then examine the distributions of
 318 the other quantities over the decay trees. In the example, besides the raw topology truth informa-
 319 tion, only a random variable following the standardized normal distribution, namely X, is stored
 320 in the input root files and thus copied by default to the output root file. Though not a genuine
 321 variable for physics analysis, X is quite good to illustrate the usage of the topology tag. Figure 2
 322 shows the distribution of X accumulated over the top ten decay trees. The figure is drawn with
 323 the root script

324
 325 `examples/in_the_paper/ex_for_tb.01/draw_X/v2/draw_X.C,`
 326

327 where, for example, a statement equivalent to

328
 329 `chain->Draw(“X >>h0”, “iDcyTr==6”)`
 330

331 is used to import X over the decay tree $J/\psi \rightarrow \mu^+\mu^-$ from the output root file to the histogram
 332 named h0. With such a figure, we can clearly see the contribution of each decay tree. Particu-
 333 larly, we can get to know whether a decay tree has a peak contribution or a contribution mainly
 334 distributed in a different region. Based on these distributions, we can get a better understand-
 335 ing of our signals and backgrounds, and thus optimize event selection criteria by applying new
 336 requirements on the displayed quantities.




Figure 2: Distribution of X accumulated over the top ten decay trees. In the legend entry “ $J/\psi \rightarrow \rho^+\rho^-\omega, \dots$ ”, the dots “ \dots ” represent the secondary decay branches: $\rho^+ \rightarrow \pi^0\pi^+$, $\rho^- \rightarrow \pi^0\pi^-$, $\omega \rightarrow \pi^0\pi^+\pi^-$.

3. Component analysis

Component analysis is the primary functionality of the program. It is developed mainly for the background analysis involved in our physics studies. We perform it over decay trees in the previous example. Also, it can be carried out as follows: over decay initial-final states; with specified particles to check their decay branches, cascade decay branches, and decay final states; with specified inclusive decay branches to examine their exclusive components; and with specified intermediate-resonance-allowed (IRA) decay branches to investigate their inner structures. This section introduces the seven (three for specified particles) kinds of component analysis, with each in a subsection. For each kind of component analysis, one item is designed and implemented in the program to set related parameters. In each subsection, we take an example to demonstrate the corresponding setting item and show the resulting topology map. For easy exposition, all of the essential topology tags involved in the component analysis functionalities are presented in another separate subsection, namely the last subsection.

Similar to the case over decay trees, to perform the component analysis over decay initial-final states, we only need to input a positive option “Y” to the corresponding item. Different from the former two kinds, to carry out the latter five kinds of component analysis, we have to explicitly specify one or more desired particles, inclusive decay branches, or IRA decay branches in the associated items. In the following examples, two particles or decay branches are set to illustrate the use of these items, but only the topology map related to one of them is shown to save space in the paper.

In addition to the indispensable parameters, two sorts of common optional parameters can be set in the items. The first sort is designed for all the seven kinds of component analysis to restrict the maximum number of components output to the plain text, tex source, and pdf files. Without the optional parameters, all components will be output. This is fine if the number of components is not massive. In cases of too many (around ten thousand or more) components, it takes a long time for the program to output the components to the plain text and tex source files as well as to get the pdf file from the tex source file. In such cases, it also takes up a large disk space to save these components in the output files. Considering further that the posterior components are generally unimportant and our time and energy to examine them are limited, it is better to set a maximum to the number of output components. To save space in the paper, we set the maximum number to five in the following examples.

The second sort of optional parameters are developed for the latter five kinds of component analysis to assign meaningful aliases to the specified particles, inclusive decay branches, and IRA decay branches. By default, the indices 0, 1, 2, and so on are used to tag the particles and decay branches in the names of the TBranch objects appended in the TTree object of the output root files. This is fine, but it is significative to replace the indices with meaningful aliases, particularly in cases of many specified particles or decay branches.

3.1. Decay trees

Component analysis over decay trees is the basic kind of topology analysis. It is quite useful to study the backgrounds involved in our research works where the signals are the complete decay trees fully reconstructed from final state particles. It has already been widely performed in the BESIII experiment, as illustrated in the previous section with the J/ψ example. This subsection introduces it further with the available optional settings using the $\Upsilon(4S)$ sample. The following example shows the associated item with the maximum number of output components set to five. In the item, a third parameter is also filled and set to “Y”. With the setting, the decay final states in the output pdf file are put under their respective decay trees, rather than in a column next to that for decay trees. It is recommended to use this optional parameter in cases there are

too many (about ten or more) particles in some final states. Here, we note that the symbol “—” can be used as a placeholder for the maximum number of output components, if only the third parameter is desired.

```

388 % Component analysis — decay trees
389 {
390   Y   5   Y
391 }

```

Component analysis over decay trees is one kind of the most time-consuming topology analysis tasks. To check further the efficiency of the program, the progress of running this example, in addition to the example in Section 2.3, is illustrated in Fig. 1 as well. Clearly, a similar linear pattern is also observed. However, since the decay of the $\Upsilon(4S)$ resonance is more complex than that of the J/ψ resonance, it takes more than twenty seconds for the program to process one hundred thousand events in this example. Nonetheless, the program still has a high processing rate.

Table 2 shows the decay trees. In the table, while the first five decay trees are listed exclusively in the main part, the rest decay trees are only summarized inclusively at the bottom row. Here, we note that the events are not densely populated over the first five decay trees because the inclusive $\Upsilon(4S)$ sample used here is not selected beforehand with any requirements. In the symbolic expressions of decay initial-final states, the dashed right arrow (\dashrightarrow) instead of the plain right arrow (\rightarrow) is used, in order to reflect that the initial states do not necessarily decay to the final states in a direct way. Similarly, it is also used in the symbolic expressions of IRA decay branches, which will be introduced in Section 3.7.

Table 2: Decay trees and their respective initial-final states.

rowNo	decay tree (decay initial-final states)	iDcyTr	nEtr	nCEtr
1	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow e^+ \nu_e D^{*-} \gamma^F, \bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}, D^{*-} \rightarrow \pi^- \bar{D}^0,$ $D^{*+} \rightarrow \pi^+ D^0, \bar{D}^0 \rightarrow \pi^0 \pi^- K^+, D^0 \rightarrow \pi^0 \pi^+ K^-$ $(\Upsilon(4S) \dashrightarrow e^+ \nu_e \mu^- \bar{\nu}_\mu \pi^0 \pi^+ \pi^+ \pi^- \pi^- K^+ K^- \gamma^F)$	20870	3	3
2	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow \pi^0 \pi^+ \pi^+ \rho^- D^-, \bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}, \rho^- \rightarrow \pi^0 \pi^-,$ $D^- \rightarrow \pi^- \pi^- K^+, D^{*+} \rightarrow \pi^+ D^0, D^0 \rightarrow K_L^0 \pi^+ \pi^-$ $(\Upsilon(4S) \dashrightarrow \mu^- \bar{\nu}_\mu \pi^0 \pi^0 K_L^0 \pi^+ \pi^+ \pi^+ \pi^- \pi^- \pi^- K^+ K^-)$	5295	2	5
3	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow \mu^+ \nu_\mu D^{*-}, \bar{B}^0 \rightarrow e^- \bar{\nu}_e D^+, D^{*-} \rightarrow \pi^- \bar{D}^0,$ $D^+ \rightarrow e^+ \nu_e \bar{K}^*, \bar{D}^0 \rightarrow \pi^0 \pi^+ \pi^- K_S^0, \bar{K}^* \rightarrow \pi^0 \bar{K}^0, K_S^0 \rightarrow \pi^+ \pi^-, \bar{K}^0 \rightarrow K_L^0$ $(\Upsilon(4S) \dashrightarrow e^+ e^- \nu_e \bar{\nu}_e \mu^+ \nu_\mu \pi^0 \pi^0 K_L^0 \pi^+ \pi^+ \pi^- \pi^- \pi^-)$	11954	2	7
4	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow e^+ \nu_e D^{*-}, \bar{B}^0 \rightarrow \pi^0 \pi^- \omega D^+, D^{*-} \rightarrow \pi^- \bar{D}^0,$ $\omega \rightarrow \pi^0 \pi^+ \pi^-, D^+ \rightarrow e^+ \nu_e \pi^+ K^-, \bar{D}^0 \rightarrow \pi^0 \pi^- K^+$ $(\Upsilon(4S) \dashrightarrow e^+ e^+ \nu_e \nu_e \pi^0 \pi^0 \pi^+ \pi^+ \pi^- \pi^- \pi^- K^+ K^-)$	14345	2	9
5	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow \mu^+ \nu_\mu D^{*-}, \bar{B}^0 \rightarrow e^- \bar{\nu}_e D^{*+} \gamma^F, D^{*-} \rightarrow \pi^- \bar{D}^0,$ $D^{*+} \rightarrow \pi^0 D^+, \bar{D}^0 \rightarrow \pi^- K^+, D^+ \rightarrow e^+ \nu_e \bar{K}^*, \bar{K}^* \rightarrow \pi^+ K^-$ $(\Upsilon(4S) \dashrightarrow e^+ e^- \nu_e \bar{\nu}_e \mu^+ \nu_\mu \pi^0 \pi^+ \pi^- \pi^- K^+ K^- \gamma^F)$	15332	2	11
rest	$\Upsilon(4S) \rightarrow \text{others (99980 in total)}$ $(\Upsilon(4S) \dashrightarrow \text{corresponding to others})$	—	99989	100000

3.2. Decay initial-final states

On some occasions, we need to investigate the decay initial-final states of backgrounds for some sophisticated physics analyses. Particularly, it is necessary to differentiate the following two fundamental types of backgrounds: the one with the same initial-final states as the signal,

and the other with different initial-final states from the signal. While the latter type of backgrounds needs to be suppressed as much as possible, the former type usually needs to be kept to study more physical effects, for example, the interference effect. Besides, examining the decay initial-final states of backgrounds sheds light on the misjudgment of final state particles at the level of signal candidates. Below is an example demonstrating the related item with the maximum number of output components set to five.

```
% Component analysis — decay initial-final states
{
  Y    5
}
```

The decay initial-final states are displayed in Table 3. The layout of the table is similar to that of Table 2, which shows the decay trees.

Table 3: Decay initial-final states.

rowNo	decay initial-final states	iDcyIFSts	nEtr	nCEtr
1	$\Upsilon(4S) \rightarrow \mu^+ \nu_\mu \pi^0 \pi^0 \pi^+ \pi^+ \pi^- \pi^- \pi^- \pi^- K^+ K^-$	41	18	18
2	$\Upsilon(4S) \rightarrow \pi^0 \pi^0 \pi^0 \pi^0 \pi^+ \pi^+ \pi^+ \pi^+ \pi^- \pi^- \pi^- \pi^- K^+ K^-$	887	18	36
3	$\Upsilon(4S) \rightarrow \mu^- \bar{\nu}_\mu \pi^0 \pi^0 \pi^0 \pi^+ \pi^+ \pi^+ \pi^+ \pi^- \pi^- \pi^- \pi^- K^+ K^-$	3350	18	54
4	$\Upsilon(4S) \rightarrow \pi^0 \pi^0 \pi^0 \pi^0 \pi^0 \pi^+ \pi^+ \pi^+ \pi^+ \pi^- \pi^- \pi^- \pi^- K^+ K^-$	1215	17	71
5	$\Upsilon(4S) \rightarrow \pi^0 \pi^0 \pi^0 \pi^0 \pi^0 K_L^0 \pi^+ \pi^+ \pi^+ \pi^+ \pi^- \pi^- \pi^- \pi^- K^-$	1207	17	88
rest	$\Upsilon(4S) \rightarrow \text{others (78208 in total)}$	—	99912	100000

3.3. Decay branches of particles

The invariant mass constraint is one of the most frequently used event selection requirements in high energy physics experiments. With the requirement applied to certain particle, the main backgrounds (especially the peaking ones) to its signal decay mode are very likely to be its other decay modes. In this case, it is significant to examine the decay branches of the particle. The following example shows the associated item with the two particles D^{*+} and J/ψ set as research objects. In the item, each row holds the information of a specified particle, and the first, second and third columns are the textual expressions, aliases, and maximum numbers of output components, respectively. As we introduce at the beginning part of this section, the aliases and maximum numbers of output components are both optional. Here, we note that the symbol “—” can also be used as a placeholder for an unassigned alias, if only the maximum number of output components is desired.

```
% Component analysis — decay branches of particles
{
  D*+   Dsp   5
  J/psi  Jpsi  5
}
```

Table 4 shows the decay branches of D^{*+} . From the table, only four decay branches of D^{*+} are found in the input inclusive MC sample. Since there is likely one or more cases of D^{*+} decays in one input entry, “nCase” and “nCCase”, instead of “nEtr” and “nCEtr”, are used in the table in order to accurately indicate what we are counting are the numbers of D^{*+} decays, rather than the numbers of entries involving the D^{*+} decays.

Table 4: Decay branches of D^{*+} .

rowNo	decay branch of D^{*+}	iDcyBrP	nCase	nCCase
1	$D^{*+} \rightarrow \pi^+ D^0$	0	31180	31180
2	$D^{*+} \rightarrow \pi^0 D^+$	1	13978	45158
3	$D^{*+} \rightarrow D^+ \gamma$	2	700	45858
4	$D^{*+} \rightarrow \pi^+ D^0 \gamma^F$	3	28	45886

It is worth mentioning here that, in addition to decay branches, production branches and mothers of specified particles can also be examined with the program. One can make the program execute the two functionalities by replacing “decay branches” in the prompt of the item with “production branches” and “mothers”, respectively.

3.4. Cascade decay branches of particles

Sometimes, the invariant mass constraint is applied to certain particle and the signal process is its cascade decay branch. In this case, it is necessary to investigate the cascade decay branches of the particle, rather than its first decay branches, so as to analyze the backgrounds effectively. Below is an example demonstrating the related item by taking the two particles B^0 and D^0 as objects of study. While the first three columns of the input to this item have the same meanings as those to the three items above, the additional fourth column sets the maximum hierarchy of decay branches to be examined. Here, the hierarchy reflects the rank of a decay branch in a cascade decay branch of one specific particle. For instance, in the following cascade decay branch of B^0 : $B^0 \rightarrow \pi^0 \pi^0 \rho^0 \pi^+ D^{*-}$, $\rho^0 \rightarrow \pi^+ \pi^-$, $D^{*-} \rightarrow \pi^- \bar{D}^0$, $\bar{D}^0 \rightarrow \eta \eta'$, $\eta \rightarrow \pi^0 \pi^0 \pi^0$, $\eta' \rightarrow \pi^0 \pi^0 \eta$, $\eta \rightarrow \gamma \gamma$, the hierarchies of the seven individual decay branches are 1, 2, 2, 3, 4, 4, and 5, respectively. In the example, the maximum hierarchy of decay branches is set to two for both B^0 and D^0 , and hence only the first two hierarchies of branches in their cascade decays will be investigated. Without such settings, all the branches in their cascade decays will be examined.

```
% Component analysis — cascade decay branches of particles
{
  B0  B0  5  2
  D0  D0  5  2
}
```

The cascade decay branches of B^0 are displayed in Table 5.

Table 5: Cascade decay branches of B^0 (only the first two hierarchies are involved).

rowNo	cascade decay branch of B^0	iCascDcyBrSP	nCase	nCCase
1	$B^0 \rightarrow \mu^+ \nu_\mu D^{*-}, D^{*-} \rightarrow \pi^- \bar{D}^0$	12	2912	2912
2	$B^0 \rightarrow e^+ \nu_e D^{*-}, D^{*-} \rightarrow \pi^- \bar{D}^0$	6	1991	4903
3	$B^0 \rightarrow \mu^+ \nu_\mu D^{*-}, D^{*-} \rightarrow \pi^0 D^-$	70	1283	6186
4	$B^0 \rightarrow e^+ \nu_e D^{*-} \gamma^F, D^{*-} \rightarrow \pi^- \bar{D}^0$	18	1132	7318
5	$B^0 \rightarrow D^{*-} D_s^{*+}, D^{*-} \rightarrow \pi^- \bar{D}^0, D_s^{*+} \rightarrow D_s^+ \gamma$	20	1119	8437
rest	$B^0 \rightarrow \text{others (42074 in total)}$	—	91594	100031

3.5. Decay final states of particles

When the invariant mass constraint is applied to certain particle reconstructed directly from a specific final state, it is significant to examine the decay final states of the particle, rather than its first or cascade decay branches, in order to study the backgrounds effectively. The following

example shows the associated item also with the two particles B^0 and D^0 set as research objects. The format of the input to the item is the same as that to the above item, but the fourth parameters here are designed to restrict the numbers of final state particles. Without the fourth parameters, all the decay final states of the specified particles will be investigated. In the example, the parameters are set to three for both B^0 and D^0 , and thus only the three-body decay final states of them will be examined.

```

486      % Component analysis — decay final states of particles
487      {
488          B0   B0   5   3
489          D0   D0   5   3
490      }
491

```

Table 6 shows the three-body decay final states of D^0 . In the table, π^0 only decays to $\gamma\gamma$; otherwise, it will be replaced with its decay products, resulting in different decay final states of D^0 .

Table 6: Decay final states of D^0 (only three-body final states are involved).

rowNo	decay final state of D^0	iDcyFStP	nCase	nCCase
1	$D^0 \rightarrow \pi^0 \pi^+ K^-$	2	6258	6258
2	$D^0 \rightarrow \mu^+ \nu_\mu K^-$	5	1487	7745
3	$D^0 \rightarrow \pi^0 \pi^+ \pi^-$	1	1162	8907
4	$D^0 \rightarrow K_L^0 \pi^+ \pi^-$	3	1158	10065
5	$D^0 \rightarrow e^+ \nu_e K^-$	11	1148	11213
rest	$D^0 \rightarrow \text{others (24 in total)}$	—	2407	13620

3.6. Inclusive decay branches

In a few physics studies, we take inclusive decay branches as signals. In such cases, it is essential to have a basic knowledge of the exclusive components of these inclusive decay branches. Below is an example demonstrating the related item by investigating the exclusive components of the two inclusive decay branches $\bar{B}^0 \rightarrow D^{*+} + \text{anything}$ and $B^0 \rightarrow K_S^0 + \text{anything}$. In the item, each row holds the information of an inclusive decay branch, and the first, second, and third columns separated with the symbol “&” are the textual expressions, aliases, and maximum numbers of output components, respectively. As we introduce at the beginning part of this section, the aliases and maximum numbers of output components are both optional. Here, we note that the symbol “—” can be used as a placeholder for an unassigned alias, if only the maximum number of output components is desired.

```

507      % Component analysis — inclusive decay branches
508      {
509          B0 --> D*+   &   B2Dsp   &   5
510          B0 --> K_S0  &   B2Ks    &   5
511      }
512

```

The exclusive components of $B^0 \rightarrow K_S^0 + \text{anything}$ are displayed in Table 7. From the table, ten exclusive components of the inclusive decay branch are found in the input sample, and the particles denoted with *anything* are mainly the traditional charmonium states.

Table 7: Exclusive components of $B^0 \rightarrow K_S^0 + \text{anything}$.

rowNo	exclusive component of $B^0 \rightarrow K_S^0 + \text{anything}$	iDcyBrIncDcyBr	nCase	nCCase
1	$B^0 \rightarrow K_S^0 J/\psi$	0	45	45
2	$B^0 \rightarrow K_S^0 \eta_c$	1	40	85
3	$B^0 \rightarrow K_S^0 \psi'$	3	33	118
4	$B^0 \rightarrow K_S^0 \chi_{c1}$	2	20	138
5	$B^0 \rightarrow K_S^0 \chi_{c0}$	4	6	144
rest	$B^0 \rightarrow K_S^0 + \text{others (5 in total)}$	—	9	153

3.7. Intermediate-resonance-allowed decay branches

In many research works, we take multi-body decay branches as signals. On such occasions, it is fundamental to investigate the intermediate resonances involved in these decay branches. In other words, we need to examine the exclusive components of these IRA decay branches. The following example shows the associated item with the two IRA decay branches $D^{*+} \rightarrow \pi^0 \pi^+ \pi^+ K^-$ and $J/\psi \rightarrow \pi^0 \pi^+ \pi^-$ set as objects of study. Since IRA decay branches look like inclusive decay branches, the format of the input to the item for IRA decay branches is identical to that for inclusive decay branches, which is introduced in the previous subsection.

```
% Component analysis — intermediate-resonance-allowed decay branches
{
  D*+ --> K- pi+ pi+ pi0 & Dsp2K3Pi & 5
  J/psi --> pi+ pi- pi0 & Jpsi23Pi & 5
}
```

Table 8 shows the exclusive components of $D^{*+} \rightarrow \pi^0 \pi^+ \pi^+ K^-$. From the table, two intermediate particles D^0 and D^+ are found in the IRA decay branch, and they decay to $\pi^0 \pi^+ K^-$ and $\pi^+ \pi^+ K^-$, respectively.

Table 8: Exclusive components of $D^{*+} \rightarrow \pi^0 \pi^+ \pi^+ K^-$.

rowNo	exclusive component of $D^{*+} \rightarrow \pi^0 \pi^+ \pi^+ K^-$	iDcyBrIRADcyBr	nCase	nCCase
1	$D^{*+} \rightarrow \pi^+ D^0, D^0 \rightarrow \pi^0 \pi^+ K^-$	0	3869	3869
2	$D^{*+} \rightarrow \pi^0 D^+, D^+ \rightarrow \pi^+ \pi^+ K^-$	1	1102	4971

3.8. Essential topology tags

Table 9 lists and interprets all of the essential topology tags involved in the component analysis functionalities. The topology tag for the component analysis over decay initial-final states is iDcyIFSts. It has a similar interpretation as iDcyTr and is shown in the third column of Table 3. For the latter five kinds of component analysis, there are two sorts of topology tags. The first sort, such as nPDcyBr_i, records the number of instances of the i^{th} specified particle or decay branch found in each event. The second sort, for example, iDcyBrP_i_j, keeps the associated index of the j^{th} found instance of the i^{th} specified particle or decay branch. The indices and the decays they stand for can be found in Tables 4 – 8.

In the topology tags, “i” in “_i” is the default index of the specified particle or decay branch, and it ranges from 0 (included) to the number of specified particles or decay branches (excluded). If the alias of the particle or decay branch is also specified, the index “i” will be replaced with the alias. For example, since “Dsp” and “Jpsi” are set as the aliases of D^{*+} and J/ψ in the

Table 9: Essential topology tags involved in each kind of component analysis.

Component type	Topology tag	Interpretation
Decay trees	iDcyTr	index of decay tree
Decay initial-final states	iDcyIFSts	index of decay initial-final states
Decay branches of particles	nPDcyBr.i	number of particle _i s (or its decay branches)
	iDcyBrP.i.j	index of decay branch of the j th particle _i
Cascade decay branches of particles	nPCascDcyBr.i	number of particle _i s (or its cascade decay branches)
	iCascDcyBrP.i.j	index of cascade decay branch of the j th particle _i
Decay final states of particles	nPDcyFSt.i	number of particle _i s (or its decay final states)
	iDcyFStP.i.j	index of decay final state of the j th particle _i
Inclusive decay branches	nIncDcyBr.i	number of inclusive decay branches
	iDcyBrIncDcyBr.i.j	index of decay branch of the j th inclusive decay branch _i
IRA decay branches	nIRADcyBr.i	number of IRA decay branches
	iDcyBrIRADcyBr.i.j	index of decay branch of the j th IRA decay branch _i

component analysis over their decay branches, the specialized topology tags nPDcyBr_Dsp and nPDcyBr_Jpsi, instead of the default ones nPDcyBr_0 and nPDcyBr_1, are used to store the numbers of D^{*+} and J/ψ found in each event.

Besides, “j” in “_j” is the default index of the found instance of certain particle or decay branch in an event, and it ranges from 0 (included) to the sample-level maximum of the number of instances found in each event (excluded). For example, the maximum of the number of D^{*+} found in each event is two for the whole sample, and thus two topology tags iDcyBrP_Dsp_0 and iDcyBrP_Dsp_1 are employed to store the indices of D^{*+} decay branches. These indices range from 0 (included) to the number of the types of D^{*+} decay branches found in the samples (excluded). In the events with only one D^{*+} , iDcyBrP_Dsp_1 is assigned with the default value -1; in the events that have no D^{*+} , the default value -1 is assigned to both iDcyBrP_Dsp_0 and iDcyBrP_Dsp_1.

4. Signal identification

Signal identification is the other functionality of the program. Though relatively simple, it can help us identify the “signals” we desire directly, quickly, and easily. Here, the “signals” are not confined to the authentic signals in our research works but can be any physics processes of interests, particularly some important backgrounds we concern. At present, the seven basic kinds of signals that can be identified with the program are as follows: (1) decay trees, (2) decay initial-final states, (3) particles, (4) (regular) decay branches, (5) cascade decay branches, (6) inclusive decay branches, and (7) IRA decay branches. For each kind of signals, one item is developed to specify related parameters. This section introduces the seven kinds of signal identification, with each in a subsection. In each subsection, we take an example to demonstrate the related setting item and show the obtained topology map. For easy exposition, all of the essential topology tags involved in the signal identification functionalities are presented in another separate subsection, that is, the last subsection.

Similar to the cases of the latter five kinds of component analysis, one or more signals can be specified in each of the signal identification items, and two signals are set in the following examples to illustrate the use of the items. Besides, meaning aliases can also be optionally

assigned to the specified signals so as to better tag them in the names of the TBranch objects appended in the TTree object of the output root files.

4.1. Decay trees

Sometimes, we need to identify certain decay trees. The following example shows the associated item with the first two decay trees listed in Table 2 set as signals. In the item, each row holds a decay branch in the decay trees, and the first, second, and third columns separated with the symbol “&” are the indices, textual expressions, and mother indices of the decay branches, respectively. The decay branches with index 0 indicate the beginning of new decay trees, and their mother indices are equal to -1, suggesting they have no mother branches because they are the first decay branches of the decay trees. Besides, the name of each decay tree can be optionally filled in the fourth column of its first decay branch. Similar to the third parameter in the item for the component analysis over decay trees (see Section 3.1), a “Y” can be optionally filled in the fifth column of the first decay branch of the first decay tree, to adjust the positions of decay final states in the output pdf file.

```
% Signal identification — decay trees
{
  0 & Upsilon(4S) --> B0 anti-B0 & -1 & 1stDcyTrInTb2 & Y
  1 & B0 --> e+ nu_e D*- gamma & 0
  2 & anti-B0 --> mu- anti-nu_mu D*+ & 0
  3 & D*- --> pi- anti-D0 & 1
  4 & D*+ --> pi+ D0 & 2
  5 & anti-D0 --> pi0 pi- K+ & 3
  6 & D0 --> pi0 pi+ K- & 4

  0 & Upsilon(4S) --> B0 anti-B0 & -1 & 2ndDcyTrInTb2
  1 & B0 --> pi0 pi+ pi- rho- D- & 0
  2 & anti-B0 --> mu- anti-nu_mu D*+ & 0
  3 & rho- --> pi0 pi- & 1
  4 & D- --> pi- pi- K+ & 1
  5 & D*+ --> pi+ D0 & 2
  6 & D0 --> K.L0 pi+ pi- & 5
}
```

Table 10 shows the resulting topology map. The results are the same as those displayed in the first two rows of Table 2.

Table 10: Signal decay trees and their respective initial-final states.

rowNo	signal decay tree (signal decay initial-final states)	iSigDcyTr	nEtr	nCEtr
1	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow e^+ \nu_e D^{*-} \gamma^F, \bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}, D^{*-} \rightarrow \pi^- \bar{D}^0,$ $D^{*+} \rightarrow \pi^+ D^0, \bar{D}^0 \rightarrow \pi^0 \pi^- K^+, D^0 \rightarrow \pi^0 \pi^+ K^-$ $(\Upsilon(4S) \rightarrow e^+ \nu_e \mu^- \bar{\nu}_\mu \pi^0 \pi^+ \pi^- \pi^- K^+ K^- \gamma^F)$	0	3	3
2	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow \pi^0 \pi^+ \pi^- \rho^- D^-, \bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}, \rho^- \rightarrow \pi^0 \pi^-,$ $D^- \rightarrow \pi^- \pi^- K^+, D^{*+} \rightarrow \pi^+ D^0, D^0 \rightarrow K_L^0 \pi^+ \pi^-$ $(\Upsilon(4S) \rightarrow \mu^- \bar{\nu}_\mu \pi^0 \pi^0 K_L^0 \pi^+ \pi^+ \pi^- \pi^- \pi^- K^+)$	1	2	5

4.2. Decay initial-final states

In a few cases, we have an interest in some decay initial-final states. Below is an example demonstrating the related item by taking the first two decay initial-final states listed in Table 3 as signals. Similar to IRA decay branches, decay initial-final states look like inclusive decay branches. Hence, except that only two columns are involved in the item, the format of the input to the item for decay initial-final states is identical to that for the component analysis over inclusive decay branches, which is introduced in Section 3.6. As we can see from the example, the

619 numbers of identical particles are supported to be written in front of their textual names in order
620 to simplify the textual expressions of the final states.

```

621 % Signal identification — decay initial-final states
622 {
623     Y(4S) --> mu+ nu_mu 3 pi0 3 pi+ 4 pi- K+ K- & 2ndDcyIFStsInTb3
624     Y(4S) --> 5 pi0 5 pi+ 5 pi- K+ K- & 2ndDcyIFStsInTb3
625 }
626
627

```

628 The obtained topology map is displayed in Table 11. The results are identical to those shown in
629 the first two rows of Table 3.

Table 11: Signal decay initial-final states.

rowNo	signal decay initial-final states	iSigDcyIFSts2	nEtr	nCEtr
1	$\Upsilon(4S) \rightarrow \mu^+ \nu_\mu \pi^0 \pi^0 \pi^+ \pi^+ \pi^- \pi^- \pi^- K^+ K^-$	0	18	18
2	$\Upsilon(4S) \rightarrow \pi^0 \pi^0 \pi^0 \pi^0 \pi^+ \pi^+ \pi^- \pi^- \pi^- \pi^- K^+ K^-$	1	18	36

630 4.3. Particles

631 Occasionally, we may want to identify some particles. The following example shows the
632 associated item with the two particles D^{*+} and J/ψ set as signals. Except that only two columns
633 are involved in the item, the format of the input to the item is identical to that for the component
634 analysis over decay branches of particles, which is introduced in Section 3.3.

```

635 % Signal identification — particles
636 {
637     D*+   Dsp
638     J/psi  Jpsi
639 }
640
641

```

642 Table 12 shows the resulting topology map. As a cross-check, the number of D^{*+} s in the table
643 equals that in Table 4.

Table 12: Signal particles.

rowNo	signal particle	iSigP	nCase	nCCase
1	D^{*+}	0	45886	45886
2	J/ψ	1	2654	48540

644 4.4. Decay branches

645 On some occasions, we have to identify certain regular decay branches. Below is an ex-
646 ample demonstrating the related item by taking the two decay branches $\bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}$ and
647 $B^0 \rightarrow K_S^0 J/\psi$ as signals. Since regular decay branches also look like inclusive decay branches,
648 except that only two columns are involved in the item, the format of the input to the item for reg-
649 ular decay branches is identical to that for the component analysis over inclusive decay branches,
650 which is introduced in Section 3.6.

```

651 % Signal identification — decay branches
652 {
653     B0 --> mu- anti-nu_mu D*+ & B2munuDsp
654     B0 --> K_S0 J/psi & B2KsJpsi
655 }
656

```

657

658 The obtained topology map is displayed Table 13. For cross-checks, we note that the number of
 659 $B^0 \rightarrow K_S^0 J/\psi$ in the table is equal to that in the first row of Table 7.

Table 13: Signal decay branches.

rowNo	signal decay branch	iSigDcyBr	nCase	nCCase
1	$\bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}$	0	4154	4154
2	$B^0 \rightarrow K_S^0 J/\psi$	1	45	4199

660 4.5. Cascade decay branches

661 Sometimes, we are interested in certain cascade decay branches. The following example
 662 shows the associated item with the two cascade decay branches $B^0 \rightarrow D^{*-} D_s^{*+}$, $D^{*-} \rightarrow \pi^- \bar{D}^0$,
 663 $D_s^{*+} \rightarrow D_s^+ \gamma$ and $B^0 \rightarrow D^{*-} D_s^{*+}$, $D^{*-} \rightarrow \pi^- \bar{D}^0$ set as signals. While the first cascade decay
 664 branch is identical to the fifth one in Table 5, the second is only part of it, which demonstrates
 665 that the cascade decay branches supported in the item are not necessarily fully specified at the
 666 level of certain hierarchy. Similar to decay trees, cascade decay branches are made up of regular
 667 decay branches. Hence, the format of the input to the item for cascade decay branches is identical
 668 to that for decay trees, which is introduced in Section 4.1.

669

```
670 % Signal identification — cascade decay branches
671 {
672   0 & B0 --> D*- D_s*+ & -1
673   1 & D*- --> pi- anti-D0 & 0
674   2 & D_s*+ --> D_s+ gamma & 0
675
676   0 & B0 --> D*- D_s*+ & -1
677   1 & D*- --> pi- anti-D0 & 0
678 }
679
```

680 Table 14 shows the resulting topology map. As a cross-check, the number of cases of the first
 681 cascade decay branch in the table equals that of the fifth cascade decay branch in Table 5.

Table 14: Signal cascade decay branches.

rowNo	signal cascade decay branch	iSigCascDcyBr	nCase	nCCase
1	$B^0 \rightarrow D^{*-} D_s^{*+}, D^{*-} \rightarrow \pi^- \bar{D}^0, D_s^{*+} \rightarrow D_s^+ \gamma$	0	1119	1119
2	$B^0 \rightarrow D^{*-} D_s^{*+}, D^{*-} \rightarrow \pi^- \bar{D}^0$	1	1180	2299

682 4.6. Inclusive decay branches

683 In a few cases, we have to identify some inclusive decay branches. Below is an example
 684 demonstrating the related item by taking the two inclusive decay branches $\bar{B}^0 \rightarrow D^{*+} + \text{anything}$
 685 and $B^0 \rightarrow K_S^0 + \text{anything}$ as signals. Except that only two columns are involved in the item, the
 686 format of the input to the item is identical to that for the component analysis over inclusive decay
 687 branches, which is introduced in Section 3.6.

688

```
689 % Signal identification — inclusive decay branches
690 {
691   anti-B0 --> D*+ & B2Dsp
692   B0 --> K_S0 & B2Ks
693 }
```

694

695 The obtained topology map is displayed in Table 15. As a cross-check, the number of $B^0 \rightarrow$
 696 $K_S^0 + \text{anything}$ in the table equals that in Table 7.

Table 15: Signal inclusive decay branches.

rowNo	signal inclusive decay branch	iSigIncDcyBr	nCase	nCCase
1	$\bar{B}^0 \rightarrow D^{*+} + \text{anything}$	0	41751	41751
2	$B^0 \rightarrow K_S^0 + \text{anything}$	1	153	41904

697 4.7. Intermediate-resonance-allowed decay branches

698 On some occasions, we need to identify certain IRA decay branches. The following ex-
 699 ample shows the associated item with the two IRA decay branches $D^{*+} \rightarrow \pi^0 \pi^+ \pi^+ K^-$ and
 700 $J/\psi \rightarrow \pi^0 \pi^+ \pi^-$ set as signals. Except that only two columns are involved in the item, the
 701 format of the input to the item is identical to that for the component analysis over IRA decay
 702 branches, which is introduced in Section 3.7.

```

703 % Signal identification — intermediate-resonance-allowed decay branches
704 {
705     D*+ --> K- pi+ pi+ pi0 & Dsp2K3Pi
706     J/psi --> pi+ pi- pi0 & Jpsi23Pi
707 }
708
709 
```

710 Table 16 shows the resulting topology map. For the purpose of cross-checks, we note that the
 711 number of $D^{*+} \rightarrow \pi^0 \pi^+ \pi^+ K^-$ in the table is equal to that in Table 8.

Table 16: Signal IRA decay branches.

rowNo	signal IRA decay branch	iSigIRADcyBr	nCase	nCCase
1	$D^{*+} \rightarrow \pi^0 \pi^+ \pi^+ K^-$	0	4971	4971
2	$J/\psi \rightarrow \pi^0 \pi^+ \pi^-$	1	59	5030

712 4.8. Essential topology tags

713 Table 17 summarizes and explains all of the essential topology tags involved in the signal
 714 identification functionalities. For signal decay trees and signal decay initial-final states, there are
 715 two sorts of topology tags. The first sort of tags, iSigDcyTr and iSigDcyIFSts, record the default
 716 indices of the specified signal decay trees and signal decay initial-final states. They have similar
 717 interpretations as iDcyTr and iDcyIFSts, and are shown in the third columns of Tables 10 and
 718 11. The second sort of tags, nameSigDcyTr and nameSigDcyIFSts, save the specified aliases of
 719 the signal decay trees and signal decay initial-final states. In cases the aliases are not specified,
 720 empty strings will be stored.

721 For the latter five kinds of signal identification, there is only one sort of topology tags, which
 722 records the number of instances of certain specified particle or decay branch found in each event.
 723 Similar to the cases in the latter five kinds of component analysis, in the topology tags, “i” in
 724 “_i” is the default index of the specified particle or decay branch, and it ranges from 0 (included)
 725 to the number of specified particles or decay branches (excluded). If the alias of the particle or
 726 decay branch is also specified, the index “i” will be replaced with the alias.

Table 17: Essential topology tags involved in each kind of signal identification.

Signal type	Topology tag	Interpretation
Decay trees	iSigDcyTr	index of signal decay tree
	nameSigDcyTr	name of signal decay tree
Decay initial-final states	iSigDcyIFSs	index of signal decay initial-final states
	nameSigDcyIFSs	name of signal decay initial-final states
Particles	nSigP.i	number of signal particles
Decay branches	nSigDcyBr.i	number of signal decay branches
Cascade decay branches	nSigCascDcyBr.i	number of signal cascade decay branches
Inclusive decay branches	nSigIncDcyBr.i	number of signal inclusive decay branches
IRA decay branches	nSigIRADcyBr.i	number of signal IRA decay branches

5. Common settings

From Sections 3 and 4, the optional parameters of the functionality items give us more choices and thus help us do our jobs quicker and better. In addition to these parameters, many optional items are designed and implemented to control the execution of the program in order to meet practical needs. Unlike the optional parameters, which only affect the individual functionalities to which they belong, the optional items have an impact on all of the functionalities, or at least most of the functionalities. The current version of the program contains two dozen common setting items on its input, functionalities, and output. In this paper, we only introduce a part of the items that are crucial to our physics studies.

5.1. Settings on input entries

The program normally processes all of the entries in the input samples, but sometimes only a part of the entries are needed to be (first) processed. Running the program over a big sample usually takes a long time. In such a case, it is a good habit to run the program first over a small part of the sample to check possible exceptions, and then over the whole sample if no exceptions are found or after the found exceptions are handled. Besides, a small number of entries is usually sufficient to do tests in the development of the program. For these reasons, an item is developed to set up the maximum number of entries to be processed. Below is an example showing the item with the maximum number set at two thousand.

```
% Maximum number of entries to be processed
{
    2000
}
```

On some occasions, especially in the course of optimizing selection criteria, we need to run the program only over entries satisfying certain requirements. For this purpose, an item is developed to select entries. The following example shows the item with X set in the range $(-1, 1)$.

```
% Cut to select entries
{
    (X > -1) && (X < 1)
}
```

Notably, only a single-line selection requirement is supported in the item, like the cases in the methods Draw() [12] and GetEntries() [13] of the class TTree. In spite of this, such a requirement is able to express any requirement with the help of the parentheses “()” as well as the logical symbols “&&”, “||”, and “!”.

5.2. Setting on input decay branches

Normally, the program deals with all of the decay branches in every decay tree. However, examining all the branches is not always required in practice. Sometimes, we only concern the first n hierarchies of the branches. Similar to that in cascade decay branches of particles (as we introduce in Section 3.4), the hierarchy here reflects the rank of a decay branch in a decay tree. For example, in the decay tree $\Upsilon(4S) \rightarrow B^0 \bar{B}^0$, $B^0 \rightarrow e^+ \nu_e D^{*-} \gamma^F$, $\bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}$, $D^{*-} \rightarrow \pi^- \bar{D}^0$, $D^{*+} \rightarrow \pi^+ D^0$, $\bar{D}^0 \rightarrow \pi^0 \pi^- K^+$, $D^0 \rightarrow \pi^0 \pi^+ K^-$, the hierarchies of the seven individual branches are 1, 2, 2, 3, 3, 4, and 4, respectively. The program provides an item to set the maximum hierarchy. Below is an example showing the item with the maximum hierarchy set at one.

```
% Maximum hierarchy of heading decay branches to be processed in each event
{
    1
}
```

With the setting, the decay branches with hierarchy larger than one will be ignored by the program. For the component analysis over the decay trees of the $\Upsilon(4S)$ sample, only the first hierarchy of $\Upsilon(4S)$ decay branches are analyzed, and the result is shown in Table 18. From the table, not only $\Upsilon(4S) \rightarrow B^0 \bar{B}^0$ but also $\Upsilon(4S) \rightarrow B^0 B^0$ and $\Upsilon(4S) \rightarrow \bar{B}^0 \bar{B}^0$ are seen because of B^0 - \bar{B}^0 mixing.

Table 18: Decay trees and their respective initial-final states.

rowNo	decay tree (decay initial-final states)	iDcyTr	nEtr	nCEtr
1	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0$ ($\Upsilon(4S) \rightarrow B^0 \bar{B}^0$)	0	81057	81057
2	$\Upsilon(4S) \rightarrow B^0 B^0$ ($\Upsilon(4S) \rightarrow B^0 B^0$)	1	9487	90544
3	$\Upsilon(4S) \rightarrow \bar{B}^0 \bar{B}^0$ ($\Upsilon(4S) \rightarrow \bar{B}^0 \bar{B}^0$)	2	9456	100000

Table 19: Decay trees and their respective initial-final states.

rowNo	decay tree (decay initial-final states)	iDcyTr	nEtr	nCEtr
1	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow \mu^+ \nu_\mu D^{*-}, \bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}$ ($\Upsilon(4S) \rightarrow \mu^+ \mu^- \nu_\mu \bar{\nu}_\mu D^{*+} D^{*-}$)	936	136	136
2	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow e^+ \nu_e D^{*-}, \bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}$ ($\Upsilon(4S) \rightarrow e^+ \nu_e \mu^- \bar{\nu}_\mu D^{*+} D^{*-}$)	1188	112	248
3	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow \mu^+ \nu_\mu D^{*-}, \bar{B}^0 \rightarrow e^- \bar{\nu}_e D^{*+}$ ($\Upsilon(4S) \rightarrow e^- \bar{\nu}_e \mu^+ \nu_\mu D^{*+} D^{*-}$)	268	110	358
4	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow D^{*-} D_s^{*+}, \bar{B}^0 \rightarrow \mu^- \bar{\nu}_\mu D^{*+}$ ($\Upsilon(4S) \rightarrow \mu^- \bar{\nu}_\mu D^{*+} D^{*-} D_s^{*+}$)	2063	72	430
5	$\Upsilon(4S) \rightarrow B^0 \bar{B}^0, B^0 \rightarrow e^+ \nu_e D^{*-}, \bar{B}^0 \rightarrow e^- \bar{\nu}_e D^{*+}$ ($\Upsilon(4S) \rightarrow e^+ e^- \nu_e \bar{\nu}_e D^{*+} D^{*-}$)	95	71	501
rest	$\Upsilon(4S) \rightarrow \text{others (81609 in total)}$ ($\Upsilon(4S) \rightarrow \text{corresponding to others}$)	—	99499	100000

Similarly, in the case of the maximum hierarchy set at two, we could get the result of the com-

ponent analysis over the first two hierarchies of $\Upsilon(4S)$ decay branches, as displayed in Table 19.

5.3. Settings on initial and final state radiation photons

Initial state radiation (ISR) and final state radiation (FSR) are inevitable physical effects in e^+e^- colliding experiments. Therefore, ISR and FSR photons are often involved in inclusive MC samples. The program processes them together with other particles in the default case. To distinguish them from other photons, the program tries to label them in the output plain text, tex source, and pdf files. Sometimes, these photons are marked out beforehand with special PDG codes according to particle status information from generators. One can inform the program of these PDG codes by the following two items.

```
% PDG code of ISR photons (Default: 222222222)
{
  222222222
}

% PDG code of FSR photons (Default: -22)
{
  -22
}
```

In this case, the program is able to label the ISR and FSR photons as γ^i (gammai) and γ^f (gammaf) in the output pdf (plain text) files, respectively.

On other occasions, ISR and FSR photons are not marked out in advance due to some reasons. In such cases, the program has to identify them by itself according to the following rules: photons who have no mothers recorded in the arrays of the PDG codes and mother indices are considered as generalized ISR photons, while other photons who have at least one e^\pm , μ^\pm , π^\pm , K^\pm , p , or \bar{p} sister are taken as generalized FSR photons. Here, the modifier “generalized” is used because the rules can not determine the types of the photons in absolute accuracy. For example, photons from radiative decays might be mistaken as FSR photons. Despite this, generalized ISR and FSR photons are good concepts, particularly in cases where the sources of the photons are not required to be distinguished clearly. The program will label the generalized ISR and FSR photons as γ^I (gammaI) and γ^F (gammaF) in the output pdf (plain text) files, respectively.

Notably, we are not concerned about these ISR and FSR photons in many cases, particularly when we want to identify our signals from some samples. If they have already been marked out beforehand, one can make the program ignore them accurately by setting the following two items to “Ys”.

```
% Ignore ISR photons (Three options: Ys, Yg and N. Default: N)
{
  Ys
}

% Ignore FSR photons (Three options: Ys, Yg and N. Default: N)
{
  Ys
}
```

In cases that these photons are not marked in advance, the option “Yg” can be used to ignore the generalized ISR and FSR photons. In “Ys” and “Yg”, “s” and “g” are the initials of the words “strict” and “generalized”, respectively.

838 5.4. Settings on candidate based analysis

839 According to the number of signal candidates in an event that are selected and retained to
840 extract physics results, data analysis in high energy experiments can be divided into the following
841 two categories: event based analysis and candidate based analysis. While at most one candidate
842 in an event is kept in event based analysis, one or more candidates in an event can be retained in
843 candidate based analysis. Generally, the quantities related to a candidate are stored in an entry of
844 the TTree objects in the root files. Thus, one or more entries relate to an event in candidate based
845 analysis, while only one entry corresponds to an event in event based analysis. Normally, the
846 indices of candidates within an event are stored in the corresponding entries in candidate based
847 analysis.

848 By default, the program analyzes the input entries one by one. In this case, the events with
849 multiple candidates will be processed repeatedly. Particularly, the number of physics processes at
850 the sample level will be overcounted. One can make the program avoid the problem by inputting
851 “Y” to the following item.

```
852  
853 % Avoid over counting for candidate based analysis (Two options: Y and N. Default: N)  
854 {  
855     Y  
856 }
```

857 Also, the indices of candidates within an event are required. We can tell the program the related
858 TBranch name with the following item.

```
859  
860  
861 % TBranch name of the indices of candidates in an event (Default: __candidate__)  
862 {  
863     iCandidate  
864 }
```

865
866 With the settings, the program will process the first entry of each event in a normal way, including
867 obtaining and storing the topology tags; it will not analyze the other entries of the same event,
868 but only store the same topology tags to them.

869 5.5. Setting on charge conjugation

870 Charge conjugation is an important concept in high energy physics. By default, charge con-
871 jugate objects (particles and decays) are processed separately in the program. However, we need
872 to handle them together in many physics studies because of the sameness between them. One
873 can have the program process them together with the item below set to “Y”.

```
874  
875 % Process charge conjugate objects together (Two options: Y and N. Default: N)  
876 {  
877     Y  
878 }
```

879
880 Performing topology analysis with this setting inserts new topology tags in the output root files
881 and adds new counters to topology maps in the output plain text, tex source, and pdf files. Tables
882 20 and 21 list and interpret all of the topology tags related to charge conjugation involved in the
883 component analysis and signal identification functionalities, respectively.

884 As an example, we carry out the component analysis over the decay branches of D^{*+} and J/ψ
885 with the charge conjugation setting. The resulting topology map of D^{*+} is displayed in Table
886 22. Besides the columns in Table 4, two additional columns with the headers “nCccCase” and
887 “nAllCase” are inserted in the table. Here, “nCccCase” represents the number of cases involving

the charge conjugate particle (D^{*-} in this table), and “nAllCase” is the sum of “nCase” and “nCccCase”.

Table 20: Topology tags related to charge conjugation involved in each kind of component analysis. For the latter five kinds of component analysis, the topology tags in the (1) and (2) groups are only designed for the self-charge-conjugate and non-self-charge-conjugate particles and decay branches, respectively. The acronyms “cc” and index_{cc} are short for “charge conjugate” and “charge conjugate index”, respectively. For self-charge-conjugate objects (particles or decays), the charge conjugate indices have the value 0; for non-self-charge-conjugate objects, they have the value 1 or -1 : while 1 tags the objects presented in the topology maps, -1 indicates their charge conjugate objects.

Component type	Topology tag	Interpretation
Decay trees	iCcDcyTr	index_{cc} of decay tree
Decay initial-final states	iCcDcyIFSts	index_{cc} of decay initial-final states
Decay branches of particles	iCcPDcyBr.i	index_{cc} of particle _i
	(1) iCcDcyBrP.i.j	index_{cc} of decay branch of the j^{th} particle _i
	(2) nCcPDcyBr.i	number of cc particle _i s (decay branches)
	(2) iDcyBrCcP.i.j	index of decay branch of the j^{th} cc particle _i
	(2) nAllPDcyBr.i	number of all particle _i s (decay branches)
Cascade decay branches of particles	iCcPCascDcyBr.i	index_{cc} of particle _i
	(1) iCcCascDcyBrP.i.j	index_{cc} of cascade decay branch of the j^{th} particle _i
	(2) nCcPCascDcyBr.i	number of cc particle _i s (cascade decay branches)
	(2) iCascDcyBrCcP.i.j	index of cascade decay branch of the j^{th} cc particle _i
	(2) nAllPCascDcyBr.i	number of all particle _i s (cascade decay branches)
Decay final states of particles	iCcPDcyFSt.i	index_{cc} of particle _i
	(1) iCcDcyFStP.i.j	index_{cc} of decay final state of the j^{th} particle _i
	(2) nCcPDcyFSt.i	number of cc particle _i s (decay final states)
	(2) iDcyFStCcP.i.j	index of decay final state of the j^{th} cc particle _i
	(2) nAllPDcyFSt.i	number of all particle _i s (decay final states)
Inclusive decay branches	iCcIncDcyBr.i	index_{cc} of inclusive decay branch _i
	(1) iCcDcyBrIncDcyBr.i.j	index_{cc} of decay branch of the j^{th} inclusive decay branch _i
	(2) nCcIncDcyBr.i	number of cc inclusive decay branch _i es
	(2) iDcyBrCcIncDcyBr.i.j	index of decay branch of the j^{th} cc inclusive decay branch _i
	(2) nAllIncDcyBr.i	number of all inclusive decay branch _i es
IRA decay branches	iCcIRADcyBr.i	index_{cc} of IRA decay branch _i
	(1) iCcDcyBrIRADcyBr.i.j	index_{cc} of decay branch of the j^{th} IRA decay branch _i
	(2) nCcIRADcyBr.i	number of cc IRA decay branch _i es
	(2) iDcyBrCcIRADcyBr.i.j	index of decay branch of the j^{th} cc IRA decay branch _i
	(2) nAllIRADcyBr.i	number of all IRA decay branch _i es

In the example, besides the essential topology tags “nPDcyBr.i” and “iDcyBrP.i.j”, the following three groups of topology tags related to charge conjugation are also inserted in the output root files: (1) “iCcPDcyBr.i” for all specified particles; (2) “iCcDcyBrP.i.j” only for self-charge-conjugate particles, such as J/ψ ; (3) “nCcPDcyBr.i”, “iDcyBrCcP.i.j”, and “nAllPDcyBr.i” only for non-self-charge-conjugate particles, such as D^{*+} . Here, “iCcPDcyBr.i” tags whether the i^{th} particle is self-charge-conjugate. For self-charge-conjugate particles, it has the value 0; for non-self-charge-conjugate particles, it has the value 1.

The topology tag “iCcDcyBrP.i.j” records the charge conjugation property of the decay branch of the j^{th} instance of the i^{th} particle. For self-charge-conjugate decay branches, it has the value 0; for non-self-charge-conjugate decay branches, it has the value 1 or -1 : while 1 tags the decay branches listed in the topology maps, -1 indicates their charge conjugate decay branches. Whereas the equal values of “iDcyBrP.i.j” for each decay branch and its charge con-

jugate decay branch indicate their sameness, the opposite values of “iCcDcyBrP.i.j” for them reflect their difference.

The topology tag “iDcyBrCcP.i.j” is designed for the charge conjugate particle of the i^{th} particle (for D^{*-} in this example). It has a similar meaning as “iDcyBrP.i.j”. Particularly, the values of “iDcyBrP.i.j” and “iDcyBrCcP.i.j” tagging charge conjugate decay branches are equal to each other. The topology tag “nCcPDcyBr.i” stands for the number of instances (or decay branches) of the charge conjugate particle of the i^{th} particle found in each event, and “nAllPDcyBr.i” is the sum of “nPDcyBr.i” and “nCcPDcyBr.i”.

Table 21: Topology tags related to charge conjugation involved in each kind of signal identification. For the latter five kinds of signal identification, the topology tags in the (*) groups are only designed for the non-self-charge-conjugate particles and decay branches. The acronyms “cc” and index_{cc} are short for “charge conjugate” and “charge conjugate index”, respectively. For self-charge-conjugate objects (particles or decays), the charge conjugate indices have the value 0; for non-self-charge-conjugate objects, they have the value 1 or -1 : while 1 tags the objects presented in the topology maps, -1 indicates their charge conjugate objects.

Signal type	Topology tag	Interpretation
Decay trees	iCcSigDcyTr	index_{cc} of signal decay tree
Decay initial-final states	iCcSigDcyIFSts	index_{cc} of signal decay initial-final states
Particles	iCcSigP.i	index_{cc} of signal particle _i
	(*) nCcSigP.i	number of cc signal particle _s
	(*) nAllSigP.i	number of all signal particle _s
Decay branches	iCcSigDcyBr.i	index_{cc} of signal decay branch _i
	(*) nCcSigDcyBr.i	number of cc signal decay branch _{es}
	(*) nAllSigDcyBr.i	number of all signal decay branch _{es}
Cascade decay branches	iCcSigCascDcyBr.i	index_{cc} of signal cascade decay branch _i
	(*) nCcSigCascDcyBr.i	number of cc signal cascade decay branch _{es}
	(*) nAllSigCascDcyBr.i	number of all signal cascade decay branch _{es}
Inclusive decay branches	iCcSigIncDcyBr.i	index_{cc} of signal inclusive decay branch _i
	(*) nCcSigIncDcyBr.i	number of cc signal inclusive decay branch _{es}
	(*) nAllSigIncDcyBr.i	number of all signal inclusive decay branch _{es}
IRA decay branches	iCcSigIRADcyBr.i	index_{cc} of signal IRA decay branch _i
	(*) nCcSigIRADcyBr.i	number of cc signal IRA decay branch _{es}
	(*) nAllSigIRADcyBr.i	number of all signal IRA decay branch _{es}

Table 22: Decay branches of D^{*+} (with the charge conjugation setting).

rowNo	decay branch of D^{*+}	iDcyBrP	nCase	nCcCase	nAllCase	nCCase
1	$D^{*+} \rightarrow \pi^+ D^0$	0	31180	31291	62471	62471
2	$D^{*+} \rightarrow \pi^0 D^+$	1	13978	14166	28144	90615
3	$D^{*+} \rightarrow D^+ \gamma$	2	700	721	1421	92036
4	$D^{*+} \rightarrow \pi^+ D^0 \gamma^F$	3	28	36	64	92100
5	$D^{*+} \rightarrow \pi^0 D^+ \gamma$	4	0	1	1	92101

5.6. Setting on initial state particles

In all of the previous examples, the program is applied to the inclusive MC samples in e^+e^- colliding experiments. Besides, the program can also be used in other types of high energy experiments, for example, the PANDA experiment [14], a $p\bar{p}$ annihilation experiment under construction at Darmstadt, Germany. On these occasions, we have to specify the right initial state particles with the following item to obtain the proper topology maps.

```

917 % Initial state particles (Default: e- e+)
918 {
919     anti-p-   p+
920 }

```

922 With the setting, the default initial state e^+e^- is replaced by $p\bar{p}$, as shown in Table 23, which
923 displays the results of a component analysis over decay trees of a small $p\bar{p}$ annihilation sample.

Table 23: Decay trees and their respective initial-final states ($p\bar{p}$ annihilation).

rowNo	decay tree	decay final state	iDcyTr	nEtr	nCEtr
1	$p\bar{p} \rightarrow p\bar{p}$	$p\bar{p}$	1	232	232
2	$p\bar{p} \rightarrow \pi^+\pi^-p\bar{p}$	$\pi^+\pi^-p\bar{p}$	24	53	285
3	$p\bar{p} \rightarrow \pi^0p\bar{p}$	$\pi^0p\bar{p}$	5	35	320
4	$p\bar{p} \rightarrow \pi^0\pi^+\pi^-p\bar{p}$	$\pi^0\pi^+\pi^-p\bar{p}$	0	33	353
5	$p\bar{p} \rightarrow \pi^0\pi^0\pi^+\pi^-\pi^-\pi^+$	$\pi^0\pi^0\pi^+\pi^-\pi^-\pi^+$	39	31	384
rest	$p\bar{p} \rightarrow \text{others (184 in total)}$	corresponding to others	—	616	1000

924 6. Summary

925 We develop a program, namely TopoAna, with C++, ROOT, and LaTeX for the topology
926 analysis of inclusive MC samples in high energy physics experiments. The program has rich
927 functionalities and aims to solve all kinds of topology analysis tasks. Meanwhile, it is easy to
928 use and has a high processing rate. These features make the program a powerful tool to analyze
929 the backgrounds involved in our research works and to identify the physics processes of interests
930 from the inclusive MC samples.

931 Since it does not rely on any specific software frameworks, the program applies to many high
932 energy physics experiments. Up to now, it has been put into use in three experiments at e^+e^-
933 colliders: the BESIII, Belle, and Belle II experiments. Besides these experiments, it can also be
934 used in other types of experiments, such as the PANDA experiment, a $p\bar{p}$ annihilation experi-
935 ment. Also, the program is applicable to the future e^+e^- colliding experiments under research
936 and development, such as the circular electron-positron collider (CEPC) [15, 16] experiment in
937 China, the super Charm- τ factory (SCTF) experiment [17] in Russia, and the super τ -Charm fac-
938 tory (STCF) experiment [18] in China. These experiments offer wide space for the application of
939 the program. With more user needs coming out in the future, we will further extend and perfect
940 it to make it more powerful and well-rounded.

941 Acknowledgements

942 This work was supported by the National Natural Science Foundation of China [grant num-
943 bers 11575017, 11661141008, 11761141009, 11875262, 11975076] and the CAS Center for
944 Excellence in Particle Physics (CCEPP). In addition, we would like to thank all of the people
945 who have helped us in the development of the program. We first thank Prof. Changzheng Yuan,
946 Bo Xin, and Haixuan Chen for their help at the early stage of developing the program. We are
947 particularly grateful to Prof. Xingtao Huang for his comments on the principles and styles of the
948 program, to Remco de Boer for his suggestions on the tex output and the use of GitHub, and to
949 Xi Chen for his discussions on the core algorithms. We are especially indebted to Prof. Xiqing

Hao, Longke Li, Xiaoping Qin, Ilya Komarov, Yubo Li, Guanda Gong, Suxian Li, Junhao Yin, Prof. Xiaolong Wang, and Yeqi Chen for their advice in extending and perfecting the program. Also, we thank Xi'an Xiong, Runqiu Ma, Wencheng Yan, Sen Jia, Lu Cao, Dong Liu, Hongpeng Wang, Jiawei Zhang, Hongrong Qi, Jiajun Liu, Maoqiang Jing, Yi Zhang, Wei Shan, and Yadi Wang for their efforts in helping us test the program.

References

- [1] ROOT User's Guide, Available online: <https://root.cern/root/html/doc/guides/users-guide/ROOTUsersGuide.html>.
- [2] Documentation of the TFile class, Available online: <https://root.cern/root/html534/TFile.html>.
- [3] K.T. Chao, Y.F. Wang, et al., Int. J. Mod. Phys. A 24 (2009) S1-794.
- [4] M. Ablikim, et al. (BESIII Collaboration), White Paper on the Future Physics Programme of BESIII, arXiv:1912.05983.
- [5] E. Kou, et al., Prog. Theor. Exp. Phys. 2019 (2019) 123C01.
- [6] J. Brodzicka, T. Browder, P. Chang, et al., Prog. Theor. Exp. Phys. 2012 (2012) 04D001.
- [7] Text of MIT license, Available online: <https://mit-license.org/>.
- [8] Documentation of the TTree class, Available online: <https://root.cern/root/html534/TTTree.html>.
- [9] Documentation of the TBranch class, Available online: <https://root.cern/root/html534/TBranch.html>.
- [10] M. Tanabashi, et al. (Particle Data Group), Phys. Rev. D 98 (2018) 030001.
- [11] Documentation of the TChain class, Available online: <https://root.cern/root/html534/TChain.html>.
- [12] Documentation of the Draw() method of the TTree class, Available online: <https://root.cern/root/html534/TTTree.html#TTTree:Draw@2>.
- [13] Documentation of the GetEntries() method of the TTree class, Available online: <https://root.cern/root/html534/TTTree.html#TTTree:GetEntries@1>.
- [14] W. Erni, et al. (PANDA Collaboration), Physics Performance Report for PANDA: Strong Interaction Studies with Antiprotons, arXiv:0903.3905.
- [15] CEPC CDR Volume 1 (Accelerator), Available online: http://cepc.ihep.ac.cn/CEPC_CDR_Vol1_Accelerator.pdf.
- [16] CEPC CDR Volume 2 (Physics & Detector), Available online: http://cepc.ihep.ac.cn/CEPC_CDR_Vol2_Physics-Detector.pdf.
- [17] A.E. Bondar, et al. (Charm-Tau Factory Collaboration), Phys. Atom. Nucl. 76 (2013) 1072.
- [18] Q. Luo, D. Xu, "Progress on Preliminary Conceptual Study of HIEPA, a Super Tau-Charm Factory in China", in Proc. 9th International Particle Accelerator Conf. (IPAC2018), Vancouver, BC, Canada, 422.