Final interview guideline:

During the final interview, you will need to demonstrate your system and the system performance will be evaluated based on its accuracy of step and heading angle detection.

1. You can assume at the starting point the **step count is 0** and **heading angle is also 0º (i.e. heading angle is relative to the direction you are facing, when you start the system**).
2. During the interview, you will be asked to start you system at a location in the MDLS lab facing any direction, and then gradually change your heading direction, standing at a fixed point. The heading angle will be verified at discrete steps when the interviewer asked you to start or stop turning. **The heading angles should be between 0-359°**. A 90° clockwise turn from 0º will give you a 90° heading angle, and a 90° anti-clockwise turn from 0º will give you 270° heading angle.
3. Following the heading angle test, you will be asked to move certain number of steps to verify the step count detection.
4. Your group can have 2 attempts, and the best performance will be considered.
5. Your tracking device need to be detached from any cables/devices. Please make sure your device is charged before the interview.
6. Your tracking device will be connected with a **marking app** via Bluetooth, and should continuously send the step and heading angle (through the COMP_Value.Steps , COMP_Value.Heading variables given in the code), which will be collected by the app for marking purpose. These are also plotted in the gyroscope section of the ST app, if you want to verify your Bluetooth packet outputs. Please make sure you can display the true step (as gyro_x) and orientation (as gyro_y) values in the ST app.
7. You will need to answer some interview questions regarding your implementation to demonstrate your understanding and explain the design decisions you made.

