Paper Time [90 minutes]

CS420 – Web Development for Portable Devices

Final Term Spring 2023 (Sample Paper)

MCQs

Take an assessment.

Question#1

We define a _____ at the top where we will display the screen coordinates of the most recent touch.

A. Div
B. Heading
C. Br
D. Href

We define a touch-sensitive div to which we will attach an event listener. We also define a div at the top where we will display the screen coordinates of the most recent touch.

Question#2

To do something with the touch data, we add a _____ function.

A. Catch
B. Handler
C. Open
D. Close

we add some JavaScript to register the event listener, and add a handler function to do something with the touch data:

Question#3

How many coordinates of the touch we can grab in touchHandler function?

A. 2
B. 10
C. 18
D. 26

In the touchHandler function we grab the x and y coordinates of the touch, and write them to the coords div:

Question#4

Coordinates of the touch in touchHandler are written in _____ div.

A. Heading
B. Href
C. Coords
D. Br

In the touchHandler function we grab the x and y coordinates of the touch, and write them to the coords div:

Question#5

We can display the screen coordinates of the most recent touch by defining div at the _____.

A. top

B. down
C. left
D. right

We also define a div at the top where we will display the screen coordinates of the most recent touch.

Question#6

To handle all types of events like mouse, touch and pen events, we have to write the code_____ for each.

A. Touch events
B. Mouse events
C. Pen events
D. Separately

To handle the mouse events, touch events and pen events we have to write the code separately for each of these.

Question#7

Pointer events include:

A. Touch events
B. Delete events
C. Update events
D. Insert events

Question#8

Pointer events model is proposed by_____.

A. Tesla
B. Microsoft
C. IBM
D. Intel

Microsoft made a standards proposal that reconciles touch events and mouse events and pen input too, into one model called pointer events.

Question#9

_____API was defined in terms of *Touch*es.

A. Delete events
B. Create events
C. Update events
D. Touch events

While the Touch Events API was defined in terms of Touches, the Pointer Events API is defined in terms of Pointers,

Question#10

_____API is defined in terms of *Pointer*s.

A. Create events
B. Update events
C. Delete events
D. Pointer events

While the Touch Events API was defined in terms of Touches, the Pointer Events API is defined in terms of Pointers,

Question#11

Pointer is defined for _____ devices.

A. Input
B. Output
C. Both Input and Output
D. IoT

Pointer is defined as: A hardware agnostic representation of input devices that can target a specific coordinate on a scree

Question#12

Pointer attribute is _____.

A. pointer
B. pointerId
C. screen
D. screenId

Pointer attributes: Attribute pointerId screenX screenY clientX clientY pageX pageY width height tiltX tiltY pressure pointerType isPrimary

Question#13

Pressure is a pointer attribute that means _____.

A. Pressure of contact on screen

B. Pressure of contact on pointer
C. Pressure of contact on width
D. Pressure of contact on height

pressure: pressure of contact on screen

Question#14

To present the class of pointer, we used _____.

A. Pointer
B. PointerId
C. PointerPressure
D. PointerType

pointerType class of Pointer: mouse, pen, or touch

Question#15

To present the main Pointer for a pointer type, we use _____.

A. PointerType
B. PointerPressure
C. IsPrimary
D. IsSecondary

isPrimary: is this the main Pointer for a pointer type

Question#16

Which of the following is event type?

A. Pointerenter
B. Pointerexit
C. Pointercreate
D. Pointerdelete

Event types :Pointerover pointerenter pointerdown pointermove pointerup pointercancel pointerout pointerleave gotpointercapture lostpointercapture

Question#17

When an element becomes target of pointer, we use _____.

A. Got
B. Gotpointer
C. Gotpointercatch
D. Gotpointercapture

gotpointercapture: when an element becomes target of pointer

Question#18

When element loses pointer capture, we use _____.

A. Lost
B. Lostpointer
C. Lostpointercatch
D. Lostpointercapture

lostpointercapture when element loses pointer capture

Question#19

Polyfill library refers to a _____ library.

A. JavaScript
B. HTML
C. PHP
D. CSS

It refers to a JavaScript library that implements an HTML5 web standard

Question#20

While entering data using any input entry method, data should be _____.

A. Visible
B. Not visible
C. Same
D. Not same

while entering data it should be clearly visible. It is much difficult to enter the small font data.

Question#21

Which of the following font size data will be difficult to enter?

A. Small
B. Large
C. Both small and large

while entering data it should be clearly visible. It is much difficult to enter the small font data.

D. Medium

Question#22

Input entry should be _____ for all the users.

A. Difficult
B. Easy
C. Both difficult and easy
D. Moderate

we must make of Input entry easy for all the users.

Question#23

Which of the following is not an input type in HTML5?

A. Date
B. Week
C. Month
D. Decade

Input Types in HTML5: search, email, url, tel number, range, date, month, week, time, datetime, datetime, local, color.

Question#24

Which of the following syntax is used for the most common input type?

A. <input type="text">
B. <input type="">
C. < type tel="text">
D. <input email ="text">

Text: The most common input type <input type="text">

Question#25

Which of the following syntax is used for the input type as email?

A. <input type="email">
B. <input type="">
C. < type text="email">
D. <input enter="email">

When we use Input Type as email. We get a @ sign as well as .com and other handy buttons: <input type="email">

Question#26

We get a @ sign as well as the .com by using the input type as_____.

A. Text
B. Radio button
C. Hidden field
D. Email

Question#27

Entering an email on the standard keyboard is _____.

A. Easy
B. Difficult
C. Not possible
D. Not allowed

Entering an email on the standard keyboard is very difficult.

Question#28

_____ Input provides the user with ability to add the numbers.

A. Email
B. Text
C. Tel
D. Radio button

Tel input provides the user with ability to add the numbers , it provides ability to quickly add *, # , + signs as well.

Question#29

We can add *, # , + signs by using input type as _____.

A. Tel
B. Text
C. Email
D. Hidden field

Tel input provides the user with ability to add the numbers , it provides ability to quickly add *, # , + signs as well.

Question#30

Which of the following syntax is used for the input type as Tel?

A. <input type="">
B. <input type="tel">
C. <input enter="tel">
D. <type text="tel">

<input type="tel">

Question#31

Which of the following Input types is used to enter the date on a Webpage?

A. Tel
B. Date
C. Email
D. Text

Date input types makes it very easy to enter the date on Webpage.
<input type="date">

Question#32

Which of the following input type is used to enter date and time?

A. <input type="time">
B. <input type="date">
C. <input type="datetime">
D. <input text="datetime">

Using Date & Time input it becomes very easy to enter data.
<input type="datetime">

Question#33

Which of the following can be used for client side validation?

A. Pattern attribute
B. Tel attribute
C. Text attribute
D. Email attribute

There's also a pattern attribute on the input element, that you can use to validate on the client side validation.

Question#34

Which of the following syntax is used for the input type as Password?

A. <input type="password">
B. <input password="type">
C. <type enter="password">
D. <input type="enterpassword">

Question#35

How can we apply the limit on password that must contain 8 or more characters?

A. Pattern =".{8,}"
B. Pattern ="8.{password}"
C. Pattern ="password8.{}"
D. Pattern.8 =".{password}"

check it in the example number 2 of Regular Expression Validation

Question#36

To increase the touchable area of the control, we can ____ label elements around input elements.

A. Modify
B. Delete
C. Wrap
D. Both modify and delete

You should always wrap label elements around your input elements, and their associated labeling texts, because it increases the touchable area of control.

Question#37

Which of the following URL is used to dial a telephone number?

A. Telecolon
B. Telephone
C. Telenumber
D. Telephonenumber

On mobile, you can use a telecolon URL to create a URL that when activated will actually dial a telephone number

Question#38

Which of the following URL typically fail on a desktop to dial a telephone number?

A. Telephone

B. Telenumber **C.** Telephonenumber D. Telecolon On mobile, you can use a telecolon URL to dial a telephone number and on desktop, these URLs will typically fails.
Question#39
Which of the following is the correct syntax of the accept attribute? A. <input type="file" file="image/*"> B. <input type="accept" accept="file/*"> C. <input type="file" accept="image/*"> D. <input type="file" image="file/*"> Accept attribute takes a comma-separated list of unique content types of files: <input type="file" accept="image/*">
Question#40
Which of the following API is used to get Live Input? A. GetUserMedia B. GetLiveUserMedia C. GetLiveMedia D. GetLive We can get Live Input, Audio and Video, directly under our App by using an API called getUserMedia.

Subjective Questions (3 Marks)

Question#1
Define a touch-sensitive div to which you can attach an event listener and also define a div at the top where you will display the screen coordinates of the most recent touch.
Question#2
What are Pointer Events, and write their description as well?
Question#3
Write any three pointer attributes.
Question#4
Write any three event types.
Question#5
Write touch handler guide lines.
Question#6
What are virtual keyboards?

Subjective Questions (5 Marks)

Question#1
Write any five input type names in HTML5.
Question#2
Write at least three important features of input.
Question#3
What is Telecolon URL, and write its syntax?
Question#4
Write any five sensor names that can be found today in mobile phones.