

CS301 quiz(1) file

By

<https://vuonlinehelp.blogspot.com/>

Compose by (ALI HASSAN)

If the elements are 3, 5, 1, 6 in which order they will be removed from the queue one by one

3516

The.....of a binary tree is a maximum level of its leaves (also the depth).

height

.....of the an empty AVL tree is define to be

Height

Following is the keyword of c++

Delete

In the perspective of memory organization every process expecting the first part of memory is for.....of the program.

code

The.....of a node in a binary tree is define as the height of its left

subtree minus height of its right subtree.

balance

If p is pointing to a node in an existing tree then info (p) means

Return the content of node p.

Following is a keyword of c++.....

Delete

Every.....tree is a binary search tree

AVL

If a function has recursive call as last statement it is known as.....

Tail recursive

During in a order traversal call if we found a node is null it means this node will satisfy following condition

it will not have left child

In binary search tree deleting a node is easy if it is a..... node

Root

Which of the following operation returns the content of binary tree node?

Info (p)

1 2 6

5 8

3

4

1 2 3 4 5 6 8

in a complete binary tree the number of node of level 5 are

30

One should be careful about transient.....that are stored by reference I data structure

Objects

In a tree we link the node in such a way that it.....a linear structure

does not remain

the function call are mode with the help of.....

stack

18. 15 25 45

35 75

15 35 25 75 45

A binary is said to be a.....binary tree if every non leaf node in binary tree has non empty left and right structure

Strictly

In which of the following function signature the value of variable num cannot be changed in function body

Binary search tree

Two common method of simulations are.....are.....

Time based simulation and event based simulation

Generally there are case (s)to delete a node from BST

1

When a function calls another function the parameters and address of the calling function are put in...

Stock

Binary search tree ()is a.....

Destructor

We can calculate the.....of subtree by counting its level from the bottom

Nodes

If there is a strictly complete binary tree of depth 3 the total number of nodes it will be

7

Amodel attempt to model real word phenomenon

Simulation

The process of getting the value of a variable using a pointer is called

Dereferencing

When a function calling itself is called as.....

Recursion

A.....is a tree in which every except possibly the last, is completely filled

Strict binary tree

In AVL tree during insertion, a single rotation can fix the balance in cases _____ and 4.

1

If a node is inserted in outer side of a node in binary search tree then to make it AVL tree,

We may have to apply single rotation

A zigzag rotation is performed. In Left-Left case of rotation in AVL tree.

False

The principal benefit of a linked list over a conventional array is that the order of the linked items may be_____ from the order that the data items are stored in memory.

Same

Stack.push(15) will push 15 on _____.

Top of the stack

Suppose we have the following values to be inserted in constructing AVL tree,

10,13,15,5,7,8

Tell when first rotation will take place,

After inserting the node 15

All the objects created using _____ operator have to be explicitly destroyed using the delete operator.

New

During the execution of a process, operating system constructs four things for that process. Which of the following is not part of that process?

Linked list

There are _____ cases of Rotation in AVL tree.

4

Which of the following line of code is incorrect?

`Float *l = float new` (not confirmed)

In simple or singly linked list there is/are _____ pointer/s in each node.

One

Suppose there are three nodes tree with three numbers 14, 4, 15. Following is not a permutation, or combination for output them.

(4, 4, 15)

The type of expression in which operator succeeds its operands is _____ expression.

Postfix

The _____ of a node in a binary tree is defined as the height of its left subtree minus height of its right subtree.

Balance

If both left and right nodes of a node are NULL then this type of node is called a _____ node.

Non leaf (not confirmed)

The function calls are made with the help of_____.

Stack

Which data structure is needed to convert infix expression to postfix expression?

Stack

In case of insertion of right inner node in BST,

Left rotation then right to make AVL

A BST generated from the data in ascending order is _____.

Linear

Which operation of queue data structure is used to get front element from the queue and then remove it from the queue?

Remove ()

In _____ various cells of memory are not located continuously.

Linked list

The _____ method of list will position the currentNode and lastCurrentNode at the start of the list.

Start

Which operation of queue data structure is used to insert an element into the Queue?

Enqueueer ()

From Operating System point of view, the recursive function calls are made with the help of _____.

Queue

We can make a lexicographic order of characters based on their _____.

ASCII values

What are the basic things associated with data structures?

All of the above

Consider the following push operations of a Stack:

Stack.push(4);

Stack.push(6);

Stack.push(5);

Stack.push(8);

If a user calls a pop() operation, then which value will be returned?

8 (stack is last in first out)

~BinarySearchTree() is a _____.

Destructor

Array cells are _____ in computer memory.

Contiguous

Leaf node of binary search tree contains _____

One Null Pointer

dequeue() operation of queue data structure is used to _____

remove an element from the front and return it

The depth of a binary tree is

Maximum level of a leaf

Which of the following operation returns but do not removes top value of the stack?

Top

Which of the following data structure is linear type?

All of above

In doubly linked list a node consists of three parts:

2 pointers and 1 object

Last node in circular linked list contains

No null pointer

A _____ model attempts to model a real-world phenomenon

Simulation

Factorial is an example of _____ function.

Recursive

The balance of a node in a binary tree is defined as the height of its _____ sub tree minus height of its right sub tree.

Left

In case of insertion of left outer node in BST,

We first apply left rotation and then rotation to make it an AVL Tree.

`int htdiff = height(root->getLeft()) - height(root->getRight());` The above line of code is taken from AVL insert method. Complete it by selecting an appropriate symbol.

Minus (-)

Each operator in a postfix expression refers to the previous _____ operand(s).

Two

For making Binary Search Tree for Strings we need, _____ data type.

Int

A _____ model attempts to model a real-world phenomenon

Simulation

The lifetime of a transient object cannot exceed that of the application.

True

Which one of the following calling method does not change the original value of the argument in the calling function?

Call by passing the value of the argument

In level-order traversal for Binary Search Tree, we visit the nodes at each level before proceeding to the next level, in a _____ order.

Left-to-right

In doubly linked list a node consists of three parts:

1 pointer and 2 objects

Binary Search Tree violates the condition of AVL tree when any node has balance equal to

1 or -1

To search an element in AVL tree, it takes maximum $1.88 \log_2 n$ time

True

How many cases of rotation are there in AVL tree?

4

_____ tree has been named after two persons Adelson-Velskii and Landis.

AVL

Which of the following is a nonlinear data structure?

Tree

AVL tree is nonlinear data structure.

True

_____ is when function is calling to itself.

Recursion

Which of the following function don't belongs to the stack class?

Crash ()

Which one is the cored function call for the following function of calculating cube?

```
int cube(int& num)
```

cube (num)

Binary search algorithm cannot be applied to ____

None of the given

copy() method of list data structure _____

Set one list to be a copy of another

While implementing non-recursive traversal for Binary Search Tree, we need to implement

Stack

Following is true in case of using Recursive method calls

The code becomes very short

_____is a self-balancing tree.

Binary Search Tree

While implementing stack with an array and to achieve LIFO behavior, we used push and pop elements at

The start of the array

Generalized code written for a class is called

Structure

Array cells are _____ in computer memory

Contiguous

In singly linked list a node comprises of _____ field/s.

Two

Which of the following statement is false?

Pointers store the next data element of a list

Leaf node of binary search tree contains _____

One null Pointer

What will be the result of evaluating following expression?

$5 + 3 * 2 / (6 - 3)$

7

Want and de-allocating memory for linked list nodes does take less time than pre-allocated array

MORE

Suppose you are writing a class for Node class and forgot to write the constructor of the class, then

Compiler will automatically generate a default constructor

Factorial is an example of _____ function.

Recursive

A binary tree is said to be a _____ binary tree if every non-leaf node in a binary tree has non-empty left and right subtrees.

Strictly

Memory address is stored in

Pointer

In level-order traversal for Binary Search Tree, _____ data structure is used.

Queue

Which of the following is the correct option for priority Queue?

The type of queues that is FIFO i.e. the person who comes first should leave first.

AVL tree is linear data structure.

False

AVL tree is a binary search tree

True

The post order traversal of a binary tree is DEBFCA. Find out the pre order traversal

A

Λ

B C

$\wedge /$

D E F

ABDCEF

In a tree, we link the nodes in such a way that it _____ a linear structure.

Does not remain

add(12) method of linked list class will:

Add 12 as value in linked list

Which of the following is the correct conversion of infix to postfix expression?

$Z+B-(D-H)/K$

ZB+DH-K/-

In singly linked list "next" field of node contains:

Address of next node

Which of the following line of code is incorrect?

The lifetime of a transient object can exceed that of the application which is accessing it.

A list is the collection of items of the _____

same type

back() method of List class is used to:

Moves the "current" pointer to backward one element.

Suppose you are writing a class for Node class and forgot to write the constructor of the class, then

_____ is the maximum height of the AVL tree.

$1.44\log_2 n$

length() method of List class is used to:

Return the length of the list

There are four cases of rotation in an _____ tree.

AVL

Allocating and de-allocating memory for linked list nodes does take _____ time than pre-allocated array.

More

_____ is utilized at the time of memory allocation in dynamic manner.

Heap

In which case of insertion we require double rotation to make the AVL tree balance.

None

The back() method decreases the value of variable current by _____.

One

In array list the worst case of removing an element is

To remove the item from start

Left, right, info, and parent are the operations of _____ data structure.

Tree

Which of the following is TRUE for search operations in a binary tree as compared to linked list or an array?

It increase the number of comparison

Which of the following is a correct statement?

An AVL tree is identical to BST except the height of left and right subtree can differ by at least 1

length() method of List class is used to:

Return the length of the list

Whenever we call a function, the compiler makes a stack, the top element of the stack is _____ of the function.

Return Address

Whenever we call a function, the compiler makes a _____ that it uses to fulfill this function call.

Stack

_____ is the major factor to see the efficiency of a program.

Time

_____ rule applies for evaluating operators of same precedence in an expression

None

The postfix form of the expression $A + B * C$ and $(A + B) * C$ will be _____.

Same

If we use array to implement list, then there is an issue that it gives difficulty when:

We will access value randomly

During in-order traversal using recursive calls, if we found a node is NULL. It means this node will satisfy following condition.

It will not have left child

Which one the following is more closer to AVL tree, (chose the best option)

Binary Search Tree

start() method of List class is used to:

Move the current pointer to first element

Consider the following infix expression. $7/8 + 9$

If one converts the above expression into postfix, what would be the resultant expression?

$78/9+$

In internal memory organization of a process, there is some area of memory for static data that holds _____ variables.

Both Static and Global

In Left-Right case of rotation in _____ tree. A double rotation is performed.

AVL

If numbers 5, 222, 4, 48 are inserted in a queue, which one will be removed first?

5

Which one is not the property of binary tree?

Sibling node should be same parent (Not Sure)

Each node in singly linked list contains_____

One Pointers

What's wrong with following loop? `while( (i < 10) && (i > 24)) { }`

The Condition is always false

Which one of the following is TRUE about recursion?

1. Recursive function calls consume a lot of memory.
2. Recursion extensively uses stack memory.
3. Recursion extensively uses stack memory.
4. Iteration is more efficient than iteration.

Which of the following is not a data structure ?

1. Linked list

2. Queue
3. stack
4. Memory cell

“+” is a _____operator.

1. Unary
2. Binary
3. Ternary
4. None of the above

When an executable program run, it is loaded in the memory and becomes a_____.

1. Thread
2. .h file
3. Process
4. None of the above

www.vustudents.ning.com

In array list the worst case of removing an element is

1. To remove an element from the end of the list
2. To remove an element from the middle of the list
3. To remove an element from the start of the list
4. We cannot remove element from an array list

The tree data structure is a

1. Linear data structure

2. Graphical data structure
3. Non-linear data structure (Not Confirm)
4. Data structure like queue

In_____, a programmer uses two pointers in the node, i.e. one to point to next node and the other to point to the previous node.

1. Linked list
2. doubly-link list
3. array
4. Structure

Each operator in a postfix expression refers to the previous _____ operand(s)

1. one
2. two
3. three
4. four

Which of the following operations returns top value of the stack?

1. push
2. pop
3. top
4. First

In the calling function, after the execution of the function called, the program continues its execution from the _____ after the function call.

1. Previous line
2. Next line
3. Beginning
4. None of the above

_____ only removes items in reverse order as they were entered.

1. Queue
2. Stack
3. Both of these
4. None of these

In the linked list implementation of the stack class, where does the push member function place the new entry on the linked list?

1. After all other entries that are greater than the new entry.
2. At the head
3. After all other entries that are smaller than the new entry.
4. At the tail

Which of the following is known as "Last-In, First-Out" or LIFO Data Structure?

1. Linked List
2. Stack
3. Queue
4. Tree

A queue is a _____data structure, whereas a stack is a _____data structure.

1. FIFO, LIFO

Each node in doubly link list has

1. 2
2. 3
3. 4

Whenever we call a function, the compiler makes a stack, the top element of the stack is _____ of the function

1. First argument
2. Return address
3. Last argument
4. none of the above

_____ is the stack characteristic but _____ was implemented because of the size limitation of the array.

1. isFull(),isEmpty()

2. pop(), push()
3. isEmpty() , isFull()

Stack and Queue can be implemented using _____,

1. Singly Link List
2. Binary Tree
3. Binary Search Tree
4. AVL Tree

The _____ method of list will position the currentNode and lastCurrentNode at the start of the list.

1. Remove
2. next
3. start
4. back

In array list the worst case of removing an element is

1. To remove an element from the end of the list

2. To remove an element from the middle of the list
3. To remove an element from the start of the list
4. We cannot remove element from an array list

STL is a _____ that is a part of the official standard of C++.

1. C program file

2. .h file

When an executable program run, it is loaded in the memory and becomes a_____.

1. Thread

2. .h file

3. Process

4. None of the above

Each node in doubly link list has,

1. pointer

2. pointers

3. pointers

4. pointer

A queue is a _____data structure, whereas a stack is a _____data structure.

1. FIFO, LIFO

2. LIFO,FIFO

3. both of these

4. none of these

Which one of the following is TRUE about recursion?

1. Recursive function calls consume a lot of memory.

2. Recursion extensively uses stack memory.

3. Recursion extensively uses stack memory.
4. Iteration is more efficient than iteration.

To create a _____ we link the last node with the first node in the list.

1. Double linked list
2. Circularly-linked list
3. Linked list
4. None of the above

_____ is the stack characteristic but _____ was implemented because of the size limitation of the array.

1. isFull(),isEmpty()
2. pop(), push()

3. isEmpty() , isFull()

4. push(),pop()

The principal benefit of a linked list over a conventional array is that the order of the linked items may be_____ from the order that the data items are stored in memory.

1. Same

2. Identical

3. Different

4. Equivalent

In_____ the 'next' returns false when it reaches to the last node due to the fact that the next field of the last node is set to NULL.

1. Circular linked list

2. Triple linked list

3. Singly linked list

4. None of the above

If numbers 5, 222, 4, 48 are inserted in a queue, which one will be removed first?

1. 48

2. 4

3. 333

4. 5

Which boolean expression indicates whether the numbers in two nodes (p and q) are the same. Assume that neither p nor q is null.

1. `p == q`

2. `p.data == q.data`

3. `p.nextNode == q.nextNode`

4. `p.data == q`

Local variables of a function are stored in,

1. Binary Search Tree

2. Stack

3. Queue

4. AVL Tree

A queue is a data structure where elements are

1. inserted at the front and removed from the back.

2. inserted and removed from the top.

3. inserted at the back and removed from the front.

4. inserted and removed from both ends.

A kind of expressions where the operator is present between two

operands called _____expressions.

1. Infix

2. Postfix

3. Prefix

4. None of the above

A template is a function or class that is written with a _____data type.

1. Specific

2. Definite

3. Generic

4. None of the above.

Whenever we call a function, the compiler makes a stack, the top element of the stack is _____ of the function.

1. First argument

2. Return address

3. Last argument

4. None of the above

Which of the following can be used to reverse a string value,

1. Stack

2. Queue

3. Both of these

4. None of these

A queue is a _____data structure, whereas a stack is a _____data structure.

1. FIFO, LIFO

2. LIFO,FIFO
3. both of these
4. none of these

Stack and Queue can be implemented using _____,

1. Singly Link List
2. Binary Tree
3. Binary Search Tree
4. AVL Tree

Which of the following is not a data structure ?

1. Linked list
2. Stack
3. Queue
4. Memory cell

Compiler uses which one of the following in Function calls,

1. Stack
2. Queue
3. Binary Search Tree
4. AVL Tree

The principal benefit of a linked list over a conventional array is that the order of the linked items may be_____ from the order that the data items are stored in memory.

1. Same
2. Identical
3. Different
4. Equivalent

Doubly Linked List always has one NULL pointer.

1. True
2. False

We cannot remove items randomly from _____

1. Stack
2. Queue
3. Both of these
4. None of these

_____ is the maximum number of nodes that you can have on a stack-linked list ?

1. Zero
2. $2n$ (where n is the number of nodes in linked list)
3. Any Number
4. None of these

“+” is a _____operator.

1. Unary
2. Binary
3. Ternary
4. None of the above

In_____, a programmer uses two pointers in the node, i.e. one to point to next node and the other to point to the previous node.

1. Linked list
2. doubly-link list
3. array
4. structure

A queue is a data structure where elements are

1. inserted at the front and removed from the back.
2. inserted and removed from the top.

3. inserted at the back and removed from the front.

4. inserted and removed from both ends.

_____ is the stack characteristic but _____ was implemented because of the size limitation of the array.

1. isFull(),isEmpty()

2. pop(), push()

3. isEmpty() , isFull()

4. push(),pop()

The _____ method of list will position the currentNode and lastCurrentNode at the start of the list.

1. Remove

2. Next

3. Start

4. Back

Parameters in function call are passed using,

-
1. Stack
 2. Queue
 3. Binary Search Tree
 4. AVL Tree

If numbers 5, 222, 4, 48 are inserted in a queue, which one will be removed first?

1. 48
2. 4
3. 333
4. 5

For a perfect binary tree of height 4, what will be the sum of highest of node

1. 31
2. 30
3. 27

4. 26

If Ahmed is cousin of Ali and Ali is cousin of Asad then Ahmed is also cousin of Asad. This statement has the following property

1. Reflexivity
2. Symmetry
3. Transitivity
4. All of the above

Which one of the following is NOT the property of equivalence relation?

1. Reflexive
2. Symmetric
3. Transitive
4. Associative

The main reason of using heap in priority queue is

1. Improve performance

2. Code readable
3. Less code
4. Heap can't be used in priority queues

The total numbers of nodes on 10th level of perfect binary tree are

1. 256
2. 512
3. 1024
4. Can't be determined

Suppose there are 100 elements in an equivalence class, so initially there will be 100 trees, the collection of these trees is called _____.

1. Cluster
2. Class
3. Forest
4. Bunch

The percolate Down procedure will move the smaller value and

bigger value.

1. Left, right
2. Right, left
3. Down, up
4. Up, down

For a perfect binary tree of height h , having N nodes, the Sum of height of nodes is

1. $N - h - 1$
2. $N - 1$
3. $N - 1 + h$
4. $N - (h - 1)$

Which of the following method is helpful in creating the heap at once?

1. Insert
2. Add
3. Update

4. percolateDown

If ahmad is boss of ehsan and ehsan is boss of umer then ahmad is also boss of umer, the above-mentioned relation is_____ .

1. Reflexive
2. Symmetry
3. Transitive
4. None of given

If we want to find median of 50 elements, then after applying builtHeap method, how many times deleteMin method will be called?

1. 5
2. 25
3. 35
4. 50

Which of the following properties are satisfied by equivalence relationship?

1. Reflexive, symmetric

2. Reflexive, transitive

3. Symmetric, transitive

4. Reflexive, symmetric and transitive

Sorting procedure normally takes___ time.

1. $N \log N$

2. $2N$

3. $N*N*N$

4. N

15. The Expression

if (! heap->isFull())

Check

1. Heap is empty

2. Heap is full

3. Heap is not empty

4. Heap is not full

The Expression

if (! heap->isEmpty())

Check

1. Heap is empty
2. Heap is full
3. Heap is not empty
4. Not a valid expression

Given the values are the array representation of heap: 12 23 26 31
34 44 56 64 78

100 If we perform 4 deleteMin operation, the last element deleted is_____ .

1. 31

2. 34

3. 44

4. 56

Which of the following heap method increase the value if key at

position 'p' by the amount 'delta'?

1. increaseKey(p, delta)
2. decreaseKey(p, delta)
3. percolateDown(p, delta)
4. remove(p, delta)

Which of the following heap method lowers the value if key at position 'p' by the amount 'delta'?

1. increaseKey(p, delta)
2. decreaseKey(p, delta)
3. percolateDown(p, delta)
4. remove(p, delta)

Which property of equivalence relation is satisfied if we say:
Ahmad R(is related to)Ahmad

1. Reflexivity
2. Symmetry

3. Transitivity

4. All of Above

Given the values are the array representation of heap; 12 23 26 31 34 44 56 64 78 100 What is the 5th smallest element in the given heap?

1. 31

2. 34

3. 44

4. 56