

PAID VU LMS HANDLING by Mam Mehwish

03184148783

Past Papers for Mids./Finals are also Available

1. Macro is defined by _____ preprocessor directive.

Options:

- a) #define
- b) #else
- c) #if
- d) #endif

Correct Option: a) #define

2. In C++, the name of the _____ is the same as that of a class with a preceding tilde (~) sign.

Options:

- a) Friend function
- b) Utility function
- c) Destructor
- d) Constructor

Correct Option: c) Destructor

3. In C++, which of the following function causes the full definition of the function to be inserted in each place when it gets called?

Options:

- a) Built-in function
- b) Recursive function
- c) Library function
- d) Inline function

Correct Option: d) Inline function

4. The bit manipulation operator _____ is used to check whether a specific bit is set or not.

Options:

- a) |
- b) &
- c) ^
- d) *

Correct Option: b) &

5. Which of the following is not true about Destructor?

Options:

- a) Destructors cannot be overloaded.
- b) Destructors don't return a value.
- c) Destructors take no arguments
- d) Destructors cannot be used for memory manipulation.

Correct Option: d) Destructors cannot be used for memory manipulation.

6. In C++, the default constructor takes _____.

Options:

- a) Only one argument
- b) More than two arguments
- c) Only two arguments
- d) No arguments

Correct Option: d) No arguments

7. Functions seekg () and seekp () require an argument of type ____ to let them know how many bytes to move forward or backward.

Options:

- a) float
- b) double
- c) long
- d) int

Correct Option: c) long

8. Which function is automatically called in C++ if we do not define it in a class?

Options:

- a) Default and Parametrized Constructor
- b) Default Constructor
- c) Inline function
- d) Parametrized Constructor

Correct Option: b) Default Constructor

9. The bit manipulation operator _____ is used to set a specific bit.

Options:

- a) |
- b) ^
- c) *
- d) &

Correct Option: a) |

10. In C++, which operator is used while accessing through the pointer to structure?

Options:

- a) =
- b) &
- c) ->
- d) _

Correct Option: c) ->

1. Macro is defined by _____ preprocessor directive.

Options:

- a) #else
- b) #define
- c) #if
- d) #if

Correct Option: b) #define

2. In C++, _____ function is used to write a character into a file while _____ is used to get a character from a file.

Options:

- a) tellg(), seekg()
- b) getc(), putc()
- c) putc(), getc()
- d) seekg(), tellg()

Correct Option: c) putc(), getc()

3. In bit manipulation of binary systems, if we shift a bit towards right, then it means we are _____ that binary value with '2'.

Options:

- a) Dividing
- b) Subtracting
- c) Multiplying
- d) Adding

Correct Option: a) Dividing

4. What will be the output of the following code?

```
void sampleFunction(int = 5, float = 4.1, char = 'A');  
  
int main(){  
    sampleFunction(50, 3.2);  
}  
  
void sampleFunction(int one, float two, char three) {  
    cout << one << ", " << two << ", " << three;  
}
```

Options:

- a) 50, 4.1, A
- b) 5, 3.2, A
- c) 5, 4.1, A
- d) 50, 3.2, A

Correct Option: d) 50, 3.2, A

5. In C++, which of the following option is used to declare a class?

Options:

- a) class
- b) CLASS
- c) cLAss
- d) Class

Correct Option: a) class

6. What will be the output of the following code?

```
int num = 2;  
  
int count = 0;
```

```
while(num != 0) {  
    if (num & 01)  
        count++;  
    num >>= 1;  
}  
cout << count;  
return 0;
```

Options:

- a) 1
- b) 2
- c) 3
- d) 4

Correct Option: a) 1

7. What will be the output of the following code?

```
int num = 2;  
int count = 0;  
while(num != 0) {  
    if (num & 01)  
        count++;  
    num >>= 1;  
}  
cout << count;  
return 0;
```

Options:

- a) B
- b) Java
- c) C#
- d) C/C++

Correct Option: This question is not related to programming languages; it's about bit manipulation. The output is 1, as explained in question 6.

8. Which function is automatically called when an object of a class is initiated?

Options:

- a) Constructor
- b) Utility function
- c) Friend function
- d) Destructor

Correct Option: a) Constructor

9. What would be the output of the following statement?

`c = 13 % 2;`

Options:

- a) 0
- b) 1
- c) 2
- d) 3

Correct Option: b) 1

10. Which of the following statement is true regarding structures?

Options:

- a) All data members must have the same memory space

- b) Variables which are part of a structure are called Member Functions
- c) All data members must have the same data type
- d) Variables which are part of a structure are called Data Members

Correct Option: d) Variables which are part of a structure are called Data Members

1. Macro is defined by _____ preprocessor directive.

Options:

- a) #else
- b) #define
- c) #if
- d) #if

Correct Option: b) #define

2. In C++, _____ function is used to write a character into a file while _____ is used to get a character from a file.

Options:

- a) tellg(), seekg()
- b) getc(), putc()
- c) putc(), getc()
- d) seekg(), tellg()

Correct Option: c) putc(), getc()

3. In bit manipulation of binary systems, if we shift a bit towards right, then it means we are _____ that binary value with '2'.

Options:

- a) Dividing
- b) Subtracting
- c) Multiplying
- d) Adding

Correct Option: a) Dividing

4. What will be the output of the following code?

```
void sampleFunction(int = 5, float = 4.1, char = 'A');  
int main(){  
    sampleFunction(50, 3.2);  
}  
void sampleFunction(int one, float two, char three) {  
    cout << one << ", " << two << ", " << three;  
}
```

Options:

- a) 50, 4.1, A
- b) 5, 3.2, A
- c) 5, 4.1, A
- d) 50, 3.2, A

Correct Option: d) 50, 3.2, A

5. In C++, which of the following option is used to declare a class?

Options:

- a) class
- b) CLASS
- c) cLAss
- d) Class

Correct Option: a) class

6. What will be the output of the following code?

```
int num = 2;
int count = 0;
while(num != 0) {
    if (num & 01)
        count++;
    num >>= 1;
}
cout << count;
return 0;
```

Options:

- a) 1
- b) 2
- c) 3
- d) 4

Correct Option: a) 1

7. What will be the output of the following code?

```
int num = 2;
int count = 0;
while(num != 0) {
    if (num & 01)
        count++;
    num >>= 1;
}
cout << count;
```

return 0;

Options:

- a) B
- b) Java
- c) C#
- d) C/C++

Correct Option: This question is not related to programming languages; it's about bit manipulation. The output is 1, as explained in question 6.

8. Which function is automatically called when an object of a class is initiated?

Options:

- a) Constructor
- b) Utility function
- c) Friend function
- d) Destructor

Correct Option: a) Constructor

9. What would be the output of the following statement?

c = 13 % 2;

Options:

- a) 0
- b) 1
- c) 2
- d) 3

Correct Option: b) 1

10. Which of the following statement is true regarding structures?

Options:

- a) All data members must have the same memory space
- b) Variables which are part of a structure are called Member Functions
- c) All data members must have the same data type
- d) Variables which are part of a structure are called Data Members

Correct Option: d) Variables which are part of a structure are called Data Members

1. MCQ 1:

- Option A: Creating object of class Complex with name cadd with parameters.
- Option B: Class with name of Complex has been created.
- Option C: It accepts two complex numbers as parameters and returns back the resultant complex number.
- Option D: Define the function named Complex.
- Correct Option: C

2. MCQ 2:

- Option A: return-type operator operator-symbol (parameter-list);
- Option B: return-type operator operator-symbol (no parameter);
- Option C: operator operator-symbol return type (no parameter);
- Option D: return type operator (operator-symbol).
- Correct Option: A

3. MCQ 3:

- Option A: strcpy
- Option B: buffree
- Option C: bufremove
- Option D: delete
- Correct Option: D

4. MCQ 4:

- Option A: Operand
- Option B: Keyword
- Option C: Class
- Option D: Object
- Correct Option: B

5. MCQ 5:

- Option A: *
- Option B: ?
- Option C: delete[]
- Option D: None of the above
- Correct Option: A

1. Bool data type takes _____ values.

- A. 1
- B. 2
- C. 3
- D. 0
- Correct Answer: B. 2

2. Correct syntax of the prototype of the overloaded operator function is _____.

- A. return type operator operator-symbol (parameter-list);
- B. return-type operator (=) (parameter);
- C. operator operator-symbol return type (no parameter);

- D. return type operator (=) const String &other;
- Correct Answer: A. return type operator operator-symbol (parameter-list);

3. Which of the following operator can be overloaded?

- A. (Multiplication operator)
- B. ? (Ternary conditional operator)
- C. ! (Logical NOT operator)
- D. delete[]
- Correct Answer: A. (Multiplication operator)

4. Which of the following is an assignment operator?

- A. - (Subtraction operator)
- B. ^ (Bitwise XOR operator)
- C. = (Assignment operator)
- D. + (Addition operator)
- Correct Answer: C. = (Assignment operator)

5. When overloading the assignment (=) operator, which of the following syntax is correct?

- A. void operator = (const String &s);
- B. void operator (=) (const String &s);
- C. void operator (= String &s);
- D. void operator (=) const String &other;
- Correct Answer: A. void operator = (const String &s);

1. `calloc()` functions allocates multiple blocks of memory, and each block has:

- A) Different length
- B) Different size
- C) Same size

- D) Same length

Correct Option: C) Same size

2. If the memory in the free store is not sufficient enough to fulfill the request, `malloc()` function returns:

- A) -1
- B) NULL
- C) 0
- D) 1

Correct Option: B) NULL

3. Which one is the correct syntax for the declaration of a function that can return a reference?

- A) &function_name datatype (parameter list)
- B) datatype (parameter list) &function_name
- C) datatype& function_name (parameter list)
- D) &datatype function_name (parameter list)

Correct Option: C) datatype& function_name (parameter list)

4. The data members that are visible only from inside the class and hidden from the outside are known as:

- A) Private and Public
- B) Private
- C) Public
- D) Friend

Correct Option: B) Private

5. In C/C++ language, memory at runtime is allocated from:

- A) Hard disk
- B) Free store (heap)

- C) Stack
- D) ROM

Correct Option: B) Free store (heap)

1. In C++, which operator is used for memory allocation?

- A) New (Correct Option)
- B) Allocate
- C) Calloc
- D) Allocate_memory

2. If the memory in the free store is not sufficient enough to fulfill the request, `malloc()` function returns _____.

- A) NULL (Correct Option)
- B) 0
- C) 1
- D) -1

3. Where can we declare a friend function in the class?

- A) Void
- B) Anywhere (Correct Option)
- C) Nowhere
- D) Main()

4. Which one is the correct syntax to declare the friend function?

- A) friend return_type friend_function_name(int, char); (Correct Option)
- B) Friend return_type (int, char);
- C) FRIEND friend_function_name(int, char);
- D) FRIEND return_type friend_function_name(int, char);

5. The data members that are visible only from inside the class and hidden from the outside are known as _____.

- A) Public
- B) Friend
- C) Private (Correct Option)
- D) Private and Public

1. In C++, the default constructor takes _____.

- No arguments
- Only two arguments
- More than two arguments
- Only one argument

****Correct Option:**** No arguments

2. What will be the output of the following code?

```
```cpp
void sampleFunction(int = 5, float = 4.1, char = 'A');
int main(){
 sampleFunction(50, 3.2);
}
void sampleFunction(int one, float two, char three) {
 cout << one << " , " << two << " , " << three;
}
```
```

- 5, 4.1, A
- 5, 3.2, A
- 50, 4.1, A
- 50, 3.2, A

****Correct Option:** 50, 3.2, A**

3. _____ is a user-defined data type.

- Class
- Constructor
- Pointer
- Function

****Correct Option:** Class**

4. Which of the following is not true about Destructor?

- Destructors cannot be overloaded.
- Destructors cannot be used for memory manipulation.
- Destructors take no arguments.
- Destructors don't return a value.

****Correct Option:** Destructors cannot be used for memory manipulation.**

5. In C++, the name of the _____ is the same as that of a class with a preceding tilde (~) sign.

- Friend function
- Utility function
- Destructor
- Constructor

****Correct Option:** Destructor**

1. _____ is a user-defined data type.

- a) Pointer
- b) Class
- c) Function
- d) Constructor

- ****Correct Option: b) Class****

2. Which function is automatically called when an object of a class is initiated?

- a) Destructor
- b) Constructor
- c) Utility function
- d) Friend function

- ****Correct Option: b) Constructor****

3. Which of the following is not true about Destructor?

- a) Destructors cannot be overloaded.
- b) Destructors cannot be used for memory manipulation.
- c) Destructors take no arguments.
- d) Destructors don't return a value.

- ****Correct Option: b) Destructors cannot be used for memory manipulation.****

4. Where to put an inline function during frequent calling inside the program from multiple source files?

- a) Main()
- b) Header File
- c) Inside the class
- d) Outside the class

- ****Correct Option: b) Header File****

5. A constructor with arguments is known as:

- a) Virtual Constructor
- b) Parameterized Constructor
- c) Destructor
- d) Default Constructor

- ****Correct Option: b) Parameterized Constructor****

1. Default scope for members of structures is _____ and default visibility for class members is _____.

Options:

- A) Public, Private
- B) Public, Public
- C) Private, Public
- D) Private, Private

Correct Answer: A) Public, Private

2. Which of the following is not an advantage of templates?

Options:

- A) Easy to understand
- B) Templates are not type-safe
- C) Helps in compiler optimizations
- D) Provides code reusability

Correct Answer: B) Templates are not type-safe

3. Which of the following cannot act as a data member of a class?

Options:

- A) Objects
- B) Structures
- C) Functions
- D) Unions

Correct Answer: C) Functions

4. 'T' is _____ data type in "template <class T>".

Options:

- A) Float
- B) Generic

- C) Specific
- D) Double

Correct Answer: B) Generic

5. In a template class, the compiler makes a copy of ____ and converts it into ____.

Options:

- A) Source code, object code
- B) Source code, object code
- C) Source code, machine code
- D) Machine code, object code

Correct Answer: A) Source code, object code

1. Which of the following is the correct format of a template function?

- A. template class [T]
- B. template<class T>
- C. template class <T>
- D. template [class T]

Correct answer: B. template<class T>

2. For a template function, we must have at least ____ generic argument.

- A. 0
- B. 1
- C. 2
- D. 3

Correct answer: B. 1

3. Classes defined within other classes are ____.

- A. Child Classes
- B. Outer Classes
- C. Parent Classes
- D. Nested Classes

Correct answer: D. Nested Classes

4. Suppose you want to find the square of a number using the template square. Which data type you cannot use to call it?

- A. String
- B. Float
- C. Int
- D. Double

Correct answer: A. String

5. Declaration and definition of a template function should be in the ____ file.

- A. Same
- B. Distinct
- C. Multiple
- D. Different

Correct answer: B. Distinct

1. For template function, we must have at least ____ generic argument.

Options:

- One
- Three
- Zero

- Two

Correct Option: One

2. In template class, compiler makes a copy of ____ and converts it to ____.

Options:

- Machine code, object code
- Source code, machine code
- Source code, object code
- Object code, source code

Correct Option: Source code, object code

3. Default scope for members of structures is ____ and default visibility for class members is ____.

Options:

- Private, Private
- Private, Public
- Public, Public
- Public, Private

Correct Option: Public, Private

4. 'T' is ____ data type in "template <class T>."

Options:

- Generic
- Double
- Specific
- Float

Correct Option: Generic

5. Which of the following cannot act as a data member of a class?

Options:

- Unions
- Functions
- Structures
- Objects

Correct Option: Functions

1. If we use cin stream to read some value and store it in some integer variable and press some alphabet key instead of numeric keys, what will happen?

Options:

- A. Its binary representation will be ignored, and the character will be stored.
- B. Some error will occur, and cin stream will detect this error. (Correct)
- C. Its binary representation will be ignored, and the value will be stored.
- D. Its ASCII code will be stored inside the computer.

2. A static variable defined in a function is initialized _____.

Options:

- A. Only once during its lifetime (Correct)
- B. Compile time of the program
- C. Every time the function is called
- D. None of the above

3. The ternary operator is shown as _____.

Options:

- A. ||
- B. |
- C. &&
- D. ?: (Correct)
- E. ===

4. What is a copy constructor?

Options:

- A. A constructor that allows a user to move data from one object to another
- B. A constructor to kill other copies of a given object
- C. A constructor to initialize an object with the values of another object (Correct)
- D. A constructor to check whether two objects are equal or not

5. _____ variables are those that are defined outside of main.

Options:

- A. Dynamic
- B. Static
- C. Local
- D. Global (Correct)

6. The new operator allocates memory from the free store and returns _____.

Options:

- A. a pointer (Correct)
- B. a float number
- C. an integer number

7. The assignment operator is used to initialize a newly declared object from an existing object.

Options:

- A. False (Correct)
- B. True

8. In overloading the assignment (=) operator, which object(s) will be passed as argument(s) in the operator function?

Options:

- A. Right object of the assignment operator

- B. Both objects will be passed (Correct)
- C. Left object of the assignment operator
- D. No objects will be passed

9. Automatic variables are created on _____.

Options:

- A. Static storage
- B. Stack (Correct)
- C. Free store
- D. Heap

1. Which of the following cannot act as a data member of a class?

Options:

- A) Unions
- B) Functions
- C) Objects
- D) Structures

Correct Option: B) Functions

2. The behavior of the compiler in _____ classes is the same as in template functions.

Options:

- A) Outer
- B) Template
- C) Abstract

Correct Option: B) Template

3. Which of the following is the correct format of a template function?

Options:

- A) template<class T>
- B) template [class T]

C) template class [T]

D) template class <T>

Correct Option: A) template<class T>

4. 'T' is ____ data type in "template <class T>".

Options:

A) Specific

B) Float

C) Generic

D) Double

Correct Option: C) Generic

5. For a template function, we must have at least ____ generic argument.

Options:

A) 0

B) 1

C) 2

D) 3

Correct Option: B) 1

1. Which option will be correct in order to free the space of memory allocated to a buffer (buf)?

- free buf
- free buf (Correct)
- remove buf
- delete buf

2. What is the correct prototype of overloading of delete operator?

- void * operator delete (size_t, size);
- void * operator delete (size_t size);
- new operator delete (void * ptr);
- void operator delete (void * ptr); (Correct)

3. The correct syntax of the stream insertion operator is:

- istream* istream::operator >> ();
- istream& istream::operator >> (char *text);
- ostream* ostream::operator << ();
- ostream& ostream::operator << (char *text); (Correct)

4. In C++, sizeof operator is used to determine _____.

- Number of words
- Size of data type (Correct)
- Length of string
- Length of words

5. Data encapsulation can be achieved through _____.

- Structures
- Arrays

- Pointers
- Classes (Correct)

6. For overloading minus (-) operator, which member operator function will be correct?

- Complex operator - (Complex c) (Correct)
- Complex - operator (Complex c)
- Complex (-) operator (Complex c)
- Complex operator (complex c1 - complex c2)

7. Which header file is used for file manipulation?

- fstream.h (Correct)
- iostream.h
- iomanip.h
- filestream.h

8. Which one is the correct syntax to declare the friend function?

- Friend return_type (int, char);
- friend return_type friend_function_name(int, char);
- FRIEND return_type friend_function_name(int, char);
- FRIEND friend_function_name(int, char); (Correct)

9. Where can we declare a friend function in the class?

- Void
- Nowhere (Correct)
- Anywhere
- Main()

10. In the code ``if (day == daysOfMonth (*this))``, ``*this`` refers to:

- Current Class

- Current Class
- Current Object (Correct)
- Any Object

1. Which header file is used for file manipulation?

- a) fstream.h
- b) fstream.h
- c) filestream.h
- d) iomanip.h
- Correct Option: a) fstream.h

2. Which of the following operator can be overloaded?

- a) delete[]
- b) ..
- c) *
- Correct Option: c) *

3. In the syntax of the overloaded operator function given below: `Complex operator + (Complex & );`
What is 'operator'?

- a) Operand
- b) Keyword
- c) Class
- d) Object
- Correct Option: b) Keyword

4. Which of the following options is not a source of the output stream?

- a) file
- b) screen
- c) simple variable

- d) region in memory
- Correct Option: c) simple variable

5. Which one is the correct syntax to declare the friend function?

- a) Friend return_type (int, char);
- b) FRIEND return_type friend_function_name(int, char);
- c) FRIEND friend_function_name(int, char);
- d) friend return_type friend_function_name(int, char);
- Correct Option: d) friend return_type friend_function_name(int, char);

6. The data members that are visible only from inside the class and hidden from the outside are known as:

- a) Private
- b) Private and Public
- c) Public
- d) Private and Public
- Correct Option: a) Private

7. Which of the following is an assignment operator?

- a) +=
- b) ^^
- Correct Option: a) +=

8. For overloading the minus (-) operator, which member operator function will be correct?

- a) Complex – operator (Complex c)
- b) Complex (-) operator (Complex c)
- c) Complex operator (complex c1- complex c2)
- d) Complex operator – (Complex c)
- Correct Option: d) Complex operator – (Complex c)

9. The correct syntax of the stream insertion operator is:

- a) ostream* ostream::operator << ();
- b) istream* istream::operator >> ();
- c) ostream& ostream::operator << (char *text);
- d) istream& istream::operator >> (char *text);
- Correct Option: None of the provided options match the correct syntax.

10. Which of the following option returns the state of the end of the file?

- a) cin.endoffile();
- b) cin.enof();
- c) cin.endof();
- d) cin.eof();
- Correct Option: d) cin.eof();

1. What will be the output of the following code?

```
#include <iostream>
using namespace std;
int main() {
    int num = 7;
    cout << setfill('*') << setw(4) << num << endl;
}
```

Options:

- a) 7*****7
- b) 7*****77*****7
- c) **7**
- d) 7***

Correct Answer: c) **7**

2. Which one is the correct syntax for the declaration of a function that can return a reference?

Options:

- a) &datatype function_name(parameter list)
- b) datatype& function_name(parameter list)
- c) datatype(parameter list) &function_name
- d) datatype(parameter list)&function_name

Correct Answer: b) datatype& function_name(parameter list)

3. How many objects are being initialized in this statement of code?

```
Date myDate[10] = { Date(09, 03, 1970), Date(08, 23, 1974) };
```

...

Options:

- a) 0
- b) 1
- c) 5
- d) 10

Correct Answer: b) 1

4. How many objects are created for the class Date in the statement?

```
Date myDates[10];
```

...

Options:

- a) 0
- b) 1
- c) 5
- d) 10

Correct Answer: d) 10

5. In the code snippet, if (day == daysOfMonth(*this)), what does *this refer to?

Options:

- a) Current Class
- b) Current Object
- c) Any Object
- d) Today Date and Time

Correct Answer: b) Current Object

6. An entry in an online encyclopedia that refers to another entry whose title has been changed is an example of _____.

Options:

- a) Dangling pointer
- b) NULL Pointer
- c) Reference pointer
- d) This pointer

Correct Answer: a) Dangling pointer

7. The correct syntax of the stream insertion operator is:

Options:

- a) `istream* istream::operator >> ();`

- b) ostream* ostream::operator << ();
- c) istream& istream::operator >> (char *text);
- d) ostream& ostream::operator << (char *text);

Correct Answer: d) ostream& ostream::operator << (char *text);

8. Where can we declare a friend function in the class?

Options:

- a) Inside the class declaration
- b) Outside the class declaration
- c) Nowhere
- d) Void

Correct Answer: Both a) Inside the class declaration and b) Outside the class declaration

9. Which of the following is an assignment operator?

Options:

- a) +=
- b) ^
- c) -
- d) *

Correct Answer: a) +=

10. The `calloc()` function allocates multiple blocks of memory, and each block has _____?

Options:

- a) Different length
- b) Same length
- c) Different size

d) Same size

Correct Answer: b) Same size

1. What will be the output of the following code?

Options:

A. ****7***

B. Error

C. 7777

D. ****7***77****

Correct Option: A. ****7***

2. Which one is not the member function of the input stream?

Options:

A. get();

B. cin.getline();

C. cin.read();

D. cin.get();

Correct Option: D. cin.get();

3. What is the output of this program?

Options:

A. Add number+4

B. Error

C. 4+14

D. 14

Correct Option: B. Error

4. Which of the following operators can be overloaded?

Options:

- A. . (dot operator)
- B. .. (double dot operator)
- C. ::
- D. ()

Correct Option: A. . (dot operator)

5. Which of the following is the assignment operator?

Options:

- A. -=
- B. ^
- C. +

Correct Option: A. -=

6. For overloading the minus (-) operator, which member operator function will be correct?

Options:

- A. Complex (-) operator (Complex c)
- B. Complex – operator (Complex c)
- C. Complex operator - (Complex c)
- D. Complex operator (complex c1- complex c2)

Correct Option: C. Complex operator - (Complex c)

7. What is the right syntax of the buf for calling the object by using the this pointer?

Options:

- A. *this.(buf)
- B. this*buf
- C. (*this).buf
- D. *this.buf

Correct Option: C. (*this).buf

8. How many objects are created for the class Date?

Options:

- A. 10
- B. 0
- C. 5
- D. 1

Correct Option: A. 10

9. In C++, which operator is used for memory allocation?

Options:

- A. new
- B. Allocate_memory
- C. New
- D. Calloc

Correct Option: A. new

10. The data members that are visible only from inside the class and hidden from the outside are known as?

Options:

- A. Public
- B. Friend
- C. Private
- D. PublicPrivate

Correct Option: C. Private

1. In C++, which operator is used for memory allocation?

- A) Allocate_memory
- B) New

- C) Calloc
- D) Allocate
- ****Correct Option:** B) New**

2. When overloading assignment (=) operator, which of the following syntax is correct?

- A) void operator (=) (const String &s);
- B) void operator (=) const String &other ;
- C) void operator = (const String &s);
- D) void operator = (const String &s);
- ****Correct Option:** C) void operator = (const String &s);**

3. Which of the following operators can be overloaded?

- A) delete[]
- B) *.
- ****Correct Options:** A) delete[] and B) *.**

4. In C++, 'sizeof' operator is used to determine _____.

- A) Length of words
- B) Length of string
- C) Number of words
- D) Size of data type
- ****Correct Option:** D) Size of data type**

5. In C/C++ language, memory at runtime is allocated from _____.

- A) Stack
- B) ROM
- C) Hard disk
- D) Free store (heap)
- ****Correct Option:** D) Free store (heap)**

6. If the memory in the free store is not sufficient enough to fulfill the request, `malloc()` function returns _____.

- A) 0
- B) 1
- C) -1
- D) NULL
- **Correct Option:** D) NULL

7. In the following code, what will be the output of `i`?

```
#include<iostream>
using namespace std;
main() {
    int i;
    int &j = i;
    i = 123;
    cout<< "\n The value of i =" << i;
}
...
```

- A) 1230
- B) 1234
- C) 5xX012345321
- D) 123
- **Correct Option:** D) 123

8. In the provided code, what does the line `Date myDates[10];` do?

- A) Creates an object of class `Date` with the name `cadd` with parameters.
- B) Class with the name of `Complex` has been created.

- C) Defines the function named `Complex`. It accepts two complex numbers as parameters and returns back the resultant complex number.

- D) Creates an array of 10 objects of the class `Date`.

- ****Correct Option:**** D) Creates an array of 10 objects of the class `Date`.

9. How many objects are created for the class `Date` in the code `Date myDates[10];`?

- A) 0

- B) 1

- C) 10

- D) It depends on the class definition.

- ****Correct Option:**** C) 10

10. Where can we declare a friend function in the class?

- A) Void

- B) Nowhere

- C) Main()

- D) Anywhere

- ****Correct Option:**** D) Anywhere

1. Which of the following options is not a source of the output stream?

Options:

- simple variable

- region in the memory

- screen

- file

Correct Option: simple variable

2. When overloading the assignment (=) operator, which of the following syntax is correct?

Options:

- void operator = (const String &s);
- void operator (=) (const String &s);
- void operator (= String &s);
- void operator (=) const String &other ;

Correct Option: void operator = (const String &s);

3. What is the output of this program?

```
#include <iostream>
using namespace std;
main () {
    int num;
    cout << "Please enter an integer value: ";
    cin >> num + 4;
}
```

Options:

- 4+1
- Error
- Add number+4
- 4

Correct Option: Error

4. What will be the output of the following code?

```
#include <iostream>
#include <iomanip>
using namespace std;
main () {
```

```
int num=7;

cout << setfill('*') << setw(4) << num << endl;

}

...
```

Options:

- ***7
- 0123
- 012345
- ****7

Correct Option: ***7

5. An entry in an online encyclopedia that refers to another entry whose title has been changed is an example of _____.

Options:

- Reference pointer
- Dangling pointer
- NULL Pointer
- This pointer

Correct Option: Reference pointer

6. Which of the following is the assignment operator?

Options:

- +
- -
- ^
- =

Correct Option: =

7. The data members that are visible only from inside the class and hidden from the outside are known as:

Options:

- Friend
- Public
- Private
- Private and Public

Correct Option: Private

8. In the following code, what will be the output of i?

```
#include<iostream>
using namespace std;
main() {
    int i;
    int &j = i;
    i = 123;
    cout << "\n The value of i =" << i;
}
...
```

Options:

- 123 0
- 12345
- x 321
- X012345

Correct Option: 123

9. Which one is the correct syntax to declare a friend function?

Options:

- Friend return_type (int, char);
- FRIEND return_type friend_function_name(int, char);
- FRIEND friend_function_name(int, char);
- friend return_type friend_function_name(int, char);

Correct Option: friend return_type friend_function_name(int, char);

10. Which option will be correct in order to free the space of memory allocated to a buffer ('buf')?

Options:

- strcpy buf
- remove buf
- delete buf
- free buf

Correct Option: delete[] buf;

MAM MEHWISH 03184148783

1. Stream insertion (<<) and extraction operators (>>) are always implemented as _____ functions.

Options:

- a) Member
- b) User-defined
- c) Non-member
- d) Friend

Correct Option: a) Member

2. Variables defined in the main function are _____ to the function main().

Options:

- a) Static
- b) Private
- c) Local
- d) Global

Correct Option: c) Local

3. Automatic variables are created constantly and destroyed _____.

Options:

- a) Never
- b) Sometime
- c) Often
- d) Always

Correct Option: c) Often

4. Which of the following header files deals with stream extraction?

Options:

- a) manipio.h

- b) string.h
- c) iostream.h
- d) fstream.h

Correct Option: c) iostream.h

5. Which statement about manipulator is not true?

Options:

- a) Stream insertion operator is on the right-hand side.
- b) The left-hand side is an ostream object.
- c) It automatically gets that object as a parameter passed into the function.
- d) They return a reference to the insertion operator.

Correct Option: c) It automatically gets that object as a parameter passed into the function.

1. 'endl' is a type of ____ manipulator.

Options:

- A) Parameter-less
- B) Class
- C) Parameterized
- D) User-defined

Correct Answer: B) Class

2. Which statement about pointers is not true?

Options:

- A) Pointer can be 'void'
- B) Pointer contains a memory address
- C) Pointer contains a value
- D) Points to an area in memory

Correct Answer: C) Pointer contains a value

3. Automatic variables are created constantly and destroyed ____.

Options:

- A) Often
- B) Never
- C) All the time
- D) Sometime

Correct Answer: A) Often

4. Which of the following header file deals with stream extraction?

Options:

- A) manipio.h
- B) iostream.h
- C) string.h
- D) fstream.h

Correct Answer: B) iostream.h

5. Variables defined in the main function are ____ to the function main().

Options:

- A) Private
- B) Static
- C) Global
- D) Local

Correct Answer: D) Local

1. Automatic variables are created constantly and destroyed ____.

Options:

- A) Often
- B) All the time
- C) Sometime

- D) Never

Correct Option: A) Often

2. Which statement about pointers is not true?

Options:

- A) Pointer can be 'void'

- B) Pointer contains a value

- C) Points to an area in memory

- D) Pointer contains a memory address

Correct Option: B) Pointer contains a value

3. '\n' is a type of ____ manipulator.

Options:

- A) Parameterized

- B) Class

- C) Parameter-less

- D) User-defined

Correct Option: C) Parameter-less

4. Variables defined in the main function are _____ to the function 'main()'.

Options:

- A) Local

- B) Global

- C) Private

- D) Static

Correct Option: A) Local

1. Which statement about pointers is not true?

Options:

- a) Pointer contains a value
- b) Pointer contains a memory address
- c) Points to an area in memory
- d) Pointer can be 'void'

Correct option: a) Pointer contains a value

2. Variables defined in the main function are _____ to the function main().

Options:

- a) Global
- b) Private
- c) Static
- d) Local

Correct option: d) Local

3. We cannot declare a function as a friend of _____ class.

Options:

- a) istream
- b) ostream
- c) Istreamdouble
- d) ostream only

Correct option: b) ostream

4. Which of the following header files deals with stream extraction?

Options:

- a) string.h
- b) manipio.h
- c) fstream.h
- d) iostream.h

Correct option: d) iostream.h

5. Stream insertion (<<) and extraction (>>) operators are always implemented as _____ functions.

Options:

- a) Friend
- b) Member
- c) Non-member
- d) Non-member

Correct option: c) Non-member

1. We cannot declare a function as a friend of _____ class.

Options:

- a) doublestream
- b) ostream only
- c) istream or ostream
- d) Istream

Correct Answer: b) ostream only

2. Stream insertion (<<) and extraction operators (>>) are always implemented as _____ functions.

Options:

- a) Non-member
- b) Friend
- c) User-defined
- d) Member

Correct Answer: a) Non-member

3. Automatic variables are created constantly and destroyed_____.

Options:

- a) Never
- b) All the time

- c) Often
- d) Sometime

Correct Answer: c) Often

4. 'endl' is a type of ____ manipulator.

Options:

- a) User-defined
- b) Parameter-less
- c) Class
- d) Parameterized

Correct Answer: b) Parameter-less

5. Which of the following header file deals with stream extraction?

Options:

- a) fstream.h
- b) iostream.h
- c) string.h
- d) manipio.h

Correct Answer: b) iostream.h

1. How many objects are created for the class Date? `Date myDates[10];`

Options:

- a) 0
- b) 1
- c) 5
- d) 10

Correct option: c) 5

2. What is the correct prototype of overloading of the delete operator?

Options:

- a) ``void operator delete(void* ptr);``
- b) ``void* operator delete(size_t size);``
- c) ``new operator delete(void* ptr);``
- d) ``new operator delete(void* ptr);``

Correct option: a) ``void operator delete(void* ptr);``

3. How many objects are initializing in this statement of code: ``Date myDate[10] = { Date(09, 03, 1970), Date(08, 23, 1974) }``?

Options:

- a) 1
- b) 3
- c) 5
- d) 10

Correct option: b) 3

4. The correct syntax of the stream insertion operator (``<<``) is:

Options:

- a) ``ostream& ostream::operator << (char* text);``

b) ``istream& istream::operator >> (char* text);``

c) ``ostream* ostream::operator << ();``

d) ``istream* istream::operator >> ();``

Correct option: a) ``ostream& ostream::operator << (char* text);``

5. Which of the following option returns the state of end of file for ``cin``?

Options:

a) ``cin.endoffile();``

b) ``cin.eof();``

c) ``cin.enof();``

d) ``cin.endof();``

Correct option: b) ``cin.eof();``

1. Which header file is used for file manipulation?

a) `fstream.h`

b) `iostream.h`

c) `iomanip.h`

d) `fstream.h`

Correct Option: d) `fstream.h`

2. Which of the following options is not a source of the output stream?

a) fileregion in the memory

b) screen

c) simple variable

Correct Option: a) fileregion in the memory

3. What is the output of this program?

```
```cpp
```

```
#include <iostream>
```

```
using namespace std;

main() {

 int num;

 cout << "Please enter an integer value: ";

 cin >> num + 4;

}

...
```

- a) 4
- b) 4+1
- c) Add number+4
- d) Error

Correct Option: d) Error

4. How many objects are initializing in this statement of code:

```
```cpp
Date myDate[10] = { Date(09, 03, 1970), Date(08, 23, 1974) }
...
```

- a) 1
- b) 3
- c) 4
- d) 10

Correct Option: a) 1

5. How many objects are initialized for the class Date?

```
```cpp
Date myDates[10];
...
```

- a) 0
- b) 1

c) 7

d) 10

Correct Option: a) 0

1. The correct syntax of the stream insertion operator is:

- A) ostream& ostream::operator << (char \*text);

- B) ostream\* ostream::operator << ();

- C) istream\* istream::operator >> ();

- D) istream& istream::operator >> (char \*text);

- Correct Option: A) ostream& ostream::operator << (char \*text);

2. How many objects are initializing in this statement of code:

```
```cpp
```

```
Date myDate[10] = { Date(09, 03, 1970), Date(08, 23, 1974) };
```

```
```
```

- A) 10

- B) 3

- C) 2

- D) 1

- Correct Option: C) 2

3. What is the correct prototype of overloading of delete operator?

- A) void \* operator delete ( size\_t size );

- B) void \* operator delete ( size\_t, size );

- C) void operator delete (void \* ptr);

- D) new operator delete (void \* ptr);

- Correct Option: C) void operator delete (void \* ptr);

4. What will be the output of the following code?



```
```cpp
```

```
#include <iostream>
```

```
#include <iomanip>
```

```
using namespace std;
```

```
main () {
```

```
    float num=15.9999;
```

```
    cout << setprecision (2) << num;
```

```
}
```

```
...
```

- A) 1615.99

- B) 15.9915

- C) 15.999

- D) 15.99

- Correct Option: D) 15.99

5. What is the output of this program?

```
```cpp
```

```
#include <iostream>
```

```
using namespace std;
```

```
main () {
```

```
 int num;
```

```
 cout << "Please enter an integer value: ";
```

```
 cin >> num + 4;
```

```
}
```

```
...
```

- A) 4+14

- B) Add number+4

- C) Error

- D) Please enter an integer value:

- Correct Option: D) Please enter an integer value:

MAM MEHWISH 03184148783

MAM MEHWISH 03184148783

👉👉 Paid Vu Lms Handling 👉👉

♦ 1 GDB= Rs 100

♦ 1 Quiz= Rs 200

♦ 1 Assignment=Rs 250

♦ Agr complete handling krwatey hain 1 subject ki with all activities= Rs 500 (Half Semester) ♦

LECTURES Play Service Available In Very Low Price. 📄

👉👉 80-100% Marks Guaranteed 👉👉

👉 Miss Mehwish:03184148783 👉

MAM MEHWISH 03184148783