

_____ computes shortest paths in a graph by using weights on edges as a measure of distance.

- ▶ Greedy algorithm
- ▶ Distance vector algorithm
- ▶ Dijkstra's algorithm (Computer Networks and Internets, page112) rep
- ▶ None of the given

_____ is used for compressed audio and video where the data rate depends on the level of compression that can be achieved.

- ▶ Constant Bit Rate (CBR) service
- ▶ Variable Bit Rate (VBR) service (Page 71)
- ▶ Available Bit Rate (ABR) service
- ▶ None of the given

Basic LAN technologies such as Ethernet, Token Ring, and FDDI use a _____.

- ▶ Connectionless service paradigm (Computer Networks and Internets, page112)
- ▶ Connection-oriented service paradigm
- ▶ Both Connectionless and Connection-oriented service paradigm
- ▶ None of the given

The product of delay and throughput measures the _____ of data that can be present on the network.

- ▶ Area
- ▶ Volume (Page 80)
- ▶ Length
- ▶ None of the given

A network with throughput T and delay D has a total of _____ bit in transit at any time.

- ▶ T / D
- ▶ T x D (Computer Networks and Internets, page203) rep
- ▶ T + D
- ▶ None of the given

One repeater _____, two repeaters _____ the maximum cable length limitation.

- ▶ doubles, triple (Page 49)
- ▶ square roots, cube roots
- ▶ and, triple
- ▶ doubles, cancel

A network uses a ----- if all computers attach to a central point

▶ Star Topology (Page 25)

▶ Ring Topology

▶ Bus Topology

▶ None of the given

Computers attached to an Ethernet use ----- in which a computer waits for the other to be idle before transmitting a frame.

▶ CSMA/CD (Computer Networks and Internets, page 93) rep

▶ CSMA/CA

▶ TOKEN PASSING

▶ None of the given

A typical port on an ATM switch operates at _____ or higher.

▶ OC-2 speed (155Mbps)

▶ OC-3 speed (100Mbps)

▶ OC-3 speed (155Mbps) (Page 72)

▶ OC-3 speed (155Gbps)

The product of delay and throughput measures the _____ of data that can be present on the network.

- ▶ Area
- ▶ Volume (Page 80) rep
- ▶ Length
- ▶ None of the given

_____ is used for compressed audio and video where the data rate depends on the level of compression that can be achieved.

- ▶ Constant Bit Rate (CBR) service
- ▶ Variable Bit Rate (VBR) service (Page 71) rep
- ▶ Available Bit Rate (ABR) service
- ▶ None of the given

Which of the following is a connecting device?

- ▶ Bridge
- ▶ Repeater
- ▶ Hub
- ▶ All the given Click here for Detail

A bridges function in the _____ layers(s).

- ▶ Physical (MAC) rep Click here for Detail

- ▶ Data link
- ▶ Network
- ▶ Physical (MAC) and Data link

IEEE LLC/SNAP header is -----, which is used to specify the type of data.

▶ 8 octets (Computer Networks and Internets, page112) rep

- ▶ 8 bytes
- ▶ 8 bits
- ▶ None of the given

The third field of the header consists of ----- bit Ethernet frame type.

- ▶ 48
- ▶ 32
- ▶ 16 (Computer Networks and Internets, page110)
- ▶ 8

An -----method, the network hardware designers specify how type information is included in the frame and the value use to identify various frame types.

- ▶ Explicit frame type (Page 35)
- ▶ Ideal frame type

- ▶ Implicit frame type
- ▶ None of the given

Local Talk is a LAN technology that employs -----

- ▶ Star topology
- ▶ Bus topology (Page 30) rep
- ▶ Ring topology
- ▶ None of the given

Questions:

1. Who examine performance of network? 2 marks

Answer:- Performance is probably the most closely monitored operational feature by users in the network environment

2. How can we compute shortest path in WAN? 2 marks

Answer:- (Page 62) We use Dijkstra's algorithm to compute shortest path from each node to every other node.

3. 100mbps Ethernet NIC is connected to control Hub which supports 10mbps. What will be Data Rate in this scenario? 2 marks

4. There are two sites office A & B, both are using VPN. If a user of another network wants to send some packet to A, then what will be the behavior of network A?

5. What type of switching technique is used in WAN?

Answer:- (Page 55) WANs can use circuit-switching or packet-switching techniques. To span long distances or many computers, networks must replace shared medium with packet switches. Each switch moves an entire packet from one connection to another. That's why they are called packet switches.