Past Papers for Mids./Finals are also Available



Miss Mehwish: 03171491481

CS506 LIVE (QUIZ) MCQs

Mid Term

Past papers for all subjects are also available
03184148783

1. **previous() is a method of**
   - Statement
   - ResultSetMetaData
   - Connection
   - ✔ ResultSet

---

2. **Which of the following syntax is used to get ResultSetMetaData object?**
   - ResultSetMetaData md = con.getMetaData(); // where con is Connection object
   - ✔ ResultSetMetaData md = rs.getMetaData(); // where rs is ResultSet object
   - ResultSet md = rs.getMetaData();
   - ResultSetMetaData md = st.getMetaData(); // where st is Statement object

---

3. **Let suppose a column has index 5 in the ResultSet object. Which of the following statement is used to retrieve the column values?**
   - String name = rs.getint(4)
   - String name = rs.getString(4)
   - ✔ String name = rs.getString(5)
   - String name = rs.getint(5)

---

4. **ResultSet Meta Data will help you in answering the following questions except:**
   - Are the column name is case sensitive?
   - How many rows are in the ResultSet?
   - How many columns are in the ResultSet?
   - ✔ What is the name of given column?

---

5. **Which of the following functions is declared in MouseMotionListener interface?**
   - public void mouseEntered(MouseEvent me);
   - ✔ public void mouseDragged(MouseEvent me);
   - public void mousePressed(MouseEvent me);
   - public void mouseClicked(MouseEvent me);

MAM MEHWISH 03184148783

Past Papers for Mids./Finals are also Available



Miss Mehwish: 03171491481

6. **Following are the code statements used in java event handling. Identify the code statement that is used for handling an event**
   - ✔ button.addActionListener(this)
   - public void actionPerformed(ActionEvent e)
   - button = new JButton("Reset")
   - container.setLayout(new FlowLayout());

---

7. **Which of the following is NOT true for java inner classes?**
   - Can have constructors
   - Can have instance variables
   - Can have Methods
   - ✔ Generally used as public utility classes

---

8. **In ResultSetMetaData methods, method returns the suggested column label for printouts.**
   - getColumnType (int)
   - ✔ getColumnLabel()
   - getColumnName()
   - getColumnCount()

---

9. **Which of the following statement object is used to execute stored procedures?**
   - None of given options
   - PreparedStatement
   - Statement
   - ✔ CallableStatement

---

10. **Which of the following statement object is used to execute precompiled SQL statements?**
    - ✔ PreparedStatement
    - CallableStatement
    - Statement
    - None of given options

1. **To compile "Test java" class, command is used in java.**
   - java Testjava
   - javac Testjava
   - javac Test
   - java Test
   - **✓ javac Test**
2. **In Java, static methods have direct access to:**
   - Instance variables
   - Instance methods
   - Static variables and methods
   - Both static and instance members

MAM MEHWISH 03184148783

Past Papers for Mids./Finals are also Available



Miss Mehwish: 03171491481

- ✓ **Static variables and methods**

3. **_, on UNIX or Windows.**
   - cjava
   - javac
   - javac
   - ✓ **javac**
4. **CmdArgs java class is compiled. If the command "java CmdArgs CS506" run in cmd, then what will be the output of given code?**
   - Public class CmdArgs{
   - public static void main(String[] args) {
   - System.out.printin("First argument * + args[0]); }
   - Do not show any output
   - CS506
   - args[0]
   - Syntax error
   - ✓ **Syntax error**
5. **In a collection class, creates a collection with no elements.**
   - Byte
   - Function
   - Class
   - Array
   - ✓ **Constructor**
6. **Bytecodes are created and stored on disk by:**
   - Bytecode verifier
   - Compiler
   - Editor
   - Class loader
   - ✓ **Compiler**
7. **The classes which contain the word _ in their names are byte-oriented streams.**
   - Byte
   - Reader
   - Writer
   - Stream
   - ✓ **Byte**
8. **Given code is showing the result of the addition of two integer type numbers. Choose correct output of this code.**
   - int i = 7; int j = 8; int k = i + 8; System.out.println("Seven " + i + " plus Eight " + j + " is " + k);
   - Seven i plus Eight j is + 15
   - Seven i plus Eight j is k
   - Seven 7 plus Eight 8 is 15
   - Seven plus Eight is k

MAM MEHWISH 03184148783

Past Papers for Mids./Finals are also Available



Miss Mehwish: 03171491481

- ✓ **Seven 7 plus Eight 8 is 15**

9. **Suppose strings are stored in a collection "arraylist". Get one string element and store it in the element variable. Choose correct line of code for this requirement.**
   - String element = String arraylist.get(i);
   - String element = (String)arraylist.get(i);
   - String element = element arraylist.get(i);
   - String element = (element) arraylist.get(i);
   - ✓ **String element = (String)arraylist.get(i);**
10. **The following is an example of: FileReader fr = new FileReader("i")**
    - Byte oriented stream
    - File stream
    - Node stream
    - Filter stream
    - ✓ **File stream**

MAM MEHWISH 03184148783

Past Papers for Mids./Finals are also Available



Miss Mehwish: 03171491481

🔥🔥 **Paid Vu Lms Handling** 🔥🔥

♦ **1 GDB= Rs 100**

♦ **1 Quiz= Rs 200**

♦ **1 Assignment=Rs 250**

💎 **Agr complete handling krwatey hain 1 subject ki with all activities= Rs 500 (Half Semester)** 💎

LECTURES Play Service Available In Very Low Price. 📱

🏆🍕 **80-100% Marks Guaranteed** 🍕🏆

🔥 **Miss Mehwish: 03171491481 0306 9080308 03184148783**🔥

MAM MEHWISH 03184148783