

**Q.1 Which of the following is true about iterating through a set?**

- A. Sets are indexed, and you can use the index to iterate
  - B. You cannot iterate over a set
  - C. Sets are unordered, so iteration may not follow insertion order**
  - D. Sets support list slicing for iteration
- 

**Q.2 In which scenario "set" is most useful?**

- A. When you need to access elements by index
  - B. When you need to store unique elements**
  - C. When you need to preserve the order of elements
  - D. When you need to modify elements in place
- 

**Q.3 How can you find the index of element 30 in a tuple t = (10, 20, 30, 40)?**

- A. t.search(30)
  - B. t.index(30)**
  - C. index(t, 30)
  - D. find(30, t)
- 

**Q.4 How can multiple elements be added to a set at once?**

- A. update()**
  - B. extend()
  - C. add()
  - D. append()
- 

**Q.5 How can you repeat the elements of a tuple (1, 2) three times?**

- A. (1, 2) \* 3**
  - B. tuple(1, 2).repeat(3)
  - C. (1, 2) + 3
  - D. (1, 2).repeat(3)
- 

**Q.6 What does Python's consistency refer to in handling data structures?**

- A. Similar operations are available for different data structures**
  - B. Lists and strings are treated as mutable
  - C. Lists and strings are immutable
  - D. Python only supports immutable data structures
-

**Q.7 How would you unpack a list `l = [1, 2, 3]` into individual variables?**

- A. `a, b, c = l`**
  - B. `a, *b = l`
  - C. `a, b = l`
  - D. `a = l[0], b = l[1]`
- 

**Q.8 Which method is used to add a single element to a set?**

- A. `append()`
  - B. `insert()`
  - C. `add()`**
  - D. `push()`
- 

**Q.9 What happens when a duplicate element is added to a set?**

- A. The duplicate is added at the end
  - B. The set throws an error
  - C. The duplicate is ignored**
  - D. The set grows in size
- 

**Q.10 Which of the following is true about variable-length unpacking in Python?**

- A. The `*` operator can be used with strings and tuples, but not lists
  - B. You can only use `*` with lists
  - C. You cannot use `*` for unpacking a tuple
  - D. The `*` operator captures all remaining elements during unpacking**
-