

Final term McQs by Aissh khan

Fall 2023

January2024

85 90% marks

((MCQS))

1: Ether Channel technology was originally developed by Cisco as a LAN technique of grouping several Fast Ethernet or Gigabit Ethernet ports into one logical channel.

A) **Switch-to-switch** B) Router-to-switch C) Gateway-to-router D) Router-to-router

2: _is correct formula to calculate the OSPFv2 cost

A) **Reference bandwidth /Interface bandwidth**

B)Reference bandwidth +2 Interface bandwidth

C) bandwidth-Interface bandwidth

D)Reference bandwidth + 2(1+ Interface bandwidth)

3: Ethernet Mac address is a 48-bit binary value that is usually represented in hexadecimal digits

A. **12** B.16 C.32 D. 128

4. command is used to disable DHCP service on IOS DHCP server

A. **no service dhcp.** B. shut down service dhcp

C. pitig D. remove dhcp service

5.In the context of Multi Area OSPF, the main area is typically called as the

A. Super area B. **Backbone Area** C. Head Area D. Lead Area

6. Extended ACLs fall under the range of

A. 1-99 B. 00-2000 C. 00-20000 D. **100-199**

7. NAT Application Type static NAT is used for

A. Many-to-many address mapping B. Many-to-one address

C. None of given options D. **One-to-one address mapping**

8. The basic rule for placing an ACL is to place it as close to the source as

A. Time based ACL B. Standard ACL

C **Extended ACL** D .None of the given

9. The Open Shortest Path First (OSPF) protocol is a routing protocol based on.....

A .path vector B. Non distance vector C Distance Vector D. **Link state**

10. __ allows you to enter a description of the ACL

A .define B.Desc C .**Remark** D.Detail

11. Which of the following parameters is not relevant to Access Lists?

A. Permit B. **Revoke** C. Remark. D. Deny

12. OSPF cos is calculated and represented in value

A. Decimal point B.**Integer** C.Hexadecimal D.Alpha-numeric

13. In normal practice, the backbone area in multi area OSPF is set as..

A .Area 1 B. Area 8080 C. **Area 0** D. Area 100

14. FF FF FF FF FF FF is a correct

A. **Ethernet broadcast area** B.Ethernet Multicast Address

C .Ethernet Unicast Address D .None

15. In the context of Switch boot up, POST stands for _program

A . **Power on Self Test**

B.Play on Self Test

C. Program on Self Test

D. Ping or Self Test

16. SSH is migsed to TCP port _Chalicex (**most important also read last two McQ m. Imp**)

A. 20 B. 21 C. **22** D.32

17. Ethernet works on of OSI Model

A. Layer 1 B.**Layer 2** C. Layer 5 D.Layer 1 & Layer 2

18. 192.168.0.0 to 192.168.255 255 is one of _IP address ranges

A.Public B.**Private** C.Multicast D.**None of the Given**

19. Which of the following is also known as NAT overloading?

A. Static NNA. B. **Port Address Translation**

C. Dynamic NAT D. Both Static and Dynamic NAT

20. How to store the configuration by replacing the startup-config by the running-config?

A. 51# running-config startup-config B. **S1#copy running-config startup-config**

C. S1(config)#copy running-config startup-config

D. S1(config)# running-config startup-config

21. Which one is valid range for private IP addresses?

A. 196.168.0.0 to 196.168.255.255

B. 198.168.0.0 to 198.168.255.255

C. None of given

D. 192.168.0.0 to 192.168.255.255

22. By default, a router has ACL(s) configured

A. One. B. Two. C. Four. D. **Zero**

23. Dynamic Routing protocol dynamically updates information's to of router

A. Mac table B. IP table

C. Subnet table D. **Routing table**

24. In computer networks, ICMP specifically stands for

Internet communication maintenance protocol

Internal control maintenance protocol

International communication message protocol

Internet control message protocol

25. A wildcard mask is a string of binary digits used by the router to determine which bits of the address are to be examined for a match.

A. 8

B. 16

C. 4

D. 32

26. IPv6 operates on of OSI model

A. Transport Layer

B. Data Link Layer

C. Session Layer

D. Network Layer

27. LSA type 2 refers to

A .Router LSA

B .Network LSA

C .External LSA

28. LSA type 1 refers to

A .Router LSA

B .Network LSA

C .External LSA

29 . Summary LSASummary LSAInterfaces trunk command is used to check whether a trunk has been established between switches.

A .Show

B .Hide

C .Interval

D .Explicit

30 .In an IP Packet, the field value. Identifies that this is an OSPF message.

A. 91 B. 86 C **89** D.87

31. OSPF stands for

A.Object Shortest Protocol Failure

B.Object Shortest Protocol Form

C.Open Short Procedure Format

D.Open Shortest Path First

32 . What is used to create the OSPF neighbor table?

A .Link-state database

B .Forwarding database

C . Routing table

D. Adjacency database

33 .Which OSPF data structure is identical in all routers in an OSPF area after convergence?

A .Adjacency database

B.Link-state database

Routing table

SPF tree

34. Which command can be used to verify the contents of the LSDB in an OSPF area?

A. Show ip ospf database

Show ip ospf interface

Show ip ospf neighbor

Show ip route ospf

35. Is the example of Link State Routing Protocol

A. IGRP B. RIP **C. OSPF** D. EIGRP

36. Static routes are added by _Protocols

A. Protocol and Network administrator

B. None of the given

D. Network administrator

37. STP stands for

A. Switched Tunnel Protocol

B. Stunning Transmission Protocol

C. Standalone Protocol

D. Spanning Tree Protocol

38. Two routers may not form an OSPF adjacency if

A. The subnet masks do not match

B. OSPF Hello or Dead Timers do not match,

C. Network Types do not match

D. All of the given

39. is the example of a distance vector routing protocol

A. EGP B. BGP4 **C. RIP** D. OSPF

40. An access port might accept frames from different VLANs to which it is assigned. This is called

A. VLAN Trunk

B.VLAN Leaking

C .VLAN Trash

D .VLAN Access

41. Protocols do not send the subnet mask along with their routing updates

A . Routing

B .Both the Given

C .None of the Given

D .Classful Routing

42 . The command Router(config)#access-list 95 is a type of _

A .Time based ACL

B .Extended ACL

C .None of given

D .Standard ACL

43 . The command access-Ext 90 represents

A .Time based ACL

B .Extended ACL

C .None of given

D .Standard ACL

44. Which of the following is the correct command that can be executed on a switch to determine the neighbors for building layer-2 topology?

A .Show neighbors

B .Show cdp neighbors

C .Show cdp

D .Switch# pair neighbors

45. Ether Channel technology was originally developed by Cisco as a LAN technique of grouping several Fast Ethernet or Gigabit Ethernet ports into one logical channels

A .Switch-to-switch

B .Router-to-switch

C .-to-router

D .Router-to-router

46. In link Aggregation it is also possible to the number of physical links between the switches to increase the overall speed of switch-to-switch communication

A .Multiply

B .Divide

C .Lessen

D .All of the given

47. Port Forwarding is also called as

A .Tunneling

B .Demultiplexing

C .Scanning

D .Segmentation

48. Protocol was the predecessor of DHCP before its emergence as the standard protocol for the purpose of assigning IP addresses

A .BootP

B .UDP

C .Ip

D .RIPing

49. . All Routing protocols share_components?

A. Similar

B. Different

C. Common

D. Shared

50. The messages help build data structures which are then proceed using?

A. **Routing algorithms.** B. Data processing techniques

B. C. Network protocols. D. Computational algorithms

51. OSPF uses the to choose the best path?

A. SPF Algorithms

B. Dijkstra's Algorithm

C. Link State Advertisements

D. Shortest Path First Algorithm

52. Routers can be grouped into areas to support a system?

A) **Hierarchical**

B) Flat Routing

C) Distance Vector Routing

D) Link-State Routing

53. : OSPF-enabled routers must recognize each other before they can share information. Which of the following mechanisms is used for this recognition?

A) IP addresses

B) Hello packets

C) **Network**

D) Routing tables

54. After adjacencies are established, routers then exchange:

A) Internet control message protocol (ICMP) packets

B) Routing information protocol (RIP) updates

C) Border gateway protocol (BGP) messages

D) **Link state advertisements (LSAs)**

55. Which process creates the routing table?

A. **Forwarding**

B. Routing

C. Switching

D. Bridging

56. OSPF creates and maintain _ databases.

A. One

B. Two

C. Three

D. Four

57. Adjacency table creates the table

A. **Neighbor** B. Contiguity C. Proximity D. Connection

58. Link_state database(LSDB) creates_ table?

- A. Link
- B. Routing
- C. Neighbor
- D. **Topology**

59. Telnet is assigned to TCP port _

- A. 20
- B. 21
- C. 22
- D. **23**

60. Http is assigned to TCP port

- A. 20
- B. **80**
- C. 22
- D. 32

• **Prepared by ::::: Aish Khan**