CS508 Quiz#4

Solved by Masters

1. In JavaScript, navigator is a _____object

Select the correct option

a. Browser

b. User defined

c. Built-in

d. Document

2. Which of the following type of numbers are not supported by PHP?

Select the correct option

a. Real Numbers

b. Unsinged Integers

c. Complex Numbers

d. Singed Integers

3. Which of the following language is used for server-side scripting?

select the correct option

a. PHP

b. C#

c. Ada

d. C++

4. The model in JavaScript provides access to the contents of the browser window.

Select the correct option

a. DOM

b. BOM

c. ROM

d. COM

5. The code written in PHP is returned to the web browser as:

Select the correct option

a. Applets

b. Plain HTML

c. Shell scripts

d. CSS flexbox

6. Which of the given is used before the declaration of variable in PHP?

Select the correct option

a. #sign

b. $ sign

c. ? sign

d. @sign

7. An in PHP is an ordered map.

Select the correct option

a. string

b. array

c. queue

d. stack

8. In the 'break' statement may have an optional parameter or argument.

Select the correct option

a. C#

b. C/C++

c. Java

d. PHP

9. In PHP 'switch' structure, the starts or implements an implicit loop.

Select the correct option

a. Break Statement

b. Continue Statement

c. For Loop

d. Return Statement

10. In JavaScript, "with" statement is an alternative of

select the correct option

a. Multiple document.write statements

b. While statement

c. Single document.write statement

d. Union statement

11. In how many places a javascript code can be placed?

Select the correct option

a. 3

b. 2

c. 4

d. 6

12. If an integer variable is not initialized in PHP then its default value will be:

Select the correct option

a. Zero

b. False

c. NULL

d. One

13. In PHP, if a number is beyond the bounds of the integer type, then it will be interpreted as a instead.

Select the correct option

a. string

b. short

c. float

d. long

14. In JavaScript, which of the given provides access to the contents of browser window?

select the correct option

a. BOM

b. ROM

c. DOM

d. COM

15. The scripts written in PHP are executed by:

Select the correct option

a. Web browser
b. Java
c. Applet Client machine
d. Web Server

16. Arrays in JavaScript are based.
Select the correct option
a. Length
b. One
b. Index Location
d. Zero Index

17. Classes and objects of PHP are similar to
Select the correct option
a. Classes and objects of Basic
b. Classes and objects of C
c. Classes and objects of Java
d. Classes and objects of C++

18. Which of the following type of numbers are not supported by PHP?
select the correct option
a. Complex Numbers
b. Unsinged Integers
c. Real Numbers
d. Singed Integers

19. To dynamically generate a web page, which of the following programming language is most suitable?

the correct option

a. PHP

b. C++

c. Ada

d. Prolog

20. The scripts written in PHP are executed by:

Select the correct option

a. Web Server

b. Web browser

c. Client machine

d. Java Applet

21. Which of the given is used before the declaration of variable in PHP?

Select the correct option

a. ? sign

b. @sign

c. #sign

d. $ sign

22. The data type of variable in PHP is automatically determined by its:

select the correct option

a. Name

b. Location

c. Size

d. Value

23. an object that describes the basic characteristics of the browser, notably its type and version. Select the correct option

a. Window

b. Navigator

c. Document

d. Location

24. How many <script> tags can be used in the <head> element?

Select the correct option

a. One

b. Many

c. Zero

d. Two

25. Which of the following language is used for server-side scripting?

Select the correct option

a. C#

b. Ada

c. C++

d. PHP

26. An in PHP is an ordered map.

Select the correct option

a. queue

b. array

c. stack

d. string

27. In Strings and numeric values are inter convertible

Select the correct option

a. C#

b. C/C++

c. PHP
d. Java

28. In JavaScript, "with" statement is an alternative of
Select the correct option
a. While statement
b. Union statement
c. Multiple document.write statements
d. Single document.write statement

29. In PHP switch structure, the starts or implements an implicit loop.
Select the correct option
a. Return Statement
b. Break Statement
c. Continue Statement
d. For Loop



Question # 6 of 10 (Start time: 10:39:13 AM, 19 July 2023) **Total Marks:**

PHP stands for _____ .

Select the correct option

- ○ PHP: Home Preprocessor
- ● PHP: Hypertext Preprocessor
- ○ PHP: Hypertext Page
- ○ PHP: Home Page

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 7 of 10 (Start time: 10:39:36 AM, 19 July 2023) **Total Marks:** 1

In JavaScript, navigator is a _____object.

Select the correct option

- ○ User defined
- ◉ Browser
- ○ Document
- ○ Built-in

Question # 9 of 10 (Start time: 08:41:24 AM, 19 July 2023) **Total Marks:**

"JavaScript" _____is available in web browser.

Select the correct option

- (●) Interpreter
- ( ) Conjunction
- ( ) Compiler
- ( ) Linker

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 10 of 10 (Start time: 10:40:55 AM, 19 July 2023) **Total Marks:** 1

To dynamically generate a web page, which of the following programming language is most suitable?

Select the correct option

Reload Math Equations

○	Ada
○	C++
○	Prolog
●	PHP

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 9 of 10 (Start time: 10:40:33 AM, 19 July 2023) **Total Marks:** 1

In _____, Strings and numeric values are inter convertible

Select the correct option

○	C/C++
○	Java
○	PHP
◉	C#

Question # 5 of 10 (Start time: 10:12:13 AM, 19 July 2023) Total Marks: 1

To dynamically generate a web page, which of the following programming language is most suitable?

Select the correct option

Reload Math Equations

○	Prolog
○	PHP
○	C++
○	Ada

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 202**

Question # 1 of 10 (Start time: 10:10:14 AM, 19 July 2023) **Total Marks:**

In JavaScript, navigator is a _____object.

Select the correct option

- ○ User defined
- ◉ Browser
- ○ Document
- ○ Built-in

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 2 of 10 (Start time: 10:11:00 AM, 19 July 2023) **Total Marks:** 1

The division of two integers (i.e. 7/2) in PHP generates a/an:

Select the correct option

Reload Math Equations

- (●) Floating point number
- ( ) Integer
- ( ) Exception
- ( ) Runtime error

Question # 4 of 10 (Start time: 10:11:56 AM, 19 July 2023) **Total Marks:**

Arrays in JavaScript are _____ based.

Select the correct option

- ○ One Index
- ○ Length
- ● Zero Index
- ○ Location

Question # 3 of 10 (Start time: 10:11:28 AM, 19 July 2023) **Total Marks:**

Which of the given is used before the declaration of variable in PHP?

Select the correct option

- ○ @ sign
- ○ # sign
- ● $ sign
- ○ ? sign

Question # 6 of 10 (Start time: 10:12:43 AM, 19 July 2023) **Total Marks**

In _____, the 'break' statement may have an optional parameter or argument.

Select the correct option

- ○ Java
- ○ C#
- ○ C/C++
- ● PHP

Question # 8 of 10 (Start time: 10:13:31 AM, 19 July 2023) **Total Marks:**

In PHP 'switch' structure, the _____ starts or implements an implicit loop.

Select the correct option

- (●) Continue Statement
- ( ) Break Statement
- ( ) Return Statement
- ( ) For Loop

Question # 7 of 10 (Start time: 10:13:08 AM, 19 July 2023) **Total Marks:**

Which operator is used for concatenation in JavaScript?

Select the correct option

- (●) +
- ( ) |
- ( ) $
- ( ) dot(.)

Question # 3 of 10 (Start time: 10:17:48 AM, 19 July 2023) **Total Marks:** 1

The resultant value of variable 'x' in JavaScript statement var x = "5" - "2" ; will be_____.

Select the correct option

- 52
- "5"-2"
- 3
- 5-2

Question # 10 of 10 (Start time: 10:14:18 AM, 19 July 2023) **Total Marks:** 1

The resultant value of variable 'x' in JavaScript statement var x = "5" - "2" ; will be_____.

Select the correct option

○	5-2
◉	3
○	52
○	"5"-2"

Question # 2 of 10 (Start time: 10:17:21 AM, 19 July 2023) **Total Marks:** 1

In JavaScript, which of the given provides access to the contents of browser window?

Select the correct option

- ○ COM
- ○ ROM
- ○ BOM
- ◉ DOM

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 1 of 10 (Start time: 10:16:56 AM, 19 July 2023) **Total Marks:**

How many <script> tags can be used in the <head> element?

Select the correct option

- ○ Two
- ○ Zero
- ○ One
- ◉ Many

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 9 of 10 (Start time: 10:13:55 AM, 19 July 2023) **Total Marks:** 1

The code written in PHP is returned to the web browser as:

Select the correct option

Reload Math Equations

●	Plain HTML
○	Shell scripts
○	Applets
○	CSS flexbox

Question # 7 of 10 (Start time: 10:19:22 AM, 19 July 2023) **Total Marks**

PHP stands for _____ .

Select the correct option

- (●) PHP: Hypertext Preprocessor
- ( ) PHP: Home Preprocessor
- ( ) PHP: Hypertext Page
- ( ) PHP: Home Page

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 8 of 10 (Start time: 10:20:00 AM, 19 July 2023) **Total Marks:**

The scripts written in PHP are executed by:

Select the correct option

Reload Math Equations

- (●) Web Server
- ( ) Java Applet
- ( ) Client machine
- ( ) Web browser

CS508 - Modern Programming Languages (Quiz 4) Quiz Start Time: 10:16 AM, 19 July 2023

Question # 6 of 10 (Start time: 10:19:05 AM, 19 July 2023) Total Marks: 1

Which of the following language is used for server-side scripting?

Select the correct option

Reload Math Equations

- Ada
- C#
- C++
- PHP

Question # 4 of 10 (Start time: 10:18:14 AM, 19 July 2023) **Total Marks:**

Which of the given operator is used to return a reference from a function in PHP?

Select the correct option

- (●) &
- ( ) &&
- ( ) Dot
- ( ) $

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 9 of 10 (Start time: 10:20:26 AM, 19 July 2023) **Total Marks:**

Which of the given is used before the declaration of variable in PHP?

Select the correct option

○	@ sign
○	# sign
○	? sign
●	$ sign

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 10 of 10 (Start time: 10:20:54 AM, 19 July 2023) **Total Marks:**

To dynamically generate a web page, which of the following programming language is most suitable?

Select the correct option

Reload Math Equations

- (●) PHP
- ( ) Prolog
- ( ) C++
- ( ) Ada

Question # 3 of 10 (Start time: 10:37:40 AM, 19 July 2023) **Total Marks:**

"with" statement in JavaScript is an alternative of _____.

Select the correct option

○	Multiple 'document.read' Statements
○	Single 'document.read' Statement
●	Multiple 'document.write' Statements
○	Single 'document.write' Statement

Question # 4 of 10 (Start time: 10:38:10 AM, 19 July 2023) **Total Marks:**

Which of the given is used before the declaration of variable in PHP?

Select the correct option

- ? sign
- # sign
- $ sign
- @ sign

Question # 5 of 10 (Start time: 10:18:37 AM, 19 July 2023) **Total Marks:**

The _____model in JavaScript provides access to the contents of the browser window.

Select the correct option

- ○ BOM
- ○ ROM
- ● DOM
- ○ COM

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 1 of 10 (Start time: 10:36:35 AM, 19 July 2023) **Total Marks:**

_____ , an object that describes the basic characteristics of the browser, notably its type and version.

Select the correct option

- Document
- Location
- Navigator
- Window

Question # 2 of 10 (Start time: 10:36:57 AM, 19 July 2023) **Total Marks**

In JavaScript, "with" statement is an alternative of _____.

Select the correct option

○	While statement
●	Multiple document.write statements
○	Single document.write statement
○	Union statement

Question # 5 of 10 (Start time: 10:38:46 AM, 19 July 2023) **Total Marks:**

The _____model in JavaScript provides access to the contents of the browser window.

Select the correct option

- (●) DOM
- ( ) ROM
- ( ) COM
- ( ) BOM

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 8 of 10 (Start time: 10:39:50 AM, 19 July 2023) **Total Marks:** 1

The data type of variable in PHP is automatically determined by its:

Select the correct option

Reload Math Equations

○	Size
●	Value
○	Location
○	Name