



VU NET



DOWNLOAD PAST PAPERS

vunet.blogspot.com

1 MB or 1 megabyte is equivalent to----

Answer (Please select your correct option)

☐

1024 bytes

☐

1024² bytes

☐

1024³ bytes

☐


1000000 bytes



A -----system collects physically separate, possibly heterogeneous, systems into a single coherent system, providing the user with access to the various resources that the system maintains

Answer (Please select your correct option)

☐ Distributed



☐ Real-time

☐ Single user

☐ Time-sharing



-----has a hierarchical file system structure.

Answer (Please select your correct option)



DOS



Windows



UNIX



None of the given options



Round-Robin Scheduling is a ----- scheduling algorithm

Answer (Please select your correct option)

☐ Preemptive



☐ non-preemptive

☐ Preemptive or non-preemptive.

☐ None of the given options



A piece of code in a cooperating process in which the process may update shared data is called-----

Answer (Please select your correct option)



Buffer



Critical section



Semaphore



None of the given options



The Swap instruction which is the hardware solution to synchronization problem does not satisfy the _____ condition, hence not considered to be a good solution.

Answer (Please select your correct option)

Progress



Bounded waiting



Mutual exclusion



None of the given






A _____ is a piece of code in a cooperating process in which the process may updates shared data (variable, file, database, etc.).

Answer (Please select your correct option)

☐ critical section



☐ critical region

☐ monitor

☐ all of the given are correct



Semaphore is a _____ solution to the synchronization problems.

Answer (Please select your correct option)

☐

Operating system

☐

Software

☐

None of the given

☐

Hardware



In Unix/ Linux, by default the standard input file is attached to the _____

Answer (Please select your correct option)

☐ Mouse

☐ Keyboard

☐ Light pen

☐ Joystick



The ----- are used for communication between related or unrelated processes on the same system or unrelated processes on different systems.

Answer (Please select your correct option)

☐ None of the given

☐ SSD socket

☐ DSD socket

☐ BSD sockets



The files which are automatically opened by the kernel for every process for the process to read its input from and send its output and error messages are called.....

Answer (Please select your correct option)

☐ None of the given

☐ Standard File descriptors

☐ File descriptors

☐ Standard files

Made By: Waqar Siddhu



Bounded Buffer is a buffer of _____ size



Answer (Please select your correct option)

☐ Variable

☐ Fixed

☐ Both

☐ None of the given



The goal of single user operating system is

Answer (Please select your correct option)

☐

To maximize utilization of CPU

☐

To maximize the user responsiveness

☐

To maximize utilization of peripheral devices

☐

To maximize throughput



Which type of operating system guarantees that critical tasks must be completed on time?

Answer (Please select your correct option)

☐

Timesharing system

☐

Multitasking system

☐

Batch system

☐

Realtime system



Made By: Waqar Siddhu



Which of the following command is used to read data from file named academics?

Answer (Please select your correct option)

☐

con < academics

☐

cat < academics

☐

socket > academics

☐

ran > academics



_____ command puts a foreground process into background.

Answer (Please select your correct option)

☐ fg☐ bg☐ Ctrl z☐ None of the given



Given the gantt chart, which one of the following is average waiting time

Answer (Please select your correct option)

☐ 35.66

☐ 1.33

☐ 34.66

☐ 2.33



_____ is solution to the problem of indefinite blockage of low-priority processes.

Answer (Please select your correct option)

☐ Aging



☐ Starvation

☐ Deadlock

☐ None of the given



The part of machine level instruction, which tells the central processor what has to be done, is

Answer (Please select your correct option)



Address



Locator



Flip-Flop



Operation code

Made By: Waqar Siddhu



Which of the following statements is false?

Answer (Please select your correct option)



Two different critical sections may be executed concurrently if they do not use the same shared variables.



Programs with critical sections can never be used simultaneously by more than one process.



None of the given



A process wanting to enter a critical section currently in use must wait for the process utilizing the critical section to terminate.

Made By: Waqar Siddhu

1 MB or 1 megabyte is equivalent to----

Answer (Please select your correct option)

☐

1024 bytes

☐

1024^2 bytes

☐

1024^3 bytes

☐

1000000 bytes

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



A -----system collects physically separate, possibly heterogeneous, systems into a single coherent system, providing the user with access to the various resources that the system maintains

Answer (Please select your correct option)

☐ Distributed

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ Real-time

☐ Single user

☐ Time-sharing

Made By: Waqar Siddhu



-----has a hierarchical file system structure.

Answer (Please select your correct option)



DOS



Windows



UNIX



None of the given options

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



Round-Robin Scheduling is a ----- scheduling algorithm

Answer (Please select your correct option)

☐ Preemptive

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ non-preemptive

☐ Preemptive or non-preemptive.

☐ None of the given options

Made By: Waqar Siddhu



A piece of code in a cooperating process in which the process may update shared data is called-----

Answer (Please select your correct option)



Buffer



Critical section



Semaphore



None of the given options

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



The Swap instruction which is the hardware solution to synchronization problem does not satisfy the _____ condition, hence not considered to be a good solution.

Answer (Please select your correct option)

☐

Progress

☐

Bounded waiting

☐

Mutual exclusion

☐

None of the given

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



A _____ is a piece of code in a cooperating process in which the process may updates shared data (variable, file, database, etc.).

Answer (Please select your correct option)

☐ critical section

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ critical region

☐ monitor

☐ all of the given are correct

Made By: Waqar Siddhu



Semaphore is a _____ solution to the synchronization problems.

Answer (Please select your correct option)



Operating system

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



Software



None of the given



Hardware

Made By: Waqar Siddhu



In Unix/ Linux, by default the standard input file is attached to the _____

Answer (Please select your correct option)

☐

Mouse

☐

Keyboard

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐

Light pen

☐

Joystick

Made By: Waqar Siddhu



The ----- are used for communication between related or unrelated processes on the same system or unrelated processes on different systems.

Answer (Please select your correct option)

☐ None of the given

☐ SSD socket

☐ DSD socket

☐ BSD sockets

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu

The files which are automatically opened by the kernel for every process for the process to read its input from and send its output and error messages are called.....

Answer (Please select your correct option)

☐ None of the given

☐ Standard File descriptors

☐ File descriptors

☐ Standard files

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



Bounded Buffer is a buffer of _____ size

Answer (Please select your correct option)

☐ Variable

☐ Fixed

☐ Both

☐ None of the given

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



The goal of single user operating system is

Answer (Please select your correct option)

☐

To maximize utilization of CPU

☐

To maximize the user responsiveness

☐

To maximize utilization of peripheral devices

☐

To maximize throughput

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



Which type of operating system guarantees that critical tasks must be completed on time?

Answer (Please select your correct option)

☐

Timesharing system

☐

Multitasking system

☐

Batch system

☐

Realtime system

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



Which of the following command is used to read data from file named academics?

Answer (Please select your correct option)

☐

con < academics

☐

cat < academics

☐

socket > academics

☐

ran > academics

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



_____ command puts a foreground process into background.

Answer (Please select your correct option)

☐ fg☐ bg☐ Ctrl z☐ None of the given

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



Given the gantt chart, which one of the following is average waiting time

Answer (Please select your correct option)

35.66



1.33



34.66



2.33



Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



_____ is solution to the problem of indefinite blockage of low-priority processes.

Answer (Please select your correct option)



Aging

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



Starvation



Deadlock



None of the given

Made By: Waqar Siddhu



The part of machine level instruction, which tells the central processor what has to be done, is

Answer (Please select your correct option)



Address



Locator



Flip-Flop



Operation code

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



Which of the following statements is false?

Answer (Please select your correct option)



Two different critical sections may be executed concurrently if they do not use the same shared variables.



Programs with critical sections can never be used simultaneously by more than one process.



None of the given



A process wanting to enter a critical section currently in use must wait for the process utilizing the critical section to terminate.

Made By: Waqar Siddhu



Main memory is a large array of -----called memory locations ranging in size from hundreds of thousands to billions.

Answer (Please select your correct option)



Interrupts



Registers



Digits



Words

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



In ----- model, there is a kernel thread for every user thread

Answer (Please select your correct option)

☐ Many-to-Many

☐ None of the given options

☐ One-to-One

☐ Many-to-One

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



A time interval when a process uses CPU only is called

Answer (Please select your correct option)



CPU burst

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



IO burst



Scheduling



None of the given options

Made By: Waqar Siddhu



The part of the program where the shared memory is accessed is called -----

Answer (Please select your correct option)

☐

Buffer

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐

Critical Section

☐

Semaphore

☐

None of the given options

Made By: Waqar Siddhu



Utilities used for system administration (halt, ifconfig, fdisk, etc.) are stored in _____ directory.

Answer (Please select your correct option)



/dev



/boot



/sbin



/lib

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



The Swap instruction which is the hardware solution to synchronization problem does not satisfy the _____ condition, hence not considered to be a good solution.

Answer (Please select your correct option)

☐

Progress

☐

Bounded waiting

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐

Mutual exclusion

☐

None of the given

Made By: Waqar Siddhu



All ----- within a process share the same address space

Answer (Please select your correct option)



Threads

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



Processes



CPU burst



IO Burst

Made By: Waqar Siddhu



In a Multilevel Queue, the foreground queue has ----- scheduling algorithm and background queue has ----- scheduling algorithm

Answer (Please select your correct option)



First Come First Serve, Round-Robin



Round-Robin, First Come First Serve

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



Round-Robin, Round-Robin



First Come First Serve, First Come First Serve

Made By: Waqar Siddhu



Priority of a process is ----- to the priority number of the process.

Answer (Please select your correct option)

☐

Directly proportional

☐

Equal

☐

Inversely proportional

☐

Greater

i think but not
sure

Made By: Waqar Siddhu



The view is that it is a program that acts as an intermediary between a user of a computer and the computer hardware, and makes the computer system convenient to use.

Answer (Please select your correct option)

☐ Top-down

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ Bottom-up

☐ Alternate

☐ None of the above

Made By: Waqar Siddhu



_____ commands in Linux helps to create a new directory.

Answer (Please select your correct option)

ls



cp



mv



mkdir



Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



_____ scheduler selects the process from the job pool and put them in main memory.

Answer (Please select your correct option)



Long term

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



Short term



Medium term



Swapper

Made By: Waqar Siddhu



-----are used for communication between unrelated processes on a system.

Answer (Please select your correct option)

☐

Pipes

☐

Named pipe (FIFO):

☐

BSD Sockets

☐

none of the given options

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



The syntax for output redirection is

Answer (Please select your correct option)



command < output-file



command >= output-file



command > output-file

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



command =< output-file

Made By: Waqar Siddhu



The shared buffer can be implemented as a circular array with logical pointers.

Answer (Please select your correct option)



Five



Two

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



Three



Four

Made By: Waqar Siddhu



Limit register contains

Answer (Please select your correct option)



The size of the process

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



Starting address of the process



Address of the next instruction



Operand to be fetched

Made By: Waqar Siddhu



Which of the following command is used to read data from file named academics?

Answer (Please select your correct option)

☐

con < academics

☐

cat < academics

☐

socket > academics

☐

ran > academics

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



_____command puts a foreground process into background.

Answer (Please select your correct option)

☐ fg☐ bg☐ Ctrl z☐ None of the given

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



_____ is solution to the problem of indefinite blockage of low-priority processes.

Answer (Please select your correct option)

☐

Aging

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐

Starvation

☐

Deadlock

☐

None of the given

Made By: Waqar Siddhu



What is the requirement for solution to critical section problem?

Answer (Please select your correct option)

☐ Mutual Exclusion

☐ Progress

☐ Bounded Waiting

☐ All of the given

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

Made By: Waqar Siddhu



Main memory is a large array of -----called memory locations ranging in size from hundreds of thousands to billions.

Answer (Please select your correct option)

☐ Interrupts

☐ Registers

☐ Digits

☐ Words





In ----- model, there is a kernel thread for every user thread


Answer (Please select your correct option)

☐ Many-to-Many

☐ None of the given options

☒ One-to-One

☐ Many-to-One






A time interval when a process uses CPU only is called

Answer (Please select your correct option)

☐

CPU burst

☐

IO burst

☐

Scheduling

☐

None of the given options



The part of the program where the shared memory is accessed is called -----

Answer (Please select your correct option)

☐

Buffer

☐

Critical Section

☐

Semaphore

☐

None of the given options



Utilities used for system administration (halt, ifconfig, fdisk, etc.) are stored in _____ directory.

Answer (Please select your correct option)

☐ /dev

☐ /boot

☒ /sbin

☐ /lib





The Swap instruction which is the hardware solution to synchronization problem does not satisfy the _____ condition, hence not considered to be a good solution.

Answer (Please select your correct option)

- ☐ Progress
- ☐ Bounded waiting
- ☐ Mutual exclusion
- ☐ None of the given





All ----- within a process share the same address space

Answer (Please select your correct option)



Threads



Processes



CPU burst



IO Burst



In a Multilevel Queue, the foreground queue has ----- scheduling algorithm and background queue has ----- scheduling algorithm

Answer (Please select your correct option)



First Come First Serve, Round-Robin



Round-Robin, First Come First Serve



Round-Robin, Round-Robin



First Come First Serve, First Come First Serve



Priority of a process is ----- to the priority number of the process.

Answer (Please select your correct option)



Directly proportional



Equal



Inversely proportional



Greater



The view is that it is a program that acts as an intermediary between a user of a computer and the computer hardware, and makes the computer system convenient to use.

Answer (Please select your correct option)

☐ Top-down



☐ Bottom-up

☐ Alternate

☐ None of the above



_____ commands in Linux helps to create a new directory.

Answer (Please select your correct option)

ls



cp



mv



mkdir



Made By: Waqar Siddhu



_____ scheduler selects the process from the job pool and put them in main memory.

Answer (Please select your correct option)

☐ Long term



☐ Short term

☐ Medium term

☐ Swapper



-----are used for communication between unrelated processes on a system.

Answer (Please select your correct option)




Pipes



Named pipe (FIFO):



BSD Sockets



none of the given options



The syntax for output redirection is

Answer (Please select your correct option)



command < output-file



command >= output-file



command > output-file



command =< output-file




The shared buffer can be implemented as a circular array with logical pointers.

Answer (Please select your correct option)

Five



Two



Three



Four





Limit register contains

Answer (Please select your correct option)

☐ The size of the process



☐ Starting address of the process

☐ Address of the next instruction

☐ Operand to be fetched



Which of the following command is used to read data from file named academics?

Answer (Please select your correct option)



con < academics



cat < academics



socket > academics



ran > academics



_____command puts a foreground process into background.

Answer (Please select your correct option)

☐ fg☐ bg☐ Ctrl z☐ None of the given



_____ is solution to the problem of indefinite blockage of low-priority processes.

Answer (Please select your correct option)

☐

Aging

☐

Starvation

☐

Deadlock

☐

None of the given



What is the requirement for solution to critical section problem?

Answer (Please select your correct option)

☐ Mutual Exclusion

☐ Progress

☐ Bounded Waiting

☐ All of the given



When process opens its first file explicitly it will get descriptor number _____

Choices:

2

standard file descriptors.

Standard input: 0 (keyboard)

Standard output: 1 (display screen)

Standard error: 2 (display screen)

page 52

3



1

4

Using _____ system call, we can create a new process in Unix.

Choices:

☒ fork☐ exec☐ wait☐ exit

Which one is not the state of the process?

Choices:

☐ Waiting

☐ Running

☒ Privileged

☐ New

To avoid the race condition, the number of processes that may be simultaneously inside their critical section is

Choices:

8

☒ 1

16

0

_____ loads, verifies, and executes programs that have been translated into Java byte code.

Choices:

☒ Java Virtual Machine☐ VMWare☐ VM Solution☐ VM PC

A time interval when a process uses CPU only is called _____.

Choices:☐ Scheduling☐ I/O burst☒ CPU burst☐ Dispatch latency

Round robin scheduling usually increases the average waiting time so its performance heavily depends upon _____.

Choices:

☐ No. of processes

☒ Time quantum

☐ Switching

☐ No. of queues

Due to which of the following reason, a parent may terminate the execution of one of its children.

Choices:

☒ Use more resources than allocated


☐ Busy other than assigned task

☐ Start abnormal behavior

☐ Many jobs in a system

Which of the following tool is used for inter process communication between related or unrelated processes on the same system or unrelated processes on different system over the network?

Choices:

☐ Pipe☐ BSD socket☒ Named pipe (FIFO)☐ Message Queue

The files which are automatically opened by the kernel for every process to read its input from and send its output and error messages are called_____.

Choices:

☐ File identifiers☐ Standard File descriptors☐ File descriptors☒ Standard files

In Unix/Linux client server process communication, server process runs in the background by terminating its command line with -----.

Choices:

☒ &☐ @☐ %☐ \$

Each thread has its own -----.

Choices:

☐ Process ID (PID)

☐ Address Space

☒ Thread ID (TID)

☐ Open file descriptors

Preemptive scheme of Short job first scheduling is known as ----- .

Choices:

☐ First Come First Serve Scheduling

☒ Shortest-Remaining-Time-First

☐ Priority Scheduling

☐ Round-Robin Scheduling

A process terminates by calling the -----system call.

Choices:

☐ wait☐ fork☒ exec☐ exit

The -----system call is used to open or create a file.

Choices:

☒ open()☐ read()☐ write()☐ close()

The syntax for input redirection is

Choices:

☒ command < input-file

☐ command > input-file

☐ command >= input-file

☐ command =< input-file

The syntax for output redirection is

Choices:

☐ command < output-file

☐ command >= output-file

☒ command > output-file

☐ command =< output-file

_____ algorithm is the optimal scheduling algorithm among all the non-preemptive scheduling algorithms.

Choices:

☒ Shortest Job First scheduling

☐ First Come First Serve

☐ Priority Scheduling

☐ Round Robin Scheduling

Process synchronization is a process of helping processes to _____

Choices:

☐ update the shared data simultaneously

☒ update the shared data and resources in an orderly fashion

☐ not to update the shared data or memory

☐ access data and memory at first come first serve basis

A parent process calling _____ system call will be suspended until any immediate child terminates.

Choices:

☒ wait☐ fork☐ exit☐ exec

_____ commands in Linux is used to copy file

Choices:

☐ ls☒ cp☐ mv☐ mkdir

Inter process communication (IPC) allows process to communicate and to synchronize their actions without sharing the same _____

Choices:

☒ Address space☐ Messages☐ Pipes☐ Message Queue

Pipe system call is used to _____ a pipe

Choices:

☐ Destroy☒ Create☐ Modify☐ Clear

Which of the following command is used to read data from file named academics?

Choices:

☒ con < academics☐ cat < academics☐ socket > academics☐ ran > academics

In a multithreaded model, Which one of the following provides true concurrency?

Choices:

☐ Many-to-one

☐ One-to-one

☒ Many-to-many

☐ One-to-many



In _____ model, there is a kernel thread for every user thread.

Choices:

☒ One-to-one☐ Many-to-one☐ Many-to-many☐ One-to-many

_____ loads, verifies, and executes programs that have been translated into Java byte code.


Choices:

☒ Java Virtual Machine

☐ VMWare

☐ VM Solution

☐ VMPC



_____ is the time taken for the dispatcher to stop one process and start another process.

Choices:

☒ Dispatch latency☐ Scheduling☐ Context switching☐ Preemption

A time interval when a process uses CPU only is called _____.

Choices:

☐ Scheduling☐ I/O burst☒ CPU burst☐ Dispatch latency

A time interval when a process uses I/O devices only is called _____.

Choices:

☐ CPU burst☒ I/O burst☐ Scheduling☐ Context switching

While two processes in execution, only one can be in critical section at a time , this requirement is named as _____.

Choices:

☐ Race condition☒ Mutual exclusion☐ Progress☐ Bounded waiting

The file descriptor for Standard Output (stdout) is -----.

Choices:

☐ 0☒ 1☐ 2☐ 3

The file descriptor for Standard error (stderr) is -----.

Choices:

0



1



2



3



----- are used by shell commands to pass data from one shell pipeline to another, without creating temporary files.

Choices:

☐ Pipes☐ Message queues☒ BSD sockets☐ FIFOs

Preemptive -----scheduling is sometimes called
shortest-remaining-time-first scheduling.

Choices:

☐ First-Come-First-Served (FCFS)

☐ Round-Robin

☒ Sorted Job First (SJF)

☐ Priority

In a Multilevel Queue, the foreground queue has ----- scheduling algorithm and background queue has ----- scheduling algorithm.

Choices:

☐ First Come First Serve, Round-Robin


☒ Round-Robin, First Come First Serve

☐ Round Robin, Round Robin

☐ First Come First Serve, First Come First Serve

A process terminates by calling the -----system call.

Choices:

☒ wait☐ fork☐ exec☐ exit

The syntax for input redirection is

Choices:

☒ command < input-file

☐ command > input-file

☐ command >= input-file

☐ command =< input-file

A _____ is a piece of code in a cooperating process in which the process may update shared data (variable, file, database, etc.).

Choices:

☐ critical section☐ critical region☐ monitor☐ semaphore

A parent process calling _____ system call will be suspended until any immediate child terminates.

Choices:

☐ wait☐ fork☒ exit☐ exec

_____ commands in Linux is used to copy file

Choices:

☐ ls☒ cp☐ mv☐ mkdir

Inter process communication (IPC) allows process to communicate and to synchronize their actions without sharing the same _____

Choices:

☒ Address space☐ Messages☐ Pipes☐ Message Queue

Pipe system call is used to _____ a pipe

Choices:


☐ Destroy☒ Create☐ Modify☐ Clear

Which of the following command is used to read data from file named academics?

Choices:

☒ con < academics☐ cat < academics☐ socket > academics☐ ran > academics

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



In a multithreaded model, Which one of the following provides true concurrency?

Choices:

☐ Many-to-one☐ One-to-one☒ Many-to-many☐ One-to-many

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306




In _____ model, there is a kernel thread for every user thread.

Choices:

☒ One-to-one

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ Many-to-one☐ Many-to-many☐ One-to-many

_____ loads, verifies, and executes programs that have been translated into Java byte code.

Choices:

☒ Java Virtual Machine☐ VMWare☐ VM Solution☐ VMPC

_____ is the time taken for the dispatcher to stop one process and start another process.

Choices:

☒ Dispatch latency

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ Scheduling☐ Context switching☐ Preemption

A time interval when a process uses CPU only is called _____.

Choices:

☐ Scheduling☐ I/O burst☒ CPU burst☐ Dispatch latency

A time interval when a process uses I/O devices only is called _____.

Choices:

☐ CPU burst☒ I/O burst☐ Scheduling☐ Context switching

While two processes in execution, only one can be in critical section at a time , this requirement is named as _____.

Choices:

☐ Race condition☒ Mutual exclusion☐ Progress☐ Bounded waiting

The file descriptor for Standard Output (stdout) is -----.

Choices:

☐ 0

☒ 1

☐ 2

☐ 3

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

The file descriptor for Standard error (stderr) is -----.

Choices:

☐ 0

☐ 1

☒ 2

☐ 3

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306



----- are used by shell commands to pass data from one shell pipeline to another, without creating temporary files.

Choices:

☐ Pipes☐ Message queues☒ BSD sockets☐ FIFOs

Preemptive -----scheduling is sometimes called
shortest-remaining-time-first scheduling.

Choices:

☐ First-Come-First-Served (FCFS)

☐ Round-Robin

☒ Sorted Job First (SJF)

☐ Priority

In a Multilevel Queue, the foreground queue has ----- scheduling algorithm and background queue has ----- scheduling algorithm.

Choices:

☐ First Come First Serve, Round-Robin

☒ Round-Robin, First Come First Serve

☐ Round Robin, Round Robin

☐ First Come First Serve, First Come First Serve

A process terminates by calling the -----system call.

Choices:

☒ wait☐ fork☐ exec☐ exit

The syntax for input redirection is

Choices:

☒ command < input-file

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ command > input-file

☐ command >= input-file

☐ command =< input-file

A _____ is a piece of code in a cooperating process in which the process may update shared data (variable, file, database, etc.).

Choices:

☐ critical section☐ critical region☐ monitor☐ semaphore

A parent process calling _____ system call will be suspended until any immediate child terminates.

Choices:

☐ wait

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ fork☒ exit☐ exec

When process opens its first file explicitly it will get descriptor number _____

Choices:

2

standard file descriptors.

Standard input: 0 (keyboard)

Standard output: 1 (display screen)

Standard error: 2 (display screen)

page 52

3



1

4

Using _____ system call, we can create a new process in Unix.

Choices:☒ fork☐ exec☐ wait☐ exit

Which one is not the state of the process?

Choices:

☐ Waiting

☐ Running

☒ Privileged

☐ New

To avoid the race condition, the number of processes that may be simultaneously inside their critical section is

Choices:

8

☒ 1

16

0

_____ loads, verifies, and executes programs that have been translated into Java byte code.

Choices:

☒ Java Virtual Machine☐ VMWare☐ VM Solution☐ VM PC

A time interval when a process uses CPU only is called _____.

Choices:☐ Scheduling☐ I/O burst☒ CPU burst☐ Dispatch latency

Round robin scheduling usually increases the average waiting time so its performance heavily depends upon _____.

Choices:

☐ No. of processes

☒ Time quantum

☐ Switching

☐ No. of queues

Due to which of the following reason, a parent may terminate the execution of one of its children.

Choices:

☒ Use more resources than allocated

☐ Busy other than assigned task

☐ Start abnormal behavior

☐ Many jobs in a system

Which of the following tool is used for inter process communication between related or unrelated processes on the same system or unrelated processes on different system over the network?

Choices:

☐ Pipe☒ BSD socket☐ Named pipe (FIFO)☐ Message Queue

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

The files which are automatically opened by the kernel for every process to read its input from and send its output and error messages are called_____.

Choices:

☐ File identifiers☐ Standard File descriptors☐ File descriptors☒ Standard files

In Unix/Linux client server process communication, server process runs in the background by terminating its command line with -----.

Choices:

☒ &

☐ @

☐ %

☐ \$

Each thread has its own -----.

Choices:

☐ Process ID (PID)

☐ Address Space

☒ Thread ID (TID)

☐ Open file descriptors

Preemptive scheme of Short job first scheduling is known as ----- .

Choices:

☐ First Come First Serve Scheduling

☒ Shortest-Remaining-Time-First

☐ Priority Scheduling

☐ Round-Robin Scheduling

A process terminates by calling the -----system call.

Choices:

☐ wait☐ fork☒ exec☐ exit

The -----system call is used to open or create a file.

Choices:

☒ open()☐ read()☐ write()☐ close()

The syntax for input redirection is

Choices:

☒ command < input-file

☐ command > input-file

☐ command >= input-file

☐ command =< input-file

The syntax for output redirection is

Choices:

☐ command < output-file

☐ command >= output-file

☒ command > output-file

☐ command =< output-file

_____ algorithm is the optimal scheduling algorithm among all the non-preemptive scheduling algorithms.

Choices:

☒ Shortest Job First scheduling

☐ First Come First Serve

☐ Priority Scheduling

☐ Round Robin Scheduling

Process synchronization is a process of helping processes to _____

Choices:

☐ update the shared data simultaneously

☒ update the shared data and resources in an orderly fashion

☐ not to update the shared data or memory

☐ access data and memory at first come first serve basis

A parent process calling _____ system call will be suspended until any immediate child terminates.

Choices:

☒ wait

Correct Answer Solved By Hadi
usmanraj20@gmail.com
03228043306

☐ fork☐ exit☐ exec