

With 32 bits IP addresses are equal to _____.

Select the correct option

☐

32^2

☐

8^{32}

☐

2^{32}

☐

4^{32}

In the context of computer networks, IEEE stands for _____.

Select the correct option



Institute of Electrical and Electronic Engineers



Institute of Engineering and Electrical Emporium



Institute of Electrical and Electronic Emporium



None of the given

Shielded twisted pair is an example of _____.

Select the correct option

☐

None of the given

☐

Coaxial cable

☐

Fiber optic cable

☒

Twisted pair

_____ is world's most popular LAN standard.

Select the correct option



IEEE802.12(g)



ANSI



Ethernet



ISO

When a new switch is installed in the network it has _____.

Select the correct option

☐

No address

☐

Few addresses

☐

All addresses

☒

None of the given

Basically WAN follows the rules/standards developed by _____.

Select the correct option



IEEE



IETF



ITU



RFC

_____ does allow the sender to overflow receiver's buffer by transmitting too much, too fast.

Select the correct option

☐	Congestion Control
☐	Flow Control
☐	Collision Control
☐	Error Control

An application requesting for services from server modules is called_____.

Select the correct option



Crimper



User



Client



Server

_____ is used to simulate new networks.

Select the correct option

☐

a) Wireshark

☒

None of the given

☐

Both a and b

☐

b) Packet Tracer

A specification called Fast Ethernet was created which runs at _____ Mbps.

Select the correct option

☐

10

☐

1000

☒

100

☐

500

Frame Check Sequence (FCS) is a _____.

Select the correct option

☐	Topology
☐	Error Recovery Process
☒	Error Detecting Code
☐	Communication Protocol

Click to

OSI stands for _____.

Select the correct option

☒	Open System Interconnection
☐	Open Sample Internet
☐	Open Short Interconnection
☐	Open System Internet

To send a packet, sender needs to know the _____ of the receiver.

Select the correct option

☐	RAM size
☐	DMA address
☒	IP address
☐	Hard disk size

Routers have _____ interfaces of many different types.

Select the correct option

☒	only two	x
☐	only four	
☐	only three	
☐	lots of	✓

Routers typically have _____ IP address per physical interface.

Select the correct option



one



three



four



two

A PC's _____ router is simply the router to which that PC sends packets when the destination is in another network or subnet.

Select the correct option



☐	alternate
☐	secondary
☐	extra
☒	default

Packet strictly refers to a protocol data unit at the_____.

Select the correct option

☐	network layer
☐	application layer
☒	physical layer
☐	data link layer

For each application program that is currently being run on a computer, a unique TCP _____ is assigned to it.

▶ Select the correct option

☐

Sequence number

☒

Port number

☐

Ack number

☐

Serial number

Ethernet was originally created in the _____.

Select the correct option



1990s



1980s



1960s



1970s



Frame Check Sequence (FCS) is a

Select the correct option

☐	Error Recovery Process
☐	Error Detecting Code ✓
☐	Communication Protocol
☐	Topology

DEC stands for _____.

Select the correct option



Digital Equipment Corporation



Data Equipment Corporation



Direct Equipment Corporation



Dual Equipment Corporation

In Ethernet network, a _____ is the result of two devices on the same Ethernet network attempting to transmit data at exactly the same time.

Select the correct option

 Reload Math Equ

☐	Collision ✓
☐	Medium
☐	Virus
☐	Spam


Activate Wir

DHCP stands for

Select the correct option



Dynamic Host Configuration Protocol



Data Host Complex Protocol



Duplex Host Control Protocol



Dual Host Control Protocol

The Ethernet _____ contains source and destination Ethernet address fields.

Select the correct option

☒	header
☐	packet
☐	segment
☐	trailer

_____ can be sent over Ethernet.

Select the correct option

☐	segment
☐	IP packet
☒	frame
☐	datagram

Ethernet places _____ between a header and trailer.

Select the correct option



source address



frame check sequence



IP packet



destination address



The Ethernet trailer contains a _____field to determine whether errors occurred during transmission.

Select the correct option

☐	fragment offset
☐	time to live
☒	frame check sequence
☐	flags

IBM stands for -----

Select the correct option



International Balanced Mode



Internal Business Machine



International Business Mode



International Business Machine

In Carrier Sense Multiple Access (CSMA), the possibility of collision still exist because of _____.

Select the correct option

☒	Sense delay	X
☐	Propagation delay	
☐	Network delay	
☐	Transmit delay	✓

The transmission of a file or data from one computer to another over a network is called _____.

Select the correct option

☐	Accessing
☒	Downloading
☐	Streaming
☐	Uploading

In transport layer, _____ provides unreliable delivery of data.

Select the correct option



SMTP



TCP



HTTP



UDP

TIA stands for

Select the correct option



Television Industry Association



Traffic Industry Association



Telephone Industry Association



Telecommunications Industry Association

The _____ process checks the incoming frame's FCS. If there are errors, discard it.

Select the correct option

☒	De-capsulation
☐	Filtering
☐	Encapsulation
☐	Fragmentation

For routing to work well, the router needs to know how to reach the various IP networks and subnets in the internetwork. This info is contained in a _____

Select the correct option

 Reload Math Equat



routing table



frame header



segment



frame trailer

Activate Win

A _____ makes a decision about where to forward the packet next by looking at the destination IP address of the IP packet.

Select the correct option

 Reload

☐

bridge

☐

repeater

☒

router

☐

hub

Act

_____is an example of routing protocol.

Select the correct option

☐	Ethernet	
☐	RIP	✓
☒	FCS	X
☐	CRC	

_____ is used to find MAC address from IP address.

Select the correct option

☐	User Datagram Protocol
☐	Transmission Control Protocol
☐	Internet Protocol
☒	Address Resolution Protocol

The Ethernet address consists of _____ bytes.

Select the correct option



4



8



2



6

Fast Ethernet is also called as _____.

Select the correct option



1000BaseT



100BaseT



500BaseT



10BaseT

A _____ consists of specialized hardware and software that forwards the network traffic back and forth between the various network devices on the network.

Select the correct option

 Reload Math Equations

☐

Protocol

☐

Host

☐

Medium

☐

Switch

Activate Windows

Click to Save Answer & Move to Next Question

-----determines best paths from senders to receivers, through the network of routers.

Select the correct option

☒	Routing
☐	Forwarding
☐	Compression
☐	Encryption

Whether or not an internetwork uses subnetting, the _____ remains the same.

Select the correct option

☐	source address	
☐	message	
☐	basic routing logic	✓
☒	destination address	x

If a sender sends a packet to someone who's on the same subnet, he can send it directly to the destination without involving -----

Select the correct option

☐

protocol

☐

medium

☐

IP address

☒

default router

When a receiver receives the frame, it does the _____ and extracts the IP packet.

Select the correct option



usual error check



encapsulation



fragmentation



routing



For routing purpose, a router uses _____ and finds an entry for it in its IP routing table.

Select the correct option

☐	source address
☐	CRC
☐	destination address
☒	FCS

150.11.30 is a _____ IP address.

Select the correct option



Class C



Class A

X



Class D



Class B

✓

IP datagrams can be divided into two or more smaller IP datagrams that are referred to as a _____.

Select the correct option

☐	Division
☐	Splitting
☐	Fragment
☐	MTU

The IP header has _____ fields.

Select the correct option



Five



Four



Three



Two

_____ is a function of router which moves a packet from router's input to appropriate router output.

Select the correct option

☒	Routing
☐	Locating
☐	Addressing
☐	Forwarding

Post Office Protocol Version 3 (POP3) and is defined in _____.

Select the correct option

☒	RFC 1939
☐	RFC 791
☐	RFC 2822
☐	RFC 2821

----- transfer packet from input buffer to appropriate output buffer.

Select the correct option

☐	Protocol data unit
☐	Preamble
☒	Switching fabrics
☐	Packet queues

Rate at which packets can be transferred from inputs to outputs is called _____.

Select the correct option



switching rate



packet rate



fabric rate



frame rate

Packet queues can form at_____.

Select the correct option



input buffer only



output port only



both input and output ports



input port only

----- perform physical and data link layer functions of an incoming physical link at a router.

Select the correct option

☐	Input ports	✓
☒	Packet queues	X
☐	Vertices	
☐	Switching fabrics	

Input ports determine output port to which an arriving packet will be forwarded via the_____.

Select the correct option

☐	fragmented segment
☒	switching fabric
☐	encapsulated PDU
☐	packet queues

Mostly, the LAN technology employs less expensive _____ cabling.

Select the correct option

☐

TCP

☐

STP

☒

UTP

☐

Coaxial

TCP is described in _____.

Select the correct option

☒	RFC 791
☐	RFC 794
☐	RFC 793
☐	RFC 795

In TCP header, _____ tells the receiving computer which application program needs to be given the data.

Select the correct option

☐	Data Port
☒	Destination port
☐	Source port
☐	External Port

All IP addresses on the same physical network have a _____ portion of their IP addresses works like a postal code.

Select the correct option

Rel

☐	Common ✓
☐	Alternate
☐	Unique
☐	Different

For each interface in a router, IP Address and Subnet mask is used to figure out the _____ in each subnet.

Select the correct option

☐	Lost packets
☐	Packets errors
☐	Fragmented frames
☐	Range of valid IP addresses ✓

Routers always _____ routes for directly connected subnets and networks, as long as the interface is both configured and working.

Select the correct option

 Reload

☒	add ✓
☐	harden
☐	loss
☐	remove

Ac

Each interface of a router uses_____.

Select the correct option

☐	FCS
☒	IP address
☐	Framing offset
☐	Fragmentation

The router can add a _____ to the subnet in its routing table.

Select the correct option

☐

segment

☐

mask

☒

route

☐

frame

After a router's interfaces are_____, it knows about subnets, the subnet numbers, and the outgoing interface it should use to forward packets to them.

Select the correct option

 Reload Math Equations

☐

encrypted

☐

encapsulated

☐

down

☒

up



Activate Windows
Go to Settings to activate Windows

The maximum amount of application-layer data that TCP can grab and place in a segment is called _____

Select the correct option

☐	Maximum Buffer Size
☐	Maximum Data Size
☐	Maximum Port Size
☒	Maximum Segment Size

To achieve reliable transport in TCP, _____ is used to check the safe and sound arrival of data.

Select the correct option

☒	Acknowledgment
☐	Buffer
☐	Packet
☐	Segment

When an NIC receives a frame, it uses the _____ to decide whether to process it or ignore it.

Select the correct option

☐	Destination address	✓
☐	Network address	
☒	IP address	X
☐	Source address	

Which of the following is the correct size of Host bits in Class C of IP address?

Select the correct option



24



12



8



16

If all the routers participate, all routers should have routes for _____ subnets or networks.

Select the correct option



only class A



only directly connected



all



only class B

The receiving router puts that interface into the route in which it received the_____.

Select the correct option

☐	fragmented frame
☐	MAC address
☐	subnet mask
☒	routing update

Routing Protocols define _____by which routers can exchange route information with other routers.

Select the correct option

☐	encryption techniques
☒	messages
☐	frame check sequences
☐	parity bits

The most typical way a router learns all the rest of the routes in an internetwork, beyond just its directly connected routes, is by using a _____.

Select the correct option

 Reload Math Equo



routing protocol



subnet mask



default route



routing graph

Activate Win

A router generates a routing protocol message that contains information about _____ and send it to another router.

Select the correct option

Rel

☐	IP networks only
☐	MAC addresses only
☒	IP networks and subnets
☐	subnets only

DHCP is a _____ protocol.

Select the correct option

☐	Routing
☒	Client-server
☐	Routed
☐	Multicasting

IP datagrams called _____.

Select the correct option

☐	POP
☐	TCP
☐	ICMP ✓
☐	UDP

_____ enabled router hides the details of the home network from the outside world.

Select the correct option

☐	RIP
☒	NAT
☐	DNS
☐	FTP

By looking at the _____, the router can pick the best route.

Select the correct option



metrics



prefix



suffix

Routing protocols define a number called a _____ that's associated with each route in a routing update. That number represents how good or how bad that route is.

Select the correct option

 Reload Math Equations



mask number



metric



next hop



hop number

Activate Windows

When a router receives _____ routing update(s), it might learn of multiple ways to reach a subnet.

Select the correct option

☐	no dynamic
☐	a single static
☒	multiple
☐	a single dynamic

Routing protocols help routers to _____ to a destination when there is more than one way to get there.

Select the correct option

☐

select the first route

☒

learn the best routes

☐

select the static route

☐

select the longest route

The committee created by the IEEE to define the common LAN features and was known as the _____ committee.

Select the correct option



802.5



802.3



802.2



802.4

RIP is a _____ protocol.

Select the correct option

☐	exterior ✓
☒	proprietary ✗
☐	private
☐	public

Which of the following is an exterior routing protocol?

Select the correct option

☐	IGRP
☒	BGP
☐	OSPF
☐	RIP

BGP stands for _____.

Select the correct option



Border Gateway Protocol



Border Gate Process



Borderless Gate Process



Broad Gateway Process

In networking RIP stands for _____.

Select the correct option

☐	Router Intersection Protocol
☐	Reset Interior Protocol
☒	Routing Information Protocol
☐	Reverse Information Protocol

Which of the following is a proprietary routing protocol?

Select the correct option



RIP



EIGRP



OSPF



BGP

The most typical way a router learns all the rest of the routes in an internetwork, beyond just its directly connected routes, is by using a _____.

Select the correct option

 Reload Map



default route



routing graph



subnet mask



routing protocol

Activat
Full Screen

IP address is _____ friendly.

Select the correct option

☐	hub
☐	fiber
☐	repeater
☒	router

DNS stands for _____.

Select the correct option

☐	Direct Name System
☐	Dual Name Source
☒	Domain Name System
☐	Duplicate Name System

google.com is an example of _____.

Select the correct option



port address



domain name



IP address



MAC address

_____ is the address that people type into a web browser address bar to find a website.

Select the correct option

☐	Checksum
☐	Protocol
☐	Subnet mask
☒	Domain name

In order to connect a computer with a switch, _____ cable is used.

Select the correct option



Closed



Cross over



Bent



Straight through

The collection of individual webpages is called as _____.

Select the correct option

☒	Website
☐	Web client
☐	Word processor
☐	Web browser

TLD stands for _____.

Select the correct option



Testing-level Domain



Topic-level Domain



Top-level Domain



Target-level Domain

In the Internet there are ____ root servers.

Select the correct option



13



6



8



3

Once (any) name server learns mapping, it _____mapping.

Select the correct option

☐	removes
☒	caches
☐	hardens
☐	encapsulates

The DNS is _____layer system.

Select the correct option

☐	network
☐	data link
☐	application ✓
☐	transport

When host makes DNS query, query is sent to its local_____.

Select the correct option

☐	ARP client
☐	DNS server
☐	FTP client
☐	SMTP server



The first 8 bytes in an Ethernet header are called the _____.

Select the correct option

☐	FCS
☒	Preamble
☐	Data
☐	SD

_____ is a transport layer protocol.

Select the correct option

☐	SMTP
☐	HTTP
☐	TCP
☒	IP

A _____ DNS server which performs domain name lookup is usually located on the network to which your computer is attached.

Select the correct option

 Reload Ma

☐

complex

☒

top-level

☐

local

☐

public

Activat
Go to Se

In most cases a _____ request is sent, to ask for the IP address associated with a domain name.

Select the correct option

☒	DNS
☐	FTP
☐	ARP
☐	SMTP

Once the DNS server returns the _____ of the requested domain to the browser, the query is resolved.

Select the correct option

☐	website
☐	URL
☒	IP address
☐	bandwidth

To access a DNS server you will need the _____ of the DNS server.

Select the correct option

☒	IP address
☐	number of ports
☐	storage capacity
☐	CRC size

_____ defines how to figure out names and IP addresses for the entire Internet, as well as inside a single site at a single company.

Select the correct option



DNS



CRC



FCS



SMTP

Click to Save Answer & Move to Next Question

Host generates a UDP packet with destination port_____.

Select the correct option

☐	21
☒	80
☐	57
☐	67

_____ is the network layer protocol of TCP/IP model.

Select the correct option

☐	TCP
☐	HTTP
☐	IP
☒	UDP

The domain name service is a _____.

Select the correct option



directory service



internet providing service



email service



mobile phone service

DNS is a distributed database implemented in a hierarchy of many

Select the correct option

☒	DNS servers
☐	web browsers
☐	routing tables
☐	web pages

TTL stands for_____.

Select the correct option

☒	Time To Live
☐	Target To Live
☐	Task To Live
☐	Test To Live

A registrar accredited by _____ verifies the uniqueness of the domain name, enters it into the database and collects a small fee for its services.

▶ Select the correct option

 Reload Math Equa

☐	IETF
☒	ICANN
☐	IEEE
☐	ARPA

Activate Windows

Go to Settings to activate Windows.

The DNS distributed database is stored on servers in the form of_____.

Select the correct option

☐	protocols
☐	routing tables
☐	forwarding tables
☒	resource records

The Electromagnetic Interference (EMI)_____.

Select the correct option

☐	None of the Given
☐	Degrades the signal strength
☐	Creates no problem at all
☐	Enhances the signal strength

DHCP is a _____ protocol.

Select the correct option



Client-server



Routed



Multicasting



Routing

_____ defines standards for WANs.

Select the correct option

☐	ITU
☒	TCP/IP
☐	IETF
☐	IEEE

A _____ is a bunch of overhead bits added to the user data so that a protocol can do its job.

Select the correct option

☐	Payload	
☐	Protocol	
☐	Header	✓
☒	Buffer	✗

A _____ is a networking device typically used to interconnect LANs to form a WAN and as such is referred to as a WAN device.

Select the correct option

☐

amplifier

☒

router

☐

hub

☐

repeater

A "good" path is one that has the -----.

Select the correct option

☐	High cost
☐	Least cost ✓
☐	Congestion
☐	Low error

In _____ routing algorithm, each node sends a copy of its distance vector to each of its neighbors.

Select the correct option



Link state



Distance vector



Static



Absolute

_____ have the right-of-way, which is the legal right to dig up roads and put cabling in the ground.

Select the correct option

☐	All companies
☒	Telcos
☐	All customers
☐	Cloud customers

To connect two routers located let's say at Atlanta and Cincinnati (450 miles), a telephone company should offer a service between two routers that acts like a cable with _____wire(s).

Select the correct option

 Reload Math Equations



four



two



one



three

Activate Windows

Telco means

Select the correct option



telemart costing



television corporation



telegraph consignment



telephone company

----- have already run cables between almost every town and city.

Select the correct option



FTP clients



Cloud consumers



SMTP clients



Telephone companies

Switches in the central offices are called _____ switches.

Select the correct option

☐	LAN
☐	WPAN
☐	PAN
☒	WAN

Link State routing algorithm uses _____.

Select the correct option

☐

Hop count

☐

Global information

☐

Local information

☐

Next hop

_____ is a function of router which moves a packet from router's input to appropriate router output.

Select the correct option

 Reload Mat



Forwarding



Addressing



Locating



Routing

Activate

Go to Set

_____ standard defines the type of header that should be added to the frame, including the field in which the VLAN can be numbered.

Select the correct option

 Reload



802.1Q



802.2



STP



ISL

_____ does not support error recovery, congestion control, and flow control.

Select the correct option

☐	TCP
☒	UDP
☐	SMTP
☐	HTTP

FTP client uses the _____ command to provide the username to the FTP server.

Select the correct option

☐	FTP HOST
☒	FTP USER
☐	FTP SERVER
☐	FTP PASS

The _____ of a serial interface controls the speed.

Select the correct option

☐	ARP/DNS
☐	CRC/FCS
☐	CRC/Checksum
☐	CSU/DSU 

CSU stands for _____.

Select the correct option



Circuit Start Unicast



Circuit Start Unit



Channel Service Unit



Channel Signal Unicast

The CSU/DSU functions can be done with _____.

Select the correct option

☐

a parity bit

☐

a protocol data unit

☒

an external device

☐

a subnet mask

A telco offers a service called T1 line or T1 circuit whose speed is_____.

Select the correct option

☐	100 bits
☐	1.5 bytes
☒	1.5 Mbps
☐	1000 Gbps

DSU stands for _____.

Select the correct option

☐	Delta Service Unicast
☐	Digital Signal Unit
☐	Digital Service Unicast
☒	Data Service Unit

Network services that hide the network from the end user are called as _____.

Select the correct option

☐

accidental network services

☐

automatic network services

☐

authentic network services

☐

alternative network services

VLAN stands for _____.

Select the correct option



Virtual Loop



Virtual LAN



Visual Loop



Visual LAN

The meaning of Straight-through Cable is

Select the correct option



Four wire pairs connect to the same pin on each end



Four wire pairs not twisted with each other



The cable Which Directly connects Computer to Computer



The cable which is not twisted

HDLC stands for _____.

Select the correct option

☒	High-level Data Link Control
☐	Host-level Data Link Control
☐	High-loss Digital Line Cost
☐	Host-link Data Line Cost

PPP stands for _____.

Select the correct option

☒	Point-to-Point Protocol
☐	Peer-to-Process Protocol
☐	Port-to-Process Protocol
☐	Point-to-Process Protocol

HDLC was defined by the _____ in the 1970s.

Select the correct option



DNS



ARP



FCS



ITU

A popular _____ protocol for point-to-point WAN links is HDLC.

Select the correct option

☒	data link layer
☐	application layer
☐	physical layer
☐	network layer

Inside the HDLC and PPP header, there's only one address field, and it is _____long.

Select the correct option



3 bytes



1 byte



4 bytes



2 bytes

Frame Relay is a _____ technology.

Select the correct option

☐	PAN
☒	WAN
☐	WPAN
☐	LAN

Frame Relay is a set of protocol specifications, all matching the functions of OSI _____.

Select the correct option

☐	Layer 6
☐	Layer 1
☐	Layer 7
☒	Layer 2

Frame Relay uses one physical _____ link connected to each site, while allowing each site to send data to each other site.

Select the correct option

☐	PAN
☐	WPAN
☐	LAN
☒	WAN

A Frame Relay network acts like a big _____ switch, with routers connecting to it.

Select the correct option

☒	WAN
☐	WPAN
☐	LAN
☐	PAN

To make Frame Relay work, each router needs a physical cable between itself and a device called a_____.

Select the correct option



Relay Storage hub



Frame storage hub



Parity relay hub



Frame Relay switch

DLCI stands for _____.

Select the correct option

☐	Data Link Control Interconnect
☐	Digital Line Control Identifier
☐	Digital Link Content Identifier
☒	Data Link Connection Identifier

The possible range of DLCIs is _____.

Select the correct option

☐	100-3030
☐	0-100
☒	0-1023
☐	50-100

DLCI is a _____number.

Select the correct option

☐	3-bit
☐	5-bit
☒	10-bit
☐	2-bit

Each Frame Relay switch forwards the frame, based on the _____, through the network, until it gets to the router on the other side.

Select the correct option

 Reload Math Equ

☐	DNS client
☐	Parity bit
☐	ARP request
☒	DLCI

Activate Wi
Go to Settings t

Each Frame Relay header contains a single address field called a_____.

Select the correct option

☐	CRC
☐	FCS
☒	DLCI
☐	ARP

In terms of electrical signals, DC stands for _____.

Select the correct option

☐	Digital Current
☐	Discrete Current
☐	Dual Current
☒	Direct Current

When routers use Frame Relay, and there is a PVC between each pair of routers, the PVCs are in a _____.

Select the correct option

☐	zero mesh
☒	full mesh
☐	half mesh
☐	quarter mesh

A VC is like a_____.

Select the correct option



data unit



routing table



digital signal



leased circuit

In VC exactly _____ devices can send and receive data.

Select the correct option

☐	three
☐	five
☒	two
☐	four

VC stands for _____.

Select the correct option

☐	Vertical Circuit
☐	Variable Control
☐	Variable Channel
☒	Virtual Circuit

PVC stands for _____.

Select the correct option



Private Virtual Controls



Permanent Vertical Controls



Permanent Virtual Circuits



Public Variable Circuits

TCP groups a number of bytes together into a packet called _____.

Select the correct option

☒	Segment
☐	Stack
☐	Packet
☐	Buffer

Frame Relay is considered to be _____ than using leased lines for a WAN.

Select the correct option



worse



expensive



slower



cheaper

Frame Relay is considered to be _____ than using leased lines.

Select the correct option

☐	worse
☒	faster
☐	slower
☐	expensive

In a Frame Relay network for the three sites. _____ from each router is needed to the telco.

Select the correct option



Six cables



One cable



Ten cables



Three cables

For each point-to-point line, router will need a separate physical serial interface and a separate_____.

Select the correct option



CSU/DSU



DNS server



ARP client



SMTP server

Frame Relay header holds the DLCI field that identifies the_____.

Select the correct option

☐	FCS
☐	CRC
☒	PVC
☐	ITU

Frame Relay trailer has a _____field.

Select the correct option

☒	FCS
☐	Hub
☐	Data
☐	DLCI

When router receives the Ethernet frame, it checks to see if errors occurred. If no error, then the router performs _____

Select the correct option



Cloud customization



DNS registration



Frame Relay encapsulation



Cloud optimization

To connect to a website's server and display its web pages, a user must have a _____ installed.

Select the correct option



Spreadsheet



FTP client



ARP client



web browser

The message used to announce the IP address and DLCI is called an _____.

Select the correct option



Inverse SMTP message



Inverse DNS message



Inverse FTP message



Inverse ARP message

Networking model created by IBM is _____.

Select the correct option



TCP



DECnet



DEC



SNA

Leased line is a type of _____.

Select the correct option

☒	WAN
☐	WPAN
☐	PAN
☐	LAN

_____creates an IP network over which IP packets can be forwarded.

Select the correct option

☐	FTP
☐	DNS
☐	ARP
☒	ISP

A company _____ between two far-away buildings for legal and practical reasons.

Select the correct option



can run only two cables



can run only single cable



can run many cables



cannot run a cable

Modems encode a binary 0 or 1 onto the analog signal by varying frequency or amplitude. Changing these characteristics of the analog signal is referred to as

Select the correct option

 Reload Math Equations



routing



modulation



multiplexing



fragmentation

Activate Windows

On the receiving side, the phone converts the electrical signal back to sound waves using a _____.

Select the correct option



monitor



keyboard



scanner



speaker

A telephone includes a _____, which converts sound waves into an analog electrical signal.

Select the correct option



monitor



microphone



printer



keyboard

_____ refers to how strong the signal is.

Select the correct option



Phase



Amplitude



Noise



Frequency

_____ refers to the number of times a signal repeats itself, from peak to peak, in one second.

Select the correct option

☒	Frequency
☐	Voltage
☐	Amplitude
☐	Phase

Point-to-point WANs tend to require _____ as compare to the equivalent network built with Frame Relay.

Select the correct option

☐	no hardware
☐	less hardware
☐	equal hardware
☒	more hardware