

CS201 1800+ MID TERM MCQS

SEARCHING FILE FOR GRAND QUIZ

CREATED BY ORANGE MONKEY TEAM

1ST FILE 95% CORRECT

The ASCII code of null character is -----

000

Which step is not performed during a proper program design?

Write details about the performed of program

How many elements are stored stored in the following? In matrix

[4][5]

20

Which of the following is not a valid variable name in

c++?

@student name

If an array has 50 elements what is allowable range of

subscripts

0-49

Compiler is a

System

software

If Num is an integer variable then Num++

means,

Add 1 with Num

For one byte there are ___ combinations of values that can be stored in computer

2^8

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

ctype.h

Default case in switch

statement is,

Optional

When break statement is encountered in switch

statement, it

Exits from switch statement

What will be the result of arithmetic expression

6+27/3*3?

33

What is the correct syntax to declare an array of size 10 of int data type?

`int name[10] ;`

How many dimensions does n-dimensional array

has?

n dimensions

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

`ptr[3]`

Which of the following values C++ use to represent true and false?

1 and 0

Declaring structures does not mean that memory is allocated.

True

For which array, the size of the array should be one more than the number of elements in an array?

Char

If a variable is passed by value to a function and the function makes some changes to that variable then it

Does not affect the original
variable

In C/C++ the #include is called,

Preprocessor Directive

Loops are----- Structure.

Repetition

In C/C++ the string constant is
enclosed

In double quotes

Switch statement deals
with,

Integer and character
data

A record is a group of related_____.

Fields

C++ views each file as a sequential stream of_____.

Bytes

To access the element of two dimensional array
we use,

Double referencin

If it is required to copy an array to another array

then,

Both arrays must be of the same size and data type

The precedence of * is higher than dot operator

False

Pointers works by pointing to a data type, which can be of the form,

All of the given options

Which of the following data type(s) can operate on modulus operator '%'?

Int

What will be the output of following

code? int x = 10 ;

cout<< "x =" << x

;

x=10

Which looping process checks the test condition at the end of the loop?

do while

What will be the correct syntax of the following statement?

nt *constptr ;

A function must always return
value.

False

C is a/an

_____ languagu

ae

function oriented

Assignment operator is used for _____.

assigning value to variables

When the logical operator AND (&&) combine two expressions exp1
and exp2 then the result will be true only,

When both exp1 and exp2 are true

Which of the following function(s) is/are included in ctype.h

header file?

All of the above

To access the data members of structure _____ is

used.

dot operator (.)

The address operator (&) can be used

with,

Variable

Both compiler and interpreter are used to translate program into machine language code.

True

Missing semicolon ';' at the end of C++

statement is

Syntax error

Switch statement is an alternative of

Multiple if

Array is passed by value to a function by default.

False

Which of the following is the correct function call having array named student of 10 elements as a parameter.

Add Record (student [])

What will be the result of expression $x\% = 2$, if x

= 7?

$x = 1$

What will be the output of following code

segment? `main(){`

`int x = 5 ;`

```
{
```

```
int x =
```

```
4 ;
```

```
cout<x
```

Remember own prayer

```
}
```

```
Cout<x;
```

```
}
```

4, 5

Which of the following operator is used to access the value of variable pointed to by a pointer?

For loop

The object _____ may be used both for file input and file

fstream

What's wrong with this for

loop? for (int k = 2, k <=12,

k++)

The commas should be

semicolons

```
Union intorDouble{
```

```
Intival;
```

```
Double charvar;
```

```
};
```

```
main()
```

```
{
```

```
intorDouble
```

```
VAZ; int size ;
```

```
size = sizeof(VAZ); }
```

What will be the value of variable "size", if int occupies 4 bytes and

double occupies 8 bytes?

C language is

developed by

Dennis Ritchie

Which of the following choice is not an example of an int datatype?

-4.0

In flow chart, the symbol used for decision making is,

Diamond

Switch statement deals with,

Integer and character data

***doc is _____ by**

Sequential File

Member function tellg() returns the current location of the pointer.

get()

Dealing with structures and functions passing by reference is the most economical method

True

In C/C++ all character strings are terminated with,

Zero

Word processor

is

Application

software

Which of the following cannot be a variable name?

10area

Which looping process is best, when the number of iterations is known?

For

By default an array of characters is passed by value to a function.

False

Which of the following operator is used to access the address of a variable?

& operator

The name of an array represents address of first location of array element.

True

Data Size of the file is always _____ the actual size of the

None of the above

When an identifier is declared with keyword

const then,

Its value can not be changed

In C/C++ if we define an array of size eight (8) i.e. intArr [8]; then the last element of this array will be stored at,

Arr[7]

If it is required to copy an array to another array

then,

Both arrays must be of the same size and data type

In C/C++ all character strings are terminated

with,

Null character

When a pointer is incremented, it actually jumps the number of memory addresses

According to data type

Do-while loop executes at

least

One Time

`+= , *= , /= , etc` are called

**Compound assignment
operator**

**Computer can understand only machine language
code.**

True

**The compilers and interpreters also belong to the System Software
category.**

True

**Editors are used to compile the
code.**

False

**The variables having a name, type and size are just like empty
boxes.**

True

What will be the result of the statement `rand ( )`

`% 50`

Less than 50.

**if `(a>b && a>c)` then the condition will be true
only if**

Both `a>b` and `a>c` are true

**In while loop the loop counter must be
initialized, Before entering the loop**

of a variable means the locations within a program from where it can be accessed.

Reference

Switch support

Character

Remember own prayer

A function is a block of statements that can be defined once and used _____ in the program.

As many times as user wants

statement is used to terminate the processing of a particular case and exit from switch structure.

break

The most suitable data type for number 325.25 is ____.

float

X is an integer variable; what does X++

means, Add 1 in X value

The operators ++ and -- are used to increment or decrement the value of a variable by

1

Which of the following loops checks the test condition at the end of

the loop? Do-While

What is the output of the following statement?

int i = 2.5; do { cout << i * 2; } while (i > 3 && i <

10); Error

What does !(7) evaluate to in decimal where ! is a NOT operator? 7

The condition in while loop may contain logical expression but not relational expression.

False

Searching is easier when an array is already sorted True

If an array has 100 elements, what is allowable range of subscripts?

0 – 99

What will be the value of 'a' and 'b' after executing the following statements?

a = 3;
b=a+4,

3

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

intarr[2][3] = {{0},{0}} ;

Which of the following function returns the size of a string variable?

strlen()

What will be the range of numbers generated by function rand () % 9?

0 to 8

Computer can understand only machine language code. True

What does $5 \wedge 6$, evaluate to in decimal where '^' is Exclusive OR operator?

False

If the file is not properly closed in the program, the program_____.

Crashes

Which of the following header file include string conversion functions? `stdlib.h`

The function of cin is

To read data from keyboard

In C/C++ language the header file which is used to perform useful task and manipulation of character data is `ctype.h`

How many parameter(s) function `getline()` takes?
3

Word processor
is
Application
software

For which values of the integer `_value` will the following code becomes an infinite loop?

```
int  
number=1;  
while (true) {  
    cout<<  
    number;  
    if (number == 3) break;  
    number  
    +=integer_value; }
```

only 0

Each pass through a loop is called
a/an

Iteration

A continue statement causes execution to
skip to
the next iteration of the loop

What is the correct syntax to declare an array of size 10 of int data type?

```
Int name[10] ;
```

Consider the following code segment. What will the following code segment display?

```
int main(){  
int age[10] =  
{0}; cout<<  
age ;  
}
```

Value of first element of array

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

```
intarr[2][3] = {0,0} ;
```

How many bytes will the pointer intPtr of type int move in the following statement?

```
intPtr += 3 ;  
12 bytes
```

If there are $2(n+1)$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

$(n+1)$ elements

Which of the following operator is used to access the value of variable pointed to by a pointer?

Operator

The _____ statement interrupts the flow of
Break

Analysis is the -----step in designing a program
First

Paying attention to detail in designing a program is
Necessary

Application Software's are

used to

Solve end user problems

Computer can do,

Exactly what we tell it

We can control our program while it is running by

using

Debugger

are part of system software

Linker and loaders

The remainder (%) operator is,

An arithmetic operator

int x = 2 * 3 + 4 * 5; What value will x contain in the sample code above?

26

What is the correct value to return to the operating system upon the successful completion of a program?

0

What is the only function all C++ programs must contain?

main()

What punctuation is used to signal the beginning and end of code blocks?

{ }

What punctuation ends most lines of C++ code?

(Semi-colon)

Which of the following is a correct comment?

/* Comment */

Which of the following is not a correct variable type?

Real

Which of the following is the correct operator to compare two variables?

==

Identify the correct statement

All lines beginning with two slash signs are considered comments.

There is a unique function in C++ program by where all C++ programs start their

Main ()

Every statement in C++ program should end with

A Semicolon (;)

A variable is/are

Those numbers that is frequently required in programs

The value of $2*15/3*7+3*2$ is

Remember own prayer

The size of a double
variable is

8 bytes

Which of the following are NOT relational operators?

==

Which of the following cannot be used as
identifiers?

Spaces

Result of " number = number / 10; " will be equal to The " number =
number % 10;"

FALSE

intx,y =10; cout<< x <<endl; The value of the x will be in the above
code

Unknown Value

In flow chart process is
represented by

Rectangle

Which of the following is the boolean operator for
logical-and?

&&

Evaluate! (1 &&! (0 ||
1)).

TRUE

Which one of the following operators is a unary operator?

Logical NOT (!)

Which of the following shows the correct syntax for an if statement?

if (expression)

In if structure the block of statements is executed only,

When the condition is true

Remember own prayer

Loader transfers the executable code from main memory to hard disk.

FALSE

What is the final value of x when the code `int x; for(x=0; x < 10; x++) {}` is run?

10

When does the code block following `while(x < 100)` execute?

When x is greater than one hundred

Which is not a loop structure?

Repeat Until

`for (int n=10; n >0; n++) { cout<< n << ", "; }` How many Time Loop will run

Infinite Time

When break statement is encountered in switch statement, it

Exits from switch statement

A for loop usually consist of

2

How many times is a do while loop guaranteed to loop?

1

41- $x = x + 4$; Is Equal

to

x += 4;

The first expression in a for loop

is

**The first value of our counter
variable**

What is the break statement

used for?

To quit the current iteration

Remember own prayer

What is the continue statement used for?

To stop the current iteration and begin the next iteration from the beginning

What is the output of the following code? for (int a = 1; a <= 1; a++) cout<<

a+

+

;

1

2

Every case statement is follows by?

:

What is required to avoid falling through from one case to the

next?

Break;

What keyword covers unhandled possibilities in switch

case?

Default

What is the result of the following code? x=0; switch(x) { case 1: cout<<

"One"; case

Hello World

Which of the following is

true?

1

Every function in C++ are
followed by

Parenthesis

Which is not a proper
prototype?

`doublefunc(char x)`

What is the return type of the function with prototype: " `intfunc(char
x, float v, double
t);`"

`int`

Which of the following is a valid function call (assuming the function
exists)?

`func();`

Which of the following is a complete
function?

`intfunc(int x) {return x=x+1;}`

Function prototypes are
useful

All of the above

A function that calls itself is
known as

Recursive function

A preprocessor directive is identified by

#

When a call to function statement is encountered,

The control is transfer to its Prototype

The directives for the preprocessors begin with

Two Slashes (//)

The file iostream includes

The declarations of the basic standard input-output library

Which of the following is false?

None of above

Which of the following statement is true about preprocessor directives?

They end with a semicolon

If the statements `int j,k; j = 123; k= 234; int* q, * r; r = &j; q=&k; cout<< *q<< ' ' << *r;` are executed, what will be displayed?

132, 234

If the statements `int j,k; j = 123; k= 234; int* q, * r; cout<< *q<< ' ' << *r;` are executed,

What will be displayed?

Garbage values

Which of the following correctly declares an array?

`intanarray[10];`

Which of the following correctly accesses the seventh element stored in `foo`, an array with 100 elements?

`foo[6];`

Which of the following gives the memory address of the first element in array `foo`, an array with 100 elements?

`Foo;`

Consider the following statement: `int age [ ] = { 0, 2, 1, 3, 4, 5, 6, 7, 8, 9 };`

Array Length is

10

`c [ 3 ] = 33;` by this Code we are assigning the value to

4th element

`for (i = 0; i < 10 ; i ++ ) { b[i] = a[i]; }` by given loop we are

Copying the two arrays

`int z, i ; int a [ 100 ] ; z=5; for ( i=0 ; i < 100 ; i ++ ) { a [ i ] = i ; } for ( i = 0 ; i < 100 ; i ++ ) { if ( z == a [ i ] ) { found = 1 ; break ; } }` Loop will be executed for _____

6 Times

Given that `#define sum(a,b) a+b` what is the value of:

`sum(3+1,2);`

6

`int m=0,v=0; for(m=5;m < 8;m++){ v=v+(m++)+(++m); } cout<< v <<endl;`
output of the V will be ?

11

Because of variable scope

Variables created in a function cannot be used another function

When we are using `const` keyword with a variable x then initializing it at the time of declaration is

Must

`void allocateme(int* p){ p = new int; *p = 2; } int main(){ int i = 1; allocateme(&i); std::cout<< i; return 0; }` What is displayed?

Outputs '1'

`int numarray[4][4] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12};` What value does `numarray [0][3]` in the sample code above contain?

4

If the statements `<br>int j,k;<br>j = 123;<br>k= 234;<br>int* q, *r;<br>cout<< *q << ' ' << * r ;<br>`are executed, what will be displayed?

garbage values

Which one of the following will declare a pointer to an integer at address `0x22ff74` in memory?

`int *x; *x =`

`0x22ff74;` An array

is also called

Constant pointer

Which of the following is the proper declaration of a pointer?

Remember own prayer

`int *x;`

Which of the following gives the memory address of integer variable a
(inta;)?

`&a;`

Which of the following is the proper Operator to allocate
memory?

New

Which of the following is the proper keyword to deallocate
memory?

Delete

When we are calling function i.e. swap (&x, &y); then it is a
call by

Reference

Which symbol is used to declare a pointer?

*

Which symbol is used to reference a
pointer?

&

In the given code `inty[10]; int *x ; x= y; y is`
giving

Address of the first element of the array

Adding to a pointer that points to an array will

Cause the pointer to point to the next element in the array.

Which one of the following operators is a unary operator?

Complement operator (~)

The statement `i++`; is equivalent to

`i = i + 1;`

A variable which is defined inside a function is called

Remember own prayer

Functional variable

Which of the following is a two-dimensional array?

`intanarray[20][20];`

`inttwoDArray[2][2] = {0,1,2,3,4,5,6};` the 1st row and 3rd element is;

2

An array of pointers is the same as ____.

Pointers to pointers

Pointers may be _____ like any other data

Arrayed (stored in an array)

In C/C++ language when an array is passed to a function then by default its passing Mechanism is,

Call by Reference

`intisdigit( int c )` Returns true if c is a

Digit

`intisupper( int c )` Returns true if c is a

Uppercase letter

`doubleatof( const char *nPtr )` Converts the string

nPtr to

double

The basic steps of file handling are:

Open the file, Read and write, Close the file

```
ofstream outFile; char outputFileName[] = "myFileOut.txt"; char  
outputText[100]
```

```
= "Welcome to VU"; outFile.open(outputFileName); at the end of the code
```

Remember own prayer

file is opened for Writing

If we open a file stream myfile for reading, what will give us the current position of the file pointer?

tellg()

If we open a file stream myfile for reading, what will give us the current position of the file pointer?

tellp()

Which of the following classes handles file

input?

Ifstream

By writing: aFile.seekg (10L, ios::beg) We are asking to move 10 bytes forward from the beginning

By using seekg () function, we can know the actual data length

we will call tellg () to give the current position in _____ number. This number is the actual data bytes inside the file.

Long

We can use inputFile.getc () to get a _____ and outputFile.putc () write

a _____ into a file.

Character,

character

will return the number of bytes reserved for a variable or data type.

sizeof operator

To access the members of a structure, which symbol is used ?

Remember own prayer

A member is a

Variable in a

structure

Which of the following is a properly defined struct?

`structa_struct {int a;};`

Which properly declares a variable of struct

Student?

`struct Student;`

Using structures we can declare:

Simple variables, Pointers and Arrays of structure

During compilation compiler looks for the _____ and process it

Preprocessor directives

When we write a class template the first line must be:

`template< class T >`, Here T can be replaced with any name but it is preferable

What does $5 \mid 6$ evaluate to in decimal?

$5 \mid 6 = 0101 \mid 0110 = 0111 = 7$

What does $5 \& 6$ evaluate to in decimal?

$5 \& 6 = 0101 \& 0110 = 0100 = 4$

What does $5 \wedge 6$ evaluate to in decimal?

$5 \wedge 6 = 01010110 \wedge 0011 = 0011 = 3$

In order to get 256 from the number 2568 we divide this number by 10 and take,

Its quotient

The correct syntax of do-while

loop is,

While (condition); do {statements

};

Which of the following function(s) is/are included in stdlib.h header file?

Remember own prayer

1 and 2 only

If the break statement is missed in switch statement then,

No effect on program

The data type before a function name represents its,

Return Type

What does $5 | 6$, evaluate to in decimal where '|' is bitwise OR operator?

5

What will be the correct syntax for initialization of pointer ptr with string "programming?"

charptr = 'programming' ;

What will be the result of expression $x \% = 2$, if $x = 7$?

$x = 3$

A precise sequence of steps to solve a problem is called

Program

The Compiler of C language is written in

UNIX

Initialization of variable at the time of

definition is,

Good Programming

In if structure the block of statements is

executed only,

When the condition is true

Pointer is a variable which

store,

Memory Address

Preprocessor program perform its function before__phase takes place.

Remember own prayer

Compiling

Which character is inserted at the end of string to indicate the end of string?

Null

How many bytes are occupied by declaring following array of characters? `charstr[] = "programming";`

12

Which of the following header file defines the `rand()` function?

`stdlib.h`

Commenting the code

Makes a program easy to understand for others

What's wrong with this for loop? `for (int k = 2, k <= 12, k++)`

The commas should be semicolons

For which array, the size of the array should be one more than the number of elements in an array?

Char

To Which category of the software "Compiler and Interpreter" belongs?

System Software

In C/C++ the string constant is

enclosed

In double quotes

The size of int data

type is

4 bytes

In Flow chart process is

represented by

Rectangle

If the break statement is missed in switch

statement then,

No effect on program

Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third column?

m[2][3] = 5 ;

How many total elements must be in two-dimensional array of 3 rows and 2 columns?

6

Consider the following code segment. What will be the output of this code segment? intarr[6] = {2, 3, 7, 4, 5, 6} ; int *ptr1 = &arr[1] ;

int *ptr2 =

&arr[4] ; cout<<

(ptr2-ptr1) ;

ptr is a pointer to constint

What will be the correct syntax to assign an array named arr of 5 elements to a pointer ptr?

C is a/an

_____ language

e

function oriented

Syntax of union is identical to

Structure

Most efficient method of dealing with structure variables is to define the structure globally.

False

In order to get 256 from the number 2568 we divide this number by 10 and take,

Its quotient

There are mainly ----- types of software

Two

In C/C++ the #include is called,

Preprocessor Directive

&& is ----- operator

Logical

In flow chart, the symbol used for decision making is,

Diamond

The correct syntax of do-while

loop is,

do { statements; } while

(condition);

C++ views each file as a sequential stream of _____.

Bytes

If the elements of an array are already sorted then the useful search

algorithm is,

Binary search

The address operator (&) can be used

with,

Variable

When a pointer is incremented, it actually jumps the number of memory addresses

,

According to data type

Each pass through a loop is called

a/an

Iteration

Call by reference mechanism should be used in a program when there is

large amount of data to be passed

**ii. small amount of data to be
passed iii. need to change the passed**

data

iv. no need to change the passed data Choose the appropriate option for the above case.

and (iii) only

Which of the following is the starting index of an array in

C++?

0

The return type of a function that do not return any value must be

Void

Which of the following is an extension of header file?

.h

We want to access array in random order which approach is better?

Pointers

When we declare a multidimensional array the compiler store the elements of multidimensional array in the form of,

Pointers

When we declare a multidimensional array the compiler store the elements of multidimensional array in the form of,

Contiguous memory

location

The function of cin is

To read data from keyboard

Care must be taken about the correct _____ of operator

In functions, that returns reference use

overloading. (Choose the most appropriate).

Both Semantic and Complexity

Global or static variables

In overloading the assignment (=) operator, which object(s) will call the operator function?

Right object of the assignment operator

Friend functions are_____.

Unidirectional (not confirm)

We cannot increment_____.

References

A pointer is_____.

The address of a variable

Overloaded assignment operator must

be Non-member function of class (not

**The concept of friend function negates the concept of_____.
(confirm)**

Encapsulation

**If class A is a friend of class B, and class B is
class C to be a friend, _____**

It has to declare, class C as a friend

The difference between pointers and references is that_____.

We can do arithmetic with pointer

A reference cannot be_____.

NULL

An address is a _____, while a pointer is a _____.

Variable, constant

The reference data types are used as _____ variables without operator

Local, &

The syntax of declaration of a function that returns the reference to an

integer is

`int&myfunc() ;`

References cannot be uninitialized. Because it is impossible to

Initialize a NULL pointer

<and> both are

Logical

Find out the logical error in following lines of code. If (x = 10) cout << "x is 10"; 10 should be enclosed in quotations

There is no semicolon at the end of if condition

What will be the result of the expression `j = i++`; if initially `j = 0` and `i = 5`? 5

Default mechanism of calling a function by passing it array is call by _____ and in case of passing variable is call by _____.

Reference, value

When the break statement is encountered in a loop's body, it transfers the _____ from the current loop.

control

Outside

statement is used to terminate the processing of a particular case

and exit from switch structure.

Break

When the if statement consists of more than one statement then enclosing statement in braces is_____.

these

Compulsory

What will be the value of the variable output in the given piece of code?

```
double output = 0; output = (2 + 2) * 4 + 2 / (4 - 2);
```

17

If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout<< statement?

2

will be used for clarity and to force the order of evaluation in an expression. ()

What does STL stand

for? Standard

template library

Skill(s) that is/are needed by programmers_____.

All of the given options

For which array, the size of the array should be one more than the number of elements in an array?

char

new and delete are_____whereas malloc and free are_____.

Operators, functions

Friend functions are____of a class.

Non-member functions

If overloaded plus operator is implemented as non-member function then which of the following statement will be true for the statement given below?

```
obj3 = obj1 + obj2 ;
```

obj2 will be passed as an argument to + operator whereas obj2 will drive the + operator

Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

Class-name operator ++(int) ;

For cin, the source is normally a _____ and destination can be _____.

Keyboard, variable

We can also do conditional compilation with preprocessor

directives. True

The programs, in which we allocate static memory, run essentially on

Stack

The default value of a parameter can be provided inside the

function definition

While calling function, the arguments are assigned to the

parameters from no specific order is followed

When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

N arguments

With user-defined data type variables (Objects), self-assignment can

produce

Logical error

Assignment operator is used to initialize a newly declared object from existing object.

True

When an object of a class is defined inside another class

then, Constructor of inner object will be called first

In the member initializer list, the data members are

initialized, In the order in which they are defined within

class

new operator allocates memory from free store and return_____.

A pointer

"new" and "delete" keywords are_____ in C++ language.

Memory Allocation Function

Return type of a function that does not return any value must be_.

void

Remember own prayer

A function's prototype is written_____the function

Before

What will be the size of the following character array? char name[] = "Adeel"; 5

From following; which one is the correct syntax of an array initialize:

Array size is 10 and it is of double data type to value 0?

doublearr[10] = {0.0};

Which of the function call is call by value for the following function prototype? float add(int);

add(x);

Null character is represented by_____in C++.

\0

What is the output of the following code, if the first case is true switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl; case 'm': cout<<"mango"<<endl; default: cout<<"anyfruit"<<endl; }

apple banana mango

Which of the following function call is "call by reference" for the following function prototype? int add (int)

add(x);

The string in the array is terminated by a

null

Default mechanism of calling a function by passing it array is call by and in case of passing variable is call by

Reference, value

<.<=>.> = are called

operator

s Relational

Why the use "cin"?

To read data from keyboard

!(x<3) means in c++

that X is greater than

3

The data in the memory is

Volatile

Each array declaration must provide the information about all these thing except.

The location of the first element to be stored

What will be the output of the program if

`x=10? If(x!=0&& x<=10)`

`{`

`cout<<"condition 1is true";`

`}`

`{`

`If(x>=10&& x<20)`

`}`

Condition 1 is true condition 2 is true

C is widely known as development language of _____operating

system. Window

A repetition statement specifies that an action is to be continued

while some remains true

Condition



2ND FILE CORRECT

Question # 3

What will be the result of the expression $j = i++$; if initially $j = 0$ and $i = 5$?

0

5

6

4

Question # 4

Default mechanism of calling a function by passing it array is call by _____ and in case of passing variable is call by _____.

Reference, Reference

Reference, value

Value, Reference

Value, Value

Question # 5

When the break statement is encountered in a loop's body, it transfers the control _____ from the current loop.

Inside

Outside

To break statement

To continue statement

Question # 6

_____ statement is used to terminate the processing of a particular case and exit from switch structure.

If

Goto

Break

Continue

Question # 7

If we pass more than one arguments to a function then they are separated by ____ .

Comma, Lecture 9

Semicolon;

Colon:

Brackets ()

Question # 8

What will be the value of the variable output in the given piece of code? `double output = 0; output = (2 + 2) * 4 + 2 / (4 - 2);`

15

17

12

1

Question # 9

If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout statement?

2

2.1

2.06

2.07

Question # 10

_____ will be used for clarity and to force the order of evaluation in an expression.

" "

() PG32

' '

[]

Question # 11

What will be the size of following array? `int arr[29];`

0

30 PAGE 105-106

29

28

Question # 12

If a function has not been declared before its definition, It is
logical error

syntax error LECTURE NO 9

logical Error

run time error

none of these

Question # 13

When the break statement is encountered in a loop's body, it
transfers the control from the current loop.

Inside

Outside By using break the loop will terminate.

To break statement

To continue statement

Question # 14

When we access a multidimensional array, each array index is surrounded by_ .

Single quotes ' '

Double quotes " "

Brackets[] Lecture 11

None of the given

Question # 15

char name [] = "Hello World" ; In the above statement, a memory of ____characters will be allocated

12 Lecture 12

10

11

13

Question # 16

A variable declared within a code block becomes **variable** for that block.

Static

Integer

Local Lecture 9

Global

Question # 17

When the if statement consists of more than one statement then enclosing these statement in braces is _____.

Compulsory

Optional

Not required

Relevant

Question # 18

Characters of a string stored in an array can be accessed directly using array _____.

Manipulation

Superscript

Subscript Page No 123

Postscript

Question # 19

**A variable declared within a code block becomes
for that block.**

variable

Static

Integer

Local Lecture 9

Global

Question # 20

The data type before a function name represents its,

Return Type

Function data

Function arguments

Function name

Question # 21

**From following; which one is the correct syntax of an array
initialize: Array size is 10 and it is of double data type to value
0?**

arr[10] = {0.0};

double arr[10] = 0.0;

Double arr[10] = {0.0}; Lecture 12

double arr[] = 0.0;

Question # 22

In C/C++, by default arguments are passed by to a function.

Value Lecture 9

Reference

Prototype

None of the given

Question # 23


By default, the starting index of an array in C++ is

0 Lecture 11

2

1

-1



3rd file correct

1. We use _____ to open a file or stream for extraction
In
2. Null character is represented by _____ in C++.
/0
3. An object of _____ class can be created for saving the current position of any opened file before reading from the file.
Streampos
4. _____ Returns true if c is a digit or a letter and false otherwise.
int isalnum(int c)
5. We use _____ to open a file or stream for insertion.
Out
6. Base address is the memory address of _____ element of an array.
1st
7. _____ allow us to have a memory location and use it as int or char interchangeably
Union
8. To read command-line arguments, the main() function itself must be given _____ arguments.
2
9. Individual characters in a string stored in an array can be accessed directly using array _____.
Subscript
10. To manipulate n-dimensional array _____ nested loops are required.
n-1

11. A character is stored in the memory in _____.
String

12. What will be the size of following array?
Int arr[29];

13. An object of _____ class can be created for saving the current position of any opened file before reading from the file.
Streampos

14. We use _____ to open a file or stream for extraction.
in

15. We use _____ to open a file or stream for Insertion.
Out

16. _____ are conventional names of the command line parameters of the 'main()' function.
'argc' and 'argv'

17. In _____, we have different data members and all of these have their own memory space.
Structures

18. How we declare an array of integer data whose size is 20 with array name "count".
int count[20];

19. A _____ is an array of characters that can store number of character specified.
String

20. File. seekg (-10L, ios:cur)
backward direction

21. A function is a block of statements that can be defined once and used _____ in the program.

As many times as user wants

22. What will be the output of the following while loop? int counter = 0 ;
while(counter < 15)
cout<< counter << " "; counter

Compile time error

23. We can access a global variable _____

From anywhere in the program

23. A repetition statement specifies that an action is to be continued while some _____ remains true.
Condition

24. Loops are _____ Structure.
Repetition

25. _____ operator is used to pass the address of a variable in call by reference method.
&

26. How many times the following do-while loop will execute? `int k = 10; do { cout << "Statements" << endl; k -= 2; } while(k > 0);`
5

27. What is the output of the following code if the 3rd case is true `switch (var) { case 'a': cout << "apple" << endl; case 'b': cout << "banana" << endl; case 'm': cout << "mango" << endl; Default: cout << "any fruit" << endl; }`
mango any fruit

28. By default, the starting index of an array in C++ is _____.
2
-1

Question No.: 1 (Marks: 1)

Compiler is a

System software

Application Software

Driver

Editor

Question No.: 2 (Marks: 1)

If Num is an integer variable then Num++ means,

Add 1 two times with Num

Add 1 with Num

Add 2 with Num

Subtract 2 from Num

Question No.: 3 (Marks: 1)

For one byte there are _____ combinations of values that can be stored in computer.

2

6

2

7

2

8

2

4

Question No.: 4 (Marks: 1)

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

cplex.h

ctype.h pg 188

stdio.h

delay.h

Question No.: 5 (Marks: 1)

Default case in switch statement is,

Optional

syntax error

Necessary

<http://www.arduino.cc/en/Reference/SwitchCase>

Question No.: 6 (Marks: 1)

When break statement is encountered in switch statement, it

Stops the entire program

Stops the execution of current statement

Exits from switch statement

None of the given options

<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/switch.html>

Question No.: 7 (Marks: 1)

What will be the result of arithmetic expression $6+27/3*3$?

33

45

9

30

Question No.: 8 (Marks: 1)

What is the correct syntax to declare an array of size 10 of int data type?

int [10] name ;

name[10] int ;

int name[10] ;

int name[] ;

Question No.: 9 (Marks: 1)

How many dimensions does n-dimensional array has?

n dimensions

2n dimensions

(n+1) dimensions

(n-1) dimensions (Array starts from 0th element)

Question No.: 10 (Marks: 1)

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

ptr[3]

(ptr+3)

*(ptr+3)

Both 1 and 3

Question No.: 11 (Marks: 1)

Which of the following values C++ use to represent true and false?

1 and 0

1 and -1

11 and 00

Any numerical value

Question No.: 12 (Marks: 1)

Declaring structures does not mean that memory is allocated.

True

False

Question No.: 13 (Marks: 1)

For which array, the size of the array should be one more than the number of elements in an array?

Int

double

float

char Pg113

Question No.: 14 (Marks: 1)

If a variable is passed by value to a function and the function makes some changes to that variable then it

Does not affect the original variable pg 83

affects the original variable

causes syntax error

None of the given options

Question No.: 15 (Marks: 1)

In C/C++ the #include is called,

Header file

Preprocessor Directive pg 269

Statement

Function

Question No.: 16 (Marks: 1)

Loops are ----- Structure.

Decision

Repetition pg 560

Sequential

Hierarchical

Question No: 1 (Marks: 1)

In C/C++ the string constant is enclosed

- ▶ In curly braces
- ▶ In small braces
- ▶ In single quotes
- ▶ **In double quotes**

<http://www.lugaru.com/man/String.Constants.html>

Question No.: 2 (Marks: 1)

For one byte there are _____ combinations of values that can be stored in computer

2

6

2

7

2

8

2

4

Question No: 3 (Marks: 1)

Switch statement deals with,

- ▶ Integer data only
- ▶ float data only
- ▶ character data only
- ▶ **Integer and character data**

<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/switch.html>

Question No: 4 (Marks: 1)

A record is a group of related _____.

- ▶ Files
- ▶ Bytes
- ▶ **Fields**
- ▶ Data

Question No: 5 (Marks: 1)

C++ views each file as a sequential stream of _____.

► **Bytes**

► Bits

► 0's or 1's

► Words

Question No: 6 (Marks: 1)

To access the element of two dimensional array we use,

► Single referencing

► Single dereferencing

► Double dereferencing

► **Double referencing** Pg175

Question No: 7 (Marks: 1)

If it is required to copy an array to another array then,

► **Both arrays must be of the same size and data type** Pg 105

► Both arrays may be of different size

► Both arrays may be of different data type

► Both arrays may be of different size and type

Question No: 8 (Marks: 1)

The precedence of * is higher than dot operator

► True

► **False**

http://docs.realsoftware.com/index.php/Operator_Precedence

Question No: 9 (Marks: 1)

Pointers works by pointing to a data type, which can be of the form,

► Integer only

► double only

► character only

► **All of the given options** Pg 144

Question No: 10 (Marks: 1)

Which of the following data type(s) can operate on modulus operator '%'?

- ▶ float, int
- ▶ float, double
- ▶ **int** Pg 22
- ▶ char

Question No: 11 (Marks: 1)

What will be the output of following code?

```
int x = 10 ;
```

```
cout << "x =" << x ;
```

- ▶ 10
- ▶ "x=10"
- ▶ **x=10**
- ▶ 10=x

Question No: 12 (Marks: 1)

Which looping process checks the test condition at the end of the loop?

- ▶ for
- ▶ while
- ▶ **do while**

Question No: 13 (Marks: 1)

What will be the correct syntax of the following statement?

ptr is a constant pointer to integer.

- ▶ const int *ptr ;
- ▶ const *int ptr ;
- ▶ int const *ptr ;
- ▶ **int *const ptr ;** Pg 154

Question No: 14 (Marks: 1)

A function must always return value.

- ▶ True
- ▶ **False**

(

Question No: 1 (Marks: 1)
Compiler is a

No: 15 (Marks: 1)
C is a/an _____ language

- ▶ low level
- ▶ object based
- ▶ object oriented
- ▶ **function oriented Pg 82**

Question No: 16 (Marks: 1)
Assignment operator is used for _____.

- ▶ calculation
- ▶ reading
- ▶ **assigning value to variables Pg 17**
- ▶ None of the given options.

Q

Question No: 3 (Marks: 1)
Which of the following function(s) is/are included in ctype.h header file?

- ▶ isdigit(int c)
- ▶ isxdigit(int c)
- ▶ tolower(int c)
- ▶ **All of the above Pg 188**

Question No: 4 (Marks: 1)
To access the data members of structure _____ is used.

- ▶ **dot operator (.) Pg 231**
- ▶ * operator
- ▶ operator◇
- ▶ None of given.

Question No: 5 (Marks: 1)
The address operator (&) can be used with,

- ▶ Statement
- ▶ Expression
- ▶ **Variable Pg 149**
- ▶ Constant

Question No: 6 (Marks: 1)

Both compiler and interpreter are used to translate program into machine language code.

▶ **True**

▶ False

<http://readanddigest.com/what-are-the-differences-between-compiler-and-interpreter/>

Question No: 7 (Marks: 1)

Missing semicolon ';' at the end of C++ statement is

▶ Logical error

▶ **Syntax error Pg 16**

▶ Runtime error

▶ None of the given options

Question No: 8 (Marks: 1)

Switch statement is an alternative of _____ statement

▶ **multiple if**

▶ continue

▶ break

▶ goto

Question No: 9 (Marks: 1)

Array is passed by value to a function by default.

▶ True

▶ **False Pg 266**

Question No: 10 (Marks: 1)

Which of the following is the correct function call having array named *student* of 10 elements as a parameter.

▶ **addRecord(student[]) ;**

▶ addRecord(student) ;

▶ addRecord(student[10]) ;

▶ addRecord(*student) ;

Question No: 11 (Marks: 1)

What will be the result of expression $x\%2$, if $x = 7$?

▶ **$x = 1$**

► x = 3

► x = 7

► x = 2

Question No: 12 (Marks: 1)

What will be the output of following code segment?

```
main(){  
int x = 5 ;  
{  
int x = 4 ;  
cout <x  
}  
cout <x  
}
```

► 5, 5

► 4, 4

► 4, 5

► 5, 4

Question No: 13 (Marks: 1)

Which of the following operator is used to access the value of variable pointed to by a pointer?

► * operator

► -> operator

► && operator

► & operator

Question No: 14 (Marks: 1)

The object _____ may be used both for file input and file output

► fstream, Pg 199

► ifstream,

► ofstream,

► none of the given options.

Question No: 15 (Marks: 1)

What's wrong with this for loop?

for (int k = 2, k <=12, k++)

► the increment should always be ++k

► the variable must always be the letter i when using a for loop

► there should be a semicolon at the end of the statement

► the commas should be semicolons

Question No: 16 (Marks: 1)

Let suppose

```
Union intorDouble{  
    Int ival;
```

```
    Double charvar;  
};  
main(){  
    intorDouble VAZ;
```

```
    int size ;  
    size = sizeof(VAZ);  
}
```

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8 bytes?

- ▶ 2
- ▶ 4
- ▶ 8
- ▶ 12

Remember own prayer

Write code which read a string not greater than 20 characters from keyboard stored it in an array Name and display it on the screen.

Question No: 23 (Marks: 5)

Write a C/C++ program which defines an array of 15 elements. This program changes all uppercase letters of an array into lowercase letters and all lowercase letters to uppercase using Character handling functions.

Question No: 1 (Marks: 1)

C language is developed by

- ▶ Bill Gates
- ▶ Robert Lafore
- ▶ **Dennis Ritchie Pg 12**
- ▶ Deitel & Deitel

Question No: 2 (Marks: 1)

Which of the following choice is not an example of an int datatype?

- ▶ 0
- ▶ -32
- ▶ 65531
- ▶ **-4.0**

Question No: 3 (Marks: 1)

In flow chart, the symbol used for decision making is,

- ▶ Rectangle
- ▶ Circle
- ▶ Arrow
- ▶ **Diamond Pg 51**

Question No: 4 (Marks: 1)

Switch statement deals with,

- ▶ Integer data only
- ▶ float data only
- ▶ character data only
- ▶ **Integer and character data**

<http://docs.oracle.com/javase/tutorial/java/nutsandbolts/switch.html>

Question No: 5 (Marks: 1)

Default case in switch statement is,

- ▶ Must

► **Optional**

- syntax error
- Necessary

<http://www.arduino.cc/en/Reference/SwitchCase>

Question No: 6 (Marks: 1)

***doc is _____ by type.**

► **Sequential File**

- Random Access File
- Data File
- Record File

Question No: 7 (Marks: 1)

Member function tellg() returns the current location of the _____ pointer.

- tellptr()
- write()
- seekg()
- **get()**

http://enggedu.com/tamilnadu/university_questions/question_answer/bernd_2007/3rd_sem/cse/cs1204/part_b/13_a_1.html

Question No: 8 (Marks: 1)

Dealing with structures and functions passing by reference is the most economical method

- **True**
- False

<http://mathbits.com/MathBits/CompSci/Structures/Functions.htm>

Question No: 9 (Marks: 1)

In C/C++ all character strings are terminated with,

- Null character
- String
- **Zero Pg 166**
- Full stop

Question No: 10 (Marks: 1)

Word processor is

- Operating system
- **Application software**
- Device driver
- Utility software

Question No: 11 (Marks: 1)

Which of the following can not be a variable name?

- ▶ area
- ▶ _area
- ▶ **10area**
- ▶ area2

Question No: 12 (Marks: 1)

Which looping process is best, when the number of iterations is known?

- ▶ **for**
- ▶ while
- ▶ do-while
- ▶ all looping processes require that the iterations be known

http://en.wikipedia.org/wiki/For_loop

Question No: 13 (Marks: 1)

By default an array of characters is passed by value to a function.

- ▶ True
- ▶ **False**

Question No: 14 (Marks: 1)

Which of the following operator is used to access the address of a variable?

- ▶ * operator
- ▶ -> operator
- ▶ && operator
- ▶ **& operator Pg 480**

Question No: 15 (Marks: 1)

The name of an array represents address of first location of array element.

- ▶ **True Pg 120**

► False

Question No: 16 (Marks: 1)

Let suppose

Union intorDouble{

Int ival;

Double charvar;

};

main(){

intorDouble VAZ;

int size ;

size = sizeof(VAZ);

}

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8 bytes?

► 2

► 4

► 8

► 12

Question No: 1 (Marks: 1)

In C/C++ the #include is called,

► Header file

► **Preprocessor Directive pg 269**

► Statement

► Function

Question No: 2 (Marks: 1)

To access the element of two dimensional array we use,

► Single referencing

► Single dereferencing

► **Double dereferencing Pg175**

► Double referencing

Question No: 3 (Marks: 1)

Data Size of the file is always _____ the actual size of the file.

- ▶ Greater than
- ▶ Equal to
- ▶ Less than or equal to

▶ **None of the above Pg 216**

Similarly in case of files, the space occupied by a file (file size) can be more than the actual data length of the file itself.

Question No: 4 (Marks: 1)

When an identifier is declared with keyword const then,

- ▶ Its value can be changed during execution.
- ▶ **Its value can not be changed Pg110**
- ▶ Its value can be changed with arithmetic operator
- ▶ Its value can be overwritten

Question No: 5 (Marks: 1)

In C/C++ if we define an array of size eight (8) i.e. int Arr [8]; then the last element of this array will be stored at,

- ▶ Arr[0]
- ▶ Arr[8]
- ▶ **Arr[7]**
- ▶ Arr[-1]

Question No: 6 (Marks: 1)

If it is required to copy an array to another array then,

- ▶ **Both arrays must be of the same size and data type Pg 105**
- ▶ Both arrays may be of different size
- ▶ Both arrays may be of different data type
- ▶ Both arrays may be of different size and type

Question No: 7 (Marks: 1)

In C/C++ all character strings are terminated with,

- ▶ **Null character Pg 166**
- ▶ String
- ▶ Zero
- ▶ Full stop

Question No: 8 (Marks: 1)

Let suppose

```
struct
    intorDoubl
    e {
int ival; Double
    charvar;
};
```

```
main(){
    intorDouble
    VAZ;
    int size ;
    size =
    sizeof(VAZ);
}
```

What will be the value of variable size, if int occupies 4 bytes and double occupies 8 bytes?

- ▶ 2
- ▶ 4
- ▶ 8
- ▶ 12

Question No: 9 (Marks: 1)

When a pointer is incremented, it actually jumps the number of memory addresses

▶ According to data type Pg 160

- ▶ 1 byte exactly
- ▶ 1 bit exactly
- ▶ A pointer variable can not be incremented

Question No: 10 (Marks: 1)

Do-while loop executes at least,

- ▶ Zero Time
- ▶ One Time
- ▶ Two Times
- ▶ N Times

Question No: 11 (Marks: 1)

+= , *= , /= , etc are called,

- ▶ Assignment operators
- ▶ Logical operator
- ▶ **Compound assignment operator Pg 63**
- ▶ Unary operator

Question No: 12 (Marks: 1)

Computer can understand only machine language code.

▶ **True Pg 12**

▶ False

Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

- ▶ cout <
- ▶ cout <
- ▶ cout <
- ▶ cout <

Question No: 14 (Marks: 1)

The compilers and interpreters also belong to the System Software category.

▶ **True Pg 11**

▶ False

Question No: 15 (Marks: 1)

Editors are used to compile the code.

▶ True

▶ **False**

Compilers are used for compilation of source codes, However Editors are used to write the source codes.

Question No: 16 (Marks: 1)

The variables having a name, type and size are just like empty boxes.

▶ **True**

▶ False

Question No: 17 (Marks: 1)

What will be the result of the statement

rand () % 50

When 50 divides any number, the remainder will always be less than 50.



4th file correct

Remember own prayer

For More Visit VUStudents.pk

CS201 Solved Grand Quiz 2020

File 1

Question No 1

The statement `cout << yptr` will show the _____ the `yptr` points to.

- ☐ Value.....(For More Visit VUStudents.pk)
- ☐ Type
- ☐ Data

What will be the result of the expression

`k = ++m;`

- ☐ 0
- ☐ 5

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question No 4

char name [] = "Hello World";

in the given statement a memory of _____ characters will be allocated.

Select Correct Option

- ☐ 13
- ☐ 11
- ☒ 12.....([For More Visit VUStudents.pk](http://VUStudents.pk))
- ☐ 10

A function's prototype is written _____ the function call.

Select Correct Option

- ☐ 52
- ☐ 50
- ☒ 51.....([For More Visit VUStudents.pk](http://VUStudents.pk))
- ☐ 57

Question No 7

In CVC++, by default argument are passed by _____ to a function.

Select Correct Option

- ☐ Reference
- ☒ Value.....([For More Visit VUStudents.pk](http://VUStudents.pk))
- ☐ Size

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question No 8

Correcting the errors from a program is termed as _____.

Select Correct Option

- ☐ Linking
- ☐ Loading
- ☐ Executing
- ☐ **Debugging**.....([For More Visit VUStudents.pk](http://VUStudents.pk))

Declaration of two-dimensional array of integers having 3 rows and 5 columns is following?

- ☐ **int arr [3][5];**([For More Visit VUStudents.pk](http://VUStudents.pk))

To get the value stored at a memory address, we use the_____.

Which of the following is the correct way to write a compound assignment operator?

- ☐ **x += 4;**([For More Visit VUStudents.pk](http://VUStudents.pk))
- ☐ x + = 4;
- ☐ x + = = 4;
- ☐ None of the above

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question No 12

We can say that a pointer is a variable that holds the _____ address.

Select Correct Option

- ☐ Byte code
- ☐ Source code

What is the use of ios::trunc mode?

Select Correct Option

- ☐ To open a file in input mode
- ☐ To open a file in output mode
- ☐ To truncate an existing file to half
- ☐ To truncate an existing file to zero.....(For More Visit VUStudents.pk)

A variable declared within a code block becomes _____ variable for that block.

Which of the following is the correct operator to compare the values of two variables?

- ☐ :=
- ☐ =
- ☐ “=
- ☐ ==.....(For More Visit VUStudents.pk)

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question No 16

What will be the value of the variable output in the given piece of code?

Double output = 0;

Output – $(2+2) * 4 + 2 / (4-2);$

- ☐ 15
- ☐ 17.....(For More Visit VUStudents.pk)
- ☐ 12
- ☐ 11

Which of the following function call is “call by reference” for the following prototype?

A variable of character data type occupies _____ bytes in memory.

- ☐ 2
- ☐ 4
- ☐ 8

According to c++ norms, the first character of a variable name must be an alphabet or

Select Correct Option

- ☐ Underscore.....(For More Visit VUStudents.pk)
- ☐ Special character
- ☐ Digit
- ☐ None of the given options

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question No 20

For breaking complex problems into smaller pieces we use _____.

Select Correct Option

- ☐ If\else
- ☐ Loops

From the following which one is the range of Random number generator function rand()?

C++ is a _____ language.

Select Correct Option

Whenever some number is added in an array name, it will jump as many _____ as the added number.

- ☐ **Rows.....(For More Visit VUStudents.pk)**
- ☐ Value
- ☐ Column
- ☐ None of the given

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question No 24

Array indexes start from _____.

Select Correct Option

- ☐ 0.....([For More Visit VUStudents.pk](http://VUStudents.pk))
- ☐ 1
- ☐ 2
- ☐ 3

_____ will explain the function of a program.

Select Correct Option

- ☐ Comments.....([For More Visit VUStudents.pk](http://VUStudents.pk))

Which of the following will be the most appropriate data type to store the value 63.547?

- ☐ Float.....([For More Visit VUStudents.pk](http://VUStudents.pk))

- ☐ Repetition.....([For More Visit VUStudents.pk](http://VUStudents.pk))
- ☐ None of the given options

For More Visit VUStudents.pk

Question No 28

The sting in the array is terminated by a _____.

Select Correct Option

- ☐ Zero
- ☐ Nil

< and > both are _____ operations.

Select Correct Option

- ☐ Relational.....([For More Visit VUStudents.pk](http://VUStudents.pk))
- ☐ Logical
- ☐ Mathematical



Remember own prayer

4ND FILE CAREFULLY WHILE ATTEMPTING

6. By default, the starting index of an array in c++ is____

Output file stream

0

7. How we declare an array of integer data whose size is 20 with array name "count".

Int count [20];

8. Which of the following is a keyword for data type in c/c++?

Int

9. C was developed with the help of----- language

BCPL and B

10. An object of ----- class can be created for saving the

Current position of any opened file before reading from the file.

Streampos

11. C++ is a-----language.

High level

12. In while loop, the loop counter is initialized at-----

Before entering the loop

13. What is the output of the following code if the 3rd case is

true

Switch(var)

{Case 'a';

Cout<<"apple"<<endl;

Mango

14. -----character is used to indicate the end of the

string.

Null

15. Which of the following is used to perform bit-wise

Exclusive OR operation?

|

16. If $x = 11$, and $x \% 3 = 3$, then value of x will be-----

2

17. A variable of character data type occupies----- by testing

memory.

1

18. Null character is represented by----in c++?

\0

19. In computer system there are mainly----type of Softwares .

2

20. There is pointer variable named ptr of type float. Which Type of variable address can be store by ptr?

Float

21.A character is stored in the memory in -----

Byte

22.X is an integer variable;whatdoesx++ means,

Add 1 inx value

23.When we call a function, its control-----

Transfers to its definition

24. '\0'takes---- space in the memory.

1 byte

25.-----will be used for enclosing function statements into
A block?
{ }

26.How can we declare an array of characters whose size is
12witharray name“ country”?
Char country[12];

27.Following is the declaration of a2darray, how many
Columns are declared for this array.
Intarr[3][2];

2

28.If we assign 2.06721 to an integer variable x, what will be
The output if we print x using cout<< statement?

2

29.We can access a global variable----
From anywhere in the program

30. We use----to include all those functions which are
located in different files.
Linker

31. A character is stored in the memory in ----

Byte

32. Which is not true regarding structure?

We can declare array of structure

33. Mr. ahmad sleeps thirty hours everyday. This sentence is----

Grammatically correct but illogical

34. -----will explain the function of a program.

Comments

35. Char **argv can be read as----

Pointer to pointer to char

36. What will be out put of the following code?

```
String name[4]= {"ali","bilal","omer","Ayesha"};
```

```
Cout<<name[0];
```

Ali

37. The data type before a function name represents its,

Return type

37. The expression $((a+b) == 10) \vee ((x+y) == 20)$ is true only if?

Either((a+b) ==)OR((x+ y)==20) istrue

38.= operator is used for ----

Assigning values to variables

39. What is the use of ios::trunc mode?

To truncate an existing file to zero

40. X is an integer variable; what does x ++ means,

Add 1 in x value

41.Structures use---- allocation.

Heap

42. What will be the size of the following character array?

Char name[] = "adeel";

6

43.A ---- is an array of characters that can store number of

Character specified.

String

44.----- statement is used to terminate the processing of a particular case and exit from switch structure.

Break

45. If $y = 20$ and $z = y++$, then the value of z will be-----

2146. If

`int a = 17;`

`int b = 3;`

`double c = a/b;`

what will be value of variable c ?

5

47. What will be the output of the following code?

`String grade[3] = {"a", "b", "c"};`

`Grade[2] = "f";`

`Cout << grade[2];`

F

48. Declaration of two-dimensional array of integers having 3

rows and 5 columns is following?

`Intarr[3][5];`

49. $A = A + 1$; can be written as----

$A++ = 1$;

50. A record is a group of related

Fields

51. What will be the result of arithmetic expression

$6+48/4*3$?

42

52.-----construct is used to execute asset of instructions

When a condition is true and other set when it is false?

Ifelse

53. If an array has 50 elements, what is allow able range of subscripts?

0 –49

54.Ifint a= 50; then the value of a/= 3;will be?

16

55.Whichof the following option is/are correct about array?

Only one type of elements can store in an array

56. Whenever some number is added in an array name, it will

Jump as many---as the added number?

Rows

57.----- return true if c is a digit or a letter and false otherwise.

isdigit(int c)

58. which of the following is the default mode of the opening using of
Of stream class?

ios::trunc

59. In which language the compiler of c language is written?

C

60. While loop executes at least?

One time

61. String are accessed by variable of type----

Char

62. Which of the following is the correct operator to compare the values of
two variables?

==

63. Not operator is a-----

Single input operator

64. Pointer points to a particular-----

Memory address

65. A function is a block of statements that can be defined once and used --- in the program.

As many times as user wants

66. ----- function is used to find the number of characters in a string?

Strlen()

67. != operator is used to check whether the operand on the left-hand side is ----- to the operand on the right-hand side.

Not equal

68. A while loop may execute ----- or more times.

0

69. How we declare an array of integer data whose size is 20 with array name "count".

```
Int count[20];
```

70. A variable declared within a code block becomes ---- variable for that block.

Local

71. If a file is opened with ios::out mode, then -----

We can write in this file

72. A function's prototype is written--- the function call.

Before

73.---- Loop is mostly used to perform repetition of a task for a known Number of times.

For

74. In shifting operations if zero is inserted at the least most bit, the Negative number will become a----number.

Positive

75. It is the job of ---- to transfer the executable code from hard disk to main memory.

Loader

76.RAID stands for-----

Redundant array of inexpensive devices

77.Array indexes start from ----

0

78.Incallby reference,-----of a variable is passed to the called function.

Address

79.Howmany times the following do-while loop will execute?

Int k = 10;

Do

{

Cout<<"statements"<<endle;?

6

80.The name of a location in memory is called----

Variable

81.-----function is used to find the number of character in a string.

Strlen()

82.Which statement is used to close a file?

Myfile.close();

**83. -----allow us to have a memory location and use it a sint or char
Inter changeably.**

None of the given

84.While handling files, one can have---- options

All of the given

**85. ----- function is used to determine then ext position to write a
Character while writing into a file.**

Tellp()

86. Which is the correct syntax to define a structure named 'student'?

Structstudent{

//variables

};

87. <and> both are ---- operators.

Logical

Identify the logical error in the following if condition

88. If((i<5) &&(i>15))?

Condition is always false

89. Not operator is a ----

Single input operator

90. The use of *sign in first and second statements is called --- and ----
of pointer.

Int *ptr= &x;

Cout<<*ptr;?

Referencing, dereferencing

91. C is widely known as development language of ---- operating system.

Linux

92.If x is declare as an integer, what will be result of the given expression?

$X = 2 + 3 * 5 \% 2 + 3 / 2 ??$

4

93.What will be the correct syntax of declaration of the following statements?

“ptr is a pointer to constint”??

Constint*ptr

94.Afte revaluating the expression

95. $X = 10 + 3 * 4 / 2 - 1$, the value of x will be?

15

96. We can read,write and manipulate the same file using----

Fstream.h

97.Return type of a function that does not return any value must be----

Void

98.Pointersstorethe----

Memory address

99. -----operator uses the sign^.

Exclusive OR

100.Toget the value stored at a memory address, we use the----

Dereferencing operator

101.Telling a computer what to do is called ----

Programming

102.Compiler translates high level language program into ---- language code.

Machine

103.Eacharray declaration must provide the information about all these Things except----

The location of the first element to be stored

104.E of is used to check for the---of file when a file is being read.

End

105.The result of $4\%3$ will be?

1

106.When the logical operator AND(&&) combine two expression exp1and exp2then the result will be true only?

When bothexp1and exp2aretrue

107. 'multi[3][3]' element can also be accessed by-----

`*(*(multi+3)+3)`

108. What is output of following code?

```
Int data[10]= {10,20,30,40,50,60,70,80,90,100};
```

```
Int *xptr=&data[4];
```

```
Int *xptr=&data [6];
```

```
Cout<<xptr + yptr ++;??
```

120

109. Which of the following is not the sub category of the system software?

None of the above

110. We get $12|8$ =----- where "|" is (bit-wise OR)?

12

111. ----- is a substitute of multiple if statement.

If..else if statement

112. Find out the logical error in following lines of code.

```
If(x= 10)
```

```
Cout<<"xis10";?
```

Assignment operator should not be used for comparison

113. Which is not true regarding structure?

c) we can't declare pointers to structure

114.-----are used to compile the code.

Compiler

115. #include<iostream>

#include<cstring>

Using name space std;

Intmain()

{

Char str1[10]= "hello";

Char str2[10]= "world";?

10

116. A ---structure specifies that an action is to be repeated while some Condition remains true.

Repetition

117.In which language the compiler of c language is written?

C

118.Characters string are terminated by-----

\0

**119. A function is a block of statements that can be defined once and used-
in the program.**

As many times as user wants

120.----- is used for output during the process of writing to the file.

Seekp()

**In case of two-dimensional array, if you add some number in a two-
dimensional name, it will jump to the next----**

Row

121.In while loop the condition is checked---- the execution of loop.

Before

122.Array indexes start from ----

0

123.Pointers store the----

Memory address

124.Which step is not performed during a proper program design?

Write details about the performance of program

125,We can say that a pointer is a variable that holds the--- address.

Memory

126. When accessing a structure memory, the identifier to the left of the Dot operator is the name of----

Structure variable

127. From the following; which one is the range of random number generator rand()?

0-32767

128. To read command-line arguments, the main () function itself must be given----arguments.

2

129. Which operator has the highest precedence?

(*,-, /, +)?

*and / both have the same highest precedence

130. Suppose we have int y[10];

To access the 4th element of the array we write----

Y[3];

131. What will be the value of the variable output in the given piece of code?

Double output= 0;

Output=(2+2)*4 + /(4-2);

17

132. What is the output of the following statement?

```
inti = 2.5; do {couti * 2; } while(i>3 && i< 10);
```

error

133. Searching is easier when an array is already sorted

True

134. If an array has 100 elements, what is allowable range of subscripts?

0 -99

While developing a program; should we think about the user interface?

```
//handouts main
```

Yes

A character is stored in the memory in _____

String

These functions seekg() and seekp() requires an argument of type _____ to let them know how many bytes to move forward or backward.

Int

dereferencing operator is represented by _____

*

_____ transfers the executable code from main memory to hard disk.

Loader

When the logical operator OR (||) combine two expressions exp1 and exp2 then the result will be false only, //bit wise “or” applies here....

When both exp1 and exp2 are false

Suppose we have `inty[10]`; To access the 4th element of the array we write _____

none of given

we have opened a file stream my file for reading (getting), my file. `tellg()` gives us the current get position of the file pointer. It returns a whole number of type _____

int

of stream is used for _____

Output file stream

A structure is a collection of _____ under a single name.

Variables

In C/C++ the string constant is enclosedcorrected rued one

In curly braces

The size of int data type is

4 bytes

In Flow chart process is represented by

Rectangle

If the break statement is missed in switch statement then, // a break Statement with no label always completes abruptly, the reason being a Break with no label. If no switch, while, do, or for statement in the Immediately enclosing method, constructor or initialize encloses the break statement, a compile-time error occurs?

This may cause a logical error

When we are using const keyword with a variable x then initializing it at the time of declaration is,?

Optional

Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third column?

m[2][3] = 5 ;

How many total elements must be in a two-dimensional array of 3 rows and 2 columns?

6

Which of the following is the correct statement for the following declaration?

***ptr is a pointer to a constant**

What will be the correct syntax to assign an array named arr of 5 elements to a pointer

ptr?

***ptr = arr[5];**

C is a/an _____ language

object oriented

The variables having a name, type and size are just like empty boxes.

True

What's wrong with this for loop?

for (int k = 2, k <= 12, k++)

the commas should be semicolons

The most efficient method of dealing with structure variables is to define the structure globally

True

There are mainly _____ types of software.

Two

When a pointer is incremented, it actually jumps the number of memory addresses ?

According to datatype

set is a parameterized manipulator.

True

if $(a > b \ \&\& \ a > c)$ then the condition will be true only if

Both $a > b$ and $a > c$ are true

In while loop the loop counter must be initialized,

Before entering the loop

_____ of a variable means the locations within a program from where it can be accessed.

Reference

Switch supports _____ data.

Integer

Character

Float

Both integer and character

A function is a block of statements that can be defined once and used _____ in the program.

As many times as a user wants

_____ statement is used to terminate the processing of a particular case and exit from switch structure.

break

The most suitable data type for number 325.25 is _____.

float

If x is an integer variable, what does $x++$ mean,

Add 1 in x value

The operators $++$ and $--$ are used to increment or decrement the value of a variable by _____

1

Which of the following loops checks the test condition at the end of the loop?

Do-While

The operator to free the allocated memory using new operator is _____.

delete

suppose we have `int y[10]`; To access the 4th element of the array we write _____

`y[3]`;

From the following, which one is the range of Random number generator function `rand()`?

0 – 32767

From following, which one is the correct syntax of an array initialize: Array size is 10 and it is of double data type to value 0?

`double arr[10] = {0.0};`

The string in the array is terminated by a _____

null

In C/C++, by default arguments are passed by _____ to a function.

Value

`char name [] = "HelloWorld";` In the above statement, a memory of _____ characters will be allocated

12

_____ Keyword is used to return some value from a function.

return

Which of the function call is call by value for the following function prototype? float add(int);

add(x);

The increment of a pointer depends on its _____.

datatype

The ASCII code of null character is _____

000

Pointers are a special type of _____ in which a memory address is stored

variables

Transpose of a matrix means that when we interchange rows and columns _____

the first row becomes the first column

Pointers store the _____

value of a variable

Which of the following function call is “call by reference” for the following function prototype? `int add(int*);`

`add(&x);`

The name of the array is a constant pointer which contains the memory address of the _____ of the array.

first element

array name always contains the memory address of the _____ of the array

first element

At the _____, we try to break up the problem into functional units
design phase

Syntax of a union is identical to _____.

structure

A union is a user-defined data type that contains only _____ from its list of members at a

time.

one object

Which of the given file handling modes are similar in their functionality?

ios::trunc, ios::ate

Which one of the given options is not a mode for reading/writing the data from a file?

Trunk

In C/C++, the header file used for string manipulation is _____.

string.h

A 2D array multi[5][10] can be accessed using the array name as **multi, this technique is

called _____.

Double dereferencing

C language was evolved from _____ language(s).

B and BCPL

The _____ statement forces the immediate next iteration of the loop.

Continue

_____ are very good tools for code reuse.

Functions

When an argument is passed by reference, _____
the function accesses the argument's original value in the calling program.

_____ executes all the lines before error and stops at the line which contains the error.

Interpreter

Analysis is the ----- step in designing a program.

First

Which of the following is the correct function call, having an array named student of 10

elements as a parameter?

addRecord(student);

When an array element is passed to a function, it is passed by

Reference

What is the correct syntax to declare an array of size 10 of int datatype?

int name[10];

If we want to copy an array, both arrays need to be of same _____.

Datatype and size

Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

`cout << "H" << x << "\n";`

Which one of the statements given below is equivalent to `x %= 5`?

`x = x % 5`

The condition in loop should be a(n) _____.

Boolean Expression

Which structure is represented by following flowchart?

if structure

Stream which sends data to the program is called _____.

Input stream

Syntax of a union is identical to _____.

Structure

When accessing a structure member, the identifier to the left of the dot operator is the

name of _____.

a structure variable

The parameter passed to `isdigit()` function is _____.
a character variable

TWAIN stands for _____.

Technology Without An Interesting Name

_____ translates high level language program into machine language code.

Compiler

From the option given below, what will be the correct output of the code?

```
for (int a = 1; a <= 3; a++)
```

```
cout << a*3-1 << " ";
```

25 8

If the return type of a function is `void` then it means that it will _____.

return any type of data

return no data

The functions that have already been defined as a part of the language are called

_____.

built-in functions

Given that doubleArray is an array of 7 integers. Which of the below is the correct statement to access the 5th element of the array?

doubleArray[4]

The symbol which is used to represent a process in a flowchart is _____.

Rectangle

When an array is passed to a function, by default it will be passed by _____.

Reference

What is the range of Random number generator function rand()?

0 – 32767

The first character of a variable name must be an alphabet or _____.

Underscore

In _____, the first pointer stores the address of the same other pointer, which contains the address of any variable.

single dereference

Initialization of variable at the time of definition is-----practice.

Good Programming

Which looping process checks the test condition at the end of the loop?

do-while

You can use a _____ statement to transfer control elsewhere out of the nested structure.

Goto

Which of the following array is the most suitable for storing a matrix structure?

Single-dimensional array

The Microsoft Word document(.doc) is a kind of _____.

Random Access File

A union is a user-defined data type that contains only _____ from its list of members at a time.

one object

In C/C++, _____ are the doors through which data can enter and come out of a program.

Streams

Which one of the given options is not a mode for reading/writing the data from a file?

Trunk

C++ views each file as a sequential stream of _____.

Bytes

In 2D array, the technique used to access the array elements is called _____

Double dereferencing

From the options given below, identify the correct option which is used for calling the function `float square (int&);`

`square (num);`

Identify the correct option which is used for calling the function `float area (int).`

`area(num);`

Which kind of error occurs in the code below to access the variable `num` in the `main`

function?

```
int num=10;
```

```
int main(){
```

```
int x ;
```

```
x = num;
```

}

No error

A program statement that invokes a function is called _____.
function call

What will be the output of the following code segment?

```
main(){  
    int a= 10 ;  
    int b =0;  
    int *x =&a;  
    b = (*x)+3 ;  
    cout<<a<<" ";<<b ;  
}
```

10,13

When the logical operator AND(&&) combines two expressions exp1 and exp2 then the result will be true only _____

When both exp1 and exp2 are true

For which array, the size of the array should be one more than the number of elements in an array?

char

What is the range of Random number generator function rand()?

0 – 32767

To assign a value to a character type variable, _____ are used around the value.

single quotes

In C/C++, the #include is called _____.

Preprocessor Directive

The number 544.53 must be stored in _____ datatype.

Float

Use of the _____ statement violates the rules of structured programming.

Goto

In Flow Chart, flow of control is represented by _____.

Arrow

What will be the correct syntax for initialization of pointer ptr of type int with variable x?

int *ptr = &x;

Syntax of a union is identical to _____.

structure

A union is a user-defined data type that contains only _____ from its list of members at a time.

one object

Which of the given file handling modes are similar in their functionality?

ios::trunc, ios::ate

Which one of the given options is not a mode for reading/writing the data from a file?

Trunk

Stream which sends data to the program is called _____.

Input stream

Syntax of a union is identical to _____.

Structure

When accessing a structure member, the identifier to the left of the dot operator is the name of _____.

a structure variable

The parameter passed to `isdigit()` function is _____.
a character variable

TWAIN stands for _____.

Technology Without An Interesting Name

_____ translates high level language program into machine language code.

Compiler

From the option given below, what will be the correct output of the code?

```
for (int a = 1; a <= 3; a++)
```

```
cout << a*3-1 << " ";
```

25 8

If the return type of a function is `void` then it means that it will _____.

return no data

The functions that have already been defined as a part of the language are called

_____.

built-in functions

Given that doubleArray is an array of 7 integers. Which of the below is the correct

statement to access the 5th element of the array?

doubleArray[4]

The symbol which is used to represent a process in a flowchart is

_____.

Rectangle

When an array is passed to a function, by default it will be passed by _____.

Reference

The first character of a variable name must be an alphabet or

_____.

Underscore

In _____, the first pointer stores the address of the some other pointer, which contains the address of any variable.

single dereference

Initialization of variable at the time of definition is ----- practice.

Good Programming

Which looping process checks the test condition at the end of the loop?

do-while

You can use a _____ statement to transfer control elsewhere out of the nested structure.

Goto

An object of _____ class can be created for saving the current position of any opened file

before reading from the file

Stream

The value returned by the eof() function is of _____ type.

Character

If a file is not properly closed in a program then what is the status of the program?

The program will terminate normally

The parameter passed to isdigit() function is _____.

a character variable

In C/C++, the header file used for string manipulation is _____.
string.h

Arrays are best data structures _____.
for relatively permanent collections of data

Each array declaration must provide the information about all these things
except
_____.
Number of elements of the array

The first step for developing a program is _____.

Linking

Analysis

_____ transfer the executable code from hard disk to main memory.

Loader

_____ operator is used to pass the address of a variable to the called
function.

&

In call by reference, _____ of a variable is passed to the called function.

Address

_____ of a function is also known as signature of a function.

Declaration

Preprocessor program performs its function before _____ phase takes place.

Compiling

Which of the following is the correct function call, having an array named student of 10 elements as a parameter?

`addRecord(student[10]);`

The remainder (%) operator is a _____ operator.

Arithmetic

Which of the following arrays is the most suitable for storing a matrix structure?

Two-dimensional array

*.doc is _____ by type.

► Random Access File

Which of the following is NOT a preprocessor directive?

- ▶ **#define**

The return type of operator function must always be void.

- ▶ **False**

Question No: 4 (Marks:1)-Please choose one

What does (*this) represent?

- ▶ **A value of the data member**

The statement `cin.get()` is used to,

- ▶ **Read a character from keyboard**

When we do dynamic memory allocation in the constructor of a class, then it is necessary to provide a destructor.

- ▶ **True**

Overloaded new operator function takes parameter of type `size_t` and returns

- ▶ **void pointer**

The second parameter of operator functions for `<<` and `>>` are objects of the class for which we are overloading these operators.

- ▶ **True**

C++ is a case-sensitive language

- ▶ **True**

To include code from the library in the program, such as `iostream`, a directive would be called up using this command.

► `#include<iostream.h>`

A template function must have only generic data types.

► True

Template class can not have static variables.

► False

What will be the correct syntax to assign an array named `arr` of 5 elements to a pointer

`ptr`?

► `*ptr= arr[5];`

What will be the correct syntax to access the value of fourth element of an array using pointer `ptr`?

► Both 1 and 3

If most significant bit of un-signed number is 1 then it represents a positive number.

► True

If there is a symbol (& sign) used with the variable name followed by data type then it

refers to ____ and if & is being used with variable name then it refers to ____.

► Reference variable, address of variable

We can also do conditional compilation with preprocessor directives.

► True

The default value of a parameter can be provided inside the

► function definition

Classes defined inside other classes are called ____ classes

► nested

What purpose do classes serve?

► All of the given options

Every class contains ____.

► Constructor

new operator is used to allocate memory from the free store during

► None of the given options

When an object of a class is defined inside another class then,

► **Destructor of inner object will be called first**

It is possible to define a class within another class.

► **True**

New and Delete are also used with _____ and datatypes as well.

► **Class, Objects**

With New keyword, datatypes and class members are initialized with meaningful values instead of garbage.

► **True**

C language is developed by

► **Dennis Ritchie**

Which of the following choice is not an example of an int datatype?

► **-4.0**

In flowchart, the symbol used for decision making is,

► **Diamond**

Switch statement deals with,

- Integer and character data

Default case in switch statement is,

- Optional

*.doc is _____ by type.

- Sequential File

Member function tellg() returns the current location of the _____ pointer.

- tellptr()

Dealing with structures and functions passing by reference is the most economical method

- True

In C/C++ all character strings are terminated with,

- Null character

Word processor is <http://vustudents.ning.com>

- Application software

Which of the following cannot be a variable name?

10area

Which looping process is best, when the number of iterations is known?

► **while**

By default an array of characters is passed by value to a function

► **False**

Which of the following operator is used to access the address of a variable?

► **&operator**

The name of an array represents address of first location of array element.

► **False**

Compiler is a

► **Application Software**

If Num is an integer variable then Num++ means,

► **Add 1 with Num**

For one byte there are _____ combinations of values that can be stored in a computer.

► 2^8

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

► `ctype.h`

Default case in switch statement is,

► Optional

When break statement is encountered in switch statement, it

► Exits from switch statement

What will be the result of arithmetic expression $6 + 27/3 * 3$?

► 33

What is the correct syntax to declare an array of size 10 of int datatype?

► `int name[10];`

How many dimensions does an n-dimensional array have?

► n dimensions

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

► **ptr[3]**

Which of the following values C++ use to represent true and false?

► **1 and 0**

Declaring structures does not mean that memory is allocated.

► **True**

For which array, the size of the array should be one more than the number of elements in an array?

► **char**

If a variable is passed by value to a function and the function makes some changes to that variable then it

► **does not affect the original variable**

In C/C++ the #include is called,

► **Preprocessor Directive**

Loops are ----- Structure.

► **Repetition**

the sizeof operator is used to determine the size of _____.
datatype

Structures use _____ allocation.
Stack

Which header file must be included to use the functions tolower() and toupper()?
ctype.h

In Analysis, we try to have a _____.
Precise problem statement

Pointers store the _____.
memory address

_____ Return true if c is a digit and false otherwise.
int isdigit(int c)

eof is used to check for the _____ of file when a file is being read.
End

The statement `cout << yptr` will show the _____ they point to.
memory address

Which of the following is true about streams?

A & B

While handling files, one can have _____ options

All of the given

If an array has 50 elements, what is the allowable range of subscripts?

0 – 49

A structure is a collection of _____ under a single name.
variables

If stream is used for _____

Input file stream

The ASCII code of null character is _____

000

Dereferencing operator is represented by _____

*

Whenever some number is added in an array name, it will jump as many _____ as the added number.

rows

To access the data members of structure, _____ is used.

Dot operator

Which of the following is true about streams? A. It is a sequence of bytes
B. It is an ordered sequence C. All bytes can

go through the streams simultaneously D. Bytes that enter first into the stream will go out last

A and B

We use _____ to open a file or stream for extraction
in

char **arg can be read as _____.

pointer to pointer to char

From following, which one is the correct syntax of an array initialize:
Array size is 10 and it is of double data type to value 0?

double arr[10] = {0.0};

Pointers work by pointing to a particular _____
datatype

_____ function give the position of the next character to be read
from that file.

tellg()

aFile.seekg(-10L, ios::cur)

backward direction

An object of _____ class can be created for saving the current position
of any opened file before reading from the file.

Stream

Structures are syntactically defined with the word _____.

struct

_____ allow us to have a memory location and use it as int or char
interchangeably

union

Question#9 of 10(Starttime:12:25:41PM) TotalMarks:1

A hierarchy of classes which are used to deal with console and disk files are called_____.

IO classes

_____ function is used to determine the next position to write a character while writing into a file.

tellp()

For binary member operators, operand on the _____ drives (calls) the operation.

Left

**We cannot increment_____.
references**

**We can _____ pointer.
all of the given**

We can _____ references.

None of the given

What will be the correct syntax for the following function call?

add(x);

An instance of a class is called _____.

object

The _____ is called automatically when an object destroys

destructor

The destructor is used to _____.

deallocate memory

_____ data is not accessible by non-member functions or outside classes.

private

Member functions of the class _____ main program.

are accessible from

Overloading means:

Using the same name to perform multiple tasks or different tasks depending on the situation.

The main advantage of function overloading is _____.

The program becomes more readable

You cannot overload the _____ operator.

?:

In C++, a variable can be declared anywhere in the program; this will increase _____.

efficiency

Memory allocated from heap or freestore _____.

cannot be returned back unless freed explicitly using free and delete operators

We cannot use _____ pointer for storing and reading data from it.

'NULL'

The dynamic memory allocation uses _____ whereas static memory allocation uses _____.

heap, stack

What will be the output of the given code?

```
#include <iostream>
#define MAX(A,B) ((A)>(B)?(A):(B))
```

```
void main(){
```

```
    int i, x, y;
```

```
    x = 23;
```

```
    y = 45;
```

```
    i = MAX(x++, y++);
```

```
    //Side-effect: //larger value incremented twice
```

```
    cout << "x = " << x << "y = " << y << '\n';
```

```
}
```

$x=24y=47$

NULL has been defined in _____ header file.

Stdlib.h

Symbolic constant PI can be defined as:

#define PI 3.14

The friend function of a class can have access _____.

to the private data members

C++ was developed by _____.

Bejarne Stroustrup

Once the _____ are created, they exist for the lifetime of the program.

static variables

Encapsulation means _____.

that the data of a class can be accessed from outside

An address is a _____, while a pointer is a _____.

constant, variable

The syntax of declaration of a function that returns the reference to an integer is _____.

`int&myfunc();`

Which one of the following is a mandatory preprocessor directive for C++?

`#include`

The members of a class declared with the keyword `struct` are _____ by default.

`Public`

`getche()` is a _____ function and defined in _____ header file.

built-in function, `conio.h`

_____ operators are the ones that require two operands on both sides of the operator.

`Binary`

_____ will return the number of bytes reserved for a variable or data type.

`sizeof` operator

_____ are not available in C language.

Library functions

The members of a class declared without any keyword are _____ by default.

private

For console input and output we use _____.

conio.h header file

The name of the destructor is the same as that of a class proceeding with a _____.

~sign

A reference cannot be NULL it has to point to a data type.

True

A pointer is _____.

a variable for storing address

Constructor is a special function, called whenever we _____.

instantiate an object of a class

Symbolic constant PI can be defined as:

#define PI 3.14

Object code is machine code but it is not _____ and _____.
relocatable, executable

The default visibility for the data members of the class is
private

accessible outside the class

The _____ is called automatically when an object destroys.
destructor

Constructor is special type of function:
which has no return type

_____ variables are those that are defined outside of main.
Global

Within the statement `obj1=obj2`; `obj1` will call the assignment operator
function and `obj2` will be passed as an argument to function.

True

When the compiler overload the assignment (`=`) operator by default then
Compiler does memberwise assignment.

It is possible to return an object from a function using this pointer.

True

Overloaded assignment operator must be

Member function of class

Let suppose

int a, b, c, d, e;

a = b = c = d = e = 42;

This can be interpreted by the compiler as

a = (b = (c = (d = (e = 42))));

In statement a + b + c, at first

b + c is executed first

Suppose int i = 10; then what is the output of cout << oct << i;

12

ostream is a _____ operator.

Standalone

_____ must be included to use stream manipulation in your code.

iomanip

_____ operators are the ones that require only one operator to work.

Unary

The end line flushes _____.

Manipulators

When an operator function is implemented as a member function then return type of function _____.

Can be any data type

When a variable is defined as static in a class then _____.

Only one copy is created for all objects of this class

Automatic variables are created on _____.

Stack

```
cout<<i<<" ";
```

```
cout<<d<<" ";
```

```
cout<<f;
```

Above statements can be written within a single line as:

```
cout<<i<<" "<<d<<" "<<f;
```

dec, hex, oct are all _____.

Non-parameterized manipulators

What will be the output of following statement?

```
cout << setfill('0') << setw(7) << 128;
```

0000128

Which of the following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

```
delete[] string;
```

If we have a program that writes the output data (numbers) to the disc, and if we collect the output data and write it on the disc in one write operation instead of writing the numbers one by one.

In the above situation the area where we will gather the number is called

Buffer

The first parameter of operator function for << operator _____.

Must be passed by reference

The second parameter of operator function for >> operator must always be passed

By reference

The only operator that the compiler overloads for user-defined data type by default is-----

Assignment(=) operator

Consider the following code, the printed value will be converted into:

```
int n=10;
```

```
cout<<oct<<n;
```

Base 8

_____ variables are defined in the main.

Local

ostream class is _____ and not under our control.

built-in

The memory allocation in C++ is carried out with the help of _____.

new operator

If B is designated as a friend of A, B can access A's non-public members.

A can access non-public members of B

If the request of new operator is not fulfilled due to insufficient memory in the heap _____.

the operator returns 0

We should not use such variable names that are starting with _____
because in C++, there are a lot of internal constants and symbolic names
that start with it.

double underscore

The friend keyword provides access _____.

in one direction only

The malloc function takes _____ argument(s).

one

The constructor contains _____.

no return type

What will be the output of the following C++ code?

```
#include <iostream.h>
```

```
#define max 100
```

```
main()
```

```
{
```

```
#ifdef max
```

```
Cout << "Hellow;
```

```
}
```

Error

Once we have defined a symbolic constant value using #define, that value _____ during program execution cannot be changed

The memory allocation functions return a chunk of memory with a pointer of type _____.
ptr

A class can be declared as a _____ of another class.
member

To avoid dangling reference, don't return _____.
the reference of a local variable from the function

Constructor is itself a _____ of C++ and _____.
function, can be overloaded

The parameter passed to isdigit() function is _____ variable.
Integer

char **argv can be read as _____.
pointer to pointer to char

To read command-line arguments, the main() function itself must be given _____ arguments.

How many bytes an integer type pointer `intPtr` will jump in memory if the statement below is executed?

```
intPtr += 2;
```

8

The increment of a pointer depends on its _____.

datatype

The statement `cout << yptr` will show the _____ the `yptr` points to.

memory address

_____ is used as a dereferencing operator.

*

Transpose of a matrix means that when we interchange rows and columns _____.

the first row becomes the first column

Individual characters in a string stored in an array can be accessed directly using array _____.

subscript

We can define a matrix as _____ array.

Multidimensional

A _____ is an array of characters that can store number of characters specified.

String

Given a two-dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?

`array[2][3] = 6;`

_____ of a variable means the location within a program from where it can be accessed.

Visibility

Which of the following function calls is "call by reference" for the following function prototype? `int add(int*);`

`add(&x);`

Which of the following function calls is "call by reference" for the following function prototype? `float add(float*);`

`add(&x);`

Which of the function calls is call by value for the following function prototype? `float add(float);`

`add(x);`

Which of the function call is "call by value" for the following function prototype?

```
float add(int);
```

```
add(x);
```

Return type of a function that does not return any value must be _____.

```
void
```

_____ will be used for enclosing function statements into a block.

```
{}
```

What is the output of the following code if the 2nd case is true

```
switch(var){  
    case 'a': cout<<"apple"<<endl;  
    case 'b': cout<<"banana"<<endl;  
    case 'm': cout<<"mango"<<endl;  
    default: cout<<"anyfruit"<<endl;  
}
```

Banana mango anyfruit

When the break statement is encountered in a loop's body, it transfers the control _____ from the current loop.

Outside

What is the output of the following code if the 3rd case is true

```
switch(var){
```

```
case 'a':cout<<"apple"<<endl;
case'b':cout<<"banana"<<endl;
case'm':cout<<"mango"<<endl;
default: cout<<"anyfruit"<<endl;
}
```

Mangoanyfruit

What istheoutputof thefollowing code,ifthefirstcaseistrue

```
switch(var) {
case'a':cout<<"apple"<<endl;
case'b':cout<<"banana"<<endl;
case'm':cout<<"mango"<<endl;
default: cout<<"anyfruit"<<endl;
}
```

Apple banana mango anyfruit

Whatwill be theoutput of following codesegment?

```
for (inti= 2;i<10; i++){
if ( i== 5) continue;
cout<<i<<" ";
}
```

2,3,4,6,7,8,9

_____statement is used to terminate the processing of a particular case and exit from switch structure.

break

What will be the result of the expression $j = i++$; if initially $j = 0$ and $i = 5$?

5

What will be the result of the expression $k = ++m$; if initially $k = 0$ and $m =$

5

What will be the result of the expression $k = ++m$; if initially $k = 0$ and $m =$
5?

6

How many times the following do-while loop will execute?

```
int k = 10; do {cout << "Statements" << endl; k -= 2;} while(k > 0);
```

6

Which of the following loops checks the test condition at the end of the loop?

Do-While

The operators $++$ and $--$ are used to increment or decrement the value of a variable by _____.

1

How many times the following loop will execute?

```
int j= 3; while(j>0){cout<<"Statements"<<endl;j-=2;}
```

2

A _____ structure specifies that an action is to be repeated while some condition remains true.

Control

!(x > 3) means in C++ that

x is less than or equal to 3

When the logical operator && combines two expressions then the result will be true only when the both expressions are _____.

true

<and> both are _____ operators.

Relational

What will be the value of variable "input" if the initial value of input is 67?

```
if(input >= 50)
```

```
input= input+ 1;
```

```
if(input <= 75)
```

```
input= input+ 2;
```

else

input= input-1;

70

!(x <3) means in C++ that

x is greater than or equal to 3

!= operator is used to check whether the operand on the left-hand-side is _____ to the operand on the right-hand-side.

Not equal

When the statement consists of more than one statement then enclosing these statements in curly braces,

Must

The most suitable data type for number 325.25 is _____.

Float

What will be the result of arithmetic expression $6 + 48 / 4 * 3$?

42

Which of the following will be the most appropriate data type to store the value 63.547?

Float

In the given expression which operator will be evaluated first? $10 + (6 / 2) - 2 * 3$?

/

What will be the value of the variable output in the given piece of code?

```
double output = 0;
```

```
output = (2 + 2) * 4 + 2 / (4 - 2);
```

17

It is the job of _____ to transfer the executable code from hard disk to main memory.

Loader

In computer systems there are mainly _____ types of softwares.

2

_____ will explain the function of a program.

Comments

if $(a > b \ \&\& \ a > c)$ then the condition will be true only if

Both $a > b$ and $a > c$ are true

A variable of character data type occupies _____ byte(s) in memory.

1

We must include the header file _____ to convert the value of one type into another type using built-in functions.

string.h

A function is a block of statements that can be defined once and used _____ in the program.

As many times as a user wants

Select the correct way to assign the address of first element of array to pointer?

int *ptr = &data;

Consider the following code segment. What will be the output of following code?

```
int addValue (int*a){
```

```
    int b = (*a)+ 2;
```

```
    return b;
```

```
}
```

```
main(){
```

```
    int x = 6;
```

```
    cout<<addValue(&x)<<" ,";
```

```
    cout<<x;
```

```
}
```

6,8,6

Here the code is given below. You have to identify the problem in the code.

```
while(i<10)&& (i>24))
```

the test condition is always false

The correct syntax of do-while loop is _____.

```
do {statements;} while (condition);
```

Matrix is defined as _____.

Multi-dimensional array

In programming, comments are used to explain the functioning of the
_____.

Program

Operating System is a type of a/an _____.

system software

From the options given, you need to choose the option which is true for the given code.

```
for (inti= 1; i>0;i++){
```

```
/*loop code*/
```

```
}
```

the test condition is always true

Which of the following values are used in C/C++ to represent true and false?

1 and 0

'While' loop may execute _____ or more times.

zero

Body of any function is enclosed within _____.

{ }

What will be the correct syntax for initialization of a pointer ptr with string "programming"?

char *ptr = "programming";

Which one of the given options is not a mode for reading/writing the data from a file?

Get

Which of the following operators is used to access the value of variable pointed by a pointer?

*operator

In case of single dereferencing, the value of the _____ is the address of the _____.
pointer, variable

The remainder (%) operator is a _____ operator.
Arithmetic

What will be the output of following code?

```
int x = 10;  
cout << "x=" << x;  
x = 10
```

The purpose of using `cout <<` is to _____.
Display information on the screen

Which of the following data types will be assumed if no data type is specified with constant?
short

When an array element is passed to a function, it is passed by _____.
reference

While programming, it is good to provide an easy to understand and easy to use interface; this programming skill is called _____.
usability

_____executes all the lines before error and stops at the line which contains the error.

Interpreter

Which of the following is the correct syntax to access the value of first element of an array using pointer ptr?

*ptr[0]

C is a/an _____ language.

function oriented

_____ of a function is also known as signature of a function.

Declaration

_____ are very good tools for code reuse.

functions

If any break statement is missed in switch statement then _____.

this may cause a logical error

A 2D array multi[5][10] can be accessed using the array name as **multi, this technique is called _____.

Double dereferencing

In C/C++, the default command line arguments passed to the main function are _____.

int argc, char **argv

A record is a group of related _____.

Fields

The Microsoft Word document (.doc) is a kind of _____.

Random Access File

NULL character is used to indicate the _____ of string.

End

How many dimensions does an n-dimensional array have?

n dimensions

Which of the following function calls is "call by reference" for the following function prototype?

func(&num);

The loop which is most suitable to be used when the number of iterations is known is called _____.

for

In C/C++, the string constant is enclosed in _____.

double quotes ""

In order to get the right most digit of a number, we divide this number by 10 and take _____.

Its remainder

What is the correct syntax to declare an array of size 10 of int datatype?

```
int name[10];
```

How many bytes of memory are occupied by array 'str'?

```
char str[] = "programming";
```

11

Suppose that an integer type pointer contains a memory address 0x22f230. What will be the new memory address if we increment this pointer by one?

0x22f234

Which of the following if missing would result in infinite recursion in case of recursive function?

Recursive call

Whenever we use a library function or a predefined object or macro, we need to use a _____.

header file

Switch statement deals with _____ type of data.

Both Integer and Character

Both compiler and _____ are used to translate program into machine language code.

Interpreter

TWAIN stands for _____.

Technology Without An Interesting Name

The parameter passed to `isdigit()` function is _____.
a character variable

C++ views each file as a sequential stream of _____.
Bytes

Structure is a collection of _____ under a single name.
only variables

The default mode for writing into a file using `ofstream` object is _____.
out

The memory address of the first element of an array is called _____.
base address

We want to access array in random order, which of the following approach is better?

Pointer

The _____ structure is a multiple-selection construct which makes the code more efficient and easy to read and understand.

switch

Which of the following is not a reserved word in C/C++?

Sum

To access rand(), which library is required to be included in program?

stdlib.h

What is the highest legal index for the following array?

int arr[4]

3

Word processor is a type of a/an _____.

application software

Identify the correct option which is used for calling the function float area (int).

area(int num);

The _____ statement allows us to select from multiple choices based on a set of fixed values for a given expression.

switch

C is widely known as a development language of _____ operating system.

Unix

To convert the value of one type into another type using built-in functions, we include _____ header file.

stdlib.h

The keyword _____ is used to get some value back from a function.

return

The function seekg() takes _____ parameter(s).

2

The function write() takes _____ as parameter(s).

String and no. of bytes to be written

When the logical operator AND (&&) combines two expressions exp1 and exp2 then the result will be true only _____.

When both exp1 and exp2 are true

Syntax of a union is identical to _____.
structure

In Flow Chart, flow of control is represented by _____.
Arrow

There can be _____ 'default' statement(s) in any switch structure.
2

The condition in loop should be a(n) _____.
Arithmetic Expression

How many nested loops would be required to manipulate an n -dimensional array?
 2^n

Which of the following is not an example of int datatype?
-4

We should use _____ for clarity and to force the order of evaluation in an expression.
parenthesis()

Which of the following is the starting index of an array in C++?

0

The statement $x += y$ can be interpreted as _____.

Adding the value of x to the value of y and storing the result in x

Given a 2D array of integers, what would be the correct way of assigning the value 5 to the element at second row and third column?

`m[1][2] = 5;`

Array is a data structure that stores _____.

Variables

A program statement that invokes a function is called _____.

function call

The compiler of C language is written in _____ language.

C

Which function is used to locate the first occurrence of a character in any string?

`strlen()`

To access the data members of structure, _____ is used.

Dot operator

In the following nested For Loop, which loop will run most number of times?

```
for( inti= 0;i< 5; i++)  
{  
    for(intk = 0;k< 5;k++)  
    {  
        .....  
    }  
}
```

Depends upon the statements in the inner loop's body

Structure use _____ allocation.

Heap

_____ function give the position of the next character to be read from that file.

tellp()

What will be the size of the following character array?

```
char name[] = "Adeel";
```

5

Function prototype is written,

Before call of that function

Which one of the following languages has been used to write the compiler of "C" language?

C

A hierarchy of classes which are used to deal with console and disk files are called _____.

Stream classes

_____ stop execution at the line that contains error(s) in the code.

Interpreter

C++ is a _____ language.

High level

How many elements are stored in the following?

int matrix [4][5];

20

_____ is a substitute of multiple if statement.

if. . . else if statement

if

int sum= 54;

Then the value of the following statement is

sum= sum-3;

51

What will be the correct syntax for declaration of the following statement?

"ptr is a constant pointer to an integer"

const int *myptr;

_____ operator is used to pass the address of a variable in call by reference method.

&

_____ data type can operate on modulus operator.

int

Whenever some number is added in an array name, it will jump as many _____ as the added number.

rows

Suppose that an integer type pointer contains a memory address 0x22f220. What will be the new memory address if we increment this pointer by one?

0x22f224

_____ is the pointer which determines the position in a file from where the next read operation occurs.

put

what is the correct context to declare an array of 15 elements of type float?

float array [14]

suppose we have a file with name "mylife.txt". what will be the correct syntax of file opening for input?

my file ("myfile.txt".ios::in)

which of the following will be the most appropriate data type to store the value 63.547?

Float

----- will explain the function of a program

Comments

these functions Seekg() and seekp() requires an argument of type -----
--to let them know many bites to move forward or backward

Int

all elements of an array must be of ----- data type

Same

what will be the result of arithmetic expression $6 + 48 / 4 * 3$?

42

-----allowusto have a memory location and use it as int or char interchangeably

none of the given

accessing a structure member the identifier to the left of the dot operator is the name of-----

structural variable

<and> both are-----operators

Arithmetic

what will be the output of the following code segment?

```
For(int= 2;i<10; i++){
```

```
    If( i= 5 )
```

```
        Continue;
```

```
    cout<<i<<“.”;
```

```
}
```

2,3,4,5,6,7,8,9

-----return true if it is a digit or a letter and false otherwise

int isalnum(int c)

if a----findanerror,it stop translating withoutgenerating anyE
executablecode

Compiler

theASCIIcode ofnull characteris-----

000

if X= 9;then theexpressionsx%=2;will calculatethevalue of x as-----

-

1

theoriginalvaluemeansunchangedin -----

CallbyValue

whichof thefollowing isused tocreatean accountstream?

Ofstream

howmanytimesthefollowing loopwillexecute?

Int j= 3;

While (j>0)

{

Cout<<"statements"<<endl;

J-= 2;

}

2

Use of word processor for writing the code of a program is not good because-----

It has less feature for writing code of a program

How many bytes and integer type pointer `intptr` will jump in memory if the statement below is executed?

`Intptr += 2;`

8

A void loop may execute ----- or more times

0

raid stands for-----

redundant array of inexpensive dices

In a file is opened with `iOS:: outmode`, then-----

A new file is created

First step in designing a program is

Analysis

What will be the result of the expression

`J = i++`

If initially j= 0 and i = 5?

5

suppose we have int y [10];

to access the 4th element of the array b write-----

Y [3];

A -----structure specifies that an action is to be repeated while some condition remains true

Control

the most suitable data type for number 325.25 is-----

float

Which one of the following should be placed immediately either before or after the noun?

Modifiers of Nouns

Title typically include both.....

a number and a description

For what purposes are colons used?

All of the above

The name of the array is a constant pointer which contains the memory address of the _____ of the array.

first element

What will be the correct syntax for the following function call? float add (int&);

add(x);

In C/C++; by default arguments are passed by _____ to a function.

Value

<, <=, >, >= are called _____ operators.

Relational

char name[] = "HelloWorld"; In the above statement, a memory of _____ characters will be allocated

12

While developing a program; should we think about the reusability?

Yes

C is widely known as a development language of _____ operating system.

Unix

Which of the following function call is "call by reference" for the following function prototype? `int add(int*);`

`add(&x);`

If a function has not been declared before its definition, it is a

None of these

While loop executes at least----

Zero time

A _____ is a precise sequence of steps to solve a particular problem.

Program

In while loop the loop counter must be initialized,

Before entering the loop

```
int counter=0 ;
```

```
while(counter<15)
```

```
cout<< counter<<" ";
```

```
counter++;
```

Infiniteloop



6th file confirm correct

Remember own prayer

For More Visit VUStudents.pk

CS201 Midterm McQs Solved Papers By Waqar Siddiqui (File 1)

Question No 1

Consider the following code segment. What will be the output of following code?

```
int addValue (int*a){  
    int b = (*a) + 2;  
    return b;  
}  
main() {  
    int x=6;  
    cout<< x<< “,”;  
    cout<<addValue(&x) << “x”;
```

✓ 6,8,6.....(For More Visit VUStudents.pk)

- ✓ The logical operator && cannot be used in a test condition
- ✓ The while loop is an exit-condition loop
- ✓ The test condition is always true
- ✓ **The test condition is always false.....(For More Visit VUStudents.pk)**

- ✓ (condition) while; do ({statement,};
- ✓ {statement;} do-while ();
- ✓ while(condition); do {statement};
- ✓ **do {statements;} while (condition);(For More Visit VUStudents.pk)**

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 4

Matric is defined as _____.

Select Correct Option

- ✓ Single dimensional array
- ✓ **Multi-dimensional array.....(For More Visit VUStudents.pk)**
- ✓ Vector product

Question NO 6

Operating System is a type of a/an _____.

From the options given, you need to choose the option which is true for the given code.

```
for (int i = 1; i > 1; i++) {  
    /* loop code */  
}
```

Question NO 8

Which of the following value are used in C/C++ to represent true and false?

Select Correct Option

- ✓ **1 and 0.....(For More Visit VUStudents.pk)**
- ✓ 1 and -1
- ✓ 11 and 00
- ✓ Any numerical value

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 9

'while' loop may execute _____ or more times.

Select Correct Option

- ✓ Three
- ✓ **Zero.....(For More Visit VUStudents.pk)**
- ✓ Two
- ✓ Once

- ✓ **{ }.....(For More Visit VUStudents.pk)**
- ✓ ()
- ✓ []
- ✓ ""

What will be the correct syntax for initialization of a pointer ptr string "programming"?

Which one of the given option is not a mode for reading/writing the data from a file?

Question NO 13

_____ mode allows us to add data or change data anywhere in the file.

Select Correct Option

- ✓ **ios::ate.....(For More Visit VUStudents.pk)**
- ✓ ios::app
- ✓ ios::binary
- ✓ ios::edit

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 14

In C/C++, _____ are the doors through which data can enter and come out of a program.

Select Correct Option

- ✓ Streams.....(For More Visit VUStudents.pk)
- ✓ Fields
- ✓ Variables
- ✓ Header files

- ✓ String of variable lengths no. of bytes to be read and flags
- ✓ Pointer array of characters and a delimiter
- ✓ String and no. of bytes to be written.....(For More Visit VUStudents.pk)

Select Correct Option

When the logical operator AND (&&) combines two expression exp1 and exp2 then the result will be true only _____.

Select Correct Option

- ✓ When both exp1 and exp2 are true.....(For More Visit VUStudents.pk)
- ✓ When both exp1 and exp2 are false
- ✓ When exp1 is true and exp2 is false
- ✓ When exp1 is false and exp2 is true

For More Visit VUStudents.pk

For More Visit VUStudents.pk

(File 2)

Question No 1

The operators ++ and – are used to increment or decrement the variable by _____.

Select Correct Option

- ✓ 3
- ✓ 2

Question NO 2

Which of the following operators is used to access the value of variable pointed by a pointer?

In case of single dereferencing, the value of the _____ is the address of the _____.

Select Correct Option

Question NO 4

The remainder (%) operator is a _____ operator.

Select Correct Option

- ✓ Arithmetic.....(For More Visit VUStudents.pk)
- ✓ Relational
- ✓ Conditional

Question NO 5

What will be the out of following code?

```
int x = 10;  
cout << "x=" << x;
```

Select Correct Option

- ✓ 10
- ✓ "x=10"(For More Visit VUStudents.pk)
- ✓ X=10
- ✓ 10=x

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 6

The purpose of using cout<< is to _____.

Select Correct Option

- ✓ **Display information on the screen.....(For More Visit VUStudents.pk)**
- ✓ Read the data from keyboard
- ✓ Read the data from a file

Which of the following data types will be assumed if no data type is specified with constant?

When an array element is passed to a function, it is passed by _____.

- ✓ **reference.....(For More Visit VUStudents.pk)**

While programming, it is good to provide an easy to understand and easy to use interface, this programming skill is called_____.

_____ executes all the lines before error and stops at the line which contains the error.

Select Correct Option

- ✓ **interpreter.....(For More Visit VUStudents.pk)**
- ✓ compiler
- ✓ linker
- ✓ debugger

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 11

Which one of the following is the correct syntax to access the value of first element of an array using pointer ptr?

Select Correct Option

- ✓ ptr[0]
- ✓ *(ptr+1)
- ✓ Ptr[1]

Question NO 13

_____ of a function is also known as signature of a function.

- ✓ Declaration.....(For More Visit VUStudents.pk)
- ✓ Calling
- ✓ Invoking

Question NO 15

If any break statement is missed in switch statement then_____.

Select Correct Option

- ✓ Compiler will give error
- ✓ This may cause a logical error.....(For More Visit VUStudents.pk)
- ✓ No effect on program
- ✓ Program stops its execution

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 16

A 2D array multi[5][10] can be accessed using the array name as **multi, this technique is called _____.

Select Correct Option

- ✓ Single referencing
- ✓ Single dereferencing
- ✓ Double referencing
- ✓ **Double dereferencing.....(For More Visit VUStudents.pk)**

In C/C++, the default command line arguments passed to the main function are _____.

- ✓ float argc, char**argv
- ✓ **int argc, char**argv.....(For More Visit VUStudents.pk)**
- ✓ int *argc, char**argv

- ✓ **Data.....(For More Visit VUStudents.pk)**

Question NO 19

The Microsoft word document(.doc) is a kind of _____.

- ✓ Sequential File
- ✓ **Random Access File.....(For More Visit VUStudents.pk)**
- ✓ Binary Access File

Question NO 20

Null character is used to indicate the _____ of string.

Select Correct Option

- ✓ Start
- ✓ **End.....(For More Visit VUStudents.pk)**
- ✓ Begin
- ✓ Middle

For More Visit VUStudents.pk

For More Visit VUStudents.pk

(File 3)

Question No 1

How many dimension does n-dimensions does n-dimensional array has?

Select Correct Option

- ✓ **n dimensions.....(For More Visit VUStudents.pk)**
- ✓ 2n dimensions
- ✓ (n+1) dimensions

Question NO 2

Which of the following function call is “call by reference” for the following function prototype?
void func (int *) ;

- ✓ func(int & num);
- ✓ **func(&num);.....(For More Visit VUStudents.pk)**
- ✓ func(*num);

The operators ++ and – are used to increment or decrement the variable by _____.

- ✓ 3
- ✓ **2**

The loop which is most suitable to be used when the number of iterations is known as is called_____.

- ✓ all looping processes require that the iterations be known

Question NO 5

In C/C++, the string constant is enclosed in _____.

Select Correct Option

- ✓ curly braces { }
- ✓ parentheses()
- ✓ single quotes ‘ ’
- ✓ **double quotes ” ” (For More Visit VUStudents.pk)**

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 6

In order to get the right most digit of a number, we divide this number by 10 and take_____.

Select Correct Option

- ✓ its remainder.....(For More Visit VUStudents.pk)
- ✓ its quotient
- ✓ its divisor
- ✓ the number

Question NO 7

What is the correct syntax to declare an array of size 10 of int data type?

- ✓ `int[10] name;`
- ✓ `name [10] int;`
- ✓ **`int name[10];`(For More Visit VUStudents.pk)**
- ✓ `int name[];`

Question NO 8

How many bytes of memory are occupied by array 'str'?

`char str[] = "programming";`

- ✓ 10
- ✓ **11.....(For More Visit VUStudents.pk)**
- ✓ 12
- ✓ 13

When the if statement consists more than one statement the enclosing these statement in curly braces is,

Select Correct Option

- ✓ Not required

Suppose that an integer contains a memory address 0x22f230. What will be the new memory address if we increment this pointer by one?

Select Correct Option

- ✓ 0x22f231
- ✓ **0x22f234.....(For More Visit VUStudents.pk)**
- ✓ 0x22f226
- ✓ 0x22f238

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 11

Which of the following if missing would result in infinite recursion in case of recursive function?

Select Correct Option

- ✓ **Recursive call.....(For More Visit VUStudents.pk)**
- ✓ Base case
- ✓ Function parameters

Whenever we use a library function or a predefined object or macro, we need to use a _____.

- ✓ Source file
- ✓ Object file
- ✓ **Header file.....(For More Visit VUStudents.pk)**
- ✓ Exe file

Both compiler and _____ are used to translate program into machine language code.

Select Correct Option

Select Correct Option

- ✓ Technology With An Interesting Name
- ✓ Technology Without An Informative Name
- ✓ **Technology Without An informative Name.....(For More Visit VUStudents.pk)**
- ✓ Technology With An Informative Name

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 16

The parameter passed to isdigit() function is _____.

Select Correct Option

- ✓ **A character variable.....(For More Visit VUStudents.pk)**
- ✓ A Boolean variable
- ✓ An integer variable

- ✓ **Only variables.....(For More Visit VUStudents.pk)**
- ✓ Both functions and variables
- ✓ Only data types

- ✓ **out.....(For More Visit VUStudents.pk)**
- ✓ bin
- ✓ app
- ✓ ate

Question NO 20

The Microsoft word document(.doc) is a kind of _____.

Select Correct Option

- ✓ Sequential File
- ✓ **Random Access File.....(For More Visit VUStudents.pk)**
- ✓ Binary Access File
- ✓ Executable File

For More Visit VUStudents.pk

For More Visit VUStudents.pk

(File 4)

Question No 1

The memory address of the first element of an array is called.

Select Correct Option

- ✓ Float address
- ✓ Foundation address
- ✓ First address
- ✓ **Base address.....(For More Visit VUStudents.pk)**

Question NO 2

The _____ structure is a multiple-selection construct which makes the code more efficient and easy to read and understand.

- ✓ multiple=if
- ✓ **switch.....(For More Visit VUStudents.pk)**
- ✓ if-else
- ✓ else-if

- ✓ **sum.....(For More Visit VUStudents.pk)**

Question NO 5

To access rand(), which library is required to be included in program?

Select Correct Option

- ✓ conio.h
- ✓ stdio.h
- ✓ **stdlib.h.....(For More Visit VUStudents.pk)**
- ✓ iostream.h

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 6

What is the highest legal index for the following array?
`int arr[4]`

Select Correct Option

- ✓ 4
- ✓ 3.....(For More Visit VUStudents.pk)
- ✓ 2
- ✓ 1

While programming, it is good to provide an easy to understand and easy to use interface, this programming skill is called_____.

Question NO 9

Word processor is a type of a/an _____.

Question NO 10

‘while’ loop may execute _____ or more times.

Select Correct Option

- ✓ Three
- ✓ Zero.....(For More Visit VUStudents.pk)
- ✓ Two
- ✓ Once

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 11

The keyword _____ is used to get some value back from a function.

Select Correct Option

- ✓ **return.....**(For More Visit VUStudents.pk)
- ✓ break
- ✓ continue
- ✓ goto

- ✓ area(&num);
- ✓ area(num);
- ✓ **area(int num);**(For More Visit VUStudents.pk)
- ✓ area(*num);

The _____ statement allows us to select from multiple choices based on a set of fixed values for a given expression.

- ✓ **switch.....**(For More Visit VUStudents.pk)

Question NO 14

C is widely known as development language of _____ operating system.

- ✓ Windows
- ✓ **Unix.....**(For More Visit VUStudents.pk)
- ✓ Mac OS
- ✓ Linux

To convert the value of one type into another using built-in functions, we include _____ header file.

Select Correct Option

- ✓ conio.h
- ✓ **stdlib.h.....**(For More Visit VUStudents.pk)
- ✓ iostream.h
- ✓ string.h

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 16

Syntax of a union is identical to _____.

Select Correct Option

- ✓ **structure.....(For More Visit VUStudents.pk)**
- ✓ class
- ✓ function
- ✓ loop

- ✓ 0
- ✓ 1

- ✓ String of variable lengths no. of bytes to be read and flags
- ✓ Pointer array of characters and a delimiter
- ✓ **String and no. of bytes to be written.....(For More Visit VUStudents.pk)**

When the logical operator AND (&&) combines two expression exp1 and exp2 then the result will be true only _____.

- ✓ **When both exp1 and exp2 are true.....(For More Visit VUStudents.pk)**
- ✓ When both exp1 and exp2 are false
- ✓ When exp1 is true and exp2 is false
- ✓ When exp1 is false and exp2 is true

Question NO 20

Null character is used to indicate the _____ of string.

Select Correct Option

- ✓ Start
- ✓ **End.....(For More Visit VUStudents.pk)**
- ✓ Begin
- ✓ Middle

For More Visit VUStudents.pk

For More Visit VUStudents.pk

(File 5)



Question No 1

Which one of the symbol is used to represent a decision in a flow chart?



Select Correct Option



✓ Arrow.....(For More Visit VUStudents.pk)

Question NO 3

There can be _____ 'default' statement(s) in any switch structure.

Select Correct Option

✓ 1

- ✓ Constant Expression
- ✓ Boolean Expression
- ✓ Primary Expression
- ✓ Arithmetic Expression.....(For More Visit VUStudents.pk)

Question NO 5

How many nested loops would be required to manipulate n-dimensional array?

Select Correct Option

- ✓ n
- ✓ n + 1
- ✓ n - 1
- ✓ 2n.....(For More Visit VUStudents.pk)

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 6

Which of the following is not an example of int data type?

Select Correct Option

- ✓ 0
- ✓ -32
- ✓ 65531
- ✓ -4.0.....(For More Visit VUStudents.pk)

We should use _____ for clarity and to force the order of evaluation in an expression.

- ✓ Parenthesis ()(For More Visit VUStudents.pk)
- ✓ Curly braces { }
- ✓ Quotation marks “ ”

- ✓ 1
- ✓ -1
- ✓ 2

Select Correct Option

- ✓ Adding the value of the x to the value of the y and storing the result in x
- ✓ Adding the value of the y to the value of the x, store the result in y
- ✓ Adding the value of the x to the value of the x, store the result in x
- ✓ Adding the value of the y to the value of the y, store the result in x

Given a 2D array of integers, what would be the correct way of assigning the value 5 to the element at second row and third column?

Select Correct Option

- ✓ `m[2][3] = 5;`(For More Visit VUStudents.pk)
- ✓ `m[3][2] = 5;`
- ✓ `m[1][2] = 5;`
- ✓ `m[2][3] = '5';`

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 11

Array is a data structure that stores _____.

Select Correct Option

- ✓ Memory address
- ✓ **Variables.....(For More Visit VUStudents.pk)**
- ✓ Data type
- ✓ Data

Question NO 12

A program statement that invokes a function is called _____.

If a function has been declared but not defined before its function call then it is termed as _____.

- ✓ BASIC
- ✓ FORTRON
- ✓ **C.....(For More Visit VUStudents.pk)**

To convert the value of one type into another type using built-in function, we include _____ header file.

Select Correct Option

- ✓ conio.h
- ✓ **stdlib.h.....(For More Visit VUStudents.pk)**
- ✓ iostream.h
- ✓ string.h

For More Visit VUStudents.pk

For More Visit VUStudents.pk

Question NO 16

Which one of the below functions is not included in ctype.h header file?

Select Correct Option

- ✓ isdigit(int c)
- ✓ isxdigit (int c)
- ✓ tolower(int c)
- ✓ **getdidit(int c)(For More Visit VUStudents.pk)**

- ✓ String of variable lengths no. of bytes to be read and flags
- ✓ Pointer array of characters and a delimiter
- ✓ **String and no. of bytes to be written.....(For More Visit VUStudents.pk)**

_____ is the pointer which determines the position in a file from where the next read

Given a 2D array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?

Select Correct Option

- ✓ m[2][3] = 6;
- ✓ **m[3][4] = 6;(For More Visit VUStudents.pk)**
- ✓ m[2][4] = 6;
- ✓ m[4][3] = 6;

7th file correct

Question No: 1 (Marks: 1) - Please choose one
In order to get 256 from the number 2568 we divide this number by 10 and take,

- ▶ Its remainder
- ▶ The number
- ▶ **Its quotient**
- ▶ Its divisor

Question No: 2 (Marks: 1) - Please choose one
The correct syntax of do-while loop is,

- ▶ (condition) while; do { statements; };
- ▶ { statements; } do-while ();
- ▶ while(condition); do { statements; };
- ▶ **do { statements; } while (condition);**

Question No: 3 (Marks: 1) - Please choose one
Which of the following function(s) is/are included in stdlib.h header file?

- ▶ double atof(const char *nptr)
- ▶ int atoi(const char *nptr)
- ▶ char *strcpy (char *s1, const char *s2)
- ▶ **1 and 2 only (Pg 191)**

Question No: 4 (Marks: 1) - Please choose one
If the break statement is missed in switch statement then,

- ▶ The compiler will give error
- ▶ **This may cause a logical error (Pg 76)**
- ▶ No effect on program
- ▶ Program stops its execution

Question No: 5 (Marks: 1) - Please choose one
The data type before a function name represents its,

- ▶ Return Type (Pg 499)
- ▶ Function data
- ▶ Function arguments
- ▶ Function name

Question No: 6 (Marks: 1) - Please choose one
Member function tellg() returns the current location of the _____ pointer.

- ▶ tellptr()
- ▶ write()
- ▶ seekg()
- ▶ get() (Pg 215)

Question No: 7 (Marks: 1) - Please choose one
What does $5 | 6$, evaluate to in decimal where '|' is bitwise OR operator?

☐ ▶ ☐

3

☐ ▶ ☐

4

☐ ▶ ☐

5 | 6 =

0 1 0 1

0 1 1 0

0 1 1 1 = 7

Question No: 8 (Marks: 1) - Please choose one

known as development language of _____ operating system.

- ▶ Linux
- ▶ Windows
- ▶ Unix (Pg 12)
- ▶ Mac OS

Question No: 9 (Marks: 1) - Please choose one

the result of arithmetic expression $6 + 27 / 3 * 3$?

- ▶ 33
- ▶ 45
- ▶ 9

► 30

Question No: 10 (Marks: 1) - Please choose one

bytes are occupied by declaring following array of characters?

char str[] = "programming";

► 10

► 11

► 12

► 13

Question No: 11 (Marks: 1) - Please choose one

the correct syntax for initialization of pointer ptr with string "programming"?

► char ptr = 'programming' ;

► char *ptr = "programming" ;

► char *ptr = 'programming' ;

► *ptr = "programming" ;

Question No: 12 (Marks: 1) - Please choose one

What will be the result of expression $x\%2$, if $x = 7$?

► $x = 1$

► 3

► 7

► 2

Question No: 13 (Marks: 1) - Please choose one

UNIX has been developed in _____ language.

► JAVA

► B

► C (pg 12)

► FORTRAN

N

Question No: 14 (Marks: 1) - Please choose one

Declaring structures does not mean that memory is allocated.

► True (Pg 229)

► False

e

Question No: 15 (Marks: 1) - Please choose one
What will be the value of i and j in the following code segment?

```
int i, j ;  
int x[5] = {2, 3, 4, 8, 9} ;  
int *ptr =&x[2];  
i = (*ptr)++ ;  
j = *ptr++ ;
```

☒ i = 5, j = 5

☐ i = 5, j = 8

☒ i = 4, j = 8

☐ i = 5, j = 9

Question No: 16 (Marks: 1) - Please choose one
When an array element is passed to a function, it is passed by -----.

☒ reference (Pg 266)

☐ data type

☐ value

☐ data

Question No: 1 (Marks: 1) - Please choose one
What is the output of the following statement?

```
int i = 2.5; do { cout << i * 2; } while (i > 3 && i < 10);
```

(a) 510

(b) 5

(c) 48

(d) error

Question No: 2 (Marks: 1) - Please choose one
What does !(7) evaluate to in decimal where ! is a NOT operator?

(a) 7

(b) 8

(c) 9

(d) 10

Question No: 3 (Marks: 1) - Please choose one

The condition in while loop may contain logical expression but not relational expression

(a) True

(b) False

Question No: 4 (Marks: 1) - Please choose one

Searching is easier when an array is already sorted

(a) True

(b) False

Question No: 5 (Marks: 1) - Please choose one

If an array has 100 elements, what is allowable range of subscripts?

(a) 0 - 99

(b) 1 - 99

(c) 0 - 100

(d) 1 - 100

Question No: 6 (Marks: 1) - Please choose one

What will be the value of 'a' and 'b' after executing the following statements?

a = 3;

b = a++;

(a) 3, 4

(b) 4, 4

(c) 3, 3

(d) 4, 3

Question No: 7 (Marks: 1) - Please choose one

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

(a) `int arr[2][3] = {0,0} ;`

(b) `int arr[2][3] = {{0},{0}} ;`

(c) `int arr[2][3] = {0},{0} ;`

(d) `int arr[2][3] = {0} ;`

Question No: 8 (Marks: 1) - Please choose one

Which of the following function returns the size of a string variable?

(a) `strlen()`

(b) `stringlen()`

(c) `strlen()`

(d) `strLength()`

Question No: 9 (Marks: 1) - Please choose one

What will be the range of numbers generated by function `rand () % 9`?

- (a) 0 to 9
- (b) 1 to 9
- (c) 0 to 8
- (d) 1 to 8

Question No: 11 (Marks: 1) - Please choose one

Computer can understand only machine language code.

- (c) True
- (d) False

Question No: 13 (Marks: 1) - Please choose one

What does $5 \wedge 6$, evaluate to in decimal where '^' is Exclusive OR operator?

- (a) True
- (b) False

Detail:-

It mean

$5 = 0101$

$6 = 0110$

$5 \wedge 6 = 0011$

If both input is same then the output is 0 and if different then output is 1

Question No: 14 (Marks: 1) - Please choose one

If the file is not properly closed in the program, the program _____.

- (a) Terminate normally
- (b) Indicate Runtime error
- (c) Indicate Compile time error
- (d) Crashes

Question No: 15 (Marks: 1) - Please choose one

Which of the following header file include string conversion functions?

- (a) `string.h`
- (b) `stdlib.h` (Pg 190)
- (c) `ctype.h`
- (d) `sconvert.h`

Question No: 1 (Marks: 1) - Please choose one

A precise sequence of steps to solve a problem is called

- ☐ Statement
- ☒ Program
- ☐ Utility
- ☐ Routine

Question No: 2 (Marks: 1) - Please choose one

The Compiler of C language is written in

- ☐ Java Language
- ☐ UNIX
- ☐ FORTRON Language
- ☒ C Language

Question No: 3 (Marks: 1) - Please choose one

Initialization of variable at the time of definition is,

- ☐ Must
- ☐ Necessary
- ☒ Good Programming
- ☐ None of the given options

Question No: 4 (Marks: 1) - Please choose one

In if structure the block of statements is executed only,

- ☐ When the condition is false
- ☐ When it contain arithmetic operators
- ☐ When it contain logical operators
- ☒ When the condition is true

Question No: 6 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

- ☒ True
- ☐ False

Question No: 7 (Marks: 1) - Please choose one

Pointer is a variable which store,

- ☐ Data
- ☒ Memory Address
- ☐ Data Type
- ☐ Values

Question No: 8 (Marks: 1) - Please choose one

Preprocessor program perform its function before _____ phase takes place.

- ☐ Editing

- ☐ Linking
- ☒ Compiling
- ☐ Loading

Question No: 9 (Marks: 1) - Please choose one
Which of the following can not be a variable name?

- ☐ area
- ☐ _area
- ☒ 10area
- ☐ area2

Question No: 10 (Marks: 1) - Please choose one
Which looping process is best, when the number of iterations is known?

- ☒ for
- ☐ while
- ☐ do-while
- ☐ all looping processes require that the iterations be known
- ☐

Question No: 11 (Marks: 1) - Please choose one
Which character is inserted at the end of string to indicate the end of string?

- ☐ new line
- ☐ tab
- ☒ null
- ☐ carriage return

Question No: 13 (Marks: 1) - Please choose one
Which of the following header file defines the rand() function?

- ☐ iostream.h
- ☐ conio.h
- ☒ stdlib.h
- ☐ stdio.h

Question No: 14 (Marks: 1) - Please choose one
Commenting the code _____

- ☒ Makes a program easy to understand for others.
- ☐ Make programs heavy, i.e. more space is needed for executable.
- ☐ Makes it difficult to compile
- ☐ All of the given options.

Question No: 15 (Marks: 1) - Please choose one
What's wrong with this for loop?
for (int k = 2, k <=12, k++)

- ☐ the increment should always be ++k
- ☐ the variable must always be the letter i when using a for loop
- ☐ there should be a semicolon at the end of the statement
- ☒ the commas should be semicolons

Question No: 16 (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

- ☐ int
- ☐ double
- ☐ float
- ☒ char

Question No: 2 (Marks: 1) - Please choose one

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- ▶ cplex.h
- ▶ **ctype.h (Pg 188)**
- ▶ stdio.h
- ▶ delay.h

Question No: 3 (Marks: 1) - Please choose one

How many parameter(s) function getline() takes?

- ▶ 0
- ▶ 1
- ▶ 2
- ▶ **3**

► Utility software

Question No: 5 (Marks: 1) - Please choose one

For which values of the integer _value will the following code becomes an infinite loop?

```
int number=1;
while (true) {
cout << number;
if (number == 3) break;
number += integer_value; }
```

► any number other than 1 or 2

► only 0

► only 1

► only 2

Rational:

Question No: 6 (Marks: 1) - Please choose one

Each pass through a loop is called a/an

► enumeration

► Iteration

► culmination

► pass through

Question No: 7 (Marks: 1) - Please choose one

A continue statement causes execution to skip to

► the return 0; statement

► the first statement after the loop

► the statements following the continue statement

► the next iteration of the loop

Question No: 8 (Marks: 1) - Please choose one

What is the correct syntax to declare an array of size 10 of int data type?

► int [10] name ;

► name[10] int ;

► int name[10] ;

► int name[] ;

Question No: 9 (Marks: 1) - Please choose one

Consider the following code segment. What will the following code segment display?

```
int main(){
int age[10] = {0};
cout << age ;
```

}

- ▶ Values of all elements of array
- ▶ Value of first element of array
- ▶ Starting address of array
- ▶ Address of last array element

Question No: 11 (Marks: 1) - Please choose one

How many bytes will the pointer intPtr of type int move in the following statement?

intPtr += 3 ;

- ▶ 3 bytes
- ▶ 6 bytes
- ▶ 12 bytes
- ▶ 24 bytes

Question No: 12 (Marks: 1) - Please choose one

If there are $2(n+1)$ elements in an array then what would be the number of iterations required search a number using binary search algorithm?

- ▶ n elements
- ▶ $(n+1)$ elements
- ▶ $2(n+1)$ elements
- ▶ $2(n+1)$ elements

Question No: 13 (Marks: 1) - Please choose one

Which of the following operator is used to access the value of variable pointed to by a pointer?

- ▶ * operator
- ▶ -> operator
- ▶ && operator
- ▶ & operator

Question No: 14 (Marks: 1) - Please choose one

The _____ statement interrupts the flow of control.

- ▶ switch
- ▶ continue
- ▶ goto
- ▶ break

Question No: 15 (Marks: 1) - Please choose one

Analysis is the ----- step in designing a program

- ▶ Last
- ▶ Middle
- ▶ Post Design
- ▶ First

Question No: 16 (Marks: 1) - Please choose one

Paying attention to detail in designing a program is _____

- ▶ Time consuming

- ▶ Redundant
- ▶ **Necessary**
- ▶ Somewhat Good

Question No: 1 (Marks: 1) - Please choose one_____

There are mainly----- types of software

- ▶ **Two**
- ▶ Three
- ▶ Four
- ▶ Five

Question No: 2 (Marks: 1) - Please choose one_____

In C/C++ the #include is called,

- ▶ Header file
- ▶ **Preprocessor Directive (Pg 15)**
- ▶ Statement
- ▶ Function

Question No: 3 (Marks: 1) - Please choose one_____

&& is----- operator.

- ▶ An arithmetic
- ▶ **Logical**
- ▶ Relational
- ▶ Unary

Question No: 4 (Marks: 1) - Please choose one_____

In flow chart, the symbol used for decision making is,

- ▶ Rectangle
- ▶ Circle
- ▶ Arrow
- ▶ **Diamond (Pg 51)**

Question No: 6 (Marks: 1) - Please choose one_____

C++ views each file as a sequential stream of_____ .

- ▶ **Bytes**

- ▶ Bits
- ▶ 0's or 1's
- ▶ Words

Question No: 7 (Marks: 1) - Please choose one_____

If the elements of an array are already sorted then the useful search algorithm is,

- ▶ Linear search
- ▶ **Binary search (Pg 188)**
- ▶ Quick search
- ▶ Random search

Question No: 8 (Marks: 1) - Please choose one_____

The address operator (&) can be used with,

- ▶ Statement
- ▶ Expression
- ▶ **Variable**
- ▶ Constant

Question No: 9 (Marks: 1) - Please choose one_____

When a pointer is incremented, it actually jumps the number of memory addresses

- ▶ **According to data type (Pg 160)**
- ▶ 1 byte exactly
- ▶ 1 bit exactly
- ▶ A pointer variable can not be incremented

Question No: 11 (Marks: 1) - Please choose one_____

Call by reference mechanism should be used in a program when there is

- i. large amount of data to be passed
- ii. small amount of data to be passed
- iii. need to change the passed data
- iv. no need to change the passed data

Choose the appropriate option for the above case.

- ▶ (i) and (ii) only
- ▶ **(i) and (iii) only**
- ▶ (ii) and (iii) only
- ▶ (ii) and (iv) only

Question No: 12 (Marks: 1) - Please choose one_____

Which of the following is the starting index of an array in C++?

- ▶ **0**
- ▶ 1
- ▶ -1
- ▶ any number

Question No: 13 (Marks: 1) - Please choose one _____
The return type of a function that do not return any value must be _____

- ▶ int
- ▶ void
- ▶ double
- ▶ float

Question No: 14 (Marks: 1) - Please choose one _____
Which of the following is an extension of header file?

- ▶ .exe
- ▶ .txt
- ▶ .h
- ▶ .c

Question No: 15 (Marks: 1) - Please choose one _____
We want to access array in random order which approach is better?

- ▶ Pointers
- ▶ Array index (Pg 176)
- ▶ Both pointers and array index are better
- ▶ None of the given options.

Question No: 16 (Marks: 1) - Please choose one _____
When we declare a multidimensional array the compiler store the elements of multidimensional form of,

- ▶ Columns
- ▶ Rows
- ▶ Contiguous memory location (Pg 174)
- ▶ Matrix

Question No: 1 (Marks: 1) - Please choose one

In C/C++ the string constant is enclosed

- ▶ In curly braces
- ▶ In small braces
- ▶ In single quotes
- ▶ In double quotes

Question No: 2 (Marks: 1) - Please choose one
The size of int data type is

- ▶ 1 bytes
- ▶ 2 bytes
- ▶ 3 bytes
- ▶ 4 bytes (Pg 257)

Question No: 3 (Marks: 1) - Please choose one
In Flow chart process is represented by

- ▶ Rectangle (Pg 51)
- ▶ Arrow symbol
- ▶ Oval
- ▶ Circle

Question No: 5 (Marks: 1) - Please choose one
When we are using const keyword with a variable x then initializing it at the time of declaration

- ▶ Must
- ▶ Optional
- ▶ Not necessary
- ▶ A syntax error

Question No: 6 (Marks: 1) - Please choose one
Which of the following is the correct way to assign an integer value 5 to element of a matrix sa
'm' at second row and third column?

- ▶ $m[2][3] = 5 ;$
- ▶ $m[3][2] = 5 ;$
- ▶ $m[1][2] = 5 ;$
- ▶ $m[2][3] = '5' ;$

Question No: 7 (Marks: 1) - Please choose one
How many total elements must be in two-dimensional array of 3 rows and 2 columns?

- ▶ 4
- ▶ 5
- ▶ 6 ($3*2=6$)
- ▶ 7

Question No: 8 (Marks: 1) - Please choose one

Which of the following is the correct statement for the following declaration?

const int *ptr.

- ☐ ptr is a constant pointer
- ☐ ptr is constant integer pointer
- ☐ ptr is a constant pointer to int
- ☒ ptr is a pointer to const int

Question No: 9 (Marks: 1) - Please choose one

Consider the following code segment. What will be the output of this code segment?

```
int arr[6] = {2, 3, 7, 4, 5, 6} ;  
int *ptr1 = &arr[1] ;  
int *ptr2 = &arr[4] ;  
cout << (ptr2 - ptr1) ;
```

- ▶ 3
- ▶ 9
- ▶ 12
- ▶ 2

Question No: 10 (Marks: 1) - Please choose one

What will be the correct syntax to assign an array named arr of 5 elements to a pointer ptr?

- ▶ *ptr = arr ;
- ▶ ptr = arr ;
- ▶ *ptr = arr[5] ;
- ▶ ptr = arr[5] ;

Question No: 11 (Marks: 1) - Please choose one

C is a/an _____ language

- ▶ low level
 - ▶ object based
 - ▶ object oriented
 - ▶ function oriented
- (Pg 77)

Question No: 13 (Marks: 1) - Please choose one

The variables having a name, type and size are just like empty boxes.

- ▶ False
- ▶ True

Question No: 15 (Marks: 1) - Please choose one

Most efficient method of dealing with structure variables is to define the structure globally

- ▶ True
- ▶ False

Question No: 16 (Marks: 1) - Please choose one

Syntax of union is identical to _____

▶ Structure (pg 242)

- ▶ Class
- ▶ Function
- ▶ None of the given options

Question No: 16 (Marks: 1) - Please choose one

commenting the code liberally is

▶ Useful.

- ▶ Time consuming
- ▶ Not necessary

Question :If we want to store a string "abc" in an array str then the size of this array must be a

- (a) 2
- (b) 3
- (c) 4
- (d) 5

Question :How many bytes will the pointer intPtr of type int move in the following statement?
intPtr += 3 ;

- (a) 3 bytes
- (b) 6 bytes
- (c) 12 bytes
- (d) 24 bytes

Question :The remainder (%) operator is,

▶ An arithmetic operator (Pg 258)

- ▶ A logical operator
- ▶ A relational operator
- ▶ A division operator

Question :When a call to function statement is encountered,

- ▶ The control is transfer to its Prototype
- ▶ **The control is transfer to its definition**
- ▶ The compiler stop execution of whole program
- ▶ The program hangs

Question :The value of $2*15/3*7+3*2$ is

- Ø 146
- Ø 76
- Ø 8
- Ø 70

Question: Carefully analyze the following lines of code and chose the correct option.

ch1="a";

ch2='a';

- Ø ch1 and ch2 are strings
- Ø **ch1 is string and ch2 is character**
- Ø ch2 is string and ch1 is character
- Ø ch1 and ch2 are characters

Question :The size of a double variable is

- Ø 2 bytes
- Ø 4 bytes
- Ø **8 bytes**
- Ø 10 bytes

Question :An array is also called

- Ø an array variable
- Ø array declaration
- Ø struct
- Ø **constant pointer**



Remember own prayer

1. In order to get 256 from the number 2568 we divide this number by 10 and take,

- ▶ Its remainder
- ▶ The number
- ▶ Its quotient
- ▶ Its divisor

2. The correct syntax of do-while loop is,

- ▶ (condition) while; do { statements; };
- ▶ { statements; } do-while ();
- ▶ while(condition); do { statements; };
- ▶ do { statements; } while (condition);

3. Which of the following function(s) is/are included in stdlib.h header file?

- ▶ double atof(const char *nptr)
- ▶ int atoi(const char *nptr)
- ▶ char *strcpy (char *s1, const char *s2)
- ▶ 1 and 2 only (Pg 191)

4. If the break statement is missed in switch statement then,

- ▶ The compiler will give error
- ▶ This may cause a logical error (Pg 76)
- ▶ No effect on program
- ▶ Program stops its execution

5. The data type before a function name represents its,

- ▶ Return Type (Pg 499)
- ▶ Function data
- ▶ Function arguments
- ▶ Function name

6. Member function tellg() returns the current location of the _____ pointer.

- ▶ tellptr()
- ▶ write()
- ▶ seekg()
- ▶ get() (Pg 215)

7. What does $5 | 6$, evaluate to in decimal where '|' is bitwise OR operator?

- ▶ 3
- ▶ 4
- ▶ 5
- ▶ 7

$5 | 6 =$

0 1 0 1

0 1 1 0

0 111=7

8. C is widely known as development language of _____ operating system.

- ▶ Linux
- ▶ Windows
- ▶ **Unix (Pg 12)**
- ▶ Mac OS

9. What will be the result of arithmetic expression $6+27/3*3$?

- ▶ 33
- ▶ 45
- ▶ **9**
- ▶ 30

10. How many bytes are occupied by declaring following array of characters?

`char str[] = "programming";`

- ▶ 10
- ▶ 11
- ▶ **12**
- ▶ 13

11. What will be the correct syntax for initialization of pointer ptr with string "programming"?

- ▶ `char ptr = 'programming' ;`
- ▶ **`char *ptr = "programming" ;`**
- ▶ `char *ptr = 'programming' ;`
- ▶ `*ptr = "programming" ;`

pg 166

array element in each array initialized with a single character enclosed in single quote. pg 21

While assigning a character value to a char type variable single quotes are used around the character as 'a'.

12. What will be the result of expression $x\%=2$, if $x=7$?

- ▶ **$x=1$**
- ▶ $x=3$
- ▶ $x=7$
- ▶ $x=2$

13. UNIX has been developed in _____ language.

- ▶ JAVA
- ▶ B
- ▶ **C(pg 12)**
- ▶ FORTRAN

14. What will be the value of i and j in the following code segment?

```
int i, j ;  
int x[5] = {2, 3, 4, 8, 9} ;  
int *ptr =&x[2];  
i = (*ptr)++ ;
```

j = *ptr++ ;

- ▶ i = 5, j = 5
- ▶ i = 5, j = 8
- ▶ i = 4, j = 8
- ▶ i = 5, j = 9

15. When an array element is passed to a function, it is passed by -----.

- ▶ reference(Pg 266)
- ▶ data type
- ▶ value
- ▶ data

16. What is the output of the following statement?

int i = 2.5; do { cout << i * 2; } while (i > 3 && i < 10);

- ▶ 510
- ▶ 5
- ▶ 48
- ▶ ERROR

17. What does !(7) evaluate to in decimal where ! is a NOT operator?

- ▶ 7
- ▶ 8
- ▶ 9
- ▶ 10

18. The condition in while loop may contain logical expression but not relational expression.

- ▶ True
- ▶ False

19. Searching is easier when an array is already sorted

- ▶ True
- ▶ False

20. If an array has 100 elements, what is allowable range of subscripts?

- ▶ 0-99
- ▶ 1-99
- ▶ 0 - 100
- ▶ 1 - 100

21. What will be the value of 'a' and 'b' after executing the following statements?

a = 3;
b = a++;

- ▶ 3, 4
- ▶ 4, 4
- ▶ 3, 3
- ▶ 4, 3

22. What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

- ▶ int arr[2][3] = {0,0} ;

- ▶ `int arr[2][3] = {{0},{0}} ;`
- ▶ `int arr[2][3] = {0},{0} ;`
- ▶ `int arr[2][3] = {0} ;`

23. Which of the following function returns the size of a string variable?

- ▶ `strlen()`
- ▶ `stringlen()`
- ▶ `strlen()`
- ▶ `strLength()`

When applied to a character array, the `strlen` function returns the length of the string stored there,
not its allocated size.

24. What will be the range of numbers generated by function `rand () % 9`?

- ▶ 0 to 9
- ▶ 1 to 9
- ▶ 0 to 8
- ▶ 1 to 8

25. Computer can understand only machine language code.

- ▶ True
- ▶ False

26. What does $5 \wedge 6$, evaluate to in decimal where '^' is Exclusive OR operator?

- ▶ True
- ▶ False

Detail:-

It mean

$5 = 0101$

$6 = 0110$

$5 \wedge 6 = 0011$

If both inputs are same then the output is 0 and if different then output is 1

27. If the file is not properly closed in the program, the program _____.

- ▶ Terminate normally
- ▶ Indicate Runtime error
- ▶ Indicate Compile time error
- ▶ Crashes

28. Which of the following header file include string conversion functions?

- ▶ `stdlib.h`

29. A precise sequence of steps to solve a problem is called

- ▶ Statement
- ▶ **Program**
- ▶ Utility
- ▶ Routine

30. In if structure the block of statements is executed only,

- ▶ When the condition is false
- ▶ When it contain arithmetic operators
- ▶ When it contain logical operators
- ▶ **When the condition is true**

31. Dealing with structures and functions passing by reference is the most economical method

- ▶ **True**
- ▶ False

32. Preprocessor program perform its function before _____ phase takes place.

- ▶ Editing
- ▶ Linking
- ▶ **Compiling**
- ▶ Loading

33. Which looping process is best, when the number of iterations is known?

- ▶ **for**
- ▶ while
- ▶ do-while
- ▶ all looping processes require that the iterations be known

34. Which character is inserted at the end of string to indicate the end of string?

- ▶ new line
- ▶ tab
- ▶ **null**
- ▶ carriage return

35. Which of the following header file defines the rand() function?

- ▶ iostream.h
- ▶ conio.h
- ▶ **stdlib.h**
- ▶ stdio.h

36. Commenting the code _____

- ▶ **Makes a program easy to understand for others.**
- ▶ Make programs heavy, i.e. more space is needed for executable.
- ▶ Makes it difficult to compile
- ▶ All of the given options.

37. What's wrong with this for loop? for (int k = 2, k <= 12, k++)

- ▶ the increment should always be ++k
- ▶ the variable must always be the letter i when using a for loop
- ▶ there should be a semicolon at the end of the statement
- ▶ **the commas should be semicolons**

38. For which array, the size of the array should be one more than the number of elements in an

array?

- ▶ int
- ▶ double
- ▶ float
- ▶ char

39. The function of cin is

- ▶ To display message
- ▶ To read data from keyboard
- ▶ To display output on the screen
- ▶ To send data to printer

40. In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- ▶ cplex.h
- ▶ ctype.h (Pg 188)
- ▶ stdio.h
- ▶ delay.h

41. How many parameter(s) function getline() takes?

- ▶ 0
- ▶ 1
- ▶ 2
- ▶ 3

42. Word processor is

- ▶ Operating system
- ▶ Application software
- ▶ Device driverUtility software

43. For which values of the integer _value will the following code becomes an infinite loop?

```
int number=1;
while (true) {
cout << number;
if (number == 3) break;
number += integer_value; }
```

- ▶ any number other than 1 or 2
- ▶ only 0
- ▶ only 1
- ▶ only 2

Rational:

46. Each pass through a loop is called a/an

- ▶ enumeration
- ▶ Iteration
- ▶ culmination
- ▶ pass through

- ▶ the return 0; statement
- ▶ the first statement after the loop
- ▶ the statements following the continue statement
- ▶ **the next iteration of the loop**

Continue statement is used, when at a certain stage, you don't want to execute the remaining statements inside your loop and want to go to the start of the loop.

48. What is the correct syntax to declare an array of size 10 of int data type?

- ▶ int [10] name ;
- ▶ name[10] int ;
- ▶ **int name[10] ;**
- ▶ int name[] ;

49. Consider the following code segment. What will the following code segment

```
display? int main(){
int age[10] = {0};
cout << age ;
```

- ```
}
```
- ▶ Values of all elements of array
  - ▶ **Value of first element of array**
  - ▶ Starting address of array
  - ▶ Address of last array element

50. How many bytes will the pointer INTPTR of type int move in the following statement? intPtr += 3 ;

- ▶ 3 bytes
- ▶ 6 bytes
- ▶ **12 bytes**
- ▶ 24 bytes

one int is 4 bytes so  $4 \times 3 = 12$  bytes movement.

51. If there are  $2(n+1)$  elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

- ▶ n elements
- ▶  **$(n+1)$  elements**
- ▶  $2(n+1)$  elements
- ▶  $2(n+1)$  elements

52. Which of the following operator is used to access the value of variable pointed to by a pointer?

- ▶ **\* operator**
- ▶ -> operator
- ▶ && operator
- ▶ & operator

53. The \_\_\_\_\_ statement interrupts the flow of control.

- ▶ switch
- ▶ continue
- ▶ goto
- ▶ **break**

54. A programmer is preparing a program

55. As a programmer is preparing a program

- ▶ **Middle**

► Post Design

► First

Analysis will be always followed by design and then code.

55. Paying attention to detail in designing a program is \_\_\_\_\_

- Time consuming
- Redundant
- Necessary
- Somewhat Good

In programming, the details matter. This is a very important skill. A good programmer always analyzes the problem statement very carefully and in detail. You should pay attention to all the aspects of the problem.

56. There are mainly----- types of software

► Two

- Three
- Four
- Five

- System Software
- Application Software

57. In C/C++ the #include is called,

- Header file
- Preprocessor Directive (Pg 15)
- Statement
- Function

a.

58. && is-----

operator.

- An arithmetic
- Logical
- Relational
- Unary

we use logical operators ( && and || ) for AND and OR respectively with relational operators.

59. In flow chart, the symbol used for decision making is,

- Rectangle
- Circle
- Arrow
- Diamond (Pg 51)

60. C++ views each file as a sequential stream of\_\_\_\_\_ .

► Bytes

- Bits
- 0's or 1's
- Words

61. If the elements of an array are already sorted then the useful search algorithm is, ► Linear search

► Binary search (Pg 188)

- Quick search
- Random search

In binary search algorithm, the 'divide and conquer' strategy is applied. This plies only to sorted arrays in ascending or descending order.

► Expression

► Variable

► Constant

63. When a pointer is incremented, it actually jumps the number of memory addresses

► According to data type (Pg 160)

► 1 byte exactly

► 1 bit exactly

► A pointer variable can not be incremented

64. Call by reference mechanism should be used in a program when there is

i. large amount of data to be passed

ii. small amount of data to be passed

iii. need to change the passed data

iv. no need to change the passed data

► and (ii) only

► (i) and (iii) only

► (ii) and (iii) only

► (ii) and (iv) only

65. Which of the following is the starting index of an array in C++?

► 0

► 1

► -1

► any number

66. The return type of a function that do not return any value must be \_\_\_\_\_

► int

► void

► double

► float

67. Which of the following is an extension of header file?

► .exe

► .txt

► .h

► .c

68. We want to access array in random order which approach is better?

► Pointers

► Array index (Pg 176)

► Both pointers and array index are better

► None of the given options.

69. When we declare a multidimensional array the compiler store the elements of multidimensional array in the

form of,

► Columns

► Rows

► Contiguous memory location (Pg 174)

► Matrix

62. The address operator (&) can be used with,

► Statement

70. In C/C++ the string constant is enclosed

- ▶ In curly braces
- ▶ In small braces
- ▶ In single quotes
- ▶ In double quotes

71. The size of int data type is

- ▶ 1 bytes
- ▶ 2 bytes
- ▶ 3 bytes
- ▶ 4 bytes (Pg 257)

72. In Flow chart process is represented by

- ▶ Rectangle (Pg 51)
- ▶ Arrow symbol
- ▶ Oval
- ▶ Circle

73. When we are using const keyword with a variable x then initializing it at the time of declaration is,

- ▶ Must
- ▶ Optional
- ▶ Not necessary
- ▶ A syntax error

74. Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third column?

- ▶ `m[2][3] = 5 ;`
- ▶ `m[3][2] = 5 ;`
- ▶ `m[1][2] = 5 ;`
- ▶ `m[2][3] = '5' ;`

75. How many total elements must be in two-dimensional array of 3 rows and 2 columns?

- ▶ 4
- ▶ 5
- ▶ 6 ( $3*2=6$ )
- ▶ 7

76. Which of the following is the correct statement for the following declaration?

`const int *ptr;`

- ▶ ptr is a constant pointer
- ▶ ptr is constant integer pointer
- ▶ ptr is a constant pointer to int
- ▶ ptr is a pointer to const int

77. Consider the following code segment. What will be the output of this code segment?

```
int arr[6] = {2, 3, 7, 4, 5, 6} ;
```

```
int *ptr1 = &arr[1] ;
```

```
int *ptr2 = &arr[4] ;
```

```
cout << (ptr2 - ptr1) ;
```

- ▶ 3
- ▶ 9
- ▶ 12
- ▶ 2

- ▶ object based
- ▶ object oriented
- ▶ **function oriented** (Pg 77)

78. The variables having a name, type and size are just like empty boxes.

- ▶ False
- ▶ **True**

79. Most efficient method of dealing with structure variables is to define the structure globally

- ▶ True
- ▶ False

80. Syntax of union is identical to \_\_\_\_\_

- ▶ **Structure** (pg 242)
- ▶ Class
- ▶ Function
- ▶ None of the given options

81. In Program commenting the code liberally is

- ▶ **Useful.**
- ▶ Time consuming
- ▶ Not necessary

82. If we want to store a string "abc" in an array str then the size of this array must be at least,

- ▶ 2
- ▶ 3
- ▶ **4**
- ▶ 5

83. The remainder (%) operator is,

- ▶ **An arithmetic operator** (Pg 258)
- ▶ A logical operator
- ▶ A relational operator
- ▶ A division operator

84. When a call to function statement is encountered,

- ▶ The control is transfer to its Prototype
- ▶ **The control is transfer to its definition**
- ▶ The compiler stop execution of whole program
- ▶ The program hangs

85. The value of  $2*15/3*7+3*2$  is

- ▶ 146
- ▶ **76**
- ▶ 8
- ▶ 70

86. Carefully analyze the following lines of code and chose the correct option.

```
ch1="a";
ch2='a';
```

- ▶ **ch1 and ch2 are strings**
- ▶ **ch1 is string and ch2 is character**
- ▶ **C is a/an language**
- ▶ low level

- ▶ ch1 and ch2 are characters

87. The size of a double variable is

- ▶ 2 bytes
- ▶ 4 bytes
- ▶ 8 bytes
- ▶ 10 bytes

The size of an int & a long int is:4 bytes

The size of a short int is:2 bytes: 4bytes

The size of a char is:1 byte

The size of a double variable is:8 byte

88. An array is also called

- ▶ an array variable
- ▶ array declaration
- ▶ struct
- ▶ constant pointer

89. Compiler is a

- ▶ System software
- ▶ Application Software
- ▶ Driver
- ▶ Editor

90. If Num is an integer variable then Num++ means,

- ▶ Add 1 two times with Num
- ▶ Add 1 with Num
- ▶ Add 2 with Num
- ▶ Subtract 2 from Num

91. For one byte there are \_\_\_\_\_ combinations of values that can be stored in computer.

- ▶  $2^6$
- ▶  $2^7$
- ▶  $2^8$
- ▶  $2^4$

Each bit is capable of holding two possible values, the number of possible different combinations of values that can be stored in n bits is  $2^n$ . For example:  
1 bit can hold  $2 = 2^1 = 2$  possible values (0 or 1)  
2 bits can hold  $2 \times 2 = 2^2 = 4$  possible values  
so 8 bits(one byte) =  $2^8 = 256$

92. Default case in switch statement is,

- ▶ Must
- ▶ Optional
- ▶ syntax error
- ▶ Necessary

93. When break statement is encountered in switch statement, it

- ▶ Stops the entire program
- ▶ Stops the execution of current statement
- ▶ Exits from switch statement
- ▶ None of the given options

- ▶ 2n dimensions
- ▶ (n+1) dimensions
- ▶ (n-1) dimensions (Array starts from 0<sup>th</sup> element)

95. What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

- ▶ **ptr[3]**
- ▶ (ptr+3)
- ▶ \*(ptr+3)
- ▶ Both 1 and 3

100 Which of the following values C++ use to represent true and false?

- ▶ **and 0**
- ▶ and -1
- ▶ and 00
- ▶ Any numerical value

101 Declaring structures does not mean that memory is allocated.

- ▶ **True**
- ▶ False

102 If a variable is passed by value to a function and the function makes some changes to that variable then it

- ▶ **Does not affect the original variable pg 83**
- ▶ affects the original variable
- ▶ causes syntax error
- ▶ None of the given options

103 Loops are ----- Structure.

Decision

**Repetition pg 560**

Sequential

Hierarchical

104 \_\_\_\_\_ is manipulator and it inserts new line character and flushes the stream.

- ▶ **endl**

105 Switch statement deals with,

- ▶ Integer data only
- ▶ float data only
- ▶ character data only
- ▶ **Integer and character data**

106 A record is a group of related \_\_\_\_\_.

- ▶ Files
- ▶ Bytes
- ▶ **Fields**

CS201 Grand Quiz Preparation Spring 2020

94. How many dimensions does n-dimensional array has?

107 ▶ To access the element of two dimensional array we use,

▶ Single referencing

▶ Single dereferencing

▶ Double dereferencing

▶ **Double referencing Pg175**

108 If it is required to copy an array to another array then,

▶ **Both arrays must be of the same size and data type Pg 105**

▶ Both arrays may be of different size

▶ Both arrays may be of different data type

▶ Both arrays may be of different size and type

109 The precedence of \* is higher than dot operator

▶ True

▶ **False**

110 Which of the following data type(s) can operate on modulus operator '%'?

▶ float, int

▶ float, double

▶ **int Pg 22**

▶ char

111 What will be the output of following code?

```
int x = 10 ;
```

```
cout << "x =" << x ;
```

▶ 10

▶ "x=10"

▶ **x=10**

▶ 10=x

112 Which looping process checks the test condition at the end of the loop?

▶ for

▶ while

▶ **do while**

▶ no looping process checks the test condition at the end

113 What will be the correct syntax of the following statement?

ptr is a constant pointer to integer.

▶ `const int *ptr ;`

▶ `const *int ptr ;`

▶ `int const *ptr ;`

▶ **`int *const ptr ;` Pg 154**

114 A function must always return value.

▶ True

▶ **False**

115 Assignment operator is used for \_\_\_\_\_.

▶ calculation

► reading

► assigning value to variables eg 1

► None of the given options.

116 What is the difference between switch statement and if statement.

1. if statement is used when we have to check two conditions while switch is a multi conditional control statement.

2. SWITCH statement can be executed with all cases if the “break” statement is not used whereas IF statement has to be true to be executed further.

117 What is wrong with following code and also give the reason of error?

```
int x , y ;
int *ptr1 = &x ;
int *ptr2 = &y ;
ptr1+ptr2 ;
```

Answer:

We need one more variable in which we put sum of ptr1 and ptr2 like

```
Int z;
z=ptr1+ptr2;
```

(Answer provided by Ferhat Qudsia)

118 Which bit of the number is used as a sign bit?

The most significant bit of the number is used as a sign bit (to denote the sign of the number). (Answer provided by Ferhat Qudsia)

119 What happened when we try to copy the array ‘arr1’ into the array ‘arr2’ in the following code segment, justify your answer?

```
main()
{
 int arr1[3]={2,3,5};
 int arr2[3];
 arr2=arr1;
}
```

We can not copy array directly in this way (arr2=arr1;)

Each member of arr1 to be copied by each member of arr2.

We can use for loop to copy array 1 to array2

(Answer provided by Ferhat Qudsia)

120 Differentiate between random access and sequential access file?

Random access file:

Random access files are not in sequence mean its not necessary put that's thing first that written first we put any thing from file any where. So tellg() and tellp() are the two very useful functions while reading from or writing into the files at some certain position.

Sequential access file:

Sequential access files are simple character files. while working with the sequential access files we write in a sequence not in a random manner

121 When the logical operator AND (&&) combine two expressions exp1 and exp2 then the result will be true only,

- ▶ When both exp1 and exp2 are true Pg 246
- ▶ When both exp1 and exp2 are false
- ▶ When exp1 is true and exp2 is false
- ▶ When exp1 is false and exp2 is true

122 Which of the following function(s) is/are included in ctype.h header file?

- ▶ isdigit(int c)
- ▶ isxdigit(int c)
- ▶ tolower(int c)
- ▶ All of the above Pg 188

123 To access the data members of structure \_\_\_\_\_ is used.

- ▶ dot operator (.) pg 231
- ▶ \* operator
- ▶ operator .
- ▶ None of given.

124 Both compiler and interpreter are used to translate program into machine language code.

- ▶ True
- ▶ False

125 Missing semicolon ';' at the end of C++ statement is

- ▶ Logical error
- ▶ Syntax error Pg 16
- ▶ Runtime error
- ▶ None of the given options

126 Switch statement is an alternative of \_\_\_\_\_ statement

- ▶ multiple if
- ▶ continue
- ▶ break
- ▶ goto

127 Array is passed by value to a function by default.

- ▶ True
- ▶ False Pg 266

128 Which of the following is the correct function call having array named student of 10 elements as a parameter.

- ▶ addRecord(student[]);
- ▶ addRecord(student);
- ▶ addRecord(student[10]);
- ▶ addRecord(\*student);

129 What will be the output of following code segment?

```
main(){
 int x = 5;
 {
```

```
int x = 4 ;
cout << x
}
cout << x
}
► 5, 5
► 4, 4
► 4, 5
► 5, 4
```

130 The object \_\_\_\_\_ may be used both for file input and file output

- **fstream**, Pg 199
- ifstream,
- ofstream,
- none of the given options.

138. Let suppose

```
Union intorDouble{
Int ival;
Double charvar;
};
main(){
intorDouble VAZ;

int size ;
size = sizeof(VAZ);
}
```

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8 bytes?

- 2
- 4
- 8
- 12

139. How a program can use a function?

The calling program just needs to write the function name and provide its arguments (without data types). It is important to note that while calling a function, we don't write the return value data type or the data types of arguments.

140. Which function is used to read/write more than a single character or single line while handling files?

We use the **getline** function to read more than single character 206

Suppose the pointer yptr is pointing to the first element of the array y and the size of array is 10. Can we increment the yptr up to 12 times? And what will happen?

(i) An array day is declared as: `int day[] = {1, 2, 3, 4, 5, 6, 7};` How many elements does array 'day' has?

(ii) If the declaration is changed as: `int day[7] = {1, 2, 3, 4, 5, 6, 7};` how many element does array 'day' has?

In both the case array day has the 7 elements.

141. C language is developed by

- ▶ Bill Gates
- ▶ Robert Lafore
- ▶ Dennis Ritchie Pg 12
- ▶ Deitel & Deitel

142. Which of the following choice is not an example of an int datatype?

- ▶ 0
- ▶ -32
- ▶ 65531
- ▶ -4.0

143. \*doc is \_\_\_\_\_ by type.

- ▶ Sequential File
- ▶ Random Access File
- ▶ Data File
- ▶ Record File

144. In C/C++ all character strings are terminated with,

- ▶ Null character
- ▶ String
- ▶ Zero Pg 166
- ▶ Full stop

145. Which of the following can not be a variable name?

- ▶ area
- ▶ \_area
- ▶ 10area
- ▶ area2

146. By default an array of characters is passed by value to a function.

- ▶ True
- ▶ False

147. Which of the following operator is used to access the address of a variable?

- ▶ \* operator
- ▶ -> operator
- ▶ && operator
- ▶ & operator Pg 480

148. The name of an array represents address of first location of array element.

- ▶ True Pg 120

149. Let suppose

```
Union intorDouble{
```

```
Int ival;
```

```
Double charvar;
```

```
};
```

```
main(){
 int Double VAZ;
 int size ;
 size = sizeof(VAZ);
}
```

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8 bytes?

- ▶ 2
- ▶ 4
- ▶ 8
- ▶ 12

150. What is the difference between for loop and while loop?

When number of iterations known we use for loop otherwise we will use while loop

151. To access the element of two dimensional array we use,

- ▶ Single referencing
- ▶ Single dereferencing
- ▶ Double dereferencing Pg175
- ▶ Double referencing

152. Data Size of the file is always \_\_\_\_\_ the actual size of the file.

- ▶ Greater than
- ▶ Equal to
- ▶ Less than or equal to
- ▶ None of the above Pg 216

Similarly in case of files, the space occupied by a file (file size) can be more than the actual data length of the file itself.

153. When an identifier is declared with keyword const then,

- ▶ Its value can be changed during execution.
- ▶ Its value can not be changed Pg110
- ▶ Its value can be changed with arithmetic operator
- ▶ Its value can be overwritten

154. In C/C++ if we define an array of size eight (8) i.e. int Arr [8]; then the last element of this array will be stored at,

- ▶ Arr[0]
- ▶ Arr[8]
- ▶ Arr[7]
- ▶ Arr[-1]

155. In C/C++ all character strings are terminated with,

- ▶ Null character Pg 166
- ▶ String
- ▶ Zero

156. Let suppose  
struct  
    intorDoubl  
    e {  
int ival; Double  
    charvar;  
};

```
main(){
 intorDouble
 VAZ;
 int size ;
 size =
 sizeof(VAZ);
}
```

What will be the value of variable size, if int occupies 4 bytes and double occupies 8 bytes?

- ▶ 2
- ▶ 4
- ▶ 8
- ▶ 12

157. Do-while loop executes at least,

- ▶ Zero Time
- ▶ **One Time**
- ▶ Two Times
- ▶ N Times

158. += , \*= , /= , etc are called,

- ▶ Assignment operators
- ▶ Logical operator
- ▶ **Compound assignment operator Pg 63**
- ▶ Unary operator

159. Computer can understand only machine language code.

- ▶ **True Pg 12**
- ▶ False

160. Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

- ▶ cout <
- ▶ cout <
- ▶ cout <
- ▶ cout <

161. The compilers and interpreters also belong to the System Software category.

▶ False

162. Editors are used to compile the code.

163. ▶ True

▶ False

Compilers are used for compilation of source codes, However Editors are used to write the source codes.

164. What will be the result of the statement

rand ( ) % 50

When 50 divides any number, the remainder will always be less than 50.

165. \n is control character which is used to insert.

▶ line break

166. Default constructor takes \_\_\_\_\_.

- ▶ one parameter
- ▶ two parameters
- ▶ no parameters
- ▶ character type parameter

167. All the preprocessors directives start with \_\_\_\_\_.

- ▶ \$
- ▶ &
- ▶ #
- ▶ \_

168. The members of a class declared with the keyword struct are \_\_\_\_\_ by default.

- ▶ static
- ▶ private
- ▶ protected
- ▶ public

169. We cannot use \_\_\_\_\_ pointer for storing and reading data from it.

- ▶ NULL
- ▶ integer
- ▶ double
- ▶ zero

170. When an object of a class is defined inside another class then,

- ▶ Destructor of enclosing class will be called first
- ▶ Destructor of inner object will be called first
- ▶ Constructor and Destructor will be called simultaneously
- ▶ None of the given options

181. Consider the following code segment. Which of the following will be called while executing code at line 2? String s1 , s2; s1 = s2 ;

CS201 Grand Quizz Preparation Spring 2020

- ▶ Copy constructor

- ▶ **Default constructor**
- ▶ Assignment operator
- ▶ Parameterized constructor

182. We cannot increment \_\_\_\_\_.

- ▶ pointers
- ▶ arrays
- ▶ **references**
- ▶ variables

183. In statement Matrix m2 = m1 ;

- ▶ **Assignment operator is being used**
- ▶ Copy constructor is being used.
- ▶ Statement has syntax error
- ▶ None of the given options

184. From the following; which on is the correct syntax of an array declaration: array size is 5 and it is of float data type?

- ▶ float [5] name;
- ▶ name[5] float;
- ▶ **float name[5];**
- ▶ None of the given options

185. If an array has 50 elements, what is allowable range of subscripts?

- ▶ **0-49**
- ▶ 1-49
- ▶ 0-50
- ▶ 1-50

186. A structure is a collection of \_\_\_\_\_ under a single name.

- ▶ values
- ▶ **variables**
- ▶ data
- ▶ None of the given

187. If a function has not been declared before its definition, It is a

- ▶ **logical error**
- ▶ syntax error
- ▶ run time error
- ▶ None of these

188. When the if statement consists more than one statement then enclosing these statement in curly braces is,

- ▶ Not required
- ▶ **Good programming**
- ▶ Relevant
- ▶ Must

189. \_\_\_\_\_ allow us to have a memory location and use it as int or char interchangeably

- ▶ structures
- ▶ union
- ▶ construct

▶ None of the given

190. In Analysis, we try to have a\_\_\_\_\_

- ▶ Determined the inputs
- ▶ Break up of problem
- ▶ Precise problem statement
- ▶ None of the given

191. \_\_\_\_\_function give the position of the next character to be read from that file.

- ▶ tellp()
- ▶ tellg()
- ▶ seekg()
- ▶ seekp()

192. Pointers store the \_\_\_\_\_

- ▶ value of a variable
- ▶ memory address
- ▶ characters
- ▶ None of the given

193. In order to get the right most digit of a number, we divide this number by 10 and take its

- ▶ Remainder
- ▶ Quotient
- ▶ Divisor
- ▶ None of the given options

194. \_\_\_\_\_ Returns true if c is a digit and false otherwise.

- ▶ int isalpha( int c )
- ▶ int isalnum( int c )
- ▶ int isxdigit( int c )
- ▶ int isdigit( int c )

195. If int a = 50; then the value of a/= 3; will be,

- ▶ 15
- ▶ 18
- ▶ 16
- ▶ 17

196. \_\_\_\_\_ contains functions for manipulations of character data.

- ▶ ctype.h
- ▶ iostream.h
- ▶ string.h
- ▶ None of the given

197. \_\_\_\_\_ Returns true if c is a digit or a letter and false otherwise.

- ▶ int isalpha( int c )
- ▶ int isalnum( int c )
- ▶ int isxdigit( int c )
- ▶ int isdigit( int c )

198. If  $\text{sum} = 5$ ; Then the value of the following statement is  $\text{sum} = \text{sum} - 3$ ;

- ▶ 52
- ▶ 50
- ▶ 51
- ▶ 57

199. To get the value stored at a memory address, we use the \_\_\_\_\_

- ▶ referencing operator
- ▶ dereferencing operator
- ▶ simple operator
- ▶ None of the given

200. In C/C++; by default arguments are passed by \_\_\_\_\_ to a function.

- ▶ Reference
- ▶ Value
- ▶ Type
- ▶ Data

201. The string in the array is terminated by a \_\_\_\_\_

- ▶ zero
- ▶ nil
- ▶ null
- ▶ one

202. Structures are syntactically defined with the word \_\_\_\_\_.

- ▶ struc
- ▶ struct
- ▶ structure
- ▶ None of the given

203. At the \_\_\_\_\_, we try to break up the problem into functional units

- ▶ analysis phase
- ▶ design phase
- ▶ Implementation phase
- ▶ None of the given

204. While developing a program; should we think about the user interface?

- ▶ Yes
- ▶ No

205. What will be the result of arithmetic expression  $5 + 25 / 5 * 5$ ?

- ▶ 45
- ▶ 6
- ▶ 30
- ▶ 9

206. Why we use "cin"?

- ▶ To send data to printer
- ▶ To read data from keyboard
- ▶ To display message
- ▶ To display output on the screen

207. \_\_\_\_\_ operator uses the sign ^.

- ▶ Bit-wise OR
- ▶ Exclusive OR
- ▶ AND Operator
- ▶ NOT operator

208. C++ is a \_\_\_\_\_ language.

- ▶ High level
- ▶ Low level
- ▶ Machine
- ▶ Fourth Generation

209.  $12 \& 8 = (1000)_2 =$  \_\_\_\_\_. & is used to AND two numbers bit-wise

- ▶ 4
- ▶ 8
- ▶ 6
- ▶ 12

210. From the following; which one is used as an assignment operator?

- ▶ Equal sign '='
- ▶ Double equal sign '=='
- ▶ Both equal and double equal sign
- ▶ None of the given options

211. What will be the value of 'a' and 'b' after executing the following statements? `int a = 9; int b = a++; cout <<`

- ▶ 10,9
- ▶ 9,10
- ▶ 9,9
- ▶ 10,10

212. These functions `seekg()` and `seekp()` requires an argument of type \_\_\_\_\_ to let them how many bytes to move forward or backward.

- ▶ int
- ▶ short
- ▶ long
- ▶ double

213. A character is stored in the memory in \_\_\_\_\_

- ▶ byte
- ▶ integer
- ▶ string
- ▶ None of the given

214. dereferencing operator is represented by \_\_\_\_\_

- ▶ \*
- ▶ +
- ▶ -
- ▶ None of the given

215. Grand Quizz Preparation transfer the executable code from main memory to hard disk.

▶ **Loader**

▶ Debugger

▶ Compiler

▶ Linker

216. When the logical operator OR (||) combine two expressions exp1 and exp2 then the result will be false only,

- ▶ When both exp1 and exp2 are true
- ▶ **When both exp1 and exp2 are false**
- ▶ When exp1 is true and exp2 is false
- ▶ When exp1 is false and exp2 is true

217. suppose we have int y[10]; To access the 4th element of the array we write\_\_\_\_\_

- ▶ y[4];
- ▶ y[3];
- ▶ y[2];
- ▶ **none of given**

218. We have opened a file stream myfile for reading (getting), myfile.tellg () gives us the current get position of the file pointer. It returns a whole number of type\_\_\_\_\_

- ▶ long
- ▶ **int**
- ▶ short
- ▶ double

219. ofstream is used for\_\_\_\_\_

- ▶ Input file stream
- ▶ **Output file stream**
- ▶ Input and output file stream
- ▶ All of the given

220. A structure is a collection of \_\_\_\_\_under a single name.

- ▶ values
- ▶ **variables**
- ▶ data
- ▶ None of the given

221. The first character of a variable name must be an alphabet or

- ▶ **Underscore**
- ▶ Digit
- ▶ Special character
- ▶ Comma

222. Suppose int multi[5][10]; when we are using \*\*multi , it means,

- ▶ Single dereferencing
- ▶ Single referencing
- ▶ Double referencing
- ▶ **Double dereferencing**

223. eof( ), bad( ), good( ), clear( ) all are manipulators.

- ▶ **True**
- ▶ False

224. It is possible to return an object from a function through this pointer.

225.

- ▶ True
- ▶ False

226. Function implementation of friend function must be defined outside the class.

- ▶ True
- ▶ False

227. The default scope for members of structures is public whereas the default visibility for class members is private.

- ▶ True
- ▶ False

228. The operator function of << and >> operators are always the member function of a class.

- ▶ True
- ▶ False

229. What does STL stand for?

- ▶ Source template library
- ▶ Standard template library
- ▶ Stream template library
- ▶ Standard temporary library

230. Which of the following array is the most suitable for storing a matrix structure

- ▶ Single-dimensional array
- ▶ Two-dimensional array
- ▶ Three-dimensional array
- ▶ Four-dimensional array

231. What will be the output of following code segment?

```
main(){
int x = 5 ;
{
 int x = 4 ;
 cout << x << "," ;
}
cout << x ;
}
```

- ▶ 5, 5
- ▶ 4, 4
- ▶ 4, 5
- ▶ 5, 4

232. Single line comments explaining code would be preceded like in the following example.

- ▶ /\*
- ▶ //
- ▶ /
- ▶ /\*\*

233. Which of the following will be the correct function call for function prototype given below?

```
int func (int &);
```

- ▶ func(int num);
- ▶ func(&num);
- ▶ func(num);
- ▶ func(\*num);

233. If & is symbol (& sign) used with the variable name followed by data type then it refers to \_\_\_\_\_ and if & is being used with variable name then it refers to \_\_\_\_\_

- ▶ Address of variable, reference variable
- ▶ Reference variable, value of variable
- ▶ **Reference variable, address of variable**
- ▶ Address of variable, value of variable

235. Which of the following operator the compiler overloads for objects by default?

- ▶ + operator
- ▶ operator
- ▶ = operator
- ▶ **== operator**

236. If overloaded plus operator is implemented as member function then which of the following option will be true for the statement given below?

obj3 = obj1 + obj2 ;

- ▶ obj1 will be passed as an argument to + operator whereas obj2 will drive the + operator
- ▶ **obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator**
- ▶ Both objects (obj1, obj2) will be passed as arguments to the + operator
- ▶ Any of the objects (obj1, obj2) can drive the + operator

237. The operator function will be implemented as \_\_\_\_\_, if both objects (obj1, obj2) are passed as arguments to - operator in the statement given below.

obj3 = obj1 - obj2;

- ▶ friend function
- ▶ member function
- ▶ **non-member function**
- ▶ either non-member or friend function

238. The input/output streams cin and cout are \_\_\_\_\_ therefore have \_\_\_\_\_.

- ▶ Structures, function
- ▶ **Objects, member functions**
- ▶ Functions, objects
- ▶ None of the given options

239. What will be the output of following statement?

cout << setfill('0') << setw(7) << 128

- ▶ **0000128**
- ▶ 0128128
- ▶ 1280000
- ▶ 0012800

240. The static data members of a class will be \_\_\_\_\_

- ▶ shared by objects
- ▶ created for each object
- ▶ **initialized within class**
- ▶ initialized within main function

241. Which of the following is used for allocating space for static variables?

- ▶ Heap
- ▶ **Static storage area**
- ▶ Free store
- ▶ Stack

242. Templates provide way of abstracting information.

- ▶ type
- ▶ data
- ▶ method
- ▶ access

243. A pointer is a special type of variable that contain \_\_\_\_\_

- ▶ Memory Address
- ▶ Data values
- ▶ Both Values and Memory
- ▶ None of given of options

244. Which is NOT a protection level provided by classes in C++?

- ▶ protected
- ▶ hidden
- ▶ private
- ▶ public

245. Users must not know about \_\_\_\_\_.

- ▶ Functions Name within Class
- ▶ Class implementation of Functionality and Interfaces
- ▶ Methods Functionality with in Class
- ▶ None of the given options

246. Assignment operator is used to initialize a newly declared object from existing object

- ▶ True
- ▶ False

247. The operator function for << (stream insertion) >> and stream extraction must be

- ▶ Member function of class
- ▶ Non-member function of class
- ▶ Both member and non-member function
- ▶ None of the given options

248. A template function must have

- ▶ One or more than one arguments
- ▶ Only one argument
- ▶ Zero arguments
- ▶ None of the given options

249. Truth tables are used for analyzing \_\_\_\_\_.

- ▶ logical expressions
- ▶ arithmetic expressions
- ▶ both logical and arithmetic expressions
- ▶ none of the given options.

250. Which of the following array is the most suitable for storing a matrix structure?

- ▶ Single-dimensional array
- ▶ Two-dimensional array
- ▶ Three-dimensional array
- ▶ Four-dimensional array

11 bytes for 11 characters of word programming and 1 for '\n'

251. When we do dynamic memory allocation in the constructor of a class, then it is necessary to provide a destructor.

252. The prototype of friend functions must be written \_\_\_\_\_ the class and its definition must be written \_\_\_\_\_

- ▶ inside, inside the class
- ▶ inside, outside the class
- ▶ **outside, inside the class**
- ▶ outside, outside the class

253. Copy constructor becomes necessary while dealing with \_\_\_\_\_ allocation in the class.

- ▶ **Dynamic memory**
- ▶ Static memory
- ▶ Both Dynamic and Static memory
- ▶ None of the given options

254. what is the function of flush command?

1): when we specify the buffer size, normally the operating system or compiler does this for us. A typical size of buffer is 512 bytes. When the information is of 512 byte size, output will take place. But in the program, we may want at some point that whatever is in the buffer, show them. For that purpose the normal mechanism is flush. Flush the stream. The flush command forces the data from the buffer to go to its destination which is normally a screen or file and make the buffer empty. Lec 34

255. what are the types of templates?

a template is a sketch to draw some shape or figure.

There are two different types of templates in C++ language i.e.' function templates and class templates. Lec 41

256. The declaratory of Plus (+) member operator function is

- ▶ **Class-Name operator + (Class-Name rhs)**
- ▶ operator Class-Name + ( )
- ▶ operator Class-Name + ( rhs)
- ▶ Class-Name operator + ( )

257.  $12 \& 8 = (1000)_2 = \underline{\hspace{2cm}}$ . & is used to AND two numbers bit-wise

Select correct option:

- ▶ 4
- ▶ **8**
- ▶ 6
- ▶ 12

258. Truth table for &

| Bit1 | Bit2 | Bit1 & Bit2 |
|------|------|-------------|
| 1    | 1    | 1           |
| 1    | 0    | 0           |
| 0    | 1    | 0           |
| 0    | 0    | 0           |

Therefore, when we apply the conditions, we get

$12 = 1\ 1\ 1\ 0$  (binary conversion of 12)

▶  $= 1\ 0\ 0\ 0$  (binary conversion of 8)

-----  
1 0 0 0, which is equals to 8

The reserved words public and private comes under the category

259. Which of the following operators can not be overloaded

- ▶ :new
- ▶ :delete
- ▶ :+=
- ▶ :sizeof

260. The reserved words public and private comes under the category

- ▶ :structures
- ▶ :strings
- ▶ :accessibility modifiers
- ▶ :types of functions

261. What is the sequence of event(s) when allocating memory using new operator?

- ▶ Only block of memory is allocated for objects
- ▶ Only constructor is called for objects
- ▶ Memory is allocated first before calling constructor
- ▶ Constructor is called first before allocating memory

262. What is the sequence of event(s) when deallocating memory using delete operator?

- ▶ Only block of memory is deallocated for objects
- ▶ Only destructor is called for objects
- ▶ Memory is deallocated first before calling destructor
- ▶ Destructor is called first before deallocating memory

263. new and delete operators cannot be overloaded as member functions.

- ▶ True
- ▶ False

264. The operator function of << and >> operators are always the member function of a class.

- ▶ True
- ▶ False

265. A template function must have at least ----- generic data type

- ▶ Zero
- ▶ One
- ▶ Two
- ▶ Three

266. If we do not mention any return\_value\_type with a function, it will return an \_\_\_\_\_ value.

- ▶ int
- ▶ void
- ▶ double
- ▶ float

267. Suppose a program contains an array declared as int arr[100]; what will be the size of array?

- ▶ 0
- ▶ 99
- ▶ 100
- ▶ 101

268. The name of an array represents address of first location of array element.

▶ True

▶ False

269. Reusing the variables in program helps to save the memory

▶ True

▶ False

270. Which of the following option is true about new operator to dynamically allocate memory to an object?

- ▶ The new operator determines the size of an object
- ▶ Allocates memory to object and returns pointer of valid type
- ▶ Creates an object and calls the constructor to initialize the object
- ▶ All of the given options

271. new and delete are \_\_\_\_\_ whereas malloc and free are \_\_\_\_\_.

- ▶ Functions, operators
- ▶ Classes, operators
- ▶ Operators, functions
- ▶ Operators, classes

272. Like member functions, \_\_\_\_\_ can also access the private data members of a class.

- ▶ Non-member functions
- ▶ Friend functions
- ▶ Any function outside class
- ▶ None of the given options

273. Which of the following statement is best regarding declaration of friend function?

- ▶ Friend function must be declared after public keyword.
- ▶ Friend function must be declared after private keyword.
- ▶ Friend function must be declared at the top within class definition.
- ▶ It can be declared anywhere in class as these are not affected by the public and private keywords.

274. The operator function overloaded for an Assignment operator (=) must be

- ▶ Non-member function of class
- ▶ Member function of class
- ▶ Friend function of class
- ▶ None of the given options

275. For non-member operator function, object on left side of the operator may be

- ▶ Object of operator class
- ▶ Object of different class
- ▶ Built-in data type
- ▶ All of the given options

276. The operator function will be implemented as \_\_\_\_\_, if obj1 drive the - operator whereas obj2 is passed as arguments to - operator in the statement given below.  
obj3 = obj1 - obj2;

- ▶ Member function
- ▶ Non-member function
- ▶ Friend function
- ▶ None of the given options

277. Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

- ▶ Class-name operator +() ;
- ▶ Class-name operator +(int) ;
- ▶ **Class-name operator ++() ;**
- ▶ Class-name operator ++(int) ;

278. The static data members of a class are initialized \_\_\_\_\_

- ▶ **at file scope**
- ▶ within class definition
- ▶ within member function
- ▶ within main function

279. Class is a user defined \_\_\_\_\_.

- ▶ **data type**
- ▶ memory referee
- ▶ value
- ▶ none of the given options.

280. We can also define a user-defined manipulators.

- ▶ True
- ▶ **False**

281. Automatic variable are created on \_\_\_\_\_.

- ▶ Heap
- ▶ Free store
- ▶ **static storage**
- ▶ stack

282. A pointer variable can be,

- ▶ Decremented only
- ▶ Incremented only
- ▶ Multiplied only
- ▶ **Both 1 and 2**

283. setprecision is a parameter less manipulator.

- ▶ True
- ▶ **False**

284. We can change a Unary operator to Binary operator through operator overloading.

- ▶ **False**
- ▶ True

285. What is the functionality of the following statement?

String str[5] = {String("Programming"), String("CS201")};

- ▶ Default constructor will call for all objects of array
- ▶ **parameterized constructor will call for all objects of array**
- ▶ Parameterized constructor will call for first 2 objects and default constructor for remaining objects
- ▶ Default constructor will call for first 3 objects and Parameterized constructor for remaining objects

286. There is an array of characters having name 'course' that has to be initialized by string 'programming' which of the following is the correct way to do this,

- i. `course[] = {'p', 'r', 'o', 'g', 'r', 'a', 'm', 'm', 'i', 'n', 'g'};`
- ii. `course[] = 'programming' ;`
- iii. `course[12] = "programming" ;`
- iv. `course = "programming" ;`

Choose the correct options.

- ▶ (i) and (ii) only
- ▶ (i) and (iv) only
- ▶ (i) and (iii) only
- ▶ (ii) and (iii) only

287. Overloaded member operator function is always called by \_\_\_\_\_

- ▶ **Class**
- ▶ Object
- ▶ Compiler
- ▶ Primitive data type

288. Copy constructor becomes necessary while dealing with \_\_\_\_\_ allocation in the class.

- ▶ **Dynamic memory**
- ▶ Static memory
- ▶ Both Dynamic and Static memory
- ▶ None of the given options

289. What will be the correct syntax to assign an array named arr of 5 elements to a pointer ptr?

- ▶ `*ptr = arr ; ptr = arr ;`
- ▶ **`*ptr = arr[5]`**
- ▶ `ptr = arr[5] ;`

290. The variables having a name, type and size are just like empty boxes.

- ▶ False
- ▶ **True**

291. Syntax of union is identical to \_\_\_\_\_

- ▶ **Structure**
- ▶ Class
- ▶ Function
- ▶ None of the given options

292. Like member functions, \_\_\_\_\_ can also access the private data members of a class.

- ▶ Non-member functions
- ▶ **Friend functions**
- ▶ Any function outside class
- ▶ None of the given options

293. Function created within function called?

- ▶ nested
- ▶ overloaded
- ▶ grouped

none of them



Remember own prayer



Remember own prayer