

Question # 1 of 10 (Start time: 12:47:50 PM, 07 July 2025)

Which of the following operator cannot be overloaded in C++ language?

Select the correct option

☐	
☒	sizeof
☐	--
☐	++

Question # 3 of 10 (**Start time: 12:48:29 PM, 07 July 2025**)

Data encapsulation can be achieved through _____.

Select the correct option

☐	Arrays
☐	Structures
☐	Pointers
☒	Classes

Question # 4 of 10 (**Start time: 12:48:43 PM, 07 July 2025**)

In C/C++ language, memory at runtime is allocated from _____.

Select the correct option

☒	Free store(heap)
☐	ROM
☐	Stack
☐	Hard disk

Question # 5 of 10 (**Start time: 12:48:57 PM, 07 July 2025**)

The return type of malloc () function is _____.

Select the correct option

☐	int pointer
☐	float pointer
☐	NULL pointer
☒	void pointer

Question # 7 of 10 (Start time: 12:49:24 PM, 07 July 2025)

What is the output of the following code if the user enters 10?

```
#include <iostream>
```

```
using namespace std;
```

```
int main() {
```

```
    int num;
```

```
    cout << "Enter a number: ";
```

```
    cin >> num;
```

```
    cout << "Output: " << num + 5;
```

```
    return 0;
```

```
}
```

Select the correct option

☐	105
☐	10
☒	15
☐	50

Question # 10 of 10 (Start time: 12:50:28 PM, 07 July 2025)

In the syntax of the overloaded operator function given below:

```
Complex operator + (Complex & );
```

What is 'operator'?

Select the correct option

☐	Class
☒	Keyword
☐	Operand
☐	Object

Question # 6 of 10 (Start time: 12:49:10 PM, 07 July 2025)

The correct syntax of stream insertion operator is:

Select the correct option

☐	<code>istream* istream::operator >> ();</code>
☐	<code>istream& istream::operator >> (char *text);</code>
☒	<code>ostream& ostream::operator << (char *text);</code>
☐	<code>ostream* ostream::operator << ();</code>

Question # 9 of 10 (Start time: 12:50:02 PM, 07 July 2025)

Which of the following correctly initializes the 3rd object of the Date class in the array mydate?

Select the correct option

☐	<code>Date mydate[2] = Date(10, 10, 2021);</code>
☒	<code>mydate[2] = Date(10, 10, 2021);</code>
☐	<code>Date mydate[3] = Date(10, 10, 2021);</code>
☐	<code>mydate[3] = Date(3, 3, 2021);</code>

Question # 8 of 10 (Start time: 12:49:37 PM, 07 July 2025)

What is the correct prototype of overloading of delete operator?

Select the correct option

☐	<code>void * operator delete (size_t size) ;</code>
☒	<code>void operator delete (void * ptr) ;</code>
☐	<code>void * operator delete (size_t, size) ;</code>
☐	<code>new operator delete (void * ptr);</code>

Question # 2 of 10 (Start time: 12:48:02 PM, 07 July 2025)

When overloading assignment (=) operator, which of the following syntax is correct?

Select the correct option

☐	<code>void operator (= String &s);</code>
☐	<code>void operator (=) const String &other ;</code>
☐	<code>void operator (=) (const String &s);</code>
☒	<code>void operator = (const String &s);</code>