

Cs-610 Important Mid Term
Mcq's Solution 100% Correct :
Solve By Vu-Topper RM!!

وَتَعَزُّ مِنْ تَشَاءٍ وَتُذَلُّ مِنْ تَشَاءٍ



PROFESSIONAL ONLINE ACADEMY



**NOTHING IS
IMPOSSIBLE**

All Paid Services

- ❖ LMS Handling
- ❖ Important Notes
- ❖ Online Classes
- ❖ Projects
- ❖ Assignments
- ❖ Quiz
- ❖ GDB's

JOIN US NOW

For More Info
Contact us at:

Rizwan Manzoor

 **0322-4021365**

Question No:1

(Marks:1)

Vu-Topper RM

Uses counter rotating rings in which data flows in opposite directions.

Ans: FDDI Page 31

Question No:2

(Marks:1)

Vu-Topper RM

The Ethernet speed was originally 3Mbps, and the current standard is the fast Ethernet operates at 100Mbps.

Ans: 10Mbps Page27

Question No:3

(Marks:1)

Vu-Topper RM

Mapping between a protocol address and a hardware address is called_.

Segmentation

Hashing

Address Resolution

Question No:4

(Marks:1)

Vu-Topper RM

Protocols of TCP/IP layering model specify how to organize data into frame and how a computer transmits frames over a network.

Session

Network interface layer

Internet Layer

Question No:5

(Marks:1)

Vu-Topper RM

In Closed-form computation, the protocol address assigned to a computer is chosen carefully so that computer's hardware address can be computed from the protocol address using basic Boolean and operations.

Arithmetic

XOR

Shift

Question No:6

(Marks:1)

Vu-Topper RM

As the Internet grew, the original Classful addressing scheme became a limitation. The IP address space was being exhausted because all networks had to choose one of possible sizes.

Three

two

four

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:7

(Marks:1)

Vu-Topper RM

Dotted decimal notation is a syntactic form the IP software uses to express binary values when interacting with humans.

8-bit

16-bit

32-bit

Question No:8

(Marks:1)

Vu-Topper RM

protocols of TCP/IP layering model specify how to ensure reliable transfer.

Physical Layer

Network Interface Layer

Transport Layer

Question No:9

(Marks:1)

Vu-Topper RM

In the IP address identifies an individual computer on the network.

Prefix

Suffix

Mux

Question No:10

(Marks:1)

Vu-Topper RM

Internet protocol (IP) address version 4 is comprised of bits.

48

32

24

Question No:11

(Marks:1)

Vu-Topper RM

A separate table is used for each physical network.

bit-binding

Checksum

address-binding

Question No:12

(Marks:1)

Vu-Topper RM

Inside a computer, each address mask is stored as a bit value.

48

64

32

Question No:13

(Marks:1)

Vu-Topper RM

Dotted decimal represents each octet in and uses a dot to separate octets.

decimal

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:14**(Marks:1)****Vu-Topper RM**

of TCP/IP Protocol Suit specifies the format of packets sent across Internet as well as the mechanisms used to forward packets.

Physical Layer

Data Link Layer

Internet Layer**Question No:15****(Marks:1)****Vu-Topper RM**

The IP class scheme does not divide the address space into equal size class and the classes do not contain the same number of networks.

16-bit

32-bit

48-bit

Question No:16**(Marks:1)****Vu-Topper RM**

of TCP/IP protocol suit defines the basic characteristics of network hardware.

Physical Layer

Data Link Layer

Internet Layer

Question No:17**(Marks:1)****Vu-Topper RM**

The protocol address of the next hop must be to an equivalent hardware address before a packet can be sent.

Encrypted

Decrypted

Translated**Question No:18****(Marks:1)****Vu-Topper RM**

Address Resolution Protocol is mostly used to bind a 32-bit IP address to an _ Ethernet address.

16-bit

48-bit

64-bit

Question No:19**(Marks:1)****Vu-Topper RM**

TCP/IP defines the term to refer any computer system that connects to a network and runs applications for users.

Router

Host computer

Bridge

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:20

(Marks:1)

Vu-Topper RM

are two standard implementations to improve computational efficiency.

Hashing and Direct indexing

Segmentation and Fragmentation

Queuing and Packetizing

Question No:21

(Marks:1)

Vu-Topper RM

In the IP address identifies the physical network to which the computer is attached.

Prefix

Suffix

Mux

Question No:22

(Marks:1)

Vu-Topper RM

In Cyclic Redundancy Checking, CRC is _____.

Divisor

Quotient

Remainder

page 20

Question No:23

(Marks:1)

Vu-Topper RM

The satellite or radio topology in which all computers are connected to each other via satellite or radio wave is a kind of

Broadcast network

page 5

Point-to-Point network

Question No:24

(Marks:1)

Vu-Topper RM

Which of the following two operations are performed by Ethernet CD?

I. It monitors outgoing signals.

II. Grabbled signal is interpreted as a collision.

III. Signals are sent back to the sender.

I and III

II and IV

I and II

page 28

Question No:25

(Marks:1)

Vu-Topper RM

The process of forwarding a packet is called _____.

Routing

page 58

Processing

Hierarchical Addressing

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:26

(Marks:1)

Vu-Topper RM

Which statement is correct about Network Interface Card (NIC)?

I. NIC contains sufficient hardware to process data independent of system CPU

II. NIC looks like any other I/O device to system CPU

III. NIC also receives interrupt on incoming data.

I and II

II and III

All of the given options

page 40

Question No:27

(Marks:1)

Vu-Topper RM

While transmitting data from source A to destination B, 4 bits are changed during the transmission then the error is a _____.

Burst error **page 22**

Single error

Double error

Question No:28

(Marks:1)

Vu-Topper RM

The switch that has no attached computers is called _____.

Packet Switch

Exterior Switch

Interior Switch **page 59**

Question No:29

(Marks:1)

Vu-Topper RM

_____ is the most popular wiring scheme because of lowest cost.

5 Base T

10 Base T **page 43**

100 base T

Question No:30

(Marks:1)

Vu-Topper RM

In _____ technique, all members of the network can send data only on the specific time slot?

CDMA

FDMA

CSMA **page 43**

Question No:31

(Marks:1)

Vu-Topper RM

The _____ of errors is difficult than the _____ of errors.

correction; detection **google**

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:32**(Marks:1)****Vu-Topper RM**

If a sender with a 100 Megabit NIC and receiver with 10 Megabit NIC wants to communicate with each other at which speed they can communicate?

100 Megabit**page 40****Question No:33****(Marks:1)****Vu-Topper RM**

Missing _____ in a frame format indicates receiving computer missed beginning of the message.

eot

sot

soh**page 16****Question No:34****(Marks:1)****Vu-Topper RM**

Source Independence phenomenon allows fast and efficient _____.

Source Addressing

Routing

Packet Switching**page 58****Question No:35****(Marks:1)****Vu-Topper RM**

In distributed route computation process each packet switch computes its routing table locally and sends messages to the _____.

Router

Graph

Neighbors page 63**Question No:36****(Marks:1)****Vu-Topper RM**

The ____ layer of the OSI model takes the data from the physical layer and perform error checking.

Transport

Data link google

Application

Question No:37**(Marks:1)****Vu-Topper RM**

CBR stands for _____.

Constant Byte Rate

Constant Bit Rate

Constant Borrow Rate

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:38**(Marks:1)****Vu-Topper RM**

A network that uses _____ usually consist of a single long cable to which computer attach.

Star Topology

Ring Topology

Bus Topology **page 26**

Question No:39**(Marks:1)****Vu-Topper RM**

If simultaneous transmission occurs, the frames interfere with each other and this phenomenon is called _____.

packet loss

collision **page 28**

delayed transmission

Question No:40**(Marks:1)****Vu-Topper RM**

In _____ all computers are attached to a central hub

Ring topology

Star topology **page 31**

Hub topology

Question No:41**(Marks:1)****Vu-Topper RM**

For adding a new computer in a point to point network _____ new connection will be required

N

N-1 **page 23**

N-2

Question No:42**(Marks:1)****Vu-Topper RM**

The fastest Ethernet hardware operates at a rate of _____

1000 bps

100 Mbps **page 27**

10 Mbps

Question No:43**(Marks:1)****Vu-Topper RM**

Which of the following the benefit to point to point communication?

Quick to configure.

Security implementation **page 23**

Cost

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:44 (Marks:1)

Vu-Topper RM

ATM offers _____speed and _____delay

High, High

High, low page 72

Low, low

Question No:45 (Marks:1)

Vu-Topper RM

Thick Ethernet is known as _____

10 Base 2

10 Base 5 google

10 Base T

Question No:46 (Marks:1)

Vu-Topper RM

Both interior and exterior switches _____packet and they also need routing tables.

Create

Delay

Forward page 59

Question No:47 (Marks:1)

Vu-Topper RM

_____is the rate at which data can be sent through the network

Throughput page 79

Propagation delay

Access delay

Question No:48 (Marks:1)

Vu-Topper RM

In a ping command, small –sized information packets of _____are sent.

TCP

UDP

ICMP page 11

Question No:49 (Marks:1)

Vu-Topper RM

Many WANs use _____addressing of efficiency

Sequence

Hierarchical page 56

Question No:50 (Marks:1)

Vu-Topper RM

Which of the following is not a function of ping commands?

Relay nodes page 11

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:51

(Marks:1)

Vu-Topper RM

Packet switched can be linked together to form a _____

LAN

WAN page 56

Bridge

Question No:52

(Marks:1)

Vu-Topper RM

Fixed network is a type of network which is classified with respect to the factor

Size

Connectivity

Mobility page 6

Question No:53

(Marks:1)

Vu-Topper RM

Parity bit can detect _____error(s)

4

3

2 page 19

Question No:54

(Marks:1)

Vu-Topper RM

When we will try to connect to the internet which of the following protocol will be used?

Telnet

TCP/IP page 84

ICMP

Question No:55

(Marks:1)

Vu-Topper RM

How many computers are mandatory to form a network?

1

2 google

4

Question No:56

(Marks:1)

Vu-Topper RM

_____ is standard wireless LAN that uses radio signals at 2.4GHz.

IEEE 803.16

IEEE 802.15

IEEE 802.11 page 29

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:57

(Marks:1)

Vu-Topper RM

LAN interface hardware obeys _____ access rule.

CSMA/CD page 34

Round ro

Question No:58

(Marks:1)

Vu-Topper RM

The most important task a bridge performs is _____.

Packet switching

Line controlling

Frame filtering page 50

Question No:59

(Marks:1)

Vu-Topper RM

ATM uses small, fixed-sized packets called cells and each cell has _____ octets.

47

52

53 page 66

Question No:60

(Marks:1)

Vu-Topper RM

_____ can't be guaranteed with variable length packets as easily as it can with fixed length cells.

Errors

Noise

None of the given page 72

Question No:61

(Marks:1)

Vu-Topper RM

Which multiplexing technique transmits digital signals?

WDM

FDM

TDM page 15

Question No:62

(Marks:1)

Vu-Topper RM

Connections in Asynchronous transfer mode are called _____.

Virtual channels page 67

Virtual Path Identifier

Question No:63

(Marks:1)

Vu-Topper RM

A ____ is a device that combines multiple signals and forwards into a single line.

Modem

Multiplexer page 41

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:64

(Marks:1)

Vu-Topper RM

_____ is inflexible.

Routing

Searching

Static routing **page 62**

Question No:65

(Marks:1)

Vu-Topper RM

If a hub is used to connect many computers in a LAN, then only _____
computers can communicate at a given time.

Three

Two **page 54**

Four

Question No:66

(Marks:1)

Vu-Topper RM

_____ is the term used for variance in transmission delays.

Friction

Segment

Jitter **page 66**

Question No:67

(Marks:1)

Vu-Topper RM

_____ is also called self healing network.

ATM

FDDI

Frame relay **page 46**

Question No:68

(Marks:1)

Vu-Topper RM

_____ and _____ are the two frame types.

Internal and external

Single and dual

Multicast and broadcast **page 35**

Question No:69

(Marks:1)

Vu-Topper RM

Bluetooth uses shared medium and _____ instead of coaxial cable.

Radio waves **page 29**

Infrared waves

Question No:70

(Marks:1)

Vu-Topper RM

Which of the following is not a guided medium?

Atmosphere **google**

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:71

(Marks:1)

Vu-Topper RM

As a result of ARPA research, the first network was established which was named as _____.

INTERNETWORKING

ARPNET

ARPANET **page 9**

Question No:72

(Marks:1)

Vu-Topper RM

Asynchronous transfer mode (ATM) can dynamically establish a _____.

Switched virtual circuit **page 70**

Virtual connection identifier

Virtual path indicator

Question No:73

(Marks:1)

Vu-Topper RM

A typical port on an ATM switch operates at _____ or _____ higher.

OC-2 speed (155Gbps)

OC-2 speed (1000Mbps)

OC-3 speed (155Mbps) **page 72**

Question No:74

(Marks:1)

Vu-Topper RM

10Base-T Ethernet is often called a _____.

ring shaped star

ring shaped bus

star shaped bus **page 46**

Question No:75

(Marks:1)

Vu-Topper RM

_____ allows automatic updates.

Dynamic routing **page 62**

Static routing

Routing

Question No:76

(Marks:1)

Vu-Topper RM

Handling variable length packets leads to memory _____.

Fragmentation **page 72**

Management

Question No:77

(Marks:1)

Vu-Topper RM

In order to forward a copy of frame, the bridge uses _____ address.

Destination **page 51**

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:78

(Marks:1)

Vu-Topper RM

We may use _____ to extend local area network.

Bridge, Router

Bridge, Hub, Router

Bridge, Hub, Repeater **page 149**

Question No:79

(Marks:1)

Vu-Topper RM

All of the given options are the types of delay except _____.

Propagation

Access

Throughput **page 79**

Question No:80

(Marks:1)

Vu-Topper RM

While computing shortest path in a graph, next hop information is inserted into _____.

Routing table **page 62**

Trailer

Header

Question No:81

(Marks:1)

Vu-Topper RM

LAN interface uses _____ to copy frame data directly from main memory

DMA **page 34**

FDDI

Hard disk

Question No:82

(Marks:1)

Vu-Topper RM

The Gigabit Ethernet hardware operates at a rate of _____.

10 Mbps

100 Mbps

1000 Mbps **page 263**

Question No:83

(Marks:1)

Vu-Topper RM

In the early resource sharing era, which resources were shared among users?

Computation **page 9**

Floppy Drives

Hard Disk

Ethernet modem

Question No:84

(Marks:1)

Vu-Topper RM

If two buildings are located far from each other then bridge, and _____ can be used to connect two LAN.

Optical fiber

page 51

Question No:85

(Marks:1)

Vu-Topper RM

Which type of network consists of wireless connection of laptops in a university classroom?

WAN

MAN

LAN

google

Question No:86

(Marks:1)

Vu-Topper RM

A typical bridge has _____.

One NIC, a CPU a memory and a ROM.

Two NICs, a CPU a memory and a ROM.

page 50

Question No:87

(Marks:1)

Vu-Topper RM

A cache memory, ROM and CPU.

_____ is used for compressed audio and video, where the data rate depends on the level of compression that can be achieved.

Constant Bit Rate

Stable Bit Rate

Variable Bit Rate

page 71

Question No:88

(Marks:1)

Vu-Topper RM

There are _____ types of data stuffing.

1

2 page 17

0

Question No:89

(Marks:1)

Vu-Topper RM

Dijkstra's algorithm can accommodate weights on _____ in graph.

Nodes page62

Edges

Path

Question No:90

(Marks:1)

Vu-Topper RM

_____ masks your IP address.

VPN

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:91**(Marks:1)****Vu-Topper RM**

Static routing computes routing table information at _____ time.

Load

Boot **page 62**

Execute

Question No:92**(Marks:1)****Vu-Topper RM**

In which type of error detection, the arithmetic sum is calculated before and after the transmission of data at both communication ends?

CRC

Parity

Checksum **page 19**

Question No:93**(Marks:1)****Vu-Topper RM**

Computer sends a connection request to the _____ to which it is attached while establishing a switched virtual circuit

Bridge

Switch **page 70**

VPI

Question No:94**(Marks:1)****Vu-Topper RM**

The bridges communicate with each other on the network and use _____ algorithm to decide which bridge will not forward frames if a cycle occurs.

Dijkstra

Shortest path first

Distributed Spanning Tree **page 53**

Question No:95**(Marks:1)****Vu-Topper RM**

Ethernet uses a _____ bit static addressing scheme in which each device is assigned a unique address by the manufacturer.

64

48

32

Question No:96**(Marks:1)****Vu-Topper RM**

Weights on graph edges reflect cost of _____.

Nodes

Traversing edge **page 63**

Trending edge

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:97

(Marks:1)

Vu-Topper RM

A _____ relies on the hardware manufacturer to assign a unique physical address to each network interface.

Static addressing scheme page 34

Configurable addressing scheme

Dynamic addressing scheme

Question No:98

(Marks:1)

Vu-Topper RM

In _____ topology, if the switch goes down all the computers will be disconnected.

Star

Ring

Bus

Question No:99

(Marks:1)

Vu-Topper RM

Which type of network consists of wired computers in a university classroom?

MAN

PAN

LAN

Question No:100

(Marks:1)

Vu-Topper RM

If you as a network administrator want to know the traffic flow of your data while communicating with a remote computer which of the following will be used to know about intermediate routers?

Ipconfig

Ping page 11

Traceroute

Question No:101

(Marks:1)

Vu-Topper RM

Hardware address is also called _____.

Physical address

Logical address

IP address

Question No:102

(Marks:1)

Vu-Topper RM

Thick Ethernet also requires _____ to avoid signal reflectance.

Transceivers

AUI cable

Terminators page 41

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:103

(Marks:1)

Vu-Topper RM

Which of the following network is using the TCP/IP model globally?

PAN

SAN

The Internet

Question No:104

(Marks:1)

Vu-Topper RM

VPNs connections are sometimes called _____.

Tunnels **page 75**

Open networking

Routing

Question No:105

(Marks:1)

Vu-Topper RM

To reduce _____ computers can be connected and distributed to a number of hubs, then the hubs can be connected to a switch.

Costs **page 54**

Quality

Efficiency

Question No:106

(Marks:1)

Vu-Topper RM

If a _____ is used the communication between two computers will not affect the other pair of computers and they can communicate at the same time

Hub

Switch **page 54**

Repeater

Question No:107

(Marks:1)

Vu-Topper RM

The length of hardware address is _____.

One to ten bytes

One to five bytes

One to six bytes **page 34**

Question No:108

(Marks:1)

Vu-Topper RM

A network analyzer is also called _____.

Network manager

Network administrator

Network monitor **page 37**

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:109

(Marks:1)

Vu-Topper RM

No any error detection scheme is perfect because transmission errors can affect _____.

Data

Additional Information

Additional information & data google

Question No:110

(Marks:1)

Vu-Topper RM

The token ring network topology is a ring but wiring topology is a _____.

Star page 44

bus

tree

Question No:111

(Marks:1)

Vu-Topper RM

_____ addresses are used in an ethernet frame.

IP page 99

Port

Logical

Question No:112

(Marks:1)

Vu-Topper RM

AUI cable connects from NIC to _____.

BNC Connector

RJ-45 Connector

Transceiver page 41

Question No:113

(Marks:1)

Vu-Topper RM

Public networks are _____.

More secure than LAN

Flexible page 74

Limited in boundary

Question No:114

(Marks:1)

Vu-Topper RM

The maximum cable length of a LAN is fixed because _____.

Additional hardware are not suitable for the LAN extension.

The electrical signal level gets weaker as it travels. Page 48

Question No:115

(Marks:1)

Vu-Topper RM

In _____ network topology is separated from route computation.

Link-state routing page 64

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:116

(Marks:1)

Vu-Topper RM

Which layer of the OSI Model directly communicates and controls the transmission medium:

Transmission

Physical

Network

Question No:117

(Marks:1)

Vu-Topper RM

A network with _____ jitter takes more time to deliver some packets than others.

Zero

High **page 80**

Low

Question No:118

(Marks:1)

Vu-Topper RM

A network uses _____ to arrange computers in a single closed loop.

Star Topology

Mesh Topology

Ring Topology **page 25**

Question No:119

(Marks:1)

Vu-Topper RM

Which of the following tasks is not done by the second layer of the OSI model?

Flow control

Framing

Channel coding **google**

Question No:120

(Marks:1)

Vu-Topper RM

ATM is a single technology designed to meet the goals of both _____ and _____.

LAN & PAN

LAN & WAN **page 66**

LAN & MAN

Question No:121

(Marks:1)

Vu-Topper RM

LAN and WAN are classified according to their _____.

Size **page 4**

Connectivity

Medium

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:122

(Marks:1)

Vu-Topper RM

The identifier that is used for data transfer in the virtual circuit network is called _____.

Virtual circuit identifier

Global address

Network identifier

Question No:123

(Marks:1)

Vu-Topper RM

In Direct point to point communication adding the Nth computer requires_____ new connections

N^2

$(N^2 - N)/2$ **page 23**

$N(N-1)$

Question No:124

(Marks:1)

Vu-Topper RM

Which of the following is the correct function of bridge?

MTU path discovery

Byte stuffing

Filtering and forwarding a frame **page 50, 51**

Question No:125

(Marks:1)

Vu-Topper RM

Point to point topology is

Size based

Mobility based

Connectivity based **page 5**

Question No:126

(Marks:1)

Vu-Topper RM

IEEE LLC / SNAP header is _____ which is used to specify the type of data.

8 octets **google**

16 octets

32 octets

Question No:127

(Marks:1)

Vu-Topper RM

What is the largest network in existence?

The internet **google**

A PAN

A Fog

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:128

(Marks:1)

Vu-Topper RM

The frame format of any LAN technology must consists of ____ and ____ -

Payload and CRC

Frame header and CRC

Frame header and payload page 36

Question No:129

(Marks:1)

Vu-Topper RM

_____ can occur a LANs when a packet is delayed because the network is busy

Jitter page 66

Loop

Deadlock

Question No:130

(Marks:1)

Vu-Topper RM

Which of the following cannot be used to extend a LAN?

Repeaters

Switches

Fiber modems

Question No:131

(Marks:1)

Vu-Topper RM

Links-state algorithm is used in _____

RIP

IGRP

OSPF page 64

Question No:132

(Marks:1)

Vu-Topper RM

According to size, there are ____ classifications of networks

2 page 2

3

4

Question No:133

(Marks:1)

Vu-Topper RM

In which topology terminators are used at the end of the cable?

Star

Bus

Question No:134

(Marks:1)

Vu-Topper RM

Switch simulates a _____ LAN connecting segments

Bridged page 54

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:135

(Marks:1)

Vu-Topper RM

PVS stands for _____

Permanent virtual circuit **page 69**

Private virtual circuit

Public virtual circuit

Question No:136

(Marks:1)

Vu-Topper RM

Hardware that calculates a CRC used two simple components _____

AND unit and XOR Unit

Shift register and XOR unit **page 20**

Shift register & AND unit

Question No:137

(Marks:1)

Vu-Topper RM

Thin ethernet is known as _____

10 base 2 **google**

10 base 5

10 base T

Question No:137

(Marks:1)

Vu-Topper RM

If a sender with a 1 Gigabit NIC and receiver with 100 Megabit NIC wants to communicate with each other than at which speed they can communicate

11 Megabit

100 Megabit

1 Gigabit

Question No:138

(Marks:1)

Vu-Topper RM

_____ is used as an alternative of packet for a specific computer network technology

Datum

Token

Frame **page 14**

Question No:139

(Marks:1)

Vu-Topper RM

The sharing of a medium and its link by two or more devices is called _____

Modulation

Encoding

Multiplexing

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:140

(Marks:1)

Vu-Topper RM

The topology each computer is connected to a central hub is called

Ring topology

Star topology **page 5**

Tree topology

Question No:141

(Marks:1)

Vu-Topper RM

Asynchronous transfer mode (ATM) is designed to work on fiber but can be used with _____

Wireless

Twisted pair **page 72**

Wifi

Question No:142

(Marks:1)

Vu-Topper RM

The basic responsibility of NIC is _____

To access medium network

To resource allocation

To access memory

Question No:143

(Marks:1)

Vu-Topper RM

Frame relay is _____

Connection oriented service **page 64**

Connectionless service

Typically ranges for 5 Mbps to 1000Mbps

Question No:144

(Marks:1)

Vu-Topper RM

The length of time required to send a variable length packet is _____

5 second

Variable **page 72**

Constant

Question No:145

(Marks:1)

Vu-Topper RM

In Token Ring, if all computers are ready to transmit it enforces _____ Access

First come first served

Round Robin **page 30**

Question No:146

(Marks:1)

Vu-Topper RM

The Ethernet standard specifies that frames are sent using the _____ scheme.

Manchester Encoding **page 27**

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:147 (Marks:1)

Vu-Topper RM

ATM uses the concept of _____.

Connection-oriented page 66

Connection-less

Variable packet size

Question No:148 (Marks:1)

Vu-Topper RM

Which of the following is a benefit of point to point communication?

Quick to configure

Security implementation

Less availability

Question No:149 (Marks:1)

Vu-Topper RM

_____ is not used to extend LAN.

Hub

Fiber modem

Repeater

Question No:150 (Marks:1)

Vu-Topper RM

Which types of VPNs are used for corporate connectivity across companies residing in different geographical locations?

Remote access VPNs

Peer-to-peer VPNs

Site-to-site VPNs google

Question No:151 (Marks:1)

Vu-Topper RM

Star topology is the kind of

Tree topology

Point-to-point topology page 05

Broadcast topology

Question No:152 (Marks:1)

Vu-Topper RM

In a _____ state, a bridge allows simultaneous use of each segment.

Ready

Steady

Question No:153 (Marks:1)

Vu-Topper RM

The network occupies larger areas like cities & countries is called

WAN

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:154

(Marks:1)

Vu-Topper RM

In link state routing _____ send link-state information about local connections.

Bridge

Switches

Hubs

Question No:155

(Marks:1)

Vu-Topper RM

Transmission media are usually categorized as _____.

Guided or unguided

Fixed or unfixed

Determinate or indeterminate

Question No:156

(Marks:1)

Vu-Topper RM

Even parity can be used to check for _____ bit/ bits of errors.

1 page 18

2

3

Question No:157

(Marks:1)

Vu-Topper RM

Routing table entries can be _____ with a default route.

Collapsed

Redirected

Emerged

Question No:158

(Marks:1)

Vu-Topper RM

The system administrator must coordinate to avoid the conflict in _____ hardware addressing scheme.

Static

Dynamic

Configurable

Question No:159

(Marks:1)

Vu-Topper RM

_____ network does not depend on CSMA/CD.

Ethernet

Fast Ethernet

Gigabit Ethernet

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:160

(Marks:1)

Vu-Topper RM

Which of the following technologies can extend the diameter of LAN medium?

Fiber optic

Repeater

Both. Fiber optic and Repeaters

Question No:161

(Marks:1)

Vu-Topper RM

Connections are formed in Asynchronous transfer mode by starting values in _____ in ATM switches, as opposed to making actual electrical connections.

Heap

Stack

Memory locations page 67

Question No:162

(Marks:1)

Vu-Topper RM

The _____ scheme must be reliable to prevent conflicts.

Static

Dynamic page 34

Configurable

Question No:163

(Marks:1)

Vu-Topper RM

Metropolitan area network is used for _____.

City page 55

Building

Country

Question No:164

(Marks:1)

Vu-Topper RM

Which addressing can be only used in the local area networks?

IP google

Physical

Port

Question No:165

(Marks:1)

Vu-Topper RM

The sharing of a _____ among the workers in an office is a goal of resource sharing.

Mouse

Printer page 9

Keyboard

For More Help Vu-Topper RM Contact What's app 03224021365

Question No:166

(Marks:1)

Vu-Topper RM

ATM uses fixed size, small cells, 48 octet's data and _____.

Octets header

5 Octets header page 65

6 Octets header

Question No:167

(Marks:1)

Vu-Topper RM

Which of the followings is not an advantage of framing?

Missing eot indicates sending computer crashed.

Missing soh indicates receiving computer missed beginning of message.

Delimiters do not contain any user data page 16

Question No:168

(Marks:1)

Vu-Topper RM

The _____ field of Ethernet frame has the purpose of receiver synchronization.

Preamble page 36

Frame Type

Data

Question No:169

(Marks:1)

Vu-Topper RM

_____ was the first internet available for the first time.

ARPANAT

ARPANET page 9

Question No:170

(Marks:1)

Vu-Topper RM

We need packets rather than bits because _____

To compress the data

Sender and receiver need to coordinate to detect transmission errors. Page 14

Question No:171

(Marks:1)

Vu-Topper RM

When an application _____ any data, it makes a copy of the data available to all other computers on the network.

Multicast page 143

Broadcast

Question No:172

(Marks:1)

Vu-Topper RM

VBR stands for _____

Virtual Bit Rate

Variable Bit Rate page 71

For More Help Vu-Topper RM Contact What's app 03224021365