DOWNLOAD SOLVED FINAL

PAST PAPERS BY WAQAR SIDDHU

More in PDF From

VU Answer

Get All Solutions.

Question No : 1 of 52 Marks: 1 (Budgeted Time 1 Min)

Here the code is given below. You have to identify the problem in the code.

while((i < 10) && (i > 24))

Answer (Please select your correct option)

VuAnswers.com

- the logical operator && cannot be used in a test condition
- the while loop is an exit-condition loop
- the test condition is always true
- the test condition is always false

Made by: Waqar Siddhu

Question No : 2 of 52 Marks: 1 (Budgeted Time 1 Min)

Which one of the statements given below is equivalent to **sum += j*j** ?

Answer (Please select your correct option)

VuAnswers.com

- sum = j * j
- sum = sum + j
- sum = sum + j * j

correct

- sum * j = j

Made by: Waqar Siddhu

Question No : 3 of 52 Marks: 1 (Budgeted Time 1 Min)

All elements of an array must be of_____.

Answer (Please select your correct option)

VuAnswers.com

- different data type
- float data types only
- character data types only
- same data type

correct

Made by: Waqar Siddhu

Question No : 4 of 52 Marks: 1 (Budgeted Time 1 Min)

In C/C++, null character is represented as _____.

Answer (Please select your correct option)

VuAnswers.com

- \n correct
- \0
- \t
- \r

Made by: Waqar Siddhu

Question No : 5 of 52 Marks: 1 (Budgeted Time 1 Min)

The dynamic memory allocation uses memory from the _____.

Answer (Please select your correct option)

VuAnswers.com

- Stack
- Heap
- System Cache
- Secondary Storage

correct

Made by: Waqar Siddhu

Question No : 6 of 52 Marks: 1 (Budgeted Time 1 Min)

When a value is referred by a normal variable then it is known as_____.

Answer (Please select your correct option)

VuAnswers.com

- Direct Reference

correct

- Indirect Reference
- Proper Reference
- Partial Reference

Made by: Waqar Siddhu

Question No : 7 of 52 Marks: 1 (Budgeted Time 1 Min)

The address operator (&) is used with a _____.

Answer (Please select your correct option)

VuAnswers.com

- Statement
- Expression
- Variable
- Constant

correct

Made by: Waqar Siddhu

Question No : 8 of 52 Marks: 1 (Budgeted Time 1 Min)

A variable declared inside a code block becomes the _____ variable for that block.

Answer (Please select your correct option)

VuAnswers.com

- global
- static
- local
- inner

correct

Made by: Waqar Siddhu

Question No : 9 of 52 Marks: 1 (Budgeted Time 1 Min)

If a friend function outside the class declares itself friend of the class, this may violate the concept of

Answer (Please select your correct option)

VuAnswers.com

- Encapsulation and data accessing
- Encapsulation and data hiding
- Friend member functions of the class
- Interface of the class

correct

Made by: Waqar Siddhu

Question No : 10 of 52 Marks: 1 (Budgeted Time 1 Min)

In C/C++, _____ are the doors through which data can enter and come out of a program.

Answer (Please select your correct option)

VuAnswers.com

- Streams

correct

- Fields
- Variables
- Header files

Made by: Waqar Siddhu

Question No : 11 of 52 Marks: 1 (Budgeted Time 1 Min)

A _____ name includes a primary name and an optional period with an extension.

Answer (Please select your correct option)

VuAnswers.com

- File

correct

- Disk
- Data
- Database

Made by: Waqar Siddhu

Question No : 12 of 52 Marks: 1 (Budgeted Time 1 Min)

The operator used for casting in C is standard _____ operator.

VuAnswers.com

Answer (Please select your correct option)

- binary
- cast
- cost
- const

correct

Made by: Waqar Siddhu

Question No : 13 of 52 Marks: 1 (Budgeted Time 1 Min)

Both endl and flush are _____.

Answer (Please select your correct option)

VuAnswers.com

- Functions
- Operators
- Manipulators
- Objects

correct

Made by: Waqar Siddhu

Question No : 14 of 52 Marks: 1 (Budgeted Time 1 Min)

What will be the output of the following statement?

cout << setbase(16) << 52 ;

Answer (Please select your correct option)

VuAnswers.com

- 52
- 34 correct
- 64
- 32

Made by: Waqar Siddhu

Question No : 15 of 52 Marks: 1 (Budgeted Time 1 Min)

The return type of the operator function for << operator is _____.

VuAnswers.com

Answer (Please select your correct option)

- class for which we overload operator
- reference of ostream class (ostream&) correct
- reference of istream class (istream&)
- void

Made by: Waqar Siddhu

Question No : 16 of 52 Marks: 1 (Budgeted Time 1 Min)

new operator allocates memory from free store and returns _____.

Answer (Please select your correct option)

VuAnswers.com

- A pointer [redacted] correct
- A reference
- An integer
- A float

Made by: Waqar Siddhu

Question No : 17 of 52 Marks: 1 (Budgeted Time 1 Min)

The pointer returned by the new operator points to _____ of memory chunks allocated by the new operator.

VuAnswers.com

Answer (Please select your correct option)

- Second memory address
- First memory address

correct

- Last memory address
- Last memory address of the previous chunk

Made by: Waqar Siddhu

Question No : 18 of 52 Marks: 1 (Budgeted Time 1 Min)

A template function must have at least _____ generic data type.

VuAnswers.com

Answer (Please select your correct option)

- Zero
- One
- Two
- Three

Made by: Waqar Siddhu

Question No : 19 of 52 Marks: 1 (Budgeted Time 1 Min)

What does STL stand for?

VuAnswers.com

Answer (Please select your correct option)

- Source template library
- Standard template library
- Stream template library
- Standard temporary library

correct

Made by: Waqar Siddhu

Question No : 20 of 52 Marks: 1 (Budgeted Time 1 Min)

The appropriate data type to store the number of rows and colums of the matrix is_____.

Answer (Please select your correct option)

VuAnswers.com

- float
- strings
- int
- char

correct

Made by: Waqar Siddhu

Question No : 21 of 52 Marks: 1 (Budgeted Time 1 Min)

By using objects as class members, _____ is achieved.

Answer (Please select your correct option)

VuAnswers.com

- Accessibility
- Reliability
- Reusability
- Usability

correct

Made by: Waqar Siddhu

Question No : 22 of 52 Marks: 1 (Budgeted Time 1 Min)

_____ data members of a contained object can be accessed from inside of the containing class.

Answer (Please select your correct option)

VuAnswers.com

- Private
- Public
- Protected
- All

correct

Made by: Waqar Siddhu

Question No : 23 of 52 Marks: 1 (Budgeted Time 1 Min)

The normal source of cin object is _____.

Answer (Please select your correct option)

VuAnswers.com

- File
- Disk
- Keyboard
- RAM

correct

Made by: Waqar Siddhu

Question No : 24 of 52 Marks: 1 (Budgeted Time 1 Min)

The stream insertion and stream extraction operators are already overloaded for _____.

Answer (Please select your correct option)

VuAnswers.com

- User-defined data types
- Built-in data types
- User-defined and built-in data types
- Constants

correct

Made by: Waqar Siddhu

Question No : 25 of 52 Marks: 1 (Budgeted Time 1 Min)

When an object of a class is defined inside an other class then _____.

Answer (Please select your correct option)

VuAnswers.com

- Constructor of enclosing class will be called first
- Constructor of inner object will be called first
- Constructor and Destructor will be called simultaneously
- Only destructor will be called

correct

Made by: Waqar Siddhu

Question No : 26 of 52 Marks: 1 (Budgeted Time 1 Min)

The order of destruction of an object is _____.

Answer (Please select your correct option)

VuAnswers.com

- same as the construction order.
- reverse as the construction order.
- independent of the construction order.
- same as the order of objects declared.

correct

Made by: Waqar Siddhu

Question No : 27 of 52 Marks: 1 (Budgeted Time 1 Min)

A constructor will create a new object with a full copy of the other object, this type of copy is known as _____.

Answer (Please select your correct option)

VuAnswers.com

- Deep copy

correct

- Shallow copy
- Constructor copy
- Object copy

Made by: Waqar Siddhu

Question No : 28 of 52 Marks: 1 (Budgeted Time 1 Min)

_____ is the only operator that the compiler overloads for user defined data type.

Answer (Please select your correct option)

VuAnswers.com

- Plus (+)
- Minus (-)
- Equal (==)
- Assignment (=)

correct

Made by: Waqar Siddhu

Question No : 29 of 52 Marks: 1 (Budgeted Time 1 Min)

A class member function defined for overloading a unary operator takes how many arguments ?

VuAnswers.com

Answer (Please select your correct option)

- Zero
- One
- Two
- N arguments

Made by: Waqar Siddhu

Question No : 30 of 52 Marks: 1 (Budgeted Time 1 Min)

Static allocation is _____ efficient than the dynamic allocation.

VuAnswers.com

Answer (Please select your correct option)

- less

correct

- more
- equally
- it depends on the situation

Made by: Waqar Siddhu

Question No : 31 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following function call is correct for the function prototype?
defaultParameters (int a, int b = 7, char z = '*');

Answer (Please select your correct option)

VuAnswers.com

- defaultParameters (5);
- defaultParameters (5, '8');
- defaultParameters (6, '#');
- defaultParameters (0, 0, '*', 0);

correct

Made by: Waqar Siddhu

Question No : 32 of 52 Marks: 1 (Budgeted Time 1 Min)

The region of memory, available for allocation at run time in C language is called _____ memory whereas in C++ , is called _____.

Answer (Please select your correct option)

VuAnswers.com

- Heap, Stack
- Stack, Free Store
- Heap, Free Store
- Free store, Heap

correct

Made by: Waqar Siddhu

Question No : 33 of 52 Marks: 1 (Budgeted Time 1 Min)

The prototype of friend function is written _____.

Answer (Please select your correct option)

VuAnswers.com

- Before the class definition
- As private member function
- Anywhere inside the class definition

correct

- In the main function

Made by: Waqar Siddhu

Question No : 34 of 52 Marks: 1 (Budgeted Time 1 Min)

Which one of the given options is correct prototype syntax for overloaded operator?

VuAnswers.com

Answer (Please select your correct option)

- return-type operator-symbol (parameter-list) operator;
- operator return-type operator-symbol (parameter-list);
- return-type operator operator-symbol (parameter-list);
- return-type operator-symbol operator (parameter-list);

correct

Made by: Waqar Siddhu

Question No : 35 of 52 Marks: 1 (Budgeted Time 1 Min)

The declarator of Plus (+) member operator function is _____.

VuAnswers.com

Answer (Please select your correct option)

- Class-Name operator + (Class-Name rhs) correct
- operator Class-Name + ( )
- operator Class-Name + (rhs)
- Class-Name operator + ( )

Made by: Waqar Siddhu

Question No : 36 of 52 Marks: 1 (Budgeted Time 1 Min)

Sequence of event(s) when allocating memory using new operator is _____.

Answer (Please select your correct option)

VuAnswers.com

- Only block of memory is allocated for objects
- Only constructor is called for objects
- Memory is allocated first before calling constructor
- Constructor is called first before allocating memory

correct

Made by: Waqar Siddhu

Question No : 37 of 52 Marks: 1 (Budgeted Time 1 Min)

Individual characters in a string stored in an array can be accessed directly using array _____.

Answer (Please select your correct option)

VuAnswers.com

- Superscript
- Subscript
- Script
- Value

correct

Made by: Waqar Siddhu

Question No : 38 of 52 Marks: 1 (Budgeted Time 1 Min)

Whenever we allocate any memory from the_____ then starting position of the block of the memory allocated is returned as an address that is kept in a pointer.

Answer (Please select your correct option)

VuAnswers.com

- Flush
- Buffer
- Heap
- Stack

correct

Made by: Waqar Siddhu

Question No : 39 of 52 Marks: 1 (Budgeted Time 1 Min)

Whenever we allocate any memory from the heap then starting position of the block of the memory allocated is returned as a _____that is kept in a pointer.

VuAnswers.com

Answer (Please select your correct option)

- Variable
- Address
- Pointer
- Array

correct

Made by: Waqar Siddhu

Question No : 40 of 52 Marks: 1 (Budgeted Time 1 Min)

Constructor is a special function, called whenever we instantiate a _____ of a class.

VuAnswers.com

Answer (Please select your correct option)

- Function
- Data member
- Object
- Pointer

correct

Made by: Waqar Siddhu

Question No : 1 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following function call is "call by reference" for the following function prototype?
void func (int *);

Answer (Please select your correct option)

VuAnswers.com

- func(int &num) ;
- func(&num) ; correct
- func(*num) ;
- func(num) ;

Made by: Waqar Siddhu

Question No : 2 of 52 Marks: 1 (Budgeted Time 1 Min)

What is the highest legal index for the following array?
int arr[4]

VuAnswers.com

Answer (Please select your correct option)

- 4
- 3 correct
- 2
- 1

Made by: Waqar Siddhu

Question No : 3 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following is the correct way to initialize a character array 'course' with string 'programming'?

Answer (Please select your correct option)

VuAnswers.com

- course[12] ="programming";

correct

- course[] = {“programming”};
- course[] = 'programming' ;
- course = “programming” ;

Made by: Waqar Siddhu

Question No : 4 of 52 Marks: 1 (Budgeted Time 1 Min)

Using a segment of source code again by adding new functionalities with slight or no modification is termed as _____.

Answer (Please select your correct option)

VuAnswers.com

- code efficiency
- code reusability
- code modification
- code compatibility

correct

Made by: Waqar Siddhu

Question No : 5 of 52 Marks: 1 (Budgeted Time 1 Min)

_____ executes all the lines before error and stops at the line which contains the error.

Answer (Please select your correct option)

VuAnswers.com

- Intrepreter
- Compiler
- Linker
- Debugger

correct

Made by: Waqar Siddhu

Question No : 6 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following values are used in C/C++ to represent true and false?

VuAnswers.com

Answer (Please select your correct option)

- 1 and 0 correct
- 1 and -1
- 11 and 00
- Any numerical value

Made by: Waqar Siddhu

Question No : 7 of 52 Marks: 1 (Budgeted Time 1 Min)

When break statement is encountered in switch statement, it _____

Answer (Please select your correct option)

VuAnswers.com

- Stops the entire program
- Stops the execution of current statement
- Exits from switch statement
- Repeats the switch statement

correct

Made by: Waqar Siddhu

Question No : 8 of 52 Marks: 1 (Budgeted Time 1 Min)

What will be the output of this code segment?

```
int arr[6] = {2, 3, 7, 4, 5, 6} ;
int *ptr1 =&arr[1] ;
int *ptr2 = &arr[4] ;
cout << (ptr2-ptr1) ;
```

VuAnswers.com

Answer (Please select your correct option)

- 3
- 9
- 12
- 2

correct

Made by: Waqar Siddhu

Question No : 9 of 52 Marks: 1 (Budgeted Time 1 Min)

In C++, Integer calculation occurs in _____ bytes.

VuAnswers.com

Answer (Please select your correct option)

- 1 byte
- 2 bytes
- 4 bytes
- 8 bytes

correct

Made by: Waqar Siddhu

Question No : 10 of 52 Marks: 1 (Budgeted Time 1 Min)

In windows operating system, function calling is like sending a/an _____ to the object.

VuAnswers.com

Answer (Please select your correct option)

- Error
- Message
- Request
- Object

correct

Made by: Waqar Siddhu

Question No : 11 of 52 Marks: 1 (Budgeted Time 1 Min)

The static data members of a class will be _____.

VuAnswers.com

Answer (Please select your correct option)

- shared by objects
- created for each object
- initialized within class
- initialized within main function

correct

Made by: Waqar Siddhu

Question No : 12 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following option is true about static data members of a class?

VuAnswers.com

Answer (Please select your correct option)

- The static data members cannot be private or public
- The static data members must be private
- The static variables must be public
- The static data members can be private or public

© Made by: Waqar Siddhu

Question No : 13 of 52 Marks: 1 (Budgeted Time 1 Min)

When a variable is defined as static in a class then _____.

Answer (Please select your correct option)

VuAnswers.com

- Separate copy of this variable is created for each object
- Only one copy is created for all objects of this class
- A copy of this variable is created for only static objects
- No copy is created for the objects of that class

correct

Made by: Waqar Siddhu

Question No : 14 of 52 Marks: 1 (Budgeted Time 1 Min)

The pointer returned by the new operator points to _____ of memory chunks allocated by the new operator.

Answer (Please select your correct option)

VuAnswers.com

- Second memory address
- First memory address [redacted] correct
- Last memory address [redacted]
- Last memory address of the previous chunk

Made by: Waqar Siddhu

Question No : 15 of 52 Marks: 1 (Budgeted Time 1 Min)

A _____ is considered as a special type of pointer which contains address of a memory location.

Answer (Please select your correct option)

VuAnswers.com

- Function
- Structure
- Reference
- Class

correct

Made by: Waqar Siddhu

Question No : 16 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following operator the compiler overloads for objects by default?

VuAnswers.com

Answer (Please select your correct option)

- + operator
- - operator
- = operator

correct

- == operator

Made by: Waqar Siddhu

Question No : 17 of 52 Marks: 1 (Budgeted Time 1 Min)

If C1 and C2 are objects of the same class, what would a user get after compiling the following statement?
C1 = C2;

VuAnswers.com

Answer (Please select your correct option)

- The compiler will generate a syntax error regarding assignment operator not overloaded.
- The compiler will execute the statement but it will be a logical error.
- A run time error occurs
- The program will execute successfully without any logical error.

© Made by: Waqar Siddhu

Question No : 18 of 52 Marks: 1 (Budgeted Time 1 Min)

With template function, the compiler automatically detects the _____ and generates _____ using passed data.

VuAnswers.com

Answer (Please select your correct option)

- passed data , a new copy of function

correct

- parameters, an old copy of function
- old copy of function, parameters
- parameters, an new copy of function

Made by: Waqar Siddhu

Question No : 19 of 52 Marks: 1 (Budgeted Time 1 Min)

What does STL stand for?

VuAnswers.com

Answer (Please select your correct option)

- Source template library
- Standard template library
- Stream template library
- Standard temporary library

correct

Made by: Waqar Siddhu

Question No : 20 of 52 Marks: 1 (Budgeted Time 1 Min)

Templates provide way of abstracting _____ information.

VuAnswers.com

Answer (Please select your correct option)

- type

correct

- data
- method
- access

Made by: Waqar Siddhu

Question No : 21 of 52 Marks: 1 (Budgeted Time 1 Min)

The appropriate data type to store the number of rows and colums of the matrix is_____.

VuAnswers.com

Answer (Please select your correct option)

- float
- strings
- int
- char

correct

Made by: Waqar Siddhu

Question No : 22 of 52 Marks: 1 (Budgeted Time 1 Min)

Classes defined inside other classes are called _____ classes

VuAnswers.com

Answer (Please select your correct option)

- looped
- nested
- overloaded
- children classes

correct

Made by: Waqar Siddhu

Question No : 23 of 52 Marks: 1 (Budgeted Time 1 Min)

_____ data members of a contained object can be accessed from inside of the containing class.

Answer (Please select your correct option)

VuAnswers.com

- Private
- Public
- Protected
- All

correct

Made by: Waqar Siddhu

Question No : 24 of 52 Marks: 1 (Budgeted Time 1 Min)

If we write a statement like s2 = s1; _____ will be the calling object and _____ will be passed to the = operator as an argument.

VuAnswers.com

Answer (Please select your correct option)

- s1, s1
- s1, s2
- s2, s1 correct
- s2, s2

Made by: Waqar Siddhu

Question No : 25 of 52 Marks: 1 (Budgeted Time 1 Min)

We can use cin.peek() function to _____.

Answer (Please select your correct option)

VuAnswers.com

- See the next character that we are going to get. correct
- Get to the end of the input buffer.
- See the first character of input buffer.
- See the last character of the current input word.

Made by: Waqar Siddhu

Question No : 26 of 52 Marks: 1 (Budgeted Time 1 Min)

The stream insertion and stream extraction operators are already overloaded for _____.

Answer (Please select your correct option)

VuAnswers.com

- User-defined data types
- Built-in data types
- User-defined and built-in data types

correct

- Constants

Made by: Waqar Siddhu

Question No : 27 of 52 Marks: 1 (Budgeted Time 1 Min)

The order of destruction of an object is _____.

Answer (Please select your correct option)

VuAnswers.com

- same as the construction order.
- reverse as the construction order.
- independent of the construction order.
- same as the order of objects declared.

correct

Made by: Waqar Siddhu

Question No : 28 of 52 Marks: 1 (Budgeted Time 1 Min)

A constructor will create a new object with a full copy of the other object, this type of copy is known as _____.

VuAnswers.com

Answer (Please select your correct option)

- Deep copy correct
- Shallow copy
- Constructor copy
- Object copy

Made by: Waqar Siddhu

Question No : 29 of 52 Marks: 1 (Budgeted Time 1 Min)

A macro when takes arguments is called_____.

Answer (Please select your correct option)

VuAnswers.com

- function
- procedure
- parameterized macro
- simple macro

correct

Made by: Waqar Siddhu

Question No : 30 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following is NOT a preprocessor directive?

VuAnswers.com

Answer (Please select your correct option)

- #error
- #define
- #line
- #ndefine

correct

Made by: Waqar Siddhu

Question No : 31 of 52 Marks: 1 (Budgeted Time 1 Min)

Static allocation is _____ efficient than the dynamic allocation.

VuAnswers.com

Answer (Please select your correct option)

- less
- more
- equally
- it depends on the situation

correct

Made by: Waqar Siddhu

Question No : 32 of 52 Marks: 1 (Budgeted Time 1 Min)

The function free() returns back the allocated memory got through calloc and malloc to _____ .

Answer (Please select your correct option)

VuAnswers.com

- stack
- heap
- free memory store
- both to heap and stack

correct

Made by: Waqar Siddhu

Question No : 33 of 52 Marks: 1 (Budgeted Time 1 Min)

If constructor contains a return statement in its body then compiler will give _____.

VuAnswers.com

Answer (Please select your correct option)

- No error
- Syntax error
- Logical error
- Run time error

correct

Made by: Waqar Siddhu

Question No : 34 of 52 Marks: 1 (Budgeted Time 1 Min)

new and delete are also used with _____ and primitive data types as well.

VuAnswers.com

Answer (Please select your correct option)

- loops
- structures, pointers
- classes , structures

correct

- constant

Made by: Waqar Siddhu

Question No : 35 of 52 Marks: 1 (Budgeted Time 1 Min)

Memory allocated at run time is a system resource and it is the responsibility of _____ to de-allocate the memory.

VuAnswers.com

Answer (Please select your correct option)

- System
- Programmer
- User of program
- Operating System

correct

Made by: Waqar Siddhu

Question No : 36 of 52 Marks: 1 (Budgeted Time 1 Min)

Friend class of the other class gets _____ access to _____.

Answer (Please select your correct option)

VuAnswers.com

- Partial, data member and member functions.
- Read only, data member and member functions.
- Complete, data members only.
- Complete, all data members and member functions.

correct

Made by: Waqar Siddhu

Question No : 37 of 52 Marks: 1 (Budgeted Time 1 Min)

While overloading new and delete operators, we should take care that _____.

Answer (Please select your correct option)

VuAnswers.com

- They should be overloaded for specific types instead of overloading globally.
- Both of these operators should not be overloaded in the same program.
- We should never overload either of these operators.
- They should be not overloaded for specific types instead of overloading globally.

correct

Made by: Waqar Siddhu

Question No : 38 of 52 Marks: 1 (Budgeted Time 1 Min)

In case of _____default mechanism of function calling is call by value.

Answer (Please select your correct option)

VuAnswers.com

- Variable

correct

- Array
- Heap
- List

Made by: Waqar Siddhu

Question No : 39 of 52 Marks: 1 (Budgeted Time 1 Min)

A constructor has the same name as that of _____ .

VuAnswers.com

Answer (Please select your correct option)

- Variable
- Class
- Structure
- Function

correct

Made by: Waqar Siddhu

Question No : 40 of 52 Marks: 1 (Budgeted Time 1 Min)

The destructor for all the objects in the program is automatically called when _____.

Answer (Please select your correct option)

VuAnswers.com

- Memory is dynamically allocated to objects
- Objects are used inside functions
- Array of objects is declared
- Program is terminated

correct

Made by: Waqar Siddhu

Question No : 1 of 52 Marks: 1 (Budgeted Time 1 Min)

In Flow Chart, flow of control is represented by _____.

Answer (Please select your correct option)

VuAnswers.com

- Rectangle
- Circle
- Diamond
- Arrow

correct

Made by: Waqar Siddhu

Question No : 2 of 52 Marks: 1 (Budgeted Time 1 Min)

The operators ++ and -- are used to increment or decrement the value of a variable by _____

Answer (Please select your correct option)

VuAnswers.com

- 3
- 2
- 1 correct
- 4

Made by: Waqar Siddhu

Question No : 3 of 52 Marks: 1 (Budgeted Time 1 Min)

To assigned a value to a character type variable, _____ are used around the value.

VuAnswers.com

Answer (Please select your correct option)

- parenthesis ( )
- single qoutes ' '
- double qoutes " "
- curly braces { }

correct

Made by: Waqar Siddhu

Question No : 4 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following syntax will be used to initialize an array of size 5 of int data type to value 0?

Answer (Please select your correct option)

VuAnswers.com

- arr[5] = {0} ;
- int arr[5]= 0 ;
- int arr[5] = {0} ; correct
- int arr[] = 0 ;

Made by: Waqar Siddhu

Question No : 5 of 52 Marks: 1 (Budgeted Time 1 Min)

Let ptr1 and ptr2 are pointer variables that points to integer data types then which one of the following arithmetic is allowed?

VuAnswers.com

Answer (Please select your correct option)

- ptr1 + ptr2
- ptr1 - ptr2
- ptr1 * ptr2
- ptr1 / ptr2

correct

Made by: Waqar Siddhu

Question No : 6 of 52 Marks: 1 (Budgeted Time 1 Min)

When an argument is passed by reference, _____

Answer (Please select your correct option)

VuAnswers.com

- the function cannot access the argument's value.
- a variable is created in the function to hold the argument's value.
- a temporary variable is created in the calling program to hold the argument's value.
- the function accesses the argument's original value in the calling program.

Made by: Waqar Siddhu

Question No : 7 of 52 Marks: 1 (Budgeted Time 1 Min)

In year _____, C was approved as a standard langauge worldwide.

Answer (Please select your correct option)

VuAnswers.com

- 1988
- 1967
- 1989
- 1986

correct

Made by: Waqar Siddhu

Question No : 8 of 52 Marks: 1 (Budgeted Time 1 Min)

The C language was developed in late 60's and early 70's, in _____.

VuAnswers.com

Answer (Please select your correct option)

- Richards Laboratories
- Microsot Laboratories
- Bell Laboratories
- IBM Laboratories

correct

Made by: Waqar Siddhu

Question No : 9 of 52 Marks: 1 (Budgeted Time 1 Min)

If a friend function outside the class declares itself friend of the class, this may violate the concept of _____.

Answer (Please select your correct option)

VuAnswers.com

- Encapsulation and data accessing
- Encapsulation and data hiding
- Friend member functions of the class
- Interface of the class

correct

Made by: Waqar Siddhu

Question No : 10 of 52 Marks: 1 (Budgeted Time 1 Min)

A structure brings together a group of _____.

Answer (Please select your correct option)

VuAnswers.com

- same data type
- different data types
- constants
- both a, b

correct

Made by: Waqar Siddhu

Question No : 11 of 52 Marks: 1 (Budgeted Time 1 Min)

The member functions of a class occupy _____ region in memory for ____ object(s) of class.

VuAnswers.com

Answer (Please select your correct option)

- separate, each
- common, all
- different, each
- different, all

correct

Made by: Waqar Siddhu

Question No : 12 of 52 Marks: 1 (Budgeted Time 1 Min)

The static data members of a class are initialized _____.

VuAnswers.com

Answer (Please select your correct option)

- at file scope
- within class definition
- within member function
- within main function

correct

Made by: Waqar Siddhu

Question No : 13 of 52 Marks: 1 (Budgeted Time 1 Min)

The static data members of a class can be accessed by _____.

VuAnswers.com

Answer (Please select your correct option)

- only class
- only objects
- both class and objects

correct

- function out side the class

Made by: Waqar Siddhu

Question No : 14 of 52 Marks: 1 (Budgeted Time 1 Min)

Static variable which is defined in a function is initialized _____.

Answer (Please select your correct option)

VuAnswers.com

- Every time the function call
- Only once during its life time
- For many times in the program
- Compile time of the program

correct

Made by: Waqar Siddhu

Question No : 15 of 52 Marks: 1 (Budgeted Time 1 Min)

When a variable is defined as static in a class then _____.

Answer (Please select your correct option)

VuAnswers.com

- Separate copy of this variable is created for each object
- Only one copy is created for all objects of this class
- A copy of this variable is created for only static objects
- No copy is created for the objects of that class

correct

Made by: Waqar Siddhu

Question No : 16 of 52 Marks: 1 (Budgeted Time 1 Min)

When a call to a user-defined function finishes, the variable defined inside the function will _____.

Answer (Please select your correct option)

VuAnswers.com

- still in existence
- not exist further
- finish but a copy will remain in memory
- become static for other functions

correct

Made by: Waqar Siddhu

Question No : 17 of 52 Marks: 1 (Budgeted Time 1 Min)

What does STL stand for?

Answer (Please select your correct option)

VuAnswers.com

- Source template library
- Standard template library
- Stream template library
- Standard temporary library

correct

Made by: Waqar Siddhu

Question No : 18 of 52 Marks: 1 (Budgeted Time 1 Min)

The code is written to _____ the program.

VuAnswers.com

Answer (Please select your correct option)

- implement
- design
- analysis
- test

correct

Made by: Waqar Siddhu

Question No : 19 of 52 Marks: 1 (Budgeted Time 1 Min)

The appropriate data type to store the number of rows and colums of the matrix is_____.

Answer (Please select your correct option)

VuAnswers.com

- float
- strings
- int
- char

correct

Made by: Waqar Siddhu

Question No : 20 of 52 Marks: 1 (Budgeted Time 1 Min)

A class whose object is contained as const object, must have _____.

VuAnswers.com

Answer (Please select your correct option)

- Getter/Setter Functions
- Default Constructor
- Parameterized Constructor

correct

- Operator Overlaoding Functions

Made by: Waqar Siddhu

Question No : 21 of 52 Marks: 1 (Budgeted Time 1 Min)

_____ data members of a contained object can be accessed from inside of the containing class.

Answer (Please select your correct option)

VuAnswers.com

- Private
- Public
- Protected
- All

correct

Made by: Waqar Siddhu

Question No : 22 of 52 Marks: 1 (Budgeted Time 1 Min)

The initializer list is used to initialize the contained objects of a class at _____.

Answer (Please select your correct option)

VuAnswers.com

- Run time
- Debugging time
- Construction time
- Compile time

correct

Made by: Waqar Siddhu

Question No : 23 of 52 Marks: 1 (Budgeted Time 1 Min)

The normal source of cin object is _____.

Answer (Please select your correct option)

VuAnswers.com

- File
- Disk
- Keyboard
- RAM

correct

Made by: Waqar Siddhu

Question No : 24 of 52 Marks: 1 (Budgeted Time 1 Min)

We can use cin.peek() function to _____.

Answer (Please select your correct option)

VuAnswers.com

- See the next character that we are going to get.
- Get to the end of the input buffer.
- See the first character of input buffer.
- See the last character of the current input word.

correct

Made by: Waqar Siddhu

Question No : 25 of 52 Marks: 1 (Budgeted Time 1 Min)

When an object of a class is defined inside another class then _____.

Answer (Please select your correct option)

VuAnswers.com

- Destructor of enclosing class will be called first

correct

- Destructor of inner object will be called first
- Constructor and Destructor will be called simultaneously
- Only destructor will be called

Made by: Waqar Siddhu

Question No : 26 of 52 Marks: 1 (Budgeted Time 1 Min)

The order of destruction of an object is _____.

Answer (Please select your correct option)

VuAnswers.com

- same as the construction order.
- reverse as the construction order.
- independent of the construction order.
- same as the order of objects declared.

correct

Made by: Waqar Siddhu

Question No : 27 of 52 Marks: 1 (Budgeted Time 1 Min)

A macro when takes arguments is called_____.

Answer (Please select your correct option)

VuAnswers.com

- function
- procedure
- parameterized macro
- simple macro

correct

Made by: Waqar Siddhu

Question No : 28 of 52 Marks: 1 (Budgeted Time 1 Min)

Which is NOT a protection level provided by classes in C++?

VuAnswers.com

Answer (Please select your correct option)

- protected
- hidden
- private
- public

correct

Made by: Waqar Siddhu

Question No : 29 of 52 Marks: 1 (Budgeted Time 1 Min)

What should be the return type of the constructor?

VuAnswers.com

Answer (Please select your correct option)

- void pointer
- int
- same as object type
- constructors do not return any thing

correct

Made by: Waqar Siddhu

Question No : 30 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following function call is correct for the function prototype?
defaultParameters (int a, int b = 7, char z = '*');

Answer (Please select your correct option)

VuAnswers.com

- defaultParameters (5);
- defaultParameters (5, '8');
- defaultParameters (6, '#');
- defaultParameters (0, 0, '*', 0);

correct

Made by: Waqar Siddhu

Question No : 31 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following function cannot be overloaded?

Answer (Please select your correct option)

VuAnswers.com

- Member functions
- Utility functions
- Constructor
- Destructor

correct

Made by: Waqar Siddhu

Question No : 32 of 52 Marks: 1 (Budgeted Time 1 Min)

Users must not know about _____.

Answer (Please select your correct option)

VuAnswers.com

- Methods functionality with in class

correct

- Objects of class
- Functions name within class
- Class implementation of functionality and interfaces

Made by: Waqar Siddhu

Question No : 33 of 52 Marks: 1 (Budgeted Time 1 Min)

new and delete are also used with _____ and primitive data types as well.

VuAnswers.com

Answer (Please select your correct option)

- loops
- structures, pointers
- classes , structures

correct

- constant

Made by: Waqar Siddhu

Question No : 34 of 52 Marks: 1 (Budgeted Time 1 Min)

If there is a symbol (& sign) used with the variable name followed by data type then it refers to _____.

Answer (Please select your correct option)

VuAnswers.com

- Logic expression
- Value of variable
- Reference variable
- Address of variable

correct

Made by: Waqar Siddhu

Question No : 35 of 52 Marks: 1 (Budgeted Time 1 Min)

Consider the following code segment.

```
class M {
public:
  M &operator+(const M &);
...
```

Answer (Please select your correct option)

VuAnswers.com

- Member function

correct

- Non-member function
- Friend function
- Virtual function

Made by: Waqar Siddhu

Question No : 36 of 52 Marks: 1 (Budgeted Time 1 Min)

Sequence of event(s) when deallocating memory using delete operator is _____.

VuAnswers.com

Answer (Please select your correct option)

- Only block of memory is deallocated for objects
- Only destructor is called for objects
- Memory is deallocated first before calling destructor

correct

- Destructor is called first before deallocating memory

Made by: Waqar Siddhu

Question No : 35 of 52 Marks: 1 (Budgeted Time 1 Min)

```
  M &operator+(const M &);
...
};

p + q          //code of line implies that  p.operator+(q)
        ...
```

Answer (Please select your correct option)

VuAnswers.com

- Member function
- Non-member function
- Friend function
- Virtual function

Made by: Waqar Siddhu

Question No : 35 of 52 Marks: 1 (Budgeted Time 1 Min)

```
...
};

p + q          //code of line implies that  p.operator+(q)
        ...
```

Let assume if p and q are class objects then function is implemented as _____.

VuAnswers.com

Answer (Please select your correct option)

- Member function
- Non-member function
- Friend function
- Virtual function

Made by: Waqar Siddhu

Question No : 36 of 52 Marks: 1 (Budgeted Time 1 Min)

Sequence of event(s) when deallocating memory using delete operator is _____.

VuAnswers.com

Answer (Please select your correct option)

- Only block of memory is deallocated for objects
- Only destructor is called for objects
- Memory is deallocated first before calling destructor
- Destructor is called first before deallocating memory

Made by: Waqar Siddhu

Question No : 37 of 52 Marks: 1 (Budgeted Time 1 Min)

What will be the correct syntax of declaration of the following statement?
ptr is a pointer to const int.

VuAnswers.com

Answer (Please select your correct option)

- const int *ptr;
- int* const ptr;
- int const *ptr;
- const *int ptr;

correct

Made by: Waqar Siddhu

Question No : 38 of 52 Marks: 1 (Budgeted Time 1 Min)

A constructor has the same name as that of _____ .

VuAnswers.com

Answer (Please select your correct option)

- Variable
- Class
- Structure
- Function

correct

Made by: Waqar Siddhu

Question No : 39 of 52 Marks: 1 (Budgeted Time 1 Min)

Whenever **new** operator is called to create an object, the _____ is also called for that object.

VuAnswers.com

Answer (Please select your correct option)

- Constructor

correct

- Destructor
- Pointer
- Array

Made by: Waqar Siddhu

Question No : 40 of 52 Marks: 1 (Budgeted Time 1 Min)

The destructor for all the objects in the program is automatically called when _____.

Answer (Please select your correct option)

VuAnswers.com

- Memory is dynamically allocated to objects
- Objects are used inside functions
- Array of objects is declared
- Program is terminated

correct

Made by: Waqar Siddhu

Question No : 1 of 52 Marks: 1 (Budgeted Time 1 Min)

In Flow Chart, flow of control is represented by _____.

Answer (Please select your correct option)

VuAnswers.com

- Rectangle
- Circle
- Diamond
- Arrow

correct

Made by: Waqar Siddhu

Question No : 2 of 52 Marks: 1 (Budgeted Time 1 Min)

You can use a _____ statement to transfer control elsewhere out of the nested structure.

VuAnswers.com

Answer (Please select your correct option)

- continue
- goto
- pause
- break

correct

Made by: Waqar Siddhu

Question No : 3 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the given operators is not a valid compound assignment operator ?

VuAnswers.com

Answer (Please select your correct option)

- >>=
- =>>
- *=
- &=

correct

Made by: Waqar Siddhu

Question No : 4 of 52 Marks: 1 (Budgeted Time 1 Min)

The purpose of using cout<< is to _____.

VuAnswers.com

Answer (Please select your correct option)

- Display information on the screen

correct

- Read the data from keyboard
- Read the data from a file
- Write into a file

Made by: Waqar Siddhu

Question No : 5 of 52 Marks: 1 (Budgeted Time 1 Min)

Assignment operator is used for _____.

VuAnswers.com

Answer (Please select your correct option)

- calculation
- reading
- assigning values to variables
- equality checking

correct

Made by: Waqar Siddhu

Question No : 6 of 52 Marks: 1 (Budgeted Time 1 Min)

Missing semicolon ';' at the end of C++ statement causes a _____ error.

VuAnswers.com

Answer (Please select your correct option)

- Logical
- Syntax
- Runtime
- Compile time

correct

Made by: Waqar Siddhu

Question No : 7 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following is not an example of int data type?

VuAnswers.com

Answer (Please select your correct option)

- 0
- -32
- 65531
- -4.0

correct

Made by: Waqar Siddhu

Question No : 8 of 52 Marks: 1 (Budgeted Time 1 Min)

For which array, the size of the array should be one more than the number of elements in an array?

VuAnswers.com

Answer (Please select your correct option)

- int
- double
- float
- char

correct

Made by: Waqar Siddhu

Question No : 9 of 52 Marks: 1 (Budgeted Time 1 Min)

If an integer takes 4 bytes in the memory then how many bytes will be allocated in the memory for the following code?

```
#include<iostream.h>
#include<stdlib.h>

int main()
```

VuAnswers.com

Answer (Please select your correct option)

- 12 bytes
- 24 bytes
- 48 bytes
- 32 bytes

Made by: Waqar Siddhu

Question No : 9 of 52 Marks: 1 (Budgeted Time 1 Min)

```
{

   int (*p)[4];
   p = (int (*) [4])malloc(3 *sizeof(*p));
   return 0;

}
```

VuAnswers.com

Answer (Please select your correct option)

- 12 bytes
- 24 bytes
- 48 bytes
- 32 bytes

Made by: Waqar Siddhu

Question No : 10 of 52 Marks: 1 (Budgeted Time 1 Min)

Which header file should be included to use functions like malloc() and calloc()?

VuAnswers.com

Answer (Please select your correct option)

- memory.h
- iostream.h
- stdlib.h

correct

- conio.h

Made by: Waqar Siddhu

Question No : 11 of 52 Marks: 1 (Budgeted Time 1 Min)

Using a segment of source code again by adding new functionalities with slight or no modification is termed as _____.

VuAnswers.com

Answer (Please select your correct option)

- code efficiency
- code reusability
- code modification
- code compatibility

correct

Made by: Waqar Siddhu

Question No : 12 of 52 Marks: 1 (Budgeted Time 1 Min)

The programs in which we allocate static memory run essentially on _____.

Answer (Please select your correct option)

VuAnswers.com

- Heap
- System Cache
- Free Store
- Stack

correct

Made by: Waqar Siddhu

Question No : 13 of 52 Marks: 1 (Budgeted Time 1 Min)

TWAIN stands for _____ .

Answer (Please select your correct option)

VuAnswers.com

- Technology With An Interesting Name
- Technology Without An Informative Name
- Technology Without An Interesting Name

correct

- Technology With An Informative Name

Made by: Waqar Siddhu

Question No : 14 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following will be the correct function call for function prototype given below?
int func (int &);

VuAnswers.com

Answer (Please select your correct option)

- func(int num);
- func(&num);
- func(num);
- func(*num);

correct

Made by: Waqar Siddhu

Question No : 15 of 52 Marks: 1 (Budgeted Time 1 Min)

The operator used for casting in C is standard _____ operator.

VuAnswers.com

Answer (Please select your correct option)

- binary
- cast
- cost
- const

correct

Made by: Waqar Siddhu

The image part with relationship ID rId2 was not found in the file.

Question No : 17 of 52 Marks: 1 (Budgeted Time 1 Min)

The stream insertion and extraction operators _____.

VuAnswers.com

Answer (Please select your correct option)

- must be overloaded as member function
- must be overloaded as non-member function
- can be overloaded either as member or non-member
- always overloaded in class functions

correct

Made by: Waqar Siddhu

Question No : 18 of 52 Marks: 1 (Budgeted Time 1 Min)

The operator function for stream insertion(>>) and stream extraction (<<) must be _____.

VuAnswers.com

Answer (Please select your correct option)

- A member function of class
- Non-member function of class
- Can be a member and non-member function
- A constructor of the class

correct

Made by: Waqar Siddhu

Question No : 19 of 52 Marks: 1 (Budgeted Time 1 Min)

In statement Matrix m2 = m1 ;

VuAnswers.com

Answer (Please select your correct option)

- Assignment operator is being used

correct

- Copy constructor is being used.
- Statement has syntax error
- Statement has logical error

Made by: Waqar Siddhu

Question No : 20 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following is true while overloading operators?

VuAnswers.com

Answer (Please select your correct option)

- Precedence of an operator can be changed
- The arity (number of operands) can be changed
- No new operators can be created
- Associativity of an operator can be changed

Made by: Waqar Siddhu

Question No : 21 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following is true about operator overloading?

VuAnswers.com

Answer (Please select your correct option)

- The operator works with only objects of the class in which it is overloaded.
- The operator works with objects and primitive data types regardless of parameters.
- The operator works with both objects and primitive data types depending on parameters.
- The operator must have a constant and an object as parameters.

Made by: Waqar Siddhu

Question No : 22 of 52 Marks: 1 (Budgeted Time 1 Min)

A template function must have at least _____ generic data type.

VuAnswers.com

Answer (Please select your correct option)

- Zero
- One
- Two
- Three

Made by: Waqar Siddhu

Question No : 23 of 52 Marks: 1 (Budgeted Time 1 Min)

Templates provide way of abstracting _____ information.

VuAnswers.com

Answer (Please select your correct option)

- type
- data
- method
- access

Made by: Waqar Siddhu

Question No : 24 of 52 Marks: 1 (Budgeted Time 1 Min)

The appropriate data type to store the number of rows and colums of the matrix is_____.

VuAnswers.com

Answer (Please select your correct option)

- int
- char
- float
- strings

Made by: Waqar Siddhu

Question No : 25 of 52 Marks: 1 (Budgeted Time 1 Min)

ANSI stands for _____.

Answer (Please select your correct option)

VuAnswers.com

- Asian National Standards Institute
- American National Standards Institute
- American Neutral Standards Institute
- Australian National Standards Institute

Made by: Waqar Siddhu

Question No : 26 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following option will be true, if we overload "-=" operator?

VuAnswers.com

Answer (Please select your correct option)

- only - operator needs to be overloaded
- Minus (-) and = operators need to be overloaded
- the -= operator need to be overloaded explicitly
- the - and = operators need to be overloaded implicitly

Made by: Waqar Siddhu

Question No : 27 of 52 Marks: 1 (Budgeted Time 1 Min)

In operator overloading, a non-member unary operator function takes _____ arguments.

VuAnswers.com

Answer (Please select your correct option)

- 0
- 2
- 1
- 3

Made by: Waqar Siddhu

Question No : 28 of 52 Marks: 1 (Budgeted Time 1 Min)

By using objects as class members, _____ is achieved.

VuAnswers.com

Answer (Please select your correct option)

- Accessibility
- Reliability
- Reusability
- Usability

Made by: Waqar Siddhu

Question No : 29 of 52 Marks: 1 (Budgeted Time 1 Min)

A class whose object is contained as const object, must have _____.

VuAnswers.com

Answer (Please select your correct option)

- Getter/Setter Functions
- Default Constructor
- Parameterized Constructor
- Operator Overlaoding Functions

Made by: Waqar Siddhu

Question No : 30 of 52 Marks: 1 (Budgeted Time 1 Min)

The initializer list is used to initialize the contained objects of a class at _____.

VuAnswers.com

Answer (Please select your correct option)

- Debugging time
- Construction time
- Compile time
- Run time

Made by: Waqar Siddhu

Question No : 31 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following statement is true about Assignment operator (=) and output stream 'cout'?

VuAnswers.com

Answer (Please select your correct option)

- Assignment operator is left associative whereas cout is right associative.
- Assignment operator is right associative whereas cout is left associative.
- Both (Assignment operator, output stream 'cout') are right associative.
- Both (Assignment operator, output stream 'cout') are left associative.

Made by: Waqar Siddhu

Question No : 32 of 52 Marks: 1 (Budgeted Time 1 Min)

The stream insertion and stream extraction operators are already overloaded for _____.

VuAnswers.com

Answer (Please select your correct option)

- User-defined data types
- Built-in data types
- User-defined and built-in data types
- Constants

Made by: Waqar Siddhu

Question No : 33 of 52 Marks: 1 (Budgeted Time 1 Min)

The input/output streams cin and cout are _____ therefore have _____.

VuAnswers.com

Answer (Please select your correct option)

- Structures, function
- Objects, member functions
- Functions, objects
- Structures, non member functions

Made by: Waqar Siddhu

Question No : 34 of 52 Marks: 1 (Budgeted Time 1 Min)

When an object of a class is defined inside an other class then _____.

VuAnswers.com

Answer (Please select your correct option)

- Constructor of enclosing class will be called first
- Constructor of inner object will be called first
- Constructor and Destructor will be called simultaneously
- Only destructor will be called

Made by: Waqar Siddhu

Question No : 35 of 52 Marks: 1 (Budgeted Time 1 Min)

If text is a pointer of class String then purpose of statement below is to _____.

text = new String [5];

VuAnswers.com

Answer (Please select your correct option)

- Create an array of 5 string objects statically
- Create an array of 5 string objects dynamically
- Create an array of pointers to String
- Create an object of String

Made by: Waqar Siddhu

Question No : 36 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following is NOT a preprocessor directive?

VuAnswers.com

Answer (Please select your correct option)

- #error
- #define
- #line
- #ndefine

Made by: Waqar Siddhu

Question No : 37 of 52 Marks: 1 (Budgeted Time 1 Min)

The function free() returns back the allocated memory got through calloc and malloc to _____ .

VuAnswers.com

Answer (Please select your correct option)

- stack
- heap
- free memory store
- both to heap and stack

Made by: Waqar Siddhu

Question No : 38 of 52 Marks: 1 (Budgeted Time 1 Min)

Which value is returned by the destructor of a class?

VuAnswers.com

Answer (Please select your correct option)

- A pointer to the class.
- An object of the class.
- A status code determining whether the class was destructed correctly
- Destructors do not return a value.

Made by: Waqar Siddhu

Question No : 39 of 52 Marks: 1 (Budgeted Time 1 Min)

(*this) represents _____.

VuAnswers.com

Answer (Please select your correct option)

- The current function of the class
- The current pointer of the class
- The current object of the class
- A value of the data member

Made by: Waqar Siddhu

Question No : 40 of 52 Marks: 1 (Budgeted Time 1 Min)

When we define an array of objects then _____.

VuAnswers.com

Answer (Please select your correct option)

- Constructor will never call
- Depends on the size of array
- Constructor will be called once for whole array
- Constructor will be called for each object of the array

Made by: Waqar Siddhu

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 1 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Loop is also called _____ structure.

Answer (Please select your correct option)

- Decision
- Repetition

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Sequential
- Hierarchical

Start Time: 4:10 PM
110:00
Time Left

MADE BY WAQAR SIDDHU

Done Local intranet 100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..:::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination
VU Examination System (...
Page Safety Tools

Question No : 2 of 52 **Marks: 1 (Budgeted Time 1 Min)**

When a multidimensional array is accessed, each array index is_____

Answer (Please select your correct option)

- separated by commas
- surrounded by brackets and separated by commas

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- separated by commas and surrounded by brackets
- surrounded by brackets.

Start Time: 4:10 PM
110:00
Time Left

2

MADE BY WAQAR SIDDHU

paper.aspx
Local intranet
100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 3 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Which of the given operators is not a valid compound assignment operator ?

Answer (Please select your correct option)

- >>=
- =>>
- *=
- &=

correct

Start Time: 4:10 PM
110:00
Time Left

MADE BY WAQAR SIDDHU

paper.aspx
Local intranet 100%

Question No : 4 of 52 Marks: 1 (Budgeted Time 1 Min)

To assigned a value to a character type variable, _____ are used around the value.

Answer (Please select your correct option)

- parenthesis ( )
- single qoutes ' '
- double qoutes " "
- curly braces { }

correct

Made by: Waqar Siddhu

Question No : 5 of 52 Marks: 1 (Budgeted Time 1 Min)

We use variable of type _____ to store any character value like a, b, c.

Answer (Please select your correct option)

- int
- double
- float
- char

correct

Made by: Waqar Siddhu

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 6 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Which of the following data types will be assumed if no data type is specified with constant?

Answer (Please select your correct option)

- short
- float
- int

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- double

Start Time: 4:10 PM
110:00
Time Left

6

MADE BY WAQAR SIDDHU

paper.aspx
Local intranet 100%

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 7 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Which header file should be included to use functions like malloc() and calloc()?

Answer (Please select your correct option)

- memory.h
- iostream.h
- stdlib.h

correct

- conio.h

email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:10 PM
110:00
Time Left

MADE BY WAQAR SIDDHU

paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..:::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
Live Search
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination
VU Examination System (...
Page Safety Tools

Question No : 8 of 52 **Marks: 1 (Budgeted Time 1 Min)**

If we have **x = 7** then the new value of x after evaluating the expression **x%= 2** is _____

Answer (Please select your correct option)

- 2
- 3
- 1
- 7

Start Time: 4:10 PM
110:00
Time Left

8

MADE BY WAQAR SIDDHU

paper.aspx
Local intranet
100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..:::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 9 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The statement x += y can be interpreted as _____.

Answer (Please select your correct option)

- Adding the value of the x to the value of the y and storing the result in x — correct
- Adding the value of the y to the value of the x; store the result in y
- Adding the value of the x to the value of the x; store the result in x
- Adding the value of the y to the value of the y; store the result in x

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:10 PM
110:00
Time Left
9
MADE BY WAQAR SIDDHU
paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
Live Search
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination
VU Examination System (...
Page Safety Tools

Question No : 10 of 52 **Marks: 1 (Budgeted Time 1 Min)**

A variable declared inside a code block becomes _____ variable for that block.

Answer (Please select your correct option)

- global
- static
- local
- inner

correct

Start Time: 4:10 PM
110:00
Time Left

10

MADE BY WAQAR SIDDHU

paper.aspx
Local intranet
100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..:::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 11 of 52 **Marks: 1 (Budgeted Time 1 Min)**

If a friend function outside the class declares itself friend of the class, this may violate the concept of _____.

Answer (Please select your correct option)

- Encapsulation and data accessing
- Encapsulation and data hiding

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Friend member functions of the class
- Interface of the class

Start Time: 4:10 PM
110:00
Time Left

11

MADE BY WAQAR SIDDHU

paper.aspx
Local intranet 100%

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 12 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Initializing the data members in the definition of the class is _____

Answer (Please select your correct option)

- syntax error — correct
- logical error
- not an error
- compile time error

Start Time: 4:10 PM
110:00
Time Left
12
MADE BY WAQAR SIDDHU
paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 13 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The functions width, fill and precision are defined in _____ header file.

Answer (Please select your correct option)

- conio.h
- iomanip.h
- iostream.h
- stdlib.h

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:10 PM
110:00
Time Left

13

MADE BY WAQAR SIDDHU

paper.aspx
Local intranet 100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
Live Search
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination
VU Examination System (...
Page Safety Tools

Question No : 14 of 52 **Marks: 1 (Budgeted Time 1 Min)**

width() is a member function of _____.

Answer (Please select your correct option)

- cin object
- cout object
- Both cout and cin objects

correct

- User-defined class

Start Time: 4:10 PM
110:00
Time Left

14

MADE BY WAQAR SIDDHU
paper.aspx
Local intranet
100%

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 15 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The first parameter of operator function for << operator,

Answer (Please select your correct option)

- Must be passed by value
- Must be passed by reference

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Can be passed by value or reference
- Must be object of class

Start Time: 4:10 PM
110:00
Time Left

15

MADE BY WAQAR SIDDHU

paper.aspx
Local intranet 100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 16 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Which of the following option is true about static data members of a class?

Answer (Please select your correct option)

- The static data members cannot be private or public
- The static data members must be private
- The static variables must be public
- The static data members can be private or public

correct

Start Time: 4:10 PM
110:00
Time Left

16

MADE BY WAQAR SIDDHU

paper.aspx
Local intranet 100%

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 17 of 52 **Marks: 1 (Budgeted Time 1 Min)**

When a call to a user-defined function finishes, the variable defined inside the function will _____.

Answer (Please select your correct option)

- still in existence
- not exist further
- finish but a copy will remain in memory
- become static for other functions

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

correct

Start Time: 4:10 PM
110:00
Time Left
17
MADE BY WAQAR SIDDHU
paper.aspx

Question No : 18 of 52 Marks: 1 (Budgeted Time 1 Min)

The pointer returned by the new operator points to _____ of memory chunks allocated by the new operator.

Answer (Please select your correct option)

- Second memory address
- First memory address

correct

- Last memory address
- Last memory address of the previous chunk

Made by: Waqar Siddhu

Question No : 19 of 52 **Marks: 1 (Budgeted Time 1 Min)**

If overloaded plus operator is implemented as member function then which of the following option will be true for the statement given below?
obj3 = obj1 + obj2 ;

Answer (Please select your correct option)

- obj1 will be passed as an argument to + operator whereas obj2 will drive the + operator
- obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator
- Both objects (obj1, obj2) will be passed as arguments to the + operator
- Any of the objects (obj1, obj2) can drive the + operator

correct

Made by: Waqar Siddhu

Question No : 20 of 52 Marks: 1 (Budgeted Time 1 Min)

A template function must have at least _____ generic data type.

Answer (Please select your correct option)

- Zero
- One
- Two
- Three

correct

Made by: Waqar Siddhu

Question No : 21 of 52 Marks: 1 (Budgeted Time 1 Min)

With template function, the compiler automatically detects the _____ and generates _____ using passed data.

Answer (Please select your correct option)

- passed data , a new copy of function — correct
- parameters, an old copy of function
- old copy of function, parameters
- parameters, an new copy of function

Made by: Waqar Siddhu

Question No : 22 of 52 Marks: 1 (Budgeted Time 1 Min)

The appropriate data type to store the number of rows and colums of the matrix is_____.

Answer (Please select your correct option)

- float
- strings
- int
- char

correct

Made by: Waqar Siddhu

Question No : 23 of 52 Marks: 1 (Budgeted Time 1 Min)

ANSI stands for _____.

Answer (Please select your correct option)

- American Neutral Standards Institute
- Australian National Standards Institute
- Asian National Standards Institute
- American National Standards Institute

correct

Made by: Waqar Siddhu

Question No : 24 of 52 Marks: 1 (Budgeted Time 1 Min)

In the member initializer list, the data members are initialized _____.

Answer (Please select your correct option)

- From left to right
- From right to left
- In the order in which they are defined within class
- There is no order for initialization

correct

Made by: Waqar Siddhu

Question No : 25 of 52 Marks: 1 (Budgeted Time 1 Min)

The initializer list is used to initialize the contained objects of a class at _____.

Answer (Please select your correct option)

- Run time
- Debugging time
- Construction time
- Compile time

correct

Made by: Waqar Siddhu

Question No : 26 of 52 Marks: 1 (Budgeted Time 1 Min)

When an object of a class is defined inside an other class then _____.

Answer (Please select your correct option)

- Constructor of enclosing class will be called first

correct

- Constructor of inner object will be called first
- Constructor and Destructor will be called simultaneously
- Only destructor will be called

Made by: Waqar Siddhu

Question No : 27 of 52 Marks: 1 (Budgeted Time 1 Min)

A constructor will create a new object with a full copy of the other object, this type of copy is known as _____.

Answer (Please select your correct option)

- Deep copy

correct

- Shallow copy
- Constructor copy
- Object copy

Made by: Waqar Siddhu

Question No : 28 of 52 Marks: 1 (Budgeted Time 1 Min)

When we define an array of objects then _____.

Answer (Please select your correct option)

- Destructor will be called once for the whole array
- Destructor will be called for each object of the array
- No Destructor will be called
- Destructor for only first object in the array will be called

correct

Made by: Waqar Siddhu

Question No : 29 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following function is used to increase the size of already allocated memory chunk?

Answer (Please select your correct option)

- malloc
- calloc
- realloc
- free

correct

Made by: Waqar Siddhu

Question No : 30 of 52 Marks: 1 (Budgeted Time 1 Min)

NULL value has been defined in _____ and _____ header files.

Answer (Please select your correct option)

- strings.h , iostream.h
- ctype.h , conio.c
- conio.c , conio.h
- stdlib.h , stddef.h

correct

Made by: Waqar Siddhu

Question No : 31 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Which of the following function call is correct for the function prototype?
defaultParameters (int a, int b = 7, char z = '*');

Answer (Please select your correct option)

- defaultParameters (5);

  correct
- defaultParameters (5, '8');
- defaultParameters (6, '#');
- defaultParameters (0, 0, '*', 0);

Made by: Waqar Siddhu

Question No : 32 of 52 Marks: 1 (Budgeted Time 1 Min)

Friend function of a class is _____.

Answer (Please select your correct option)

- Private function
- Non-member function

correct

- Public function
- Member function

Made by: Waqar Siddhu

Question No : 33 of 52 Marks: 1 (Budgeted Time 1 Min)

The declarator of Plus (+) member operator function is _____.

Answer (Please select your correct option)

- Class-Name operator + (Class-Name rhs)
- operator Class-Name + ( )
- operator Class-Name + (rhs)
- Class-Name operator + ( )

Made by: Waqar Siddhu

Question No : 34 of 52 Marks: 1 (Budgeted Time 1 Min)

The operator function will be implemented as _____, if obj1 drive the - operator whereas obj2 is passed as arguments to - operator in the statement given below.

```
obj3 = obj1 - obj2;
```

Answer (Please select your correct option)

- Friend function
- Virtual Function
- Member function — correct
- Non-member function

Made by: Waqar Siddhu

Question No : 35 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Consider the following code segment

```
class M {
  friend int operator!(const M &);
...
};
```

Answer (Please select your correct option)

- Member function
- Non-member function
- Binary operator function
- Friend Function

Made by: Waqar Siddhu

Question No : 36 of 52 Marks: 1 (Budgeted Time 1 Min)

When the compiler overloads the assignment (=) operator by default then _____.

Answer (Please select your correct option)

- compiler does not allow default overload of assignment (=) operator
- member of the class are not assigned properly
- Compiler does assiggnment of some selected members
- compiler does member wise assignment.

Made by: Waqar Siddhu

Question No : 37 of 52 Marks: 1 (Budgeted Time 1 Min)

Correct syntax of function prototype for overloading new operator is _____.

Answer (Please select your correct option)

- void* new operator(size_t size)
- void* new(size_t size)
- operator new(size_t size)
- void* operator new(size_t size)

correct

Made by: Waqar Siddhu

Question No : 38 of 52 Marks: 1 (Budgeted Time 1 Min)

There is a pointer variable named ***ptr*** of type float then address of which type of variable the ***ptr*** will store in it?

Answer (Please select your correct option)

- int correct
- float
- char
- double

Made by: Waqar Siddhu

Question No : 39 of 52 Marks: 1 (Budgeted Time 1 Min)

Which one is the correct syntax for defining an identifier PI with preprocessor directive?

Answer (Please select your correct option)

- #undef PI 3.1415926
- #define PI 3.1415926 correct
- #define PI = 3.1415926
- #ifdef PI = 3.1415926

Made by: Waqar Siddhu

Question No : 40 of 52 Marks: 1 (Budgeted Time 1 Min)

Whenever we allocate any memory from the_____ then starting position of the block of the memory allocated is returned as an address that is kept in a pointer.

Answer (Please select your correct option)

- Flush
- Buffer
- Heap correct
- Stack

Made by: Waqar Siddhu

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/VUTES/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 1 of 52 **Marks: 1 (Budgeted Time 1 Min)**

A _____ statement specifies that an action is to be repeated while some condition remains true.

Answer (Please select your correct option)

- repetition
- control
- conditional

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- assignment

Start Time: 4:16 PM
108:00
Time Left

MADE BY WAQAR SIDDHU

Done

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/VUTES/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 2 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The operators ++ and -- are used to increment or decrement the value of a variable by _____

Answer (Please select your correct option)

- 3
- 2
- 1 correct
- 4

Start Time: 4:16 PM

108:00

Time Left

2

MADE BY WAQAR SIDDHU

paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..:::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 3 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Variables which hold memory addresses are called _____

Answer (Please select your correct option)

- Pointer Variables

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Local variables
- Local objects
- Function Variables

Start Time: 4:16 PM
108:00
Time Left
3
MADE BY WAQAR SIDDHU
paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/VUTES/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination | VU Examination System (...

Page Safety Tools

Question No : 4 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The condition in loop should be a(n) _____.

Answer (Please select your correct option)

- Arithmatic Expression — correct
- Constant Expression
- Boolean Expression
- Primary Expression

Start Time: 4:16 PM
108:00
Time Left

4

MADE BY WAQAR SIDDHU

paper.aspx

Question No : 5 of 52 Marks: 1 (Budgeted Time 1 Min)

When **break** statement is encountered in a loop body it _____.

Answer (Please select your correct option)

- transfers the control outside from current loop

correct

- transfers the control outside from current program
- enforces the next iteration of loop
- generates compile time error

Made by: Waqar Siddhu

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer

http://localhost/VUTES/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 6 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Which of the following is not an example of int data type?

Answer (Please select your correct option)

- 0
- -32
- 65531
- -4.0

correct

Start Time: 4:16 PM

108:00

Time Left

6

MADE BY WAQAR SIDDHU

paper.aspx

Local intranet 100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer

http://localhost/VUTES/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 7 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The dynamic memory allocation uses memory from the _____.

Answer (Please select your correct option)

- Stack
- Heap

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- System Cache
- Secondary Storage

Start Time: 4:16 PM
108:00
Time Left

7

MADE BY WAQAR SIDDHU

paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/VUTES/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 8 of 52 **Marks: 1 (Budgeted Time 1 Min)**

_____ executes all the lines before error and stops at the line which contains the error.

Answer (Please select your correct option)

- Intrepreter

correct

- Compiler
- Linker
- Debugger

Start Time: 4:16 PM
108:00
Time Left

8

MADE BY WAQAR SIDDHU

paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/VUTES/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 9 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The return type of a function that does not return any value must be _____.

Answer (Please select your correct option)

- float
- int
- void

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- double

Start Time: 4:16 PM
108:00
Time Left

9

MADE BY WAQAR SIDDHU

paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ....:: - Windows Internet Explorer

http://localhost/VUTES/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 10 of 52 **Marks: 1 (Budgeted Time 1 Min)**

In C/C++, when two programs a and b are trying to open a file xyz.txt at same time then _____.

Answer (Please select your correct option)

- Both programs will generate error
- Only one of them will succeed in opening that file and other will fail
- Both programs will open the file
- One of the program will re-start

correct

Start Time: 4:16 PM
108:00
Time Left

10

MADE BY WAQAR SIDDHU

paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..:::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 11 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Which of the following is the correct C++ syntax to allocate space dynamically for an array of 10 int?

Answer (Please select your correct option)

- new int(10) ;
- new int[10] ;
- int new(10) ;
- int new[10];

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:16 PM
108:00
Time Left
11
MADE BY WAQAR SIDDHU
paper.aspx
Local intranet
100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/VUTES/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 12 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The **ws** manipulator can be used with _____ stream(s).

Answer (Please select your correct option)

- Output
- Input
- Input/Output
- Buffered

correct

Start Time: 4:16 PM
108:00
Time Left

12

MADE BY WAQAR SIDDHU

paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 13 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Which of the following is not a value of base field in set flag function ?

Answer (Please select your correct option)

- oct
- bin

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- dec
- hex

Start Time: 4:16 PM
108:00
Time Left
13
MADE BY WAQAR SIDDHU
paper.aspx
Local intranet
100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..:::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 14 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The return type of the operator function for << operator is _____.

Answer (Please select your correct option)

- class for which we overload operator
- reference of ostream class (ostream&)
- reference of istream class (istream&)
- void

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:16 PM
108:00
Time Left
14
MADE BY WAQAR SIDDHU
paper.aspx

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...:::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
Live Search
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination
VU Examination System (...
Page Safety Tools

Question No : 15 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The parameter passed to the user-defined manipulator during its definition is an object of _____.

Answer (Please select your correct option)

- ofstream
- instream
- ostream
- ifstream

Start Time: 4:16 PM
108:00
Time Left
15
MADE BY WAQAR SIDDHU
paper.aspx
Local intranet
100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
Live Search
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination
VU Examination System (...
Page Safety Tools

Question No : 16 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The operator function overloaded for an assignment operator (=) must be _____.

Answer (Please select your correct option)

- Friend function of class
- Non-member function of Friend function
- Non-member function of class
- Member function of class

Start Time: 4:16 PM
108:00
Time Left
16
MADE BY WAQAR SIDDHU
paper.aspx
Local intranet
100%

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/VUTES/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 17 of 52 **Marks: 1 (Budgeted Time 1 Min)**

With template function, the compiler automatically detects the _____ and generates _____ using passed data.

Answer (Please select your correct option)

- passed data , a new copy of function — correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- parameters, an old copy of function
- old copy of function, parameters
- parameters, an new copy of function

Start Time: 4:16 PM
108:00
Time Left
17
MADE BY WAQAR SIDDHU
paper.aspx
Local intranet
100%

The image part with relationship ID rId2 was not found in the file.

Question No : 19 of 52 Marks: 1 (Budgeted Time 1 Min)

The appropriate data type to store the number of rows and colums of the matrix is_____.

Answer (Please select your correct option)

- float
- strings
- int correct
- char

Made by: Waqar Siddhu

Question No : 20 of 52 Marks: 1 (Budgeted Time 1 Min)

The operator function will be implemented as _____, if both objects (obj1, obj2) are passed as arguments to - operator in the statement given below.

```
obj3 = obj1 - obj2;
```

Answer (Please select your correct option)

- friend function
- member function correct
- non-member function
- either non-member or friend function

Made by: Waqar Siddhu

Question No : 21 of 52 Marks: 1 (Budgeted Time 1 Min)

By using objects as class members, _____ is achieved.

Answer (Please select your correct option)

- Accessibility
- Reliability
- Reusability
- Usability

correct

Made by: Waqar Siddhu

Question No : 22 of 52 Marks: 1 (Budgeted Time 1 Min)

In the member initializer list, the data members are initialized _____.

Answer (Please select your correct option)

- From left to right
- From right to left
- In the order in which they are defined within class

correct

- There is no order for initialization

Made by: Waqar Siddhu

Question No : 23 of 52 Marks: 1 (Budgeted Time 1 Min)

_____ data members of a contained object can be accessed from inside of the containing class.

Answer (Please select your correct option)

- Private

correct

- Public
- Protected
- All

Made by: Waqar Siddhu

Question No : 24 of 52 Marks: 1 (Budgeted Time 1 Min)

The statement cin.get (); is used to _____.

Answer (Please select your correct option)

- Read a string from keyboard
- Read a character from keyboard correct
- Read a string from file
- Read a character from file

Made by: Waqar Siddhu

Question No : 25 of 52 Marks: 1 (Budgeted Time 1 Min)

When an object of a class is defined inside an other class then _____.

Answer (Please select your correct option)

- Constructor of enclosing class will be called first

correct

- Constructor of inner object will be called first
- Constructor and Destructor will be called simultaneously
- Only destructor will be called

Made by: Waqar Siddhu

Question No : 26 of 52 Marks: 1 (Budgeted Time 1 Min)

The order of destruction of an object is _____.

Answer (Please select your correct option)

- same as the construction order.
- reverse as the construction order. correct
- independent of the construction order.
- same as the order of objects declared.

Made by: Waqar Siddhu

Question No : 27 of 52 Marks: 1 (Budgeted Time 1 Min)

When we define an array of objects then _____.

Answer (Please select your correct option)

- Destructor will be called once for the whole array
- Destructor will be called for each object of the array
- No Destructor will be called
- Destructor for only first object in the array will be called

correct

Made by: Waqar Siddhu

Question No : 28 of 52 Marks: 1 (Budgeted Time 1 Min)

At the time of linking, library functions are available in the _____form.

Answer (Please select your correct option)

- compiled
- text
- runable
- code

correct

Made by: Waqar Siddhu

Question No : 29 of 52 Marks: 1 (Budgeted Time 1 Min)

If we define an identifier with the statement #define PI 3.1415926 then during the execution of the program, the value of PI_____.

Answer (Please select your correct option)

- can not be replaced
- can be changed by using function
- remains constant [redacted] correct
- can be changed by some operation

Made by: Waqar Siddhu

Question No : 30 of 52 Marks: 1 (Budgeted Time 1 Min)

The functions used for dynamic memory allocation return pointer of type _____.

Answer (Please select your correct option)

- int
- float
- double
- void

correct

Made by: Waqar Siddhu

Question No : 31 of 52 Marks: 1 (Budgeted Time 1 Min)

Which of the following is a valid class declaration?

Answer (Please select your correct option)

- class B { }
- public class A { }
- object A { int x; };
- class A { int x; };

correct

Made by: Waqar Siddhu

Question No : 32 of 52 Marks: 1 (Budgeted Time 1 Min)

If constructor contains a return statement in its body then compiler will give _____.

Answer (Please select your correct option)

- No error
- Syntax error correct
- Logical error
- Run time error

Made by: Waqar Siddhu

Question No : 33 of 52 Marks: 1 (Budgeted Time 1 Min)

Which one of the given options is correct prototype syntax for overloaded operator?

Answer (Please select your correct option)

- return-type operator-symbol (parameter-list) operator;
- operator return-type operator-symbol (parameter-list);
- return-type operator operator-symbol (parameter-list);
- return-type operator-symbol operator (parameter-list);

Made by: Waqar Siddhu

Question No : 34 of 52 Marks: 1 (Budgeted Time 1 Min)

The following prototype of unary operator function indicates that it is _____.
Date operator++(int)

Answer (Please select your correct option)

- Member functions of post increment operator
- Member functions of pre increment operator

correct

- Non-member functions of post increment operator
- Non-member functions of pre increment operator

Made by: Waqar Siddhu

Question No : 35 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Consider the following code segment.

```
class M {
public:
  M &operator+(const M &);
...
```

Answer (Please select your correct option)

- Member function
- Non-member function
- Friend function
- Virtual function

Made by: Waqar Siddhu

Question No : 36 of 52 Marks: 1 (Budgeted Time 1 Min)

Consider the following code segment

```
class M {
  friend int operator!(const M &);
...
};
```

Answer (Please select your correct option)

- Member function
- Non-member function
- Binary operator function
- Friend Function

Made by: Waqar Siddhu

Question No : 37 of 52 Marks: 1 (Budgeted Time 1 Min)

When we define an array of objects then _____.

Answer (Please select your correct option)

- Constructor will be called once for whole array
- Constructor will be called for each object of the array

correct

- Constructor will never call
- Depends on the size of array

Made by: Waqar Siddhu

Question No : 38 of 52 Marks: 1 (Budgeted Time 1 Min)

While overloading new and delete operators, we should take care that _____.

Answer (Please select your correct option)

- They should be overloaded for specific types instead of overloading globally.
- Both of these operators should not be overloaded in the same program.
- We should never overload either of these operators.
- They should be not overloaded for specific types instead of overloading globally.

Made by: Waqar Siddhu

Question No : 39 of 52 Marks: 1 (Budgeted Time 1 Min)

When the logical operator AND (&&) combines two expressions exp1 and exp2 then the result will be true only _____

Answer (Please select your correct option)

- When both exp1 and exp2 are true
- When both exp1 and exp2 are false
- When exp1 is true and exp2 is false
- When exp1 is false and exp2 is true

Made by: Waqar Siddhu

Question No : 40 of 52 Marks: 1 (Budgeted Time 1 Min)

In top down _____ programming a problem is broken into small pieces or modules and each small piece corresponds to a function.

Answer (Please select your correct option)

- Object Oriented
- Structured
- Assembly
- High level

Made by: Waqar Siddhu

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 1 of 52 Marks: 1 (Budgeted Time 1 Min)

In Flow Chart, flow of control is represented by _____.

Answer (Please select your correct option)

- Rectangle
- Circle
- Diamond
- Arrow

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:45 AM
120:00
Time Left

MADE BY WAQAR SIDDHU

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 2 of 52 Marks: 1 (Budgeted Time 1 Min)

What is the range of Random number generator function rand()?

Answer (Please select your correct option)

- 0 - 32768
- 1 - 32768
- 0 - 32767 correct
- 1 - 32767

Start Time: 4:45 AM
118:00
Time Left

MADE BY WAQAR SIDDHU

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 3 of 52 Marks: 1 (Budgeted Time 1 Min)

Matrix is defined as_____.

Answer (Please select your correct option)

- Single dimensional array
- Multi-dimensional array

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Vector product
- Scalar product

Start Time: 4:45 AM
118:00
Time Left

3

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 4 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The programs in which we allocate static memory run essentially on _____.

Answer (Please select your correct option)

- Heap
- System Cache
- Free Store
- Stack

correct

Start Time: 4:45 AM
118:00
Time Left

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 5 of 52 Marks: 1 (Budgeted Time 1 Min)

If a function has been declared but not defined before its function call then it is termed as_____.

Answer (Please select your correct option)

- logical error
- syntax error

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- run time error
- program time error

Start Time: 4:45 AM
117:00
Time Left

5

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 6 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Whenever we use a library function or a predefined object or macro, we need to use a _____.

Answer (Please select your correct option)

- source file
- object file
- header file
- exe file

correct

Start Time: 4:45 AM
117:00
Time Left
6

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 7 of 52 Marks: 1 (Budgeted Time 1 Min)

The First step for developing a program is _____.

Answer (Please select your correct option)

- linking
- debugging
- analysis

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- loading

Start Time: 4:45 AM
117:00
Time Left

7

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 8 of 52 Marks: 1 (Budgeted Time 1 Min)

In C/C++, the default command line arguments passed to the main function are _____ .

Answer (Please select your correct option)

- float argc, char **argv
- int argc, char **argv [redacted] correct
- int *argc, char *argv
- int argc, float **argv

Start Time: 4:45 AM
117:00
Time Left
8

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 9 of 52 **Marks: 1 (Budgeted Time 1 Min)**

In the statement *int &x = y;* compiler _____.

Answer (Please select your correct option)

- Creates a new variable **x** in memory and assigns it value of variable **y**
- Creates a new variable **x** and assigns it the address of variable **y**
- **x** is just a new name of variable **y** without creating a new variable in memory
- Creates a new variable **y** in memory and assigns it value of variable **x**

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:45 AM
117:00
Time Left
9
MADE BY WAQAR SIDDHU
Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 10 of 52 Marks: 1 (Budgeted Time 1 Min)

The function seekg() takes _____ parameter(s).

Answer (Please select your correct option)

- 0
- 1
- 2 correct
- 3

Start Time: 4:45 AM
117:00
Time Left

10

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 11 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The operator used for casting in C is standard _____ operator.

Answer (Please select your correct option)

- binary
- cast

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- cost
- const

Start Time: 4:45 AM
116:00
Time Left

11

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 12 of 52 **Marks: 1 (Budgeted Time 1 Min)**

In case of pass by reference, _____.

Answer (Please select your correct option)

- The values of the variables are passed to the function so that it can manipulate them
- The location of variable in memory is passed to the function

correct

- The function declaration should contain ampersand (&) in its type declaration
- Temporary variables are created to store the values of the variables passed

Start Time: 4:45 AM
116:00
Time Left
12
MADE BY WAQAR SIDDHU
Start SQL Server Service Man... 11.bmp - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 13 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Both endl and flush are _____.

Answer (Please select your correct option)

- Functions
- Operators
- Manipulators

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Objects

Start Time: 4:45 AM
116:00
Time Left

13

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 14 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The first parameter of overloaded stream insertion operator is _____ where second parameter is _____.

Answer (Please select your correct option)

- input stream, object of class
- object of class, output stream
- output stream, object of class

correct

- object of class, input stream

Start Time: 4:45 AM
116:00
Time Left
14
MADE BY WAQAR SIDDHU
Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 15 of 52 Marks: 1 (Budgeted Time 1 Min)

The first parameter of operator function for << operator,

Answer (Please select your correct option)

- Must be passed by value
- Must be passed by reference

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Can be passed by value or reference
- Must be object of class

Start Time: 4:45 AM
116:00
Time Left

15

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 16 of 52 **Marks: 1 (Budgeted Time 1 Min)**

With template function, the compiler automatically detects the _____ and generates _____ using passed data.

Answer (Please select your correct option)

- passed data , a new copy of function — correct
- parameters, an old copy of function
- old copy of function, parameters
- parameters, an new copy of function

Start Time: 4:45 AM
115:00
Time Left
16

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 17 of 52 Marks: 1 (Budgeted Time 1 Min)

Templates provide way of abstracting _____ information.

Answer (Please select your correct option)

- type

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- data
- method
- access

Start Time: 4:45 AM
115:00
Time Left

17

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 18 of 52 Marks: 1 (Budgeted Time 1 Min)

The appropriate data type to store the number of rows and colums of the matrix is_____.

Answer (Please select your correct option)

- float
- strings
- int

correct

- char

Start Time: 4:45 AM

115:00

Time Left

18

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 19 of 52 Marks: 1 (Budgeted Time 1 Min)

ANSI stands for _____.

Answer (Please select your correct option)

- American Neutral Standards Institute
- Australian National Standards Institute
- Asian National Standards Institute
- American National Standards Institute

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:45 AM
115:00
Time Left

19

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 21 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The initializer list is used to initialize the contained objects of a class at _____.

Answer (Please select your correct option)

- Run time
- Debugging time
- Construction time
- Compile time

Start Time: 4:45 AM

115:00

Time Left

21

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 20 of 52 Marks: 1 (Budgeted Time 1 Min)

In the member initializer list, the data members are initialized _____.

Answer (Please select your correct option)

- From left to right
- From right to left
- In the order in which they are defined within class

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- There is no order for initialization

Start Time: 4:45 AM
115:00
Time Left

20

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) .....:: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 22 of 52 Marks: 1 (Budgeted Time 1 Min)

_____ in the following options is not a method of input stream.

Answer (Please select your correct option)

- getline()
- peek()
- unget()

correct

- write()

Start Time: 4:45 AM
114:00
Time Left

22

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 23 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The stream insertion and stream extraction operators are already overloaded for _____.

Answer (Please select your correct option)

- User-defined data types
- Built-in data types
- User-defined and built-in data types
- Constants

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:45 AM
114:00
Time Left

23

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) .....:: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 24 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Every stream has _____.

Answer (Please select your correct option)

- Source only
- Destination only
- Source and destination

correct

- No source

Start Time: 4:45 AM
114:00
Time Left
24
MADE BY WAQAR SIDDHU
Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 25 of 52 Marks: 1 (Budgeted Time 1 Min)

When an object of a class is defined inside an other class then _____.

Answer (Please select your correct option)

- Constructor of enclosing class will be called first

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Constructor of inner object will be called first
- Constructor and Destructor will be called simultaneously
- Only destructor will be called

Start Time: 4:45 AM
114:00
Time Left

25

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::... Fall 2012 (FinalTerm) ...:: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 26 of 52 Marks: 1 (Budgeted Time 1 Min)

The order of destruction of an object is _____.

Answer (Please select your correct option)

- same as the construction order.
- reverse as the construction order. correct
- independent of the construction order.
- same as the order of objects declared.

Start Time: 4:45 AM
114:00
Time Left

26

MADE BY WAQAR SIDDHU

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination | VU Examination System (...

Page Safety Tools

Question No : 27 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The operator delete takes a void pointer as argument which _____.

Answer (Please select your correct option)

- Points to the block of memory to be deallocated.

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Points to all the objects of the class.
- Means that delete points to nothing.
- is of no use

Start Time: 4:45 AM
113:00
Time Left

27

MADE BY WAQAR SIDDHU

Start | SQL Server Service Man... | untitled - Paint | VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 28 of 52 **Marks: 1 (Budgeted Time 1 Min)**

A special name which is substituted in code by its definition and as a result we get an expanded code, is called_____.

Answer (Please select your correct option)

- include
- directive
- macro
- define

correct

Start Time: 4:45 AM
113:00
Time Left
28
MADE BY WAQAR SIDDHU
Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..:::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination | VU Examination System (...

Page Safety Tools

Question No : 29 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Where we can include a header file in the program?

Answer (Please select your correct option)

- anywhere — correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- in start
- at the end
- at the middle

Start Time: 4:45 AM
113:00
Time Left

29

MADE BY WAQAR SIDDHU

Start | SQL Server Service Man... | untitled - Paint | VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) .....:: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 30 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Which of the following is NOT a common error that can happen with memory allocation?

Answer (Please select your correct option)

- Memory leak
- Unreferenced memory
- Void pointers

correct

- Dangling pointers

Start Time: 4:45 AM
113:00
Time Left

30

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 31 of 52 Marks: 1 (Budgeted Time 1 Min)

The functions used for dynamic memory allocation return pointer of type _____.

Answer (Please select your correct option)

- int
- float
- double
- void

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:45 AM
113:00
Time Left

31

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 32 of 52 **Marks: 1 (Budgeted Time 1 Min)**

If constructor contains a return statement in its body then compiler will give _____.

Show Picture

Answer (Please select your correct option)

- No error
- Syntax error
- Logical error
- Run time error

correct

Start Time: 4:45 AM
112:00
Time Left

32

MADE BY WAQAR SIDDHU

paper.aspx
Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 33 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Users must not know about _____.

Answer (Please select your correct option)

- Methods functionality with in class

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Objects of class
- Functions name within class
- Class implementation of functionality and interfaces

Start Time: 4:45 AM
112:00
Time Left

33

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) .....:: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 34 of 52 **Marks: 1 (Budgeted Time 1 Min)**

new and delete are also used with _____ and primitive data types as well.

Answer (Please select your correct option)

- loops
- structures, pointers
- classes , structures
- constant

correct

Start Time: 4:45 AM
112:00
Time Left
34
MADE BY WAQAR SIDDHU
Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination | VU Examination System (...

Page Safety Tools

Question No : 35 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Friend function of a class is _____.

Answer (Please select your correct option)

- Private function
- Non-member function

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Public function
- Member function

Start Time: 4:45 AM
112:00
Time Left

35

MADE BY WAQAR SIDDHU

Start | SQL Server Service Man... | untitled - Paint | VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination VU Examination System (...

Page Safety Tools

Question No : 36 of 52 **Marks: 1 (Budgeted Time 1 Min)**

The following prototype of unary operator function indicates that it is _____.
Date operator++(int)

Answer (Please select your correct option)

- Member functions of post increment operator
- Member functions of pre increment operator

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Non-member functions of post increment operator
- Non-member functions of pre increment operator

Start Time: 4:45 AM
112:00
Time Left

36

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 37 of 52 Marks: 1 (Budgeted Time 1 Min)

The operator function will be implemented as _____, if obj1 drive the - operator whereas obj2 is passed as arguments to - operator in the statement given below.

```
obj3 = obj1 - obj2;
```

Answer (Please select your correct option)

- Friend function
- Virtual Function
- Member function

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

- Non-member function

Start Time: 4:45 AM
111:00
Time Left

37

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 38 of 52 Marks: 1 (Budgeted Time 1 Min)

With user-defined data type variables (objects), self assignment can produce _____.

Answer (Please select your correct option)

- Syntax error
- Logical error
- Link error
- Run time Error

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:45 AM
111:00
Time Left

38

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::.. Fall 2012 (FinalTerm) ...::: - Windows Internet Explorer
http://localhost/vutes/client/Instructions.aspx
File Edit View Favorites Tools Help
Favorites Suggested Sites Web Slice Gallery
Examination VU Examination System (...
Page Safety Tools

Question No : 39 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Correct syntax for function prototype of overloading delete operator is _____.

Answer (Please select your correct option)

- void* operator delete(void* ptr);
- void operator delete(void* ptr);
- void* delete operator(void ptr);
- void* delete operator(void* ptr);

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

Start Time: 4:45 AM
111:00
Time Left

39

MADE BY WAQAR SIDDHU

Start SQL Server Service Man... untitled - Paint VU Examination Syste...

VU Examination System (CLIENT) VUTES 6.5 ::::: Fall 2012 (FinalTerm) ..... - Windows Internet Explorer

http://localhost/vutes/client/Instructions.aspx

File Edit View Favorites Tools Help

Favorites Suggested Sites Web Slice Gallery

Examination | VU Examination System (...

Page Safety Tools

Question No : 40 of 52 **Marks: 1 (Budgeted Time 1 Min)**

Base address is the memory address of _____ element of an array.

Answer (Please select your correct option)

1st

correct

Correct answer solved by hadi
email : usmanraj20@gmail.com
Cell : 03228043306

2nd

3rd

4th

Start Time: 4:45 AM

111:00

Time Left

40

MADE BY WAQAR SIDDHU

Start | SQL Server Service Man... | 39.bmp - Paint | VU Examination Syste...

MORE PAST PAPERS BY WAQAR SIDDHU

Provide Solved in PDF Get From

VU Answer

Get All Solutions.