CS201 QUIZ-1 BY Attiq Kundi

&

CS201 Final Term all MCQS

SUBSCRIBE "Knowledge For Us" ON YOU TUBE

CS504 100 % CORRECT MCSQ

AND Many MoRe

Humari Mehnat k liye Ager ho sakay to Humaray channel ko Zaroor Subcribe Karen..*JazakAllah*

"Knowledge For Us"

Question # 1

< and > both are _____ operators.

Arithmetic
Relational
Logical
Mathematical
Question # 2

Find out the logical error in following lines of code. If (x = 10) cout "x is 10";

10 should be enclosed in quotations
There is no semicolon at the end of if condition
Assignment operator should not be used for Comparison
Variable x should not be inside parenthesis

Question # 3

What will be the result of the expression j = i++; if initially j = 0 and i = 5?

0
5

6
4

Question # 4

Default mechanism of calling a function by passing it array is call by _____ and in case of passing variable is call by ___.

Reference, Reference
Reference, value
Value, Reference
Value, Value

Question # 5

When the break statement is encountered in a loop's body, it transfers the control _____from the current loop.

Inside
Outside
To break statement
To continue statement
Question # 6

_____statement is used to terminate the processing of a particular case and exit from switch structure.

If
Goto
Break
Continue

Question # 7

If we pass more than one arguments to a function then they are separated by____.

Comma, Lecture 9
Semicolon;

Colon:

Brackets ()

OUR WHATSAPP GROUP JOIN

Question # 8

What will be the value of the variable output in the given piece of code?
double output = 0; output = (2 + 2) * 4 + 2 / (4 – 2);

15
17
12
1

Question # 9

If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout statement?

2
2.1
2.06
2.07

Question # 10

_____ will be used for clarity and to force the order of evaluation in an expression.
" "
() PG32
' '
[ ]

Question # 11

What will be the size of following array? int arr[29];

0

30 PAGE 105-106

29

28

f a function has not been declared before

its definition, It is logical error

syntax error LECTURE NO 9
logical Error
run time error
none of these

Question # 13

When the break statement is encountered in a loop‟s body, it transfers the control from the current loop.

Inside

Outside By using break the loop will terminate.

To break statement

To continue statement

Question # 14

When we access a multidimensional array, each array index is surrounded by_.

Single quotes ' '

Double quotes " "

Brackets[] Lecture 11

None of the given

Question # 15

char name [] = “Hello World” ; In the above statement, a memory of_____characters will be allocated

12 Lecture 12

10

11

13

Question # 16

A variable declared within a code block becomes variable for that block.

Static

Integer
Local Lecture 9
Global

Question # 17

When the, if statement consists of more than one statement then enclosing these statement in braces, is _____.

Compulsory
Optional
Not required
Relevant

Question # 18

Characters of a string stored in an array can be accessed directly using array.

Manipulation

Superscript

Subscript Page No 123

Postscript

Question # 19

A variable declared within a code block becomes variable for that block.

Static

Integer

Local Lecture 9

Global

Question # 20

The data type before a function name represents its,

Return Type

Function data

Function arguments

Function name

Question # 21

From following; which one is the correct syntax of an array initialize: Array size is 10 and it is of double data type to value 0?

arr[10] = {0.0};

double arr[10]= 0.0;

Double arr[10] = {0.0}; Lecture 12

double arr[] = 0.0;

Question # 22

In C/C++, by default arguments are passed by__to a function.

Value Lecture 9

Reference

Prototype

None of the given

Question # 23

By default, the starting index of an array in C++ is

0 Lecture 11

2

1

-1

Default constructor takes _____.

one parameter

two parameters

no parameters

character type parameter

All the preprocessors directives start with _____.

$

&

#

_

The members of a class declared with the keyword struct are _____by default.

static

private

protected

public

Loops are _____ Structure

Decision

Sequential

Repetition

None of the given options

We cannot use _____ pointer for storing and reading data from it.

NULL

integer

double

zero

When an object of a class is defined inside another class then,

Destructor of enclosing class will be called first

Destructor of inner object will be called first

Constructor and Destructor will be called simultaneously

None of the given options

Consider the following code segment. Which of the following will be called while executing code at line 2? String s1 , s2; s1 = s2 ;

Copy constructor

Default constructor

Assignment operator

Parameterized constructor

We cannot increment _____.

pointers

arrays

references

variables

In statement Matrix m2 = m1 ;

Assignment operator is being used

Copy constructor is being used.

Statement has syntax error

None of the given options

From the following; which on is the correct syntax of an array declaration: array size is 5 and it is of float data type?

float [5] name;

name[5] float;

float name[5];

None of the given options

If an array has 50 elements, what is allowable range of subscripts?

0–49

1–49

0–50

1–50

A structure is a collection of _____under a single name.

values

variables

data

None of the given

If a function has not been declared before its definition, It is a

logical error

syntax error

run time error

None of these

When the if statement consists more than one statement then enclosing these statement in curly braces is,

Not required

Good programming

Relevant

Must

_____ allow us to have a memory location and use it as int or char interchangeably

structures

union

construct

None of the given

In Analysis, we try to have a_____

Determined the inputs

Break up of problem

Precise problem statement

None of the given

_____function give the position of the next character to be read from that

file.

tellp()

tellg()

seekg()

seekp()

Pointers store the _____

value of a variable

memory address

characters

None of the given

In order to get the right most digit of a number, we divide this number by 10 and take its

Remainder

Quotient

Divisor

None of the given options

_____ Returns true if c is a digit and false otherwise.

int isalpha(int c)

int isalnum(int c)

int isxdigit(int c)

int isdigit(int c)

If int a = 50; then the value of a/= 3; will be,

15

18

16

17

_____ contains functions for manipulations of character data.

ctype.h

iostream.h

string.h

None of the given

_____ Returns true if c is a digit or a letter and false otherwise.

int isalpha(int c)

int isalnum(int c)

int isxdigit(int c)

int isdigit(int c)

If int sum = 54; Then the value of the following statement is sum = sum - 3 ;

52

50

51

57

To get the value stored at a memory address, we use the_____

referencing operator

dereferencing operator

simple operator

None of the given

In C/C++; by default arguments are passed by _____ to a function.

Reference

Value

Type

Data

The string in the array is terminated by a _____

zero

nil

null

one

Structures are syntactically defined with the word_____.

struc

struct

structure

None of the given

C is widely known as development language of _____ operating system.

Linux

Unix

Windows

Mac OS

http://vustudents.ning.com

At the_____, we try to break up the problem into functional units

analysis phase

design phase

Implementation phase

None of the given

While developing a program; should we think about the user interface?

Yes

No

What will be the result of arithmetic expression 5+25/5*5?

45

6

30

9

Why we use "cin"?

To send data to printer

To read data from keyboard

To display message

To display output on the screen

_____operator uses the sign ^.

Bit-wise OR

Exclusive OR

AND Operator

NOT operator

C++ is a_____ language.

High level

Low level

Machine

Fourth Generation

12 & 8 = (1000) 2 =_____. & is used to AND two numbers bit-wise

4

8

6

12

From the following; which one is used as an assignment operator?

Equal sign ‘=’

Double equal sign ‘==’

Both equal and double equal sign

None of the given options

What will be the value of ‘a’ and ‘b’ after executing the following statements? int a = 9; int b = a++; cout<<

10,9

9,10

9,9

10,10

These functions seekg() and seekp() requires an argument of type _____to let

them how many bytes to move forward or backward.

int

short

long

double

A character is stored in the memory in _____

byte

integer

string

None of the given

dereferencing operator is represented by _____

*

+

–

None of the given

_____ transfers the executable code from main memory to hard disk.

Loader

Debugger

Compiler

Linker

When the logical operator OR (||) combine two expressions exp1 and exp2 then the result will be false only,

When both exp1 and exp2 are true

When both exp1 and exp2 are false

When exp1 is true and exp2 is false

When exp1 is false and exp2 is true

suppose we have int y[10]; To access the 4th element of the array we write_____

y[4];

y[3];

y[2];

none of given

we have opened a file stream myfile for reading (getting), myfile.tellg () gives us the current get position of the file pointer. It returns a whole number of type_____

long

int

short

double

ofstream is used for_____

Input file stream

Output file stream

Input and output file stream

All of the given

A structure is a collection of _____under a single name.

values

variables

data

None of the given

The first character of a variable name must be an alphabet or

► **Underscore**

- Digit
- Special character
- Comma

Suppose **int multi[5][10];** when we are using **multi , it means,

- Single dereferencing
- Single referencing
- Double referencing
- Double dereferencing

eof( ), bad( ), good( ), clear( ) all are manipulators.

- **True**
- False

It is possible to return an object from a function through **this** pointer.

► **True**

► False

Function implementation of friend function must be defined outside the class.

► **True**

► False

The default scope for members of structures is **public** whereas the default visibility for class members is **private**.

► **True**

► False

The operator function of << and >> operators are always the member function of a class.

► True

► **False**

How many bytes are occupied by declaring following array of characters?

char str[] = “programming”;

- ► 10
- ► 11
- ► **12**
- ► 13

What does STL stand for?

- ► Source template library
- ► **Standard template library**
- ► Stream template library
- ► Standard temporary library

Which of the following array is the most suitable for storing a matrix structure

- ► Single-dimensional array

► **Two-dimensional array**

► Three-dimensional array

► Four-dimensional array

What will be the output of following code segment?

```
main(){

int x = 5 ;

{

  int x = 4 ;


  cout << x << “,” ;

 }

cout << x ;

}
```

► 5, 5

► 4, 4

► **4, 5**

► 5, 4

Single line comments explaining code would be preceded like in the following example.

- /*
- //
- /
- //*

The _____ statement interrupts the flow of control.

- switch
- continue
- goto
- **break**

Which of the following will be the correct function call for function prototype given below?

int func (int &);

- func(int num);

- func(&num);
- func(num);
- func(*num);

If there is a symbol (& sign) used with the variable name followed by data type then it refers to _____ and if & is being used with variable name then it refers to _____.

- Address of variable, reference variable
- Reference variable, value of variable
- Reference variable, address of variable
- Address of variable, value of variable

Which of the following operator the compiler overloads for objects by default?

- + operator
- - operator
- = operator
- **== operator**

If overloaded plus operator is implemented as member function then which of the following option will be true for the statement given below?

obj3 = obj1 + obj2 ;

► obj1 will be passed as an argument to + operator whereas obj2 will drive the + operator

► obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator

► Both objects (obj1, obj2) will be passed as arguments to the + operator

► Any of the objects (obj1, obj2) can drive the + operator

The operator function will be implemented as _____, if both objects (obj1, obj2) are passed as arguments to - operator in the statement given below.

obj3 = obj1 - obj2;

► friend function

► member function

► non-member function

► either non-member or friend function

The input/output streams cin and cout are _____ therefore have _____.

- ► Structures, function
- ► Objects, member functions
- ► Functions, objects
- ► None of the given options

What will be the output of following statement?

cout << setfill('0') << setw(7) << 128

- ► 0000128
- ► 0128128
- ► 1280000
- ► 0012800

The static data members of a class will be _____

- shared by objects
- created for each object
- **initialized within class**
- initialized within main function

Which of the following is used for allocating space for static variables?

- Heap
- **Static storage area**
- Free store
- Stack

Templates provide way of abstracting _____ information.

- **type**
- data
- method
- access

A pointer is a special type of variable that contain _____

- **Memory Address**
- Data values
- Both Values and Memory
- None of given of options

Which is NOT a protection level provided by classes in C++?

- protected
- hidden
- private
- **public**

Users must not know about _____.

- ► Functions Name within Class
- ► Class implementation of Functionality and Interfaces
- ► Methods Functionality with in Class
- ► None of the given options

Assignment operator is used to initialize a newly declared object from existing object

- ► **True**
- ► False

The operator function for << (stream insertion) >> and stream extraction must be

- ► Member function of class
- ► Non-member function of class
- ► Both member and non-member function
- ► None of the given options

http://vustudents.ning.com

A template function must have

- ► **One or more than one arguments**
- ► Only one argument
- ► Zero arguments
- ► None of the given options

Truth tables are used for analyzing _____.

- ► **logical expressions**
- ► arithmetic expressions
- ► both logical and arithmetic expressions
- ► none of the given options.

Which of the following array is the most suitable for storing a matrix structure?

- ► Single-dimensional array
- ► **Two-dimensional array**
- ► Three-dimensional array

► Four-dimensional array

How many bytes are occupied by declaring following array of characters?

char str[] = “programming”;

► 10

► 11

► 12

► 13

11 bytes for 11characters of word programming and 1 for '**\n**'

When we do dynamic memory allocation in the constructor of a class, then it is necessary to provide a destructor.

► **True**

► False

The prototype of friend functions must be written ____ the class and its definition must be written ____

► inside, inside the class

► inside, outside the class

► **outside, inside the class**

► outside, outside the class

Copy constructor becomes necessary while dealing with _____allocation in the class.

► **Dynamic memory**

► Static memory
► Both Dynamic and Static memory

► None of the given options

Dealing with structures and functions passing by reference is the most economical method

► **True**

► False

1st...what is the function of flush commond?

1): when we specify the buffer size, normally the operating system or compiler does this for us. A typical size of buffer is 512 bytes. When the information is of 512 byte size, output will take place. But in the program, we may want at some point that whatever is in the buffer, show them. For that purpose the normal mechanism is flush. Flush the stream. The flush command forces the data from the buffer to go to its destination which is

normally a screen or file and make the buffer empty. **Lec 34**

2nd...what are the types of tamplates?

a template is a sketch to draw some shape or figure.

There are two different types of templates in C++ language i.e.' function templates and class templates. **Lec 41**

The declarator of Plus (+) member operator function is

- ► Class-Name operator + (Class-Name rhs)
- ► operator Class-Name + ( )
- ► operator Class-Name + (rhs)
- ► Class-Name operator + ( )

12 & 8 = (1000) 2 =_____. & is used to AND two numbers bit-wise

Select correct option:

4

8

6

12

Is ka answer 8 hy, see handouts page number 246.

Truth table for &

Bit1	Bit2	Bit1 & Bit2
1	1	1
1	0	0
0	1	0
0	0	0

Therefore, when we apply the conditions, we get

12 = 1 1 1 0 (binary conversion of 12)

8 = 1 0 0 0 (binary conversion of 8)
---

1 0 0 0, which is equals to 8

The reserved words public and private comes under the category

Which of the following operators can not be overloaded?

1) :new
2) :delete
3) :+=
4) :sizeof

The reserved words public and private comes under the category

1) :structures

2) :strings
3) :accessibility modifiers
4) :types of functions

Question No: 10 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

- ► Only block of memory is allocated for objects
- ► Only constructor is called for objects
- ► **Memory is allocated first before calling constructor**
- ► Constructor is called first before allocating memory

Question No: 11 (Marks: 1) - Please choose one

What is the sequence of event(s) when deallocating memory using delete operator?

- ► Only block of memory is deallocated for objects
- ► Only destructor is called for objects
- ► Memory is deallocated first before calling destructor
- ► **Destructor is called first before deallocating memory**

Question No: 12 (Marks: 1) - Please choose one

new and **delete** operators cannot be overloaded as member functions.

- ► True
- ► **False**

Question No: 13 (Marks: 1) - Please choose one

The operator function of << and >> operators are always the member function of a class.

- ► True

► **False**

Question No: 14 (Marks: 1) - Please choose one

A template function must have at least ---------- generic data type

► Zero

► One
► Two
► Three

Question No: 15 (Marks: 1) - Please choose one

If we do not mention any *return_value_type* with a function, it will return an _____ value.

► **int**

► void
► double
► float

Question No: 16 (Marks: 1) - Please choose one

Suppose a program contains an array declared as **int arr[100];** what will be the size of array?

► 0

► 99

► **100**

► 101

Question No: 17 (Marks: 1) - Please choose one

The name of an array represents address of first location of array element.

► **True**

► False

Question No: 18 (Marks: 1) - Please choose one

Reusing the variables in program helps to save the memory

► **True**

► False

Question No: 19 (Marks: 1) - Please choose one

Which of the following option is true about new operator to dynamically allocate memory to an object?

► The new operator determines the size of an object

► **Allocates memory to object and returns pointer of valid type**

► Creates an object and calls the constructor to initialize the object

► All of the given options

Question No: 20 (Marks: 1) - Please choose one

new and delete are _____ whereas malloc and free are _____.

► Functions, operators

► Classes, operators

► **Operators, functions**

► Operators, classes

Question No: 21 (Marks: 1) - Please choose one

Like member functions, _____ can also access the private data members of a class.

- Non-member functions
- **Friend functions**
- Any function outside class
- None of the given options

Question No: 22 (Marks: 1) - Please choose one

Which of the following statement is best regarding declaration of friend function?

- Friend function must be declared after public keyword.
- Friend function must be declared after private keyword.
- **Friend function must be declared at the top within class definition.**
- It can be declared anywhere in class as these are not affected by the public and private keywords.

Question No: 23 (Marks: 1) - Please choose one

The operator function overloaded for an Assignment operator (=) must be

- Non-member function of class
- **Member function of class**
- Friend function of class
- None of the given options

Question No: 24 (Marks: 1) - Please choose one

For non-member operator function, object on left side of the operator may be

- Object of operator class
- Object of different class

► **Built-in data type**

► All of the given options

Question No: 25 (Marks: 1) - Please choose one

The operator function will be implemented as _____, if obj1 drive the - operator whereas obj2 is passed as arguments to - operator in the statement given below.

obj3 = obj1 - obj2;

► Member function

► Non-member function

► **Friend function**

► None of the given options

Question No: 26 (Marks: 1) - Please choose one

Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

► Class-name operator +() ;

► Class-name operator +(int) ;

► **Class-name operator ++() ;**

► Class-name operator ++(int) ;

Question No: 27 (Marks: 1) - Please choose one

The static data members of a class are initialized _____

► **at file scope**

► within class definition

► within member function
► within main function

Question No: 28 (Marks: 1) - Please choose one

Class is a user defined_____.

► **data type**

► memory referee
► value
► none of the given options.

http://vustudents.ning.com

Question No: 29 (Marks: 1) - Please choose one
We can also define a user-defines manipulators.

► True

► **False**

Question No: 30 (Marks: 1) - Please choose one

Automatic variable are created on _____.

► Heap

► Free store

► **static storage**

► stack

Question No: 3 (Marks: 1) - Please choose one

A pointer variable can be,

- ► Decremented only
- ► Incremented only
- ► Multiplied only
- ► **Both 1 and 2**

Question No: 4 (Marks: 1) - Please choose one

setprecision is a parameter less manipulator.

- ► True
- ► **False**

Question No: 5 (Marks: 1) - Please choose one

We can change a Unary operator to Binary operator through operator overloading.

- ► **False**
- ► True

What is the functionality of the following statement?

String str[5] = {String(“Programming”), String(“CS201”)};

► Default constructor will call for all objects of array

► **Parameterized constructor will call for all objects of array**

► Parameterized constructor will call for first 2 objects and default constructor for remaining objects

► Default constructor will call for first 3 objects and Parameterized constructor for remaining objects

There is an array of characters having name ‘course’ that has to be initialized by string ‘programming’ which of the following is the correct way to do this,

i. course[] = {‘p’, ’r’, ’o’, ’g’, ’r’, ’a’, ’m’, ’m’, ’i’, ’n’, ’g’};
ii.course[] = ‘programming’ ;
iii. course[12] = “programming” ;
iv. **course = “programming” ;**

Choose the correct options.

► (i) and (ii) only

► (i) and (iv) only

► **(i) and (iii) only**

► (ii) and (iii) only

Overloaded member operator function is always called by _____

► **Class**

► Object

► Compiler

► Primitive data type

Consider the following code segment

```
class M {
  friend int operator!(const M &);
...
};

!s                    // code of line implies that   operator!(s)
...
```

Let assume if s is an object of the class then function is implemented as _____

► Member function

► Non-member function

► Binary operator function

► None of the given options

None of the given options

Copy constructor becomes necessary while dealing with _____allocation in the class.

► **Dynamic memory**

► Static memory

► Both Dynamic and Static memory

► None of the given options

1) C/C++ string constant is enclosed in http://vustudents.ning.com

Small braces

Curly braces

Double quote

Single quote

2) Unary operator takes argument

Zero

One

Two

Three

3) When define array of objects Constructor will call
Destructor will call

The size of int data type is

► 1 bytes
► 2 bytes
► 3 bytes
► **4 bytes**

In Flow chart process is represented by

► **Rectangle**
► Arrow symbol
► Oval

► Circle

If the break statement is missed in switch statement then,

► The compiler will give error
► This may cause a logical error
► No effect on program
► Program stops its execution

When we are using const keyword with a variable x then initializing it at the time of declaration is,

► **Must**
► Optional
► Not necessary

► A syntax error

Which of the following is the correct way to assign an integer value 5 to element of a matrix say ‘m’ at second row and third column?

► **m[2][3] = 5 ;**
► m[3][2] = 5 ;
► m[1][2] = 5 ;
► m[2][3] = ‘5’;

How many total elements must be in two-dimensional array of 3 rows and 2 columns?

► 4
► 5
► **6**
► 7

Which of the following is the correct statement for the following declaration?

const int *ptr.

► ptr is a constant pointer

ptr is constant integer pointer ►

► ptr is a constant pointer to
int ptr is a pointer to const int ►

Consider the following code segment. What will be the output of this code segment?

int arr[6] = {2, 3, 7, 4, 5, 6} ;

int *ptr1 =&arr[1] ;

int *ptr2 = &arr[4] ;

cout << (ptr2-ptr1) ;

► 3
► 9
► 12
► **2**

What will be the correct syntax to assign an array named arr of 5 elements to a pointer ptr?

► *ptr = arr ;
ptr = arr ; ►

► ***ptr = arr[5]** ;
ptr = arr[5] ; ►

The variables having a name, type and size are just like empty boxes.

►False

True ►

What's wrong with this for loop?

for (int k = 2, k <=12, k++)

► the increment should always be ++k
► the variable must always be the letter i when using a for loop
► there should be a semicolon at the end of the statement
► the commas should be semicolons

Most efficient method of dealing with structure variables is to define the structure globally

► True
False ►

Syntax of union is identical to _____

► **Structure**
► Class
► Function
► None of the given options

Like member functions, _____ can also access the private data members of a class.

Non-member functions

► Friend functions

Any function outside class

None of the given options

Function created with in function called?

nested

overloaded

grouped

none of them

CS201- Introduction to Programming

Latest Solved Mcqs from Final term Papers

Latest Mcqs

FINALTERM EXAMINATION 2011

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one

All A template function must have at least ---------- generic data type

► Zero
► One (Page 499)
► Two
► Three

Question No: 2 (Marks: 1) – Please choose one

Which of the following statement is best regarding declaration of friend function?

► Friend function must be declared after public keyword
. ► Friend function must be declared after private keyword.

► Friend function must be declared at the top within class definition.

► It can be declared anywhere in class as these are not affected by the public and private keywords. (Page

346)

Question No: 3 (Marks: 1) - Please choose one

Which one of the following is the declaration of overloaded pre-increment operator implemented as

member function?

► Class-name operator +() ;
► Class-name operator +(int) ;
► **Class-name operator ++() ; (Page 389)**
► Class-name operator ++(int) ;

Question No: 4 (Marks: 1) - Please choose one

Class is a user defined_____.

► **data type (Page 317)**
► memory referee
► value
► none of the given options.

Question No: 5 (Marks: 1) - Please choose one

How many bytes will the pointer intPtr of type int move in the following statement? intPtr += 3 ;
2

► 3 bytes
► 6 bytes
► **12 bytes**

► 24 bytes

Question No: 6 (Marks: 1) - Please choose one

Which of the following is the correct C++ syntax to allocate space dynamically for an array of 10 int?

► new int(10) ;
► **new int[10] ;**
► int new(10) ;
► int new[10];

► Data values
► **Memory Address (Page 267)**
► Both data and values
► None of the given option

Question No: 8 (Marks: 1) - Please choose one

Reference Value Type Data The code is written to _____ the program.

► **implement**
► design
► analysis
► none of the given options

FINALTERM EXAMINATION CS201
- Introduction to programming Final
Term Spring 2010

Operator overloading can be performed through_____.

► Classes
► **Function (Page 371)**
► Operators
► Reference

► **Direct Reference (page 143)**

►Indirect Reference.
3

► Partial Reference
► Proper Reference
When a value is referred by a normal variable is known as direct reference

Question No: 3 (Marks: 1) - Please choose one

Which of the following function is used to increase the size of already allocated memory chunk?

► malloc
► calloc
► realloc (Page 285)

► free

► #error
► #define
► #line
► #ndefine (Page 272)

► iostream.h (Page 15)
► fstream.h
► istream.h
► ostream.h
Question No: 6 (Marks: 1) – Please choose one

Overloaded delete operator function takes the same parameter as an argument returned by new

operator

function.

► True (Page 414)
► False

The same pointer that is returned by the new operator, is passed as an argument to the delete operator.

These rules apply to both, if operators (new and delete) are overloaded as member or non-

member operators

(as global operators).

Question No: 7 (Marks: 1) – Please choose one

When an array of object is created dynamically then there is no way to provide parameterized constructors

for array of objects.

► **True (Page 414)**
► False

Question No: 8 (Marks: 1) – Please choose one
4

C is widely known as development language of _____ operating system.

► Linux
► Windows
► **Unix (Page 12)**
► Mac OS

In the start C became widely known as the development language of the UNIX operating system, and the

UNIX operating system was written by using this C language. The C language is so powerful that the

compiler of C and other various operating systems are written in C.

Question No: 9 (Marks: 1) - Please choose one
Computer can understand only machine language code.

► **True**
► False

► True
► **False (Page 151)**

Class templates can have friends. A class or class template, function, or function template can be a friend to

a template class. Friends can also be specializations of a class template or function template, but

not partial

specializations.

Question No: 11 (Marks: 1) – Please choose one

What will be the value of 'a' and 'b' after executing the following statements?

A=3;

b = a++;

► 3, 4
► 4, 4
► 3, 3
► **4, 3**

Question No: 12 (Marks: 1) – Please choose one

Consider the following code segment. What will be the output of following code?

```
Int addValue (int *a){
int b = (*a) + 2;
return b ;
}
main () {
int x =6 ;
cout << x << "," ;
cout << addValue(&x) << "," ;
cout << x ;

}
```

5

► **6,8,6**

► 6,6,8
► 6,8,8
► 6,6,6

Question No: 13 (Marks: 1) – Please choose one

_____ is used to trace the logic of the program and correct the logical errors.

► Compiler
► Editor
► Linker
► **Debugger (Page 13)**

new and delete are _____ whereas malloc and free are _____.

► Functions, operators
► Classes, operators
► **Operators, functions (Page 342-285)**
► Operators, classes

Hence, we can call new and delete operators, P# 342

we have allocated a memory space for our use by malloc function. P# 285

Question No: 15 (Marks: 1) - Please choose one

Like member functions, _____ can also access the private data members of a class.

► Non-member functions
► **Friend functions (Page 346)**
► Any function outside class
► None of the given options

Question No: 16 (Marks: 1) – Please choose one

Which situation would require the use of a non-member overloaded operator?

► The overloaded operator is an Assignment operator.
► **The left most operand is an object of a class.(Page 375)**
► The left operand is built-in data type.
► The operator returns a reference.

When an operator function is implemented as a non-member function, the left-most operand may be an

object of the operator's class, an object of a different class, or a built-in type

Question No: 17 (Marks: 1) - Please choose one

The stream insertion and stream extraction operators are already overloaded for _____.

► User-defined data types
► **Built-in data types http://www.sstutor.com/cpp/stream1.htm**
► User-defined and built-in data types
► None of the given options

6

Question No: 18 (Marks: 1) - Please choose one

If we define an identifier with the statement **#define PI 3.1415926** then during the execution of the program

the value of PI _____.

► can not be replaced
► None of the given options
► **Remain constant. (Page 271)**

► can be changed by some operation

Question No: 19 (Marks: 1) - Please choose one

Assignment operator is ----------associative.

► **right**
► left
► binary
► unary

Question No: 20 (Marks: 1) - Please choose one

When ever dynamic memory allocation is made in C/C++, it is freed_____.

► **Explicitly (Page 527)**
► Implicitly
► Both explicitly and implicitly
► None of the given options

Question No: 21 (Marks: 1) – Please choose one

The appropriate data type to store the number of rows and colums of the matrix is_____.

► float

► **int (Not sure)**
► char
► none of the given options.

Question No: 22 (Marks: 1) – Please choose one

Which of the following function do NOT initialize the chunk of memory to all zero?

► calloc() function
► Both malloc() and calloc()
► None of the above
► **malloc() function** (Page 283)

The **malloc** function differs from **calloc** in the way that the space allocated by **malloc** is not initialized and

contains any values initially.

Question No: 23 (Marks: 1) – Please choose one

The function free() returns back the allocated memory got thorough calloc and
7

malloc to _____ .

► stack
► **heap**
► stack and heap
► None of the given options

Question No: 24 (Marks: 1) – Please choose one
width() is member function of _____

► cin object
► cout object
► **Both cin and cout object (Page 440)**

► None of the given option

► true
► **false (Page 518)**

Templates are type-safe. This is because the types that templates act upon are known at compile time, so the

compiler can perform type checking before errors occur.

Question No: 26 (Marks: 1) - Please choose one

A Matrix can be composed of ints, floats or doubles as their elements. Best way is to handle this ,

_____

► Write a separate class to handle each
► **Use templates (Page 527)**
► Use strings to store all types
► None of the given options

FINALTERM EXAMINATION
Spring 2010

CS201- Introduction to Programming Question No: 1 (Marks: 1) - Please choose one

In if structure the block of statements is executed only,

► When the condition is false
► When it contain arithmetic operators
► When it contain logical operators
► **When the condition is true (Page 38)**

Question No: 2 (Marks: 1) - Please choose one

Header file: **fstream.h** includes the definition of the stream classes _____.

8

► ifstream, fstream, cout
► **ifstream, fstream, ofstream (Page 199)**
► fstream, cin, cout
► None of the above

► **dot operator (.) (Page 231)**
► * operator
► U operator

► None of given.

Question No: 4 (Marks: 1) - Please choose one
eof( ), bad( ), good( ), clear( ) all are manipulators.

► **True (Page 433)**
► False

Question No: 5 (Marks: 1) - Please choose one

Which kind of functions can access private member variables of a class?

► **Friend functions of the class (Page 374)**
► Private member functions of the class
► Public member functions of the class
► Friend, private and public functions

► True
► **False (Page 79)**

► Member function
► **Non-member function (Page 348)**
► Private function
► Public function

Question No: 8 (Marks: 1) - Please choose one

Function implementation of friend function must be defined outside the class.

► True
► **False (Page 346)**

Question No: 9 (Marks: 1) - Please choose one
9

► File
► Disk
► **Keyboard (Page 424)**
► RAM

Question No: 10 (Marks: 1) - Please choose one

Which of the following is correct way to initialize a variable x of int type with value 10?

► int x ; x = 10;
► **int x = 10;**
► int x, x = 10;
► x = 10;

Question No: 11 (Marks: 1) - Please choose one

Consider the following code segment. What will be the output of the following program?

```
int func(int) ;

int num = 10 ;

int main(){

int num ;

num = 5 ;

cout << num ;



cout << func(num) ;

}

int func(int x){

return num ;

}
```

► 5, 5
► 10, 5
► **5, 10**
► 10, 10

Question No: 12 (Marks: 1) - Please choose one

With template function, the compiler automatically detects the passed data and generates a new copy of

function using passed data.

► **True Page 510**
► False

Question No: 13 (Marks: 1) - Please choose one

What will be the correct syntax to declare two-dimensional array of float data type?

► float arr{2}{2} ;
► **float arr[2][2] ;**
10

► float arr[2,2] ;
► float[2][2] arr ;

► Must be passed by value
► **Must be passed by reference (Page 446)**
► Can be passed by value or reference
► Must be object of class

► **True (Page 280)**
► False

Question No: 16 (Marks: 1) - Please choose one

While calling function, the arguments are assigned to the parameters from _____.

► **left to right. (Page 295)**
► right to left
► no specific order is followed
► none of the given options.

► looped

► **nested (Page 492)**
► overloaded
► none of the given options.

Question No: 18 (Marks: 1) - Please choose one

If we define an identifier with the statement **#define PI 3.1415926** then during the execution of the program

the value of PI _____.

► can not be replaced
► None of the given options
► **Remain constant. (Page 271)**
► can be changed by some operation

► A pointer to the class.
11

► An object of the class.
► A status code determining whether the class was destructed correctly
► **Destructors do not return a value. (page 323)**

► Constructor
► Destructor
► **Both a constructor and a destructor (Lecture 27)**
► None of the given options

► **One or more than one arguments**
► Only one argument
► Zero arguments
► None of the given options

► **Databases Management (page 563)**
► Networks
► Writing Operating System
► none of the given options

Question No: 23 (Marks: 1) - Please choose one

When a call to a user-defined function finishes, the variable defined inside the function is still in existence.

► True
► **False (Page 460)**

Question No: 24 (Marks: 1) - Please choose one

The precedence of an operator can be changed through operator overloading.

► True
► **False (Page 372)**

Question No: 25 (Marks: 1) - Please choose one

A Matrix can be composed of ints, floats or doubles as their elements. Best way is to handle this ,

_____

► Write a separate class to handle each
► **Use templates (Page 527)**
► Use strings to store all types
► None of the given options

12

Question No: 26 (Marks: 1) - Please choose one

"**delete**" operator is used to return memory to free store, which is allocated by the "**new**" operator.

► **True (page 332)**
► False

► Data
► **Memory Address (Page 267)**
► Data Type

► Values

► *
► +
► @
► # (Page 269)

Question No: 3 Marks: 1) - Please choose one

Within the statement **obj1=obj2;** ***obj1*** will call the assignment operator function and ***obj2*** will be passed

as an argument to function.

► True
► False

Question No: 4 (Marks: 1) - Please choose one

What is the sequence of event(s) when deallocating memory using delete operator?

► Only block of memory is deallocated for objects

► Only destructor is called for objects
► Memory is deallocated first before calling destructor

► **Destructor is called first before deallocating memory (Page 414)**

Question No: 5 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are

13

overloading these operators.

► **True (page 453)**
► False

Question No: 6 (Marks: 1) - Please choose one

To include code from the library in the program, such as iostream, a directive would be called up

using this

command.

► #include “iostream.h”
► include <iostream.h>
► include <iostream.h>
► **#include <iostream.h> (sure)**

► int
► short
► **float (Sure)**
► char

► **True (Page 503)**
► False

Question No: 9 (Marks: 1) - Please choose one

For which values of the integer _value will the following code becomes an infinite loop?

```
int number=1;

while (true) {

cout << number;


if (number == 3) break;

number += integer_value; }
```

► any number other than 1 or 2
► **only 0**
► only 1
► only 2

Question No: 10 (Marks: 1) - Please choose one
Template class cannot have static variables.

► True
► False
14

Question No: 11 (Marks: 1) - Please choose one
Which of the following is used with bit manipulation?

► Signed integer
► **Un-signed integer (Page 245)**
► Signed double
► Un-signed double

Question No: 12 (Marks: 1) - Please choose one

Structure is a collection of _____ under a single name.

► Only Functions
► **Only Variables (Page 229)**
► Both Functions and Variables
► None of the given options

Question No: 13 (Marks: 1) - Please choose one

Which of the following is the correct C++ syntax to allocate space dynamically for an array of 10 int?

► new int(10) ;
► **new int[10] ;**
► int new(10) ;
► int new[10];

Question No: 14 (Marks: 1) - Please choose one

Unary operator implemented as member function takes ____ arguments whereas non-member

function

takes _____ arguments.

► One, zero
► **Zero, one**
► One, two
► Two, one

Question No: 15 (Marks: 1) - Please choose one

The first parameter of overloaded stream insertion operator is _____ where second

parameter is

_____

► input stream, object of class
► object of class, output stream
► output stream, object of class
► object of class, input stream

► **True (Page 272)**
► False

15

Question No: 17 (Marks: 1) - Please choose one

If a symbolic constant has been defined, it will be an error to define it again.

► **True (Page 273)**
► False

Question No: 18 (Marks: 1) - Please choose one

While calling function, the arguments are assigned to the parameters from _____.

► **left to right. (Page 295)**
► right to left

► no specific order is followed

► none of the given options.

► looped
► **nested (Page 492)**
► overloaded
► none of the given options.

Question No: 20 (Marks: 1) - Please choose one

If we define an identifier with the statement **#define PI 3.1415926** then during the execution of the program

the value of PI _____.

► cannot be replaced
► None of the given options
► **Remain constant. (Page 271)**
► can be changed by some operation

► **right**
► left
► binary
► unary

Question No: 22 (Marks: 1) - Please choose one

If **text** is a pointer of class **String** then what is meant by the following statement?
text = new String [5];

► Creates an array of 5 string objects statically

► **creates an array of 5 string objects dynamically**

► Creates an array of pointers to string

► Creates a string Object

Question No: 23 (Marks: 1) - Please choose one

The return type of the operator function for << operator is _____.

► **class for which we overload operator**

► reference of ostream class (ostream&)
► reference of istream class (istream&)
► void

► **implement (Page 520)**
► design
► analysis
► none of the given options.

Question No: 25 (Marks: 1) - Please choose one

Memory allocated at run time is a system resource and it is the responsibility of _____ to de-

allocate the

memory.

► System
► **Programmer (Page 331)**
► User of program
► None of given options

► True
► **False (Page 518)**

FINALTERM EXAMINATION
Spring 2010

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one
*.doc is _____ by type.

.

► Sequential File
► Random Access File
► Data File
► Record File

► #error
17

► #define
► #line
► **#ndefine (Page 2727)**

► True

► **False (Page 79)**

► The current function of the class
► The current pointer of the class
► **The current object of the class (Page 390)**
► A value of the data member

► Read a string from keyboard
► **Read a character from keyboard (Page 426)**
► Read a string from file
► Read a character from file

Question No: 6 (Marks: 1) - Please choose one

When we do dynamic memory allocation in the constructor of a class, then it is necessary to

provide a

destructor.

► **True (Page 479)**
► False

Question No: 7 (Marks: 1) - Please choose one

Overloaded new operator function takes parameter of type *size_t* and returns

► void (nothing)
► **void pointer (Page 415)**
► object pointer
► int pointer

Question No: 8 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are

overloading these operators.

► **True (Page 453)**
► False

Question No: 9 (Marks: 1) - Please choose one
18

► **True (Page 68)**
► False
Question No: 10 (Marks: 1) - Please choose one

To include code from the library in the program, such as iostream, a directive would be called up

using this

command.

► #include “iostream.h”

► include <iostream.h>
► include <iostream.h>
► **#include <iostream.h> (Sure)**

► True
► **False (Page 501)**

► True
► **False**
Question No: 13 (Marks: 1) - Please choose one

What will be the correct syntax to assign an array named ***arr*** of 5 elements to a pointer ***ptr***?

► *ptr = arr ;
► ptr = arr ;
► *ptr = arr[5] ;
► ptr = arr[5] ;

Question No: 14 (Marks: 1) - Please choose one

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

► ptr[3]
► (ptr+3)
► *(ptr+3)
► **Both 1and 3**

Question No: 15 (Marks: 1) - Please choose one

If most significant bit of un-signed number is 1 then it represents a positive number.

► True
► **False (Page 251)**

Question No: 16 (Marks: 1) - Please choose one
19

If there is a symbol (& sign) used with the variable name followed by data type then it refers to

_____ and

if & is being used with variable name then it refers to _____.

► Address of variable, reference variable
► Reference variable, value of variable
► **Reference variable, address of variable (Page 367)**
► Address of variable, value of variable

► **True (Page 272)**
► False

Question No: 18 (Marks: 1) - Please choose one

The default value of a parameter can be provided inside the _____

► function prototype
► function definition
► **both function prototype or function definition (Page 294)**

► none of the given options.

Question No: 19 (Marks: 1) - Please choose one

Classes defined inside other classes are called _____ classes

► looped
► **nested (Page 492)**
► overloaded
► none of the given options.

► Data encapsulation
► Providing a convenient way of modeling real-world objects
► Simplifying code reuse
► **All of the given options**

► Constructor
► Destructor
► **Both a constructor and a destructor (Lecture 27)**
► None of the given options

Question No: 22 (Marks: 1) - Please choose one

new operator is used to allocate memory from the free store during
20

► Compile Time
► **Run Time**
► Link Time
► None of the given options

Question No: 23 (Marks: 1) - Please choose one

When an object of a class is defined inside another class then,

► Destructor of enclosing class will be called first
► Destructor of inner object will be called first
► Constructor and Destructor will be called simultaneously
► None of the given options

► **True (Page 492)**
► False

Question No: 25 (Marks: 1) - Please choose one

New and Delete are also used with _____ and data types as well.

► **Class, Objects (Page 342)**
► Structures, Pointers
► Both Class and structures
► None of above

Question No: 26 (Marks: 1) - Please choose one

With New keyword, data types and class members are initialized with meaningful values instead

of

garbage.

► **True (Page 334)**
► False

FINALTERM EXAMINATION

Spring 2010

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one

If it is required to copy an array to another array then,

► **Both arrays must be of the same size and data type (Page 105)**
► Both arrays may be of different size
► Both arrays may be of different data type
► Both arrays may be of different size and type

Question No: 2 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

► **True**
► False

Question No: 3 (Marks: 1) - Please choose one
eof( ), bad( ), good( ), clear( ) all are manipulators.

► **True (Page 433)**
► False
Question No: 4 (Marks: 1) - Please choose one

Overloaded new operator function takes parameter of type *size_t* and returns

► void (nothing)
► **void pointer (Page 415)**
► object pointer
► int pointer
Question No: 5 (Marks: 1) - Please choose one

When new operator is overloaded at global level then corresponding built-in new operator will not be

visible to whole of the program.

► **True (Page 413)**

► False
Question No: 6 (Marks: 1) - Please choose one

If there is more than one statement in the block of a for loop, which of the following must be placed at the

beginning and the ending of the loop block?

► parentheses ( )
► **braces { } (Page 37)**
► brackets [ ]
► arrows < >

Question No: 7 (Marks: 1) - Please choose one

The return type of a function that do not return any value must be _____

► float
► int
► **void (Page 79)**
► double

Question No: 8 (Marks: 1) - Please choose one
UNIX has been developed in _____ language.

22

► JAVA
► B
► **C (Page 12)**
► FORTRAN
Question No: 9 (Marks: 1) - Please choose one

Like member functions, _____ can also access the private data members of a class.

► Non-member functions
► **Friend functions (Page 346)**
► Any function outside class
► None of the given options
Question No: 10 (Marks: 1) - Please choose one

Which of the following statement is best regarding declaration of friend function?

► Friend function must be declared after public keyword.
► Friend function must be declared after private keyword.
► Friend function must be declared at the top within class definition.

► **It can be declared anywhere in class as these are not affected by the public and private keywords. (Page 346)**

Question No: 11 (Marks: 1) - Please choose one

The operator function overloaded for an Assignment operator (=) must be

► Non-member function of class
► **Member function of class (Page 372)**
► Friend function of class
► None of the given options

Question No: 12 (Marks: 1) - Please choose one

The **endl** and **flush** are _____

► Functions
► Operators
► **Manipulators (Page 434)**
► Objects
Question No: 13 (Marks: 1) - Please choose one

If a symbolic constant has been defined, it will be an error to define it again.

► **True (Page 273) 15**
► False

The operator used for casting, in C, is standard _____ operator.

23

► none of the given options.
► **cast (Page 281)**
► cost
► const

► True
► **False (Page 323)**
Question No: 16 (Marks: 1) - Please choose one

Which of the following function call is correct for the function prototype?

defaultParameters (int a, int b = 7, char z = '*');

► **defaultParameters (5);**
► defaultParameters (5, '8');
► defaultParameters (6, '#');
► defaultParameters (0, 0, '*', 0);
Question No: 17 (Marks: 1) - Please choose one

When an operator function is defined as member function for a binary Plus (+) operator then the number of

argument it take is/are.

► Zero
► One
► **Two (Page 371)**
► N arguments

► True
► **False (Page 320)**
Question No: 19 (Marks: 1) - Please choose one

When an object of a class is defined inside an other class then,

► **Constructor of enclosing class will be called first (Page 464)**
► Constructor of inner object will be called first
► Constructor and Destructor will be called simultaneously
► None of the given options
24

Question No: 20 (Marks: 1) - Please choose one

The appropriate data type to store the number of rows and colums of the matrix is_____.

► float
► **int (Not sure)**
► char
► none of the given options.

► **data type (page 317)**
► memory referee
► value
► none of the given options.

► Decremented
► Incremented
► Multiplied

► **Both Iecremented and Decremented (Page 366)**
Question No: 23 (Marks: 1) - Please choose one
NULL value has been defined in _____ and _____ header files.

► strings.h and iostream.h
► ctype.h and conio.c
► conio.c and conio.h
► **stdlib.h and stddef.h (Page 281)**
Question No: 24 (Marks: 1) - Please choose one

A Matrix can be composed of ints, floats or doubles as their elements. Best way is to handle this ,

_____

► Write a separate class to handle each
► **Use templates (Page 527)**
► Use strings to store all types
► None of the given options

Question No: 25 (Marks: 1) - Please choose one
"setprecision" manipulator will set 25

► **The number of digits after the decimal point (Page 440)**

► The number of digits before the decimal point
► The number of digits in a number
► None of the given options
Question No: 26 (Marks: 1) - Please choose one

Which of the following option will be true, if we overload "-=" operator?

► only - operator needs to be overloaded
► Minus (-) and = operators need to be overloaded
► **the -= operator need to be overloaded explicitly**
► the - and = operators need to be overloaded implicitly

Fall 2009

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one

In C/C++ if we define an array of size eight (8) i.e. int Arr [8]; then the last element of this array will

be stored

at,

► Arr[0]
► Arr[8]

► **Arr[7]**
► Arr[-1]
Question No: 2 (Marks: 1) - Please choose one

When an array is passed to a function then default way of passing this array is,

► By data

► **By reference (Page 154)**
► By value
► By data type

► Memory addresses
► Variables
► **Data Type (Page 100)**
► Data

► **True (Page 408)**
► False
26

Question No: 5 (Marks: 1) - Please choose one

When we define an array of objects then,

► Destructor will call once for whole array
► **Destructor will call for each object of the array**
► Destructor will never call
► Depends on the size of array

Question No: 6 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

► Only block of memory is allocated for objects
► Only constructor is called for objects
► **Memory is allocated first before calling constructor (Page 414)**
► Constructor is called first before allocating memory

Question No: 7 (Marks: 1) - Please choose one

We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory

allocation internally.

► True
► **False**

Question No: 8 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class For which we are overloading these operators.

► **True (Page 453)**
► False

Question No: 9 (Marks: 1) - Please choose one

Which of the following is correct way to initialize a variable x of int type with value 10?

► int x ; x = 10 ;
► **int x = 10 ; (sure)**
► int x, x = 10;
► x = 10 ;

Question No: 10 (Marks: 1) - Please choose one

Default mechanism of function calling in case of array is _____ and in case of

variable is ___.

► Call by value, call by reference
► Call by referene, call by reference

► **Call by reference, call by value (Page 119)**
► Call by value, call by value

► Source template library

27

► **Standard template library (Page 519)**
► Stream template library
► Standard temporary library

Question No: 12 (Marks: 1) - Please choose one

Skill(s) that is/are needed by programmer's _____.

► Paying attention to detail
► Think about the reusability
► Think about user interface

► **All of the given options (Page 4 & 5)** **Question No: 13 (Marks: 1) - Please choose one**

For which array, the size of the array should be one more than the number of elements in an array?

► int
► double
► float
► **char (Page 113)**

new and delete are _____ whereas malloc and free are _____.

► Functions, operators
► Classes, operators
► **Operators, functions (Page 342-285)**

► Operators, classes

► Member functions
► Public member functions

► Private member functions
► **Non-member functions (Page 346)**

The prototype of friend functions must be written ____ the class and its

definition must be written ____

► inside, inside the class
► **inside, outside the class (Page 346)**
► **outside, inside the class**
► outside, outside the class

Question No: 17 (Marks: 1) - Please choose one

If overloaded plus operator is implemented as non-member function then which of the following statement will be true for the statement given below?

obj3 = obj1 + obj2 ;

► obj2 will be passed as an argument to + operator whereas obj2 will

drive the + operator

► obj1 will drive the + operator whereas obj2 will be passed as an argument
to + operator
► Both objects (obj1, obj2) will be passed as arguments to the + operator (not sure)
► Any of the objects (obj1, obj2) can drive the + operator
Question No: 18 (Marks: 1) - Please choose one

Which one of the following is the declaration of overloaded pre-increment operator implemented as

member

function?

► Class-name operator +() ;

► Class-name operator +(int) ;
► Class-name operator ++() ; (page 389)
► Class-name operator ++(int) ;
Question No: 19 (Marks: 1) - Please choose one

For cin, the source is normally a _____ and destination can be _____.

► File, native data type

► Disk, user-define type
► Keyboard, variable (Page 424)

For *cin*, the source is normally keyboard and the destination can be an ordinary variable

► File, user-define type

► True (Page 272)
► False
Question No: 21 (Marks: 1) - Please choose one

The programs, in which we allocate static memory, run essentially on _____

► Heap
► System Cache
► None of the given options
► Stack (Page 280)
The programs, in which we allocate static memory, run essentially on stack.

Question No: 22 (Marks: 1) - Please choose one

The default value of a parameter can be provided inside the _____

► function prototype
► **function definition (Page 249)**
► both function prototype or function definition

► none of the given options.

The default value of a parameter is provided inside the function prototype or function definition.
Question No: 23 (Marks: 1) - Please choose one

29

While calling function, the arguments are assigned to the parameters from _____.

► **left to right. (page 295)**

► right to left
► **no specific order is followed**
► none of the given options.
Question No: 24 (Marks: 1) - Please choose one

When an operator function is defined as member function for a binary Plus (+) operator then the number of

argument it take is/are.

► Zero
► One
► **Two (Page 371)**
► **N arguments**

Question No: 25 (Marks: 1) - Please choose one

With user-defined data type variables (Objects), self assignment can produce

_____.

► Syntax error
► **Logical error**
► Link error
► **Non of the given options (not sure)**
Question No: 26 (Marks: 1) - Please choose one

Assignment operator is used to initialize a newly declared object from existing object.

► **True (Page 479)**
► False

Question No: 27 (Marks: 1) - Please choose one

When an object of a class is defined inside an other class then,

► **Constructor of enclosing class will be called first (Page 496)**
► Constructor of inner object will be called first
► Constructor and Destructor will be called simultaneously
► None of the given options

Question No: 28 (Marks: 1) - Please choose one

In the member initializer list, the data members are initialized,

► From left to right
► From right to left
► **In the order in which they are defined within class**
► None of the given options

Question No: 29 (Marks: 1) - Please choose one

new operator allocates memory from free store and return _____.

30

► **A pointer**
► A reference
► An integer

► A float

Question No: 30 (Marks: 1) - Please choose one

"new" and "delete" keywords are _____ in C++ language.

► Built-in- Function
► Operators

► **Memory Allocation Function (Page 332)**
► None of the given options

Spring 2010

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one

► is ---------- operator.
► An arithmetic

► **Logical (Page 40)**
► Relational
► Unary

Question No: 2 (Marks: 1) - Please choose one

Which of the following function(s) is/are included in **ctype.h** header file?

► isdigit(int c)
► isxdigit(int c)
► tolower(int c)

► **All of the above (Page 188)**

Question No: 3 (Marks: 1) - Please choose one

Disks are _____ devices having access time of _____ milliseconds.

► Electro-physical, 6
► Electro-Mechanical, 4

► Electro-physical, 5
► **Electro-Mechanical, 7 (Page 427)**

► *
31

► ++

► @
► **# (Page 269)**
Question No: 5 (Marks: 1) - Please choose one

When we use manipulators in our program then which header file should be included?

► iostream.h
► stdlib.h
► stdio.h
► **iomanip.h (Page 433)**

Question No: 6 (Marks: 1) - Please choose one

setprecision is a parameter less manipulator.

► True
► **False (Page 439)**

► #error
► #define
► #line
► **#ndefine (Page 272)**

► True
► **False (Page 369)**

Question No: 9 (Marks: 1) - Please choose one

What does **(*this)** represents?

► The current function of the class
► The current pointer of the class
► **The current object of the class (Page 390)**
► A value of the data member

► Member function
► **Non-member function (Page 348)**
► Private function
► Public function

Question No: 11 (Marks: 1) - Please choose one A function can declare itself a friend of a class.

► True
► **False (Page 346)**

Question No: 12 (Marks: 1) - Please choose one

Overloaded delete operator function takes the same parameter as an argument returned by new operator function.

► **True (Page 414)**
► False

Question No: 13 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are overloading these operators.

► **True (Page 453)**
► False

The second parameter to *operator* << is an object of the class that we are overloading the operator for. Similar

is the case for *operator* >>

Question No: 14 (Marks: 1) - Please choose one

A template function must have at least ---------- generic data type

► Zero
► **One (Page 499)**
► Two
► Three

► True
► **False (Page 501)**

► True

► **False (Page 506)**

Question No: 17 (Marks: 1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?

► new line
► tab
► **null (Page 113)**
► carriage return

Question No: 18 (Marks: 1) - Please choose one

is used for _____.

33

► calculation
► reading
► **assigning value to variables (Page 372)**
► None of the given options.

Question No: 19 (Marks: 1) - Please choose one vuzs

The object _____may be used both for file input and file output

► **fstream, (Page 199)**
► ifstream,
► ofstream,
► none of the given options.

Question No: 20 (Marks: 1) - Please choose one

Which of the following function calling mechanism is true for the function prototype given below?
float func(float &);

► Call by value
► Call by reference using pointer

► **Call by reference using reference variable**
► None of the given options

Question No: 21 (Marks: 1) - Please choose one

The programs, in which we allocate static memory, run essentially on _____

► Heap

► System Cache
► None of the given options

► **Stack (Page 280)**

Question No: 22 (Marks: 1) - Please choose one

Overloaded delete operator function takes parameter of void pointer and returns

_____.

► **void**
► void pointer
► pointer to an object
► pointer of type int

► void pointer

► int
► same as object type

► **constructors do not return any thing (Page 313)**

Question No: 24 (Marks: 1) - Please choose one

It is a way of reusing the code when we contain objects of our already written classes into a new class,

► **True**
34

► False

► true
► **false (Page 518)**

Question No: 26 (Marks: 1) - Please choose one

The functions used for dynamic memory allocation return pointer of type _____

► int
► float
► **void**
► double

FINALTERM EXAMINATION

Fall 2008

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one

There are mainly ---------- types of software

► Two (Page 9)
► Three
► Four
► Five

seekg() and write() are functionally _____ .

► Different
► Identical
► Two names of same function
► None of the above

Question No: 3 (Marks: 1) - Please choose one

When a pointer is incremented, it actually jumps the number of memory addresses

► **According to data type (Page 160)**
► 1 byte exactly
► 1 bit exactly
► A pointer variable can not be incremented

Question No: 4 (Marks: 1) - Please choose one
setw is a parameterized manipulator.

35

► **True (Page 437)**
► False

Question No: 5 (Marks: 1) - Please choose one
eof( ), bad( ), good( ), clear( ) all are manipulators.

► **True (Page 433)**
► False

► Local

► Global
► **Global or static (Page 369)**
► None of the given option

► **Class-Name operator + (Class-Name rhs) (Page 371)**
► operator Class-Name + ( )
► operator Class-Name + (rhs)
► Class-Name operator + ( )

Question No: 8 (Marks: 1) - Please choose one

The compiler does not provide a copy constructor if we do not provide it.

► True
► **False (Page 476)**

Question No: 9 (Marks: 1) - Please choose one

What is the functionality of the following syntax to delete an array of 5 objects named ***arr***

allocated using

new operator?

delete arr ;

► Deletes all the objects of array
► **Deletes one object of array (Page 411)**
► Do not delete any object
► Results into syntax error

This statement will call the destructor only for the object pointed by the ***arr*** and deallocate the space

allocated to

this object

Question No: 10 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

► Only block of memory is allocated for objects
► Only constructor is called for objects
► **Memory is allocated first before calling constructor (Page 414)**
► Constructor is called first before allocating memory

Question No: 11 (Marks: 1) - Please choose one

What is the sequence of event(s) when deallocating memory using delete operator?

► Only block of memory is deallocated for objects

► Only destructor is called for objects
► Memory is deallocated first before calling destructor

► Destructor is called first before deallocating memory (Page 414)

Question No: 12 (Marks: 1) - Please choose one

new and **delete** operators cannot be overloaded as member functions.

► True
► False (Page 414)

Question No: 13 (Marks: 1) - Please choose one

The operator function of << and >> operators are always the member function of a class.

► True
► False (Page 446)

► Zero
► One (Page 499)
► Two
► Three

Question No: 15 (Marks: 1) - Please choose one

If we do not mention any *return_value_type* with a function, it will return an _____ value.

► int (Page 79)
► void
► double
► float

Question No: 16 (Marks: 1) - Please choose one

Suppose a program contains an array declared as **int arr[100];** what will be the size of array?

► 0
► 99
► 100 (Page 103)
► 101

37

Question No: 17 (Marks: 1) - Please choose one

The name of an array represents address of first location of array element.

► **True**
► False

The name of the array is a constant pointer which contains the memory is the address of first element

of the

array

Question No: 18 (Marks: 1) - Please choose one Reusing
the variables in program helps to save the memory

► **True**
► False
Question No: 19 (Marks: 1) - Please choose one

Which of the following option is true about new operator to dynamically allocate memory to an object?

► The new operator determines the size of an object
► Allocates memory to object and returns pointer of valid type
► Creates an object and calls the constructor to initialize the object
► **All of the given options**

► Functions, operators
► Classes, operators
► **Operators, functions (Page 342-285)**
► Operators, classes
Question No: 21 (Marks: 1) - Please choose one

Like member functions, _____ can also access the private data members of a class.

► Non-member functions
► **Friend functions (Page 346)**

► Any function outside class
► None of the given options

Question No: 22 (Marks: 1) - Please choose one

Which of the following statement is best regarding declaration of friend function?

► Friend function must be declared after public keyword.
► Friend function must be declared after private keyword.
► Friend function must be declared at the top within class definition.

► It can be declared anywhere in class as these are not affected by the public and private keywords. (Page 346)

38

Question No: 23 (Marks: 1) - Please choose one

The operator function overloaded for an Assignment operator (=) must be

► Non-member function of class
► Member function of class (Page 372)
► Friend function of class
► None of the given options

Question No: 24 (Marks: 1) - Please choose one

For non-member operator function, object on left side of the operator may be

► Object of operator class
► Object of different class
► Built-in data type
► All of the given options (Page 375)

Question No: 25 (Marks: 1) - Please choose one

The operator function will be implemented as _____, if obj1 drive the - operator whereas obj2 is passed as

arguments to - operator in the statement given below.

obj3 = obj1 - obj2;

► Member function (Page 373)
► Non-member function
► Friend function
► None of the given options

Question No: 26 (Marks: 1) - Please choose one

Which one of the following is the declaration of overloaded pre-increment operator implemented as

member function?

► Class-name operator +() ;
► Class-name operator +(int) ;
► **Class-name operator ++() ; (Page 389)**
► Class-name operator ++(int) ;

► **at file scope (Page 466)**
► within class definition
► within member function
► within main function

Question No: 28 (Marks: 1) - Please choose one

Class is a user defined_____.

► **data type (Page 317)**

39

► memory referee
► value
► none of the given options.

► **True**
► False

► Heap
► Free store
► static storage
► **stack (Page 461)**

FINALTERM EXAMINATION
fall 2008

CS201- Introduction to Programming (Session - 2)

Question No: 1 (Marks: 1) - Please choose one

If Num is an integer variable then Num++ means,

- Add 1 two times with Num
- **Add 1 with Num**
- Add 2 with Num
- Subtract 2 from Num

Question No: 2 (Marks: 1) - Please choose one

If the return type of a function is void then it means that it will,

- Return any type of data
- Return some specific type of data
- **Return no data**
- Return just character data

Question No: 3 (Marks: 1) - Please choose one

Which of the following is a valid class declaration?

- **class A { int x; };**
- class B { }
- public class A { }
- object A { int x; };

Question No: 4 (Marks: 1) - Please choose one

40

When we use manipulators in our program then which header file should be included?

- iostream.h
- stdlib.h
- stdio.h

- **iomanip.h (Page 433)**

- **True (Page 408)**

- False

- File

- Disk

- **Keyboard (Page 424)**

- RAM

- **True (Page 423)**

- False

Question No: 8 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

- Only block of memory is allocated for objects

- Only constructor is called for objects

- **Memory is allocated first before calling constructor (Page 414)**

- Constructor is called first before allocating memory

Question No: 9 (Marks: 1) - Please choose one

We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory

allocation internally.

- **True (Page 412)**
- False

Question No: 10 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are overloading these operators.

- **True (Page 453)**
- False

Question No: 11 (Marks: 1) - Please choose one

Which looping process checks the test condition at the end of the loop?

41

- for
- while
- **do while**
- no looping process checks the test condition at the end

Question No: 12 (Marks: 1) - Please choose one

In a group of nested loops, which loop is executed the most number of times?

- the outermost loop
- **the innermost loop**
- all loops are executed the same number of times
- cannot be determined without knowing the size of the loops

- True
- **False (Page 513)**

Question No: 14 (Marks: 1) - Please choose one

Consider the following statements to initialize a two-dimensional array.

- int arr[2][3] = {4, 8, 9, 2, 1, 6} ;

- int arr[3][2] = {4, 8, 9, 2, 1, 6} ;
- int arr[][2] = {{4,8},{9, 2},{1, 6}} ;

Which of the following option(s) are correct to initialize a two-dimensional array with 3 rows and 2 columns?

- (ii) only
- (iii) only
- **(ii) and (iii)**
- and (iii)

Question No: 15 (Marks: 1) - Please choose one

There is a pointer variable named ***ptr*** of type int then address of which type of variable the ***ptr*** will store in it?

- variable of type char
- variable of type short
- **variable of type int**
- variable of type double

Question No: 16 (Marks: 1) - Please choose one

Let suppose

Union intorDouble{

Int ival;

Double charvar;

};

main(){

42

intorDouble VAZ;

int size ;

size = sizeof(VAZ);

}

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8 bytes?

- 2
- 4
- 8
- 12

Question No: 17 (Marks: 1) - Please choose one

new and delete are _____ whereas malloc and free are _____.

- Functions, operators
- Classes, operators
- **Operators, functions (Page 342-285)**
- Operators, classes

Question No: 18 (Marks: 1) - Please choose one

The member functions of a class occupy _____ region in memory for ____ object(s) of class.

- separate, each
- **common, all (Page 334)**
- different, each
- different, all

- Member functions
- Public member functions
- Private member functions
- **Non-member functions (Page 346)** **Question No: 20 (Marks: 1) - Please choose one**

Which of the following is true while overloading operators?

- Precedence of an operator can be changed
- The arity (number of operands) can be changed
- No new operators can be created
- Associativity of an operator can be changed

Question No: 21 (Marks: 1) - Please choose one

Which of the following option will be true to overload the -= operator?

- **only - operator needs to be overloaded (not sure)**
- Minus (-) and = operators need to be overloaded
- the -= operator need to be overloaded explicitly
- the - and = operators need to be overloaded implicitly

43

Question No: 22 (Marks: 1) - Please choose one

The input/output streams; cin and cout are ____

- Operators
- **Functions**
- Objects
- Structures

Question No: 23 (Marks: 1) - Please choose one
dec, hex, oct are all _____

- Member functions
- Objects of input/output streams
- Parameterized manipulators

- **Non-parameterized manipulators (Page 435)**

Question No: 24 (Marks: 1) - Please choose one

What will be the output of the following statement?

cout << setbase(16) << 52 ;

- 74
- 52
- **34**
- 64

Question No: 25 (Marks: 1) - Please choose one

The first parameter of overloaded stream insertion operator is _____ where second parameter is _____

- input stream, object of class
- object of class, output stream
- **output stream, object of class**
- object of class, input stream

Question No: 26 (Marks: 1) - Please choose one

We can also do conditional compilation with preprocessor directives.

- **True (Page 272)**
- False

Question No: 27 (Marks: 1) - Please choose one

With user-defined data type variables (Objects), self assignment can produce _____.

- Syntax error
- **Logical error**
- Link error
- Non of the given options

Question No: 28 (Marks: 1) - Please choose one

The return type of the operator function for >> operator is _____.

- **class for which we overload this operator**
- reference of ostream class (ostream&)
- reference of istream class (istream&)
- void

- **Constructor of enclosing class will be called first (Page 496)**
- Constructor of inner object will be called first
- Constructor and Destructor will be called simultaneously
- None of the given options

Question No: 30 (Marks: 1) - Please choose one

Where we can include a header file in the program?

- **any where (Page 270)**
- in start
- at the end

For binary member operators, operands on the _____ drives (calls) the operation.

1. Left
2. Right
3. Both left and right
4. None of the given

We cannot increment _____.

1. pointers

2. arrays

3. references

4. variables

We can _____ pointer.

1. increment
2. decrement
3. reassign
4. all of the given

We can _____references.

► increment
2.decrement
3. reassign
4. None of the given

What will be the correct syntax for the following function call? float add (int &);

1. add(int x);
2. add(&x);
3. add(x);
4. add(*x);

An instance of a class is called _____.

1. structure
2. data type
3. object
4. member function

The _____ is called automatically when an object destroys

1. destructor
2. constructor
3. main program
4. default constructor

The destructor is used to _____.

1. allocate memory
2. deallocate memory
3. create objects
4. allocate static memory

_____data isn't accessible by non-member functions or outside classes.

1. Public
2. private
3. Static
4. Globally declared

Member functions of the class _____ main program.

1. are not accessible
2. are accessible from
3. are defined within the
4. are private to

Overloading means :

► Using the same name to perform multiple tasks or different tasks depending on the situation.

► Using the different name to perform multiple tasks or different tasks depending on the situation

► Using the same name to perform multiple tasks or same tasks depending on the situation

► Using the same name to perform difficult tasks or complex tasks and it does not depend on the situation

The main advantage of function overloading is _____.

► The program becomes portable2.The program becomes complex

3. The function becomes inline 4. The program becomes more readable

You cannot overload the _____ operator

1. ? : 2. *

3. / 4. ++

Memory allocated from heap or free store _____.

► can be returned back to the system automatically

► can be allocated to classes only

► cannot be returned back unless freed explicitly using malloc and realloc

► cannot be returned back unless freed explicitly using free and delete operators

We cannot use _____ pointer for storing and reading data from it.

1. 2. intege

r

3. double
4. zero

The dynamic memory allocation uses _____ whereas static memory allocation uses _____.

1. heap , stack
2. stack , lists
3. array , stack
4. classes , array

What will be the output of the given code? #include #define MAX(A, B) ((A) > (B) ? (A) : (B))

void main() { int i, x, y; x = 23; y = 45; i = MAX(x++, y++); // Side-effect: // larger value incremented twice cout << "x = " << x << " y = " << y << '\n'; }

1. x=23
   y=45

2. x=24
   y=46

3. x=24
   y=47

4. x=22
   y=47

getche() is a _____ function and defined in _____ header file.

1. user-define function , conio.h
2. built-in function , conio.h
3. built-in function, stlib.h
4. built -in function, iostream.h

Symbolic constant PI can be defined as:

1. #define PI 3.14 ;
2. #define PI 3.14
3. #define PI=3.14
4. # include pi= 3.14

The parameter passed to isdigit() function is _____variable.

1. Character
2. Boolea

n

3. Integer
4. Float

char **argv can be read as_____.

1. pointer to pointer
2. pointer to char
3. pointer to pointer to char
4. None of the given

To read command-line arguments, the main() function itself must be given _____ arguments.

1. 1
2. 2
3. 3
4. 4

The increment of a pointer depends on its_____.

1. variable
2. value
3. data type
4. None of the given

How many bytes an integer type pointer intPtr will jump in memory if the statement below is executed? intPtr += 2 ;

1. 2
2. 4
3. 8
4. 12

QUESTION

The statement cout << yptr will show the _____the yptr points to.

1. Value
2. memory address
3. Variable
4. None of the given

QUESTION

_____ is used as a dereferencing operator.

1. * 2. +

► -4.None of the above

Transpose of a matrix means that when we interchange rows and columns_____.

1. the first row becomes the Last column
2. the first row becomes the first column
3. the Last row becomes the first column
4. the first column becomes the first row

Individual characters in a string stored in an array can be accessed directly using array _____.

1. superscript 2. script

3. subscript 4. value

We can define a matrix as_____ array.

1. Sorted 2. Unsorted

3. Single dimensional 4. Multi dimensional

A _____is an array of characters that can store number of character specified.

1. Char 2. String
3. Multidimensional array 4. Data type

Given a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column? ٦٫٥

1. array[3][4] = 6 ; 2. array[2][4] = 6 ;
3. array[4][3] = 6 ; 4. array[2][3] = 6 ;

A

_____ of a variable means the locations within a program from where it can be accessed.

1. Data type
2. Visibility
3. Value
4. Reference

Which of the following function call is "call by reference" for the following function prototype?
int add (int *);

1. add(&x);
2. add(int x);
3. add(x);
4. add(*x);

Which of the following function call is "call by reference" for the following function prototype?
float add (float *);

1. add(&x);
2. add(float x);
3. add(x);
4. add(*x);

Which of the function call is call by value for the following function prototype? float add(float);

1. add(&x);
2. add(x);
3. add(float x);
4. add(*x);

Which of the function call is "call by value" for the following function prototype? float add(int);

1. add(&x);
2. add(x);
3. add(int x);
4. add(*x);

Return type of a function that does not return any value must be _____.

1. char
2. int
3. void
4. double

_____ will be used for enclosing function statements into a block.

1. " "
2. ()
3. []
4. {}

What is the output of the following code if the 2nd case is true switch (var) { case 'a':cout<<"apple"<<<"banana"<<<"mango"<<<"any="" fruit"<<="" p="" style="box-sizing: border-box;">A

1. banana
2. banana
3. banana
4. None of the given

mango

any fruit

When the break statement is encountered in a loop's body, it transfers the control _____ from the current loop.

1. Inside 2. Outside

4. To

To break statement continue statement

What is the output of the following code, if the first case is true switch (var) { case 'a':cout<<"apple"<<endl; case 'b':cout<<"banana"<<endl; case 'm':cout<<"mango"<<endl; default: cout<<"any fruit"<<endl; }

1. apple

2. apple

any fruit

3. apple

banana

mango

any fruit

4. none of above

What will be the output of following code segment? for (int i = 2; i<10; i++){ if (i == 5) continue; cout << i << "," ; }

1. 2,3,7,8,9

2. 2,3,4,6,7,8, 9

3. 2,3,4

4. 4,6,7,8,9

_____statement is used to terminate the processing of a particular case and exit from switch structure.

1. if
2. goto
3. break
4. continue

What will be the result of the expression k = ++m; if initially k = 0 and m = 5?

1. 0
2. 5
3. 6
4. 4

What will be the result of the expression j = i++; if initially j = 0 and i = 5?

1. 0
2. 5
3. 6
4. 4

What will be the result of the expression k = ++m; if initially k = 0 and m = 4?

1. 0
2. 5
3. 6
4. 4

What will be the result of the expression k = ++m; if initially k = 0 and m = 5?

1. 0
2. 5
3. 6
4. 4

How many times the following do-while loop will execute? int k = 10; do { cout << "Statements" << endl; k -= 2; } while(k>0);

1. 4
2. 5
3. 6
4. 7

Which of the following loops checks the test condition at the end of the loop?

1. While
2. Do-While
3. For
4. Nested Loop

The operators ++ and -- are used to increment or decrement the value of a variable by _____.

1. 1
2. 2
3. 3
4. 4

How many times the following loop will execute? int j = 3; while(j > 0) { cout << "Statements" << endl; j -= 2; }

1. 0
2. 1

3. 2

4. 3

A _____ structure specifies that an action is to be repeated while some condition remains true.

1. Control
2. Logical
3. Repetition
4. Relational

!(x > 3) means in C++ that

- x is greater than 3
- x is less than or equal to 3
- x is less than 3
- x is equal to 3

When the logical operator && combines two expressions then the result will be true only when the both expressions are _____

1. Logical
2. Arithmetic
3. true
4. false

< and > both are _____ operators.

1. Arithmetic
2. Relational
3. Logical
4. Mathematical

What will be the value of variable **“**input**”** if the initial value of input is 67? if(input >= 50) input = input + 1; if(input <= 75) input = input + 2; else input = input - 1;

1. 68
2. 69
3. 70
4. 66

!(x < 3) means in C++ that

1. x is less than 3
2. x is greater

tha
n

or

equa
l

to
3

4.x

is

3.x is greater than 3

equal

to 3

!= operator is used to check whether the operand on the left-hand-side is _____ to the operand on the right-hand-side.

1. Less than or equal
2. Greater than or equal
3. Not equal
4. Approximately equal to

When the if statement consists more than one statement then enclosing these statement in curly braces is,

1. Not required
2. Good programming
3. Relevant
4. Mus
t

The most suitable data type for number 325.25 is _____.

1. char
2. int
3. short
4. float

What will be the result of arithmetic expression 6+48/4*3?

1. 10
2. 40.5
3. 42
4. 41

Which of the following will be the most appropriate data type to store the value 63.547?

1. Integer
2. Character
3. Short
4. Float

In the given expression which operator will be evaluated first? 10 + (6 / 2) - 2 * 3?

1. +
2. -
3. /
4. *

What will be the value of the variable output in the given piece of code? double output = 0; output =(2+2)*4+2/(4-2); ^

1. 15
2. 17
3. 12
4. 11

_____ operators are the ones that require two operands on both sides of the operator.

1. Double
2. Tow sided
3. Binary
4. None of the given

It is the job of _____ to transfer the executable code from hard disk to main memory.

1. Interpreter
2. Debugger
3. Linker
4. Loader

In computer systems there are mainly _____ type of softwares.

1. 1
2. 2
3. 3
4. 4

_____ will explain the function of a program.

1. Comments
2. Debugger
3. Compiler
4. Linker

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one

All A template function must have at least ---------- generic data type

► Zero

► One (Page 499)
► Two
► Three

Question No: 2 (Marks: 1) – Please choose one

Which of the following statement is best regarding declaration of friend function?

► Friend function must be declared after public keyword

► ► Friend function must be declared after private keyword.
Friend function must be declared at the top within class definition.
It can be declared anywhere in class as these are not affected by the public and private keywords. (Page 346)

Question No: 3 (Marks: 1) - Please choose one

Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

► Class-name operator +() ;

► Class-name operator +(int) ;

► Class-name operator ++() ; (Page 389)

► Class-name operator ++(int) ;

Question No: 4 (Marks: 1) - Please choose one

Class is a user defined_____.

► data type (Page 317)

► memory referee
► value
► none of the given options.

Question No: 5 (Marks: 1) - Please choose one

How many bytes will the pointer intPtr of type int move in the following statement? intPtr += 3 ;

► 3 bytes

► 6 bytes

► **12 bytes**

► 24 bytes

Question No: 6 (Marks: 1) - Please choose one

Which of the following is the correct C++ syntax to allocate space dynamically for an array of 10 int?

► new int(10) ;

► **new int[10] ;**

► int new(10) ;

► int new[10];

Question No: 7 (Marks: 1) - Please choose one A

Pointer is a special variable that contain

► Data values

► **Memory Address (Page 267)**

► Both data and values

► None of the given option

Question No: 8 (Marks: 1) - Please choose one

Reference Value Type Data The code is written to _____ the program.

► **implement**

► design

► analysis

► none of the given options

FINALTERM EXAMINATION

CS201 - Introduction to programming

Final Term Spring 2010

Operator overloading can be performed through_____.

► Classes
► **Function (Page 371)**
► Operators
► Reference

Question No: 2 (Marks: 1) - Please choose one

When a value is referred by a normal variable then it is known as,

► **Direct Reference (page 143)**
►Indirect Reference.

► Partial Reference

► Proper Reference

When a value is referred by a normal variable is known as direct reference

Question No: 3 (Marks: 1) - Please choose one

Which of the following function is used to increase the size of already allocated memory chunk?

► malloc

► calloc

► **realloc (Page 285)**

► free

Question No: 4 (Marks: 1) - Please choose one
Which of the following is NOT a preprocessor directive?

► #error

► #define

► #line

► **#ndefine (Page 272)**

Question No: 5 (Marks: 1) – Please choose one

The stream objects **cin** and **cout** are included in which header file?

► **iostream.h (Page 15)**

► fstream.h

► istream.h

► ostream.h

Question No: 6 (Marks: 1) – Please choose one

Overloaded delete operator function takes the same parameter as an argument returned by new operator function.

► True (Page 414)

► False

The same pointer that is returned by the new operator, is passed as an argument to the delete operator. These rules apply to both, if operators (new and delete) are overloaded as member or non-member operators (as global operators).

Question No: 7 (Marks: 1) – Please choose one

When an array of object is created dynamically then there is no way to provide parameterized constructors for array of objects.

► True (Page 414)

► False

Question No: 8 (Marks: 1) – Please choose one

C is widely known as development language of _____ operating system.

- ► Linux
- ► Windows
- ► **Unix (Page 12)**
- ► Mac OS

In the start C became widely known as the development language of the UNIX operating system, and the UNIX operating system was written by using this C language. The C language is so powerful that the compiler of C and other various operating systems are written in C.

Question No: 9 (Marks: 1) - Please choose one
Computer can understand only machine language code.

True

- ► False

Question No: 10 (Marks: 1) - Please choose one

We can not define a function as a friend of a Template class.

- ► True

False (Page 151)

Class templates can have friends. A class or class template, function, or function template can be a friend to a template class. Friends can also be specializations of a class template or function template, but not partial specializations.

Question No: 11 (Marks: 1) – Please choose one

What will be the value of 'a' and 'b' after executing the following statements?

A=3;

b = a++;

► 3, 4

► 4, 4
► 3, 3
► **4, 3**

Question No: 12 (Marks: 1) – Please choose one

Consider the following code segment. What will be the output of following code?

```
Int addValue (int *a){
int b = (*a) + 2;
return b ;
}
main () {
int x =6 ;
cout << x << “,” ;
cout << addValue(&x) << “,” ;
cout << x ;
}
```

► **6,8,6**

► 6,6,8
► 6,8,8
► 6,6,6

Question No: 13 (Marks: 1) – Please choose one

_____ is used to trace the logic of the program and correct the logical errors.

► Compiler
► Editor
► Linker
► **Debugger (Page 13)**

Question No: 14 (Marks: 1) - Please choose one

new and delete are _____ whereas malloc and free are _____.

► Functions, operators

► Classes, operators
► **Operators, functions (Page 342-285)**

► Operators, classes

Hence, we can call new and delete operators, P# 342

we have allocated a memory space for our use by malloc function. P# 285

Question No: 15 (Marks: 1) - Please choose one

Like member functions, _____ can also access the private data members of a class.

► Non-member functions

► **Friend functions (Page 346)**

► Any function outside class
► None of the given options

Question No: 16 (Marks: 1) – Please choose one

Which situation would require the use of a non-member overloaded operator?

► The overloaded operator is an Assignment operator.

The left most operand is an object of a class.(Page 375)

The left operand is built-in data type.
The operator returns a reference.

When an operator function is implemented as a non-member function, the left-most operand may be an object of the operator's class, an object of a different class, or a built-in type

Question No: 17 (Marks: 1) - Please choose one

The stream insertion and stream extraction operators are already overloaded for _____.

► User-defined data types
► **Built-in data types http://www.sstutor.com/cpp/stream1.htm**

► User-defined and built-in data types
► None of the given options



Question No: 18 (Marks: 1) - Please choose one

If we define an identifier with the statement **#define PI 3.1415926** then during the execution of the program the value of PI _____.

- ► can not be replaced
- ► None of the given options
- ► **Remain constant. (Page 271)**
- ► can be changed by some operation

Question No: 19 (Marks: 1) - Please choose one

Assignment operator is ----------associative.

- ► **right**
- ► left
- ► binary
- ► unary

Question No: 20 (Marks: 1) - Please choose one

When ever dynamic memory allocation is made in C/C++, it is freed_____.

- ► **Explicitly (Page 527)**
- ► Implicitly
- ► Both explicitly and implicitly
- ► None of the given options

Question No: 21 (Marks: 1) – Please choose one

The appropriate data type to store the number of rows and colums of the matrix is_____.

- ► float

► **int (Not sure)**

► char
► none of the given options.

Question No: 22 (Marks: 1) – Please choose one

Which of the following function do NOT initialize the chunk of memory to all zero?

► calloc() function

► Both malloc() and calloc()
► None of the above
► **malloc() function** (Page 283)

The **malloc** function differs from **calloc** in the way that the space allocated by **malloc** is not initialized and contains any values initially.

Question No: 23 (Marks: 1) – Please choose one

The function free() returns back the allocated memory got thorough calloc and

malloc to _____ .

► stack

► **heap**

► stack and heap
► None of the given options

Question No: 24 (Marks: 1) – Please choose one
width() is member function of _____

► cin object

► cout object
► **Both cin and cout object (Page 440)**

► None of the given option

Question No: 25 (Marks: 1) - Please choose one

Templates are not type safe.

► true

► **false (Page 518)**

Templates are type-safe. This is because the types that templates act upon are known at compile time, so the compiler can perform type checking before errors occur.

Question No: 26 (Marks: 1) - Please choose one

A Matrix can be composed of ints, floats or doubles as their elements. Best way is to handle this ,

_____

► Write a separate class to handle each

► **Use templates (Page 527)**

- ► Use strings to store all types
- ► None of the given options

FINALTERM EXAMINATION

Spring 2010

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one In if structure the block of statements is executed only,

- ► When the condition is false
- ► When it contain arithmetic operators
- ► When it contain logical operators
- ► **When the condition is true (Page 38)**

Question No: 2 (Marks: 1) - Please choose one

Header file: **fstream.h** includes the definition of the stream classes _____.

► ifstream, fstream, cout

► **ifstream, fstream, ofstream (Page 199)**

► fstream, cin, cout
► None of the above

Question No: 3 (Marks: 1) - Please choose one

To access the data members of structure _____ is used.

► **dot operator (.) (Page 231)**

► * operator
► U operator
► None of given.

Question No: 4 (Marks: 1) - Please choose one
eof( ), bad( ), good( ), clear( ) all are manipulators.

► **True (Page 433)**

► False

Question No: 5 (Marks: 1) - Please choose one

Which kind of functions can access private member variables of a class?

► **Friend functions of the class (Page 374)**

► Private member functions of the class
► Public member functions of the class
► Friend, private and public functions

Question No: 6 (Marks: 1) - Please choose one The
return type of operator function must always be void.

► True

► **False (Page 79)**

Question No: 7 (Marks: 1) - Please choose one

Friend function of a class is _____ .

► Member function

► **Non-member function (Page 348)**

► Private function

► Public function

Question No: 8 (Marks: 1) - Please choose one

Function implementation of friend function must be defined outside the class.

► True

► **False (Page 346)**

Question No: 9 (Marks: 1) - Please choose one



The normal source of **cin** object is,

- File
- Disk
- **Keyboard (Page 424)**
- RAM

Question No: 10 (Marks: 1) - Please choose one

Which of the following is correct way to initialize a variable x of int type with value 10?

- int x ; x = 10;
- **int x = 10;**
- int x, x = 10;
- x = 10;

Question No: 11 (Marks: 1) - Please choose one

Consider the following code segment. What will be the output of the following program?

```
int func(int) ;

int num = 10 ;


int main(){

int num ;

num = 5 ;

cout << num ;

cout << func(num) ;

}

int func(int x){

return num ;
```

}

- ► 5, 5
- ► 10, 5
- ► **5, 10**
- ► 10, 10

Question No: 12 (Marks: 1) - Please choose one

With template function, the compiler automatically detects the passed data and generates a new copy of function using passed data.

- ► **True Page 510**
- ► False

Question No: 13 (Marks: 1) - Please choose one

What will be the correct syntax to declare two-dimensional array of float data type?

- ► float arr{2}{2} ;
- ► **float arr[2][2] ;**

► float arr[2,2] ;

► float[2][2] arr ;

Question No: 14 (Marks: 1) - Please choose one

The first parameter of operator function for << operator,

► Must be passed by value

► **Must be passed by reference (Page 446)**

► Can be passed by value or reference

► Must be object of class

Question No: 15 (Marks: 1) - Please choose one

Heap is constantly changing in size.

► **True (Page 280)**

► False

Question No: 16 (Marks: 1) - Please choose one

While calling function, the arguments are assigned to the parameters from _____.

► **left to right. (Page 295)**

► right to left

► no specific order is followed

► none of the given options.

Question No: 17 (Marks: 1) - Please choose one

Classes defined inside other classes are called _____ classes

► looped

► **nested (Page 492)**

► overloaded

► none of the given options.

Question No: 18 (Marks: 1) - Please choose one

If we define an identifier with the statement **#define PI 3.1415926** then during the execution of the program the value of PI _____.

► can not be replaced

► None of the given options

► **Remain constant. (Page 271)**

► can be changed by some operation

Question No: 19 (Marks: 1) - Please choose one
Which value is returned by the destructor of a class?

► A pointer to the class.

► An object of the class.

► A status code determining whether the class was destructed correctly

► **Destructors do not return a value. (page 323)**

Question No: 20 (Marks: 1) - Please choose one

Every class contains _____.

► Constructor

► Destructor

► **Both a constructor and a destructor (Lecture 27)**

► None of the given options

Question No: 21 (Marks: 1) - Please choose one A template function must have

► **One or more than one arguments**

► Only one argument

► Zero arguments

► None of the given options

http://en.wikipedia.org/wiki/Template_%28programming%29

Question No: 22 (Marks: 1) - Please choose one

Structured Query Language is used for _____

► **Databases Management (page 563)**

► Networks

► Writing Operating System

► none of the given options

Question No: 23 (Marks: 1) - Please choose one

When a call to a user-defined function finishes, the variable defined inside the function is still in existence.

► True

► **False (Page 460)**

Question No: 24 (Marks: 1) - Please choose one

The precedence of an operator can be changed through operator overloading.

► True

► **False (Page 372)**

Question No: 25 (Marks: 1) - Please choose one

A Matrix can be composed of ints, floats or doubles as their elements. Best way is to handle this ,

_____

► Write a separate class to handle each

► **Use templates (Page 527)**

► Use strings to store all types

► None of the given options

Question No: 26 (Marks: 1) - Please choose one

"**delete**" operator is used to return memory to free store, which is allocated by the "**new**" operator.

► **True (page 332)**

► False

FINALTERM EXAMINATION

Spring 2010

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one
Pointer is a variable which store,

► Data

► **Memory Address (Page 267)**

► Data Type
► Values

Question No: 2 (Marks: 1) - Please choose one

All preprocessor directives are started with the symbol_____.

► *

► +
► @
► **# (Page 269)**

Question No: 3 Marks: 1) - Please choose one

Within the statement **obj1=obj2;** ***obj1*** will call the assignment operator function and ***obj2*** will be passed as an argument to function.

► True

► False

Question No: 4 (Marks: 1) - Please choose one

What is the sequence of event(s) when deallocating memory using delete operator?

► Only block of memory is deallocated for objects

► Only destructor is called for objects

► Memory is deallocated first before calling destructor

► **Destructor is called first before deallocating memory (Page 414)**

Question No: 5 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are

overloading these operators.

► **True (page 453)**

► False

Question No: 6 (Marks: 1) - Please choose one

To include code from the library in the program, such as iostream, a directive would be called up using this command.

► #include “iostream.h”

► include <iostream.h>

► include <iostream.h>

► **#include <iostream.h> (sure)**

Question No: 7 (Marks: 1) - Please choose one

The number 544.53 must be stored in _____ data type.

► int

► short

► **float (Sure)**

► char

Question No: 8 (Marks: 1) - Please choose one

A template function can have different type of arguments.

► **True (Page 503)**

► False

Question No: 9 (Marks: 1) - Please choose one

For which values of the integer _value will the following code becomes an infinite loop?

```
int number=1;

while (true) {
        cout << number;
        if (number == 3) break;
        number += integer_value; }
```

- any number other than 1 or 2
- **only 0**
- only 1
- only 2

Question No: 10 (Marks: 1) - Please choose one
Template class cannot have static variables.

- True
- False

Question No: 11 (Marks: 1) - Please choose one

Which of the following is used with bit manipulation?

- ► Signed integer
- ► **Un-signed integer (Page 245)**
- ► Signed double
- ► Un-signed double

Question No: 12 (Marks: 1) - Please choose one

Structure is a collection of _____ under a single name.

- ► Only Functions
- ► **Only Variables (Page 229)**
- ► Both Functions and Variables
- ► None of the given options

Question No: 13 (Marks: 1) - Please choose one

Which of the following is the correct C++ syntax to allocate space dynamically for an array of 10 int?

- ► new int(10) ;
- ► **new int[10] ;**
- ► int new(10) ;
- ► int new[10];

Question No: 14 (Marks: 1) - Please choose one

Unary operator implemented as member function takes ____ arguments whereas non-member function takes _____ arguments.

- ► One, zero
- ► **Zero, one**

► One, two
► Two, one

Question No: 15 (Marks: 1) - Please choose one

The first parameter of overloaded stream insertion operator is _____ where second parameter is _____

► input stream, object of class

► object of class, output stream
► output stream, object of class
► object of class, input stream

Question No: 16 (Marks: 1) - Please choose one

We can also do conditional compilation with preprocessor directives.

► **True (Page 272)**
► False

Question No: 17 (Marks: 1) - Please choose one

If a symbolic constant has been defined, it will be an error to define it again.

► **True (Page 273)**

► False

Question No: 18 (Marks: 1) - Please choose one

While calling function, the arguments are assigned to the parameters from _____.

► **left to right. (Page 295)**

► right to left

► no specific order is followed

► none of the given options.

Question No: 19 (Marks: 1) - Please choose one

Classes defined inside other classes are called _____ classes

► looped

► **nested (Page 492)**

► overloaded

► none of the given options.

Question No: 20 (Marks: 1) - Please choose one

If we define an identifier with the statement **#define PI 3.1415926** then during the execution of the program the value of PI _____.

cannot be replaced

None of the given options

► **Remain constant. (Page 271)**

can be changed by some operation

Question No: 21 (Marks: 1) - Please choose one

Assignment operator is ----------associative.

► **right**

► left

► binary

► unary

http://msdn.microsoft.com/en-us/library/ms173145.aspx

Question No: 22 (Marks: 1) - Please choose one

If **text** is a pointer of class **String** then what is meant by the following statement?

text = new String [5];

► Creates an array of 5 string objects statically

► **creates an array of 5 string objects dynamically**



► Creates an array of pointers to string

► Creates a string Object

Question No: 23 (Marks: 1) - Please choose one

The return type of the operator function for << operator is _____.

► class for which we overload operator

► reference of ostream class (ostream&)
► reference of istream class (istream&)
► void

Question No: 24 (Marks: 1) - Please choose one

The code is written to _____ the program.

► implement (Page 520)

► design
► analysis
► none of the given options.

Question No: 25 (Marks: 1) - Please choose one

Memory allocated at run time is a system resource and it is the responsibility of _____ to de-allocate the memory.

System
► Programmer (Page 331)

► User of program
► None of given options

Question No: 26 (Marks: 1) - Please choose one
Templates are not type safe.

► True

► False (Page 518)

FINALTERM EXAMINATION

Spring 2010

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one
*.doc is _____ by type. .

- ► Sequential File
- ► Random Access File
- ► Data File
- ► Record File

Question No: 2 (Marks: 1) - Please choose one
Which of the following is NOT a preprocessor directive?

- ► #error

► #define

► #line

► **#ndefine (Page 2727)**

Question No: 3 (Marks: 1) - Please choose one The return type of operator function must always be void.

► True

► **False (Page 79)**

Question No: 4 (Marks: 1) - Please choose one
What does **(*this)** represents?

► The current function of the class

► The current pointer of the class

► **The current object of the class (Page 390)**

► A value of the data member

Question No: 5 (Marks: 1) - Please choose one
The statement **cin.get ();** is used to,

► Read a string from keyboard

► **Read a character from keyboard (Page 426)**

► Read a string from file

► Read a character from file

Question No: 6 (Marks: 1) - Please choose one

When we do dynamic memory allocation in the constructor of a class, then it is necessary to provide a destructor.

► **True (Page 479)**

► False

Question No: 7 (Marks: 1) - Please choose one

Overloaded new operator function takes parameter of type *size_t* and returns

- ► void (nothing)
- ► **void pointer (Page 415)**
- ► object pointer
- ► int pointer

Question No: 8 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are overloading these operators.

- ► **True (Page 453)**
- ► False

Question No: 9 (Marks: 1) - Please choose one

C++ is a case-sensitive language

► **True (Page 68)**

► False

Question No: 10 (Marks: 1) - Please choose one

To include code from the library in the program, such as iostream, a directive would be called up using this command.

► #include “iostream.h”

► include <iostream.h>

► include <iostream.h>

► **#include <iostream.h> (Sure)**

Question No: 11 (Marks: 1) - Please choose one

A template function must have only generic data types.

► True

► **False (Page 501)**

Question No: 12 (Marks: 1) - Please choose one

Template class can not have static variables.

► True

► **False**

Question No: 13 (Marks: 1) - Please choose one

What will be the correct syntax to assign an array named ***arr*** of 5 elements to a pointer ***ptr***?

*ptr = arr ;

ptr = arr ;

*ptr = arr[5] ;

► ptr = arr[5] ;

Question No: 14 (Marks: 1) - Please choose one

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

► ptr[3]

► (ptr+3)

► *(ptr+3)

► **Both 1and 3**

Question No: 15 (Marks: 1) - Please choose one

If most significant bit of un-signed number is 1 then it represents a positive number.

► True

► **False (Page 251)**

Question No: 16 (Marks: 1) - Please choose one

If there is a symbol (& sign) used with the variable name followed by data type then it refers to _____ and

if & is being used with variable name then it refers to _____.

- ► Address of variable, reference variable
- ► Reference variable, value of variable
- ► **Reference variable, address of variable (Page 367)**
- ► Address of variable, value of variable

Question No: 17 (Marks: 1) - Please choose one

We can also do conditional compilation with preprocessor directives.

- ► **True (Page 272)**
- ► False

Question No: 18 (Marks: 1) - Please choose one

The default value of a parameter can be provided inside the _____

- ► function prototype
- ► function definition
- ► **both function prototype or function definition (Page 294)**
- ► none of the given options.

Question No: 19 (Marks: 1) - Please choose one

Classes defined inside other classes are called _____ classes

- ► looped
- ► **nested (Page 492)**
- ► overloaded
- ► none of the given options.

Question No: 20 (Marks: 1) - Please choose one
What purpose do classes serve?

- ► Data encapsulation
- ► Providing a convenient way of modeling real-world objects
- ► Simplifying code reuse
- ► **All of the given options**

Question No: 21 (Marks: 1) - Please choose one

Every class contains _____.

- ► Constructor
- ► Destructor
- ► **Both a constructor and a destructor (Lecture 27)**
- ► None of the given options

Question No: 22 (Marks: 1) - Please choose one

new operator is used to allocate memory from the free store during

Compile Time

Run Time

Link Time

► None of the given options

Question No: 23 (Marks: 1) - Please choose one When an object of a class is defined inside another class then,

► Destructor of enclosing class will be called first

► Destructor of inner object will be called first

► Constructor and Destructor will be called simultaneously

► None of the given options

Question No: 24 (Marks: 1) - Please choose one It is possible to define a class within another class.

► True (Page 492)

► False

Question No: 25 (Marks: 1) - Please choose one

New and Delete are also used with _____ and data types as well.

► Class, Objects (Page 342)

► Structures, Pointers

► Both Class and structures

► None of above

Question No: 26 (Marks: 1) - Please choose one

With New keyword, data types and class members are initialized with meaningful values instead of garbage.

► True (Page 334)

► False

FINALTERM EXAMINATION

Spring 2010

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one If it is required to copy an array to another array then,

- **Both arrays must be of the same size and data type (Page 105)**
- Both arrays may be of different size
- Both arrays may be of different data type
- Both arrays may be of different size and type

Question No: 2 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

► **True**

► False

http://mathbits.com/MathBits/CompSci/Structures/Functions.htm

Question No: 3 (Marks: 1) - Please choose one

eof( ), bad( ), good( ), clear( ) all are manipulators.

► **True (Page 433)**

► False

Question No: 4 (Marks: 1) - Please choose one

Overloaded new operator function takes parameter of type *size_t* and returns

► void (nothing)

► **void pointer (Page 415)**

► object pointer

► int pointer

Question No: 5 (Marks: 1) - Please choose one

When new operator is overloaded at global level then corresponding built-in new operator will not be visible to whole of the program.

► **True (Page 413)**

► False

Question No: 6 (Marks: 1) - Please choose one

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?

► parentheses ( )

► **braces { } (Page 37)**

► brackets [ ]
► arrows < >

Question No: 7 (Marks: 1) - Please choose one

The return type of a function that do not return any value must be _____

► float

► int
► **void (Page 79)**

► double

Question No: 8 (Marks: 1) - Please choose one

UNIX has been developed in _____ language.

► JAVA

► B
► **C (Page 12)**
► FORTRAN

Question No: 9 (Marks: 1) - Please choose one

Like member functions, _____ can also access the private data members of a class.

► Non-member functions

► **Friend functions (Page 346)**

► Any function outside class
► None of the given options

Question No: 10 (Marks: 1) - Please choose one

Which of the following statement is best regarding declaration of friend function?

► Friend function must be declared after public keyword.

► Friend function must be declared after private keyword.
► Friend function must be declared at the top within class definition.
► **It can be declared anywhere in class as these are not affected by the public and private keywords. (Page 346)**

Question No: 11 (Marks: 1) - Please choose one

The operator function overloaded for an Assignment operator (=) must be

► Non-member function of class

► **Member function of class (Page 372)**

► Friend function of class
► None of the given options

Question No: 12 (Marks: 1) - Please choose one

The **endl** and **flush** are _____

- ► Functions
- ► Operators
- ► **Manipulators (Page 434)**
- ► Objects

Question No: 13 (Marks: 1) - Please choose one

If a symbolic constant has been defined, it will be an error to define it again.

- ► **True (Page 273) 15**
- ► False

Question No: 14 (Marks: 1) - Please choose one

The operator used for casting, in C, is standard _____ operator.

► none of the given options.

► **cast (Page 281)**

► cost
► const

Question No: 15 (Marks: 1) - Please choose one
Constructors can not be overloaded like ordinary functions.

► True

► **False (Page 323)**

Question No: 16 (Marks: 1) - Please choose one

Which of the following function call is correct for the function prototype?

defaultParameters (int a, int b = 7, char z = '*');

► **defaultParameters (5);**
► defaultParameters (5, '8');
► defaultParameters (6, '#');
► defaultParameters (0, 0, '*', 0);

Question No: 17 (Marks: 1) - Please choose one

When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

► Zero

► One
► **Two (Page 371)**

► N arguments

Question No: 18 (Marks: 1) - Please choose one

We can not define a variable of user-defined data type in the class.

► True

► **False (Page 320)**

Question No: 19 (Marks: 1) - Please choose one

When an object of a class is defined inside an other class then,

► **Constructor of enclosing class will be called first (Page 464)**

► Constructor of inner object will be called first
► Constructor and Destructor will be called simultaneously
► None of the given options

Question No: 20 (Marks: 1) - Please choose one

The appropriate data type to store the number of rows and colums of the matrix is_____.

► float

► **int (Not sure)**

► char
► none of the given options.

Question No: 21 (Marks: 1) - Please choose one

Class is a user defined_____.

► **data type (page 317)**

► memory referee
► value
► none of the given options.

Question No: 22 (Marks: 1) - Please choose one A pointer variable can be,

► Decremented

► Incremented
► Multiplied
► **Both Iecremented and Decremented (Page 366)**

Question No: 23 (Marks: 1) - Please choose one

NULL value has been defined in _____ and _____ header files.

► strings.h and iostream.h

► ctype.h and conio.c
► conio.c and conio.h
► **stdlib.h and stddef.h (Page 281)**

Question No: 24 (Marks: 1) - Please choose one

A Matrix can be composed of ints, floats or doubles as their elements. Best way is to handle this ,

_____

► Write a separate class to handle each
► **Use templates (Page 527)**
► Use strings to store all types
► None of the given options

Question No: 25 (Marks: 1) - Please choose one
"setprecision" manipulator will set

► **The number of digits after the decimal point (Page 440)**

► The number of digits before the decimal point
► The number of digits in a number
► None of the given options

Question No: 26 (Marks: 1) - Please choose one

Which of the following option will be true, if we overload "-=" operator?

► only - operator needs to be overloaded

► Minus (-) and = operators need to be overloaded
► **the -= operator need to be overloaded explicitly**

► the - and = operators need to be overloaded implicitly

Fall 2009

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one

In C/C++ if we define an array of size eight (8) i.e. int Arr [8]; then the last element of this array will be stored at,

► Arr[0]

► Arr[8]
► **Arr[7]**

► Arr[-1]

Question No: 2 (Marks: 1) - Please choose one

When an array is passed to a function then default way of passing this array is,

► By data

► **By reference (Page 154)**

► By value
► By data type

Question No: 3 (Marks: 1) - Please choose one

Array is a data structure which store

► Memory addresses

► Variables
► **Data Type (Page 100)**

► Data

Question No: 4 (Marks: 1) - Please choose one

We can also create an array of user define data type.

► **True (Page 408)**

► False

Question No: 5 (Marks: 1) - Please choose one

When we define an array of objects then,

► Destructor will call once for whole array

► Destructor will call for each object of the array

► Destructor will never call
► Depends on the size of array

Question No: 6 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

► Only block of memory is allocated for objects

► Only constructor is called for objects

► Memory is allocated first before calling constructor (Page 414)

► Constructor is called first before allocating memory

Question No: 7 (Marks: 1) - Please choose one

We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally.

► True

► False

Question No: 8 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class
For which we are overloading these operators.

► True (Page 453)

► False

Question No: 9 (Marks: 1) - Please choose one

Which of the following is correct way to initialize a variable x of int type with
value 10?

► int x ; x = 10 ;

► int x = 10 ; (sure)

► int x, x = 10;
► x = 10 ;

Question No: 10 (Marks: 1) - Please choose one

Default mechanism of function calling in case of array is _____ and in case of variable is ___.

► Call by value, call by reference

► Call by referene, call by reference
► Call by reference, call by value (Page 119)

► Call by value, call by value

Question No: 11 (Marks: 1) - Please choose one

What does STL stand for?

► Source template library

► Standard template library (Page 519)

► Stream template library
► Standard temporary library

Question No: 12 (Marks: 1) - Please choose one

Skill(s) that is/are needed by programmer's _____.

► Paying attention to detail

► Think about the reusability
► Think about user interface
► All of the given options (Page 4 & 5)

Question No: 13 (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

► int

► double

► float
► **char (Page 113)**

Question No: 14 (Marks: 1) - Please choose one

new and delete are _____ whereas malloc and free are _____.

► Functions, operators

► Classes, operators
► **Operators, functions (Page 342-285)**

► Operators, classes

Question No: 15 (Marks: 1) - Please choose one

Friend functions are _____ of a class.

► Member functions

► Public member functions
► Private member functions
► **Non-member functions (Page 346)**

Question No: 16 (Marks: 1) - Please choose one

The prototype of friend functions must be written ____ the class and its

definition must be written ____

► inside, inside the class

► **inside, outside the class (Page 346)**

► **outside, inside the class**
► outside, outside the class

Question No: 17 (Marks: 1) - Please choose one

If overloaded plus operator is implemented as non-member function then which of the following statement will be true for the statement given below?

obj3 = obj1 + obj2 ;

► obj2 will be passed as an argument to + operator whereas obj2 will

drive the + operator

► obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator

► Both objects (obj1, obj2) will be passed as arguments to the + operator (not sure)

► Any of the objects (obj1, obj2) can drive the + operator

Question No: 18 (Marks: 1) - Please choose one

Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

► Class-name operator +() ;

► Class-name operator +(int) ;

► Class-name operator ++() ; (PAGE 389)

► Class-name operator ++(int) ;

Question No: 19 (Marks: 1) - Please choose one

For cin, the source is normally a _____ and destination can be _____.

► File, native data type

► Disk, user-define type

► Keyboard, variable (Page 424)

For *cin*, the source is normally keyboard and the destination can be an ordinary variable

► File, user-define type

Question No: 20 (Marks: 1) - Please choose one

We can also do conditional compilation with preprocessor directives.

► True (Page 272)

► False

Question No: 21 (Marks: 1) - Please choose one

The programs, in which we allocate static memory, run essentially on _____

► Heap

► System Cache

► None of the given options

► **Stack (Page 280)**

The programs, in which we allocate static memory, run essentially on stack.

Question No: 22 (Marks: 1) - Please choose one

The default value of a parameter can be provided inside the _____

► function prototype

► **function definition (Page 249)**

► both function prototype or function definition

► none of the given options.

The default value of a parameter is provided inside the function prototype or function definition.

Question No: 23 (Marks: 1) - Please choose one

While calling function, the arguments are assigned to the parameters from _____.

► **left to right. (page 295)**

► right to left
► **no specific order is followed**

► none of the given options.

Question No: 24 (Marks: 1) - Please choose one

When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

► Zero

► One

► **Two (Page 371)**

► **N arguments**

Question No: 25 (Marks: 1) - Please choose one

With user-defined data type variables (Objects), self assignment can produce

_____.

► Syntax error

► **Logical error**

► Link error
► **Non of the given options (not sure)**

Question No: 26 (Marks: 1) - Please choose one

Assignment operator is used to initialize a newly declared object from existing object.

► **True (Page 479)**

► False

Question No: 27 (Marks: 1) - Please choose one

When an object of a class is defined inside an other class then,

► **Constructor of enclosing class will be called first (Page 496)**

► Constructor of inner object will be called first
► Constructor and Destructor will be called simultaneously

► None of the given options

Question No: 28 (Marks: 1) - Please choose one

In the member initializer list, the data members are initialized,

► From left to right

► From right to left
► **In the order in which they are defined within class**

► None of the given options

Question No: 29 (Marks: 1) - Please choose one

new operator allocates memory from free store and return _____.

► **A pointer**

► A reference
► An integer

► A float

Question No: 30 (Marks: 1) - Please choose one

"new" and "delete" keywords are _____ in C++ language.

► Built-in- Function

► Operators

► None of the given options

Spring 2010

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one

&& is ---------- operator.

► An arithmetic

► Relational

► Unary

Question No: 2 (Marks: 1) - Please choose one

Which of the following function(s) is/are included in **ctype.h** header file?

► isdigit(int c)

► isxdigit(int c)
► tolower(int c)
► All of the above (Page 188)

Question No: 3 (Marks: 1) - Please choose one

Disks are _____ devices having access time of _____ milliseconds.

► Electro-physical, 6

► Electro-Mechanical, 4
► Electro-physical, 5
► Electro-Mechanical, 7 (Page 427)

http://www.tns.com/taocs_dp.asp

Question No: 4 (Marks: 1) - Please choose one

All preprocessor directives are started with the symbol_____.

► *

► ++

► @
► # (Page 269)

Question No: 5 (Marks: 1) - Please choose one

When we use manipulators in our program then which header file should be included?

► iostream.h

► stdlib.h
► stdio.h
► iomanip.h (Page 433)

Question No: 6 (Marks: 1) - Please choose one

setprecision is a parameter less manipulator.

► True

► False (Page 439)

Question No: 7 (Marks: 1) - Please choose one
Which of the following is NOT a preprocessor directive?

► #error

► #define
► #line
► #ndefine (Page 272)

Question No: 8 (Marks: 1) - Please choose one

We can do arithmetic with references like pointers.

► True

► False (Page 369)

Question No: 9 (Marks: 1) - Please choose one

What does **(*this)** represents?

► The current function of the class

► The current pointer of the class

► The current object of the class (Page 390)

► A value of the data member

Question No: 10 (Marks: 1) - Please choose one

Friend function of a class is _____ .

► Member function

► Non-member function (Page 348)

► Private function

► Public function

Question No: 11 (Marks: 1) - Please choose one

A function can declare itself a friend of a class.

► True

► False (Page 346)

Question No: 12 (Marks: 1) - Please choose one

Overloaded delete operator function takes the same parameter as an argument returned by new operator function.

► True (Page 414)

► False

Question No: 13 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are overloading these operators.

► True (Page 453)

► False
The second parameter to *operator* << is an object of the class that we are overloading the operator for. Similar is the case for *operator* >>

Question No: 14 (Marks: 1) - Please choose one

A template function must have at least ---------- generic data type

► Zero

► Two

► Three

Question No: 15 (Marks: 1) - Please choose one

A template function must have only generic data types.

► True

► False (Page 501)

Question No: 16 (Marks: 1) - Please choose one

We can not make a member function of a class as template function.

► True

► False (Page 506)

Question No: 17 (Marks: 1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?

► new line

► tab

► null (Page 113)

► carriage return

Question No: 18 (Marks: 1) - Please choose one

is used for _____.

► calculation

► reading

► assigning value to variables (Page 372)

► None of the given options.

Question No: 19 (Marks: 1) - Please choose one vuzs

The object _____may be used both for file input and file output

► fstream, (Page 199)

► ifstream,
► ofstream,
► none of the given options.

Question No: 20 (Marks: 1) - Please choose one

Which of the following function calling mechanism is true for the function prototype given below?

float func(float &);

► Call by value
► Call by reference using pointer
► Call by reference using reference variable

► None of the given options

Question No: 21 (Marks: 1) - Please choose one

The programs, in which we allocate static memory, run essentially on _____

► Heap

► System Cache
► None of the given options

► Stack (Page 280)

Question No: 22 (Marks: 1) - Please choose one

Overloaded delete operator function takes parameter of void pointer and returns

_____.

► **void**

► void pointer
► pointer to an object
► pointer of type int

Question No: 23 (Marks: 1) - Please choose one

What should be the return type of the constructor?

► void pointer

► int
► same as object type
► **constructors do not return any thing (Page 313)**

Question No: 24 (Marks: 1) - Please choose one

It is a way of reusing the code when we contain objects of our already written classes into a new class,

► **True**

► False

Question No: 25 (Marks: 1) - Please choose one vuzs
Templates are not type safe.

► true

► false (Page 518)

Question No: 26 (Marks: 1) - Please choose one

The functions used for dynamic memory allocation return pointer of type _____

► int

► float

► void

► double

FINALTERM EXAMINATION

Fall 2008

CS201- Introduction to Programming

Question No: 1 (Marks: 1) - Please choose one

There are mainly ---------- types of software

► Two (Page 9)

► Three
► Four
► Five

Question No: 2 (Marks: 1) - Please choose one seekg()
and write() are functionally _____ .

► Different

► Identical
► Two names of same function
► None of the above

Question No: 3 (Marks: 1) - Please choose one

When a pointer is incremented, it actually jumps the number of memory addresses

► **According to data type (Page 160)**

► 1 byte exactly
► 1 bit exactly
► A pointer variable can not be incremented

Question No: 4 (Marks: 1) - Please choose one
setw is a parameterized manipulator.

► **True (Page 437)**

► False

Question No: 5 (Marks: 1) - Please choose one

eof( ), bad( ), good( ), clear( ) all are manipulators.

► **True (Page 433)**

► False

Question No: 6 (Marks: 1) - Please choose one

In functions that return reference, use _____variables.

► Local

► Global

► **Global or static (Page 369)**

► None of the given option

Question No: 7 (Marks: 1) - Please choose one The declarator of Plus (+) member operator function is

► **Class-Name operator + (Class-Name rhs) (Page 371)**

► operator Class-Name + ( )

► operator Class-Name + (rhs)

► Class-Name operator + ( )

Question No: 8 (Marks: 1) - Please choose one

The compiler does not provide a copy constructor if we do not provide it.

► True

► **False (Page 476)**

Question No: 9 (Marks: 1) - Please choose one

What is the functionality of the following syntax to delete an array of 5 objects named ***arr*** allocated using new operator?

delete arr ;

Deletes all the objects of array

► **Deletes one object of array (Page 411)**

Do not delete any object
Results into syntax error

This statement will call the destructor only for the object pointed by the ***arr*** and deallocate the space allocated to this object

Question No: 10 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

► Only block of memory is allocated for objects

► Only constructor is called for objects

► **Memory is allocated first before calling constructor (Page 414)**

► Constructor is called first before allocating memory

Question No: 11 (Marks: 1) - Please choose one

What is the sequence of event(s) when deallocating memory using delete operator?

► Only block of memory is deallocated for objects

► Only destructor is called for objects

► Memory is deallocated first before calling destructor

► **Destructor is called first before deallocating memory (Page 414)**

Question No: 12 (Marks: 1) - Please choose one

new and **delete** operators cannot be overloaded as member functions.

► True

► **False (Page 414)**

Question No: 13 (Marks: 1) - Please choose one

The operator function of << and >> operators are always the member function of a class.

► True

► **False (Page 446)**

Question No: 14 (Marks: 1) - Please choose one

A template function must have at least ---------- generic data type

► Zero

► **One (Page 499)**

► Two
► Three

Question No: 15 (Marks: 1) - Please choose one

If we do not mention any *return_value_type* with a function, it will return an _____ value.

► int (Page 79)

► void
► double
► float

Question No: 16 (Marks: 1) - Please choose one

Suppose a program contains an array declared as **int arr[100];** what will be the size of array?

► 0

► 99
► 100 (Page 103)

► 101

Question No: 17 (Marks: 1) - Please choose one

The name of an array represents address of first location of array element.

► **True**

► False

The name of the array is a constant pointer which contains the memory is the address of first element of the array

Question No: 18 (Marks: 1) - Please choose one

Reusing the variables in program helps to save the memory

► **True**

► False

Question No: 19 (Marks: 1) - Please choose one

Which of the following option is true about new operator to dynamically allocate memory to an object?

► The new operator determines the size of an object

► Allocates memory to object and returns pointer of valid type

► Creates an object and calls the constructor to initialize the object

► **All of the given options**

Question No: 20 (Marks: 1) - Please choose one

New and delete are _____ whereas malloc and free are _____.

► Functions, operators

Classes, operators

► **Operators, functions (Page 342-285)**

► Operators, classes

Question No: 21 (Marks: 1) - Please choose one

Like member functions, _____ can also access the private data members of a class.

► Non-member functions

► **Friend functions (Page 346)**

► Any function outside class
► None of the given options

Question No: 22 (Marks: 1) - Please choose one

Which of the following statement is best regarding declaration of friend function?

► Friend function must be declared after public keyword.

► Friend function must be declared after private keyword.
► Friend function must be declared at the top within class definition.
► **It can be declared anywhere in class as these are not affected by the public and private keywords. (Page 346)**

Question No: 23 (Marks: 1) - Please choose one

The operator function overloaded for an Assignment operator (=) must be

► Non-member function of class

► **Member function of class (Page 372)**

► Friend function of class
► None of the given options

Question No: 24 (Marks: 1) - Please choose one

For non-member operator function, object on left side of the operator may be

► Object of operator class

► Object of different class
► Built-in data type
► **All of the given options (Page 375)**

Question No: 25 (Marks: 1) - Please choose one

The operator function will be implemented as _____, if obj1 drive the - operator whereas obj2 is passed as arguments to - operator in the statement given below.

obj3 = obj1 - obj2;

► **Member function (Page 373)**

► Non-member function
► Friend function
► None of the given options

Question No: 26 (Marks: 1) - Please choose one

Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

► Class-name operator +() ;

► Class-name operator +(int) ;

► **Class-name operator ++() ; (Page 389)**

► Class-name operator ++(int) ;

Question No: 27 (Marks: 1) - Please choose one

The static data members of a class are initialized _____

► **at file scope (Page 466)**

► within class definition
► within member function
► within main function

Question No: 28 (Marks: 1) - Please choose one

Class is a user defined_____.

► **data type (Page 317)**

► memory referee

► value
► none of the given options.

Question No: 29 (Marks: 1) - Please choose one
We can also define a user-defines manipulators.

► **True**

► False

Parameterized manipulators require one or more arguments. setfill (near the bottom of the iomanip.h header file) is an example of a parameterized manipulator. You can create your own parameterized manipulators and your own simple manipulators.

Question No: 30 (Marks: 1) - Please choose one

Automatic variable are created on _____.

► Heap

► Free store
► static storage

► **stack (Page 461)**

FINALTERM EXAMINATION

fall 2008

CS201- Introduction to Programming (Session - 2)

Question No: 1 (Marks: 1) - Please choose one

If Num is an integer variable then Num++ means,

Add 1 two times with Num

Add 1 with Num

Add 2 with Num

- Subtract 2 from Num

Question No: 2 (Marks: 1) - Please choose one

If the return type of a function is void then it means that it will,

- Return any type of data
- Return some specific type of data
- **Return no data**
- Return just character data

Question No: 3 (Marks: 1) - Please choose one

Which of the following is a valid class declaration?

- **class A { int x; };**
- class B { }
- public class A { }
- object A { int x; };

Question No: 4 (Marks: 1) - Please choose one

When we use manipulators in our program then which header file should be included?

- iostream.h
- stdlib.h
- stdio.h
- ✶ **iomanip.h (Page 433)**

Question No: 5 (Marks: 1) - Please choose one

We can also create an array of user define data type.

- **True (Page 408)**
- False

Question No: 6 (Marks: 1) - Please choose one

The normal source of **cin** object is,

- File
- Disk
- RAM

Question No: 7 (Marks: 1) - Please choose one

A stream is an ordered sequence of bytes.

- ✶ **True (Page 423)**
- False

Question No: 8 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

- Only block of memory is allocated for objects
- Only constructor is called for objects
- ✶ **Memory is allocated first before calling constructor (Page 414)**

- Constructor is called first before allocating memory

Question No: 9 (Marks: 1) - Please choose one

We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally.

- **True (Page 412)**
- False

Question No: 10 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are overloading these operators.

- **True (Page 453)**
- False

Question No: 11 (Marks: 1) - Please choose one

Which looping process checks the test condition at the end of the loop?

- for
- while
- **do while**

► no looping process checks the test condition at the end
http://mathbits.com/MathBits/CompSci/looping/MCLooping.htm

Question No: 12 (Marks: 1) - Please choose one

In a group of nested loops, which loop is executed the most number of times?

- the outermost loop
- **the innermost loop**
- all loops are executed the same number of times

► cannot be determined without knowing the size of the loops
http://mathbits.com/mathbits/java/Looping/MCLooping.htm

Question No: 13 (Marks: 1) - Please choose one

Template class can not have static variables.

- True
- **False (Page 513)**

Question No: 14 (Marks: 1) - Please choose one

Consider the following statements to initialize a two-dimensional array.

- int arr[2][3] = {4, 8, 9, 2, 1, 6} ;
- int arr[3][2] = {4, 8, 9, 2, 1, 6} ;
- int arr[][2] = {{4,8},{9, 2},{1, 6}} ;

Which of the following option(s) are correct to initialize a two-dimensional array with 3 rows and 2 columns?

- (ii) only
- (iii) only
- **(ii) and (iii)**
- and (iii)

Question No: 15 (Marks: 1) - Please choose one

There is a pointer variable named ***ptr*** of type int then address of which type of variable the ***ptr*** will store in it?

- variable of type char
- variable of type short
- **variable of type int**
- variable of type double

Question No: 16 (Marks: 1) - Please choose one

Let suppose

Union intorDouble{

Int ival;

Double charvar;

};

main(){

---

intorDouble VAZ;

int size ;

size = sizeof(VAZ);

}

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8 bytes?

- 2
- 4
- 8
- 12

Question No: 17 (Marks: 1) - Please choose one

new and delete are _____ whereas malloc and free are _____.

- Functions, operators
- Classes, operators
- ✶ **Operators, functions (Page 342-285)**
- Operators, classes

Question No: 18 (Marks: 1) - Please choose one

The member functions of a class occupy _____ region in memory for ____ object(s) of class.

- separate, each
- ✶ **common, all (Page 334)**
- different, each
- different, all

Question No: 19 (Marks: 1) - Please choose one

Friend functions are _____ of a class.

- Member functions
- Public member functions

- Private member functions
- **Non-member functions (Page 346)**

Question No: 20 (Marks: 1) - Please choose one

Which of the following is true while overloading operators?

- Precedence of an operator can be changed
- The arity (number of operands) can be changed
- No new operators can be created
- Associativity of an operator can be changed

Question No: 21 (Marks: 1) - Please choose one

Which of the following option will be true to overload the -= operator?

- **only - operator needs to be overloaded (not sure)**
- Minus (-) and = operators need to be overloaded
- the -= operator need to be overloaded explicitly
- the - and = operators need to be overloaded implicitly

Question No: 22 (Marks: 1) - Please choose one

The input/output streams; cin and cout are ____

- Operators
- **Functions**
- Objects
- Structures

Question No: 23 (Marks: 1) - Please choose one

dec, hex, oct are all _____

- Member functions
- Objects of input/output streams
- Parameterized manipulators
- ✶ **Non-parameterized manipulators (Page 435)**

Question No: 24 (Marks: 1) - Please choose one

What will be the output of the following statement?

cout << setbase(16) << 52 ;

- 74
- 52
- **34**
- 64

Question No: 25 (Marks: 1) - Please choose one

The first parameter of overloaded stream insertion operator is _____ where second parameter is _____

- input stream, object of class
- object of class, output stream
- **output stream, object of class**
- object of class, input stream

Question No: 26 (Marks: 1) - Please choose one

We can also do conditional compilation with preprocessor directives.

- ✶ **True (Page 272)**
- False

Question No: 27 (Marks: 1) - Please choose one

With user-defined data type variables (Objects), self assignment can produce _____.

- Syntax error
- **Logical error**
- Link error
- Non of the given options

Question No: 28 (Marks: 1) - Please choose one

The return type of the operator function for >> operator is _____.

- **class for which we overload this operator**

- reference of ostream class (ostream&)
- reference of istream class (istream&)
- void

Question No: 29 (Marks: 1) - Please choose one

When an object of a class is defined inside an other class then,

- **Constructor of enclosing class will be called first (Page 496)**

- Constructor of inner object will be called first
- Constructor and Destructor will be called simultaneously
- None of the given options

Question No: 30 (Marks: 1) - Please choose one

Where we can include a header file in the program?

- **any where (Page 270)**

- in start
- at the end
- none of the given options.

1) An alternative to translators

► Assembler

- Compiler
- **Interpreter**
- Mnemonics

2) The sign of modulus is

- /
- \
- **%**
- -

3) This ___ view of the database is called a database model.

- theoretical
- **conceptual** **Page no 253**
- empirical
- logic

4) Which of following is not a phase of SDLC?

- Testing
- **Problem identification**
- Requirement analysis
- Implementation

► In modern computer applications, problems are more easily solved in the context of:

► **Parallel processing** **Page no 209**

► Traditional context
► Traditional processing
► Technology

6) 5%2 would give

► 0

► **1**
► 2
► 5

7) Design phase is followed by ___

► **Requirement analysis** **Page no 218**
► Implementation
► Testing
► Maintenances

► In particular the chart that indicates the entire game is overseen by a function named ___

► objects
► **control game** **Page no 224**
► function
► forms

9) The simplest form of array is the ___ array.

- multi-dimensional
- two-dimensional
- **one-dimensional**
- all of above

10) A Specific example is the ___ series of standards, which address numerous industrial activities such as design, production, installation and servicing

- **ISO 900** **Page no 233**
- IEEE
- ISO/IEC 15504
- SQA

11) A paradigm works on object called

- Imperative paradigm
- Declarative paradigm
- Functional paradigm
- **Object-oriented paradigm**

- An object is actually a special case of the general concept of a

- coupling

- binding
- cohesion
- **components**

13) A significant example of iterative techniques is:

- Relational process
- Conventional process

- **Rational unified process**
- Unified process

- If the result after comparison of two variables in relational operator is False, then if statement returns value

- 1
- No
- !
- **0**

15) The description of the object's properties is called

- Object
- **Class**
- Function
- Instance

- A model which represents the shift away from strict adherence from the waterfall model is:

- Incremental model
- Waterfall model
- Spiral model
- **Iterative model** Page no 222

► The **loop** control structure iterates a set of instructions based on the provided condition.

► One example of an **agile method** is **extreme programming (XP).**

► **Factory Pattern** is based on real time factory concept

► The result of **each intermediate step** in the entire development process should be “tested” for accuracy.

► Which of the following data type will be used for a variable having string of symbols and alphabets. **Character**

► Which of the following language is related to functional paradigm. **LISP**

► SLDC = **SOFTWARE DEVELOPMENT LIFE CYCLE**

► Software engineering IS AN engineering discipline that is concerned with **all aspects of software production**

► An object is actually a special case of the more general concept of a **component**

► The major steps in the traditional **software development life cycle** are **requirements**

► **Analysis**, **design**, **implementation**, and **testing.**

► **Design** stages is about developing a solution to the problem.

► **Which** is contrast to the **imperative paradigm** is the **declarative paradigm.**

► **black-box testing,** which refers to tests that do not rely on knowledge of the software's interior composition.

► How many choices are possible when using a single lf-else statement**?** **2**

► **Mathematicians** refer to functional paradigm**.**

► Each programming language tends to approach the parallel processing paradigm from its own point of view, resulting in different terminology.in Ada we use term **Task** for this purpose

► The **imperative paradigm,** also known as the **procedural paradigm,** represents the **traditional approach** to the programming process.

► While **copyrights** and software license agreements provide legal avenues to inhibit outright copying and unauthorized use of software.

► **control coupling,** which occurs when a module passes control of execution to another, as in a function call

► The Select Operation extracts **rows** from a relation.

► The PROJECT operation extracts **columns** from a relation.

► An **array** is a "**rectangular**" block of data whose entries are of the same type.

► The problem known as the **incorrect summary problem** can arise if one transaction is in the middle of transferring funds from one account to another when another transaction tries to compute the **total deposits in the bank**.

► A **subschema** is a description of only that portion of

the database pertaining to a particular user's needs.

► **Declarative Paradigms** system is designed for general-purpose.

► How do you initialize an array in C. **int arr[3]={1,2,3}**

► We use **information hiding** to reduce unnecessary dependencies or effects on other modules.

► A process which is used by the software industry to design, develop and test high quality software is known as **software life cycle.**

► Stakeholders can be a **government agency**,

► **Ergonomic** which deals with designing systems that harmonize with the physical abilities of humans.

► Which of the following symbol is used as assignment operator in Ada. **:=**

► **Implementation** stage that distinct between the tasks of a **software analyst** (sometimes referred to as a system analyst) and a **programmer.**

► The node at the top is called the **root** node**.**

► The links between **objects** in an object-oriented database are normally maintained by the DBMS,

► In modern computer applications. problems or more easily solved in the context of **parallel processing** 2 traditional contact three traditional processing 4r technology.

► In which of the following paradigms a program is constructed by connecting smaller predefined program units. **functional paradigms**

► Which one of the following is the traditional approach of programming process. **imperative paradigm**

► Which from the following is not a relational operator **= => =! =% =**

► A significant example of iterative techniques is: **Rational Unified Process**

► The …… provides a standardized way of implementing success system that leads to a manageable solution.

decorator pattern

► In object-oriented paradigm each object will have its own collection of functions which is known as **methods**

► Writing programs in a machine language is a tedious task that often leads to errors that must be located and corrected. **debugging**.

► Correct syntax is **if (condition) Statement A Else Statement B**

► is exemplified by two transactions each of which makes a deduction from the same account **lost update problem**

► In If two modules interact with the same item of data then modifications made to one module may affect the other. **data coupling**

► A paradigm works on object called **object oriented paradigm**

► In the case of highly standardized languages, compiler designers often provide features, sometimes called machine language. **language extensions**

► The syntax for using && is. **cmd1 && cmd2**

► The set of instructions in a computer language to get the desired results is known as **program**

► This description of the object's properties is called **a class**.

► A software license is a **legal agreement** between the owner and user of a software product that grants the user certain permissions to use the product without transferring ownership rights to the intellectual property.

► Software development companies are establishing **software quality assurance**

► **(SQA)** groups, which are charged with overseeing and enforcing the quality control systems adopted by the organization.

► A **tree** is a collection whose entries have a hierarchical organization similar to that of an organization chart of a typical company.

► In the case of **large databases** that are subject to heavy transaction loads, it is highly likely that a random snapshot will find the database in the middle of some transaction**.**

► From a lay- person’s perspective, requirements analysis is often equated with **what.**

► This **conceptual** view of the database is called a database model**.**

► Which one is a Unary operator. **NOT OPERATOR**

► A software license is a ___ between the owner and the user of a software product that grant the user certain permission to use the product without transferring ownership right to the intellectual property? **Legal agreements**

► Which one is a unary operator? **Not**

► If the result after comparison two variables in rational operator is false. Then if statement return values? **0**

► A process that is used by the software industry to design, develop and test high-quality software is known as **software life cycle**

► The imperative paradigm is also known as the particular machine… **procedural paradigm**

► Which software testing methodology is to develop the test of set data that ensures that each instruction in the software is executed at least once? **Basis path testing**