CS201 - Introduction to Programming (Quiz 3)

Question # 9 of 10 (Start time: 11:19:25 AM, 28 June 2024)

a = a|b; ca be written as_____.

Select the correct option

○	a ==b;
○	a =|b;
●	a |=b;
○	a=b;

CS201 - Introduction to Programming (Quiz 3)

Question # 8 of 10 (Start time: 11:18:53 AM, 28 June 2024)

The constructor contains _____.

Select the correct option

- ○ no return type
- ○ return type
- ○ objects
- ○ classes

CS201 - Introduction to Programming (Quiz 3)

Question # 7 of 10 (Start time: 11:18:19 AM, 28 June 2024)

We cannot use _____ pointer for storing and reading data from it.

Select the correct option

- ○ double
- ○ integer
- ◉ NULL ✓
- ○ zero

CS201 - Introduction to Programming (Quiz 3)

Question # 10 of 10 (Start time: 11:20:57 AM, 28 June 2024)

Constructor is a special function, called whenever we _____.

Select the correct option

- ○ create a class
- ○ destroy an object
- ○ create a function
- ○ instantiate an object of a class ✓

Question # 13 of 15 (Start time: 10:34:39 AM, 27 January 2023) Total Mark

Which of the following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

Select the correct option

- delete []string ;
- delete string ;
- delete string[] ;
- delete string[5] ;

CS201 - Introduction to Programming (Quiz 3)

Question # 6 of 10 (Start time: 11:17:46 AM, 28 June 2024)

Constructor has _____.

Select the correct option

- ○ return type
- ○ the same name as data member
- ○ no name
- ● the same name as of class ✓

CS201 - Introduction to Programming (Quiz 3)

Question # 5 of 10 (Start time: 11:17:01 AM, 28 June 2024)

In a class we can have _____ constructor(s).

Select the correct option

- ○ no
- ◉ many
- ○ two
- ○ only one

CS201 - Introduction to Programming (Quiz 3)

Question # 4 of 10 (Start time: 11:16:09 AM, 28 June 2024)

Multiplicatiive, Additive and assignment operators are ____ operators.

Select the correct option

○	Relational
◉	Binary
○	Conditional
○	Unary

CS201 - Introduction to Programming (Quiz 3)

Question # 3 of 10 (Start time: 11:14:40 AM, 28 June 2024)

The members of a class declared with the keyword struct are _____by default.

Select the correct option

- ○ protected
- ○ static
- ◉ public
- ○ private

CS201 - Introduction to Programming (Quiz 3)

Question # 2 of 10 (Start time: 11:13:40 AM, 28 June 2024)

The exclusive OR operator returns 1 if _____.

Select the correct option

- ○ None of the given
- ○ Both inputs are 0
- ○ Both inputs are 1
- ○ One input is 1 and other is zero ✓

CS201 - Introduction to Programming (Quiz 3)

Question # 1 of 10 (Start time: 11:12:49 AM, 28 June 2024)

The heap memory structure _____.

Select the correct option

- ○ is just like stack
- ○ remains constant
- ○ contains no space
- ○ constantly changes in size ✓

CS201 - Introduction to Programming (Quiz 4)

Question # 10 of 10 (Start time: 07:54:56 AM, 02 July 2024)

The read and write member functions input or output some number of bytes to or from a character array in memory.

Select the correct option

- True
- False

CS201 - Introduction to Programming (Quiz 4)

Question # 8 of 10 (Start time: 07:53:46 AM, 02 July 2024)

Once an object is declared as a friend, _____.

Select the correct option

- (●) it has access to all non-public members as if they were public
- ( ) it has access to public members only
- ( ) it has no access to data members of the class
- ( ) it has access to protected data members only

CS201 - Introduction to Programming (Quiz 4)

Question # 7 of 10 (Start time: 07:53:16 AM, 02 July 2024)

Within the statement obj1=obj2; obj1 will call the assignment operator function and obj2 will be passed as an argument to function.

Select the correct option

- (●) True
- ( ) False

CS201 - Introduction to Programming (Quiz 4)

Question # 5 of 10 (Start time: 07:51:47 AM, 02 July 2024)

If class A is a friend of class B, and class B is a friend of class C. If class A wants class C to be a friend, _____

Select the correct option

- it has to declare, class B and class A as friend classes
- it has to declare, class C as a friend
- it has to declare , class A as a friend
- it has to declare, class B as a friend

CS201 - Introduction to Programming (Quiz 4)

Question # 3 of 10 (Start time: 07:50:53 AM, 02 July 2024)

In functions, that returns reference use _____.

Select the correct option

- ○ global or local variables
- ○ ordinary variables
- ○ array
- ◉ global or static variables

CS201 - Introduction to Programming (Quiz 4)

Question # 4 of 10 (Start time: 07:51:26 AM, 02 July 2024)

Stream operators are heavily overloaded means , they allow to handle int and character data type only.

Select the correct option

- True
- False

CS201 - Introduction to Programming (Quiz 4)

Question # 1 of 10 (Start time: 07:49:19 AM, 02 July 2024)

Overloaded delete operator function takes parameter of void pointer and returns.

Select the correct option

- ○ void (nothing)
- ○ object pointer
- ◉ void pointer
- ○ int pointer

CS201 - Introduction to Programming (Quiz 4)

Question # 6 of 10 (Start time: 07:52:38 AM, 02 July 2024)

A reference cannot be NULL it has to point a data type.

Select the correct option

- ○ false
- ◉ true

CS201 - Introduction to Programming (Quiz 4)

Question # 9 of 10 (Start time: 07:54:30 AM, 02 July 2024)

A pointer is _____.

Select the correct option

○	an indication of the variable to be accessed next.
○	the address of a variable
◉	a variable for storing address
○	the data type of an address variable

Apps YouTube WhatsApp Get Into PC - Downl... ChatGPT Gemini Merge PDF

CS201 - Introduction to Programming (Quiz 4)

Question # 3 of 10 (Start time: 08:27:12 PM, 02 July 2024)

Once the _____ are created, they exist for the life time of the program

Select the correct option

- ○ local variables
- ○ non static variables
- ○ global variables ✓
- ○ automatic variables

vulms.vu.edu.pk/Quiz/QuizQuestion.aspx?ver=992b2e6d-f412-4a01-a6c7-0e9

Apps YouTube WhatsApp Get Into PC - Downl... ChatGPT Gemini Merge P

Question # 2 of 10 (Start time: 08:26:31 PM, 02 July 2024)

The only operator that the compiler overloads for user define data type by default is

Select the correct option

- Equal (==) operator
- Minus (-) operator
- Plus (+) operator
- Assignment (=) operator

Apps YouTube WhatsApp Get Into PC - Downl... ChatGPT Gemini Merge PDF files onli... 3D Warehous

Question # 1 of 10 (Start time: 08:25:47 PM, 02 July 2024)

C++ provides member functions, which control the formatting to be performed during stream I/O operations.

Select the correct option

- True
- False

Apps YouTube WhatsApp Get Into PC - Downl... ChatGPT Gemini Merge PDF files onli... 3D Warehouse Fa

Question # 5 of 10 (Start time: 08:28:34 PM, 02 July 2024)

Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

Select the correct option

- Class-name operator +() ;
- Class-name operator ++(int) ;
- Class-name operator +(int) ;
- Class-name operator ++();

vulms.vu.edu.pk/Quiz/QuizQuestion.aspx?ver=1

Apps YouTube WhatsApp Get,Into PC - Downl... Cha

CS201 - Introduction to Programming (Quiz 4)

Question # 4 of 10 (Start time: 08:27:50 PM, 02 July 2024)

int &i; It means that i is a _____to an integer.

Select the correct option

- data type
- pointer
- reference ✓
- constant pointer

CS201 - Introduction to Programming (Quiz 4)

Question # 7 of 10 (Start time: 08:30:35 PM, 02 July 2024)

date+=1; is equivalent to _____.

Select the correct option

- date+1
- 1+date
- date++ ✓
- ++date

Apps YouTube WhatsApp Get,Into PC - Downl... ChatGPT Gemini

CS201 - Introduction to Programming (Quiz 4)

Question # 9 of 10 (Start time: 08:32:39 PM, 02 July 2024)

In C++ operators, which of the following operator cannot be overloaded ____

Select the correct option

- ○ +
- ○ ?:
- ○ <<
- ○ -

Question # 6 of 10 (Start time: 08:29:19 PM, 02 July 2024)

When we use cin stream to read some number from the keyboard and store it in the integer variable, then what will happen?

Select the correct option

- Its binary representation will be ignored and the value will be stored
- Its ASCII code will be stored inside the computer
- Its binary representation will be ignored and the character will be stored ✓
- Some error will occur and cin stream will detect this error.

Question # 10 of 10 (Start time: 08:33:50 PM, 02 July 2024)

With user data type variables (Objects) self assignment can produce

Select the correct option

- Logical error
- Run time error
- Link error
- Syntax error

Apps YouTube WhatsApp Get, Into PC - Downl... ChatGPT

Question # 8 of 10 (Start time: 08:31:11 PM, 02 July 2024)

Identify the correct syntax for making a class friend of other class

335

Select the correct option

○	class ClassOne { friend OtherClass ; private: {
○	friend OtherClass ; private: //here we write the data members of ClassOne
○	Friend class ClassOne { friend OtherClass ; private:
○	friend ClassOne { OtherClass ;

Ask Copilot

Friend Classes

We have seen that a class can define friend functions for itself. Similarly a class can be declared as a friend class of the other class. In that case, the function of a class gets complete access to the data members and functions of the other class. So it is an interesting expansion of the definition that not only the functions but also a class can be a friend of the other class. The syntax of declaring a friend class is that within the class definition, we write the keyword *friend* with the name of the class. It is going to be a friend class. i.e. *friend class-name;*
We can also write the word class after the keyword friend and before the class name as

friend class class-name ;

Now let's take another example of a class. Suppose, we have classes *ClassOne* and *OtherClass*. We want to make *OtherClass* a friend class of the *ClassOne*. So we declare *OtherClass* a friend class in the definition of the *ClassOne* as following.

```
class ClassOne
        {
                friend OtherClass ;
                private:
                //here we write the data members of ClassOne
        };
```

The line

```
friend OtherClass ;
```

can also be written as

```
friend class OtherClass ;
```

Highlight-Handout-.pdf
Ask Copilot
otherclass
1/25

```
};
```

The line

```
friend OtherClass ;
```

can also be written as

```
friend class OtherClass ;
```

The line *friend OtherCalss;* explains that *OtherClass* is a friend of *ClassOne*. If *OtherClass* is the friend of *ClassOne*, all the functions of *OtherClass* will have access to all the inside part of *ClassOne*.

The following code segment shows the declaration of friend class. It shows that *OtherClass* is a friend of *ClassOne* so it has access to the private data of *ClassOne*.

```
class ClassOne
{
        friend class OtherClass;
        private:
        int topSecret;
};

class OtherClass
{
        public:
        void change( ClassOne co )
};
```


© Copyright Virtual University of Pakistan

Q. We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally.

A. True

B. False

ANSWER

Q. With user-defined data type variables (Objects), self assignment can produce _____.

A. Syntax error

B. Logical error

C. Link error

D. Non of the given options

CS201 - Introduction to Programming (Quiz No 3)

Quiz Start Time: 10:12 AM, 27 January 202

Question # 11 of 15 (Start time: 10:32:08 AM, 27 January 2023)

Total Mark

Which of the following is unary operator?

Select the correct option

Reload Math Equations

- j++
- ++j
- All of the Given
- j--

Click to Save Answer & Move to Next Question

WWW.SANDICAM.COM

_____ variables are used to maintain state.

Select the correct option

- (●) Static
- ( ) Local
- ( ) Dynamic
- ( ) Global

Click to Save Answer & Move to Next Question

CS201 - Introduction to Programming (Quiz 4)

Question # 2 of 10 (Start time: 07:49:53 AM, 02 July 2024)

Let suppose

```
int a, b, c, d, e;
a = b = c = d = e = 42;
```

This can be interpreted by the complier as

Select the correct option

- ○ a = b = (c = (d = (e = 42)));
- ◉ (a = b = (c = (d = (e = 42))));
- ○ a = (b = (c = (d = (e = 42))));
- ○ (a = b) = (c = d) = (e = 42);

www.BANDICAM.com

Which of the following is the correct definition of streams?

Select the correct option

- It is an unordered sequence of bits
- It is an ordered sequence of bits
- It is an unordered sequence of bytes
- It is an ordered sequence of bytes

www.BANDICAM.com

Question # 3 of 15 (Start time: 10:16:44 AM, 27 January 2023) **Total Mark**

Below is given a code snippet

```
char name[50];
cin>>name;
cout<<name;
```

Now if user enters the name, for example "Sohail Aslam" than what will be the output of the code ?

Select the correct option

- Sohail Aslam
- Aslam Sohail
- Aslam
- Sohail

www.BANDICAM.com

When we use cin stream to read some number from the keyboard and store it in the integer variable, then what will happen?

Select the correct option

- Its ASCII code will be stored inside the computer
- Its binary representation will be ignored and the value will be stored
- Its binary representation will be ignored and the character will be stored
- Some error will occur and cin stream will detect this error.

www.BANDICAM.com

The return type of the operator function for << operator is _____.

Select the correct option

- void
- reference of istream class (istream&)
- class for which we overload operator
- reference of ostream class (ostream&)

Q. dec, hex, oct are all _____

A. Member functions

B. Objects of input/output streams

C. Parameterized manipulators

D. Non-parameterized manipulators

ANSWER

Question No: 7 (M - 1) .

When an array of object is created dynamically then there is no way to provide parameterized constructors for a

- ► True
- ► False

if we are allocating an array of objects, there is no way to pass arguments to objects' constructors. Therefore it objects that are stored in such an array have a no-argument constructor.

Question No: 8 (M - 1) .

C is widely known as development language of _____ operating system.

- ► Linux
- ► Windows
- ► Unix
- ► Mac OS

1. Must be passed by value
2. Must be passed by reference
3. Can be passed by value or reference
4. Must be object of class

. **The second parameter of operator function for >> operator must always be passed**

1. By reference
2. Function takes no argument
3. By value
4. None of the given

. **The only operator that the compiler overloads for user define data type by default is**

It is possible to return an object from function using this pointer

1. True
2. False

Overloaded assignment operator must be

1. Member function of class
2. Non-member function of class

Unary minus	-	Returns opposite sign operand
Increment Operator	++	Increments the value of an operand by 1
Decrement Operator	– –	Decrements the value of an operand by 1
NOT Operator	!	Reverses the logical state of an operand
Addressof Operator	&	Returns the address of an operand
sizeof() operator	sizeof()	Returns the size used by the data type in bytes

BeginnersBook.com

https://beginnersbook.com/2022/08/unary-operator-in-c-with-examples/