Download File From
VU Solution Point

62 Operator System fals under the category of ___ types of Software.

System software

63 We can change the number of operands through operators overloading.

False

64 A friend function of a class has ___ access.

class to all data member and function of the

65 Setprecision is a Parameter less manipulator.

False

66 Only operator compiler loads for users is

Assignment operator

67 Cerr and clog are the objects of stream class.

True

68 Loader loads the executable code from main memory to hard disk.

False

69 Pre Processor directive functions before ___ Phase.

Compiler

70 The operator overloaded for an assignment operator (=) must be

non-member function of class

79 Which of the following function cannot be overloaded?

Destuctor

80 Static variable which is defined in a function is initilized

only once during its life time

81 Static memory allocation is also known as ____ ?

Compile time allocation

82 In Flow chart, flow of controls is represented by ____.

Download File From
VU Solution Point

Arrow

83 The operators ++ and -- are used to incement the value of a variable to ____.

1

84 to assigned a value to a character type variable ____ are used around the value.

Sigle quotes''

85 In year ____ C was approved as a standard language worldwide.

1989

86 The C language was developed in late 60's and early 70's in ____

Bell laboratories

Download File From
VU Solution Point

39 Header files fstream.h includes the defination of the stream classes
ifstream, fstream, ofstream

40 Flush and endl are manipulators?
True

41 The return type of operator function must always be void.
Friend function of the class

42 The statement cin.get(); is used to.
read a character from keyboard

43 Overloaded new operators function takes parameter of type size-t.
Void Pointer

44 To include code from the library in the program such as iostream a directive would be called up using this command.
#include < iostream.h >

45 C++ is a case sensitive language.
True

46 Templates class can not have static variables.
False

Download File From
VU Solution Point

an object.

True

8 Break statement can be used outside a loop or switch statement

True

9 keyword ___ is used to return some value from a function.

return

10 Symbolic constant has been defined. it will be an error to define it again >

True

11 Every class contains ___.

Constructor

12 Assignment operator is ___ Associative.

Binary

13 Can not define a variable of user Defined Data type in the class.

False

14 Class is a user defined ___.

Data type

15 Which of the following is the correct c++ syntax to allocate space Dynamically for an array of 10 int ?

new int [10];

54 With new keyword, data types and class members are initialized with meaningful values instead of garbage.

True

55 Class is a user defined ——.

Data type.

56 ~~Dead~~ Dealing with structures and function Passing by refrence is the most economical method ?

True

57 A Pointer is a special variable that contain.

Memory Adress

58 The return type of a function that do not return any value.

void

59 Like member function —— can also access the Private data members of a class ?

friend function

60 eof(), bad(), good(), clear().all are manipulator ?

True

61 Constructors can not be overloaded like ordinary function

True

87 Is a friend function outside the class declares itself of the class This may violate the concept of
Encapsulation and data hiding

88 a structure brings together a group ~~of~~ of ___
Different Data type

89 This static data members of a class are initialized ___.
Within class defination

90 The static data members of a class can be accessed by ___.
both class and objects

91 The static data members of a class are initialized ___.
within class definition

92 When a call to a user defined functions finishes, the variable defined inside the function will ___
not exist further

93 What does STL stand for?
Standard template library

94 The code is written to implement the program.
implement

71 The static data members of a class are intialized

Within class definition

72 We can do condition compilation with pre processor directives.

False

73 A template function must have at least — or more arguments

one

74 Stream insertion (<<) and extraction (>>) are always implemented.

Non member

75 Over loaded members operator function is always called by —

objects

76 Declaring structure does not mean that memory is allocated.

True

77 Identifier is a name that can be given to variable, labels and functions

True

78 When memory of a program is allocated at run time then it is called —

Dynamic memory allocation

Download File From
VU Solution Point

CS 201

Objective Part

1 Access the Data Members of Structure ___ is used.

Dot Operator

2 When an operator Function is defined as member for a unary operator then the number of argument it take are.

One

3 Friend Function of a class is

Non - Member Function

4 Can also create a Array with user Define Data type.

False

5 Deleting an Array of objects without Specifying {} brackets may lead to memory ~~task~~ leak.

False

6 Which of the following data type can operate on modulous operator % ?

int

7 When an operator function is defined as member function then operand on the left side of operator must be

31 Every class contains ___
Constructor

32 New and delete are ___ whereas malloc and free are ___
Operators, Functions

33 Stream insertion mean and stream extraction operators are already overloaded for ___
Built in Data type

34 Assignment operators ~~ais~~ ___ Associative
Right

35 if we define an identifier with the statement #define PI 3.1415 then during the execution of the program the value of PI are ?
Remain Constant

36 Which of the following function do not initialize the chunk of memory to all zero?
Malloc function

37 Templates are not type safe?
False

38 In if structure the block of statement is executed when ?
~~Coding~~
Condition are true

24 Overloaded delete operator function takes the same parameter as an argument returned by new operator function.

True

25 When an array of objects is ~~used~~ created dynamically then there is no way to provide Parameterized constructors for array of objects.

True

26 C is widely known as development language of ___ operating system.

Unix

27 Compoter can understand only machine language code?

True

28 We can not define a function as a friend of a template class

False

29 What will be the value of 'a' and 'b' after executing the program

```
A = 3;
b = a++
```

3, 4

30 ___ is used to trace the logic of the program and correct the logical errors.

Debugger

16 A Pointer is a special variable that contain

Memory Adress

17 Operator overloading can be performed through

Function

18 Which of the function is used to increase the size of already allocated memory chunk?

Realloc

19 Which of the following is not a preprocessor Directice?

#ndefine

20 The stream Objects cin and cout are included in which header file?

Iostream.h

21 How many bytes will the Pointer intptr of type int more in the intptr+=3

12 bytes

22 Refrence value type data the code is written to ___ the program

Implement

23 When a value is refrred by a normal variable then it is Knam as

Direct Refrence

95 The appropriate data type to Store the number of rows and Columns of the matrix is ___
int

96 A class whose objects is contained as const objects, must have ___
Parameterized constructor

97 ___ data members of a contained objects can be ~~as~~ accessed from inside of the class.
- Private
- Public
- Protected

All

Download File From
VU Solution Point

98 The normal source of cin objects is ___.
key board

99 A macro when takes arguments is called ___.
Parameterized macro

100 Which is not a Protection level Provided by classes in C++ ?
Midden

101 What should be the return type of the constructor ?
Constructor do not return any thing

47 Which of the following data type can operate on modulus operator %?

int

48 We can do conditional compilation with preprocessor directives

True

49 If most signnificant bit of un-signed number is 1 then it represent is 1 than it represents a positive number.

False

50 The default value of a Parameter can be provided inside the

both (function Prototype + function defination)

51 Symbolic constant has been defined, it will be an error to define it again.

True

52 classes defined inside other classes are called ___

nested

Download File From
VU Solution Point

53 What Purpose do classes serve?

- Data encapsulation
- Simplifying code reuse
- Provised a convenient way of modeling real world objects.

All of the given