Professional Online Academy Vu Topper RM

C508- Modern Programming Update MCQ'S Final Term By Vu Topper RM

Follow Us on YouTube: @vutopperrm

For More Help Contact What's app Me!!!
Number's = # 0322-4021365, 0316-4980094

Rizwan Manzoor
Vu Topper RM



بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:1 **(Marks:1)** **Vu-Topper RM**

How many parameters are required by 'arraycopy' function in a JAVA program?

A. Five
B. Four
C. Three
D. Two

Question No:2 **(Marks:1)** **Vu-Topper RM**

_____ keyword is used in C# to inform the garbage collector not to relocate the object.

A. pause
B. exclude
C. stop
D. fixed

Question No:3 **(Marks:1)** **Vu-Topper RM**

Which of the following is NOT supported in JAVA?

A. Operator Overloading
B. Inheritance
C. Object-Orientation
D. Concurrency

Question No:4 **(Marks:1)** **Vu-Topper RM**

Concurrency in Java is supported through:

A. Threads
B. Batch execution
C. Resource allocation
D. Operator overloading

Question No:5 **(Marks:1)** **Vu-Topper RM**

Restricted use of pointers is permitted in C# within the code marked as:

A. void

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

B. static
C. unsafe
D. safe

Question No:6 **(Marks:1)** **Vu-Topper RM**
A type conversion that occurs without any special directive from the programmer is known as:
A. Strict conversion
B. Explicit conversion
C. Implicit conversion **Page 98**
D. Imperative conversion

Question No:7 **(Marks:1)** **Vu-Topper RM**
Which of the following are the types of constants in PROLOG?
A. short and char
B. float and numbers
C. single and decimal
D. atoms and numbers **Google**

Question No:8 **(Marks:1)** **Vu-Topper RM**
The super class of all exception classes in Java is:
A. Throwable **Google**
B. Error
C. System
D. Exception

Question No:9 **(Marks:1)** **Vu-Topper RM**
In java, explicit conversion of primitive type is done by _____
A. boxing
B. casting
C. overloading
D. aliasing

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:10 **(Marks:1)** **Vu-Topper RM**

When a class inherits from another class in Java then:

A. all fields and methods are inherited
B. only public fields and methods are inherited
C. only private fields and methods are inherited
D. only static fields and methods are inherited

Question No:11 **(Marks:1)** **Vu-Topper RM**

A variable name in PROLOG starts with _____

A. Number
B. Capital letter
C. Small letter
D. $ sign

Question No:12 **(Marks:1)** **Vu-Topper RM**

A main() function in a JAVA program:

A. must be inside a class
B. returns more than one value
C. is always declared as a global function
D. cannot be inside a class

Question No:13 **(Marks:1)** **Vu-Topper RM**

_____ cannot be converted to other types in Java.

A. Int
B. Char
C. Double
D. Booleans **Page 98**

Question No:14 **(Marks:1)** **Vu-Topper RM**

The keyword that is used to generate exception explicitly in Java is:

A. Try
B. Catch
C. Throw **Google**

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

D. Finally

Question No:15 **(Marks:1)** **Vu-Topper RM**

Default access (if no other access is specified) for classes and fields in Java is:

A. Public
B. Private
C. Package **Google**
D. Protected

Question No:16 **(Marks:1)** **Vu-Topper RM**

The basic tool for writing programs in PROLOG is:

A. Recursion **Page 85**
B. Inheritance
C. Polymorphism
D. Object-Orientation

Question No:17 **(Marks:1)** **Vu-Topper RM**

How many kinds of "type conversion" of primitive types are there in Java?

A. 2 **Page 175**
B. 3
C. 4
D. 5

Question No:18 **(Marks:1)** **Vu-Topper RM**

Expert system_____ provide a structure to design expert system.

A. Mechanism
B. Shells
C. Lists
D. Techniques

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:19 **(Marks:1)** **Vu-Topper RM**

Which of the following primitive type is available in JAVA?

A. typedef
B. struct
C. byte
D. enum

Question No:20 **(Marks:1)** **Vu-Topper RM**

which of given is the magical thing in Prolog?

A. Program partition
B. List Processing
C. Predicate
D. Inference engine

Question No:21 **(Marks:1)** **Vu-Topper RM**

The correct way to write comments in a PROLOG program is:

A. % This is another comment
B. /* This is also a comment */
C. # Consider this a comment
D. // this is a comment

Question No:22 **(Marks:1)** **Vu-Topper RM**

In a PROLOG program, the definitions of predicate sentences or phrases are known as:

A. Facts
B. Inferences
C. Declarations
D. Clauses

Question No:23 **(Marks:1)** **Vu-Topper RM**

How many elements are in the following PROLOG list?[[a,list,of,lists], and, numbers,[1,2,3]]

A. 9

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

B. 2
C. 4
D. 6

Question No:24 **(Marks:1)** **Vu-Topper RM**
When you declare a class object in a JAVA program then:
A. storage is allocated to the object
B. Object is automatically initialized
C. Constructor of a class is called
D. no storage is allocated to the object

Question No:25 **(Marks:1)** **Vu-Topper RM**
While eliminating repeated elements of list in PROLOG, each element should be replaced with:
A. Previous element
B. Next element
C. Blank space
D. Single copy of the same element

Question No:26 **(Marks:1)** **Vu-Topper RM**
The inference mechanism of PROLOG is based upon _____.
A. Forward chaining
B. Back tracking
C. Propositional logic
D. Recursion

Question No:27 **(Marks:1)** **Vu-Topper RM**
In the context of PROLOG language, which problem(s) may mostly occur in backward chaining algorithm?
A. Complexity
B. Readiness
C. Completeness
D. Repetition

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:28 **(Marks:1)** **Vu-Topper RM**

The facts in a PROLOG program must end with:

A. Colon (:)
B. Semicolon (;)
C. Full stop (.)
D. Comma (,)

Question No:29 **(Marks:1)** **Vu-Topper RM**

In the context of Java language, which of following is NOT a correct statement?

A. Abstract class defines only the structure of the class not its implementation
B. Abstract class can be initiated by 'new' operator
C. Abstract class can be inherited
D. Every class containing abstract method must be declared abstract

Question No:30 **(Marks:1)** **Vu-Topper RM**

To sort a list in PROLOG language, we need to:

A. Use the Forward Chaining mechanism
B. Write the sorting algorithm
C. Tell the inference engine of PROLOG that what sorting means
D. Use Dynamic Programming Techniques

In Prolog, a "member(X, T)" predicate is used to check the membership of X in _____.

A. stack
B. symbol
C. class
D. list

Which of the following is treated as an atom and not as a list data type in PROLOG?

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

A. [a, t, o, m]
B. [a]
C. [ ]
D. [a, b, c]

Which of the following is used as a placeholder for a value that is not required in a PROLOG program?
A. Colon (:)
B. Parenthesis
C. Underscore (_)
D. Space

A PROLOG program can have:
A. Exactly one instance of a goal
B. Multiple Goals
C. Even number of goals
D. Odd number of goals

In a PROLOG program, the names of all relationships and objects must begin with:
A. Uppercase letter
B. Dollar sign ($)
C. Lowercase letter
D. Underscore

In a Java program, the storage for an array is allocated when you:
A. create a new class
B. run the program
C. use 'new' operator
D. declare an array

A predicate may have _____ or more arguments.
A. two

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

B. zero
C. three
D. one

_____ has a steep learning curve and suffers from lack of standardization.

A. PROLOG
B. SNOBOL
C. Java
D. C++

The _____ in a PROLOG program has all parameters as constants and it cannot contain any condition.

A. Proposition
B. Predicate
C. Clause
D. Fact

Set membership in Prolog is same as _____ membership.

A. Join
B. Union
C. List
D. Symbol

All the variables in PROLOG clauses/predicates are:

A. Global
B. Strongly typed
C. Local
D. Generic

The 'arraycopy' function in JAVA is a part of:

A. java.util.Scanner
B. java.util.Arrays

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

C. java.io.File
D. java.lang.System

_____ method is used to begin the execution of a thread in Java.
A. start()
B. run()
C. runThread()
D. startThread()

If a class (inheriting an abstract class) does not define all of the functions of an abstract class then it will be known as:
A. Static class
B. Abstract
C. Concrete class
D. A simple class

The legal range of values for byte data type in C# is:
A. 0 to 255
B. -128 to 127
C. 0 to 65535
D. -32768 to 32767

Each class in a Java program can have:
A. Many constructor functions
B. no constructor function
C. Only one constructor function
D. Maximum two constructor functions

Which of the following conversion has to be done explicitly by the programmer in C#?
A. int to long
B. float to double
C. float to int

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

D. int to float

In C#, the order of operator evaluation is:

A. From right to left
B. From left to right
C. Arbitrary
D. Not specified

What would be returned if the following Java code is executed?

```
try {
return 0;
}
finally {
return 2;
}
```

A. 0
B. 2
C. Runtime error
D. Logical error

If x and y are integer variables and z is a Boolean variable then which of the following statement causes compilation error in C#?

A.
```
if(y>x)
{
//some code
}
```
B.
```
if(x>y)
{
//some code
}
```
C.
```
if(z)
{
//some code
```

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

}

D. if(x=y)

{

//some code

The concept of C# jagged array is similar in function to _____

A. Java structs

B. Java Array of Arrays

C. C++ Pointers

D. C++ rectangular Array

Which of the following method in a Java class cannot be changed (overridden) in a subclass?

A. private void radius(){…};

B. public static void area(){…};

C. public void display(){…};

D. public final void result(){…};

Consider the following variable declaration in Java:
Integer x;
Here, the variable 'x' is referred to as:

A. package

B. invalid variable

C. Object of type Integer

D. simple integer variable

C# does not support the conversion of _____ values to integers.

A. Character

B. Boolean

C. Floating Point

D. Decimal

VuTopper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

In Java, constructor functions of classes have the following return type:

A. int
B. No return type
C. void
D. const int

All Java classes (built-in or user-defined) are sub-classes of _____ class.

A. System
B. Thread
C. Object
D. Throwable

C# language is very similar to:

A. C-Language
B. Prolog
C. Delphi
D. Java

The program written in C# compiles to:

A. Object code
B. machine code
C. Source code
D. an intermediate language (IL)

Which of the following is not primitive type in java?

A. byte
B. char
C. array
D. Boolean

Suppose a class named 'Circle' inherits from the class 'Shape'. This can be written in Java as follows:

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

VuTopper RM

For More Help Contact What's app 03224021365

Reload Math Equations

A. class Circle extends Shape{…}
B. class Circle inherits Shape{…}
C. class Circle::Shape{…}
D. class Shape inherits Circle{…}

Following statement in PROLOG is considered as _____.
"unsuitable_for(Person, Drug) :- aggravates(Drug, Condition), suffers_from(Person, Condition)."
Reload Math Equations

A. Variable
B. Fact
C. Rule
D. Goal

What happens when you don't initialize the fields in the constructor of a Java class?
Select the correct option

A. Runtime error occurs
B. Logical error occurs
C. Default values are assigned
D. A compile-time error occurs

In a Java program, which of the following clause will be executed even if no exceptions are found?
Select the correct option

A. throws
B. throw
C. catch
D. finally

VU Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

With programming in _____ we state "what" and not "how".
Select the correct option

A. FORTRAN
B. ALGOL
C. C#
D. PROLOG

which of the following generates readable code which is easy to maintain.
Select the correct option

A. Facts
B. Back tracking
C. Clauses
D. Inference mechanism

Which of the following feature of Java prevents memory leaks and dangling pointers?
Reload Math Equations

A. Operator Overloading
B. Type Checking
C. Multithreading
D. Automatic Garbage Collection

How many public classes can be in a single JAVA source file?
Reload Math Equations

A. 4
B. 1
C. 3
D. 2

Every class in a JAVA program is a part of:
Select the correct option

A. Function

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

B. Structure
C. another class
D. Package

Support for web applications in Java is provided through:
Select the correct option
A. Utilities
B. Applets
C. Interfaces
D. Packages

The Java Bytecode is created by the Java compiler and is stored in ____ file
Select the correct option
A. .sys
B. .class
C. .exe
D. .jvm

The methods that allow two threads to cooperate (or synchronize) with each other in a Java program are:
Select the correct option
A. wait() and run()
B. run() and notify()
C. sleep() and yield()
D. wait() and notify()

What will be the result of following LISP statement?
(> (- 7 6) (+ 4 8))
A. 68
B. -7
C. +4
D. NIL

VU topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

What is optional in the following syntax of 'dotimes' loop and is used to hold computational result?
(dotimes (count n result)
body
)

A. n
B. body
C. count
D. result

Which of the following statement of LISP creates an array of size 5?

A. (make linear-array (5))
B. (setq linear-array (array '(5)))
C. (setf linear-array (make-array '(5)))
D. (setf (make-array '(5)))

Prolog has very powerful _____mechanism.

A. Pointer arithmetic
B. Object oriented
C. String manipulation
D. Inference

To iterate over the list elements one at a time, which of the following looping structure is used in LISP?

A. dotimes
B. foreach
C. dolist
D. while_list

In LISP, _____ function is same as _____function.

A. cdr , cons
B. car , rest

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

C. car , first
D. car , secon

Which of the following is a correct if-statement in LISP?
A. if(score < 66) 'High
B. if(< score 66) 'High
C. if(66 score <) 'High
D. if(score 66 <) 'High

Problem solving in PROLOG is achieved by using:
A. Facts
B. Objects
C. Functions
D. Streams

PROLOG supports the _____ programming paradigm.
A. Functional
B. Declarative
C. Object Oriented
D. Aspect Oriented

Everything in LISP is considered as a _____.
A. Class
B. Object
C. Symbol
D. Function

To create a two-dimensional array in LISP, _____ index values are used.
A. Two
B. Four
C. Six
D. Three

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

In LISP, following statement returns the difference of the two lists.

A. (L1 difference L2)
B. (set-difference L1 L2)
C. (Difference L1 L2)
D. (L1 Difference L2)

We have extensive use of _____ in LISP.

A. while loop
B. recursion
C. for loop
D. switch statement

Which of the following is not required to write a program in PROLOG?

A. Algorithm
B. Logical Relationship
C. Rule
D. Fact

List items can be iterated over using _____ statement in LISP.

A. iList
B. looplist
C. dolist
D. iterate

A query given to a PROLOG system:

A. is a pattern matching exercise
B. does not involve database
C. is treated an object
D. cannot contain variables

_____ LISP iteration may also change global variables as a side effect.

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

A. list
B. time
C. dotime
D. dolist

Array elements can be accessed by using _____ function in LISP.
A. getf
B. aref

The function that is used to remove all properties of a symbol in LISP is:
A. terminate-all
B. remprop
C. NULLP
D. REMOVE

Which of the following statement in LISP is used to list all properties of symbol ‘k’?
A. >(obtain all ‘k)
B. >(symbol-plist ‘k)
C. >(get ‘k)
D. >(get all ‘k)

Prolog database is based upon _____.
A. Facts and queries
B. Facts and rules
C. Facts
D. Rules and queries

Which of the following predicate of LISP is used to test whether the operand is a number or not?
A. symbolp
B. isNumber
C. number

VuTopper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What’s app 03224021365

D. atom

Identify the correct output of following LISP statements:

>(setq Y '(L M N))

>(member 'm Y)

A. (m L M N)

B. (M N)

C. (L m N)

D. (m)

Which of the following function in LISP determines whether ‘m’ is a member of list ‘T’ or not?

A. (defun member (m T))

B. (eq member (T, m))

C. (cond ((member T) m)

D. (isMember (m, T))

What is the objective of following statement in LISP?

>(setf (get 'w 'age) 20)

A. It simply sets the value of ‘get’, ‘w’ and ‘age’ as 20

B. It gets the age of symbol w and assigns it to setf after 20 milliseconds

C. It assigns value 20 to setf and gets the values of variables w and age

D. It sets the age property of symbol w as 20

In LISP, _____ is the main tool used for iteration.

A. Do-While Loop

B. For Loop

C. While Loop

D. Recurs

The first programming language to support Recursion was _____.

A. LISP

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

Vu Topper RM

For More Help Contact What’s app 03224021365

B. FORTRAN
C. ADA
D. COBOL

The correct syntax of 'setf' function in LISP is:
A. (setf (symbol attribute value) object)
B. (setf (object value) attribute)
C. (setf (get object attribute) value)
D. (setf (object attribute) value)

Array indexes in LISP can be:
A. Characters
B. Floating point numbers
C. Integers
D. any discrete type

How many times the following loop in LISP will be executed?
(dotimes (count n result)
body
)
A. n/2
B. n-1
C. n+1
D. n

Function in LISP is itself a _____.
A. Datatype
B. Object
C. List
D. Variable

In LISP programming language, if we want to test that whether "w" is a list or not then which of the following predicate in used?

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

A. ifList
B. ?list
C. isList
D. listp

Which of the following is a correct variable name in PROLOG?
A. roll_No.
B. Age
C. marks
D. percentage

In LISP, there is no concept of _____ .
A. Functions
B. Sequential statements
C. Symbols
D. Strings

Disjunction in Prolog is through _____and conjunction is through _____.
A. Coma (,), OR
B. Dot(.) , OR
C. **OR, coma (,)**

Array indexes in LISP can be:
A. Integers
B. any discrete type
C. Floating point numbers
D. Characters

In Prolog, we specify _____and do not specify _____.
A. Problem , Solution
B. Result , Inputs

VU Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

C. Facts, Problem
D. Result , Outputs

What will be the output of following LISP expression?
>(/ 5.0 2)
A. 5/2
B. 2.5
C. 2/5
D. 0.4

Function in LISP is itself a _____.
A. Variable
B. Object
C. Datatype
D. List

The correct way to write comments in a PROLOG program is:
/* This is also a comment */
% This is another comment

The correct syntax of "if statement" in LISP is:
A. (if <test> <then> <else>)
B. (if <else> <then> <test>)
C. (if <then> <test> <else>)
D. (if <else> <test> <then>)

The property list in LISP is a substitute of _____.
A. Java interfaces
B. C/C++ pointer
C. C/C++ structure
D. Compiler

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

The inference mechanism of PROLOG is based upon _____.

A. Back tracking
B. Forward chaining
C. Recursion
D. Propositional logic

Disjunction in Prolog is through _____and conjunction is through _____.

A. Coma (,), OR
B. Dot(.) , OR
C. OR, coma (,)
D. OR, Dot(.)

The main feature of PROLOG language is its ability to handle and process _____.

A. Symbols
B. Classes
C. Objects
D. Functions

The facts in a PROLOG program must end with:

A. Colon (:)
B. Comma (,)
C. Full stop (.)
D. Semicolon (

Which of the following are the types of constants in PROLOG?

A. atoms and numbers
B. single and decimal
C. float and numbers
D. short and char

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Each axiom in PROLOG program is:

A. an object
B. Conditional statement
C. a function
D. Horn clause

Which of the following statement in LISP is used to list all properties of symbol ‘k’?

A. >(obtain all ‘k)
B. >(get ‘k)
C. >(get all ‘k)
D. >(symbol-plist ‘k)

The first programming language to support Recursion was _____.

A. ADA
B. FORTRAN
C. COBOL
D. LISP

Which of the following statement returns the union of the two lists in LISP?

A. >(L1 union L2)
B. >Union L1
C. >(union L1 L2)
D. >(L1 UNION L2)

LISP was the first programming language that introduced the concept of _____.

A. Dynamic typing
B. Arrays
C. Trees
D. Pointers

VuTopper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What’s app 03224021365

How many element(s) are there in LISP list (a (b c))?

A. 4
B. 3
C. 2
D. 1

Question No:0_1 (Marks:1) Vu-Topper RM

In a PROLOG program, the definitions of predicate sentences or phrases are known as:

A. Inferences
B. Facts
C. Declarations
D. Clauses

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

1. In JavaScript, navigator is a _____object

Select the correct option

a. Browser

b. User defined

c. Built-in

d. Document

2. Which of the following type of numbers are not supported by PHP?

Select the correct option

a. Real Numbers

b. Unsinged Integers

c. Complex Numbers

d. Singed Integers

3. Which of the following language is used for server-side scripting?

select the correct option

a. PHP

b. C#

c. Ada

d. C++

4. The model in JavaScript provides access to the contents of the browser window

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Select the correct option

a. DOM

b. BOM

c. ROM

d. COM

5. The code written in PHP is returned to the web browser as:

Select the correct option

a. Applets

b. Plain HTML

c. Shell scripts

d. CSS flexbox

6. Which of the given is used before the declaration of variable in PHP?

Select the correct option

a. #sign

b. $ sign

c. ? sign

d. @sign

7. An in PHP is an ordered map.

Select the correct option

a. string

b. array

c. queue

d. stack

8. In the 'break' statement may have an optional parameter or argument.

VU Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Select the correct option

a. C#

b. C/C++

c. Java

d. PHP

9. In PHP 'switch' structure, the starts or implements an implicit loop.

Select the correct option

a. Break Statement

b. Continue Statement

c. For Loop

d. Return Statement

10. In JavaScript, "with" statement is an alternative of

select the correct option

a. Multiple document.write statements

b. While statement

c. Single document.write statement

d. Union statement

11. In how many places a javascript code can be placed?

Select the correct option

a. 3

b. 2

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

c. 4

d. 6

12. If an integer variable is not initialized in PHP then its default value will be:

Select the correct option

a. Zero

b. False

c. NULL

d. One

13. In PHP, if a number is beyond the bounds of the integer type, then it will be interpreted as a instead.

Select the correct option

a. string

b. short

c. float

d. long

14. In JavaScript, which of the given provides access to the contents of browser window?

select the correct option

a. BOM

b. ROM

c. DOM

d. COM

15. The scripts written in PHP are executed by:

Select the correct option

VuTopperRM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

a. Web browser
b. Java
c. Applet Client machine
d. Web Server

16. Arrays in JavaScript are based.
Select the correct option
a. Length
b. One
b. Index Location
d. Zero Index

17. Classes and objects of PHP are similar to
Select the correct option
a. Classes and objects of Basic
b. Classes and objects of C
c. Classes and objects of Java
d. Classes and objects of C++

18. Which of the following type of numbers are not supported by PHP?
select the correct option
a. Complex Numbers
b. Unsinged Integers
c. Real Numbers
d. Singed Integers

19. To dynamically generate a web page, which of the following programming language is most suitable?

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

the correct option

a. PHP

b. C++

c. Ada

d. Prolog

20. The scripts written in PHP are executed by:

Select the correct option

a. Web Server

b. Web browser

c. Client machine

d. Java Applet

21. Which of the given is used before the declaration of variable in PHP?

Select the correct option

a. ? sign

b. @sign

c. #sign

d. $ sign

22. The data type of variable in PHP is automatically determined by its:

select the correct option

a. Name

b. Location

c. Size

d. Value

23. an object that describes the basic characteristics of the browser, notably its type and version. Select the correct option

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

a. Window

b. Navigator

c. Document

d. Location

24. How many <script> tags can be used in the <head> element?

Select the correct option

a. One

b. Many

c. Zero

d. Two

25. Which of the following language is used for server-side scripting?

Select the correct option

a. C#

b. Ada

c. C++

d. PHP

26. An in PHP is an ordered map.

Select the correct option

a. queue

b. array

c. stack

d. string

27. In Strings and numeric values are inter convertible

Select the correct option

a. C#

b. C, C++

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

c. PHP
d. Java

28. In JavaScript, "with" statement is an alternative of
Select the correct option
a. While statement
b. Union statement
c. Multiple document.write statements
d. Single document.write statement

29. In PHP switch structure, the starts or implements an implicit loop.
Select the correct option
a. Return Statement
b. Break Statement
c. Continue Statement
d. For Loop

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 6 of 10 (Start time: 10:39:13 AM, 19 July 2023) **Total Marks:**

PHP stands for _____ .

Select the correct option

- ○ PHP: Home Preprocessor
- ● PHP: Hypertext Preprocessor
- ○ PHP: Hypertext Page
- ○ PHP: Home Page

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 7 of 10 (Start time: 10:39:36 AM, 19 July 2023) **Total Marks:** 1

In JavaScript, navigator is a _____object.

Select the correct option

○	User defined
●	Browser
○	Document
○	Built-in

CS508 - Modern Programming Languages (Quiz 4) Quiz Start Time: 10:36 AM, 19 July 2023

Question # 10 of 10 (Start time: 10:40:55 AM, 19 July 2023) Total Marks: 1

To dynamically generate a web page, which of the following programming language is most suitable?

Select the correct option

Reload Math Equations

- Ada
- C++
- Prolog
- PHP

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 9 of 10 (Start time: 10:40:33 AM, 19 July 2023) **Total Marks:** 1

In _____, Strings and numeric values are inter convertible

Select the correct option

○	C/C++
○	Java
○	PHP
●	C#

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 5 of 10 (Start time: 10:12:13 AM, 19 July 2023) **Total Marks:** 1

To dynamically generate a web page, which of the following programming language is most suitable?

Select the correct option

Reload Math Equations

○	Prolog
○	PHP
○	C++
○	Ada

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 202**

Question # 1 of 10 (Start time: 10:10:14 AM, 19 July 2023) **Total Marks:**

In JavaScript, navigator is a _____object.

Select the correct option

- ○ User defined
- ◉ Browser
- ○ Document
- ○ Built-in

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 2 of 10 (Start time: 10:11:00 AM, 19 July 2023) **Total Marks:** 1

The division of two integers (i.e. 7/2) in PHP generates a/an:

Select the correct option

Reload Math Equations

- (●) Floating point number
- ( ) Integer
- ( ) Exception
- ( ) Runtime error

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 4 of 10 (Start time: 10:11:56 AM, 19 July 2023) **Total Marks:**

Arrays in JavaScript are _____ based.

Select the correct option

- ○ One Index
- ○ Length
- ● Zero Index
- ○ Location

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 3 of 10 (Start time: 10:11:28 AM, 19 July 2023) **Total Marks:**

Which of the given is used before the declaration of variable in PHP?

Select the correct option

- ○ @ sign
- ○ # sign
- ● $ sign
- ○ ? sign

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 202**

Question # 6 of 10 (Start time: 10:12:43 AM, 19 July 2023) **Total Marks**

In _____, the 'break' statement may have an optional parameter or argument.

Select the correct option

○	Java
○	C#
○	C/C++
●	PHP

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 8 of 10 (Start time: 10:13:31 AM, 19 July 2023) **Total Marks:**

In PHP 'switch' structure, the _____ starts or implements an implicit loop.

Select the correct option

- (●) Continue Statement
- ( ) Break Statement
- ( ) Return Statement
- ( ) For Loop

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 7 of 10 (Start time: 10:13:08 AM, 19 July 2023) **Total Marks: 1**

Which operator is used for concatenation in JavaScript?

Select the correct option

- (●) +
- ( ) |
- ( ) $
- ( ) dot(.)

CS508 - Modern Programming Languages (Quiz 4) Quiz Start Time: 10:16 AM, 19 July 2023

Question # 3 of 10 (Start time: 10:17:48 AM, 19 July 2023) Total Marks: 1

The resultant value of variable 'x' in JavaScript statement var x = "5" - "2" ; will be_____.

Select the correct option

○	52
○	"5"-2"
●	3
○	5-2

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 10 of 10 (Start time: 10:14:18 AM, 19 July 2023) **Total Marks:** 1

The resultant value of variable 'x' in JavaScript statement var x = "5" - "2" ; will be_____.

Select the correct option

○	5-2
●	3
○	52
○	"5"-2"

CS508 - Modern Programming Languages (Quiz 4) Quiz Start Time: 10:16 AM, 19 July 2023

Question # 2 of 10 (Start time: 10:17:21 AM, 19 July 2023) Total Marks: 1

In JavaScript, which of the given provides access to the contents of browser window?

Select the correct option

○	COM
○	ROM
○	BOM
●	DOM

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 1 of 10 (Start time: 10:16:56 AM, 19 July 2023) **Total Marks:**

How many <script> tags can be used in the <head> element?

Select the correct option

○	Two
○	Zero
○	One
●	Many

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:10 AM, 19 July 2023**

Question # 9 of 10 (Start time: 10:13:55 AM, 19 July 2023) **Total Marks:** 1

The code written in PHP is returned to the web browser as:

Select the correct option

Reload Math Equations

- (●) Plain HTML
- ( ) Shell scripts
- ( ) Applets
- ( ) CSS flexbox

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 202**

Question # 7 of 10 (Start time: 10:19:22 AM, 19 July 2023) **Total Marks**

PHP stands for _____ .

Select the correct option

◉	PHP: Hypertext Preprocessor
○	PHP: Home Preprocessor
○	PHP: Hypertext Page
○	PHP: Home Page

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 8 of 10 (Start time: 10:20:00 AM, 19 July 2023) **Total Marks:**

The scripts written in PHP are executed by:

Select the correct option

Reload Math Equations

- (●) Web Server
- ( ) Java Applet
- ( ) Client machine
- ( ) Web browser

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 6 of 10 (Start time: 10:19:05 AM, 19 July 2023) **Total Marks:** 1

Which of the following language is used for server-side scripting?

Select the correct option

Reload Math Equations

○	Ada
○	C#
○	C++
●	PHP

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 4 of 10 (Start time: 10:18:14 AM, 19 July 2023) **Total Marks:**

Which of the given operator is used to return a reference from a function in PHP?

Select the correct option

- (●) &
- ( ) &&
- ( ) Dot
- ( ) $

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 9 of 10 (Start time: 10:20:26 AM, 19 July 2023) **Total Marks:**

Which of the given is used before the declaration of variable in PHP?

Select the correct option

○	@ sign
○	# sign
○	? sign
●	$ sign

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 2023**

Question # 10 of 10 (Start time: 10:20:54 AM, 19 July 2023) **Total Marks:**

To dynamically generate a web page, which of the following programming language is most suitable?

Select the correct option

Reload Math Equations

◉	PHP
○	Prolog
○	C++
○	Ada

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 3 of 10 (Start time: 10:37:40 AM, 19 July 2023) **Total Marks:**

"with" statement in JavaScript is an alternative of _____.

Select the correct option

○	Multiple 'document.read' Statements
○	Single 'document.read' Statement
●	Multiple 'document.write' Statements
○	Single 'document.write' Statement

CS508 - Modern Programming Languages (Quiz 4) Quiz Start Time: 10:36 AM, 19 July 2023

Question # 4 of 10 (Start time: 10:38:10 AM, 19 July 2023) **Total Marks:**

Which of the given is used before the declaration of variable in PHP?

Select the correct option

- ? sign
- # sign
- $ sign
- @ sign

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:16 AM, 19 July 202**

Question # 5 of 10 (Start time: 10:18:37 AM, 19 July 2023) **Total Marks:**

The _____model in JavaScript provides access to the contents of the browser window.

Select the correct option

○	BOM
○	ROM
◉	DOM
○	COM

CS508 - Modern Programming Languages (Quiz 4) Quiz Start Time: 10:36 AM, 19 July 2023

Question # 1 of 10 (Start time: 10:36:35 AM, 19 July 2023) **Total Marks:** 1

_____ , an object that describes the basic characteristics of the browser, notably its type and version.

Select the correct option

- ○ Document
- ○ Location
- ◉ Navigator
- ○ Window

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 202**

Question # 2 of 10 (Start time: 10:36:57 AM, 19 July 2023) **Total Marks**

In JavaScript, "with" statement is an alternative of _____.

Select the correct option

○	While statement
●	Multiple document.write statements
○	Single document.write statement
○	Union statement

CS508 - Modern Programming Languages (Quiz 4) **Quiz Start Time: 10:36 AM, 19 July 2023**

Question # 5 of 10 (Start time: 10:38:46 AM, 19 July 2023) **Total Marks:**

The _____model in JavaScript provides access to the contents of the browser window.

Select the correct option

- (●) DOM
- ( ) ROM
- ( ) COM
- ( ) BOM

– Modern Programming Languages (Quiz 4) Quiz Start Time: 10:36 AM, 19 Ju

on # 8 of 10 (Start time: 10:39:50 AM, 19 July 2023) Total

data type of variable in PHP is automatically determined by its:

the correct option

Reload Math Equ

- Size
- Value
- Location
- Name

Visit My YouTube Channel
For Subjective and More
Important Files
Channel Name = #VuTopperRM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365