CS511 WEB ENGINEERING

FINAL TERM PREPERATION

Most important MCQ's & Questions

Recorded with iTop Screen Recorder

WEEK 7 TO 16

Learning with universe

In php, string can be concatenated using----------

- ".." operator
- "~" operator
- "->" operator
- "." operator

In case of --------- method to send form data, the field of form and their values are sent through query string as part of http header.

- Post
- Get
- Send
- Dispatch

The exact syntax of jQuery's get() function is:
Note: the three dots "…" in option represent parameter.

Recorded with iTop Screen Recorder

- JGet(…)
- $_Get[…];
- $->get(…);
- $.get(…);

The JQuery's "serialize()" method can be used;

- One any javascript function to call it from any part of web page
- On any DOM element to convert it into a binary string
- On DOM form element to encode it into a query string
- On any HTML web page to include external jquery script into the page

Consider the following code written using jquery:
$("p.warning").html("no warning")
When the obove line is executed.

- Text of all the <p> tags having style named "warning" will be updated to "no warning"
- Text of all the <p> tags having tag name "warning" will be updated to "no warning"
- Text of all the <p> tags having id "warning" will be updated to "no warning"
- Text of all the <p> tags having class "warning" will be updated to "no warning"

The function var_dump($expression) can be used for:

- Initializing value of $expression
- duplicating value of $expression
- Displaying structured expression such as type and value of $expression
- deleting value of $expression

In php, by convention:

- The constants are written using capital letters
- Constants name should start with a double underscore (_ _)
- Constants name should start with a single underscore (_)
- The constants are written using small letters

------- is executed on the server side whereas------- on client side.

- Javascript, CSS
- Javascript, PHP
- PHP, javascript
- CSS, PHP

Recorded with iTop Screen Recorder

Which of the following is not NOT of the valid JQuery manipulators?

- attr()
- pttrn()
- text()
- html()

Which of the following is NOT server side technology?

- Javascript
- PHP

In PHP, the super global array for storing session's data is _____
Select the correct option

- $_LOCAL
- $_SESSION_POOL
- $_BUFFER
- $_SESSION

Recorded with iTop Screen Recorder

Suppose we want to check that the variable named "USER" is set (or not) in session. Identify the correct statement for this purpose.
Select the correct option

- if(!$_SESSION_SET['USER']) {}
- if($_SESSION_SET['USER']) {}
- if(notset($_SESSION['USER'])) {}
- if(isset($_SESSION['USER'])) {}

HTML5 gives us web storage to store data on client's machine in the form of:
Select the correct option

- Javascript variables
- CSS classes
- Key/value pair
- DOM tree

In context of Web Application Design, the 3-layer Model comprises of:
Select the correct option

- Browser Layer, HTTP Layer, Server Layer
- Presentation Layer, Business Layer, Data Layer
- HTML Layer, Javascript Layer, CSS Layer
- Server Layer, HTTP Layer, Database Layer

Learning with universe
Recorded with iTop Screen Recorder

Cookies are a way to store data ____
Select the correct option

- On ISP's in-proc server
- In javascript
- In SSL server memory
- On client side

Recorded with iTop Screen Recorder

By maintaining the sessions, the server can track the _____
Select the correct option

- PHP Validation Regex
- States of the user
- JavaScript Routing Mechanism
- CSS Interactive states

- JavaScript Routing Mechanism
- CSS Interactive states

Recorded with iTop Screen Recorder

In PHP a user session on server is started using:
Select the correct option

- invoke_session()
- session_begin()
- session_start()
- execute_session()

Suppose, An event is triggered then the browser will construct a/an _____ that contains information about the event.

Event object

You can define an entire event handling function within the markup. This is highly recommended.

False

Recorded with iTop Screen Recorder

User cannot initiate events.

False

dblclick, mousedown and mouseup are type of _____.

Mouse event

In context of AJAX, the _____ event is fired on a HTML document when the load state of the page's content has changed.
Select the correct option

- onreadystatechange
- onstatusupdate
- onstatuschange
- Onstateupdate

AJAX requests are initiated _____
Select the correct option

- On ISP's in-proc server
- In SSL server memory
- In CSS classes
- On client side

Recorded with iTop Screen Recorder

Event triggered by browser cannot be handled.

False

Events triggered by devices like touch screens are type of _____.

Touch event

Which of the following is not a form event?

Formdate

The _____ occurs when the element loses focus.

Blur event

<input type="email" id="email" name="email">

Identify the validation level of the above code.

HTML LEVEL

Learning with universe
Recorded with iTop Screen Recorder

JQuery can be included in JavaScript through the following piece of code.

<script src="https://code.jquery.com/jquery-3.6.0.min.js">

Universal selector matches all elements.

$("*")

Recorded with iTop Screen Recorder

Which sign does jQuery use as a shortcut for "jQuery"?
Which of the following sign does JQuery use as an alias of JQuery?

$()

Ability of a website or web application to function across different browsers is called ____

Cross browser funcitonality

4. fixed
5. sticky

The ---------- method removes event handlers from selected elements. This method can remove all or selected event handlers, or stop specified functions from running when the event occurs.

unbind()

The jQuery ---------- event is used to attach one or more event handlers for selected elements from a set of elements. It specifies a function to run when the event occurs.

bind()

Recorded with iTop Screen Recorder

---------- is when you use JavaScript to add, remove, and modify elements of a website. It is very common in web development.

DOM manipulation

The jQuery---------- method is used to create custom animations.

animate()