

DOWNLOAD MIDTERM

PAST PAPERS BY WAQAR SIDDHU

More in PDF From

VU Answer

Get All Solutions.



ATM was designed for _____ and use a _____

Answer (Please select your correct option)

☐

LANs, Connectionless service paradigm

☐

WANs, Connectionless service paradigm

☐

Both LANs and WANs, Connectionless service paradigm

☐

Both LANs and WANs, Connection-oriented service paradigm

correct

Made By: Waqar Siddhu



In Point-to-Point type of topologies there are two topologies _____.

Answer (Please select your correct option)



Tree and Ring



Star and Ring



Star and Tree



Bus and Mesh

correct

Made By: Waqar Siddhu



In -----, network occupies larger areas like cities & countries.

Answer (Please select your correct option)

LAN



WAN



correct

MAN



CAN



Made By: Waqar Siddhu



Hardware that calculates a CRC uses two simple components.

Answer (Please select your correct option)



AND unit with XOR unit



Shift register with XOR unit

correct



Shift register with AND unit



Shift register with shift XOR unit

Made By: Waqar Siddhu



A network that uses a ----- usually consist of a single long cable to which computers attach.

Answer (Please select your correct option)

☐ Star Topology

☐ Ring Topology

☒ Bus Topology

☐ Tree Topology

correct

Made By: Waqar Siddhu



A ----- provides mechanism that a customer can use to set a physical address.

Answer (Please select your correct option)



Static addressing scheme



Configurable addressing scheme

correct



Dynamic addressing scheme



Masking

Made By: Waqar Siddhu



Formally named _____ informally known as the thick wire Ethernet or Thick net.

Answer (Please select your correct option)



10 Base 2



10 Base 5



10 Base T

correct



100 Base T

Made By: Waqar Siddhu



Preamble field in Ethernet frame consist of _____ bits.

Answer (Please select your correct option)

☐ 8

☐ 32

☐ 48

☐ 64

correct



A bridge functions in the _____ layer(s).

Answer (Please select your correct option)

☐ Physical

correct

☐ Data link

☐ Network and Data link

☐ Physical and Data link



Generally a Bridge is used to perform _____.

Answer (Please select your correct option)

☐ Extend a LAN, Filter and Forward a packet

☐ Routing

☐ Filter and Forward a frame

☐ Filter and Forward a packet

correct



_____ technology can support both LAN and WAN connections.

Answer (Please select your correct option)

☐

Frame relay

☐

Ethernet

☐

SMDS

☐

ATM

correct

Made By: Waqar Siddhu



One repeater _____, two repeaters _____ the maximum cable length limitation.

Answer (Please select your correct option)



Square root, Cube root



Double, Triple

correct



Triple, Quad



Double, Quad



_____ is used for compressed audio and video where the data rate is related to level of compression.

Answer (Please select your correct option)



Constant Bit Rate (CBR) service



Variable Bit Rate (VBR) service



Available Bit Rate (ABR) service



Uniform Bit Rate (UBR) service

correct

Made By: Waqar Siddhu



_____ is used for ordinary data.

Answer (Please select your correct option)



Available Bit Rate (ABR) service

correct



Uniform Bit Rate (UBR) service



Constant Bit Rate (CBR) service



Variable Bit Rate (VBR) service

Made By: Waqar Siddhu



_____ sends a message to a remote computer and reports whether the computer responds.

Answer (Please select your correct option)

☐

Telnet

☒

Ping
Ping

correct

☐

Traceroute

☐

ICMP

Made By: Waqar Siddhu



A network with throughput T and delay D would have a total no of _____ bits in transit at any time.

Answer (Please select your correct option)



$T + D$



$T \times D / \text{Unit Time}$



T / D



$T \times D$

correct

Made By: Waqar Siddhu



A network that permits many sources to take turns accessing a shared communication resource is providing a form of _____.

Answer (Please select your correct option)



Phase Division Multiplexing



Time Division Multiplexing



Frequency Division Multiplexing



Wave Division Multiplexing

Made By: Waqar Siddhu



A network which is based on packets uses a computer which may have _____, memory and _____ for switching.

Answer (Please select your correct option)



Administration Rights, Algorithm



Source address, Destination address



Interface, Program



Input, Output



In direct point to point communication adding the N^{th} computer requires _____ new connections.

Answer (Please select your correct option)

☐

$N(N - 1)$

☐

N^2

☐

$N - 1$

☐

$(N^2 - N)/2$

correct

Made By: Waqar Siddhu



Computers attached to an ethernet use _____ in which a computer waits for the Ether to be idle before transmitting a frame.

Answer (Please select your correct option)

☐ CSMA/CD

correct

☐ CSMA/CA

☐ Token Passing

☐ Round Robin

Made By: Waqar Siddhu



ATM was designed for _____ and use a _____

Answer (Please select your correct option)

- ☐ LANs, Connectionless service paradigm
- ☐ WANs, Connectionless service paradigm
- ☐ Both LANs and WANs, Connectionless service paradigm
- ☐ Both LANs and WANs, Connection-oriented service paradigm



In broadcast topology there are two categories_____.

Answer (Please select your correct option)

☐ Satellite/Radio and Ring

☐ Satellite/Radio and Star

☐ Ring and star

☐ Satellite/Radio

correct

Made By: Waqar Siddhu

----- have advantages arisen from the size and ease of computation.

Answer (Please select your correct option)

☐ CRC

☐ Parity

☒ Checksums

correct

☐ VRC



When an application----- data, it makes a copy of the data available to all other computers on the network.

Answer (Please select your correct option)

☐ Broadcasting

☐ Multicasting

correct

☐ Unicasting

☐ Anycasting

Made By: Waqar Siddhu



Basic LAN technologies such as Ethernet, Token Ring, and FDDI use a _____.

Answer (Please select your correct option)

- ☐ Connectionless service paradigm
- ☐ Connection-oriented service paradigm
- ☐ Both Connectionless and Connection-oriented service paradigm
- ☐ Connection-oriented service paradigm without acknowledgment

correct



If the sending computer crashes before transmitting a complete frame, the _____ will not arrive and the receiver will know that the frame is _____.

Answer (Please select your correct option)

☐ soh, complete

☐ soh, incomplete

☐ eot, incomplete

☐ eot, complete

correct



----- was especially most concerned about the lack of highly powered computers.

Answer (Please select your correct option)

☐ ARPA

correct

☐ IEEE

☐ EIA

☐ Goverment

Made By: Waqar Siddhu



"Frame type" field of the header consists of _____ bits.

Answer (Please select your correct option)

8



10



16



32



correct

Made By: Waqar Siddhu



Virtual Circuit connection identifier occupies _____ bits.

Answer (Please select your correct option)

☐ 16

correct

☐ 24☐ 32☐ 8



_____ senses a signal on a cable and then transmits an amplified copy of the signal.

Answer (Please select your correct option)



Bridge



Hub



Transceiver



Repeater

correct

Made By: Waqar Siddhu



One repeater _____, two repeaters _____ the maximum cable length limitation.

Answer (Please select your correct option)

☐ Square root, Cube root

☒ Double, Triple

correct

☐ Triple, Quad

☐ Double, Quad



A Bridge forwards or filters a frame by comparing the information in its address table to the frame's _____.

Answer (Please select your correct option)

☐ Layer 2 source address

☐ Layer 3 source address

☒ Layer 2 destination address

☐ Layer 3 destination address

correct



A network that permits many sources to take turns accessing a shared communication resource is providing a form of _____.

Answer (Please select your correct option)

☐ Phase Division Multiplexing

☐ Time Division Multiplexing

☐ Frequency Division Multiplexing

☐ Wave Division Multiplexing



No error detection scheme is perfect because transmission errors can affect _____.

Answer (Please select your correct option)



Data



Additional Information



Additional information & data



Transmission medium

correct

Made By: Waqar Siddhu

LAN that uses ATM technology has a _____.

Answer (Please select your correct option)

☐ Star topology

correct

☐ Bus topology

☐ Ring topology

☐ Mesh topology

Made By: Waqar Siddhu



FDDI can transmits data at a rate of _____.

Answer (Please select your correct option)



100 million bits per second

correct



10 million bits per second



1000 million bits per second



3 million bits per second

The next hop to which a packet is sent depends only on_____.

Answer (Please select your correct option)

☐ Packet's destination

correct

☐ Packet's original source

☐ Path the packet has taken

☐ Routed Protocol



Most WAN systems include a mechanism that can be used to eliminate the common case of duplication routing is called_____.

Answer (Please select your correct option)

☐ Dynamic route

☐ Hierarchal address

☐ Default route

☐ Shortest path

correct

Made By: Waqar Siddhu



_____ in which delay among packets can vary.

Answer (Please select your correct option)

☐ Virtual Private Network

☐ Isochronous Networks

☐ Asynchronous Networks

☐ Synchronous Networks



A typical port on an ATM switch operates at _____ or higher.

Answer (Please select your correct option)

☐ OC-2 speed (155Mbps)

☐ OC-3 speed (100Mbps)

☒ OC-3 speed (155Mbps)

☐ OC-3 speed (155Gbps)

correct

Made By: Waqar Siddhu



In -----, network occupies the smaller area like a room a floor or a building

Answer (Please select your correct option)

LAN



correct

WAN



MAN



PAN



Made By: Waqar Siddhu



A network that uses a ----- usually consist of a single long cable to which computers attach.

Answer (Please select your correct option)

☒ Bus Topology

correct

☐ Tree Topology

☐ Star Topology

☐ Ring Topology



A network uses a ----- if all computers attach to a central point

Answer (Please select your correct option)

☒ Star Topology

correct

☐ Ring Topology

☐ Bus Topology

☐ Mesh Topology



A----- provides mechanism that automatically assigns a physical address to a station when the station first boots.

Answer (Please select your correct option)



Static addressing scheme



Configurable addressing scheme



Dynamic addressing scheme



Dynamic Host Configuration

correct

Made By: Waqar Siddhu



----- was especially most concerned about the lack of highly powered computers.

Answer (Please select your correct option)

☐ ARPA

correct

☐ IEEE

☐ EIA

☐ Goverment



A bridge functions in the _____ layer(s).

Answer (Please select your correct option)

☐ Physical

correct

☐ Data link

☐ Network and Data link

☐ Physical and Data link



Which of the following is not used to extend LAN ?

Answer (Please select your correct option)

☐

Bridge

☐

Repeater

☐

Fiber modem

☐

Router

correct

Made By: Waqar Siddhu



The working of connection-oriented service for networking is similar to the _____.

Answer (Please select your correct option)

☐ Ethernet

☒ Telephone

☐ IP

☐ UDP

correct



_____ senses a signal on a cable and then transmits an amplified copy of the signal.

Answer (Please select your correct option)

☐ Repeater

correct

☐ Bridge

☐ Hub

☐ Transceiver



Unlike Frame Relay and ATM, SMDS (Switched multi-megabit Data service) offers_____.

Answer (Please select your correct option)

- ☐ Connectionless service paradigm
- ☐ Connection oriented service paradigm
- ☐ Both Connectionless and Connection-oriented service paradigm
- ☐ Stateless Connection oriented service paradigm

correct



A Bridge forwards or filters a frame by comparing the information in its address table to the frame's _____.

Answer (Please select your correct option)

☐ Layer 2 source address

☐ Layer 3 source address

☒ Layer 2 destination address

☐ Layer 3 destination address

correct



ATM is designed to work on_____.

Answer (Please select your correct option)

☐ Twisted Pair

☐ Coaxial

☐ Radio Frequency

☐ Fiber

correct

Made By: Waqar Siddhu



_____ identifies intermediate computers along a path to remote destination

Answer (Please select your correct option)

☐ Ping

☒ Traceroute

☐ ICMP

☐ OSPF

correct



_____ computes shortest paths in a graph by using weights on edges as a measure of distance.

Answer (Please select your correct option)



Greedy Algorithm



Distance vector Algorithm



Dijkstra's algorithm



Binary Search Algorithm

correct



_____ has no way to determine the cause of the problem.

Answer (Please select your correct option)

☐ ICMP

☐ ARP

☐ Ping

☐ Traceroute

correct

Made By: Waqar Siddhu



A network that permits many sources to take turns accessing a shared communication resource is providing a form of _____.

Answer (Please select your correct option)



Phase Division Multiplexing



Time Division Multiplexing



Frequency Division Multiplexing



Wave Division Multiplexing



No error detection scheme is perfect because transmission errors can affect _____.

Answer (Please select your correct option)

☐ Additional Information

☐ Additional information & data

☐ Transmission medium

☐ Data

correct



Computers attached to an ethernet use _____ in which a computer waits for the Ether to be idle before transmitting a frame.

Answer (Please select your correct option)

☐ CSMA/CD

correct

☐ CSMA/CA

☐ Token Passing

☐ Round Robin

Made By: Waqar Siddhu



Most WAN systems include a mechanism that can be used to eliminate the common case of duplication routing is called_____.

Answer (Please select your correct option)

☐ Dynamic route

☐ Hierarchal address

☒ Default route

☐ Shortest path

correct



A typical port on an ATM switch operates at _____ or higher.

Answer (Please select your correct option)

☐ OC-2 speed (155Mbps)

☐ OC-3 speed (100Mbps)

☒ OC-3 speed (155Mbps)

☐ OC-3 speed (155Gbps)

correct

In _____, network occupies the smaller area like a room, a floor or a building.

Answer (Please select your correct option)

☐ LAN

correct

☐ WAN

☐ MAN

☐ Wireless WAN

Made By: Waqar Siddhu

In which type of network topology, computers are connected to a central device?

Answer (Please select your correct option)

☐ Ring

correct

☐ Mesh

☐ Bus

☐ Star

Made By: Waqar Siddhu

The term _____ refers to the general concept of a small block of data in a computer network.

Answer (Please select your correct option)

☐ Packet

correct

☐ Byte

☐ Cell

☐ Information

Made By: Waqar Siddhu

_____ is the scheme, which is designed to help in detecting transmission errors by sending one extra bit of information with each character.

Answer (Please select your correct option)

☐ Parity checking

correct

☐ Checksums

☐ CRC

☐ LRC

Made By: Waqar Siddhu

_____ have advantages arisen from the size and ease of computation.

Answer (Please select your correct option)

☐ CRC

☐ Parity

☐ Checksums

☐ VRC

correct

Made By: Waqar Siddhu

The Fast Ethernet hardware operates at a rate of _____.

Answer (Please select your correct option)

☐ 10 Mbps

☐ 100 Mbps

correct

☐ 1000 Mbps

☐ 1 Gbps

Made By: Waqar Siddhu

The Gigabit Ethernet hardware operates at a rate of _____.

Answer (Please select your correct option)



10 Mbps



100 Mbps



1000 Mbps



10 Gbps

correct

Made By: Waqar Siddhu

Wireless LAN uses _____ as a media access method.

Answer (Please select your correct option)

☐ CSMA/CD

☐ CSMA/CA

☐ Token Passing

☐ CSMA

correct

Made By: Waqar Siddhu

The _____ relies on the hardware manufacturer to assign a unique physical address to each network interface.

Answer (Please select your correct option)

☐ Static addressing scheme

correct

☐ Configurable addressing scheme

☐ Dynamic addressing scheme

☐ Dynamic Configurable addressing scheme

Made By: Waqar Siddhu

IEEE LLC/SNAP header is consist of _____ which is used to specify the type of data.

Answer (Please select your correct option)

☐ 8 octets

correct

☐ 10 octets

☐ 12 bytes

☐ 16 bits

Formally named _____ is informally known as the twisted pair Ethernet or TP Ethernet.

Answer (Please select your correct option)

☐ 10 Base 2

☐ 10 Base 5

☐ 10 Base T

☐ 100 Base T

correct

Made By: Waqar Siddhu

_____ senses a signal on a cable and then transmits an amplified copy of the signal.

Answer (Please select your correct option)

☐ Bridge

☐ Hub

☐ Transceiver

☐ Repeater

correct

Made By: Waqar Siddhu

Generally a Bridge is used to perform _____.

Answer (Please select your correct option)

☐ Extend a LAN, Filter and Forward a packet

☐ Routing

☐ Filter and Forward a frame

☐ Filter and Forward a packet

correct

Made By: Waqar Siddhu

Which of the following is not used to extend LAN ?

Answer (Please select your correct option)

- ☐ Bridge
- ☐ Repeater
- ☐ Fiber modem
- ☐ HUB

correct

Made By: Waqar Siddhu

If a bridge is unable to find _____ in its table then it just forwards frames to the other segment.

Answer (Please select your correct option)

☐ IP address

☐ Destination address

☐ Source address

☐ Port address

Made By: Waqar Siddhu

Most WAN systems include a mechanism that can be used to eliminate the common case of duplication routing is called_____.

Answer (Please select your correct option)

☐ Dynamic route

☐ Hierarchal address

☐ Default route

☐ Shortest path

correct

Made By: Waqar Siddhu

The working of connection-oriented service for networking is similar to the _____.

Answer (Please select your correct option)

☐ Ethernet

☒ Telephone

☐ IP

☐ UDP

correct

Made By: Waqar Siddhu

ATM assigns each VC a _____ identifier which is divided into two parts to produce a hierarchy.

Answer (Please select your correct option)

☐ 23-bit

☐ 24-bit

correct

☐ 21-bit

☐ 22-bit

Made By: Waqar Siddhu

_____ is used for delay sensitive applications requiring high data rate.

Answer (Please select your correct option)

☐ Constant Bit Rate (CBR) service

correct

☐ Variable Bit Rate (VBR) service

☐ Available Bit Rate (ABR) service

☐ Uniform Bit Rate (UBR) service

Made By: Waqar Siddhu

Header of cell takes _____ of network capacity.

Answer (Please select your correct option)

☐ 5%

☐ 10%

☐ 12%

☐ 15%

correct

Made By: Waqar Siddhu



In broadcast topology there are two categories ____.

Answer (Please select your correct option)



Satellite/Radio and Ring

correct



Satellite/Radio and Star



Ring and star



Satellite/Radio

Made By: Waqar Siddhu



In -----, network occupies the smaller area like a room a floor or a building

Answer (Please select your correct option)

☐ LAN

correct

☐ WAN

☐ MAN

☐ PAN



The Ethernet standard specifies that frames are sent using the -----

Answer (Please select your correct option)

☐ Manchester Encoding

correct

☐ Nonreturn to zero(NRZ)

☐ Return to zero(RZ)

☐ Differential Manchester



A ----- relies on the hardware manufacturer to assign a unique physical address to each network interface.

Answer (Please select your correct option)

☐ Static addressing scheme

correct

☐ Configurable addressing scheme

☐ Dynamic addressing scheme

☐ Burned MAC



When an application----- data, it makes a copy of the data available to all other computers on the network.

Answer (Please select your correct option)

☐ Broadcasting

☐ Multicasting

correct

☐ Unicasting

☐ Anycasting

Made By: Waqar Siddhu



Formally named _____ informally known as the thick wire Ethernet or Thick net.

Answer (Please select your correct option)

☐ 10 Base 2

☐ 10 Base 5

☐ 10 Base T

☐ 100 Base T

correct



Basic LAN technologies such as Ethernet, Token Ring, and FDDI use a _____.

Answer (Please select your correct option)

- ☐ Connectionless service paradigm
- ☒ Connection-oriented service paradigm
- ☐ Both Connectionless and Connection-oriented service paradigm
- ☐ Connection-oriented service paradigm without acknowledgment

correct



In which type of topology computers are connected to a central device?

Answer (Please select your correct option)

☐ Ring

correct

☐ Mesh

☐ Bus

☐ Star

Made By: Waqar Siddhu



----- was especially most concerned about the lack of highly powered computers.

Answer (Please select your correct option)

☐ ARPA

correct

☐ IEEE

☐ ELA

☐ Goverment

Made By: Waqar Siddhu



"Frame type" field of the header consists of _____ bits.

Answer (Please select your correct option)

☐ 8

☐ 10

☐ 16

☐ 32

correct

Made By: Waqar Siddhu



A bridge uses the _____ to determine which computers connect to which segment and uses the _____ to determine whether to forward a copy of frame.

Answer (Please select your correct option)



Source address, Destination address

correct



Destination address, Source address



Destination address, MAC Address



Destination address, Destination address

Made By: Waqar Siddhu



Generally a Bridge is used to perform _____.

Answer (Please select your correct option)



Extend a LAN, Filter and Forward a packet



Routing



Filter and Forward a frame



Filter and Forward a packet

correct

Made By: Waqar Siddhu



If bridge cannot find _____ in its tables then forwards frames to the other segment.

Answer (Please select your correct option)



IP address



Destination address



Source address



Port address

correct



_____ technology can support both LAN and WAN connections.

Answer (Please select your correct option)

☐ Frame relay

☐ Ethernet

☐ SMDS

☐ ATM

correct

Made By: Waqar Siddhu



Virtual Circuit connection identifier occupies _____ bits.

Answer (Please select your correct option)

☐ 16

correct

☐ 24

☐ 32

☐ 8

Made By: Waqar Siddhu



_____ is used for ordinary data.

Answer (Please select your correct option)



Available Bit Rate (ABR) service

correct



Uniform Bit Rate (UBR) service



Constant Bit Rate (CBR) service



Variable Bit Rate (VBR) service

Made By: Waqar Siddhu



Unlike Frame Relay and ATM, SMDS (Switched multi-megabit Data service) offers_____.

Answer (Please select your correct option)

- ☐ Connectionless service paradigm
- ☐ Connection oriented service paradigm
- ☐ Both Connectionless and Connection-oriented service paradigm
- ☐ Stateless Connection oriented service paradigm



The term _____ refers to the general concept of a small block of data in a network.

Answer (Please select your correct option)

☐ Packet

correct

☐ Byte

☐ Cell

☐ Information

Made By: Waqar Siddhu



LAN that uses ATM technology has a _____.

Answer (Please select your correct option)

☐ Star topology

correct

☐ Bus topology

☐ Ring topology

☐ Mesh topology

Made By: Waqar Siddhu



The next hop to which a packet is sent depends only on _____.

Answer (Please select your correct option)

☐ Packet's destination

correct

☐ Packet's original source

☐ Path the packet has taken

☐ Routed Protocol

Made By: Waqar Siddhu

In _____, network occupies the smaller area like a room, a floor or a building.

Answer (Please select your correct option)

☐ LAN

correct

☐ WAN

☐ MAN

☐ Wireless WAN

Made By: Waqar Siddhu

In which type of network topology, computers are connected to a central device?

Answer (Please select your correct option)

☐ Ring

correct

☐ Mesh

☐ Bus

☐ Star

Made By: Waqar Siddhu

The term _____ refers to the general concept of a small block of data in a computer network.

Answer (Please select your correct option)

☐ Packet

correct

☐ Byte

☐ Cell

☐ Information

Made By: Waqar Siddhu

_____ is the scheme, which is designed to help in detecting transmission errors by sending one extra bit of information with each character.

Answer (Please select your correct option)

☐ Parity checking

correct

☐ Checksums

☐ CRC

☐ LRC

Made By: Waqar Siddhu

_____ have advantages arisen from the size and ease of computation.

Answer (Please select your correct option)

☐ CRC

☐ Parity

☐ Checksums

☐ VRC

correct

Made By: Waqar Siddhu

The Fast Ethernet hardware operates at a rate of _____.

Answer (Please select your correct option)



10 Mbps



100 Mbps

correct



1000 Mbps



1 Gbps

Made By: Waqar Siddhu

The Gigabit Ethernet hardware operates at a rate of _____.

Answer (Please select your correct option)

☐

10 Mbps

☐

100 Mbps

☒

1000 Mbps

☐

10 Gbps

correct

Made By: Waqar Siddhu

Wireless LAN uses _____ as a media access method.

Answer (Please select your correct option)

☐ CSMA/CD

☐ CSMA/CA

☐ Token Passing

☐ CSMA

correct

Made By: Waqar Siddhu

The _____ relies on the hardware manufacturer to assign a unique physical address to each network interface.

Answer (Please select your correct option)

☐ Static addressing scheme

correct

☐ Configurable addressing scheme

☐ Dynamic addressing scheme

☐ Dynamic Configurable addressing scheme

Made By: Waqar Siddhu

IEEE LLC/SNAP header is consist of _____ which is used to specify the type of data.

Answer (Please select your correct option)

☐ 8 octets

correct

☐ 10 octets

☐ 12 bytes

☐ 16 bits

Formally named _____ is informally known as the twisted pair Ethernet or TP Ethernet.

Answer (Please select your correct option)

☐ 10 Base 2

☐ 10 Base 5

☐ 10 Base T

☐ 100 Base T

correct

Made By: Waqar Siddhu

_____ senses a signal on a cable and then transmits an amplified copy of the signal.

Answer (Please select your correct option)

☐ Bridge

☐ Hub

☐ Transceiver

☐ Repeater

correct

Made By: Waqar Siddhu

Generally a Bridge is used to perform _____.

Answer (Please select your correct option)

☐ Extend a LAN, Filter and Forward a packet

☐ Routing

☐ Filter and Forward a frame

☐ Filter and Forward a packet

correct

Made By: Waqar Siddhu

Which of the following is not used to extend LAN ?

Answer (Please select your correct option)

- ☐ Bridge
- ☐ Repeater
- ☐ Fiber modem
- ☐ HUB

correct

Made By: Waqar Siddhu

If a bridge is unable to find _____ in its table then it just forwards frames to the other segment.

Answer (Please select your correct option)

☐ IP address

☐ Destination address

☐ Source address

☐ Port address

Made By: Waqar Siddhu

Most WAN systems include a mechanism that can be used to eliminate the common case of duplication routing is called_____.

Answer (Please select your correct option)

☐ Dynamic route

☐ Hierarchal address

☐ Default route

☐ Shortest path

correct

Made By: Waqar Siddhu

The working of connection-oriented service for networking is similar to the _____.

Answer (Please select your correct option)

☐ Ethernet

☒ Telephone

☐ IP

☐ UDP

correct

Made By: Waqar Siddhu

ATM assigns each VC a _____ identifier which is divided into two parts to produce a hierarchy.

Answer (Please select your correct option)

☐ 23-bit

☐ 24-bit

correct

☐ 21-bit

☐ 22-bit

Made By: Waqar Siddhu

_____ is used for delay sensitive applications requiring high data rate.

Answer (Please select your correct option)

☐ Constant Bit Rate (CBR) service

correct

☐ Variable Bit Rate (VBR) service

☐ Available Bit Rate (ABR) service

☐ Uniform Bit Rate (UBR) service

Made By: Waqar Siddhu

Header of cell takes _____ of network capacity.

Answer (Please select your correct option)

☐ 5%

☐ 10%

☐ 12%

☐ 15%

correct

Made By: Waqar Siddhu



ATM was designed for _____ and use a _____

Answer (Please select your correct option)



LANs, Connectionless service paradigm



WANs, Connectionless service paradigm



Both LANs and WANs, Connectionless service paradigm



Both LANs and WANs, Connection-oriented service paradigm

correct

Made By: Waqar Siddhu



In Point-to-Point type of topologies there are two topologies _____.

Answer (Please select your correct option)



Tree and Ring



Star and Ring



Star and Tree



Bus and Mesh

correct

Made By: Waqar Siddhu



In -----, network occupies larger areas like cities & countries.

Answer (Please select your correct option)

LAN



WAN



correct

MAN



CAN



Made By: Waqar Siddhu



Hardware that calculates a CRC uses two simple components.

Answer (Please select your correct option)



AND unit with XOR unit



Shift register with XOR unit

correct



Shift register with AND unit



Shift register with shift XOR unit

Made By: Waqar Siddhu



A network that uses a ----- usually consist of a single long cable to which computers attach.

Answer (Please select your correct option)

☐ Star Topology

☐ Ring Topology

☒ Bus Topology

☐ Tree Topology

correct

Made By: Waqar Siddhu



A ----- provides mechanism that a customer can use to set a physical address.

Answer (Please select your correct option)



Static addressing scheme



Configurable addressing scheme

correct



Dynamic addressing scheme



Masking

Made By: Waqar Siddhu



Formally named _____ informally known as the thick wire Ethernet or Thick net.

Answer (Please select your correct option)



10 Base 2



10 Base 5



10 Base T

correct



100 Base T

Made By: Waqar Siddhu



Preamble field in Ethernet frame consist of _____ bits.

Answer (Please select your correct option)

☐ 8

☐ 32

☐ 48

☐ 64

correct



A bridge functions in the _____ layer(s).

Answer (Please select your correct option)

☐ Physical

correct

☐ Data link

☐ Network and Data link

☐ Physical and Data link



Generally a Bridge is used to perform _____.

Answer (Please select your correct option)



Extend a LAN, Filter and Forward a packet



Routing



Filter and Forward a frame



Filter and Forward a packet

correct

Made By: Waqar Siddhu



_____ technology can support both LAN and WAN connections.

Answer (Please select your correct option)

☐

Frame relay

☐

Ethernet

☐

SMDS

☐

ATM

correct

Made By: Waqar Siddhu



One repeater _____, two repeaters _____ the maximum cable length limitation.

Answer (Please select your correct option)



Square root, Cube root



Double, Triple

correct



Triple, Quad



Double, Quad



_____ is used for compressed audio and video where the data rate is related to level of compression.

Answer (Please select your correct option)



Constant Bit Rate (CBR) service



Variable Bit Rate (VBR) service



Available Bit Rate (ABR) service



Uniform Bit Rate (UBR) service

correct

Made By: Waqar Siddhu



_____ is used for ordinary data.

Answer (Please select your correct option)



Available Bit Rate (ABR) service

correct



Uniform Bit Rate (UBR) service



Constant Bit Rate (CBR) service



Variable Bit Rate (VBR) service

Made By: Waqar Siddhu



_____ sends a message to a remote computer and reports whether the computer responds.

Answer (Please select your correct option)



Telnet



Ping
Ping

correct



Traceroute



ICMP

Made By: Waqar Siddhu



A network with throughput T and delay D would have a total no of _____ bits in transit at any time.

Answer (Please select your correct option)

☐

$T + D$

☐

$T \times D / \text{Unit Time}$

☐

T / D

☐

$T \times D$

correct

Made By: Waqar Siddhu



A network that permits many sources to take turns accessing a shared communication resource is providing a form of _____.

Answer (Please select your correct option)



Phase Division Multiplexing



Time Division Multiplexing



Frequency Division Multiplexing



Wave Division Multiplexing

Made By: Waqar Siddhu



A network which is based on packets uses a computer which may have _____, memory and _____ for switching.

Answer (Please select your correct option)



Administration Rights, Algorithm



Source address, Destination address



Interface, Program



Input, Output



In direct point to point communication adding the N^{th} computer requires _____ new connections.

Answer (Please select your correct option)

☐

$N(N - 1)$

☐

N^2

☐

$N - 1$

☐

$(N^2 - N)/2$

correct

Made By: Waqar Siddhu



Computers attached to an ethernet use _____ in which a computer waits for the Ether to be idle before transmitting a frame.

Answer (Please select your correct option)

☐ CSMA/CD

correct

☐ CSMA/CA

☐ Token Passing

☐ Round Robin

Made By: Waqar Siddhu



In broadcast topology there are two categories ____.

Answer (Please select your correct option)



Satellite/Radio and Ring

correct



Satellite/Radio and Star



Ring and star



Satellite/Radio

Made By: Waqar Siddhu



In -----, network occupies the smaller area like a room a floor or a building

Answer (Please select your correct option)

☐ LAN

correct

☐ WAN

☐ MAN

☐ PAN



The Ethernet standard specifies that frames are sent using the -----

Answer (Please select your correct option)

☐ Manchester Encoding

correct

☐ Nonreturn to zero(NRZ)

☐ Return to zero(RZ)

☐ Differential Manchester



A ----- relies on the hardware manufacturer to assign a unique physical address to each network interface.

Answer (Please select your correct option)

☐ Static addressing scheme

correct

☐ Configurable addressing scheme

☐ Dynamic addressing scheme

☐ Burned MAC



When an application----- data, it makes a copy of the data available to all other computers on the network.

Answer (Please select your correct option)

☐ Broadcasting

☐ Multicasting

correct

☐ Unicasting

☐ Anycasting

Made By: Waqar Siddhu



Formally named _____ informally known as the thick wire Ethernet or Thick net.

Answer (Please select your correct option)

☐ 10 Base 2

☐ 10 Base 5

☐ 10 Base T

☐ 100 Base T

correct



Basic LAN technologies such as Ethernet, Token Ring, and FDDI use a _____.

Answer (Please select your correct option)

- ☐ Connectionless service paradigm
- ☒ Connection-oriented service paradigm
- ☐ Both Connectionless and Connection-oriented service paradigm
- ☐ Connection-oriented service paradigm without acknowledgment

correct



In which type of topology computers are connected to a central device?

Answer (Please select your correct option)

☐ Ring

correct

☐ Mesh

☐ Bus

☐ Star

Made By: Waqar Siddhu



----- was especially most concerned about the lack of highly powered computers.

Answer (Please select your correct option)

☐ ARPA

correct

☐ IEEE

☐ ELA

☐ Goverment

Made By: Waqar Siddhu



"Frame type" field of the header consists of _____ bits.

Answer (Please select your correct option)

☐ 8

☐ 10

☐ 16

☐ 32

correct

Made By: Waqar Siddhu



A bridge uses the _____ to determine which computers connect to which segment and uses the _____ to determine whether to forward a copy of frame.

Answer (Please select your correct option)



Source address, Destination address

correct



Destination address, Source address



Destination address, MAC Address



Destination address, Destination address

Made By: Waqar Siddhu



Generally a Bridge is used to perform _____.

Answer (Please select your correct option)

☐ Extend a LAN, Filter and Forward a packet

☐ Routing

☐ Filter and Forward a frame

☐ Filter and Forward a packet

correct

Made By: Waqar Siddhu



If bridge cannot find _____ in its tables then forwards frames to the other segment.

Answer (Please select your correct option)

☐

IP address

☐

Destination address

☐

Source address

☐

Port address

correct



_____ technology can support both LAN and WAN connections.

Answer (Please select your correct option)

☐ Frame relay

☐ Ethernet

☐ SMDS

☐ ATM

correct

Made By: Waqar Siddhu



Virtual Circuit connection identifier occupies _____ bits.

Answer (Please select your correct option)

☐ 16

correct

☐ 24

☐ 32

☐ 8

Made By: Waqar Siddhu



_____ is used for ordinary data.

Answer (Please select your correct option)



Available Bit Rate (ABR) service

correct



Uniform Bit Rate (UBR) service



Constant Bit Rate (CBR) service



Variable Bit Rate (VBR) service

Made By: Waqar Siddhu



Unlike Frame Relay and ATM, SMDS (Switched multi-megabit Data service) offers_____.

Answer (Please select your correct option)

- ☐ Connectionless service paradigm
- ☐ Connection oriented service paradigm
- ☐ Both Connectionless and Connection-oriented service paradigm
- ☐ Stateless Connection oriented service paradigm



The term _____ refers to the general concept of a small block of data in a network.

Answer (Please select your correct option)

☐ Packet

correct

☐ Byte

☐ Cell

☐ Information

Made By: Waqar Siddhu



LAN that uses ATM technology has a _____.

Answer (Please select your correct option)

☐ Star topology

correct

☐ Bus topology

☐ Ring topology

☐ Mesh topology

Made By: Waqar Siddhu



The next hop to which a packet is sent depends only on _____.

Answer (Please select your correct option)

☐ Packet's destination

correct

☐ Packet's original source

☐ Path the packet has taken

☐ Routed Protocol

Made By: Waqar Siddhu