CS-201 MCQ’s

1. Which loop is mostly used to perform repetition of a task for a known number of times?

a) Nested Loop

b) While

c) For

d) Do-While

2. The name of a location in memory is called _____.

a) Number

b) Variable

c) Cell

d) Constant

3. If an array has 50 elements, what is the allowable range of subscripts?

a) 1 - 49

b) 1 - 50

c) 1 - 500

d) 1 - 51

4. The character used to indicate the end of a string is _____.

a) Null

b) E

c) New line

d) Blank space

5. When the "break" statement is encountered in a loop's body, it transfers the control _____ from the current loop.

a) Outside

b) Inside

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

c) To break statement

d) To continue statement

6. What will be the value of the variable "output" in the given code?

```cpp
double output = 0;
output = (2 + 2) * 4 + 2 / (4 - 2);
```

a) 11

b) 12

c) 15

d) 17

7. Find the syntax error in the following piece of code:

```cpp
if (x > y);
    cout << "x is greater than y";
else
    cout << "y is greater than x";
```

a) No error in the code

b) Condition in the if statement is wrong

c) Semicolon should not be after the if statement

d) Braces not given for if and else block

8. What will be the output for the following code segment?

```cpp
for (int num = 3; num <= 5; num++) {
    if (num % 2 != 0)
```

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

```
        continue;
    cout << num << " ";
  }
```

a) 5 3 4 2

b) 5 4 3 2

c) 2 4

d) 4

9. Sometimes after allocating memory, we need additional space. For this purpose, we use:

a) void pointer

b) reallocation function

c) realloc function

d) calloc function

10. We cannot use _____ pointer for storing and reading data from it.

a) zero

b) NULL

c) integer

d) double

11. What will be the output of the following C++ code?

```cpp
#include <iostream>
#define max 100
int main()
{
#ifdef max
```

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

```
std::cout << "Hello";
#endif

return 0;
}
```

a) "Hello"

b) "Max is 100"

c) Error

d) Hello

12. For casting, we normally declare a pointer of type _____.

a) integer

b) NULL

c) void

d) None of the given

13. What is the storage space of the double data type?

a) 4

b) 8

c) 16

d) 32

14. Programmer should be very careful about the memory management because it can _____.

a) affect the logic of the program

b) cause problems of memory leakage and dangling pointers

c) return void pointers

d) create problems of NULL pointers

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

15. Structures are syntactically defined with the word _____.

a) None of the given

b) struc

c) struct

d) structure

16. The `_____` function is used to determine the next position to write a character while writing into a file.

a) seekp()

b) seekg()

c) tellp()

d) tellg()

17. The heap memory structure _____.

a) remains constant

b) contains no space

c) is just like the stack

d) constantly changes in size

18. RAID stands for _____.

a) Redundant Array of Inexpensive Disk

b) Redundant Array of Inexperience Devices

c) Redundant Array of Inexpensive Dices

d) Reduced Array of Inexpensive Devices

19. How many bits form a byte?

a) 2

b) 4

c) 6

d) 8

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

20. Which of the following code segment represents a left shift operator?

a) result = number >> 1;

b) result = number << 1;

c) cout << 1;

d) cin >> number;

21. The dynamic memory allocation uses _____ whereas static memory allocation uses _____.

a) array, stack

b) classes, array

c) stack, lists

d) heap, stack

22. In _____, we have different data members and all of these have their own memory space.

a) union

b) construct

c) structures

d) None of the given

23. With the use of dynamic allocation of memory, the system resources can be _____.

a) all of the given options

b) used efficiently

c) used carelessly

d) wasted

24. Initializing the data member within the class is _____.

a) a syntax error

b) not an error

c) a logical error

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

d) a runtime error

25. "a = a | b;" can be written as _____.

a) a = | b;

b) a == b;

c) a = b;

d) a |= b;

26. We should not use variable names that start with _____ because in C++, there are lots of internal constants and symbolic names that start with it.

a) none of the given options

b) upper case alphabets

c) double underscore

d) lower case alphabets

27. The original value remains unchanged in _____.

a) Call by value

b) Dynamic Variables

c) Call by reference

d) Pointers

28. The memory allocation functions return a chunk of memory with a pointer of type _____.

a) ptr

b) void

c) integer

d) float

29.Memory allocated from heap or free store _____.

A) can be returned back to the system automatically

B) can be allocated to classes only

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢cannot be returned back unless freed explicitly using malloc and realloc

➢**cannot be returned back unless freed explicitly using free and delete operators**

30.Once the _____ are created, they exist for the life time of the program.

Select correct option:

➢local variables

➢non static variables

➢**static variables**

➢automatic variables

31.The members of a class declared with the keyword struct are _____by default.

➢static

➢private

➢protected

➢**public.**

32.If the memory in the free store is not sufficient _____.

Select correct option:

➢malloc function returns 1

➢malloc function returns 0

➢**malloc functions returns NULL pointer**

➢malloc function returns free space

33.This reference to a variable can be obtained by preceding the identifier of a variable with _____.

➢dot operator

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢ampersand sign &

➢^ sign

➢operator

34.Once an object is declared as a friend, _____.

➢it has access to all non-public members as if they were public

➢it has access to public members only

➢it has no access to data members of the class

➢it has to protected data members only

35.Reference variables must _____.

➢not be initialized after they are declared

➢be initialized after they are declared

➢contain integer value

➢contain zero value

36.The syntax of declaration of a function that returns the reference to an integer is _____.

➢ int &myfunc() ;

➢ int myfunc();

➢ int myfunc() &;

➢ integer &myfunc();

37.Reference is not really an address it is _____.

➢a synonym

➢an antonym

➢a value

➢a number

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

38.If the request of new operator is not fulfilled due to insufficient memory in the heap _____.

➢the new operator returns 2

➢the new operator returns 1

➢the operator returns 0

➢free operator returns nothing

39.Functions declared with the _____ specifier in a class member list are called friend

functions of that class.

➢protected

➢private

➢Public

➢friend

40.The friend keyword provides access _____.

➢**in one direction only**

➢in two directions

➢to all classes

➢to the data members of the friend class only

41.References cannot be uninitialized. Because it is impossible to

_____

Select correct option:

➢ reinitialize a pointer

➢reinitialize a reference

➢initialize a NULL pointer

➢cast a pointer

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

42. new operator can be used for _____.

Select correct option:

➢only integer data type

➢only char and integer data types

➢integer , float, char and double data types

➢dot operator

43.The destructor is used to _____.

➢allocate memory

➢deallocate memory

➢create objects

➢allocate static memory

44.If we want to allocate memory to an array of 5 integers dynamically, the syntax will be _____.

➢int *iptr ;iptr = new int[5] ;

➢integer iptr** ;iptr= new int[5]

➢int iptr ;iptr= int [5]

➢iptr= new[5]

45.Memory allocated from heap or free store _____.

➢can be returned back to the system automatically

➢can be allocated to classes only

➢cannot be returned back unless freed explicitly using malloc and realloc

➢cannot be returned back unless freed explicitly using free and delete operators

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

46.Operator overloading is to allow the same operator to be bound to more than one implementation, depending on the types of the _____.

➢Compilers

➢Operands

➢Function names

➢Applications

47.The operator to free the allocated memory using new operator is _____.

➢free

➢del

➢delete

➢remove

48.The concept of friend function negates the concept of _____.

➢inheritance

➢polymorphism

➢persistence

➢encapsulation

49.Functions declared with the _____ specifier in a class member list are called friend functions of that class.

➢protected

➢private

➢public

➢friend

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

50.Public or private keywords can be _____

➢**written only for once in the class or structure declaration**

➢written multiple times in the class or structure declaration

➢written only twice in the class declaration

➢written outside the class

51.The friend keyword provides access _____.

➢in one direction only

➢in two directions

➢to all classes

➢to the data members of the friend class only

52.References cannot be uninitialized. Because it is impossible to _____

➢reinitialize a pointer

➢reinitialize a reference

➢initialize a NULL pointer

➢cast a pointer

53.new operator can be used for _____.

➢only integer data type

➢only char and integer data types

➢integer , float, char and double data types

➢dot operator

54.The destructor is used to _____.

➢allocate memory

➢deallocate memory

➢create objects

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢allocate static memory

55.Reference is not really an address it is _____.

➢a synonym

➢an antonym

➢a value

➢a number

56.If we want to allocate memory to an array of 5 integers dynamically, the syntax will be

_____.

➢int *iptr ;iptr = new int[5] ;

➢integer iptr** ;iptr= new int[5]

➢int iptr ;iptr= int [5]

➢iptr= new[5]

57.Memory allocated from heap or free store _____.

➢can be returned back to the system automatically

➢can be allocated to classes only

➢cannot be returned back unless freed explicitly using malloc and realloc

➢cannot be returned back unless freed explicitly using free and delete operators

58.Operator overloading is to allow the same operator to be bound to more than one

implementation, depending on the types of the _____.

➢Compilers

➢Operands

➢Function names

➢Applications

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

59.The operator to free the allocated memory using new operator is _____.

➢free

➢del

➢**delete**

➢remove

60.reference is a thing by which we can create _____of any data type.

➢ copy

➢ **Synonym**

➢ Pointer

➢ None of the given

61.What is the sequence of event(s) when deallocating memory of an object using delete operator?

➢ Only block of memory is deallocated for object

➢ Only destructor is called for object

➢ **Memory is deallocated first before calling destructor**

➢ Destructor is called first before deallocating memory

62.When operator function is implemented as member function then return type of function _____.

➢ Must be an object of same class

➢ Must be user-defined data type

➢ **Must be built-in data type**

➢ Can be any data type

63.Overloaded new operator function takes parameter of type size_t and returns

➢ void (nothing)

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢void pointer

➢object pointer

➢int pointer

64.This reference to a variable can be obtained by preceding the identifier of a variable with _____.

➢ dot operator

➢ ampersand sign &

➢ ^ sign

➢ * operator

65.In overloading the assignment (=) operator, which object(s) will call the operator function?

➢ **Left object of the assignment operator**

➢ Right object of the assignment operator

➢ Both objects will call the operator function

➢ No object will call the operator function

66.We can _____ pointer.

➢ increment

➢ decrement

➢ reassign

➢ all of the given

67.In overloading the assignment (=) operator, which object will be passed as an argument(s) in the operator function?

➢ Left object of the assignment operator

➢ Right object of the assignment operator

➢ Both objects will be passed

➢ No objects will be passed

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

68.It is possible to return an object from function using this pointer.

➢ True

➢ False

69.If class A is a friend of class B, and class B is a friend of class C. If class A wants class C to be a friend, _____

➢ it has to declare, class C as a friend

➢ it has to declare, class B as a friend

➢ it has to declare , class A as a friend

➢ it has to declare, class B and class A as friend classes

70.The destructor is used to _____.

➢deallocate memory

71.The main advantage of macros is that _____and program runs faster

➢macros are more efficient

72._____ is a special type of pointer we have to cast it before we use it.

➢void

73.Programmer should be very careful about the memory management because it can _____.

➢cause problems of memory leakage and dangling pointers

74.Constructor is special type of function :

➢which has no return type

75.Unix operating system was written in C language

➢C

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

76.When accessing a structure member, the identifier to the left of the dot operator is the name of _____.

➢Structure variable

77.Constructor has _____.

➢the same name as of class

For console input and output we use _____.

➢iostream

78.We should not use such variable names that are starting with _____ because in C++, there are lots of internal constants and symbolic names that start with it.

➢upper case alphabets

79.The members of a class declared with the keyword struct are _____by default.

➢public

80._____will return the number of bytes reserved for a variable or data type.

➢ **sizeof operator**

➢ free operator

➢ void pointer

➢ new operator

81.A reference cannot be NULL it has to point a data type.

➢true

➢false

82.While using _____ operator we do not need to supply number of bytes allocated.

➢insertion

➢dot

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢malloc

➢new

83.When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

➢1

➢2

➢0

➢N

84.For binary member operators, operands on the _____ drives (calls) the operation.

➢left

➢right

➢both

85.Reference is not really an address it is _____

➢an antonym

➢a value

➢a number

➢synonym

86.We cannot increment _____.

➢pointers

➢arrays

➢references

➢variable

87.how many arguments are used while using unary operator function.

➢1

➢2

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢0

➢3

89.Pointers are a special type of _____in which a memory address is stored

➢ variables

➢ Location

➢ Characters

➢ None of the given

90.If x is declare as an integer, what will be result of the given expression?
x = 2 + 3 * 5 % (2 + 2) / 2

➢ 4

➢3.5

➢3

➢3.75

91.Which of the following is not a valid variable name in C++?

➢ NameOfStudent

➢ nameOfStudent

➢ _studentName

➢ @studentName

92.What will be the result of arithmetic expression 6+48/4*3?

➢ 10

➢ 40.5

➢ 42

➢ 41

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

93.< ,<= , > , >= are called _____ operators.

➢Arithmetic

➢Logical

➢Relational

➢Conational

94.Pointers work by pointing to a particular_____ .

➢ Value

➢ **variable**

➢ data type

➢ None of the given

95.The most suitable data type for number 325.25 is _____.

➢ char

➢ int

➢ short

➢ float

96.How many times the following loop will execute? int j = 3; while(j > 0) { cout "Statements"

endl; j -= 2; }

Select correct option:

➢0

➢1

➢ 2

➢ 3

97.Loops are _____ Structure

➢ Decision

➢Sequential

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢Repetition

➢None of the given options

98.Structures use _____ allocation.

➢ Queue

➢ Heap

➢ Cache

➢ Stack

99.The members of a class declared with the keyword struct are _____by default.

➢public

➢private

100._____will return the number of bytes reserved for a variable or data type.

➢ **sizeof operator**

➢ free operator

➢ void pointer

➢ new operator

101.A reference cannot be NULL it has to point a data type.

➢ true

➢ false

102.While using _____ operator we do not need to supply number of bytes allocated.

➢ insertion

➢ dot

➢ malloc

➢ new

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

103.When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

➢1

➢2

➢0

➢N

104.For binary member operators, operands on the _____ drives (calls) the operation.

➢left

➢right

➢both

105.We can _____references.

➢ reassign

➢ join

106.Reference is not really an address it is _____

➢ an antonym

➢ a value

➢ a number

➢ synonym

107.We cannot increment _____.

➢pointers

➢arrays

➢references

➢variable

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

108.how many arguments are used while using unary operator function.

➢**1**

➢2

➢0

➢3

109.int &i; It means that i is a _____to an integer.

➢pointer

➢**refrence**

➢data type

➢none

110.We can _____references.

➢increment

➢decrement

➢reaasign

➢non

111._____will return the number of bytes reserved for a variable or data type.

➢**sizeof operator**

➢free operator

➢new operator

112.For binary member operators, operands on the _____ drives (calls) the operation.

➢**left**

➢right

➢both

➢none

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

113.int &i; It means that i is a _____to an integer.

➢pointer

➢reference

114.An address is a _____ , while a pointer is a _____.

➢constant , variable

➢**variable , constant**

➢global , variable

➢non static variable , constant

115.A pointer is _____.

➢the address of a variable

➢an indication of the variable to be accessed next

➢a variable for storing address

➢the data type of an address variable

116.The new operator automatically determines the size of memory required to store that object , so

it does not need _____.

➢free operator

➢dot operator

➢sizeof operator

➢size off operator

117.We cannot increment _____.

➢pointers

➢arrays

➢refrencce

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

118.The _____ data type always represents an empty set of values in C++

➢nil

➢void

➢zero

119.public or private keywords can be _____

➢written only for once in the class or structure declaration

➢written multiple times in the class or structure declaration

➢written only twice in the class declaration

➢written outside the class

120.The destructor is used to _____.

➢allocate memory

➢deallocate memory

➢create objects

121.Which one of the following is the declaration of overloaded pre-increment operator

implemented as member function?

➢Class-name operator +() ;

➢Class-name operator +(int) ;

➢Class-name operator ++();

➢Class-name operator ++(int) ;

122.You cannot overload the _____ operator

➢? :

➢*

➢/

➢+

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

123.In C language, the region of memory allocated at runtime is called _____.

➢stack

➢heap

➢free store

➢available memory

124.Reference variables must _____.

➢not be initialized after they are declared

➢be initialized after they are declared

➢contain integer value

➢contain zero value

125.reference is a thing by which we can create _____of any data type.

➢copy

➢Synonym

➢Pointer

➢none

126.A reference cannot be NULL it has to point a data type

➢true

➢false

127.In functions, that returns reference use _____

➢global or local variables

➢global or static variables

➢ordinary variables

➢array

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

128.The friend functions are

➢**not member of a class**

➢member of a class

➢inline functions

➢void functions

129.The concept of _____ allows us to separate the interface from the implementation.

of the class.

➢pointers

➢inheritance

➢polymorphism

➢**encapsulation**

130._____ operators are the ones that require only one operator to work.

➢Unit

➢**Unary**

➢Single

➢none

131.C++ offers _____ levels of data access control inside a class

➢**three**

➢four

➢two

➢five

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

132.References cannot be uninitialized. Because it is impossible to _____

➢reinitialize a pointer

➢reinitialize a reference

➢initialize a NULL pointer

➢cast a pointer

133.In C language, the region of memory allocated at runtime is called _____

➢stack

➢heap

➢free store

➢available memory

134.In functions, that returns reference use _____

➢global or local variables

➢global or static variables

➢ordinary variables

➢array

135.A reference cannot be NULL it has to point a data type

➢true

➢false

136.public or private keywords can be _____

➢written only for once in the class or structure declaration

➢written multiple times in the class or structure declaration

➢written only twice in the class declaration

➢written outside the class

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

137.The friend function of a class can have access _____

➢to the public data members only

➢to the private data members

➢to the protected data members

➢to the main program

138.In c++ the region of available memory is called _____

➢heap

➢**empty space**

➢free store

➢allocated memory

139.When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are

➢zero

➢one

➢two

➢n arguments

140.If class A is a friend of class B, and class B is a friend of class C. If class A wants class C to be a friend, _____

➢**it has to declare, class C as a friend**

➢it has to declare, class B as a friend

➢it has to declare , class A as a friend

➢it has to declare, class B and class A as friend classes

141.We can _____reference

➢increment

➢decrement

➢**reassign**

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢none of the given

142.A pointer is

➢the address of a variable

143.n indication of the variable to be accessed next. a variable for storing address

➢the data type of an address variable

144.Overloaded member operator function is always called by _____

➢Class

➢Object

➢Compiler

➢Primitive data type

145.The difference between pointers and references is that

➢we cannot do arithmetic with pointers

➢we can do arithmetic with pointers

➢we cannot reassign pointers

➢we can assign references

146.While using _____ operator we do not need to supply number of bytes allocated.

➢insertion

➢dot

➢malloc

➢new

147.Memory allocated from heap or free store

➢can be returned back to the system automatically

➢can be allocated to classes only

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢cannot be returned back unless freed explicitly using malloc and realloc

➢cannot be returned back unless freed explicitly using free and delete operators

148.If B is designated as friend of A, B can access A's non-public members

➢B cannot access private member of A

➢B cannot access protected member of A

➢A can access non-public members of B

➢A cannot access B

149.Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

➢Class-name operator +() ;

➢Class-name operator +(int) ;

➢Class-name operator ++();

➢Class-name operator ++(int) ;

150.An address is a _____ , while a pointer is a

➢constant , variable

➢variable , constant

151.To prevent dangling reference the functions returning reference should be used with

➢local variables

➢global variables only.

➢arrays

152.When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

➢ Zero

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

➢One

➢Two

➢N arguments

153.Deleting an array of objects without specifying [] brackets may lead to memory leak.

➢ **True**

➢False

154.following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

➢ delete string ;

➢delete []string ;

➢delete string[] ;

➢delete string[5] ;

155.The function will return a reference to the global variable that exists throughout the program and thus there will be no danger of _____.

➢ garbage collection

➢ dangling reference

➢ wastage of memory

156.What is the sequence of event(s) when deallocating memory of an object using delete operator?

➢ Only block of memory is deallocated for object

➢ Only destructor is called for object

➢ Memory is deallocated first before calling destructor

➢ Destructor is called first before deallocating memory

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

157.Overloaded new operator function takes parameter of type size_t and returns

- ➢ void (nothing)
- ➢ void pointer
- ➢ **object pointer**
- ➢ int pointer

158.We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally.

- ➢ **True**
- ➢ False

159.What is the function of the following statement to delete an array of 5 objects named 'arr' allocated using new operator? delete arr ;

- ➢ Deletes all the objects of array
- ➢Deletes only one object of array
- ➢Do not delete any object
- ➢**Results into syntax error**

160.Friend function declaration can go _____ the class

- ➢ only outside
- ➢ only within
- ➢ in the member function of
- ➢ **anywhere in**

161.A structure is a collection of _____under a single name.

A. Array

B. Pointer

C. Datatype

D. Variables

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

162.The memory allocation functions return a chunk of memory with a pointer of type_____.

A. Ptr

B. Void

C. Float

D.Integer

163.A file opened with the help of _____ can be used for both input and output.

A. Fstream

B. Ofstream

C. Iostream

D. Ifstream

164.Macros are categorized into _____ type(s).

A. One

B. Two

C. Five

D. Three

165.All the preprocessors directives starts with _____.

A.-

B. &

C. #

D. $

166.When we include the header file in the angle brackets the compiler searches for it in _____.

A. All the drives

B. Current folder

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

C. Current directory

D. Specific directory

167.For accessing data members we use _____ operator

A. .dot

B. Plus+

C. Division /

D. multiplication *

168.The dynamic memory allocation uses _____ whereas static memory allocation uses _____.

A.stack , lists

B. array , stack

C. Heap,stack

D. classes , array

169.A file opened with _____ is used for input and cannot be used for output.

A.Ifstream

B. Ostream

C. Istream

D. Fstream

170.The data, contained in the structure, is defined in the _____.

A. None

B. Parenthesis

C. Curly braces

D.Inverted commas

171.student s[100]; means that ‘s’ is an array of hundred students of type

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

'student' structure. What will be the correct statement to access the 'name' data element of the fifty sixth student from the array?

A.s.name[56];

B. s[55].name;

C.s.name[55];

D.s[56].name;

172. Which of the following code segment represents a left shift operator?

A. cout<<1;

B. cin >> number ;

C. result = number >> 1 ;

173.Array indexes start from _____.

A. 1

B. 0 Page 266

C. 2

D. 3

174.An instance of a class is called _____.

A. Object Page 324

B. Structure

C. Data type

D. Member function

175.Which header file is required to use file I/O operations?

A. <fstream> Google

B. <ifstream>

C. <ostream>

D. <iostream>

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

176.Name the function whose definition can be substituted at a place where

its function call is made _____.

A. inline function Google

B. static function

C. friend function

D. volatile function

177.Default constructor takes _____.

A. no parameters Page 315

B. one parameter

C. two parameters

D. character type parameter

178._____function gives the position of the next character to be read from that file.

A. Tellp()

B. Tellg() Page 215

C. Seekp()

D. Seekg()

179.the sizeof operator is used to determine the size of _____.

A. Data

B. Variable

C. Data type Page 235

D. None of the given

180.Shifting the binary numbers is similar to shifting the _____ numbers.

A. Octal

B. Base 7

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

C. Decimal Page 252

D. Hexadecimal

181._____function is used to determine the next position to

write a character while writing into a file.

A. Tellg()

B. Tellp() Page 215

C. Seekp()

D. Seekg()

We have opened a file stream myfile for reading (getting), myfile.tellg () gives us the current get position of the file pointer. It returns a whole number of type_____

A.Int

B. Long Page 215

C. Short

D. Double

What is the use of ios::trunc mode?

A. To open a file in input mode

B. To open a file in output mode

C. To truncate an existing file to half

D.To truncate an existing file to zero Google

Structures use _____ for memory allocation.

A. Heap Google

B. Stack

C. Queue

D.Cache

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

Which of the following is not a file opening mode_____?

A.Ios::in

B. Ios::out

C. Ios::ate

D. ios::truncate

Structures are syntactically defined with the word_____.

A. Struc

B. Struct Page 229

C. Structure

D. None of the given

Which of the following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

A. Delete string;

B. Delete [] string;

C. Delete string [1];

D. Delete string [5];

Consider the following code segment. Which of the following will be called while executing code at line 2?

String s1,s2;

S1=s2;

A. Default operator

B. Copy constructor

C. Assignment operator

D. Parameterized constructor

free function is available in _____ header file.

A.stdlib.h

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

B. conio.h

C. string.h

D. iostream.h

C++ offers _____ levels of data access control inside a class

A. Two

B. Five

C. Four

D.Three Google

The stream-insertion operator is >> and the stream-extraction operator is <<.

True

False

The concept of _____ allows us to separate the interface from the implementation of the class.

A. Pointers

B. Inheritance

C. Polymorphism

D.Encapsulation Google

Which of the following is unary operator?

A.I++

B. I--

C. ++i

D. All of the Given

Identify the correct syntax for making a class friend of other class

friend ClassOne

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

{

OtherClass;

private;

//here we write the data members of ClassOne

};

lassOne

{friend OtherClass ;

private:

//here we write the data members of ClassOne

};

class ClassOne

{

friend OtherClass ;

private:

//here we write the data members of ClassOne

};

Friend class ClassOne

{

friend OtherClass ;

private:

//here we write the data members of ClassOne

};

Let suppose

int a, b, c, d, e;

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

a = b = c = d = e = 42;

This can be interpreted by the complier as:

A. a = (b = (c = (d = (e = 42))));

B. (a = b) = (c = d) = (e = 42);

C. a = b = (c = (d = (e = 42)));

D.(a = b = (c = (d = (e = 42))));

We cannot increment _____.

A. Arrays

B. Pointers

C. Variables

D. References Page 364

_____ operators are the ones that require only one operator to work.

A. Unit

B. Unary Page 370

C. Binary

D. Single

The constructor contains _____.

A. Class Page 313

B. Object

C. Return

D. None of these

We can _____references.

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

A.Reassign

B. Increment

C. Decrement

D. None of the given Google

The destructor is used to _____.

A. create objects

B. allocate memory

C. de-allocate memory Page 338

D. allocate static memory

Functions declared with the _____ specifier in a class member list are called friend functions of that class.

A. Friend

B. Public

C. Private

D. Protected

To prevent dangling reference the functions returning reference should be used with _____

A. Arrays

B. local variables

C. global variables only

D.static and global variables

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

If we want to allocate memory to an array of 5 integers dynamically, the syntax will be _____.

A. iptr= new[5]

B. int iptr ; iptr= int [5]

C. int *iptr ; iptr = new int[5] ;

D. integer iptr** ; iptr= new int[5]

The function will return a reference to the global variable that exists throughout the program and thus there will be no danger of _____.

A. System crash

B. Garbage collection

C. Dangling reference Page 365

D.Wastage of memory

If class A is a friend of class B, and class B is a friend of class C. If class A wants class C to be a friend, _____

A. it has to declare, class B as a friend

B. it has to declare, class C as a friend

C. it has to declare , class A as a friend

D. it has to declare, class B and class A as friend classes

If we use cin stream to read some value and store it in some integer variable and press some alphabet key instead of numeric keys. then what will happen?

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

A.Its ASCII code will be stored inside the computer

B. Some error will occur and cin stream will detect this error.

C.Its binary representation will be ignored and the value will be stored

D.Its binary representation will be ignored and the character will be stored

Which one of the following is the correct statement about operator overloading?

A. N-arithmetic operators can be overloaded only.

B. Arithmetic operators can be overloaded only.

C. Associativity and precedence of operators do not change.

D. Precedence of operators are changed after overloading.

new operator can be used for _____

A. dot operator

B. only integer data type

C. only char and integer data types

D. integer, float, char and double data types

Friend classes are used in cases where one class is _____to another class.

A.Independent

B. Encapsulated

C. tightly coupled.

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

D. loosely coupled.

_____will return the number of bytes reserved for a variable or data type.

A. void pointer

B. free operator

C. new operator

D.size of operator

int &i; It means that i is a _____to an integer.

A. Pointer

B. data type

C. reference Page 358

D. constant pointer

Which of the following is the correct definition of streams?

It is an ordered sequence of bytes

_____data isn't accessible by non-member functions or outside classes

A. Static

B. Public

C. Private

D. Globally declared.

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

If we have a program that writes the output data(numbers) to the disc ,and if we collect the output data and write it on the disc in one write operation instead of writing the numbers one by one.In the above situation the area where we will gather the number is called

A. Stack

B. Heap

C. Cache

D.Buffer

Default constructor generated by _____does _____for us.

A. classes , initialization

B. compiler , initialization

C. compiler, no initialization

D. main program, memory management

What is the function of the following statement to delete an array of 5 objects named ‘arr’ allocated using new operator?

delete arr ;

A.Results into syntax error

B. Do not delete any object

C. Deletes all the objects of array

D. Deletes only one object of array

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

The syntax of declaration of a function that returns the reference to an integer is _____.

A.Int myfunc();

B. Int myfunc() &;

C.Int &myfunc() ;

D.Integer &myfunc();

If we do not write our own assignment operator then which of the following problem may occur?

A. Null pointer

B. Memory leak

C. Dangling pointer

D. Unreferenced memory

What is the difference between cout and cerr?

A.Cout is unbuffered output and cerr is a buffered output

B. Cout is not standard output and cerr is a standard output

C. Cout is buffered output and cerr is not a unbuffered output

D. Cout is standard output and cerr is not a standard output

The only operator that the compiler overloads for user define data type by default is

A. Plus (+) operator Google

B. Minus (-) operator

C. Equal (==) operator

D. Assignment (=) operator

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

The friend functions are _____.

A. void functions

B. inline functions

C. member of a class

D. not member of a class Page 523

The friend function of a class can have access _____.

A.to the private data members

B. to the protected data members

C. to the public data members only

D. to public, private and protected data members

Let suppose a = b = c

In such situation, it is necessary to return a reference of an object from assignment operator function.

True

False

You cannot overload the _____ operator

A. /

B. +

C. ?;

D. ++

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

Bugs can occur due to _____

A. default values

B. uninitialized data

C. object destruction

D. initialization of a variable

When new operator is overloaded at global level then corresponding built-in new operator will also be visible to whole of the program.

True

False

Care must be taken about the correct_____ of operator while overloading. (Choose the most appropriate).

A. Semantic

B. Complexity

C. None of the given option

D.Both Semantic and Complexity

Ternary operator is shown as_____.

A. lll

B. ?:

C. &&

D. = = =

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

These functions seekg() and ssekp()requires an argument of type_____ to determine the backward.

A.Int

B. Long

C. Short

D. Double

The stream-insertion operator is >> and the stream -extraction operator is <<.

True

False

The return type of the overloading new operator must be?

A.Int pointer

B. Void pointer

C. Object pointer

D. Void (nothing)

Reference is not really an address it is _____.

A. A value

B. A number

C. A synonym

D. An antonym

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

The reference data types are used as_____ variables without any _____.

A. Local, &

B. Global, dot

C. Static, deference

D. Ordinary, deference

Overloaded member operator function is always called by ___

A.Class

B. Object

C. Compiler

D. Primitive data types

Encapsulation means_____.

A. That data becomes public.

B. That the data of a class cannot be accessed from outside.

C.That the data of a class can be accessed from outside.

D. That the can be accessible anywhere within a main program.

Memory allocated from heap or free store _____.

A.Can be allocated to classes only

B. Can be returned back to the system automatically

C. Cannot be returned back unless freed explicitly using malloc and realloc

D. Cannot be returned back unless freed explicitly using free and

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

delete operators

_____ operators are the ones that require two operators on both sides of the operator.

A. Unary

B. Binary

C. Double

D. Two sided

when the compiler overloads the assignment (=) operator by default then

A.Class members are not assigned properly.

B. Compiler does member wise assignment.

C. Compiler does not do member wise assignment.

D.Compiler does not allow default assignment operator.

In C language, the region of memory allocated at runtime is called_____

A. Stack

B. Heap

C. Free store

D. Available memory

_____is the pointer which determines the position in a file from where the next read operation occurs.

A. Set

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

B. Put

C. Get

D. Tell

Once we have defined a symbolic constant value using #defined, the value_____ during program.

A. Varies

B. Becomes zero

C. Can be changed.

D. Cannot be changed.

The function calloc takes two arguments, first argument is the_____ and the second argument is the _____.

A. Size of array, member of bytes.

B. Size of space, member of bytes.

C. Space in terms of string character, size of list.

D. Required space in terms of number. Size of space

The default visibility for the data members of the class is.

A. Public

B. Private

C. Protected

D. Accessible outside the class.

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

Symbolic constant Pi can be defined as.

A. #defined pi 3.14;

B. #defined pi 3.14

C. #include pi = 3.14

D. #defined pi = 3.14

When accessing a structure member, the identifier to the left of the dost operator is the name of_____.

A. Structure data

B. Structure tag

C. Structure member

D. Structure variable

_____Operator uses the sign ^.

A.Bit-wise OR

B. NOT operator

C.Exclusive OR

D. AND operator

We should not use such variable names that are starting with_____ because in C++, then names that start with it.

A. Double underscore

B. Lower case alphabets

C. Upper case alphabets

D. None of the given option

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

The statement cin.get (); is used to_____.

A.Read a string from file

B. Read a character from file

C. Read a string from keyboard

D. Read a character from keyboard Page 426

Ostream is a _____ operator.

A. None

B. Member

C. Dependent

D. Standalone

The second parameter of operator function for >> operator must always be passed

A.By value

B. By reference

C. None of the given option

D. Function takes no argument

If text is a pointer of type String, then what will be the functionality of following statement?text = new string [5];

A.Creates a string object

B. Creates array of of pointer to string

C. Creates array of 5 objects statistically

D. Creates array of 5 objects dynamically

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

When operator function is implemented as member function then return type of function ____.

A. Can be any data type

B. Must be built – in data type

C. Must be user defined data type

D. Must be an object of same class

We cannot define friends for the _____ that are already written and not in our control.

A. Classes

B. Functions

C. Destructor

D.Constructors

With user data type variables (Objects) self assignment can produce

A. Link error

B. Syntax error

C.Logical error

D.Run time error

When an operator function is defined as member function for a binary Plus (+) operator then the number of extra arguments it takes is/are.

A. One

B. Five

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

C. Zero

D. N arguments

The get member function, when passed no arguments, inputs an entire stream and returns it as the value of the function call.?

False

True

What will be the output of the following code segment?

Float pi=32.3996;

Cout<<fixed;

Cout<<setprecision(2)<<pi;

A. 32.00

B. 32.39

C. 32.40

D. 32.310

C++ provides member functions, which control the formatting to be performed during stream I/O operations.

True

False

In overloading the assignment (=) operator, which object(s) will call the operator function?

A.Right object of the assignment operator

B. No object will call the operator function

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

C.Left object of the assignment operator

D.Both objects will call the operator function

The was manipulator can be used with __ stream(s).

None of the given option

A.Input

B. Output

C.Both of these

D. None of the these

When we use cin stream to read some number from the keyboard and store it in the integer variable, then what will happen?

A.Its to ASCII code will be stored inside the computer

B. Some error will occure and cin stream will detect this error

C. Its binary representation will be ignored and the character will be stored

D.Its binary representation will be ignored and the value will be stored

*This is a pointer that always points to

A. A value of data member

B. Current object of the class

C. Current function of the class

D. Current pointer of the class

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

If operator function is non-member function, then object on left side of operator cannot be_____?

A.Built-in data type

B. Object of operator class

C. Object of different class

D. Object of member function

What is the purpose of endl stream manipulator?

A.Insert a new line

B. Flush the stream

C. Terminate a string with null

D.Insert a new line and flush the stream

Overloaded assignment operator must be

A. Global function

B. Friend function of class

C.Member function of class

D. Non-member function of class

C++ offers type-safe I/O. The << and >> operators are overloaded to accept data items of specific types.\

False

True

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

For the joining of two strings in string class, we may use “+” operator, can we use “-” operator the same way for subtracting strings?

A. Yes

B. No

C. Yes along “?” operator only

D. Yes along “+”operator only

:: is called _____.

A.Bitwise OR

B. Condition operator

C. One’s complement operator

D. Scope resolution operator

The stream insertion and extraction operators are not already overloaded for __

A. User- defined data types

B. Built-in data types

C. None of the given option

D.Both built –in and user – defined types

In C++ operators, which of the following operator cannot be overloaded _____.

A.-

B. ?

C. +

D. <<

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

Automatic variable are created on _____.

A. Heap

B. Stack

C. Free store

D. Static storage

When we used eof (end of file) with the file reading than which of the following is a true statement?

A. This is a way to check type of the stream

B. This is a way to check source of the stream

C.This is a way to check state of the stream

D. This is a way to check destination of the stream

Which one of the following is the declaration of overloaded pre increment operator implemented as member function?

A.Class –name operator +();

B. Class –name operator +(int);

C. Class –name operator ++();

D.Class –name operator ++(int);

The first parameter of operator function for << operator _____.

A. Must be object class

B. Must be passed by value

C.Must be passed by reference

D.Can be passed by value or reference

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

Ostream class is ____ and not under our control.

A. User-defined

B. Built-in

C. Both

D. None

Which of the following functionality can be achieved through overloading?

A.We can change associativity of all operator

B. We can change the precedence of same operator

C. We can change the associativity of some operator

D. New operator cannot be defined through operator overloading

The operator function for << (stream insertion) >> and stream extraction must be

A. None of given option

B. Member function of class

C. Non –member function of class

D.Both member and non-member function

Static variable which is defined in a function is initialized ____.

A. None of the above

B. Compile time of program

C. Every time the function call

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

D. Only once during its life time

Overloaded delete operator function takes parameter of void pointer and returns.

A. Void

B. Int pointer

C. Void pointer

D. Object pointer

_____ must be included to use stream manipulator in your code.

A.Conio.h

B. Stdlib.h

C. Iomanip

D.Iostream

Consider the following code, the printed value will be converted into:

int n = 10;

cout<<oct<<n;

A. base 2

B. base 8

C. base 10

D. decimal number system

Which of the following is normally a destination for cin stream?

A. Mouse

B. Printer

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

C. Variable

D. Keyboard

Which of the following is a destination of cout stream?

A. Printer

B. Constant

C. Variable

D. Data type

The return type of the operator function for << operator is ____.

A. Void

B. Class which we overload operator

C. Reference of ostrem class(istream&)

D.Reference of ostrem class(ostream&)

Static data members of a class can be ____.

A. Public

B. Private

C.Both

D. None

Once the _____ are created, they exist for the life time of the program

A. Local variables

B. Static variables Page 365

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

C. Automatic variables

D. non static variables

The members of a class declared with the keyword struct are _____by default.

A. Static

B. Public

C. Private

D. Protected

If the memory in the free store is not sufficient _____.

A. Malloc function returns 0

B. Malloc function returns 1

C. Malloc function returns free space

D.Malloc functions returns NULL pointer

This reference to a variable can be obtained by preceding the identifier of a variable with _____.

A. ^ sign

B. Operator

C. Dot operator

D. Ampersand sign &

Once an object is declared as a friend, _____.

A.It has access to public members only

B. It has to protected data members only

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

C. It has no access to data members of the class

D.It has access to all non-public members as if they were public

Reference variables must _____.

A.Contain zero value

B. Contain integer value

C.Be initialized after they are declared

D. Not be initialized after they are declared

What is the sequence of event(s) when allocating memory to an object using new operator?

A. Only destructor is called for object

B. Only block of memory is deallocated for object

C. Destructor is called first before deallocating memory

D.Memory is allocated first before calling constructor

The endl and flush are _____

Manipulators

Deleting an array of objects without specifying [] brackets may lead to memory leak.

False

True

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

A variable which is defined inside a function is called

Automatic variable

_____ variables are defined in the main.

Local

Assignment operator is used to initialize a newly declared object from existing object.

True

False

When a variable is defined as static in a class then _____.

Only one copy is created for all objects of this class

Within the statement obj1=obj2; obj1 will call the assignment operator function and obj2 will be passed as an argument to function.

True

False

Which of the following is normally a source for cin stream?

Keyboard

When an array of object is created dynamically then there is no way to provide parameterized constructors for array of objects.

True

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."

False

It is possible to return an object from function using this pointer.

True

False

"All contents within '**CS201 Important MCQ's' + subjective notes**, authored by **Binary Classroom**, are protected by copyright; reproduction and distribution without explicit permission is prohibited."