CS201 FOR FINAL TERM

UPDATED QUIZ 2 2021

PROVIDE BY ORANGE MONKEY

Remember Own Prayer

1. **To avoid dangling reference don't return**

   The reference of a local variable from the function……confirm

2. **Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?**

   Class name operator ++()….confirm from net

3. **Reference is a thing by which we can create _____ of any data type**

   Synonym…..confirm

4. **Reference cannot be uninitialized because it is impossible to _____.**

   Initialize a Null pointer…..confirm

5. **The syntax of declaration of a function that returns the reference to an integer is _____.**

   Int & myfunc()……confirm

6. **Friend function declaration can go _____ the class**

   Anywhere in……confirm

7. **To prevent dangling reference the functions returning reference should be used with _____.**

   Static and global variables…….confirm

8. **The only operator that the compiler overloads for user define data type be default in**

   Arrangement (=) operator …..confirm from net

9. **If operator function is non-member function then object on left side of operator cannot be _____?**

Object of member function…….confirm

10. Which of the following functionality can be achieved through overloading?

New operators cannot be defined through operator overloading

11. The return type of the overloading new operator must be?

Void*….confirm from net

12. For binary member operators, operands on the _____ derives (calls) the operation.

Left…….confirm

13. Identify the correct method of adding two strings, s1 and s2.

Strcat(s1,s2)

14. A friend function of a class is a function defined _____.

Outside that class and that has the right to access all members of the class

15. Care must be taken about the correct _____ of operator while overloading.

Both Semantic and Complexity……confirm from net

16. We can _____ reference.

None of the given….confirm

17. If text is a pointer of type string then what will be the functionality of following statement?

Text = new String {5};

Creates array of 5 objects dynamically…..confirm from net

18. Look at the statement given below
Int & a; and tell what will happen?

Compiler will generate an error 'a' declared as reference but not initialized……confirm

Remember Own Prayer

19. The syntax of declaration of a function that returns the reference to an integer is _____.

Int & myfunc();….confirm

20. Which of the following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

Delete []string;….confirm from net

21. If we do not write our own assignment operator then which of the following problem may occur?

22. Identify the correct syntax for making a class friend of other class

```
friend ClassOne
{
OtherClass;
private;
//here we write the data members of ClassOne
};
```

23. Once an object is declared as a friend _____

It has access to all non-public members as if they were public….confirm from net

24. Reference is a thing by which we can create _____ of any data type.

alias or synonym…both……confirm

25. A _____ function of a class is defined outside that class scope. But it can access all private and protected members of the class.

Firend…..confirm

26. Once the _____ are created they exist for the life time of the program

Static variables…..confirm

27. A class can be declared as a _____ of other class.

Friend….confirm

Remember Own Prayer

28. Reference variables must _____.

Be initialized after they are declared….confirm from net

29. We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally.

True

30. Operator overloading is to allow the same operator to be bound to more than one implementation, depending on the types of the _____.

Operands…….confirm

31. The friend keyword provides access _____.

In one direction only……confirm

32. The friend functions are _____.

Not member of a class….confirm

33. Ternary operator is shown as _____.

?;……confirm

34. Reference is not really an address it is _____.

A synonym

35. In C++ operators, which of the following operator cannot be overloaded _____.

?;…..confrim

36. Overloaded assignment operator must be

Member function of class

37. An address is a _____, while a pointer is a _____.

Variable, constant…confirm from net

38. When new operator is overloaded at global level then corresponding built-in new operator will also be visible to whole of the program.

False….confirm

Remember Own Prayer

39. When new or delete operator is overloaded at global level then corresponding built-in new or delete operator will not be visible to whole of the program.

True….confirm

40. When an operator function is defined as member function for a binary Plus (+) operator then the number of extra arguments it takes is/are

One….confirmF

41. i+=2 is equivalent to _____.

i= i + 2;

42. Assignment operator is used to initialize a newly declared object from existing object.

True….confirm from net

43. When an array of object is created dynamically then there is no way to provide parameterized constructors for array of objects.

True…confirm from net

44. In overloading the assignment (=) operator, which object will be passed as an arguments in the operator function?

Left object of the assignment operator

45. Friend functions are _____

Private

46. We can _____ pointer.

Decrement increment reassign…all options…… confirm

47. The function will return a reference to the global variable that exists throughout the program and thus there will be no danger of_____.

Dangling reference……confirm

48. The reference data types are used as _____ variables without any _____ operator.

Ordinary , deference…….confirm

Remember Own Prayer

49. What is the function of the following statement to delete an array of 5 objects named 'arr' allocated using new operator?
Delete arr;

Do not delete any object

50. If B is designated as friend of A, B can access A's non-public members

A cannot access B….confirm from net

51. What is the sequence of event(s) when deallocating memory of an object using delete operator?

Memory is dealloacted first before calling destructor…confirm from net

52. _____ operators are the ones that require two operands on both sides of the operator.

Binary…..confirm

53. Int & I; it means that i is a _____ to an integer.

Reference…..confirm

54. When operator function is implemented as member function then return type of function _____.

Can be any data type….confirm from net

55. The concept of _____ allows us to separate the interface from the implementation of the class.

Encapsulation….confirm

56. With user data type variables (objects) self assignment can produce

Logical error….confirm

57. When the compiler overloads the assignment (=) operator by default then

Compiler does member wise assignment..confirm from net

58. Which of the following is unary operator?

+i, i++, ==I …all options…..confirm

59. Reference is not really an address it is _____.

Remember Own Prayer

A synonym

60. What is meant by the following statement?
String str[5] = {String("Programming''), String("CS201")};

Parameterized constructor will be called for all objects of array

61. When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

Two…confirm

62. Friend classes are used in cases where one class is _____ to another class

Independent

63. The difference between pointers and references is that _____

We can do arithmetic with pointers….confirm

64. When an operator function is defined as member function for a Unary operator then the number of extra arguments it takes is/are.

One……confirm

65. *This is a pointer that always points to

Current pointer of the class

Remember Own Prayer

Question # 1:-

Care must be taken about the correct _____ of operator while overloading. (Choose the most appropriate).

1. Semantic
2. Complexity
3. Both Semantic and Complexity
4. None of the given options

Question # 2:-

In functions, that returns reference use _____.

1. global or local variables
2. global or static variables
3. ordinary variables

Question # 3:-

In overloading the assignment (=) operator, which object(s) will call the operator function?

1. Left object of the assignment operator
2. Right object of the assignment operator
3. Both objects will call the operator function
4. No object will call the operator function

Question # 4:-

Friend functions are _____.

1. Unidirectional **(not confirm)**
2. bidirectional
3. like inline functions
4. private

Question # 5:-

We cannot increment _____.

1. pointers
2. arrays
3. references
4. Vaiables

Question # 6:-

Remember Own Prayer

A pointer is _____.

1. the address of a variable
2. an indication of the variable to be accessed next.
3. the data type of an address variable

Question # 7:-

Overloaded assignment operator must be

1. Member function of class
2. Non-member function of class **(not confirm)**
3. Friend function of class
4. Global function

Question # 8:-

The concept of friend function negates the concept of _____.

1. inheritance
2. polymorphism
3. persistence
4. encapsulation

Question # 9:-

If class A is a friend of class B, and class B is a friend of class C. If class A wants class C to be a friend, _____

1. it has to declare, class C as a friend
2. it has to declare, class B as a friend
3. it has to declare , class A as a friend
4. it has to declare, class B and class A as friend classes

Question # 10:-

The difference between pointers and references is that _____.

1. we cannot do arithmetic with pointers

Remember Own Prayer

2. we can do arithmetic with pointers
3. we cannot reassign pointers
4. we can assign references

Question # 11:-

A reference cannot be _____.

1. 1
2. zero
3. NULL
1. 4 integer

Question # 12:-

An address is a _____ , while a pointer is a _____.

1. constant , variable
2. variable , constant
3. global , variable
4. non static variable , constant

Question # 13:-

The reference data types are used as _____ variables without any _____ operator

1. ordinary , deference
2. global , dot
3. static , deference
4. local , &

Question # 14:-

The syntax of declaration of a function that returns the reference to an integer is _____.

Remember Own Prayer

1. int & myfunc() ;
2. int myfunc();
3. int myfunc() &;
4. integer & myfunc();

Question # 15:-

References cannot be uninitialized. Because it is impossible to

_____

1. reinitialize a pointer
2. reinitialize a reference
3. initialize a NULL pointer

cast a pointer

mber Own Prayer

If we write a statement like **s2 = s1;** ___ will be the calling object and ____ will be passed to the = operator as an argument.

- ► s1, s1
- ► s1, s2
- ► **s2, s1**
- ► s2, s2

If we write a statement like *s2 = s1*; *s2* will be the calling object and *s1* will be passed to the = operator as an argument. P# 397

www.vuzs.info

what will be out put of cout <<setfill('0')<<setw(7)<<128;

Overloaded new operator function takes parameter of type *size_t* and returns

- ► **void (nothing)**

► **void pointer**
► **object pointer**
► **int pointer**

Also note that the *new* operator returns a *void* pointer. Any *new* operator we write must have this parameter and return type.

Which of the following is the correct way to declare a variable x of integer type?

► **x int ;**
► **integer x ;**
► **int x;**
► **x integer**

Reserve words cannot be used as a variable name.

► **True**
► **False**

There are few data types in C language. These data types are reserved words of C language. The reserve words can not be used as a variable manes. P# 17

A template function must have at least ---------- generic data type

► **Zero**
► **One**
► **Two**
► **Three**

The function arguments must contain at least one generic data type. P# 499

Template functions can also be overloaded

► **True**
► **False**

We can write overloaded template functions as long as there is use of different number or type of arguments.. P # 503

We can not make a member function of a class as template function.

► **True**
► **False not sure**

When break statement is encountered in switch statement, it

► **Stops the entire program**
► **Stops the execution of current statement**
► **Exits from switch statement**
► **None of the given options**

We can also define a variable of user define data type (object) as static.

- True
- False

The declarator of Plus (+) member operator function is

- Class-Name operator + (Class-Name rhs)
- operator Class-Name + ( )
- operator Class-Name + (rhs)
- Class-Name operator + ( )

Let suppose

```
int a, b, c, d, e;
a = b = c = d = e = 42;
```

This can be interpreted by the complier as:

- a = (b = (c = (d = (e = 42))));
- (a = b = (c = (d = (e = 42))));
- a = b = (c = (d = (e = 42)));
- (a = b) = (c = d) = (e = 42);

a = (b = (c = (d = (e = 42))));

What will be the range of numbers generated by function rand () % 9?

- 0 to 9
- 1 to 9
- 0 to 8
- 1 to 8

When 6 divides any number, the remainder will always be less than 6. Ther result will be between therefore we will add 1. 1 + rand ( ) % 6;

Which of the following is the correct function call having array named *student* of 10 elements as a parameter.

- addRecord(student[]) ;
- addRecord(student) ;
- addRecord(student[10]) ;
- addRecord(*student) ;

when we pass array we don't give limit of array

Example:

Pass array to function

```
#include
  #include
  void read(int *,int);
  void dis(int *,int);

  void main()
  {
   int a[5],b[5],c[5],i;

   printf("Enter the elements of first list \n");
   read(a,5);
   printf("The elements of first list are \n");
   dis(a,5);
  }

  void read(int c[],int i)
  {
   int j;
   for(j=0;j      scanf("%d",&c[j]);
   fflush(stdin);
  }

  void dis(int d[],int i)
  {
   int j;
   for(j=0;j     printf("%d ",d[j]);
   printf("\n");
  }
```

wn Prayer

Declaring structures does not mean that memory is allocated.
Example:

- ► **True**
- ► **False**

structures do not occupy any memory until it is associated with the structure variable

Identifier is a name that can be given to variables, labels and functions.

- ► **True**
- ► **False**

An 'Identifier' means any name that the user creates in his/her program. These names can be of variables, functions and labels

If a class A declares itself a friend of class B and a class B declares itself a friend of class C then

- ► **Class A is also a friend of class C.**
- ► **Class B is also a friend of class A.**
- ► **Class A is also a friend of class C if A declares C as its friend.**
- ► **Class A is also a friend of class C if C declares A as its friend.**

If we want a two-way relationship, OtherClass will have to declare ClassOne as a friend class, resulting in a complete two-way relationship

Which of the following statement is best regarding declaration of friend function?

- ► **Friend function must be declared after public keyword.**
- ► **Friend function must be declared after private keyword.**
- ► **Friend function must be declared at the top within class definition.**
- ► **It can be declared anywhere in class as these are not affected by the public and private keywords.**

Friend is a very strong statement. It is too strong to be affected by public or private we can put it anywhere in the class

A pointer is a special type of variable that contain _____

- ► **Memory Address**
- ► **Data values**
- ► **Both Values and Memory**
- ► **None of given of options**

Pointer is a special type of variable that contains a memory address.

When memory for a program is allocated at run time then it is called _____

- ► **static memory allocation**
- ► **dynamic memory allocation**
- ► **stack memory allocation**
- ► **virtual memory allocation**

When we create an object of the class at run time, it will allocate memory according to our requirement. So there is no waste of memory and the situations in which we want to store large data in small memory or vice versa are prevented. So we do dynamic memory allocation inside these classes.

What purpose do classes serve?

- ► **Data encapsulation**
- ► **Providing a convenient way of modeling real-world objects**
- ► **Simplifying code reuse**
- ► **All of the given options**

Which of the following function cannot be overloaded?

- ► **Member functions**
- ► **Utility functions**
- ► **Constructor**

► **Destructor**

The destructors can be summarized as The destructors cannot be overloaded. The destructors take no arguments. The destructors don't return a value

The following prototype of unary operator function indicates that it is _____ .
Date operator++(int)

► **Member functions of post increment operator**
► **Member functions of pre increment operator**
► **Non-member functions of post increment operator**
► **Non-member functions of pre increment operator**

Overloading Unary Operators

```
// Preincrement operator overloaded as a member function.
Date Date::operator++()
{
  helpIncrement();
  return *this;  // value return; not a reference return
}

// Postincrement operator overloaded as a member function.
// Note that the dummy integer parameter does not have a
// parameter name.
Date Date::operator++(int)
{
  Date temp = *this;
  helpIncrement();

  // return non-incremented, saved, temporary object
  return temp;   // value return; not a reference return
} // This paper was solved by vuzs Team and meant for hosting
at vuzs otherwise its stolen contents
```

Static variable which is defined in a function is initialized _____.

► **Only once during its life time**
► **Every time the function call**
► **Compile time of the program**
► **None of the above**

Once the static variables are created, they exist for the life of the program. They do not die.

In the member initialize list, the data members are initialized,

► **From left to right**
► **From right to left**
► **In the order in which they are defined within class**
► **None of the given options**

If we do not indent the code properly it will _____

- ► **Be a syntax error**
- ► **Be a logical error**
- ► **Not be an error at all**
- ► **None of the given options**

we Indent the code for better readability and understanding

Truth tables are used for analyzing _____.

- ► **logical expressions**
- ► **arithmetic expressions**
- ► **both logical and arithmetic expressions**
- ► **none of the given options.**

The truth tables are very important. These are still a tool available for analyzing logical expressions.

Static memory allocation is also known as _____

- ► **Dynamic allocation**
- ► **Compile time allocation**
- ► **Run time allocation**
- ► **None of the given options**

This type of memory static allocation. It is also known as compile time allocation.

Question No: 1 (Marks: 1) - Please choose one
When we define an array of objects then,
· Destructor will call once for whole array
· **Destructor will call for each object of the array**
· Destructor will never call
· Depends on the size of array

Question No: 2 (Marks: 1) - Please choose one
We can also create an array of user define data type
· **True**
· False

Question No: 3 (Marks: 1) - Please choose one
What is the sequence of event(s) when allocating memory using new operator?
· Only block of memory is allocated for objects
· Only constructor is called for objects
· **Memory is allocated first before calling constructor**
· Constructor is called first before allocating memory
If a single object is allocated, *operator new* is called to allocate memory, and then the constructor is called to initialize the object.

· If an array of objects is allocated, *operator new[]* is called to allocate memory for the whole array, and then the constructor is called for each element of the array.
· When a single object is deleted, the destructor for the object is called first, and then *operator delete* is called to free the memory occupied by the object.
· When an array of objects is deleted, the destructor for each element of the array object is called first, and then *operator delete[]* is called to free the memory occupied by the array.
http://www.vuzs.info/

Question No: 4 (Marks: 1) - Please choose one

We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally

· **True**
· False

Although, this is good to deallocate an array of objects without specifying array operator ([]) as there is no dynamic memory allocation occurring from inside the Date class. But this is a bad practice.

Question No: 5 (Marks: 1) - Please choose one

The declarator of Plus (+) member operator function is

· **Class-Name operator + (Class-Name rhs)**
· Operator Class-Name + ( )
· Operator Class-Name + (rhs)
· Class-Name operator + ( )

Page 371,373 example are here
Complex operator + (Complex &);
Complex operator + (parameter-list);
The syntax of the prototype of the overloaded operator function is:
return-type operator operator-symbol (parameter-list);
operator is the keyword here. An example of this will be as follows:
Complex operator + (Complex &);

Question No: 6 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are overloading these operators

· True (not sure)
· False

http://www.vuzs.info/

Question No: 7 (Marks: 1) - Please choose one

Which of the following is correct way to initialize a variable x of int type with value 10?

· int x ; x = 10 ;
· int x = 10 ;
· int x, x = 10;
· **x = 10 ;**

variable already created in question only it is asking for initialization.

Question No: 8 (Marks: 1) - Please choose one

Default mechanism of function calling in case of array is _____and in case of variable is _____

· Call by value, call by reference
· Call by referene, call by reference
· **Call by reference, call by value**
· Call by value, call by value

Question No: 9 (Marks: 1) - Please choose one

What does STL stand for?

· Source template library
· **Standard template library**
· Stream template library
· Standard temporary library

STL stands for Standard Template Library

Question No: 10 (Marks: 1) - Please choose one

Skill(s) that is/are needed by programmers _____

· Paying attention to detail
· Think about the reusability
· Think about user interface

· **All of the given options**

Programming is an important activity as people life and living depends on the programs one make. Hence while programming one should

o Paying attention to detail
o Think about the reusability.
o Think about user interface
o Understand the fact the computers are stupid
o Comment the code liberally

http://www.vuzs.info/

Question No: 11 (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

· int
· double
· float
· **char**

Question No: 12 (Marks: 1) - Please choose one

new and delete are _____whereas malloc and free are _____

· Functions, operators
· Classes, operators
· **Operators, functions**
· Operators, classes

new and delete are operators in c++

C functions like **malloc()** and **free()** functions can also be used from within C++ code

Question No: 13 (Marks: 1) - Please choose one

The prototype of friend functions must be written _____the class and its definition must be written _____

· inside, inside the class
· **inside, outside the class**
· outside, inside the class
· outside, outside the class

Question No: 14 (Marks: 1) - Please choose one

Friend function of a class are _____of a class.

· **Non-member functions** **not sure**
· Friend functions
· Any function outside class
· None of the given options

http://www.vuzs.info/

Question No: 15 (Marks: 1) - Please choose one

If overloaded plus operator is implemented as non-member function then which of the following statement will be true for the statement given below?

obj3 = obj1 + obj2 ;

· **obj2 will be passed as an argument to + operator whereas obj2 will drive the + operator**
· obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator
· Both objects (obj1, obj2) will be passed as arguments to the + operator
· Any of the objects (obj1, obj2) can drive the + operator

c3 = c1 + c2 ; In the above statement (c3 = c1 + c2;), c1 is the object that is calling or driving the **+** operator. **c2** object is being passed as an argument to the **+** operator. So c1 and c2 objects are added by the **+** operator and resultant

Question No: 16 (Marks: 1) - Please choose one

Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

· Class-name operator +() ;
· Class-name operator +(int) ;
· **Class-name operator ++()** ;
· Class-name operator ++(int) ;

Overloading Unary Operators

```
// Preincrement operator overloaded as a member function.
Date Date::operator++()
{
   helpIncrement();
   return *this;  // value return; not a reference return
}

// Postincrement operator overloaded as a member function.
// Note that the dummy integer parameter does not have a
// parameter name.
Date Date::operator++(int)
{
   Date temp = *this;
   helpIncrement();

   // return non-incremented, saved, temporary object
   return temp;   // value return; not a reference return
}
```

Question No: 17 **(Marks: 1) - Please choose one**

For cin, the source is normally a _____and destination can be _____

· File, native data type

· Disk, user-define type

· Keyboard, variable

· File, user-define type

For cin, the source is normally keyboard and the destination can be an ordinary variable i.e. native-data type variable. It could be some area of memory or our own data type, i.e. object for which we h

Question No: 18 **(Marks: 1) - Please choose one**

We can do condition compilation with pre processor directives.

· True

· False

All the preprocessor directives start with the sharp sign (#). We can also do conditional compilation with it.

Question No: 19 **(Marks: 1) - Please choose one**

The programs, in which we allocate static memory, run essentially on _____

· Heap

· System Cache

· None of the given options

· Stack

The programs, in which we allocate static memory, run essentially on stack

Question No: 20 **(Marks: 1) - Please choose one**

A template function must have at least ---------- or more arguments

· Zero

· One

· Two

· Three

The function arguments must contain at least one generic data type. Normal function declaration is: return_type function_name(argument_list)

Question No: 21 **(Marks: 1) - Please choose one**

The default value of a parameter can be provided inside the _____

· function prototype

· function definition

· both function prototype or function definition

· none of the given options

The default value of a parameter is provided inside the function prototype or function definition.

Question No: 22 **(Marks: 1) - Please choose one**

While calling function, the arguments are assigned to the parameters from _____

· left to right

· right to left

· no specific order is followed
· none of the given options

While calling function, the arguments are assigned to the parameters from left to right.

Question No: 23 (Marks: 1) - Please choose one
When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are

· Zero
· One
· Two
· N arguments

Operators as member functions
Aside from the operators which must be members, operators may be overloaded as member or non-member functions. The choice of whether or not to overload as a member is up to the programmer. Operators are generally overloaded as members when they:
change the left-hand operand, or
1. require direct access to the non-public parts of an object.
When an operator is defined as a member, the number of explicit parameters is reduced by one, as the calling object is implicitly supplied as an operand. Thus, binary operators take one explicit parameter and unary operators none. In the case of binary operators, the left hand operand is the calling object, and no type coercion will be done upon it.

Question No: 24 (Marks: 1) - Please choose one
new operator allocates memory from free store and return _____
· A pointer
· A reference
· An integer
· A float

Question No: 25 (Marks: 1) - Please choose one
With user-defined data type variables (Objects), self assignment can produce____

· Syntax error not sure
· Logical error
· Link error
· Non of the given options

Question No: 26 (Marks: 1) – Write Simple Program
Assignment operator is used to initialize a newly declared object from existing object
· True
· False

Question No: 27 (Marks: 1) – Briefly define/Justify
When an object of a class is defined inside an other class then,
· Constructor of enclosing class will be called first
· Constructor of inner object will be called first
· Constructor and Destructor will be called simultaneously
· None of the given options
• ***A class can contain instances of other classes as its data members.*** • It is a way of reusing the code when we contain objects of our already written classes into a new class.
• The inner data members of the object are constructed and then the object itself.
The order of destruction of an object is reverse to this construction order, where the outer object is destroyed first before the inner data members.
• Initializer list is used to initialize the inner objects at the construction time.
• In C++, we can have structures or classes defined inside classes. Classes defined within other classes are called nested classes.

Question No: 28 (Marks: 1) – Brief answer required
In the member initializer list, the data members are initialized,
· From left to right
· From right to left
· In the order in which they are defined within class
· None of the given options

Question No: 29 (Marks: 1) - Brief answer required

"new" and "delete" keywords are _____in C++ language

· Built-in- Function

· **Operators**

· Memory Allocation Function

· None of the given options

Remember Own Prayer

In C/C++ if we define an array of size eight (8) i.e. int Arr [8]; then the last element of this array will be stored at,

► Arr[0]

- Arr[8]
- **Arr[7]**
- Arr[-1]

Question No: 2 (M - 1) .
When an array is passed to a function then default way of passing this array is,

- By data
- **By reference**
- By value
- By data type

Question No: 3 (M - 1) .
Array is a data structure which store

- Memory addresses
- Variables
- Data Type
- **Data**

Question No: 4 (M - 1) .
We can also create an array of user define data type.

- **True**
- False

Question No: 5 (M - 1) .
When we define an array of objects then,

- Destructor will call once for whole array
- **Destructor will call for each object of the array**
- Destructor will never call
- Depends on the size of array

Question No: 6 (M - 1) .
What is the sequence of event(s) when allocating memory using new operator?

- Only block of memory is allocated for objects
- Only constructor is called for objects
- **Memory is allocated first before calling constructor**
- Constructor is called first before allocating memory

Question No: 7 (M - 1) .
We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally.

- **True**
- False

Question No: 8 (M - 1) .
The second parameter of operator functions for are objects of the class for which we are overloading these operators.

- **True**
- False

Question No: 9 (M - 1) .
Which of the following is correct way to initialize a variable x of int type with value 10?

- int x ; x = 10 ;
- int x = 10 ;
- int x, x = 10;
- **x = 10 ;**

Question No: 10 (M - 1) .
Default mechanism of function calling in case of array is _____ and in case of variable is ___.

- Call by value, call by reference
- Call by referene, call by reference
- **Call by reference, call by value**
- Call by value, call by value

Question No: 11 (M - 1) .
What does STL stand for?

- ► Source template library
- ► **Standard template library**
- ► Stream template library
- ► Standard temporary library

Question No: 12 (M - 1) .
Skill(s) that is/are needed by programmers _____.

- ► Paying attention to detail
- ► Think about the reusability
- ► Think about user interface
- ► **All of the given options**

Question No: 13 (M - 1) .
For which array, the size of the array should be one more than the number of elements in an array?

- ► int
- ► double
- ► float
- ► **char**

Question No: 14 (M - 1) .
new and delete are _____ whereas malloc and free are _____.

- ► Functions, operators
- ► Classes, operators
- ► **Operators, functions**
- ► Operators, classes

Question No: 15 (M - 1) .
Friend functions are _____ of a class.

- ► Member functions
- ► Public member functions
- ► Private member functions
- ► **Non-member functions**

Question No: 16 (M - 1) .
The prototype of friend functions must be written ____ the class and its definition must be written ____

- ► inside, inside the class
- ► **inside, outside the class**
- ► outside, inside the class
- ► outside, outside the class

Question No: 17 (M - 1) .
If overloaded plus operator is implemented as non-member function then which of the following statement will be true for the statement given below?
obj3 = obj1 + obj2 ;

- ► obj2 will be passed as an argument to + operator whereas obj2 will drive the + operator
- ► **obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator**
- ► Both objects (obj1, obj2) will be passed as arguments to the + operator
- ► Any of the objects (obj1, obj2) can drive the + operator

Question No: 18 (M - 1) .
Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

- ► Class-name operator +() ;
- ► Class-name operator +(int) ;
- ► **Class-name operator ++() ;**
- ► Class-name operator ++(int) ;

Question No: 19 (M - 1) .
For cin, the source is normally a _____ and destination can be _____.

- ► File, native data type
- ► Disk, user-define type

► **Keyboard, variable**
► File, user-define type

Question No: 20 (M - 1) .
We can also do conditional compilation with preprocessor directives.

► **True**
► False

Question No: 21 (M - 1) .
The programs, in which we allocate static memory, run essentially on _____

► Heap
► System Cache
► None of the given options
► **Stack**

Question No: 22 (M - 1) .
The default value of a parameter can be provided inside the _____

► function prototype
► function definition
► **both function prototype or function definition**
► none of the given options.

Question No: 23 (M - 1) .
While calling function, the arguments are assigned to the parameters from _____.

► **left to right.**
► right to left
► no specific order is followed
► none of the given options.

Question No: 24 (M - 1) .
When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

► Zero
► **One**
► Two
► N arguments

Question No: 25 (M - 1) .
With user-defined data type variables (Objects), self assignment can produce _____.

► Syntax error
► **Logical error**
► Link error
► Non of the given options

Question No: 26 (M - 1) .
Assignment operator is used to initialize a newly declared object from existing object.

► **True**
► False

Question No: 27 (M - 1) .
When an object of a class is defined inside an other class then,

► Constructor of enclosing class will be called first
► **Constructor of inner object will be called first**
► Constructor and Destructor will be called simultaneously
► None of the given options

Question No: 28 (M - 1) .
In the member initializer list, the data members are initialized,

► From left to right
► From right to left
► **In the order in which they are defined within class**
► None of the given options

Question No: 29 (M - 1) .
new operator allocates memory from free store and return _____.

- ► **A pointer**
- ► A reference
- ► An integer
- ► A float

Question No: 30 (M - 1) .
"new" and "delete" keywords are _____ in C++ language.

- ► Built-in- Function
- ► **Operators**
- ► Memory Allocation Function
- ► None of the given options

Remember Own Praye

Operator overloading can be performed through_____.

- ► Classes
- ► **Functions**
- ► Operators
- ► Reference

Question No: 2 (M - 1) .
When a value is referred by a normal variable then it is known as,

- ► **Direct Reference**
- ► Indirect Reference
- ► Partial Reference
- ► Proper Reference

When a value is referred by a normal variable is known as direct reference

Question No: 3 (M - 1) .
Which of the following function is used to increase the size of already allocated memory chunk?

- ► malloc
- ► calloc
- ► **realloc**
- ► free

(FQ, vuzs, 2010)

Question No: 4 (M - 1) .
Which of the following is NOT a preprocessor directive?

- ► #error

► #define
► #line
► **#ndefine**

list of preprocessors
• #include • #include "filename" • #define • #undef • #ifdef • #ifndef • #if • #else • #elif • #endif • #error • #line • #pragma • #assert

Question No: 5 (M - 1) .
The stream objects **cin** and **cout** are included in which header file?
► **iostream.h**
► fstream.h
► istream.h
► ostream.h
http://www.vuzs.info/
Question No: 6 (M - 1) .
Overloaded delete operator function takes the same parameter as an argument returned by new operator function.
► **True**
► False
The same pointer that is returned by the new operator, is passed as an argument to the delete operator. These rules apply to both, if operators (new and delete) are overloaded as member or non-member operators (as global operators).

Question No: 7 (M - 1) .
When an array of object is created dynamically then there is no way to provide parameterized constructors for array of objects.
► **True**
► False
if we are allocating an array of objects, there is no way to pass arguments to objects' constructors. Therefore it is required that the objects that are stored in such an array have a no-argument constructor.

Question No: 8 (M - 1) .
C is widely known as development language of _____ operating system.
► Linux
► Windows
► **Unix**
► Mac OS
In the start C became widely known as the development language of the UNIX operating system, and the UNIX operating system was written by using this C language. The C language is so powerful that the compiler of C and other various operating systems are written in C.
http://vuzs.ne
Question No: 9 (M - 1) .
Computer can understand only machine language code.
► **True**
► False
Question No: 10 (M - 1) .
We can not define a function as a friend of a Template class.
► True
► **False**

Class templates can have friends. A class or class template, function, or function template can be a friend to a template class. Friends can also be specializations of a class template or function template, but not partial specializations.

Remember Only Prayer

Question No: 11 (M - 1) .
What will be the value of 'a' and 'b' after executing the following statements?
a = 3;
b = a++;

- ► 3, 4
- ► 4, 4
- ► 3, 3
- ► **4, 3**

Question No: 12 (M - 1) .
Consider the following code segment. What will be the output of following code?

```
int addValue (int *a){
int b = (*a) + 2;
return b ;
}
main () {
int x =6 ;
cout <<  x << ",” ;
cout << addValue(&x) << ",” ;
cout <<  x ;
}
```

http://vuzs.ne

- ► **6,8,6**
- ► 6,6,8
- ► 6,8,8
- ► 6,6,6

http://www.vuzs.info/

Question No: 13 (M - 1) .
_____ is used to trace the logic of the program and correct the logical errors.

- ► Compiler
- ► Editor
- ► Linker
- ► **Debugger**

Question No: 14 (M - 1) .
new and delete are _____ whereas malloc and free are _____.

- ► Functions, operators
- ► Classes, operators
- ► **Operators, functions**
- ► Operators, classes

Hence, we can call new and delete operators, P# 342
we have allocated a memory space for our use by malloc function. P# 285

Question No: 15 (M - 1) .
Like member functions, _____ can also access the private data members of a class.

- ► Non-member functions
- ► **Friend functions**
- ► Any function outside class
- ► None of the given options

Question No: 16 (M - 1) .
Which situation would require the use of a non-member overloaded operator?

- ► The overloaded operator is an Assignment operator.

http://vuzs.ne

► The left most operand is an object of a class.

► **The left operand is built-in data type.**

► The operator returns a reference.

(100% confirmed by Rainbowbright)

Question No: 17 (M - 1) .

The stream insertion and stream extraction operators are already overloaded for _____.

► User-defined data types

► **Built-in data types**

► User-defined and built-in data types

► None of the given options

Question No: 18 (M - 1) .

If we define an identifier with the statement **#define PI 3.1415926** then during the execution of the program the value of PI _____.

► can not be replaced

► None of the given options

► **Remain constant.**

► can be changed by some operation

Question No: 19 (M - 1) . vuzs

Assignment operator is ----------associative.

► **right**

► left

► binary

► unary

You can assign values to several variables in a single statement. For example, the following code sets the contents of apples and oranges to the same value:
apples = oranges = 10;
The assignment operator is right associative, so this statement executes by first storing the value 10 in oranges and then storing the value in oranges in apples, so it is effectively
apples = (oranges = 10);

http://www.vuzs.info/

Question No: 20 (M - 1) .

When ever dynamic memory allocation is made in C/C++, it is freed_____.

► **Explicitly**

► Implicitly

► Both explicitly and implicitly

► None of the given options

(Rainbowbright, vuzs. jul2011)

Question No: 21 (M - 1) .

The appropriate data type to store the number of rows and colums of the matrix is_____.

► float

► **int**

► char

► none of the given options.

Question No: 22 (M - 1) .

Which of the following function do NOT initialize the chunk of memory to all zero?

► calloc() function

► Both malloc() and calloc()

► None of the above

► **malloc() function**

The **malloc** function differs from **calloc** in the way that the space allocated by **malloc** is not initialized and contains any values initially.

Question No: 23 (M - 1) .
The function free() returns back the allocated memory got thorough calloc and malloc to _____ .

- ► stack
- ► **heap**
- ► stack and heap
- ► None of the given options

http://vuzs.ne

Question No: 24 (M - 1) .
width() is member function of _____

- ► cin object
- ► cout object
- ► **Both cin and cout object**
- ► None of the given option

Question No: 25 (M - 1) .

Templates are not type safe.

- ► true
- ► **false**

Templates are type-safe. This is because the types that templates act upon are known at compile time, so the compiler can perform type checking before errors occur.

Question No: 26 (M - 1) .
A Matrix can be composed of ints, floats or doubles as their elements. Best way is to handle this , _____

- ► Write a separate class to handle each
- ► **Use templates**
- ► Use strings to store all types
- ► None of the given options

1. For binary member operators, operands on the _____ drives (calls) the operation.

Left

2. We cannot increment _____.

references

3. We can _____ pointer.

all of the given

4. We can _____ references.

None of the given

Remember Own Pray

5. What will be the correct syntax for the following function call?
float add (int &);

add(x);

6. An instance of a class is called _____.

object

7. The _____ is called automatically when an object destroys

destructor

8. The destructor is used to _____.

1. deallocate memory

9. _____ data isn't accessible by non-member functions or outside classes.

private

10. Member functions of the class _____ main program.

1. are accessible from

11. Overloading means :

1. Using the same name to perform multiple tasks or different tasks depending on the situation.

12. The main advantage of function overloading is _____.

1. The program becomes more readable

13. You cannot overload the _____ operator.

1. ? :

Remember Own Prayer

14. In C++, a variable can be declared anywhere in the program this will increase _____.

1. efficiency

15. Memory allocated from heap or free store _____.

1. cannot be returned back unless freed explicitly using free and delete operators

16. We cannot use _____ pointer for storing and reading data from it.

1. 'NULL

17. The dynamic memory allocation uses _____ whereas static memory allocation uses _____.

1. heap , stack

18. What will be the output of the given code?

```
#include #define MAX( A, B ) ((A) > (B) ? (A) : (B))
void main() {
int i, x, y;
x = 23;
y = 45;
i = MAX( x++, y++ );
// Side-effect: // larger value incremented twice
cout<< "x = " << x << " y = " << y << '\n';
}
```

1. x=24 y=47

19. NULL has been defined in _____ header file.

1. Stdlib.h

20. Symbolic constant PI can be defined as:

1. #define PI 3.14

21. The friend function of a class can have access _____.

Remember Own Prayer

1. to the private data members

22. C++ was developed by _____.

1. BejarneStroustrup

23. Once the _____ are created, they exist for the life time of the program.

1. static variables

24. Encapsulation means _____.

1. that the data of a class can be accessed from outside

25. An address is a _____, while a pointer is a _____.

1. variable, constant

26. The syntax of declaration of a function that returns the reference to an integer is _____.

1. int &myfunc();
2. int myfunc();
3. int myfunc() &;
4. integer &myfunc();

27. Which one of the following is mandatory preprocessor directive for c++?

1. #undef
2. #include
3. #undef
4. All of the given

28. The members of a class declared with the keyword struct are _____ by default.

1. static
2. Private
3. protected
4. public

Remember Own Prayer

29. getche() is a _____ function and defined in _____ header file.

1. user-define function ,conio.h
2. built-in function ,conio.h
3. built-in function, stlib.h
4. built -in function, iostream.h

30. _____ operators are the ones that require two operands on both sides of the operator.

1. Double
2. Tow sided
3. Binary
4. None of the given

31. _____ will return the number of bytes reserved for a variable or data type.

1. sizeof operator
2. free operator
3. void pointer
4. new operator

32. _____ are not available in C language.

1. User defned functions
2. Built in functions
3. Library functions
4. Inline functions

33. The members of a class declared without any keyword are _____ by default.

1. protected
2. private
3. public
4. constant

34. For console input and output we use _____.

Remember Own Prayer

1. conio.h header file
2. stdlib.h header file
3. process.h header file
4. getch.h header file

35. The name of the destructor is the same as that of a class proceeding with a _____.

1. &sign
2. # sign
3. @ sign
4. ~ sign

36. A reference cannot be NULL it has to point a data type.

1. True
2. False

37. A pointer is _____.

1. the address of a variable
2. an indication of the variable to be accessed next
3. a variable for storing address
4. the data type of an address variable

38. Constructor is a special function, called whenever we _____.

1. create a function
2. instantiate an object of a class
3. destroy an object
4. create a class

39. Symbolic constant PI can be defined as:

1. #define PI 3.14;
2. #define PI 3.14
3. #define PI=3.14
4. # include pi=3.14

40. Object code is machine code but it is not _____ and _____.

Remember Own Prayer

1. relocatable, executable
2. faster, efficient
3. compiled, debugged
4. tested, compiled

41. The default visibility for the data members of the class is

1. private
2. protected
3. public
4. accessible outside the class

42. The _____ is called automatically when an object destroys.

1. destructor
2. constructor
3. main program
4. default constructor

43. Constructor is special type of function :

1. which has no return type
2. which returns NULL pointer
3. which returns zero
4. which returns integer type data

44. _____ variables are those that are defined outside of main.

1. Local
2. Dynamic
3. Global
4. Static

45. Within the statement obj1=obj2; obj1 will call the assignment operator function and obj2 will be passed as an argument to function.

1. True

Remember Own Prayer

2. False

46. When the compiler overload the assignment (=) operator by default then

1. Class members are not assigned properly
2. Compiler does not allow default assignment operator
3. Compiler does member wise assignment.
4. None of the given

47. It is possible to return an object from function using this pointer.

1. True
2. False

48. Overloaded assignment operator must be

1. Member function of class
2. Non-member function of class
3. Friend function of class
4. Global function

49. Let suppose
int a, b, c, d, e;
a = b = c = d = e = 42;
This can be interpreted by the compiler as

1. (a = b = (c = (d = (e = 42))));
2. a = (b = (c = (d = (e = 42))));
3. a = b = (c = (d = (e = 42)));
4. (a = b) = (c = d) = (e = 42);

50. In statement a+b+c, at first

1. a+b is executed first
2. b+c is executed first
3. All executed at the same time
4. None of the given

51. Suppose int i = 10; then what is the output of cout<<oct<<i;

Remember Own Prayer

1. 10
2. 11
3. 12
4. 13

52. ostream is a _____ operator.

1. dependent
2. member
3. standalone
4. None of the given

53. _____ must be included to use stream manipulation in your code.

1. conio.h
2. iostream
3. stdlib.h
4. iomanip

54. _____ operators are the ones that require only one operator to work.

1. Unit
2. Unary
3. Single
4. None of the given

55. The endl and flush are _____.

1. Functions
2. Operators
3. Manipulators
4. Objects

56. When operator function is implemented as member function then return type of function _____.

1. Must be an object of same class
2. Must be user-defined data type
3. Must be built-in data type

Remember Own Prayer

4. Can be any data type

57. When a variable is defined as static in a class then _____.

1. Separate copy of this variable is created for each object
2. Only one copy is created for all objects of this class
3. A copy of this variable is created for only static objects
4. None of the given

58. Automatic variables are created on _____.

1. Heap
2. Free store
3. Static storage
4. stack

59.
```
cout<<i<< " ";
cout<< d <<" ";
cout<< f;
```

Above statements can be written within statement of one line as:

1. cout<<i<<" "<< d " "<< f << ;
2. cout<<i<<<< d <<<< f <<;
3. cout<<i<<" "<< d <<" "<< f;
4. cout<<i<< " "<< d <<" " f<<;

60. dec, hex, oct are all _____.

1. Member functions
2. Objects of input/output streams
3. Parameterized manipulators
4. Non-parameterized manipulators

61. What will be the output of following statement?
```
cout<<setfill('0')<<setw(7)<< 128;
```

1. 0128128
2. 0000128

Remember Own Prayer

3. 1280000
4. 0012800

62. Which of the following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

1. delete string;
2. delete []string;
3. delete string[];
4. delete string[5];

63. If we have a program that writes the output data(numbers) to the disc, and if we collect the output data and write it on the disc in one write operation instead of writing the numbers one by one.
In the above situation the area where we will gather the number is called

1. Heap
2. Stack
3. Buffer
4. Cache

64. The first parameter of operator function for << operator _____.

1. Must be passed by value
2. Must be passed by reference
3. Can be passed by value or reference
4. Must be object of class

65. The second parameter of operator function for >> operator must always be passed

1. By reference
2. Function takes no argument
3. By value
4. None of the given

Remember Own Prayer

66. The only operator that the compiler overloads for user define data type by default is

1. Plus (+) operator
2. MInus (-) operator
3. Assignment (=) operator
4. Equal (==) operator

67. Consider the following code, the printed value will be converted into:

```
int n=10;
cout<<oct<<n;
```

1. Base 8
2. Base 2
3. Base 10
4. Decimal number system

68. _____ variables are defined in the main.

1. Global
2. Dynamic
3. Local
4. All

69. ostream class is _____ and not under our control.

1. user-defined
2. built-in
3. both user-defined and built-in
4. None of the given

70. The memory allocation in C++ is carried out with the help of _____.

1. NULL pointer
2. new operator
3. dot operator
4. + operator

Remember Own Prayer

71. If B is designated as friend of A, B can access A's non-public members.

1. B cannot access private member of A
2. B cannot access protected member of A
3. A can access non-public members of B
4. A cannot access B

72. If the request of new operator is not fulfilled due to insufficient memory in the heap _____.

1. the new operator returns 2
2. the new operator returns 1
3. the operator returns 0
4. free operator returns nothing

73. We should not use such variable names that are starting with _____ because in C++, there are lots of internal constants and symbolic names that start with it.

1. upper case alphabets
2. lower case alphabets
3. double underscore
4. None of the given

74. The friend keyword provides access _____.

1. in one direction only
2. in two directions
3. to all classes
4. to the data members of the friend class only

75. The malloc function takes _____ argument(s).

1. two
2. three
3. four
4. one

76. The constructor contains _____.

Remember Own Prayer

1. return type
2. no return type
3. objects
4. classes

77. What will be the output of the following c++ code?

```
#include<iostream.h>
#define max 100
main()
{
#ifdef max
Cout<<"Hellow;
}
```

1. Hello
2. "Hellow"
3. Max is 100
4. Error

78. Once we have defined a symbolic constant value using #define, that value _____ during program execution

1. can be changed
2. cannot be changed
3. varies
4. becomes zero

79. The memory allocation functions return a chunk of memory with a pointer of type _____.

1. integer
2. float
3. ptr
4. void

80. A class can be declared as a _____ of other class.

1. member
2. member function
3. friend

Remember Own Prayer

4. part

81. To avoid dangling reference, don't return _____.

1. the reference of a local variable from the function
2. the reference of a global variable from the function
3. the reference of a static variable from the function
4. the reference of a private data member from the function

82. Constructor is itself a _____ of C++ and _____.

1. class, can be overloaded
2. function, cannot be overloaded
3. function, can be overloaded
4. object, can not be initialized

83. The parameter passed to isdigit() function is _____ variable.

1. Character
2. Boolean
3. Integer
4. Float

84. char **argv can be read as _____.

1. pointer to pointer
2. pointer to char
3. pointer to pointer to char
4. None of the given

85. To read command-line arguments, the main() function itself must be given _____ arguments.

1. 1
2. 2
3. 3
4. 4

86. How many bytes an integer type pointer intPtr will jump in memory if the statement below is executed?
intPtr += 2 ;

Remember Own Prayer

1. 2
2. 4
3. 8
4. 12

87. The increment of a pointer depends on its _____.

1. variable
2. value
3. data type
4. None of the given

88. The statement cout<<yptr will show the _____ theyptr points to.

1. Value
2. memory address
3. variable
4. None of the given

89. _____ is used as a dereferencing operator.

1. *
2. +
3. -
4. None of the above

90. Transpose of a matrix means that when we interchange rows and columns _____.

1. the first row becomes the Last column
2. the first row becomes the first column
3. the Last row becomes the first column
4. the first column becomes the first row

91. Individual characters in a string stored in an array can be accessed directly using array _____.

1. superscript
2. script
3. subscript

Remember Own Prayer

4. value

92. We can define a matrix as _____ array.

1. Sorted
2. Unsorted
3. Single dimensional
4. Multi dimensional

93. A _____ is an array of characters that can store number of character specified.

1. Char
2. String
3. Multidimensional array
4. Data type

94. Given a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?

1. array[3][4] = 6 ;
2. array[2][4] = 6 ;
3. array[4][3] = 6 ;
4. array[2][3] = 6 ;

95. _____ of a variable means the locations within a program from where it can be accessed.

1. Data type
2. Visibility
3. Value
4. Reference

96. Which of the following function call is "call by reference" for the following function prototype?
int add (int *);

1. add(&x);
2. add(int x);
3. add(x);

Remember Own Prayer

4. add(*x);

97. Which of the following function call is "call by reference" for the following function prototype?
float add (float *);

1. add(&x);
2. add(float x);
3. add(x);
4. add(*x);

98. Which of the function call is call by value for the following function prototype?
float add(float);

1. add(&x);
2. add(x);
3. add(float x);
4. add(*x);

99. Which of the function call is "call by value" for the following function prototype?
float add(int);

1. add(&x);
2. add(x);
3. add(int x);
4. add(*x);

100. Return type of a function that does not return any value must be _____.

1. char
2. int
3. void
4. double

101. _____ will be used for enclosing function statements into a block.

1. " "

Remember Own Prayer

2. ()
3. []
4. {}

102. What is the output of the following code if the 2nd case is true

```
switch (var) {
case 'a': cout<<"apple"<<endl;
case 'b':cout<<"banana"<<endl;
case 'm':cout<<"mango"<<endl;
default: cout<<"any fruit"<<endl;
}
```

1. banana
2. banana
   any fruit
3. banana
   mango
   any fruit
4. None of the given

103. When the break statement is encountered in a loop's body, it transfers the control _____ from the current loop.

1. Inside
2. Outside
3. To break statement
4. To continue statement

104. What is the output of the following code if the 3rd case is true

```
switch (var) {
case 'a':cout<<"apple"<<endl;
case 'b':cout<<"banana"<<endl;
case 'm':cout<<"mango"<<endl;
default: cout<<"any fruit"<<endl;
}
```

Remember Own Prayer

1. mango
2. mango
   any fruit
3. apple
4. None of the given

105. What is the output of the following code, if the first case is true

```
switch (var) {
case 'a':cout<<"apple"<<endl;
case 'b':cout<<"banana"<<endl;
case 'm':cout<<"mango"<<endl;
default: cout<<"any fruit"<<endl;
}
```

1. apple
2. apple
   any fruit
3. apple
   banana
   mango
   any fruit
4. none of above

106. What will be the output of following code segment?

```
for (int i = 2; i<10; i++) {
if ( i == 5) continue;
cout<<i<< "," ;
}
```

1. 2,3,7,8,9
2. 2,3,4,6,7,8,9
3. 2,3,4
4. 4,6,7,8,9

107. _____ statement is used to terminate the processing of a particular case and exit from switch structure.

Remember Own Prayer

1. if
2. goto
3. break
4. continue

108. What will be the result of the expression j = i++; if initially j = 0 and i = 5?

1. 0
2. 5
3. 6
4. 4

109. What will be the result of the expression k = ++m; if initially k = 0 and m = 4?

1. 0
2. 5
3. 6
4. 4

110. What will be the result of the expression k = ++m; if initially k = 0 and m = 5?

1. 0
2. 5
3. 6
4. 4

111. How many times the following do-while loop will execute?
int k = 10; do { cout<< "Statements" <<endl; k -= 2; } while(k>0);

1. 4
2. 5
3. 6
4. 7

112. Which of the following loops checks the test condition at the end of the loop?

Remember Own Prayer

1. While
2. Do-While
3. For
4. Nested Loop

113. The operators ++ and -- are used to increment or decrement the value of a variable by _____.

1. 3
2. 2
3. 1
4. 4

114. How many times the following loop will execute? int j = 3; while(j > 0) { cout<< "Statements" <<endl; j -= 2; }

1. 0
2. 1
3. 2
4. 3

115. A _____ structure specifies that an action is to be repeated while some condition remains true.

1. Control
2. Logical
3. Repetition
4. Relational

116. !(x> 3) means in C++ that

1. x is greater than 3
2. x is less than or equal to 3
3. x is less than 3
4. x is equal to 3

117. When the logical operator && combines two expressions then the result will be true only when the both expressions are _____.

Remember Own Prayer

1. Logical
2. Arithmetic
3. true
4. false

118. < and > both are _____ operators.

1. Arithmetic
2. Relational
3. Logical
4. Mathematical

119. What will be the value of variable "input" if the initial value of input is 67?

```
if(input >= 50)
input = input + 1;
if(input <= 75)
input = input + 2;
else
input = input - 1;
```

1. 68
2. 69
3. 70
4. 66

120. !(x< 3) means in C++ that

1. x is less than 3
2. x is greater than or equal to 3
3. x is greater than 3
4. x is equal to 3

121. != operator is used to check whether the operand on the left-hand-side is _____ to the operand on the right-hand-side.

1. Less than or equal
2. Greater than or equal
3. Not equal

Remember Own Prayer

4. Approximately equal to

122. When the if statement consists more than one statement then enclosing these statement in curly braces is,

1. Not required
2. Good programming
3. Relevant
4. Must

123. The most suitable data type for number 325.25 is _____.

1. char
2. int
3. short
4. float

124. What will be the result of arithmetic expression 6+48/4*3?

1. 10
2. 40.5
3. 42
4. 41

125. Which of the following will be the most appropriate data type to store the value 63.547?

1. Integer
2. Character
3. Short
4. Float

126. In the given expression which operator will be evaluated first? 10 + (6 / 2) - 2 * 3?

1. +
2. -
3. /

Remember Own Prayer

4. *

127. What will be the value of the variable output in the given piece of code?

```
double output = 0;
output = (2 + 2) * 4 + 2 / (4 - 2);
```

1. 15
2. 17
3. 12
4. 11

128. It is the job of _____ to transfer the executable code from hard disk to main memory.

1. interpreter
2. Debugger
3. Linker
4. Loader

129. In computer systems there are mainly _____ type of softwares.

1. 1
2. 2
3. 3
4. 4

130. _____ will explain the function of a program.

1. Comments
2. Debugger
3. Compiler
4. Linker

131. if (a>b && a>c) then the condition will be true only if

1. Both a>b and a>c are true
2. a>b is false and a>c is true
3. a>b is true and a>c is false

Remember Own Prayer

4. Both a>b and a>c are false

132. A variable of character data type occupies _____ byte(s) in memory.

1. 1
2. 2
3. 4
4. 8

133. We must include the header file _____ to convert the value of one type into another type using built-in functions.

1. conio.h
2. stdlib.h
3. string.h
4. iostream.h

134. A function is a block of statements that can be defined once and used _____ in the program.

1. One time
2. Two times
3. Three times
4. As many times as user wants

135. Select the correct way to assign the address of first element of array to pointer?

1. int *ptr = &data[1];
2. int *ptr = &data;
3. int *ptr = data;
4. int *ptr = data[0];

136. Consider the following code segment. What will be the output of following code?

```
int addValue (int *a){
int b = (*a) + 2;
return b;
}
```

Remember Own Prayer

```
main() {
int x = 6;
cout<<addValue(&x)<<",";
cout<<x;
}
```

1. 6,8,6
2. 6,6,8
3. 6,8,8
4. 6,6,6

137. Here the code is given below. You have to identify the problem in the code.

```
while(i< 10) && (i> 24))
```

1. the logical operator && cannot be used in test condition
2. the while loop is an exit-condition loop
3. the test condition is always true
4. the test condition is always false

138. The correct syntax of do-while loop is _____.

1. (condition) while; do {statements;};
2. {statements;} do-while();
3. while(condition); do {statements;};
4. do {statements;} while (condition);

139. Matrix is defined as _____.

1. Single dimensional array
2. Multi-dimensional array
3. Vector product
4. Scalar product

140. In programming, comments are used to explain the functioning of the _____.

1. Debugger
2. Editor
3. Program

Remember Own Prayer

4. Linker

141. Operating System is a type of a/an _____.

1. application software
2. system software
3. computer language
4. interpreter

142. From the options given, you need to choose the option which is true for the given code.

```
for (int i = 1; i>0; i++) {
/*loop code*/
}
```

1. the logical operator && cannot be used in a test condition
2. the while loop is an exit-condition loop
3. the test condition is always false
4. the test condition is always true

143. Which of the following values are used in C/C++ to represent true and false?

1. 1 and 0
2. 1 and -1
3. 11 and 00
4. any numerical value

144. 'While' loop may execute _____ or more times.

1. three
2. zero
3. two
4. one

145. Body of any function is enclosed within _____.

1. { }
2. ( )
3. [ ]

Remember Own Prayer

4. " "

146. What will be the correct syntax for initialization of a pointer ptr with string "programming"?

1. char ptr = 'programming';
2. char *ptr = "programming";
3. char *ptr = 'programming';
4. *ptr = "programming";

147. Which one of the given option is not a mode for reading/writing the data from a file?

1. in
2. out
3. trunc
4. get

148. Which of the following operators is used to access the value of variable pointed by a pointer?

1. * operator
2. -> operator
3. && operator
4. &operator

149. In case of single dereferencing, the value of the _____ is the address of the _____.

1. pointer, variable
2. pointer, constant
3. variable, pointer
4. constant, pointer

150. The remainder (%) operator is a _____ operator.

1. Logical
2. Arithmetic
3. Relational
4. Conditional

Remember Own Prayer

151. What will be the output of following code?

```
int x = 10;
cout<<"x="<<x;
```

1. 10
2. "x=10"
3. x=10
4. 10=x

152. The purpose of using cout<< is to _____.

1. Display information on the screen
2. Read the data from keyboard
3. Read the data from a file
4. Write into a file

153. Which of the following data types will be assumed if no data type is specified with constant?

1. short
2. float
3. int
4. double

154. When an array element is passed to a function, it is passed by _____.

1. reference
2. data type
3. value
4. data

155. While programming, it is good to provide an easy to understand and easy to use interface; this programming skill is called _____.

1. scalability
2. usability
3. reliability
4. sustainability

Remember Own Prayer

156. _____ executes all the lines before error and stops at the line which contains the error.

1. Intrepreter
2. Compiler
3. Linker
4. Debugger

157. Which of the following is the correct syntax to access the value of first element of an array using pointer ptr?

1. ptr[0]
2. *(ptr+1)
3. ptr[1]
4. *ptr[0]

158. C is a/an _____ language.

1. low level
2. object based
3. object oriented
4. function oriented

159. _____ of a function is also known as signature of a function.

1. Definition
2. Declaration
3. Calling
4. Invoking

160. _____ are very good tools for code reuse.

1. operators
2. loops
3. functions
4. variables

161. If any break statement is missed in switch statement then _____.

Remember Own Prayer

1. compiler will give error
2. this may cause a logical error
3. no effect on program
4. program stops its execution

162. A 2D array multi[5][10] can be accessed using the array name as **multi, this technique is called _____.

1. Single referencing
2. Single dereferencing
3. Double referencing
4. Double dereferencing

163. In C/C++, the default command line arguments passed to the main function are _____.

1. float argc, char **argv
2. int argc, char **argv
3. int *argc, char *argv
4. int argc, float **argv

164. A record is a group of related _____.

1. Data
2. Fields
3. Bytes
4. Files

165. The microsoft word document (.doc) is a kind of _____.

1. Sequential File
2. Random AccessFile
3. Binary Access File
4. Executable File

166. NULL character is used to indicate the _____ of string.

1. Start
2. End

Remember Own Prayer

3. Begin
4. Middle

167. How many dimensions does n-dimensional array has?

1. n dimensions
2. 2n dimensions
3. (n+1) dimensions
4. (n-1) dimensions

168. Which of the following function call is "call by reference" for the following function prototype?

1. func(int &num);
2. func(&num);
3. func(*num);
4. func(num);

169. The loop which is most suitable to be used when the number of iterations is known is called _____.

1. for
2. while
3. do-while
4. all looping processes require that the iterations be known.

170. In C/C++, the string constant is enclosed in _____.

1. curly braces { }
2. parentheses( )
3. single quotes ' '
4. double quotes " "

171. In order to get the right most digit of a number, we divide this number by 10 and take _____.

1. Its remainder
2. Its quotient
3. Its divisor
4. The number

Remember Own Prayer

172. What is the correct syntax to declare an array of size 10 of int data type?

1. int [10] name;
2. name[10] int;
3. int name[10];
4. int name[];

173. How many bytes of memory are occupied by array 'str'?

```
char str[] = "programming";
```

1. 10
2. 11
3. 12
4. 13

174. Suppose that an integer type pointer contains a memory address 0x22f230. What will be the new memory address if we increment this pointer by one?

1. 0x22f231
2. 0x22f234
3. 0x22f226
4. 0x22f238

175. Which of the following if missing would result in infinite recursion in case of recursive function?

1. Recursive call
2. Base case
3. Function parameters
4. Local variables

176. Whenever we use a library function or a predefined object or macro, we need to use a _____.

1. source file
2. object file
3. header file
4. exe file

Remember Own Prayer

177. Switch statement deals with _____ type of data.

1. Integer
2. Float
3. Character
4. Both Integer and Character

178. Both compiler and _____ are used to translate program into machine language code.

1. debugger
2. linker
3. loader
4. interpreter

179. TWAIN stands for _____.

1. Technology With An Interesting Name
2. Technology Without An Informative Name
3. Technology Without An Interesting Name
4. Technology With An Informative Name

180. The parameter passed to isdigit() function is _____.

1. a character variable
2. a boolean variable
3. an integer variable
4. a character string

181. C++ views each file as a sequential stream of _____.

1. Bits
2. Bytes
3. Numbers
4. Words

182. Structure is a collection of _____ under a single name.

1. only functions

Remember Own Prayer

2. only variables
3. both functions and variables
4. only data types

183. The default mode for writing into a file using ofstream object is _____.

1. out
2. bin
3. app
4. ate

184. The memory address of the first element of an array is called _____.

1. floor address
2. foundation address
3. first address
4. base address

185. We want to access array in random order which of the following approach is better?

1. Pointer
2. Array index
3. Both pointers and array index are better
4. Matrix

186. The _____ structure is a multiple-selection construct which makes the code more efficient and easy to read and understand.

1. multiple-if
2. switch
3. if-else
4. else-if

187. Which of the following is not a reserved word in C/C++?

1. int
2. float

Remember Own Prayer

3. double
4. sum

188. To access rand(), which library is required to be included in program?

1. conio.h
2. stdio.h
3. stdlib.h
4. iostream.h

189. What is the highest legal index for the following array? int arr[4]

1. 4
2. 3
3. 2
4. 1

190. Word processor is a type of a/an _____.

1. operating system
2. application software
3. device driver
4. utility software

191. Identify the correct option which is used for calling the function float area (int).

1. area(&num);
2. area(num);
3. area(int num);
4. area(*num);

192. The _____ statement allows us to select from multiple choices based on a set of fixed values for a given expression.

1. switch
2. break
3. continue

Remember Own Prayer

4. goto

193. C is widely known as development language of _____ operating system.

1. Windows
2. Unix
3. Mac OS
4. Linux

194. To convert the value of one type into another type using built-in functions, we include _____ header file.

1. conio.h
2. stdlib.h
3. iostream.h
4. string.h

195. The keyword _____ is used to get some value back from a function.

1. return
2. break
3. continue
4. goto

196. The function seekg() takes _____ parameter(s).

1. 0
2. 1
3. 2
4. 3

197. The function write() takes _____ as parameter(s).

1. String of pointer type
2. String of variable lengths, no. of bytes to be read and flags
3. Poimter array of characters and a delimiter
4. String and no. of bytes to be written

Remember Own Prayer



198. When the logical operator AND (&&) combines two expressions exp1 and exp2 then the result will be true only _____.

1. When both exp1 and exp2 are true
2. When both exp1 and exp2 are false
3. When exp1 is true and exp2 is false
4. When exp1 is false and exp2 is true

199. Syntax of a union is identical to _____.

1. structure
2. class
3. function
4. loop

200. Which one of the symbol is used to represent a decision in a flow chart?

1. 
2.  **correct**
3. 
4. 

201. In Flow Chart, flow of control is represented by _____.

1. Rectangle
2. Circle
3. Diamomd
4. Arrow

202. There can be _____ 'default' statement(s) in any switch structure.

Remember Your Own Prayer

1. 1
2. 2
3. 3
4. n

203. The condition in loop should be a(n) _____.

1. Constant Expression
2. Boolean Expression
3. Primary Expression
4. Arithmetic Expression

204. How many nested loops would be required to manipulate n-dimensional array?

1. n
2. n + 1
3. n - 1
4. 2n

205. Which of the following is not an example of int data type?

1. 0
2. -32
3. 65531
4. -4

206. We should use _____ for clarity and to force the order of evaluation in an expression.

1. brackets []
2. parenthesis ()
3. curly braces {}
4. quotation marks " "

207. Which of the following is the starting index of an array in C++?

1. 0
2. 1

Remember Own Prayer

3. -1
4. 2

208. The statement x += y can be interpreted as _____.

1. Adding the value of the x to the value of the y and storing the result in x
2. Adding the value of the y to the value of x, store the result in y
3. Adding the value of the x to the value of x, store the result in x
4. Adding the value of the y to the value of y, store the result in x

209. Given a 2D array of integers, what would be the correct way of assigning the value 5 to the element at second row and third column?

1. m[2][3] = 5;
2. m[3][2] = 5;
3. m[1][2] = 5;
4. m[2][3] = '5';

210. Array is a data structure that stores _____.

1. Memory addresses
2. Variables
3. Data type
4. Data

211. A program statement that invokes a function is called _____.

1. function declaration
2. function call
3. function definition
4. function prototype

212. If a function has been declared but not defined before its function call then it is termed as _____.

Remember Own Prayer

1. logical error
2. syntax error
3. run time error
4. program time error

213. The compiler of C language is written in _____ language.

1. JAVA
2. BASIC
3. FORTRAN
4. C

214. Which one of the below functions is not included in ctype.h header file?

1. isdigit(int c)
2. isxdigit(int c)
3. tolower(int c)
4. getdigit(int c)

215. Which function is used to locate the first occurance of a character in any string?

1. strchr()
2. strstr()
3. strtok()
4. strlen()

216. To access the data members of structure, _____ is used.

1. Logical operator
2. Dereference operator
3. Dot operator
4. Address operator

217. In the following nested For Loop, which loop will run most number of times?

```
for( inti = 0; i< 5; i++)
{
```

Remember Own Prayer

```
for(int k = 0; k < 5; k++)
{
. . . . .
}
}
```

1. Outer loop
2. Inner loop
3. Both loops run equal number of times
4. Depends upon the statements in the inner loop's body

218. Structure use _____ allocation.

1. Queue
2. Heap
3. Cache
4. Stack

219. _____ function give the position of the next character to be read from that file.

1. tellp()
2. tellg()
3. seekg()
4. seekp()

220. What will be the size of the following character array?
char name[] = "Adeel";

1. 5
2. 6
3. 4
4. 7

221. Function prototype is written,

1. Within main function
2. After the return statement in main
3. Before the return statement in main
4. Before call of that function

Remember Own Prayer

222. Which one of the following languages has been used to write the compiler of "C" language?

1. Java
2. Fortran
3. Basic
4. C

223. A hierarchy of classes which are used to deal with console and disk files are called _____.

1. Stream classes
2. Simple classes
3. Binary classes
4. IO classes

224. _____ stops execution at the line that contains error(s) in the code.

1. Compiler
2. Debugger
3. Interpreter
4. Linker

225. C++ is a _____ language.

1. High level
2. Low level
3. Machine
4. Assembly language

226. How many elements are stored in the following?
int matrix [4][5];

1. 9
2. 20
3. 25
4. 10

227. _____ is a substitute of multiple if statement.

Remember Own Prayer

1. if. . .elseif statement
2. Continue statement
3. Break statement
4. Default statement

228. if
int sum = 54;
Then the value of the following statement is
sum = sum - 3;

1. 52
2. 50
3. 51
4. 57

229. What will be the correct syntax for declaration of the following statement?
"ptr is a constant pointer to an integer"

1. const * int myptr;
2. const int *myptr;
3. int const *ptr;
4. int *const ptr;

230. _____ operator is used to pass the address of a variable in call by reference method.

1. %
2. +
3. @
4. &

231. _____ data type can operate on modulus operator.

1. int
2. float
3. char
4. double

232. Whenever some number is added in an array name, it will jump as many _____ as the added number.

Remember Own Prayer

1. rows
2. value
3. column
4. bytes

233. Suppose that an integer type pointer contains a memory address 0x22f220. What will be the new memory address if we increment this pointer by one?

1. 0x22f221
2. 0x22f222
3. 0x22f223
4. 0x22f224

234. _____ is the pointer which determines the position in a file from where the next read operation occurs.

1. put
2. seek
3. get
4. tell

Remember Own Prayer

To access the data members of structure _____ is used.

► **dot operator (.)**

► * operator

► à operator

► None of given.

Question No: 2 (M - 1) .

What does 5 ^ 6 , evaluate to in decimal where '^' is Exclusive OR operator?

► 1

► 2

► **3**

► 4

Question No: 3 (M - 1) .

If constructor contains a return statement in its body then compiler will give _____

► **No error**

► Syntax error

► Logical error

► Run time error

Question No: 4 (M - 1) .

We can use New keyword inside of Class Constructor.

►True

►**False**

Question No: 5 (M - 1) .

When an operator function is define as member function for a Unary operator then the number of argument it take is/are,

►Zero

►**One**

►Two

►N arguments

The declarator of Plus (+) member operator function is

►**Class-Name operator + (Class-Name rhs)**
►operator Class-Name + ( )
►operator Class-Name + (rhs)
►Class-Name operator + ( )

Question No: 7 (M - 1) .

Friend function of a class is _____ .
►Member function
►**Non-member function**
►Private function
►Public function

Question No: 8 (M - 1) .

We can also create an array of user define data type.

►**True**

►False

Question No: 9 (M - 1) .

What is the sequence of event(s) when deallocating memory using delete operator?

►Only block of memory is deallocated for objects

►Only destructor is called for objects
►**Memory is deallocated first before calling destructor**
►Destructor is called first before deallocating memory

Question No: 10 (M - 1) .

Deleting an array of objects without specifying [] brackets may lead to memory leak

►**True**

►False

Question No: 11 (M - 1) .

Which of the following data type(s) can operate on modulus operator '%'?

► float, int

► float, double

► **int**

► char

Question No: 12 (M - 1) .

Array is passed by value to a function by default.

►True

►**False**

Question No: 13 (M - 1) .

With template function, the compiler automatically detects the passed data and generates a new copy of function using passed data.

►**True**
►False

Question No: 14 (M - 1) .

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

►**int arr[2][3] = {0,0} ;**
►int arr[2][3] = {{0},{0}} ;
►int arr[2][3] = {0},{0} ;
►int arr[2][3] = {0} ;

Question No: 15 (M - 1) .

When an operator function is define as member function then operand on the left side of operator must be an object.

►**True**

►False

Question No: 16 (M - 1) .

break statement can be used outside a loop or switch statement.

►**True**

►False

Question No: 17 (M - 1) .

The keyword_____ is used to return some value from a function.

►**return**

►break

►continue

►goto

Question No: 18 (M - 1) .

Every data member or function inside the structure is ___ by default whereas everything declared inside a class is ____ by default.

►private, public

►public, private

►private, protected

►public, protected

Question No: 19 (M - 1) .

Which of the following is true for the C++ statement given below?

int &ref = val ;

►It creates a synonym for variable 'val'

►It creates an alias for variable 'val'

►It's a new name for variable 'val'

►All of the given options

Question No: 20 (M - 1) .

If overloaded plus operator is implemented as non-member function then which of the following statement will be true for the statement given below?

obj3 = obj1 + obj2 ;

►obj2 will be passed as an argument to + operator whereas obj2 will drive the + operator

►obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator

►Both objects (obj1, obj2) will be passed as arguments to the + operator

►Any of the objects (obj1, obj2) can drive the + operator

Question No: 21 (M - 1) .

Unary operator implemented as member function takes ____ arguments whereas non-member function takes _____ arguments.

►One, zero

►Zero, one

►One, two

►Two, one

Question No: 22 (M - 1) .

The input/output streams cin and cout are _____ therefore have _____.

► Structures, function

► Objects, member functions

► Functions, objects

► **None of the given options**

Question No: 23 (M - 1) .

If a symbolic constant has been defined, it will be an error to define it again.

► **True**

► False

Question No: 24 (M - 1) .

Every class contains _____.

► **Constructor**

► Destructor

► Both a constructor and a destructor

► None of the given options

Question No: 25 (M - 1) .

new and delete keywords are _____ in C++ language.

► Built-in- Function

► Operators

► **Memory Allocation Function**

► None of the given options

Question No: 26 (M - 1) .

Consider the following code segment.

```
class M {

public:

  M &operator+(const M &);

...

};
```

p + q //code of line implies that p.operator+(q)

...

Let assume if p and q are class objects then function is implemented as _____

►**Member function**

►Non-member function

►Friend function

►None of the given options

Question No: 27 (M - 1) .

Assignment operator is ----------associative.

►**right**

►left

►binary

►unary

Assignment operators in imperative programming languages are usually defined to be right-associative.

(Refrenced by: **asad ali (asad_call2002@yahoo.com)**

Question No: 28 (M - 1) .

Static variable which is defined in a function is initialized _____.

► **Only once during its life time**

► Every time the function call

► Compile time of the program

► None of the above

www.vuzs.info

Question No: 29 (M - 1) .

Wecan not define a variable of user-defined data type in the class.

►True

►**False**

Question No: 30 (M - 1) .

A constructor that will create a new object with a full copy of the other object, is copy is known as _____

►**deep copy**

►shallow copy

►constructor copy

►none of the options

Remember Own Prayer

http://vustudents.ning.com

Quiz Start Time: 09:34 PM Time Left 82 sec(s)

Question # 1 of 10 (Start time: 09:34:54 PM) Total Marks: 1
While developing a program; should we think about the user interface? //handouts main reusability hay..us ki yahan option hi nahi hay
Select correct option:

Yes

No

Quiz Start Time: 09:34 PM Time Left 75 sec(s)

Question # 2 of 10 (Start time: 09:35:20 PM) Total Marks: 1
A character is stored in the memory in _____
Select correct option:

byte

integer

string

None of the given

Quiz Start Time: 09:34 PM

Question # 3 of 10 (Start time: 09:36:21 PM) Total Marks: 1
These functions seekg() and seekp() requires an argument of type _____to let them how many bytes to move forward or backward.
Select correct option:

int

short

long

double

Quiz Start Time: 09:34 PM Time Left 85 sec(s)

Question # 4 of 10 (Start time: 09:37:30 PM) Total Marks: 1
dereferencing operator is represented by _____
Select correct option:

*

+

–

None of the given

Quiz Start Time: 09:34 PM Time Left 86 sec(s)

Question # 5 of 10 (Start time: 09:38:55 PM) Total Marks: 1
_____ transfers the executable code from main memory to hard disk.

Select correct option:

Loader

Debugger

Compiler

Linker

Quiz Start Time: 09:34 PM Time Left 85 sec(s)

Question # 6 of 10 (Start time: 09:40:21 PM) Total Marks: 1
When the logical operator OR (||) combine two expressions exp1 and exp2 then the result will be false only, //bitwise “or” applies here….
Select correct option:

When both exp1 and exp2 are true

When both exp1 and exp2 are false

When exp1 is true and exp2 is false

When exp1 is false and exp2 is true

Quiz Start Time: 09:34 PM Time Left 79 sec(s)

Question # 7 of 10 (Start time: 09:41:43 PM) Total Marks: 1
suppose we have int y[10]; To access the 4th element of the array we write_____
Select correct option:

y[4];

y[3];

y[2];

none of given

Quiz Start Time: 09:34 PM Time Left 82 sec(s)

Question # 8 of 10 (Start time: 09:43:10 PM) Total Marks: 1
we have opened a file stream myfile for reading (getting), myfile.tellg () gives us the current get position of the file pointer. It returns a whole number of type_____
Select correct option:

long

int

short

double

Quiz Start Time: 09:34 PM Time Left 80 sec(s)

Question # 9 of 10 (Start time: 09:44:42 PM) Total Marks: 1
ofstream is used for_____
Select correct option:

Input file stream

Output file stream

Input and output file stream

All of the given

Quiz Start Time: 09:34 PM Time Left 80 sec(s)
http://vustudents.ning.com

Question # 10 of 10 (Start time: 09:46:11 PM) Total Marks: 1
A structure is a collection of _____under a single name.
Select correct option:

values

variables

data

None of the given

Question No: 1 (Marks: 1) - Please choose one

In C/C++ the string constant is enclosed ……. **corrected r red one**

► In curly braces
► In small braces
► In single quotes
► **In double quotes**

Question No: 2 (Marks: 1) - Please choose one

The size of int data type is

► 1 bytes
► 2 bytes
► 3 bytes
► 4 bytes

Question No: 3 (Marks: 1) - Please choose one

In Flow chart process is represented by

► Rectangle
► Arrow symbol
► Oval
► Circle

Question No: 4 (Marks: 1) - Please choose one

If the break statement is missed in switch statement then,**// a break statement with no label always completes abruptly, the reason being a break with no label. If no switch, while, do, or for statement in the immediately enclosing method, constructor or initializer encloses the break statement, a compile-time error occurs.**

► **The compiler will give error**
► This may cause a logical error
► No effect on program
► Program stops its execution

Question No: 5 (Marks: 1) - Please choose one

When we are using const keyword with a variable x then initializing it at the time of declaration is,

► **Must**
► Optional
► Not necessary
► A syntax error

Question No: 6 (Marks: 1) - Please choose one

Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third column?

► m[2][3] = 5 ;

► m[3][2] = 5 ;

► m[1][2] = 5 ;
► m[2][3] = '5';

Question No: 7 (Marks: 1) - Please choose one

How many total elements must be in two-dimensional array of 3 rows and 2 columns?

► 4
► 5
► 6
► 7

Question No: 8 (Marks: 1) - Please choose one

Which of the following is the correct statement for the following declaration?
const int *ptr.

► ptr is a constant pointer

► ptr is constant integer pointer

► ptr is a constant pointer to int

► ptr is a pointer to const int

Question No: 9 (Marks: 1) - Please choose one

Consider the following code segment. What will be the output of this code segment?As arrays starts from 0 index……at 1st position is 3……n at position 4th is 5……5-3=2

```
int arr[6] = {2, 3, 7, 4, 5, 6} ;
int *ptr1 =&arr[1] ;
int *ptr2 = &arr[4] ;
cout << (ptr2-ptr1) ;
```

► 3

► 9
► 12
► **2**

Question No: 10 (Marks: 1) - Please choose one

What will be the correct syntax to assign an array named *arr* of 5 elements to a pointer *ptr*?

► *ptr = arr ;

► ptr = arr ;

► ***ptr = arr[5] ;**

► ptr = arr[5] ;

Question No: 11 (Marks: 1) - Please choose one

C is a/an _____ language

► low level
► object based
► **object oriented**
► function oriented

Question No: 13 (Marks: 1) - Please choose one

The variables having a name, type and size are just like empty boxes.

► False
► True

Question No: 14 (Marks: 1) - Please choose one

What's wrong with this for loop?
for (int k = 2, k <=12, k++)

► the increment should always be ++k
► the variable must always be the letter i when using a for loop
► there should be a semicolon at the end of the statement
► the commas should be semicolons

Question No: 15 (Marks: 1) - Please choose one

Most efficient method of dealing with structure variables is to define the structure globally

► True
► False

Question No: 16 (Marks: 1) - Please choose one

Syntax of union is identical to _____

- ►Structure
- ►Class
- ►Function
- ►None of the given options

FINALTERM EXAMINATION
Fall 2008
CS201- Introduction to Programming

Time: 120 min
Marks: 75

Question No: 1 (Marks: 1) - Please choose one

There are mainly ---------- types of software.//

- ► Two
- ► Three
- ► Four
- ► Five

Question No: 2 (Marks: 1) - Please choose one

seekg() and write() are functionally _____ .//

Write() Writes a specified number of bytes from a memory location to the file.
seekg() Moves the file position indicator to a specific location in the file.
The Position property of TFileStream simplifies seeking in a file and performs the same function as the ifstream methods tellg() and seekg(). You can read Position to determine the current file position, or you can write to Position to move the file position.

- ► Different
- ► Identical
- ► **Two names of same function**
- ► None of the above

Question No: 3 (Marks: 1) - Please choose one

When a pointer is incremented, it actually jumps the number of memory addresses

- ► According to data type
- ► 1 byte exactly
- ► 1 bit exactly
- ► A pointer variable can not be incremented

Question No: 4 (Marks: 1) - Please choose one

setw is a parameterized manipulator.

► True
► False

Question No: 5 (Marks: 1) - Please choose one

eof( ), bad( ), good( ), clear( ) all are manipulators.

► True
► False

Question No: 6 (Marks: 1) - Please choose one

In functions that return reference, use _____variables.

► Local
► Global
► Global or static
► None of the given option

Question No: 7 (Marks: 1) - Please choose one

The declarator of Plus (+) member operator function is
//not confirmed

► Class-Name operator + (Class-Name rhs)
► operator Class-Name + ( )
► operator Class-Name + (rhs)
► Class-Name operator + ( )

Question No: 8 (Marks: 1) - Please choose one

The compiler does not provide a copy constructor if we do not provide it…….

//Normally it provides but in some cases of classes it is good practice to provide user define copy constructor…

► True
► False

Question No: 9 (Marks: 1) - Please choose one

What is the functionality of the following syntax to delete an array of 5 objects named ***arr*** allocated using new operator?
delete arr ;

- ► Deletes all the objects of array
- ► Deletes one object of array
- ► Do not delete any object
- ► Results into syntax error

Question No: 10 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

- ► Only block of memory is allocated for objects
- ► Only constructor is called for objects
- ► Memory is allocated first before calling constructor
- ► Constructor is called first before allocating memory

Question No: 11 (Marks: 1) - Please choose one
What is the sequence of event(s) when deallocating memory using delete operator?

- ► Only block of memory is deallocated for objects
- ► Only destructor is called for objects
- ► Memory is deallocated first before calling destructor
- ► Destructor is called first before deallocating memory

Question No: 12 (Marks: 1) - Please choose one

new and **delete** operators cannot be overloaded as member functions.

- ► True
- ► **False**

Question No: 13 (Marks: 1) - Please choose one

The operator function of << and >> operators are always the member function of a class.

- ► True
- ► False

Question No: 14 (Marks: 1) - Please choose one

A template function must have at least ---------- generic data type

- ► Zero
- ► One
- ► Two
- ► Three

Question No: 15 (Marks: 1) - Please choose one

If we do not mention any *return_value_type* with a function, it will return an _____ value.

- ► int
- ► void
- ► double
- ► float

Question No: 16 (Marks: 1) - Please choose one

Suppose a program contains an array declared as **int arr[100];** what will be the size of array?

- ► 0
- ► 99
- ► 100
- ► 101

Question No: 17 (Marks: 1) - Please choose one

The name of an array represents address of first location of array element.

- ► True
- ► False

Question No: 18 (Marks: 1) - Please choose one

Reusing the variables in program helps to save the memory

- ► True
- ► False

Question No: 19 (Marks: 1) - Please choose one

Which of the following option is true about new operator to dynamically allocate memory to an object?

// **new** is an operator that allows dynamic memory allocation on the heap. Except for a form called the "placement new", new attempts to allocate enough memory on the heap for the new data and, if successful, returns the address to the newly allocated memory. However if new can not allocate memory on the heap it will throw an exception of type std::bad_alloc. This removes the need to explicitly check the result of an allocation.

- The new operator determines the size of an object
- Allocates memory to object and returns pointer of valid type
- Creates an object and calls the constructor to initialize the object
- **All of the given options**

Question No: 20 (Marks: 1) - Please choose one
new and delete are _____ whereas malloc and free are _____.

- Functions, operators
- Classes, operators
- Operators, functions
- Operators, classes

Question No: 21 (Marks: 1) - Please choose one

Like member functions, _____ can also access the private data members of a class.

- Non-member functions
- Friend functions
- Any function outside class
- None of the given options

Question No: 22 (Marks: 1) - Please choose one

Which of the following statement is best regarding declaration of friend function?

- Friend function must be declared after public keyword.
- Friend function must be declared after private keyword.
- Friend function must be declared at the top within class definition.
- It can be declared anywhere in class as these are not affected by the public and private keywords.

Question No: 23 (Marks: 1) - Please choose one
The operator function overloaded for an Assignment operator (=) must be

- Non-member function of class
- **Member function of class**
- Friend function of class
- None of the given options

Question No: 24 (Marks: 1) - Please choose one
For non-member operator function, object on left side of the operator may be

- Object of operator class
- Object of different class
- Built-in data type
- All of the given options

Question No: 25 (Marks: 1) - Please choose one
The operator function will be implemented as _____, if obj1 drive the - operator whereas obj2 is passed as arguments to - operator in the statement given below.
obj3 = obj1 - obj2;

- ► Member function
- ► Non-member function
- ► **Friend function**
- ► None of the given options

Question No: 26 (Marks: 1) - Please choose one
Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

- ► Class-name operator +() ;
- ► Class-name operator +(int) ;
- ► Class-name operator ++() ;
- ► Class-name operator ++(int) ;

Question No: 27 (Marks: 1) - Please choose one

The static data members of a class are initialized _____

- ► at file scope
- ► **within class definition**
- ► within member function
- ► within main function

Question No: 28 (Marks: 1) - Please choose one

Class is a user defined_____.

- ► data type
- ► memory referee
- ► value
- ► none of the given options.

Question No: 29 (Marks: 1) - Please choose one
We can also define a user-defines manipulators.

- ► **True**
- ► False

Question No: 30 (Marks: 1) - Please choose one

Automatic variable are created on _____.

- ► Heap
- ► Free store
- ► static storage
- ► stack

Current

Question No: 1 (Marks: 1) - Please choose one

Compiler is a

- ► System software
- ► Application Software
- ► Driver
- ► Editor

Question No: 2 (Marks: 1) - Please choose one

Operating System is

- ► An application software
- ► System Software
- ► Computer Language
- ► Interpreter

Question No: 3 (Marks: 1) - Please choose one

Which one is the correct syntax for defining an identifier **PI** with preprocessor directive?

- ► #define PI 3.1415926;
- ► #define PI 3.1415926
- ► #define PI = 3.1415926 ;
- ► #define PI = 3.1415926

Question No: 4 (Marks: 1) - Please choose one

Character strings are arrays of characters that can store

- ► Only one character
- ► Limited number of characters
- ► **Number of characters specified.**
- ► None of the given option

Question No: 5 (Marks: 1) - Please choose one
Which of the following is NOT a preprocessor directive?

- ► #error
- ► #define
- ► #line
- ► **#ndefine**

Question No: 6 (Marks: 1) - Please choose one

Which kind of functions can access private member variables of a class?

- ► Friend functions of the class
- ► Private member functions of the class
- ► Public member functions of the class
- ► Friend, private and public functions

Question No: 7 (Marks: 1) - Please choose one
Let suppose int a, b, c, d, e;, a = b = c = d = e = 42;
This can be interpreted by the complier as:// **assignment is right-associative.**

- ► **a = (b = (c = (d = (e = 42))));**
- ► (a = b = (c = (d = (e = 42))));
- ► a = b = (c = (d = (e = 42)));
- ► (a = b) = (c = d) = (e = 42);

Question No: 8 (Marks: 1) - Please choose one

Friend function of a class is _____ . http://vustudents.ning.com

- ► **Member function**
- ► Non-member function
- ► Private function
- ► Public function

Question No: 9 (Marks: 1) - Please choose one

Function implementation of friend function must be defined outside the class.

- ► **True**
- ► False

Question No: 10 (Marks: 1) - Please choose one
When we define an array of objects then,

- ► Constructor will be called once for whole array
- ► **Constructor will be called for each object of the array**
- ► Constructor will never call
- ► Depends on the size of array

Question No: 11 (Marks: 1) - Please choose one

The stream objects **cin** and **cout** are included in which header file?

- ► **iostream.h**
- ► fstream.h
- ► istream.h
- ► ostream.h

Question No: 12 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

- ► Only block of memory is allocated for objects
- ► Only constructor is called for objects
- ► **Memory is allocated first before calling constructor**
- ► Constructor is called first before allocating memory

Question No: 13 (Marks: 1) - Please choose one
Missing semicolon ';' at the end of C++ statement is

- ► Logical error
- ► **Syntax error**
- ► Runtime error
- ► None of the given options

Question No: 14 (Marks: 1) - Please choose one

An array stores the numbers into consecutive memory locations.

- ► **True**
- ► False

Question No: 15 (Marks: 1) - Please choose one

The template functions do NOT promote the code reuse

- ► True
- ► **False**

Question No: 16 (Marks: 1) - Please choose one

What will be the correct syntax for initialization of pointer ***ptr*** of type int with variable ***x***?

- ► int ptr = &x ;
- ► int ptr = x ;
- ► **int *ptr = &x ;**
- ► int ptr* = &x ;

Question No: 17 (Marks: 1) - Please choose one

Which of the following function calling mechanism is true for the function prototype given below?
float func(float &);

- ► **Call by value**
- ► Call by reference using pointer
- ► Call by reference using reference variable
- ► None of the given options

Question No: 18 (Marks: 1) - Please choose one

If overloaded plus operator is implemented as non-member function then which of the following statement will be true for the statement given below?
obj3 = obj1 + obj2 ;

- ► **obj2 will be passed as an argument to + operator whereas obj2 will drive the + operator**
- ► obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator
- ► Both objects (obj1, obj2) will be passed as arguments to the + operator
- ► Any of the objects (obj1, obj2) can drive the + operator

Question No: 19 (Marks: 1) - Please choose one

Which of the following object(s) will call the member operator function within the statement given below?

obj1=obj2+obj3;

- Object obj1
- Object obj2
- **Object obj3**
- Any of the object

Question No: 20 (Marks: 1) - Please choose one

For cin, the source is normally a _____ and destination can be _____.

- File, native data type
- Disk, user-define type
- **Keyboard, variable**
- File, user-define type

Question No: 21 (Marks: 1) - Please choose one

The static data members of a class will be _____

- shared by objects
- created for each object
- initialized within class
- **initialized within main function**

Question No: 22 (Marks: 1) - Please choose one

Which of the following function cannot be overloaded?

- Member functions
- Utility functions
- Constructor
- **Destructor**

Question No: 23 (Marks: 1) - Please choose one

The region of memory, available for allocation at run time in C language is called _____ memory whereas in C++ language is called as _____.

- Heap, Stack
- Stack, Free Store
- Heap, Free Store
- **None of above**

Question No: 24 (Marks: 1) - Please choose one

A variable which is defined inside a function is called

- **Automatic variable**
- Global variable
- Functional variable
- None of the given option

Question No: 25 (Marks: 1) - Please choose one

The default copy constructor provides member wise assignment.

- **True**
- False

Question No: 26 (Marks: 1) - Please choose one

The code is written to _____ the program.

- **implement**
- design
- analysis
- none of the given options.

Question No: 27 (Marks: 1) - Please choose one

When a call to a user-defined function finishes, the variable defined inside the function is still in existence.

- True
- **False**

Question No: 28 (Marks: 1) - Please choose one

To avoid dangling reference, always return the reference of a local variable from a function.

- **True**
- False

Question No: 29 (Marks: 1) - Please choose one

Analysis is the ---------- step in designing a program.

- Last
- Middle
- Post Design

► **First**

Question No: 30 (Marks: 1) - Please choose one

"delete" operator is used to return memory to free store, which is allocated by the **"new"** operator.

► **True**
► False

Question No: 1 (Marks: 1) - Please choose one

In C/C++ if we define an array of size eight (8) i.e. int Arr [8]; then the last element of this array will be stored at,

► Arr[0]
► Arr[8]
► Arr[7]
► Arr[-1]

Question No: 2 (Marks: 1) - Please choose one

When an array is passed to a function then default way of passing this array is,

► By data
► By reference
► By value
► By data type

Question No: 3 (Marks: 1) - Please choose one

Array is a data structure which store

► **Memory addresses**
► Variables
► Data Type
► Data

Question No: 4 (Marks: 1) - Please choose one

We can also create an array of user define data type.

► True
► False

Question No: 5 (Marks: 1) - Please choose one

When we define an array of objects then,

- ► Destructor will call once for whole array
- ► Destructor will call for each object of the array
- ► Destructor will never call
- ► Depends on the size of array

Question No: 6 (Marks: 1) - Please choose one

What is the sequence of event(s) when allocating memory using new operator?

- ► Only block of memory is allocated for objects
- ► Only constructor is called for objects
- ► Memory is allocated first before calling constructor
- ► Constructor is called first before allocating memory

Question No: 7 (Marks: 1) - Please choose one

We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally.

- ► True
- ► False

Question No: 8 (Marks: 1) - Please choose one

The second parameter of operator functions for << and >> are objects of the class for which we are overloading these operators.

- ► **True**
- ► False

Question No: 9 (Marks: 1) - Please choose one

Which of the following is correct way to initialize a variable x of int type with value 10?

- ► int x ; x = 10 ;
- ► **int x = 10 ;**
- ► int x, x = 10;
- ► x = 10 ;

Question No: 10 (Marks: 1) - Please choose one

Default mechanism of function calling in case of array is _____ and in case of variable is ___. http://vustudents.ning.com

- Call by value, call by reference
- Call by referene, call by reference
- **Call by reference, call by value**
- Call by value, call by value

Question No: 11 (Marks: 1) - Please choose one

What does STL stand for?

- Source template library
- **Standard template library**
- Stream template library
- Standard temporary library

Question No: 12 (Marks: 1) - Please choose one

Skill(s) that is/are needed by programmers _____.

- Paying attention to detail
- Think about the reusability
- Think about user interface
- **All of the given options**

Question No: 13 (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

- int
- double
- float
- **char**

Question No: 14 (Marks: 1) - Please choose one

new and delete are _____ whereas malloc and free are _____.

- ► Functions, operators
- ► Classes, operators
- ► **Operators, functions**
- ► Operators, classes

Question No: 15 (Marks: 1) - Please choose one

Friend functions are _____ of a class.

- ► Member functions
- ► Public member functions
- ► Private member functions
- ► **Non-member functions**

Question No: 16 (Marks: 1) - Please choose one

The prototype of friend functions must be written ____ the class and its definition must be written ____

- ► inside, inside the class
- ► inside, outside the class
- ► **outside, inside the class**
- ► outside, outside the class

Question No: 17 (Marks: 1) - Please choose one

If overloaded plus operator is implemented as non-member function then which of the following statement will be true for the statement given below?
obj3 = obj1 + obj2 ;

► **obj2 will be passed as an argument to + operator whereas obj2 will drive the + operator**

► obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator

► Both objects (obj1, obj2) will be passed as arguments to the + operator

► Any of the objects (obj1, obj2) can drive the + operator

Question No: 18 (Marks: 1) - Please choose one

Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

- Class-name operator +() ;
- Class-name operator +(int) ;
- Class-name operator ++() ;
- **Class-name operator ++(int) ;**

Question No: 19 (Marks: 1) - Please choose one

For cin, the source is normally a _____ and destination can be _____.

- File, native data type
- Disk, user-define type
- **Keyboard, variable**
- File, user-define type

Question No: 20 (Marks: 1) - Please choose one

We can also do conditional compilation with preprocessor directives.

- **True**
- False

Question No: 21 (Marks: 1) - Please choose one

The programs, in which we allocate static memory, run essentially on _____

- Heap
- System Cache
- None of the given options
- **Stack**

Question No: 22 (Marks: 1) - Please choose one

The default value of a parameter can be provided inside the _____

- function prototype
- **function definition**
- both function prototype or function definition
- none of the given options.

Question No: 23 (Marks: 1) - Please choose one

While calling function, the arguments are assigned to the parameters from _____.

- ► left to right.
- ► right to left
- ► **no specific order is followed**
- ► none of the given options.

Question No: 24 (Marks: 1) - Please choose one

When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

- ► Zero
- ► One
- ► Two
- ► **N arguments**

Question No: 25 (Marks: 1) - Please choose one

With user-defined data type variables (Objects), self assignment can produce _____.

- ► Syntax error
- ► **Logical error**
- ► Link error
- ► Non of the given options

Question No: 26 (Marks: 1) - Please choose one

Assignment operator is used to initialize a newly declared object from existing object.

- ► **True**
- ► False

Question No: 27 (Marks: 1) - Please choose one

When an object of a class is defined inside an other class then,

- ► Constructor of enclosing class will be called first
- ► **Constructor of inner object will be called first**
- ► Constructor and Destructor will be called simultaneously
- ► None of the given options

Question No: 28 (Marks: 1) - Please choose one

In the member initializer list, the data members are initialized,

- From left to right
- From right to left
- **In the order in which they are defined within class**
- None of the given options

Question No: 29 (Marks: 1) - Please choose one

new operator allocates memory from free store and return _____.

- **A pointer**
- A reference
- An integer
- A float

Question No: 30 (Marks: 1) - Please choose one

"new" and "delete" keywords are _____ in C++ language.

- Built-in- Function
- Operators
- **Memory Allocation Function**
- None of the given options

Cs201 quiz today made by Abdullah

1.which software testing refers to tests that do not rely on knowledge of software's interior composition

(white-box testing)

2.The language understood by a computer without translation is known as:

(Machine language)

3.which one is a unary operator?

(NOT)

4.In the case of highly standardized language, compiler designers often provide feature ,sometimes called

(Language extension)

5.Under_____paradigm a program is viewed as an entity that accept inputs and produces outputs

(functional)

6.in c++,symbolic representation of "Assignment" operator is _____

(=)

7. A translator which takes assembly language program as input & produce machine language code as output is know as:

(Assembler)

8.Which of the following statement is used in c++.

(cout<<)

9.We used_____ to reduce unnecessary dependencies or effects on other module

(information hiding)

10.The memory allocation functions return a chunk of memory with a pointer of type_____

(void)

Abdullah

11.default constructor takes_____

(no parameters)

12. In a class we have_____constructor(s).

(many)

13.which one of the following in mandatory preprocessor directive for c++?

(#include <iostream>)

14.Header files provide_____so the program running on the operating system can run without an error on the other system

(accessibility)

15.With the use of dynamic allocation of memory,the system resources can be_____

(Used efficiently)

16._____for parameters is also done for inline functions.

(automatic type checking)

17.We should not use such variable names that are starting with_____because in c++. There are lots of internal constants and symbolic names that start with it

(double underscore)

18.Which of the following code segment represents a left a left shift operator?

(Cout<<1)

19. c++ was developed by _____

(bejama stoustrup)

20. special name which is substituted in code by its definition and as a result we get an expanded code is called

(macro)

21. a= a+1; can be written as____

(a + = 1;)

22. The compilar generates_____automatically

(constuctors)

23.The data numbers of the class are initialized_____

(At runtime)

24._____for parameters is also done for infine functions

(automatic type checking)

25.AN instance of a class is called_____

(object)

26. with the use of dynamic allocation of memory. The system resources can be _____

(used efficiently)

27.When we include header file in the angle brackets the compiler search for it in_____

(specific directory)

28._____ is a special type of pointer we have to castit before we use it.

(void)

29.Multiplicative, additive and assignment operators are _____ operators.

(binary)

30.a =a+1; can be written as_____

(a + = 1;)

31.The compiler generates_____automatically

(constructors)

32.The data members of the class are initialized_____

(at runtime)

33._____for parameters is also done for inline functions

(automatic type checking)

34.AN instance of class of a class is called_____

(object)

35.with the use of dynamic allocation of memory , the system resources can be_____

(used efficiently)

36.for converting a void type pointer ptr, the correct syntax is:

(Int* ptr)

37.header files provide____so the program running on one operating system can run without an error on the other system

(reliability)

38.a pointer with value null is defined in the header files____and____

(stdlib.h,stdef.h)

39.molic function returns____to the ____from the available memory

(void pointer,starting of chunk of memory…from the array)

40.constructor is a special function, called whenever we_____

(Instantiate an object of a class)

41.we should not use such variable names that are starting with_____because in c++there are lots of internal constant….with it

(double underscope)

42.CONStructor is itself a_____of c++ and_____

(function can be overloaded)

43what is the other name of variable

(Identifier)

44.what will be the output of the following c++ code?

#include<iostream.h>

#define max 100

Main()

{#ifdef max

Cout<"hello world"

(error)

45. In shifting operations if zero is inserted at the left most bit,the negative number will become a___number

(positive)

46.The compilar generates ____automatically

(constructors

47.A class is____

(a member function)

48.bugs can occur due to_____

(uninitialized data)

49.the heap memory structure_____

(constantly change in size

50 how many bits form a byte

(8)

51.the function calloc takes two arguments. First argument is the_____ and the second argument is the_____

(require space in terms of number ,size of space)

52the main advantage of function overloading is that___

(the program become more redable)

53.A pointer with value null is defined in the header files_____and_____

(stdlib.h…..)

54.the_____is the increment operator in c++

(++)

55.what will be the output of the given code)

X=32; y=45;

(x=24 y=46)

56.the constructor constains_____

(no returntype)

57.multiplicative,additive and assignment operators are_____ operators

(Binary)

58 for accessing data members we use____operator

(dot)

59.in a class we can have_____constructor

(Only one)

60.object code is machine code but it is not____and _____

(relocatable ,executable)

61.shifting the binary number Is similar to shifting the __number

(decimal)

62.The____is called automatically when an object destroys

(destructor)

63.an integer uses four bytes and the integer calculation occur in___bytes

(2byte)

64.which of the following code segment represents a left shift operator?

(cout<<1)

65. Raid stand for__

(redundant array of inexperience device)

66. windows operating system may itself takes memory from____

(list)

67what is the storage space of double data type

(8)

68. dynamic memory allocation uses____Whereas static memory allocation uses_____

(Heap , stack)

69.which one is the correct example of a unary operator

(-)

70.which is the output of following code

(b correct answr)

71. array indexes start from_____

0

72.which one of the following is used to perform bit-wise exclusive or operation

(^)

73.getche() is a_____function and defined in_____header file

(build-in function,iostream.h)

74.In c++, a variable can be declared anywhere in the program, this will increase_____

(Portability)

75the compilar use a name mangling technique to_____

Compile the function

76.macros are categorized into type(s)

Two

77constructor is a special function called whenever we____

Instantiate an object of a clas

Abdullah

Cs201 today quiz

1.Once the _____are created, they exist for the life time of the program

(static variable)

2.A class can be declared as a_____of other class.

(friend)

3.Reference variabales must_____

(be initialized after they are declared)

4.we can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally

(False)

5.operator overloading is to allow the same operator to be bound to more than one implementation, depending on the types of the

(operands)

6.the friend keyword provides access_____

(in one direction only)

7.the friend functions are_____

(not member of a class)

8.temary operator is shown as_____

(?:)

9.Reference is not really an address it is_____

(a synonym)

10.Reference is a thing by which we can create_____of any data type

(synonym)

11.In c++ operators. Which of the following operator cannot

ove de s

e functi

o

Abdullah cheater

19.to prevent dangling reference the functions returning reference should be used with_____

(static and global variables)

20.the only operator that the compiler overloads for user define data type by default is

(assignment(=) operator

21.if operator function is non-member function that object on left side of operator cannot be_____?

(object of operator class)

22.which of the following functionality can be achieved through overloading?

(new operators cannot be defined through operator overloading)

23.oveloaded member operator function is always called by_____

(class)

24 Overloaded member operator function is always called by _____

► **Class**
► Object

► Compiler
►Primitive data type

25 Loader loads the executable code from hard disk to main memory.

► **True**
► False

26 Which of the following is the correct C++ syntax to allocate space dynamically for an array of 10 int?

► new int(10) ;
► **new int[10] ;**
► int new(10) ;
► int new[10];

27. The prototype of friend functions must be written ____ the class and its definition must be written ____

► inside, inside the class

► **inside, outside the class**
► outside, inside the class
► outside, outside the class

28. Like member functions, _____ can also access the private data members of a class.

► Non-member functions

► Friend functions
► Any function outside class
► None of the given options

29. To perform manipulation with input/output, we have to include _____ header file.

► **iostream.h**
► stdlib.h
► iomanip.h
► fstream.h

30. The **endl** and **flush** are _____

► Functions
► Operators
► **Manipulators**
► Objects

31 If we want to use stream insertion and extraction operators with _____ then we have to overload these operators.

► int, float, double

► objects of class
► int, float, object
► **int, char, float**

32. The static data members of a class can be accessed by _____

► only class
► only objects
► **both class and objects**
► none of given options

33. Classes defined inside other classes are called _____ classes

► looped

► **nested**
► overloaded
► none of the given options.

34. Which value is returned by the destructor of a class?

► A pointer to the class.
► An object of the class.
► A status code determining whether the class was destructed correctly

► **Destructors do not return a value.**

35. Consider the following code segment

```
class M {

   friend int operator!(const M &);

...

};
```

```
!s                    // code of line implies that     operator!(s)
...
```

Let assume if s is an object of the class then function is implemented as _____

- ► **Member function**
- ► Non-member function
- ► Binary operator function
- ► None of the given options

36. If **text** is a pointer of class **String** then what is meant by the following statement?

```
text = new String [5];
```

- ► **Creates an array of 5 string objects statically**
- ► Creates an array of 5 string objects dynamically
- ► Creates an array of pointers to string
- ► Creates a string Object

37. Static variable which is defined in a function is initialized _____.

- ► **Only once during its life time**
- ► Every time the function call
- ► Compile time of the program
- ► None of the above

38. In functions that return reference, use _____variables.

- ► Local
- ► Global
- ► **Global or static**
- ► None of the given option

39. What is the functionality of the following syntax to delete an array of 5 objects named ***arr*** allocated using new operator?

```
delete arr ;
```

- ► Deletes all the objects of array
- ► Deletes one object of array
- ► Do not delete any object
- ► **Results into syntax error**

40. What is the sequence of event(s) when allocating memory using new operator?

- ► Only block of memory is allocated for objects
- ► Only constructor is called for objects
- ► Memory is allocated first before calling constructor
- ► **Constructor is called first before allocating memory**

41. What is the sequence of event(s) when deallocating memory using delete operator?

- ► Only block of memory is deallocated for objects
- ► Only destructor is called for objects
- ► Memory is deallocated first before calling destructor
- ► **Destructor is called first before deallocating memory**

42. **new** and **delete** operators cannot be overloaded as member functions.

- ► True
- ► **False**

43. The operator function of << and >> operators are always the member function of a class.

- ► True
- ► **False**

44. Which of the following option is true about new operator to dynamically allocate memory to an object?

- ► **The new operator determines the size of an object**
- ► Allocates memory to object and returns pointer of valid type
- ► Creates an object and calls the constructor to initialize the object
- ► All of the given options

45. new and delete are _____ whereas malloc and free are _____.

- ► Functions, operators
- ► Classes, operators
- ► **Operators, functions**
- ► Operators, classes

46. Which of the following statement is best regarding declaration of friend function?

- ► Friend function must be declared after public keyword.
- ► Friend function must be declared after private keyword.
- ► Friend function must be declared at the top within class definition.
- ► **It can be declared anywhere in class as these are not affected by the public and private keywords.**

47. The operator function will be implemented as _____, if obj1 drive the – operator whereas obj2 is passed as arguments to – operator in the statement given below.

```
obj3 = obj1 – obj2;
```

- ► Member function
- ► **Non-member function**
- ► Friend function
- ► None of the given options

48. Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

- ► Class-name operator +() ;
- ► Class-name operator +(int) ;

► Class-name operator ++() ;
► **Class-name operator ++(int) ;**

49. Class is a user defined_____.

► **data type**
► memory referee
► value
► none of the given options.

50. The static data members of a class are initialized _____

► at file scope
► within class definition
► within member function
► **within main function**

51. There are mainly ---------- types of software

► **Two**
► Three
► Four
► Five

52. When x = 7; then the expression x%= 2; will calculate the value of x as,

► **1**
► 3
► 7
► 2

53. A pointer variable can be,

► Decremented only
► Incremented only
► Multiplied only
► **Both 1 and 2**

54. setprecision is a parameter less manipulator.

► True
►**False**

55. We can change a Unary operator to Binary operator through operator overloading.

►**False**
► True

56. **delete** operator is used to return memory to free store which is allocated by the **new** operator

► **True**
►False

57. When we do dynamic memory allocation in the constructor of a class, then it is necessary to provide a destructor.

► **True**
►False

58. What is the functionality of the following statement?

String str[5] = {String("Programming"), String("CS201")};
► Default constructor will call for all objects of array
► Parameterized constructor will call for all objects of array
► **Parameterized constructor will call for first 2 objects and default constructor for remaining objects**
► Default constructor will call for first 3 objects and Parameterized constructor for remaining objects vuzs

59. What is the sequence of event(s) when allocating memory using new operator?

► Only block of memory is allocated for objects
► Only constructor is called for objects
► **Memory is allocated first before calling constructor**
► Constructor is called first before allocating memory

60. Deleting an array of objects without specifying [] brackets may lead to memory leak

► **True**
►**False**

61. Which of the following data type will be assumed if no data type is specified with constant?

► short
► float
► **int**
► double

62. There is an array of characters having name 'course' that has to be initialized by string 'programming' which of the following is the correct way to do this,

i. course[] = {'p', 'r', 'o', 'g', 'r', 'a', 'm', 'm', 'i', 'n', 'g'};
ii.course[] = 'programming' ;
iii. course[12] = "programming" ;
iv. course = "programming" ;
Choose the correct options.
► (i) and (ii) only
► (i) and (iv) only
► **(i) and (iii) only**
► (ii) and (iii) only

63. What will be the correct syntax of the following statement?

***ptr is a constant pointer to integer*.**
► const int *ptr ;
► const *int ptr ;
► int const *ptr ;
► **int *const ptr ;**

The keyword **const** for pointers can appear before the type, after the type, or in both places. The following are legal declarations:

```
const int * ptr1;       /* A pointer to a constant integer:
                           the value pointed to cannot be changed  */
int * const ptr2;       /* A constant pointer to integer:
                           the integer can be changed, but ptr2
                           cannot point to anything else           */
const int * const ptr3; /* A constant pointer to a constant integer:
                           neither the value pointed to
                           nor the pointer itself can be changed   */
```

Declaring an object to be const means that the this pointer is a pointer to a const object. A const this pointer can by used only with const member functions vuzs.info

64. Overloaded member operator function is always called by _____

- ► Class
- ► Object
- ► **Compiler**
- ► Primitive data type

65. Loader loads the executable code from hard disk to main memory.

- ► **True**
- ►**False**

66. Which of the following is the correct C++ syntax to allocate space dynamically for an array of 10 int?

- ► new int(10) ;
- ► **new int[10] ;**
- ► int new(10) ;
- ► int new[10];

67. The prototype of friend functions must be written _____ the class and its definition must be written _____

- ► inside, inside the class
- ► **inside, outside the class**
- ► outside, inside the class
- ► outside, outside the class

68. Like member functions, _____ can also access the private data members of a class.

- ► Non-member functions
- ► **Friend functions**
- ► Any function outside class
- ► None of the given options

69. To perform manipulation with input/output, we have to include _____ header file.

- ► iostream.h
- ► stdlib.h
- ► iomanip.h
- ► fstream.h

70. The **endl** and **flush** are _____

- ► Functions
- ► Operators
- ► **Manipulators**
- ► Objects

71. If we want to use stream insertion and extraction operators with _____ then we have to overload these operators.

- ► int, float, double
- ► **objects of class**
- ► int, float, object
- ► int, char, float

72. If we want to use stream insertion and extraction operators with _____ then we have to overload these operators.

- ► int, float, double
- ► **objects of class**
- ► int, float, object
- ► int, char, float

73. Classes defined inside other classes are called _____ classes

- ► looped
- ► **nested**
- ► overloaded
- ► none of the given options.

74. Which value is returned by the destructor of a class?

- ► A pointer to the class.
- ► An object of the class.
- ► A status code determining whether the class was destructed correctly
- ► **Destructors do not return a value**

75. Consider the following code segment

```
class M {
 friend int operator!(const M &);
...
};
```

!s // code of line implies that operator!(s)

...

Let assume if s is an object of the class then function is implemented as _____

- ► Member function
- ► Non-member function
- ► Binary operator function
- ► None of the given options

None of the given options

76. When the compiler overloads the assignment (=) operator by default then _____

► **compiler does member wise assignment.**

► compiler does not allow default overload of assignment (=) operator
► member of the class are not assigned properly
► None of the given options

77. If **text** is a pointer of class **String** then what is meant by the following statement?

text = new String [5];
► Creates an array of 5 string objects statically
► **Creates an array of 5 string objects dynamically**
► Creates an array of pointers to string
► Creates a string Object

78. Static variable which is defined in a function is initialized _____.

► **Only once during its life time**
► Every time the function call
► Compile time of the program
► None of the above

79. The appropriate data type to store the number of rows and is_____.

► floatcolums of the matrix
► **int**
► char
► none of the given options.

80. Copy constructor becomes necessary while dealing with _____allocation in the class.

► **Dynamic memory**
► Static memory
► Both Dynamic and Static memory
► None of the given options

81.

Abdullah cheat