CS201

Quiz-01

Quiz by Attiq Kundi

SUBSCRIBE " Knowledge For Us " ON YOU TUBE

100 % CORRECT MCSQ

AND Many MoRe

CS 201

Also Added Today Quiz 24-May-2023

The ASCll code of null character is ----------.

(000) correct answer

Which step is not not performed during a proper program design?

(Write details about the performance of program) correct answer

How many elements are stored in the following ? int matrix [4][5];

(20) correct answer

Which of the following is not a valid variable name in c++?

(@studentName) correct answer

If an array has 50 elements.What is allowable range of subscripts?

(0-49) correct answer

<. <=.> .>= are called ----------operators.

(Relational) correct answer

by Attiq Kundi

Why we use “cin “?

(To read data from keyboard) correct answer

!(x<3)means in c++ that

(x is greater than 3) correct answer

The data in the memory is ---------

(volatile) correct answer

Each array declaration must provide the information about all these things except ----- - - -

The location of the first element to be stored

What will be the output of the program if x=10? If

(x!=0&&x<=10)

{

Cout <<”condation 1 is true”;

}

If(x>=10 && x<=20)

{

Condation 1 is true condation 2 is true

C is widely known development language of_____operating system.

Windows

A repetition statement specifies that an action is to be continued while some_____remains true.

Condition

by Atiq Kundi

_____is a substitute of multiple if statement.

If—elseif statement

If a_____finds an error. It stops translating without generating any executable code.

Compiler

Function prototype is written .

Before call of that function

The_____is an unconditional branch of execution .

Goto statement

What will be the output of the following code snippet?

String str1 = “Hello beautiful”;

String str2 = “yes we can”;

String str3 = strcpy(str1,str2);

Cout<<str3<<endI;

Hello beautiful Yes we can

In two dimensional array .We use_____„for oop(s)“to populate the array.

2

eof is used to check for the_____of file when a file is being read.

End

How many times the following loop will execute? Int j

= 3;

by Atiq Kundi

```
While(j>0)
{
Cout << “statements” << endI;
J=2;
}
```

2

Null character is used to indicate the_____of string.

End

There is a pointer named ptr of type float. Which type of variable address can be stored by ptr?

Float

How many bytes an integer type pointer intPtr will jump in memory if the statement below is executed?

```
intPtr +=2;
```

4

We must include the header file_____to convert the value of one type into another type using built-infunctions.

iostream.h

Use of word processor for writing the code of a program is not good because.

It has no compiler

_____Loop executes at least one times.

Do while

by Attiq Kundi

The data . contained in the structure. is defined in the_____

Curly braces

What is the use of ios::trunk mode?

To truncate an existing file to zero

CS201 Solved Quiz No-1 December 13, 2015

We use_____to open a file or stream for extraction

In

Null character is represented by_____in C++.

/0

An object of_____class can be created for saving the current position of any opened file before reading from the file.

Streampos (pg215)

_____Returns true if c is a digit or a letter and false otherwise.

int isalnum(int c)

We use_____to open a file or stream for insertion.

Out

Base address is the memory address of_____element of an array.

1st

_____allow us to have a memory location and use it as int or char

by Atiq Kundi

interchangeably

union

To read command-line arguments, the main() function itself must be given _____arguments.

2

Individual characters in a string stored in an array can be accessed directly using array _____.

Subscript

To manipulate n-dimensional array_____nested loops are required.

n-1

A character is stored in the memory in _____

String

What will be the size of following array?

int arr[29];

29

An object of_____class can be created for saving the current position of any opened file before reading from the file.

Streampos

We use_____to open a file or stream for extraction.

In

We use_____to open a file or stream for insertion.

by Attiq Kundi

Out

_____are conventional names of the command line parameters of the „main()“ function.
_argc‘ and
_argv‘

In___, we have different data members and all of these have their own memory space.
Structures

How we declare an array of integer data whose size is 20 with array name “count”.
int count[20];

A___is an array of characters that can store number of character specified.
String

File. seekg (-10L, ios:cur)
backword direction

What will be the output of the following while loop? int counter = 0 ; while(counter < 15) cout << counter << “ ”; counter++;
Compile time error

We can access a global variable _____
From the functions only
From anywhere in the program

A repetition statement specifies that an action is to be continued while some_____ remains true.
Condition

Loops are_____Structure.
Repetition

by Atiq Kundi

_____operator is used to pass the address of a variable in call by reference method.

&

How many times the following do-while loop will execute? int k = 10; do { cout << "Statements" << endl; k -= 2; } while(k>0);

5

What is the output of the following code if the 3rd case is true switch (var) { case „a": cout<<"apple"<<endl; case „b": cout<<"banana"<<endl; case „m": cout<<"mango"<<endl; default: cout<<"any fruit"<<endl; }

mango any fruit

by Attiq Kundi

CS201 SOLVED QUIZ NO 1 DECEMBER 09, 2019

The ASCll code of null character is_____

010

Each array declaration must provide the information about all these things except_____

The location of the first element to be stored

Arecord is agroup of related_____

Data

Pointers store the_____

Value of the variable

We can say that a pointer is a variable that hold the_____adress.

Source code

afile.seekg(-10-ios::cur

Backward direction

Deferencing operator is represented by_____

***,+,- non of the given**

A precise sequence of steps to solve a problem is called

Program

The Compiler of C language is written in

by Attiq Kundi

C Language

Initialization of variable at the time of definition is,

Good Programming

In if structure the block of statements is executed only,

When the condition is true

Which of the following function(s) is/are included in **stdlib.h** header file?

double atof(const char *nptr)
int atoi(const char *nptr)

1 and 2 only

Dealing with structures and functions passing by reference is the most economical method

True

Pointer is a variable which store,

Memory Address

Preprocessor program perform its function before_____phase takes place.

Compiling

Which of the following can not be a variable name?

10area

Which looping process is best, when the number of iterations is known?

while

by Attiq Kundi

Which character is inserted at the end of string to indicate the end of string?

null

How many bytes are occupied by declaring following array of characters?
char str[] = —programming‖;

11 plus one for null char (11+1= 12)

12

Which of the following header file defines the **rand()** function?

stdlib.h

Commenting the code _____

Makes a program easy to understand for others

What's wrong with this for loop? for (int k = 2, k <=12, k++)

the commas should be semicolons

For which array, the size of the array should be one more than the number of elements in an array?

char

To Which category of the software "Compiler and Interpreter" belongs?

They belong to system software.

What is the result of the expression x = 2 + 3 * 4 – 4 / 2

12

Write a declaration statement for an array of 10 elements of type float. Include an initialization statement of the first four elements to 1.0, 2.0, 3.0 and 4.0.

float tmp [10] = {1.0,2.0,3.0,4.0};

by Atiq Kundi

Write down the output of the following code? int array[7], sum
= 0;
for(int i=0;i<7;i++)
{
array[i] = i; sum+= array[i];
}
cout<< " Sum = " <<sum;

21

what will be the output of the following segment of C++ code?

```
int A[5] = {1 , 2, 3, 4};
int i;
for (i=0; i<5; i++)
{
A[i] = 2*A[i];
cout << A[i] << " ";
}
```

2 4 6 8 0

Write a C++ program that will determine if a departmental store customer has exceeded the credit limit on a charge account.
Program should input the following facts in five variables
1. Account number
2. Balance at the beginning of month (Beginning balance)
3. total of all items charged by customer this month (charges)
4. total of all credits (credits)
5. allowed credit limit Calculate the
new balance
New balance = Beginning balance + charges – credits
Determine if **new balance** exceeds the **allowed credit limit**. For those customers whose credit limit is exceeded. The program should display the message "Credit Limit exceeded."

by Atiq Kundi

What is the output of the following statement?
int i = 2.5; do { cout i * 2; } while (i > 3 && i < 10);

error

What does !(7) evaluate to in decimal where ! is a NOT operator?

7

The condition in while loop may contain logical expression but not relational expression.

False

Searching is easier when an array is already sorted

True

If an array has 100 elements, what is allowable range of subscripts?

- 99

What will be the value of „a" and „b" after executing the following statements?

a = 3;
b = a++;

4, 3

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

int arr[2][3] = {{0},{0}} ;

Which of the following function returns the size of a string variable?

s trlen()

What will be the range of numbers generated by function rand () % 9?

(a) 0 to 9
(b)1 to 9
(c)0 to 8
(d)1 to 8

by Atiq Kundi

Computer can understand only machine language code.

(e) True

What does 5 ^ 6 , evaluate to in decimal where „^“ is Exclusive OR operator?

False

It mean
5 = 0101
6 = 0110
5 ^ 6 = 0011

If the file is not properly closed in the program, the program_____.

Terminate normally

Which of the following header file include string conversion functions?

string.h

Which header file must be included while handling files?

<fstream.h>

by Attiq Kundi

An array day is declared as: int day[] = {1, 2, 3, 4, 5, 6, 7};

How many elements does array 'day' has?

Solution:-

7 elements

If the declaration is changed as: int day[7] = {1, 2, 3, 4, 5, 6, 7}; How many elements does array 'day' has?

Solution:-

7 elements

The function of cin is

To read data from keyboard

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

ctype.h

by Attiq Kundi

How many parameter(s) function getline() takes?

3

Word processor is

Application software

For which values of the integer _value will the following code becomes an infinite loop?

```
int
number
=1;
while
(true) {
  cout << number;
  if (number == 3) break;
  number += integer_value; }
```

only 0

Each pass through a loop is called a/an

Iteration

A continue statement causes execution to skip to

the statements following the continue statement

What is the correct syntax to declare an array of size 10 of int data type?

int name[10] ;

Consider the following code segment. What will the following code segment display?

```
int main(){
int age[10]
= {0}; cout
```

by Atiq Kundi

<< age ;
}

Value of first element of array

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

int arr[2][3] = {0,0} ;

How many bytes will the pointer *intPtr* of type int move in the following statement?
intPtr += 3 ;

12 bytes

If there are $2^{(n+1)}$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

(n+1) elements

Which of the following operator is used to access the value of variable pointed to by a pointer?

*** operator**

The____statement interrupts the flow of control.

break

Analysis is the -------step in designing a program

First

Paying attention to detail in designing a program is _____

by Atiq Kundi

Necessary

Which programming tool is helpful in tracing the logical errors?

Debugger tool is helpful in tracing the logical errors.

When the if statement consists more than one statement then enclosing these statement in curly braces is,

Must

The while loop becomes infinite,

When the condition is always true

Which of the following function(s) is/are included in **stdlib.h** header file?

1 and 2 only

If we want to store a string “abc” in an array str then the size of this array must be at least,

2

No executable code will be generated if error is found during translation of the program using interpreter.

True

Word processor is

Application software

Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

cout << "H" << x << "\n";

Which of the following is correct way to initialize a variable x of int type with value 10?

by Atiq Kundi

int x = 10 ;

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?

braces { }

Name of an array is a constant pointer.

True

How many bytes will the pointer ***intPtr*** of type **int** move in the following statement?

intPtr += 3 ;

12 bytes

What will be the value of 'a' and 'b' after executing the following statements?

```
a = 3;
b = a++;
```

3, 4

Loader loads the executable code from hard disk to main memory.

True

Which of the following is used with bit manipulation?

Signed double

Which of the follwoing values C++ use to represent true and false?

1 and 0

The argument of the isdigit() function is _____

by Atiq Kundi

character,

Which data type should be used to store the value 50.7 ?

Float

What operator do you use to assign a pointer the address of another variable or constant?

& sige

i.e. **int i;**

**int *
ptri; ptri
= &i;**

A precise sequence of steps to solve a problem is called

Program

The Compiler of C language is written in

C Language

Initialization of variable at the time of definition is,

Good Programming

In if structure the block of statements is executed only,

When the condition is true

Which of the following function(s) is/are included in stdlib.h header file?

1 and 2 only

by Atiq Kundi

Dealing with structures and functions passing by reference is the most economical method

True

Pointer is a variable which store,

Memory Address

Preprocessor program perform its function before_phase takes place.

Compiling

Which of the following can not be a variable name?

10area

Which looping process is best, when the number of iterations is known?

all looping processes require that the iterations be known

Which character is inserted at the end of string to indicate the end of string?

null

How many bytes are occupied by declaring following array of characters?
char str[] = “programming”;

12

Which of the following header file defines the rand() function?

stdlib.h

Commenting the code

Makes a program easy to understand for others.

What's wrong with this for loop?
for (int k = 2, k <=12, k++)

the commas should be semicolons

by Atiq Kundi

For which array, the size of the array should be one more than the number of elements in an array?

char

To Which category of the software “Compiler and Interpreter” belongs?

What is the result of the expression x = 2 + 3 * 4 – 4 / 2

12

first multiplies 3*4 = 12 then Division 4/2 = 2
2+12-2 = 12

by Attiq Kundi

Write down the output of the following code?

```
int array[7], sum = 0;
   for(int i=0;i<7;i++)
   {
   array[i] = i;
   sum+= array[i];
}
   cout<< " Sum = " <<sum;
```

ANS

21

Loop will run times starts from zero and add values from 1 to 6 which is equal to 21

What will be the output of the following segment of C++ code?

```
int A[5] = {1 , 2, 3, 4};
int i;
for (i=0; i<5; i++)
 {
  A[i] = 2*A[i];
  cout << A[i] << "  ";
 }
```

ANS

2 4 6 8 0

Loops will run 5 times as its starting from zero. It will multiply the value of each item in array as last time is not initialized so it will multiply it with zero to give zero as output

In C/C++ the string constant is enclosed

In single quotes

In flow chart, the symbol used for decision making is,

Diamond

The data type before a function name represents its,

Return Type

by Attiq Kundi

The operator used to take the address of a variable is,

(e) &

The header file which is used for input and output is

iostream.h

When we are using command line argument(s), the default argument in C/C++ is/are _____.

argc and argv

In C++, Integer calculation occurs in_____bytes.

2 bytes

In the declaration of two dimensional array,

First index represents row and second represents column

The address operator (&) can be used with,

Variable

__translates high level language program into machine language code

Compiler

Which of the following data type(s) can operate on modulus operator „%“?

float, int

by Atiq Kundi

What will be the result of the expression z = x % y, if x = 19 and y = 4?

3

Which character is inserted at the end of string to indicate the end of string?

null

What will be the value of i and j in the following code segment?

```
int i, j ;
int x[5] = {2, 3, 4, 8, 9} ;
int *ptr
=&x[2];
i =
(*ptr)++
;
j = *ptr++ ;
```

i = 5, j = 5

Syntax of union is identical to _____

Structure

To Which category of the software “Compiler and Interpreter” belongs?

System software

by Attiq Kundi

What is function of **cout** ?

To display output on the screen

In Flow chart process is represented by

Rectangle

&& is---------- operator.

Logical

An over Flow condition occurs when we try to assign a value to a variable which is,

Less than its maximum size

For dereferencing an array element using pointer, we use the operator

&

In the declaration of two dimensional array,

First index represents row and second represents column

by Atiq Kundi

Which of the following data type(s) can operate on modulus operator „%“?

float, int

Which of the following is the correct way to declare a variable x of integer type?

int x;

Which of the following can not be a variable name?

(e) 10area

Which of the function call is ***call by value*** for the following function prototype? float area (int);

(f) area(num) ;

Recursive functions are used when there is a repetitive pattern.

(g) True

What will be the range of numbers generated by function rand () % 9?

0 to 8

What will be the correct syntax to declare two-dimensional array of float data type?

(e) float arr[2][2] ;

When a function finishes its execution then,

Control returns to statement following function call

Consider the following statements to initialize a two-dimensional array.

int arr[][2] = {{4,8},{9, 2},{1, 6}} ;

Editors are used to compile the code.

False

by Attiq Kundi

What is function of **cout** ?

To display output on the screen

< , <= , > , >= are called ---------- operators.

Relational

In while loop the loop counter must be initialized,

Before entering the loop

Data Size of the file is always_____the actual size of the file.

Greater than

The precedence of * is higher than dot operator (.)operator

True

Let ptr1 and ptr2 are pointer variables that points to integer data type then which one of the following arithmetic is allowed,

(h)ptr1 * ptr2

Word processor is

Application software

by Attiq Kundi

What will be the range of numbers generated by function rand () % 9?

0 to 8

How many bytes will the pointer ***intPtr*** of type **int** move in the following statement?

```
intPtr += 3;
```

12 bytes

What will be the correct syntax to assign an array named ***arr*** of 5 elements to a pointer ***ptr***?

***ptr = arr[5] ;**

What will be the output of the following code segment?

```
char *x = ”programming” ;
cout << *(x+2) << *(x+3) << *(x+5) << *(x+8) ;
```

ogai

There is a pointer variable named ***ptr*** of type int then address of which type of variable the ***ptr*** will store in it?

variable of type int

Flow charts explain the working of a program in pictorial format.

True

The object_____may be used both for file input and file output

(h)ifstream,

by Atiq Kundi

Most efficient method of dealing with structure variables is to define the structure globally

True

If a variable is passed by value to a function and the function makes some changes to that variable then it

does not affect the original variable

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

ctype.h

The header file which is used for input and output is

iostream.h

by Attiq Kundi

Suppose **int multi[5][10];** when we are using **multi , it means,
Double referencing

To access the data members of structure___is used.
dot operator (.)

The precedence of * is higher than dot operator (.)operator
True

Which of the following is the starting index of an array in C++?
0

When a call to function statement is encountered,
(h)The control transfers to its Prototype

A function must always return value.
False

If an array has 100 elements, what is allowable range of subscripts? (a) 0 –
0 – 100

If a pointer appears on left hand side of an assignment operator then right side of that assignment operator must be,
Address of variable

by Attiq Kundi

Editors are used to compile the code.
False

Which bitwise operator returns false if both bits are 1?
OR

What does !(7) evaluate to in decimal where ! is a NOT operator?
7

Structures cannot be passed as Function Parameters
False

When break statement is encountered in a loop body it,
Transfers the control outside from current loop

A union is a user-defined data type that contains only___from its list of members at a time.

Two objects

The size of int data type is
2 bytes

Q2
When the logical operator AND (&&) combine two expressions exp1 and exp2 then the result will be true only,
When both exp1 and exp2 are true

The correct syntax of do-while loop is,
do { statements; } while (condition);

_____provide communication channels between files and program.
Function seekg()

All elements of an array must be of,
same data type

Function seekg() takes_____parameter(s).
1

Structures help to define program-specific_____.
functions

by Atiq Kundi

In the declaration of two dimensional array,

First index represents row and second represents column

What will be the result of arithmetic expression 6+27/3*3?

33

Which of the function call is ***call by value*** for the following function prototype?

```
float area (int);
```

area(num) ;

How many bytes are occupied by declaring following array of characters?

```
char str*+ = "programming";
```

12

What will be the correct syntax to assign an array named ***arr*** of 5 elements to a pointer ***ptr***?

***ptr = arr[5] ;**

Let ptr1 and ptr2 are pointer variables then which of the following

arithmetic operation is allowed on pointers?

Addition
Subtraction
Multiplication

All of the above

The variables having a name, type and size are just like empty boxes.

True

When break statement is encountered in a loop body it,

Transfers the control outside from current loop

If two programs **a** and **b** are trying to open a file **xyz.txt** at approximately same time then

Both programs will generate error

by Atiq Kundi

The data type of size one byte is
int

If Num is an integer variable then Num*= 4; means,
Multiply 4 with Num and assign the result to Num

Member function tellg() returns the current location of the _____ pointer.
tellptr()

If we want to store a string “abc” in an array str then the size of this array must be at least,
2

by Attiq Kundi

Pointer is a variable which store,

Memory Address

C is widely known as development language of_____operating system.

Windows

C++ is a case-sensitive language

True

What is the output of the following code?

for (int a = 1; a <= 1; a++) cout << a++; cout << a;

12

A continue statement causes execution to skip to

the next iteration of the loop

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?

braces { }

What will be the correct syntax for the following function call?

square (&num);

by Atiq Kundi

Which of the following statement will assign an integer value 5 to element of a matrix say „m" at second row and third column?

m[2][3] = 5 ;

Class can be defined as

A class includes both data members as well as functions to manipulate that data

_____operator uses the

sign ^ Exclusive OR

For console input and output we use_____. conio.h header file

Header file provide_____so the program running on one operating system can run without an error on the other system

Portability

Constructor has_____.

The same name as of class

The object code of our program is combined with the_____.

Object code of the library functions

The malloc functions takes_____argument(s)

Two

The function overloading requires_____.

The argument list to be different

Bugs can occur due to_____.

Uninitialized data

by Atiq Kundi

The name of the destructor is the same as that of a class proceeding with a__.

becomes more reliable

How many dimensions does n-dimensional array has?

n dimensions

Consider the following code segment. What will be the output of following code?

```
int addValue (int *a){
int b = (*a) + 2;
return b ;
m a

i n

( ) { i n t

x =6 ;
cout << x << "," ;
cout << addValue(&x) << "," ; cout << x ;
}
```

~sign

The main advantage of function overloading is that_____.

The 6,8,6 program

If most significant bit of un-signed number is 1 then it represents a positive number.

True

by Attiq Kundi

e compiler store the elements of multidimensional array in the form of,

Matrix

What is function of **cout** ?

To display output on the screen

provide communication channels between files and program.

Function seekg()

The data type before a function name represents its,

Return Type

In C/C++ language when an array is passed to a function then by default its passing mechanism is,

Call by Reference

Array is a data structure which store

Variables

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?

braces { }

Array is passed by value to a function by default.

False

Which of the following is the correct function call having array named *student* of 10 elements as a parameter.

addRecord(student[10]) ;

What will be the correct syntax for initialization of pointer ***ptr*** of type int with variable ***x***?

int *ptr = &x ;

t will be the correct syntax for initialization of pointer ***ptr*** with string "programming"?

by Atiq Kundi

char *ptr = “programming” ;

The condition in while loop may contain logical expression but not relational expression.

True

We want to access array in random order which approach is better?

Pointers

Single line comments explaining code would be preceded like in the following example.

//

Function write() takes_____as parameter(s).

String of variable lengths, no. of bytes to be read and flags

Structure is a collection of_____under a single name.

Only Functions

Compiler is a

System software

In while loop the loop counter must be initialized,

Before entering the loop

If Num is an integer variable then Num*= 4; means,

4 with Num and assign the result to Num

In C/C++ ,the arguments are passed by_____to a function by default .

value

Disks is divided into_____with power of_____.

Chunks, 2n

C is widely known as development language of_____operating system.

Windows

by Atiq Kundi

Assignment operator „=" is a

Binary operator

Consider the following code segment. What will be the output of the following program?

```
int func(int) ;
int num = 10 ;

int
main(){
int num ;
num = 5 ;

cout << num ;

cout << func(num) ;

}

int func(int
x){ return
num ;

}
```

5, 5

Name of an array is a constant pointer.

True

What will be the correct syntax to assign an array named ***arr*** of 5 elements to a pointer ***ptr***?

ptr = arr[5] ;

If there are $2^{(n+1)}$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

by Attiq Kundi

(a) n elements
(b) (n+1) elements
(c) 2(n+1) elements
(d) $2^{(n+1)}$

elements Q12

In C/C++, null character is represented as

(e) \n
(a) \0
(b) \t
(c) \

r Q13

How many nested loop would be required to manipulate n-dimensional array?

(a) 2n
(b) **n**
(c) n +1
(d) n -

1 Q14

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

ptr[3]
(a) (ptr+3)
(b) *(ptr+3)
(c) Both 1and

3 Q15

Single line comments explaining code would be preceded like in the following example.

(a) /*
//
(b) /
(c) //

Q16

If a variable is passed by value to a function and the function makes some changes to that variable then it

does not affect the original variable
(a) affects the original variable
(b) causes syntax error
(c) None of the given options

Q1
7 What is meant by *num and &num? [1]

ANS * num is a pointer and &num is a reference to that pointer. Q18

Suppose there is a pointer to structure ***sPtr**. How can we access the data member „**name**" with **sPtr**? [1]

by Attiq Kundi

ANS

Structure data members using pointers Using the * operator;
(*sptr).name

Q19

ANS Why we close a file after use? [2]

To save our data stored on file. Also this process makes our program fast and reliable

Q20

Define Flow chart. [3] ANS

Flow Chart

A flow chart is a pictorial representation of a program. There are labeled geometrical symbols, together with the arrows connecting one symbol with other. A flow chart helps in correctly designing the program by visually showing the sequence of instructions to be executed.

Q21

Write down the function definition if we want to pass the arguments to a functionby reference without changing the values stored at that addresses. [5]

Q22

From writing to execution of the program following software are used explain for what purpose each is used. [10]

Editor
Compiler/Interpreter
Linker
Loader

ANS

Editors *is* a tool for writing the code of a program. For this purpose we used Editors in which we write our code. We can use word processor too for this, but word processors have many other features like bold the text, italic, coloring the text etc, so when we save a file written in a word processor, lot of other information including the text is saved on the disk. For programming purposes we don‟t need these things we only need simple text. Text editors are such editors which save only the text which we type. So for programming we will be using a text editor

Compiler and Interpreter

Compilers translate the English like language (Code written in C) into a language (Machine language) which computers can understand. The Compiler read the whole program and translates it into machine language completely. The difference between interpreter and compiler is that compiler will stop translating if it finds an error and there will be no executable code generated whereas Interpreter will execute all the lines before

by Atiq Kundi

error and will stop at the line which contains the error. So Compiler needs syntactically correct program to produce an executable code. We will be using compiler in our course As we write the code in English and we know that computers can understand only 0s and 1s. So we need a translator which translates the code of our program

into machine language. There are two kinds of translators which are known as Interpreter and Compilers. These translators translate our program which is written in C-Language into Machine language. Interpreters translates the program line by line meaning it reads one line of program and translates it, thenit reads second line, translate it and so on. The benefit of it is that we get the errors as we go along and it is very easy to correct the errors. The drawback of the interpreter is that the program executes slowly as the interpreter translates the program line by line. Another drawback is that as interpreters are reading the program line by line so they cannot get the overall picture of the program hence cannot optimize the program making it efficient.

.

Linker Most of the time our program is using different routines and functions that are located in different files, hence it needs the executable code of those routines/functions. Linker is a tool which performs this job, it checks our program and includes all those routines or functions which we are using in our program to make a standalone executable code and this process is called Linking

Loader after a executable program is linked and saved on the disk and it is ready for execution. We need another process which loads the program into memory and then instruct the processor to start the execution of the program from the first instruction (the starting point of every C program is from the main function). This processor is known as loader. Linker and loaders are the part of development environment. These are part of system software.

Q1

There are mainly ---------- types of software

(a) Two
(b) Three
(c) Four
(d) Five

Q2

< , <= , > , >= are called ---------- operators.

(a) Logical
(b) Arithmetic
(e) Relational
(c) Conational

Q3

In order to get 256 from the number 2568 we divide this number by 10 and take,

(a) Its remainder
(b) The number

by Atta Kundi

Its quotient

(c) Its divisor

Q4

If int x = 10; then the value of x/= 3; will be,

(a) 10

3

(b) 13

(c) 1

Q5

How many parameter(s) function getline() takes?

(a) 0

(b) 1

(c) 2

3

Q6

Suppose **int multi[5][10];** when we are using **multi , it means,

(a) Single dereferencing

(b) Single referencing

(c) Double referencing

(d) Double dereferencing

Q7

To access the data members of structure___is used.

dot operator (.)

(a) * operator

(b) € operator

(c) None of given.

Q8

There is NO difference between **bitwise AND operator (&)** and **Logical AND (&&) operator.**

True

(a) False

Q9

Which of the following data type(s) can operate on modulus operator „%"?

float, int

(a) float, double

(b) int

(c) cha

r Q10

What's wrong with this while loop?

while((i < 10) && (i > 24))

(a) the logical operator && cannot be used in a test condition

(b) the while loop is an exit-condition loop

the while loop is an exit-condition loop

(c) the test condition is always true

by Atiq Kundi

Q1
1 The switch structure is a_____construct

(a) single-selection
(b) bi-selection
multiple-selection
(c) unconditional

Q12

Keyword „array" must be used to declare an array.

(a) True
(b) Fals

e Q13

What will be the correct syntax to declare two-dimensional array of float data type?

(a) float arr{2}{2} ;
float arr[2][2] ;
(b) float arr[2,2] ;
(c) float[2][2] arr

; Q14

When an array element is passed to a function then this array element is passed to the function.

By reference
(a) By data type
(b) By value
(c) By

data Q15

Which of the following operator is used to access the value of variable pointed to by a pointer?

(a) * operator
(b) -> operator
(c) && operator
& operator

Q16

Paying attention to detail in designing a program is _____

(a) Time consuming
(b) Redundant
Necessary
(c) Somewhat Good

Q1
7 How does elements of two-dimensional array store into memory? (1)

Two dimensional arrays are also stored in liner order. As like one dimensional array.

Q18

Which strategy is used by binary search algorithm to search a number? (1)

ANS

„divide and conquer" strategy is applied.

by Attiq Kundi

Q19
Write down the general syntax of switch statement. (2)

ANS

switch (*variable/expression*)

{

case *constant1 : statementLlist1* ; case *constant2: statementLlist1* ; *default: statementLlist1* ;

}

Q20
What is a Linker? (3)

Linker Most of the time our program is using different routines and functions that are located in different files, hence it needs the executable code of those routines/functions. Linker is a tool which performs this job, it checks our program and includes all those routines or functions which we are using in our program to make a standalone executable code and this process is called Linking

Q21
What are similarities and differences between Structures and Unions? (5)

Structure

In structures, the data members are public by default. It means that these are visible to all and anyone can change them. Is there any disadvantage of this? Think about the date.
syntax
struct student
{
char
name[60];
char
address[100];
float GPA;
};
Unions We have another construct named union. The concept of union in C/C++ is: if we have something in the memory, is there only one way to access that memory location or there are other ways to access it. We have been using int and char interchangeably in our programs. We have already developed a program that prints the ACSII codes. In this program, we have stored a char inside an integer. Is it possible to have a memory location and use it as int or char interchangeably? For such purposes, the construct union is used. The syntax of union is:
union intOrChar
{
i
n
t

by Attiq Kundi

```
        i
        ;
        c
        h
        a
        r
        c
        ;
};
```

Q22

`Differentiate between C and c++.  (10)`

1. C was the C++ predecessor. As it's name implies, alot of C remains in C++. Although not actually being more powerful than C.
2. C++ allows the programmer to more easily manage and operate with Objects, using an OOP (Object Oriented Programming) concept
3. C++ allows the programmer to create classes, which are somewhat similar to C structures. However, to a class can be assigned methods, functions associated to it, of various prototypes, which can access and operate within the class, somewhat like C functions often operate on a supplied handler pointer.
4. Although it is possible to implement anything which C++ could implement in C, C++ aids to standardize a way in which objects are created and managed, whereas the C programmer who implements the same system has a lot of liberty on how to actually implement the internals, and style among programmers will vary a lot on the design choices made
5. In C, some will prefer the handler-type, where a main function initializes a handler, and that handler can be supplied to other functions of the library as an object to operate on/through. Others will even want to have that handler link all the related function pointers within it which then must be called using a convention closer to C++.
6. C++ applications are generally slower at runtime, and are much slower to compile than C programs. The low-level infrastructure for C++ binary execution is also larger. For these reasons C is always commonly used even if C++ has alot of popularity, and will probably continue to be used in projects where size and speed are primary concerns, and portable code still required (assembly would be unsuitable then).

Q1

The remainder (%) operator is

(a) A logical operator

An arithmetic operator

(b) A relational operator

(c) A division operator

by Atiq Kundi

Q2

If int sum = 10; then the value of the statement sum = sum + 3 ; is ,

(a) 7
(b) Illegal statement
(c) Garbage value

13

Q3

Which of the following function(s) is/are included in **ctype.h** header file?

(a) isdigit(int c)
(b) isxdigit(int c)
(c) tolower(int c)

All of the above

Q4

In C/C++ which of the following header file is used for string manipulation?

stdlib.h

(a) string.h
(b) strings.h
(c) stype.h

Q5

_____provide communication channels between files and program.

(a) Streams
(b) Language like C++

Function seekg()

(c) None of the above

Q6

__translates high level language program into machine language code

(a) Debugger
(b) Editor

Compiler

(c) Linker

Q7

Which of the following data type(s) can operate on modulus operator „%“?

float, int

(a) float, double
(b) int
(c) char

Q8

C++ is a case-sensitive language

True

(a) False

Q9

To include code from the library in the program, such as iostream, a directive would be called up using this command.

(a) #include “iostream.h”
(b) include <iostream.h>
(c) include <iostream.h>

by Atiq Kundi

#include <iostream.h>

Q10

What will be the range of numbers generated by function rand () % 9?

(a) 0 to 9

(b) 1 to 9

0 to 8

(c) 1 to 8

Q1

1 An array stores the numbers into consecutive memory locations.

True

(a) Fals

e Q12

Which of the following is the correct statement for the following declaration? const int *ptr.

(a) ptr is a constant pointer **ptr is constant integer pointer**

(b) ptr is a constant pointer to int

(c) ptr is a constant pointer to

int Q13

Which of the following header file defines the **rand()** function?

(a) iostream.h

(b) conio.h

stdlib.h

(c) stdio.

h Q14

Consider the following code segment. What will be the output of following code?

```
int addValue
(int *a){ int b =
(*a) + 2; return
b ;
}
ma
in
()
{
int
x
=6
;
cout << x << "," ;
cout << addValue(&x)
<< "," ; cout << x ;
}
```

(a) 6,8,6

by Atiq Kundi

(b) 6,6,8
(c) 6,8,8
(d)
6,6,

Q15
Identifier is a name that can be given to variables, labels and functions.

True
(a) Fal
s Q16
For which array, the size of the array should be one more than the number of elements in an array?
(a) Int
(b) Char
(c) Double
float

Q17
Give a precise definition of f**unction** . (1)

AN S

Functions In C/C++, functions are a way of modularizing the code. A bigger problem is broken down into smaller and more manageable parts. There is no rule of thumb for the length of each part but normally one function‟s length is not more than one screen.

Q18
What will be the size of array if we initialize an array with declaration: **int arr[] = {0, 0, 0, 0};**? (1)

ANS
int
arr
[3]
;
Q1
9
What is the difference between **switch** statement and **if** statement. (2)
ANS
In switch statement only one variable can be tested on various condition but using if we can tested multi variables in single statement

Q20
Evaluate the following arithmetic expressions. (3)

a) X = 2 + 6 * 4– 4 * 20 / 5 +3 * 2
b) Y = (6 * 7) - (2 + 3) * (3 – 1) + 5 * (3 +1)

by Attiq Kundi

ANS

a) X = 2 + (6 * 4)–((4 * 20) / 5) + (3 * 2)
b) Y =((6 * 7) - (2 + 3) * (3 – 1) +(5 * (3 +1)))

a) 16
b) 52

Q21
What is the difference between = in C as compared to = used in algebra. (5)

ANS
In C = sign is used to assigned the value in algebra = sign is show that the both side are equal.
In C there must be a variable on the = sign and the right side of the = sign must be a arithmetic expression, variable or a value.
In algebra both side of the equation may or may not be expression. Q22

Write a program which consists of three variables Area, Per, Base, this program should find the area of triangle using the formula, (10)

Area = (Base * Per)/2

```
#include<iostream.h>
#include<conio.h>
main()
{
   float Area, Per, Base;
    // Area = (Base * Per)/2
    Per = 5.0;
    Base = 2.5;
    Area = (Base * Per)/2; cout
  <<"Area = "<<Area;
  getche();
       }
```

Q1
In C/C++ language the header file which is used to perform useful task and manipulation of character data is

(d) cplext.h
ctype.h
(e) stdio.h
(f) delay.h

Q2
The header file which is used for input and output is

by Attiq Kundi

(e) maths.h
(f) string.h

by Attiq Kundi

iostream.h

(g) ctype.h

Q3

Suppose **int multi[5][10];** when we are using **multi , it means,

(e) Single dereferencing

(f) Single referencing

Double referencing

(g) Double dereferencing

Q4

To access the data members of structure___is used.

dot operator (.)

(e) * operator

(f) € operator

(g) None of given.

Q5

The precedence of * is higher than dot operator (.)operator

True

(c) False

Q6

Which of the following is the starting index of an array in C++?

0

(d) 1

(e) -1

(f) any number

Q7

When a call to function statement is encountered,

The control transfers to its Prototype

(e) The control transfers to its definition

(f) Control returns to statement following function call

(g) The compiler stops execution of whole program

Q8

A function must always return value.

(c) True

False

Q9

If an Array has 100 elements, what is allowable range of subscripts? (e) 0 – 99

1 – 99

0 – 100

1 – 100

Q10

If a pointer appears on left hand side of an assignment operator then right side of that assignment operator must be,

(d) Variable name

by Atiq Kundi

Address of variable

(e) Variable value

(f) Constan

t Q11

Editors are used to compile the code.

(c) True

False

Q12

Which bitwise operator returns false if both bits are 1?

(d) AND

(e) XOR

(f) NOT

OR

Q13

What does !(7) evaluate to in decimal where ! is a NOT operator?

7

(e) 8

(f) 9

(g) 1

0 Q14

Structures cannot be passed as Function Parameters

(c) True

False

Q15

When break statement is encountered in a loop body it,

Transfers the control outside from current loop

(d) Transfers the control outside from current program

(e) Enforces the next iteration of loop

(f) Generates compile time

error. Q16

A union is a user-defined data type that contains only__from its list of members at a time.

(e) One object

Two objects

(f) Three objects

(g) None of the given options

Q17

Why programming is important? Describe in ONE line. (1)

Q18

Which bitwise operator returns true if both bits are different and returns falseif both bits are same? (1)

by Atiq Kundi

Q19

Why we close a file after use? (2)

Q20

Can you use an assignment operator to assign the value of one C-string to another? (3)

Q21

The statement int Name [2][2]; define a 2x2 array, Write the code which read data from keyboard for this array. (5)

Q22

Write a program which reads a text file "**PlayersInfo.txt**" residing in the current directory. Open the file **PlayersInfo.txt** in read mode and assign these values to the struct **Player;** assume order of the data in the file to be exactly the same as the order of struct attributes. The struct **Player** has following attributes

i) Name
ii) Height
iii) Age
iv) Score
v) Game

After reading the file and assigning values to the struct, in the end close the file PlayersInfo.txt. (10)

Q23
Q24

Write a program to convert upper case letter to lower case letter. (5)
Write a program to convert lower case letter to upper case letter. (5

Q2

Write a program to convert upper case letter to lower case letter.

(5) Ans:

```
#include <iostream>


using std::cout;

using std::cin;

using std::endl;
```

by Attiq Kundi

```
#include <stdlib.h>


int main()

{

    char inputString[100];

    char lowerCase[100];

     cout<<"Please enter a string (maximum 100 characters): ";

    gets(inputString);

     int i=0;

    for(i=0; i<strlen(inputString); i++)

    {

        lowerCase[i] = tolower(inputString[i]);

    }

    lowerCase[i]='\0';

    puts(lowerCase);

    system("PAUSE");

    return 0;

}
```

Write a program to convert lower case letter to upper case letter. (5)

Ans:

by Attiq Kundi

```
#include <iostream>


using
std::cout;
using
std::cin;
using
std::endl;
#include
<stdlib.h>
int main()
{
    char
    inputString[
    100]; char
    upperCase[1
    00];
     cout<<"Please enter a string (maximum 100
    characters): "; gets(inputString);
     int i=0;
    for(i=0; i<strlen(inputString); i++)
    {
        upperCase[i] = toupper(inputString[i]);
    }
    upperCase[i]
```

by Attiq Kundi

```
='\0';
```

by Attiq Kundi

```
    puts(upperC
    ase);
    system("PA
    USE");
    return 0;
}
```

CS201

GRAND QUIZ FILE (NEW)

ALMOST 800 + MCQS

Which of the following is are serve word for data types in c/c++?

Int

C was developed with the help of ---------- language

BCPL and B

--- is used for input file or for reading from the file.

Tellg()

Following is the declaration a ----------array.Int arr[2][2][2]

3-demensional

! (x < 3) means in c++ that

X is greater than 3

by Atiq Kundi

Which of the following option is correct to compare the declaration of the function?

by Attiq Kundi

---------- **(parameter1,parameter2)**

{

// code to be executed

}

Void functionNAME

Ofstream is used for --------

Output file stream

By default, the starting index of an arrar in c++ is _____

0

How we declare an array of integer data whose size is 20 with array name "count".

Int count [20];

An object of ---------- class can be created for saving the current position of any opened file before reading from the file.

Streampos

C++isa ----------language.

High level

character is used to indicate the end of the string.

Null

by Atiq Kundi

In while loop, the loop counter is initialized at -----

Before entering the loop

Whatistheoutputofthwfollowingcodeifthe3rdcaseis true

Switch (var)

{Case „a";

Cout<<"apple"<<endl;

Mango

Which of the following is used to perform bit-wise exclusive OR operation?

|

If x = 11, and x % = 3, then value of x will be----

2

A variable of character data type occupies ----------bytes in memory.

1

by Atiq Kundi

Null character is represented by ---------- in c++?

\0

In computer system there are mainly---------- type of softwares.

2

There is pointer variable named ptr of type float. Which type ofvariable address canbe storeby ptr?

Float

A character is stored in the memory in -----

Byte

X is an integer variable; what does x++ means,

Add 1 in x value

When wecallafunction, its control--------

Transfers to its definition

'\0'takes ---------- space in thememory.

1 byte

by Atiq Kundi

= operator is used for ----

Assigning values to varaibles

What is the use of ios::trunc mode?

To truncate an existing file to zero

X is an integer variable; what does x ++ means,

Add 1 in x value

_____operator uses the sign &

Bitwise AND operator

_____operator uses the sign I

Bit-wise OR operator

_____operator uses the sign ~

Not operator

_____operator uses the sign <<

Left shift operator

_____operator uses the sign >>

Right shift operator

What can be the resultant number when you AND two numbers 12 & bit-wise using & operator?

8

Structures use----------allocation.

Heap

What will be the size of the following character array?

by Atiq Kundi

Char name[] = “adeel”;

6

A is an array of characters that can store number of

character specified.

String

---- statement is used to terminate the processing of a

particular case and exit from switch structure.

Break

---------- will be used for enclosing function statements into

a block?

{ }

How can we declare an array of characters whose size is

12 with array name“country”?

Char country[12];

Following is the declaration of a 2d array, how many columns are declared for this array.

Int arr[3][2];

2

If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout<<statement?

2

We can access a global variable ----

From anywhere in the program

We use --------- to include all those functions which are

located in different files.

Linker

by Atiq Kundi

A character is stored in the memory in ----

Byte

Which is not true regarding structure?

We can declare array of structure

Mr. ahmad sleeps thirty hours every day. This sentence is __

Grammatically correct but illogical

34 -- will explain the function of a program.

Comments

Char **argv can be read as ----

Pointer to pointer to char

What will be output of the following code? String name[4]= ,"ali","bilal","omer",Ayesha"-; Cout<< name [0];

Ali

The data type before a function name represents its,

Return type

37. The expression ((a+b) = = 10) || ((x+y) = = 20) is true only if?

by Atiq Kundi

Either ((a+b) = =) OR ((x + y) = =20) is true

45. If y = 20 and z = y ++, then the value of z will be------

2146. If

Int a =

17; int

b = 3;

double c = a/b;

what will be value of variable c?

5

What will be the output of the following code?

String grade [3] = {"a", "b", "c"}; Grade[2]

= "f";

Cout<< grade[2];

F

Declaration of two-dimensional array of integers having 3 rows and 5 columns is following?

Int arr [3][5];

A = a + 1; can be written as ----

A+ = 1;

A record is a group of related

by Atiq Kundi

Fields

What will be the result of arithmetic expression 6+48/4*3?

42

Construct is used to execute a set of instructions when a condition is true and other set when it is false?

If\else

If an array has 50elements ,what is allowable range of subscripts?

0 – 49

If int a = 50; then the value of a/= 3; will be?

16

Which of the following option is/are correct about array?

Only one type of elements can store in an array

Whenever some number is added in an array name , it will jump as many as the added number?

Rows

by Attiq Kundi

---------- Returns true if c is a digit or a letter and false otherwise.

Int is a l num (int c)

Which of the following is the default mode of the opening using of ofstream class?

Ios::trunc

In which language the compiler of c language is written?

C

While loop executes at least?

One time

String are accessed by variable of type----

Char

Which of the following is the correct operator to compare the values of two variables?

= =

Not operator is a -----

Single input operator

Pointer points to a particular-----

Memory address

by Atiq Kundi

A function is a block of statements that can be defined on can used----in the program.

As many times as user wants

Function is used to find the number of characters ina string?

Strlen()

!=operator is used to check whether the operand on the left-handside is to the operand on the right-hand-side.

Not equal

A while loop may execute ---------- or more times.

0

How we declare an array of integer data whose size is20 with array name “count”.

Int count[20];

Av ariable declared with in a code block becomes ---------- variable for that block.

Local

If a file is opened with ios::out mode, then -------

We can write in this file

by Attiq Kundi

A function's prototype is written --- the function call.

Before

Loop is mostly used to perform repetition of a tasks for a known number of times.

For

In shift int operations if zero is inserted at the lest most bit, the negative number will become a----------number.

Positive

It is the job of----------to transfer the executable code from hard disk to main memory.

Loader

RAID stands for------

Redundant array of inexpensive devices

Array indexes start from ----

0

In call by reference, ---------- of a variable is passed to the called function.

Address

How many times the following do-while loop will execute?

by Atiq Kundi

Intk=

10;

Do

{

Cout << “statements” << endle; ?

6

The name of a location in memory is called ----

Variable

Function is used to find the number of character in a string.

Strlen()

Which statement is used to close a file?

Myfile.close();

------- Allow us to have a memory location and use it as int or char interchangeably.

None of the given

While handling files, one can have ---------- options

All of the given

---------- Function is used to determine the next position to write a character while writing into a file.

Tellp()

by Atiq Kundi

Whichisthecorrectsyntaxtodefineastructurenamed‘student’?

Struct student{
//varaibles
};

<and>bothare---------- operators.

Logical

Identify the logical error in the following if condition 88. If ((i<5) & & (i>15)) ?

Condition is always false

Not operator is a ----

Single input operator

The use of * sign in first and second statements is called --- and ----

of pointer.

Int*ptr=

&x;

Cout<<*ptr;

?

Referencing, dereferencing

C is widely known as development language of ---------- operating system.

Linux

by Atiq Kundi

If x is declare as an integer, what will be result of the given expression?

X = 2 + 3 * 5 % 2 + 3 / 2 ??

4

What will be the correct syntax of declaration of the following statements?

"ptr is a pointer to const int" ??

Const int *ptr

When the logical operator AND (&&) combine two expression exp1 and exp2 then the result will be true only?

When both exp1 and exp2 are true

by Attiq Kundi

'multi*3+*3+' element can also be accessed by ------

***(*(multi + 3) + 3)**

What is output of following code?

```
Int data [10] = {10,20,30,40,50,60,70,80,90,100};
Int*xptr=&data[4]; Int
*xptr =&data [6];
Cout<<xptr+ yptr++;??
```

120

Whichofthefollowingisnotthesubcategoryofthesystemsoftware?

None of the above

We get 12|8= ---------- where "|" is (bit-wise OR)?

12

After evaluating the expression

X = 10 +3 * 4 / 2 – 1, the value of x will be?

15

We can read, write and manipulate the same file using----

Fstream.h

Return type of a function that does not return any value must be----

Void

Pointers store the----

Memory address

-- operator uses the sign^.

Exclusive OR

by Atiq Kundi

To get the value store data memory address , we use the----

Dereferencing operator

Telling a computer what to do is called ----

Programming

Compiler translates high level language program into ---------- language

code.

Machine

Each array declaration must provide the information about all these things except----

The location of the first element to be stored

E of is used to check for the ---------- of file when a file is being used.

End

The result of 4%3 will be?

1

------- is a substitute of multiple if statement.

If..elseif statement

Find out he logical error in following lines of code. If (x=10)

Cout << "x is 10"; ?

Assignment operator should not be used for comparison

Which is not true regarding structure?

by Atiq Kundi

we can't declare pointers to structure

114-------are used to compiler the code.
Compiler

For converting a void type pointer ptr into integer type, the correct syntax is: int* ptr

A pointer with value NULL is defined in the header files_____and_____.

Stdlib.h stddef.h

Constructor is a special function, called whenever we_____.

Instantiate an object of a class

Constructor is itself a_____of C++ and_____.

Function, can be overloaded

What is the other name of a variable?

Identifier

In shifting operations if zero is inserted at the left most bit, the negative number will become a ___number.

Positive

A class is_____.

User defined Data type

Bugs can occur due to_____.

Uninitialized data

The heap memory structure_____.

by Atiq Kundi

Constantly changes in size

How many bits from a byte?

8

The function calloc takes two arguments, first argument is the_____ and the second argument is the_____.

Required space in terms of numbers, size of space

The main advantage of function overloading is that_____.

The program becomes more readable

Marco are categorized into_____type(S)

Two

When we include the header file in the angle brackets the compiler searches for it in _____.

Specific directory

115. #include <iostream> #include <cstring> Using namespace std; Int main()

{

Charstr1[10]="hello"; Char str2[10]="world";? 10

A structure specifies that an action is to be repeated while some

by Attiq Kundi

condition remains true.

Repetition

In which language the compiler of c language is written?

C

Characters string are terminated by -----

\0

What will be the value of the variable output in the given piece of code? Double output = 0;

Output = (2 +2) * 4 + / (4 – 2);

17

What is the output of the following statement? int i = 2.5; do {

couti*2;}while(i>3&&i<10); error

Searching is easier when an array is already sorted True

If an array has 100 elements, what is allowable range of subscripts?

0 - 99

While developing a program; should we think about the user interface?

//handouts main

Yes

A character is stored in the memory in _____

String

These functions seekg() and seekp() requires an argument of type _____to let them how many bytes to move forward or backward.

Int

dereferencing operator is represented by __

*

A function is a block of statements that can be defined once and used-

by Atiq Kundi

-- in the program.

As many times as user wants

Is used for output during the process of writing to the file.

Seekp()

In case of two-dimensional array , if you add some number in a two- dimensional name, it will jump to the next----

Row

In while loop the condition is checkedthe execution of loop.

Before

Array indexes start from ----

0

Pointers store the----

Memory address

Which step is not performed during a proper program design?

Write details about the performance of program

We can say that a pointer is a variable that holds the------address.

Memory

When accessing a structure memory, the identifier to the left of the dot operator is the name of ----

Structure variable

From the following; which one is the range of random number generator rand() ?

O – 32767

To read command-line arguments, the main () function itself must be given ----------arguments.

2

Which operator has the highest precedence? (*, -, /, +)?

by Atiq Kundi

* and / both hane the same highest precedence

Suppose we have inty[10];

To access the 4th element of the array we write----

Y[3];

transfers the executable code from main memory to hard disk.

Loader

When the logical operator OR (||) combine two expressions exp1 and exp2 then the result will be false only, //bitwise "or" applies here….

When both exp1 and exp2 are false

suppose we have int y[10]; To access the 4th element of the array we write_

none of given

we have opened a file stream myfile for reading (getting), myfile.tellg () gives us the current get position of the file pointer. It returns a whole number of

type_____

int

ofstream is used for___

Output file stream

A structure is a _____under a single name. collection of

Variables

In C/C++ the string constant is enclosed ...corrected r red one

In curly braces

The size of int data type is 4 bytes

In Flow chart process is represented by

by Attiq Kundi

Rectangle

If the break statement is missed in switch statement then,// a break statement with no label always completes abruptly, the reason being a break with no label. If no switch, while, do, or for statement in the immediately enclosing method,

by Attiq Kundi

constructor or initializer encloses the break statement, a compile-time error occurs?
This may cause a logical error

When we are using const keyword with a variable x then initializing it at the time of declaration is, ?
Optional

Which of the following is the correct way to assign an integer

value 5 to element of a matrix say 'm' at second row and third

column?
m[2][3] = 5 ;

How many total elements must be in two-dimensional array of 3 rows and 2 columns?
6

Which of the following is the correct statement for the following declaration?
*ptr is a pointer to const int

What will be the correct syntax to assign an array named arr of 5 elements to a pointer
ptr?
*ptr = arr[5] ;

C is a/an language
object oriented

The variables having a name, type and size are just like empty boxes.

by Atiq Kundi

True

What's wrong with this for loop? for (int k = 2, k <=12, k++)

the commas should be semicolons

Constructor is a special type of function;

Which has no return type

```
#include <iostream>
#include<conio.h> Using
namespace std;
   Void display (int=1, float=2,3, char='@');
   Main()
   {
   Display();
   Display(5);
   Display(6,7,8);
   Getch();
   }
   Void display( int first float second char third)
   {cout<"intfirst=<<first cout <<second=<<second cout<<third=<<third}
```

First=1, second=2,3, third=@first=5, second=2,3, third =@ first=6, second=7,8 third=@ first=9, second=10,11 third=$

Default constructor generated by_____does_____for us

Compiler, no initialization

#define CIRCUMFERENCE(X)(2*PI*R) is a

Definition of a marco

Constructor is itself a_____of C++ and___.

Function, can be overloaded

by Atiq Kundi

We cannot use_____pointer for storing and reading data from it

NULL

Which function is used to delete the allocated memory space?

Free()

the main advantage of function overloading is that_____.

The program becomes more readable

The data members of the class are initialized_____.

At runtime

An instance of a class is called_____.

Object

Malloc function returns_____to the_____from the available memory

Void pointer, starting of the chunk of memory allocated from the heap

The_____is the increment operator in c++

++

The constructor contains_____.

No return type

For accessing data members we use_____operator

Dot.

In a class we can have_____constructor

Only one

by Atiq Kundi

Object code is machine code but it is not_____and_____.

Reloadable, executable

Getche() is a_____function and defined in_____header file.

Built in function, conio.h

In C++ a variable can be declared anywhere in the program, this will increase_____.

Readability

The compiler use a name mangling technique to_____.

Generate a unique token that is assigned to each function

Most efficient method of dealing with structure variables is to define the structure globally

True

There are mainly types of software.//

Two

When a pointer is incremented, it actually jumps the number of memory addresses ?

According to data type

by Attiq Kundi

setw is a parameterized manipulator.

True

if (a>b && a>c) then the condition will be true

only if Both a>b and a>c are

by Attiq Kundi

true

In while loop the loop counter must be initialized,

Before entering the

loop

_____of a variable means the

locations within a program from where it

can be accessed.

Reference

Switch support data.

Integer Character Float Both integer and character

A function is a block of statements that

can be defined once and used__in the

program.

As many times as user wants

_____statement is used to

terminate the processing of a

particular case and exit from

by Atiq Kundi

switch structure.

break

The most suitable data type for number 325.25 is_.

float

X is an integer variable; what does X++ means,

Add 1 in X value

The operators ++ and –- are used to increment or decrement the value of a variable by_____

1

Which of the following loops checks the test condition at the end of the loop?

Do-While

The operator to free the allocated memory using new operator is ___.

delete

by Atiq Kundi

suppose we have int y[10]; To access the 4th element of the array we write_

_____

y[3];

From the following; which one is the range of Random number generator function rand()?

0 – 32767

From following; which one is the correct syntax of an array initialize: Array size is 10 and it is of double data type to value 0?

double arr[10] = {0.0};

The string in the array is terminated by a____

null

In C/C++; by default arguments are passed by_____to a function.

Value

by Atiq Kundi

char name [] = "Hello World" ; In the above statement, a memory of characters will be allocated

12

_Keyword is used to return some value from a function.

return

Which of the function call is call by value for the following function prototype?
float add(int);

add(x);

The increment of a pointer depends on its _.

data type

The ASCHI code of null character is_____

000

Pointers are a special type of in which a memory address is

store

Transpose of a matrix means that when we interchange rows and columns_____

the first row becomes the first column

by Atiq Kundi

Pointers store the____
value of a variable

Which of the following function call is "call by reference" for the following functionprototype?
int add (int *); add(&x);

The name of the array is a constant pointer which contains the memory address of the of the array.
first element

array name always contains the memory address of the of the array
first element

At the , we try to break up the problem into functional units
design phase

Syntax of a union is identical to _ .
structure

A union is a user-defined data type that contains only_--from its list

of members at a time.
one object

Which of the given file handling modes are similar in their functionality ?
ios::trunc, ios::ate

by Atiq Kundi

Which one of the given option is not a mode for reading/writing the data from a file?
Trunk

In C/C++, the header file used for string manipulation is _.
string.h

A 2D array multi[5][10] can be accessed using the array name as **multi , this technique is called _.

Double dereferencing

C language was evolved from language(s).
B and BCPL

The statement forces the immediate next iteration of the loop.
Continue

_____ are very good tools for code reuse.
Functions

When an argument is passed by reference, _____
the function accesses the argument‘s original value in the calling program.

_____ executes all the lines before error and stops at the line which contains the error.

Intrepreter

by Atiq Kundi

Analysis is the step in designing a program.
First

Which of the following is the correct function call, having array named student of 10 elements as a parameter?
addRecord(student);

When an array element is passed to a function, it is passed by _____.
Reference

What is the correct syntax to declare an array of size 10 of int data type?
int name[10] ;

If we want to copy an array, both arrays need to be of same _.
Data type and size

Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

cout << "H" << x << "\n";

Which one of the statements given below is equivalent to x %= 5?
x = x % 5

The condition in loop should be a(n)_____.
Boolean Expression

Which structure is represented by following flow chart ?

if structure

Stream which sends data to the program is called_____.

by Atiq Kundi

Input stream

Syntax of a union is identical to_____ .

Structure

When accessing a structure member, the identifier to the left of the dot operator is the name of_____.

a structure variable

The parameter passed to is digit() function is_____.

a character variable

TWAIN stands for_____ .

Technology Without An Interesting Name

_____Translates high level language program into machine language code.

Compiler

From the option given below, what will be the correct output of the code? for (int a = 1; a <= 3; a++)

cout<<a*3-1<<" ";

2 5 8

If the return type of a function is void then it means that it will_____.

return any type of data return no data

by Atiq Kundi

The functions that have already been defined as a part of the language are called _____.

built-in functions

Given that double Array is an array of 7 integers.Whichofthebelowisthe correct statement to access the 5th element of the array?

doubleArray[4]

Special name which is substituted in code by its definition and as a result we get an expanded code is called

Macro

A=a+1, can be written as _____

A+=1

The compiler generates_____automatically.

Constructors

The data members of the class are initialized _____

At runtime

- **Explicitly write keyword private in the class definition**
- **Separate the interface and implementation**
- **The default constructor has no arguments**
- **Constructor has the same name as of class**
- **Initializing the data members in the definition of the class is a syntax error**

___for parameters is also done for inline functions.

Automatic type checking

An instance of a class is called_____.

Object

With the use of dynamic allocation of memory, the system resources can be_____.

by Atiq Kundi

Used efficiently

When we include the header file in the angle brackets the compiler searches for it in

Specific directory

___is a special type of pointer we have to cast it before we use it.

Void

Multiplicative, additive and assignment operators are_____operators

Binary

The memory allocation functions return a chunk of memory with a pointer of type _____.

Void

Default constructor takes_____.

No parameters

The symbol which is used to represent a process in a flow chart is _____.

Rectangle

When an array is passed to a function , by default it will be passed by_.

Reference

What is the range of Random number generator function rand()?

0 – 32767

The first character of a variable name must be an alphabet or _____.

Underscore

by Atiq Kundi

In___,the first pointer stores the address of the some other pointer, which contains the address of any variable.

single dereference

by Attiq Kundi

Initialization of variable at the time of definition is ---------- practice.

Good Programming

Which looping process checks the test condition at the end of the loop?

do-while

You can use a_____statement to transfer control else where out of the nested structure.

Goto

Which of the following array is the most suitable for storing a matrix structure?

Single-dimensional array

The microsoft word document(.doc) is a kind of_____.

Random Access File

A union is a user-defined data type that contains only_____from its list of members at a time.

one object

In C/C++,_____are the doors through which data can enter and come out of a program.

Streams

Which one of the given option is not a mode for reading/writing the data from a file?

Trunk

C++ view search file as a sequential stream of_____.

Bytes

In 2Darray,the technique used to access the array elements is called

Double dereferencing

by Atiq Kundi

From the options given below, identify the correct option which is used for calling the function float square (int &);

square (num);

Identify the correct option which is used for calling the function float area (int).

area(num) ;

Which kind of error occurs in the code below to access the variable num in the

main function?

intnum

=10; int

main(){

int x;

x = num ;

}

No error

A program statement that in vokes a function is called_____.

function call

Whatwillbetheoutputofthefollowingcodesegment?main(){

int a =

10 ; int

b =0; int

*x=&a;

b =

(*x)+3 ;

cout << a << —, ‖ << b ;

}

by Atiq Kundi

1
0
, 1
3

When the logical operator AND (&&) combines two expressions exp1 and exp2thentheresultwillbetrueonly

When both exp1 and exp2 are true

Forwhicharray,thesizeofthearrayshouldbeonemorethanthenumber of elements in an array?
char
What is the range of Random number generator function rand()?

0 – 32767

Toassignedavaluetoacharactertypevariable,_____areusedaround the value.
single qoutes ' '

In C/C++, the #include is called_____.
Preprocessor Directive

Thenumber544.53mustbestoredin_____data type.
Float

Use of the_____statement violates the rules of structured programming.
Goto

In Flow Chart, flow of control is represented by_____.
Arrow

by Atiq Kundi

What will be the correct syntax for initialization of pointer ptr of type int with variablex?

int *ptr = &x ;

Syntax of a union is identical to_____ .

structure

Aunionisauser-defineddatatypethatcontainsonly_____fromitslist ofmembersatatime.

one object

Which of the given file handling modes are similar in their functionality ?

ios::trunc, ios::ate

Which one of the given option is not a mode for reading/writing the data from a file?

Trunk

Streamwhichsendsdatatotheprogramiscalled_____.

Input stream

Syntax of a union is identical to_____ .

Structure

When accessing a structure member, the identifier to the left of the dot operator is the name of _.

a structure variable

The parameter passed to is digit() function is_____.

a character variable

TWAIN stands for_____ .

Technology Without An Interesting Name

_____Translates high level language program into machine language code.

Compiler

by Atiq Kundi

From the option given below, what will be the correct output of the code? for (int a = 1; a <= 3; a++)

cout<<a*3-1<<" "; 2

5 8

If the return type of a function is void then it means that it will _____.

return no data

The functions that have already been defined as a part of the language are called _____.

built-in functions

Given that doubleArray is an array of 7 integers. Which of the below is the correct statement to access the 5th element of the array?

doubleArray[4]

The symbol which is used to represent a process in a flow chart is _____.

Rectangle

When an array is passed to a function, by default it will be passed by _.

Reference

The first character of a variable name must be an alphabet or _____.

Underscore

In ____, the first pointer stores the address of the some other pointer, which contains the address of any variable.

single dereference

Initialization of variable at the time of definition is ---------- practice.

Good Programming

by Attiq Kundi

Which looping process checks the test condition at the end of the loop?

do-while

You can use a_____statement to transfer control else where out of the nested structure.

Goto

An object of_____class can be created for saving the current position of any opened file

before reading from the file Stream

The value returned by the of() function is of_____type.

Character

If a file is not properly closed in a program then what is the status of the program ?

The program will terminate normally

The parameter passed to is digit() function is_____.

a character variable

by Atiq Kundi

In C/C++, the header file used for string manipulation is_____.

string.h

Arrays are best data structures_____.

for relatively permanent collections of data

Each array declaration must provide the information about all these things except _____.

Number of elements of the array

The First step for developing a program is_____.

Linking Analysis

_____Transfers the executable code from hard disk to main memory.

Loader

_____Operator Is used to pass the address of a variable to the called function.

&

In call by reference ,_____of a variable is passed to the called **function. Address**

_____of a function is also known as sig nature of a function.

Declaration

Preprocess or program performs its function before_____phase takes place. **Compiling**

by Atiq Kundi

Which of the following is the correct function call, having array named student of 10 elements as a parameter?

addRecord(student[10]);

The remainder (%) operator is a _____ operator.

Arithmetic

Which of the following array is the most suitable for storing a matrix structure?

Two-dimensional array

*.docis_____ by type.

Random Access File

Which of the following is NOT a preprocessor directive?

#define

The return type of operator function must always be void.

False

What does (*this) represents?

A value of the data member

The statement cin.get();isusedto,

Read a character from keyboard

When we do dynamic memory allocation in the construct or of a class, then it is necessary to provide a destructor.

True

Overloaded new operator function takes parameter of type size_t and returns

void pointer

These cond parameter of operato rfunctions for <<and>> are objects of the class for which we are overloading these operators.

True

by Atiq Kundi

C++ is a case-sensitive language

True

To include code from the library in the program, such as iostream, a directive would be called up using this command.

#include <iostream.h>

A template function must have only generic data types.

True

Template class can not have static variables.

False

What will be the correct syntax to assign an array name darro f5 elements to a pointer ptr?

***ptr = arr[5] ;**

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

Both 1and 3

by Atiq Kundi

If most significant bit of un-signed number is 1 then it represents a positive number.

True

If there is a symbol (& sign) used with the variable name followed by data type then it

Refers to__and if & is being used with variable name then it refers to

____.

Reference variable, address of variable

We can also do conditional compilation with preprocessor directives.

True

The default value of a parameter can be provided inside the

_____

function definition

Classes defined inside other classes are called_____class

nested

What purpose do classes serve?

All of the given options

Every class contains_____.

Constructor

New operator is used to allocate memory from the free store during

None of the given options

by Atiq Kundi

When an object of a class is defined inside another class then,
Destructor of inner object will be called first

It is possible to define a class within another class.
True

New and Delete are also used with_____and data types as well.
Class, Objects

With New keyword, data types and class members are initialized with meaningful values instead of garbage.
True

C language is developed by
Dennis Ritchie

Which of the following choice is not an example of an int data type?
-4.0

In flow chart, the symbol used for decision making is,
Diamond

Switch statement deals with,
Integer and character data

Default case in switch statement is,
Optional

*.docis_____by type.
Sequential File

Member function tell g() returns the current location of the___

by Atiq Kundi

pointer.
tellptr()

Dealing with structures and functions passing by reference is the most economical method
True

In C/C++ all character strings are terminated with,
Null character

Word processor is http://vustudents.ning.com
Application software

Which of the following can not be a variable name?

10area

Which looping process is best, when the number of iterations is known?
while

By default an array of characters is passed by value to a function
False

Which of the following operator is used to access the address of a variable?
& operator

The name of an array represents address of first location of array element.
False

Compiler is a
Application Software

If Num is an integer variable then Num++ means,

by Atiq Kundi

Add 1 with Num

For one byte there are_____combinations of values that can be stored in computer.

2^8

InC/C++languagetheheaderfilewhichisusedtoperformusefultaskandmanipulationofcharacterdatais

ctype.h

Default case in switch statement is,

Optional

When break statement is encountered in switch statement, it

Exits from switch statement

will be the result of arithmetic expression 6+27/3*3?

Whatisthecorrectsyntaxtodeclareanarrayofsize10ofintdatatype?

int name[10] ;

How many dimensions does n-dimensional array has?

n dimensions

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

ptr[3]

Which of the following values C++ use to represent true and false?

1 and 0

by Attiq Kundi

Declaring structures does not mean that memory is allocated.

True

For which array, the size of the array should be one more than the number of elements in an array?

char

In a class we can have_____constructor(s).

Only one

Which one of the following is mandatory preprocessor directive for c++?

#include <isotream>

Header files provide_____so the program running on one operating system can run without an error on the other system

Accessibility

We should not use such variable names that are starting with_____because in C++ these are lots of internal constants and symbolic names that start with it.

Double underscore

Which of the following code segment represents a left shift operator?

Result= number<<1

Which of the following code segment represent a bitwise And operator?

&

Which of the following code segment represent a bitwise OR operator?

I

_____of the following code segment represent a Bitwise Exclusive OR operator

Which of the following code segment represent a NOT operator

by Atiq Kundi

~

If a variable is passed by value to a function and the function makes some changes to that variable then it

does not affect the original variable

InC/C++ the #include is called,

Preprocessor Directive

Loops are_____Structure.

Repetition

The size of operator is used to determine the size of_____.

data type

Structures use _____ allocation.

Stack

Which header file must be included to use the functions to lower() and to upper()?

ctype.h

In Analysis, we try to have a _____

Precise problem statement

CS201
Mid-Term
Quiz by Attiq Kundi
SUBSCRIBE "Knowledge For Us" ON YOU TUBE

by Attiq Kundi

100 % CORRECT MCSQ

AND Many MoRe

CS 201

by Attiq Kundi

Pointers store the _____

memory address

_____Returns true if c is a digit and false otherwise.

int isdigit(int c)

e of is used to check for the_____of file when a file is being read.

End

The statement cout<< yptr will show the_____the y ptr points to.

memory address

Which of the following is true about streams?

A& B

While handling files ,one can have_____options

All of the given

Ifanarrayhas50elements,whatisallowablerangeofsubscripts?

0 – 49

A structure is a collection of_____under a single name.

variables

If stream is used for_____

Input file stream

by Attiq Kundi

The ASCHI code of null character is_____

000

dereferencing operator is represented by _____

*****

When ever some number is added In an array name , it will jump as many _____as the added number.

rows

To access the data members of structure,_____is used.

Dot operator

Which of the following is true about streams?

A. It is a sequence of bytes
B. It is an ordered sequence
C. All bytes can go through the stream simultaneously
D. Bytes that enters first into the stream will go out at last

A and B

We use_____to open a file or stream for extraction

in

char**argv can be read as_____.

pointer to pointer to char

From following; which one is the correct syntax of an array initialize: Arraysizeis10anditisofdoubledata typetovalue0?

double arr[10] = {0.0};

by Atiq Kundi

Pointers work by pointing to a particular_____
data type

_____function give the position of the next character to be read from that file.
tellg()

aFile. seekg (-10L, ios:cur)
backward direction

An object of_____class can be created for saving the current position of any opened file before reading from the file.
Stream

Structures are syntactically defined with the word_____.
struct

_____Allow us to have a memory location and use it as intorchar interchangeably
union

A hierarchy of classes which are used to deal with console and disk files are called _____.
IO classes

_____function is used to determine the next position to write a character while writing into a file.
tellp()

by Atiq Kundi

For binary member operators, operands on the_____drives(calls)the operation.

Left

We cannot increment_____.

references

We can_____pointer.

all of the given

We can_____references.

None of the given

What will be the correct syntax for the following function call?

add(x);

An instance of a class is called_____.

object

The____is called automatically when an object destroys

destructor

The destructor is used to_____.

deallocate memory

_____data isn't accessible by non-member functions or outside classes.

by Atiq Kundi

private

Member functions of the class_____main program.
are accessible from

Overloading means :
Using the same name to perform multiple tasks or different tasks depending on the situation.

The main advantage of function overloading is_____.
The program becomes more readable

You cannot overload the_____operator.
? :

InC++,avariablecanbedeclaredanywhereintheprogramthiswillincrease _.

efficiency

Memory allocated from heap or free store_____.
cannot be returned back unless freed explicitly using free and delete operators

We cannot use_____pointer for storing and reading data from it.
'NULL

The dynamic memory allocation uses_____where as static memory allocation uses__.
heap , stack

by Atiq Kundi

What will be the output of the given code? #include

#defineMAX(A,B)((A)>(B)?(A):(B)) void main() {

inti,

x,y;

x =

23;

y =45;

i = MAX(x++, y++);

// Side-effect: // larger value incremented twice cout << "x = " << x << " y

= " << y << '\n';

}

x=24 y=47

NULL has been defined in_____header file.

Stdlib.h

Symbolic constant PI can be defined as:

#define PI 3.14

The friend function of a class can have access_____.

to the private data members

C++ was developedby_____.

Bejarne Stroustrup

Once the_____are created, they exist for the lifetime of the program.

static variables

by Atiq Kundi

Encapsulation means_____.

that the data of a class can be accessed from outside

An address is a_____,while a pointer is a_____.

constant, variable

The syntax of declaration of a function that returns the reference to an integeris _.

int & myfunc();

Which one of the following is mandatory preprocessor directive for c++?

#include

The members of a class declared with the key word structure _____by default.

Public

getche() is a_____function and defined in_____header file.

built-in function , conio.h

_____operators are the ones that require two operands on both sides of the operator.

Binary

_____Will return the number of bytes reserved for a variable or data type.

Size of operator

by Atiq Kundi

_____are not available in C language.

Library functions

The members of a class declared without any key word are_____by default .

private

For console input and output we use_____.

conio.h header file

The name of the destructor is the same as that of a class proceeding with a _.

~ sign

A reference cannot be NULL it has to point a data type.

True

A pointer is_____.

a variable for storing address

Constructor is a special function, called when ever we_____.

instantiate an object of a class

by Atiq Kundi

Symbolic constant PI can be defined as:

by Attiq Kundi

#define PI 3.14

Object code is machine code butit is not____and_____.

relocatable, executable

The default visibility for the data members of the class is private

accessible outside the class

The___is called automatically when an object destroys.
destructor

Constructor is special type of function : which has no
return type

_____variables are those that are defined outside of main.

Global

With in the statement obj1=obj2;obj1 will call the assignment operator functionandobj2will be passed as an argument to function.

True

Whenthe compiler overload the assignment(=)operator bydefault then
Compiler does member wise assignment.

by Atiq Kundi

It is possible to return an object from function using this pointer.

True

Overloaded assignment operator must be Member function of class

Let suppose

Int a, b, c, d, e;

a = b = c = d = e = 42;

This can be interpreted by the compiler as a=(b=(c

=(d= (e = 42))));

In statement a+b+c, at first b+c is

executed first

Suppose int i = 10; then what is the output of cout<<oct<<i;

12

O stream is a_____operator.

Standalone

_____Must be included to use stream manipulation in your code.

Iomanip

_____Operators are the ones that require only one operator to work.

Unary

The end land flus hare_____.

Manipulators

When operator function is implemented as member function then return type of function _.

by Attiq Kundi

Can be any data type

by Attiq Kundi

When a variable is defined as static in a class then_____.

Only one copy is created for all objects of this class

Automatic variables are created on_____.

Stack

cout<<i<<"";

cout<<d<<"";

cout <<f;

Above statements can be written within statement of one line as:

cout << i <<" "<< d <<" "<< f;

dec,hex,octareall_____.

Non-parameterized manipulators

What will be the output of following statement?

cout<<setfill('0')<<setw(7)<<128;

0000128

Which of the following syntax is best used to delete an array of 5objects named 'string' allocated using new operator.

delete []string;

If we have a program that writes the output data(numbers) to the disc, and if we collect the output data and write it on the disc in one write operation instead of writing the numbers one by one.

In the above situation the area where we will gather the number is called Buffer

The first parameter of operator function for << operator_____.

Must be passed by reference

by Atiq Kundi

The second parameter of operator function for >> operator must always be passed

By reference

The only operator that the compiler overloads for user define data type by default is------

Assignment (=) operator

Consider the following code, the printed value will be converted into: int n=10;

cout <<oct<<n;

Base 8

_____variables are defined in the main.

Local

O stream class is_____and not under our control.

built-in

The memory allocation in C++ is carried out with the help of_____.

new operator

If B is designated as friend of A,B can access A's non-public members.

A can access non-public members of B

If the request of new operator is not fulfilled due to insufficient memory in theheap _.

the operator returns 0

We should not use such variable names that are starting with_____
because in C++, there are lots of internal constants and symbolic names that start with it.

double underscore

by Atiq Kundi

The friend key word provides access_____.

in one direction only

The malloc function takes_____argument(s).

one

The constructor contains_____.

no return type

What will be the output of the following c++ code?

```
#include<iostream.h>
#define max 100
main()
{
#ifdef max
Cout<<"Hellow;
}
```

Error

Once we have defined as ymbolic constant valueu sing#define, that value _____

during program execution cannot be changed

The memory allocation functions return a chunk of memory with a pointer of type _.

by Attiq Kundi

ptr

A class can be declared as a_____of other class.

member

To avoid dangling reference, don't return_____.

the reference of a local variable from the function

Constructor is its elfa_____of C++ and_____.

function, can be overloaded

Theparameterpassedtoisdigit()functionis_____variable.

Integer

char**argv can be read as_____.

pointer to pointer to char

To read command-line arguments, the main() function itself must be given _____arguments.

2

How many bytes an integer type pointer intPtr will jump in memory if the statement below is executed?

intPtr += 2;

8

by Attiq Kundi

The increment of a pointer depends on its_____.
data type

The statement cout<< yptr will show the_____the yptr points to.
memory address

_____is used as a dereferencing operator.
*****

Transpose of a matrix means that when we interchange rows and columns _.
the first row becomes the first column

Individual characters in a string stored in an array can be accessed directly using array_.
subscript

We can define a matrix as_____array.
Multi dimensional

A _____is an array of characters that can store number of character
specified. String

Given a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?
array[2][3] = 6;

_____of a variable means the locations with in a program from where it can be accessed.
Visibility

Which of the following function call is "call by reference" for the following function prototype?
int add (int *);add(&x);

by Atiq Kundi

Which of the following function call is "call by reference" for the following function prototype?
float add (float *); add(&x);

Which of the function call is call by value for the following function prototype?
float add(float); add(x);

by Attiq Kundi

Which of the function call is "call by value" for the following function prototype?

float add(int);

add(x);

Return type of a function that does not return any value must be_____.

void

_____will be used for enclosing function statements into a block.

{ }

Whatistheoutputofthefollowingcodeifthe2ndcaseistrue switch (var){

case 'a': cout<<"apple"<<endl; case

'b':cout<<"banana"<<endl; case

'm':cout<<"mango"<<endl; default: cout<<"any

fruit"<<endl;

}

Banana mango any fruit

When the break statement is encountered in a loop's body, it transfers the control from the current loop.

Outside

What is the output of the following code if the 3rd case is true

switch (var) {

case 'a':cout<<"apple"<<endl; case

'b':cout<<"banana"<<endl; case

'm':cout<<"mango"<<endl; default: cout<<"any

fruit"<<endl;

}

Mango any fruit

by Atiq Kundi

What is the output of the following code, if the first case is true

switch (var){ case 'a':cout<<"apple"<<endl; case

'b':cout<<"banana"<<endl; case

'm':cout<<"mango"<<endl; default: cout<<"any

fruit"<<endl;

}

Apple banana mango any fruit

What will be the output of following code segment? for(int i=2;i<10;

i++) {

if(i==5)continue;

cout<<i<<",";

}

2,3,4,6,7,8,9

_____Statement is used to terminate the processing of a particular case and exit from switch structure.

break

What will be the result of the expression j= i++; if initially j= 0and i= 5**?**

5

What will be the result of the expression k = ++m; if initially k = 0 and m = 5?

6

How many times the following do-while loop will execute?

int k=10; do{cout<<"Statements"<<endl;k-=2;}while(k>0);

6

by Attiq Kundi

Which of the following loops checks the test condition at the end of the loop?

by Attiq Kundi

Do-While

The operators++and— are used to increment or decrement the value of a ariable by _.

1

How many times the following loop will execute?

intj=3;while(j>0){cout<<"Statements"<<endl;j -=2;}

2

A____structure specifies that an action is to be repeated while some condition remains true.

Control

!(x>3)means in C++that x is less

than or equal to 3

When the logical operator&& combines two expressions then the result will be true only when the both expressions are_____.

true

<and>both are_____operators.

Relational

What will be the value of variable “input” if the initial value of input is 67?

```
if(input >= 50)
input = input + 1;
if(input <= 75)
input = input + 2;
```

by Atiq Kundi

else

input = input - 1;

70

!(x < 3) means in C++ that

x is greater than or equal to 3

!=operator is used to check whether the operand on the left-hand-side is _____to the operand on the right-hand-side.

Not equal

When the if statement consists more than one statement then enclosing these statement in curly braces is,

Must

The most suitable data type for number 325.25 is_____.

Float

What will be the result of arithmetic expression 6+48/4*3?

42

Which of the following will be the most appropriate data type to store the value 63.547?

Float

In the given expression which operator will be evaluated first? 10 + (6 / 2) - 2 * 3?

/

What will be the value of the variable output in the given piece of code? double output

= 0; output = (2 + 2) * 4 + 2 / (4 - 2);

by Atiq Kundi

17

It is the job of_____to transfer the executable code from hard disk to
main memory. Loader

In computer systems the reared mainly_____type of softwares .

2

_____will explain the function of a program.

Comments

if(a>b&&a>c) then the condition will be true only if Both a>b and a>c are
true

A variable of character data type occupies_____byte(s)in memory.
1

We must include the header file_____to convert the value of one type into another type using built-in functions
. string.h

A function is a block of statements that can be defined once and used _____in the program.
As many times as user wants

Select the correct way to assign the address of first element of array to pointer?
int *ptr = &data;

Consider the following code segment. What will be the output of following code?

by Atiq Kundi

```
int addValue (int *a){ int b
= (*a) + 2; return b;
}
main()
{ int x
= 6;
cout<<addValue(&x)<<","; cout<<x;
}
```

6,8,6

Here the code is given below. You have to identify the problem in the code. while(i < 10) && (i > 24))

the test condition is always false

The correct syntax of do-while loop is_____.

do {statements;} while (condition);

Matrix is defined as_____.

Multi-dimensional array

In programming, comments are used to explain the functioning of the _____.

Program

Operating System is a type of a/an_____.

system software

From the options given, you need to choose the option which is true for the given code.

by Atiq Kundi

```
for (int i = 1; i>0; i++) {
/*loop code*/
}
```

the test condition is always true

by Attiq Kundi

Which of the following values are used in C/C++ to represent true and false?

1 and 0

'While' loop may execute _____ or more times.

zero

Body of any function is enclosed within _____.

{ }

What will be the correct syntax for initialization of a pointer ptr with string "programming"?

char *ptr = "programming";

Which one of the given option is not a mode for reading/writing the data from a file?

Get

Which of the following operators is used to access the value of variable pointed by a pointer?

*** operator**

In case of singled referencing, the value of the _____ is the address of the __.

pointer, variable

The remainder (%) operator is a _____ operator.

Arithmetic

What will be the output of following code? int x=10;

cout<<"x="<<x;

x=10

by Atiq Kundi

The purpose ofusingcout<<isto_____.

Display information on the screen

Which of the following data types will be assumed if no data type is specified with constant?

Short

All the preprocessors directive starts with_____.

#

NULL has been defined in_____header file.

stdlib.h

Which one is the correct example of a unary operator

&

In which statement there can be _____ default statement(s)

1

To access the data members of structure _____ is used

Dot operator

The statement cout << yptr will show the_____the yptr points to

Memory address

If an array has 50 elements. What is allowable range of subscript

0-49

A^=b can be written as_____

A=a^b;

If j=10 and x=++j then the value of x will be_____.

by Atiq Kundi

11

The string in the array is terminated by a_____.

Null

In C++, what will be the highest index of the following array? Int array{15}

14

Which of the following is a correct way to assign the address of the first element of array to pointer? Int data[10];

Int*ptr= data [0]

For casting, we normally declare a pointer of type_____.
We are going to use

A=aIb; can be written as_____.

aI=b;

The exclusive OR operator returns 1 if_____.

One inputs is 1 and other is zero

Sometimes after allocating memory we need additional space, for this purpose we use _____.

Reallocate function

An integer uses four bytes and the integer calculations occur in_____bytes.
4

Shifting the binary numbers is similar to shifting the_____numbers

by Atiq Kundi

Decimal

_____operator uses the sign^

Exclusive OR

When an array element is passed to a function, it is passed by_____.

reference

While programming, it is good to provide an easy to understand and easy to use interface; this programming skill is called_____.

usability

_____executes all the lines before error and stops at the line which contains the error.

Intrepreter

Which of the following is the correct syntax to access the value of first element of an array using pointer ptr?

***ptr[0]**

C is a/an_____ language.

function oriented

_____of a function is also known as sig nature of a function.

Declaration

_____Are very good tools for coder use.

functions

by Atiq Kundi

If any break statement is missed in switch statement then_____.

this may cause a logical error

A 2D array multi[5][10] can be accessed using the array nameas**multi, this technique is called_.

Double dereferencing

In C/C++, the default command line arguments passed to the main function are _.

int argc, char **argv

Are cord is a group of related_____.

Fields

The micro soft word document(.doc) is a kind of_____.

Random Access File

NULL character is used to indicate the_____of string.

End

How many dimensions does n-dimensional array has?

n dimensions

Which of the following function call is "call by reference" for the following function prototype?

func(&num);

The loop which is most suitable to be used when the number of iterations is known is called _.

for

In C/C++, the string constant is enclosed in_____.

by Atiq Kundi

double quotes " "

by Attiq Kundi

In order to get the right most digit of a number, we divide this number by 10 and take _.

Its remainder

What is the correct syntax to declare an array of size 10 of int data type?

int name[10];

How many bytes of memory are occupied by array 'str'? char str[] =

"programming";

11

Suppose that an integer type pointer contain same memory address 0x22f230. What will be the new memory address if we increment this pointer by one?

0x22f234

Which of the following if missing would result in infinite recursion incase of recursive function?

Recursive call

When ever we use a library function or a predefined object or macro, we need to use a _.

header file

Switch statement deals with_____type of data.

Both Integer and Character

Both compiler and_____are used to translate program into machine language code.
Interpreter

TWAIN stands for_____.
Technology Without An Interesting Name

by Attiq Kundi

The parameter passed to is digit() function is_____.

a character variable

C++ view search file as a sequential stream of_____.

Bytes

Structure is a collection of_____under a single name.

only variables

The default mode for writing into a file using of stream object is_____.

out

The memory address of the first element of an array is called_____.

base address

We want to access array in random order which of the following approach is better?

Pointer

The____structure is a multiple-selection construct which makes the code more efficient and easy to read and understand.

switch

Which of the following is not a reserved word in C/C++?

Sum

To access rand(), which library is required to be included in program?

stdlib.h

by Atiq Kundi

What is the highest legal index for the following array?

int arr[4]

3

Word process or is a type of a/an_____.

application software

Identify the correct option which is used for calling the function float area (int).

area(int num);

The____statement allows us to select from multiple choices
based on a set of fixed values for a given expression.

switch

C is widely known as developmentl anguage of_____operating system.

Unix

Toconvertthevalueofonetypeintoanothertypeusingbuilt-infunctions,we include header file.

stdlib.h

The keyword_____is used to get some value back from a function.

return

Thefunction seek g()takes_____parameter(s).

2

Thefunction write()takes_____as parameter(s).

String and no. of bytes to be written

When the logical operator AND (&&) combines two expressions exp1 and exp2thentheresultwillbetrueonly _____.

by Atiq Kundi

When both exp1 and exp2 are true

Syntax of a union is identical to_____.
structure

In Flow Chart, flow of control is represented by_____.
Arrow

There can be_____'default' statement(s) in any switch structure.
2

The condition in loop should be a(n)_____.
Arithmetic Expression

How many nested loops would be required to manipulate n-dimensional array?
2n

Which of the following is not an example of int data type?
-4

We should use_____for clarity and to force the order of evaluation in an expression.
parenthesis ()

Which of the following is the starting index of an array in C++?

0

The statement x+=y can be interpreted as_____.
Adding the value of the x to the value of the y and storing the result in x

by Atiq Kundi

Given a 2D array of integers, what would be the correct way of assigning the value 5 to the element at second row and third column?

m[1][2] = 5;

Array is a data structure that stores_____.

Variables

A program statement that invoke as a function is called_____.

function call

The compiler of C language is written in_____language.

C

Which function is used to locate the first occurance of a character in any string?

strlen()

To access the data members of structure,_____is used.

Dot operator

In the following nested For Loop, which loop will run most number of

times? for(int i = 0; i < 5; i++)

{

for(int k = 0; k < 5; k++)

{

. . . . .

}

}

Depends upon the statements in the inner loop's body

Structure use_____allocation.

Heap

by Atiq Kundi

_____Function give the position of the next character to be read from that file.

tellp()

What will be the size of the following character array? char name[] ="Adeel";

5

Function prototype is written,

Before call of that function

Which one of the following languages has been used to write the compiler of "C" language?

C

A hierarchy of classes which are used to deal with console and disk files are called _.

Stream classes

_____Stops execution at the line that contains error(s)I n the code.

Interpreter

C++ is a____language.

High level

How many elements are stored in the following? int matrix [4][5];

20

_____is a substitute of multiple if statement.

if. . .else if statement

by Attiq Kundi

if

int sum = 54;

Then the value of the following statement is sum = sum -3;

51

What will be the correct syntax for declaration of the following statement? "ptr is a constant pointer to an integer"

const int *myptr;

_____operator is used to pass the address of a variable in call by reference method.

&

_____data type can operate on modulus operator.

int

When ever some number is added in an array name, it will jump as many _____as the added number.

rows

Suppose that an integer type pointer contain same mory address 0x22f220. What will be the new memory address if we increment this pointer by one?

0x22f224

_____Is the pointer which determines the position in a file from where the next read operation occurs.

put

what is the correct syntax to declare an array of 15 elements of type float?

by Atiq Kundi

float array [14]

suppose we have a file with name “mylife.txt”. what will be the correct Syntax of file opening for input?

my file (—myfile.txt‖. ios::in)

Which of the following will be the most appropriated at a type to store the value 63.5 47?

float

-------will explain the function of a program

Comments

These functions Seek g()and seek p() requires an argument of type------

-- to let them how many bites to move forward or backward Int

All elements of an array must be of---------- data type

Same

what will be the result of arithmetic expression 6 + 48 / 4 * 3?

42

----------allow us to have a memory location and use it as intor char interchangeably

none of the given

accessing a structure member the identifier to the left of the dot operator is the name of----------

structural variable

by Attiq Kundi

<and> both are ---------- operators

Arithmetic

what will be the output of the following code segment? For (int = 2; i<10; i++){

If (i = = 5)

Continue;

cout<<i<<".";

}

2,3,4,5,6,7,8,9

---------- returns true if she is a digit or a letter and false otherwise

Int isalnum (int c)

If a --- find an error, it stop translating without generating any E executable code

Compiler

the ASCII code of null character is----------

000

If X=9; then the expression sx%=2; will calculate the value of x as------

- 1

the original value means unchanged in --------

Call by Value

by Atiq Kundi

which of the following is used to create an output stream?

Ofstream

Structures are syntactically defined with the word _____.

Struct

Which of the following is the default mode of the file opening while using the ofstream class?

ios::in

how many times the following loop will execute? Int j = 3;

```
While (j >0)
{
Cout<<"statements"<<endl;
J - = 2;
}
```

2

Use of word processor for writing the code of a program is not good because --------

It has less feature for writing code of a program

how many bytes and integer type pointer intptr will jump in memory if the statement below is executed?

Int ptr

+=2;

8

Avoid loop may execute---------- or more Times

0

raid stands for------

redundant array of inexpensive dices

by Atiq Kundi

in a file is opened with iOS:: out mode, then----------

a new file is created

by Attiq Kundi

first step in design in gaprogram is **Analysis**

what will be the result of the expression J = i++

If initially j=0andi=5? 5

suppose we have int y [10];

to access the 4th element of the array be write-------

Y [3];

A ----------structure specify that an action is to be repeated while

some condition remains true Control

the most suitable data type for number 325.25 is------

float

Which one of the following should be placed immediately either before or after the noun?

Modifiers of Nouns

Titles typically include both……

a number and a description

For what purposes colons are used?

All of the above

The name of the array is a constant pointer which contains the memory address of the of the array.

first element

by Attiq Kundi

What will be the correct syntax for the following function call?

float add (int &); add(x);

In C/C++; by default arguments are passed by_____to afunction.

Value

<,<=,>,>=are called_____operators.

Relational

char name [ ] = “Hello World” ; In the above statement, a memory of _____characters will be allocated

12

While developing a program; should we think about the reusability?

Yes

C is widely known as development language of_____operating system.

Unix

Which of the following function call is “call by reference” for the following function prototype?

int add (int *); add(&x);

If a function has not been declared before its definition,

It is a None of these

While loop executes at least----

by Attiq Kundi

Zero time

A_____is a precise sequence of steps to solve a particular **problem. Program**

In while loop the loop counter must be initialized,
Before entering the loop

int couter = 0 ; while(counter < 15) cout<<counter<<" "; counter++;

Infinite loop

Why we use "cin"?
To read data from keyboard

Loopsare_____Structure
Repetition

Topic 13 to 18
By
Attiq Kundi

In an n-dimensional array , we use__for loop(s) to populate the

array n

In 3 dimensional array, we use_____for loop(s) to populate the array

3

In 2 dimensional array, we use_for loop(s) to populate the array

2

In 1 dimensional array, we use_____for loop(s) to populate the array

1

A group is a record of related_____

Fields

by Attiq Kundi

__contains functions for manipulations of

character data ctype.h

Ifstream inFile refers _____

Object for reading from a file

ofstream outFile refers _____

object for writing to a file

A character is stored in the memory in _____

Byte

A string which is assigned to a string variable is terminated by

Null character

When an identifier is declared with keyword const

then, Its value cannot be changed

If stream is used for_____

Input file stream

Which of the following option is correct about array

Only one type of elements can be stored in an array

Suppose that an integer type pointer contains a memory address 0x221220. What will be the new memory address if we increment this pointer by one

0x221224

In the case of pointer to pointer or_____the first pointer contains the address of the second pointer, which contains the address of the variable, which contains the desired value

Double dereference

The data in the memory is _____

Volatile

Suppose we have a file with name myfile.text What will be the correct syntax of file opening for input

myFile,open(“myfile.text”, ios::in);

by Atiq Kundi

In analysis, we try to have a _____

Precise problem statement

__Returns true if c is a digit or a letter and false

otherwise int isalnum (int c)

_____Returns true if c is a digit and false
otherwise int isdigit(int c)

_____Returns true if c is a letter and false
otherwise Int isalpha(int c)

__Returns true if c is a hexadecimal digit character and false otherwise

Int isxdigit(int c)

_____Returns true if c is a lowercase letter and false

otherwise Int islower(int c)

__Returns true if c is a uppercase letter and false otherwise

Int isupper(int c)

__if c is an uppercase letter, tolower returns c as a lowercase letter. Otherwise, tolower returns the argument unchanged

Int tolower (int c)

__if c is an lowercase letter, toupper returns c as a uppercase letter. Otherwise, toupper returns the argument unchanged

Int toupper(int c)

Returns true if c is a white-space character newline (‘\n’), space (‘’), from feed (‘\f’),

by Atiq Kundi

carriage return (‘\r’), horizontal tab (‘\t\), or vertical tab (‘\v’) and false otherwise

Int isspace(int c)

__returns true if c is a control character and false

otherwise Int iscntrl(int c)

_____Returns true if c is a printing character other than a space, a digit, or a letter and false otherwise

Int ispunct (int c)

Return true value if c is a printing character including space (‘’) and false otherwise

Int isprint (int c)

Returns true if c is a printing character other than space(‘’) and false

otherwise Int isgraph(int c)

The function tolower and toupper are _____

Conversion function

Which header file must be included to use the function tolower() and toupper()

Ctype.h

Which mode of file is used to open a file or stream for

insertion Out

by Attiq Kundi

Which mode of file is used to open a file or stream for extraction

In

Append rather than truncate an existing file. Each insertion will be written to the end of the file

App

Discards the file's contents if it

exists. Trunk

Opens the file without truncating, but allows data to be written anywhere

in the file Ate

Treat the file as binary rather than text. A binary file has data stored in internal formats, rather than readable text format

Binary

Following is the declaration of a_____array. Int

arr[2][2] 2 dimensional

__are conventional names of the command line parameters of the 'main()' function.

'argc' and 'argv'

What will be the correct syntax for declaration of the following statement

'ptr is a constant pointer to an integer

Int*const ptr;

What will be the correct syntax for declaration of the following statement

'ptr is a pointer to const in'

by Atiq Kundi

const int *ptr.

Transpose of a matrix means that when we interchange rows and columns_____

The first row becomes the first columns

Char dest[50] = using strncat function";

Char src[50] = this part is added and this is ignored;
Strncat(dest, src, 19);
Cout <<dest;

Using strncat function , this part is added

Base address is the memory address of_____element of an array.

1st

While handling files, one can have_____options

Read the file, write in some file, read and write in the some file…all

String are accessed by variable of type

Char

For the following statement, how much memory will be allocated to my array[0]
Char*myarray[] = {"arif","sadia"}

5 bytes

by Atiq Kundi

To get the value stored of a memory address we use the _____

Deferencing operator

Data means _____

The value of whatever the data points to

If a file is opened ios::out, then _____

A new file is created

If we want to append into the file, the mode will be_____

ios::app

If we want to write anywhere in the file, the mode is_____

ios::app

Following is the declaration of a 2D array, how many row are declared for this array int arr[3][2]

3

Following is the declaration of a 2D array, how many columns are declared for this array int arr[3][2]

2

In case of two dimensional array, if you add some number in a two-dimensional array name, it will jump to the next_____.

Rows

Which of the following is true about streams? It is a sequence of bytes

by Attiq Kundi

It is an ordered sequence
All bytes can go through the stream simultaneously Bytes
that enters first into the stream will go out at last

A and B

Which of the following is a correct way to assign the address of the first element of array is pointer? Int data[10]

Int*ptr=data[0];

A_is an array of characters that can store number of character

specified String

A string which is assigned to a string variable is terminated by_____.

Null character

How many bytes an integer type pointer int ptr will jump in memory if the statement below is executed? Int ptr +=2

8

Give a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth columns

Array[2][3]=6;

Following is an array of_____rows and_____, int

num[3][4]; 3 and 4

What will be the output of the following code segment?
Char myName[]=”student ID”;
Int n=sizeof(myName);
Cout<<n;

11

If we have a pointer on the left hand side then the right hand side should have

by Atiq Kundi

a/an_____

Address

The parameter passed to isdigit() function is_____variable

Character or integer

Ofstream is used for_____

Output file stream

A hierarchy of classes which are used to deal with console and disk files are called_____

Stream classes

'\0' takes _ space in the memory.

1 byte… not sure

Which statement is used to close a file

Myfile.close()

Which statement is used to open a file

My file.open()

We must include the header file_____to convert the value of one type into another type using built-in-function.

by Atiq Kundi

String.h

Pointer points to a particular_____.

Memory address

Ifstream is used for_____

Input file stream

Ofstream is used for

Output file stream

To get the value stored at a memory address, we use the_____.
Deferencing operator

To read command-line arguments, the main() function itself must be given _____ arguments.

2

When an identifier is declared with keyword const then,

Its value cannot be changed

Constructor is itself_____of C++ and _____

Function, can be overloaded

In analysis, we try to have a _____

Precise problem statement

In c++ a variable can be declare anywhere in the program this will

increase Readability

by Atiq Kundi

The name of the array is a constant pointer which contains the memory address of the_____of the array"

First element

What is output of following code?

```
Int data[10]=[10,20,30,40,50,60,70,80,90,100];
Int     xptr=&data[4];
Int*yptr=&data[6];
Cout<<xptr+xptr++
```

120

C++ offers_____levels of data access control inside a class

Three

The function calloc takes two arguments, first argument is the _ and the second argument is the _____

Required space in terms of numbers, size of space

The statement cout<<yptr will show_____the yptr points to

Memory address

The use of *sign in first and second statements is called_____and_____of pointer.

```
Int * ptr = &x
    Cout<<*ptr
```

Referencing dereferencing

What will be the output of following program?

```
Int data[10]=[10,20,30,40,50,60,70,80,90,100];
Int*yptr=&data[5];
    Cout<<++yptr
```

61

by Atiq Kundi

Character string are terminated by _____

‘\0’

There is a pointer variable named ptr of type float. Which type of variable address can be stored by ptr.

int

char **argv can be read as

array of pointers to char

eof is used to check for the_____of file when a file is being

read end

suppose we have int y[10]; To access the 4th element of the array we write_____

y[4];
y[3];
y[2];
none of given

From the following; which one is the range of Random number generator function rand()?

0 – 32768
1 – 32768
0 – 32767
1 – 32767

From following; which one is the correct syntax of an array initialize: Array size is 10 and it is of double data type to value 0?

arr[10] = {0.0};
double arr[10]= 0.0;

by Atiq Kundi

double arr[10] = {0.0};
double arr[] = 0.0;

The string in the array is terminated by a_____

zero
nil
null
one

In C/C++; by default arguments are passed by_____to a function.

Reference
Value
Type Data

char name [] = "Hello World" ; In the above statement, a memory of __characters will be allocated

12

_____Keyword is used to return some value from a function.

break
return

Which of the function call is call by value for the following function prototype? float add(int);

add(x);

The increment of a pointer depends on its_ _____.

data type

by Atiq Kundi

The ASCHI code of null character is_____

000

Pointers are a special type of_____in which a memory address is stored

variables

Transpose of a matrix means that when we interchange rows

and columns_____

the first row becomes the Last column
the first row becomes the first column

Pointers store the _____

value of a variable

Which of the following function call is "call by reference" for the following function prototype? int add (int *);

add(&x);

The name of the array is a constant pointer which contains the memory address of the_of the array.

first element

by Atiq Kundi

array name always contains the memory address of the_____of the array

first element

Which function is used to delete the allocated memory space? Free

Symbolic constant PI can be defined

as #define PI3, 14

Windows operating system may itself takes memory from_____.

Heap

All the preprocessors directive starts with_____.#

Which one of the following is used to perform bit-wise OR operator

I

Constructor is itself a_____of C++ and_____.

Function, can be overloaded

RAID stands for_____.

Redundant array of inexpensive devices

Object code is machine code but it is not_____and_____.

Reloadable, executable

by Atiq Kundi

At the_____, we try to break up the problem into functional units analysis phase

design phase

For binary member operators, operands on the _____ drives (calls) the operation.

Left

We cannot increment_____.

references

We can_____pointer.

all of the given

We can_____references.

None of the given

by Atiq Kundi

What will be the correct syntax for the following function call?

float add (int &);

add(x);

An instance of a class is called_____.

object

The_____is called automatically when an object destroys

destructor

The destructor is used to_____.

1. deallocate memory

___data isn't accessible by non-member functions or outside classes.

private

Member functions of the class_____main program.

are accessible from

Overloading means :

Using the same name to perform multiple tasks or different tasks depending on the situation.

by Atiq Kundi

The main advantage of function overloading is _____.

The program becomes more readable

You cannot overload the_____operator.

1. ? :

In C++, a variable can be declared anywhere in the program this will increase_____.

efficiency

Memory allocated from heap or free store_____.

cannot be returned back unless freed explicitly using free and delete operators

We cannot use_____pointer for storing and reading data from it.

'NULL

The dynamic memory allocation uses_____whereas static memory allocation uses_____.

heap , stack

What will be the output of the given code?

```
#include #define MAX( A, B ) ((A) > (B) ? (A) : (B)) void main() {
int i, x, y; x =
23;
y = 45;
```

by Atiq Kundi

```
i = MAX( x++, y++ );
// Side-effect: // larger value incremented twice cout<< "x = " << x << " y = "
<< y << '\n';
}
```

x=24 y=47

NULL has been defined in_____header file.

Stdlib.h

Symbolic constant PI can be defined as:

#define PI 3.14

The friend function of a class can have access _____.

to the private data members

C++ was developed by_____.

2. BejarneStroustrup

Once the_____are created, they exist for the life time of the program.

3. static variables

Encapsulation means_____.

4. that the data of a class can be accessed from outside

An address is a_____, while a pointer is a _____.

5. variable, constant

by Atiq Kundi

The syntax of declaration of a function that returns the reference to an integer is_____.

int &myfunc();

Which one of the following is mandatory preprocessor directive for c++?

#include

The members of a class declared with the keyword struct are___by default.

public

getche() is a_____function and defined in _____header file.

built-in function ,conio.h

_____operators are the ones that require two operands on both sides of the operator.

Binary

_____will return the number of bytes reserved for a variable or data type.

sizeof operator

_____are not available in C language.

Library functions

by Atiq Kundi

The members of a class declared without any keyword are_____by default.

private

For console input and output we use_____.

conio.h header file

The name of the destructor is the same as that of a class proceeding with a__.

~ sign

A reference cannot be NULL it has to point a data type.

True

A pointer is_____.

a variable for storing address

Constructor is a special function, called whenever we _____.

instantiate an object of a class

Symbolic constant PI can be defined as:

#define PI 3.14

Object code is machine code but it is not_____and _____.

relocatable, executable

The default visibility for the data members of the class is

private

The__is called automatically when an object destroys.

destructor

Constructor is special type of function :

which has no return type

_____variables are those that are defined outside of main.

Global

by Atiq Kundi

Within the statement obj1=obj2; obj1 will call the assignment operator function and obj2 will be passed as an argument to function.

True

by Attiq Kundi

When the compiler overload the assignment (=) operator by default then

Compiler does member wise assignment.

It is possible to return an object from function using this pointer.

True

Overloaded assignment operator must be

Member function of class

Let suppose int a, b, c,
d, e;

a = b = c = d = e = 42;
This can be interpreted by the compiler as

2. a = (b = (c = (d = (e = 42))));

In statement a+b+c, at first

b+c is executed first

Suppose int i = 10; then what is the output of cout<<oct<<i;

12
13

ostream is a_____operator.

None of the given

_____must be included to use stream manipulation in your code.

iomanip

_____operators are the ones that require only one operator to work.

Unary

The endl and flush are_____.

Manipulators

When operator function is implemented as member function then return

by Atiq Kundi

type of function_____.

When a variable is defined as static in a class then _____.

Only one copy is created for all objects of this class

Automatic variables are created on_____.

Stack

```
cout<<i<< " "; cout<< d <<" ";
    cout<< f;
```

Above statements can be written within statement of one line as:

cout<<i<<" "<< d <<" "<< f;

dec, hex, oct are all_____.

Non-parameterized manipulators

What will be the output of following statement?
cout<<setfill('0')<<setw(7)<< 128;

2. 0000128

Which of the following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

delete []string;

If we have a program that writes the output data(numbers) to the disc, and if we collect the output data and write it on the disc in one write operation instead of writing the numbers one by one.

In the above situation the area where we will gather the number is called

Buffer

by Atiq Kundi

The first parameter of operator function for << operator _____.

Must be passed by reference

The second parameter of operator function for >> operator must always be passed

By reference

The only operator that the compiler overloads for user define data type by default is

Assignment (=) operator

Consider the following code, the printed value will be converted into:

```
int n=10; cout<<oct<<n;
```

Base 8

_____variables are defined in the main.

Local

ostream class is_____and not under our control.

built-in

The memory allocation in C++ is carried out with the help of___.

new operator

If B is designated as friend of A, B can access A's non- public members.

A can access non-public members of B

If the request of new operator is not fulfilled due to insufficient memory in the heap_____.

the operator returns 0

by Attiq Kundi

We should not use such variable names that are starting with___because in C++, there are lots of internal constants and symbolic names that start with it.

double underscore

The friend keyword provides access_____.

in one direction only

The malloc function takes_____argument(s).

one

The constructor contains_____.

no return type

What will be the output of the following c++ code? #include<iostream.h>

```
#define max 100 main()
{
#ifdef max
Cout<<"Hellow;
}
```

Error

Once we have defined a symbolic constant value using #define, that value_ _____during program execution

cannot be changed

The memory allocation functions return a chunk of memory with a pointer of type_____.

ptr

A class can be declared as a_____of other class.

member

To avoid dangling reference, don't return_____.

the reference of a local variable from the function

Constructor is itself a_____of C++ and_____.

by Atiq Kundi

function, can be overloaded

The parameter passed to isdigit() function is _____ variable.

Integer

char **argv can be read as_____.

pointer to pointer to char

To read command-line arguments, the main() function itself must be given _____arguments.

2

How many bytes an integer type pointer intPtr will jump in memory if the statement below is executed?

intPtr += 2 ;

8

The increment of a pointer depends on its_____.

data type

The statement cout<<yptr will show the _____ theyptr points to.

memory address

_____is used as a dereferencing operator.

*

Transpose of a matrix means that when we interchange rows and columns___.

the first row becomes the first column

Individual characters in a string stored in an array can be accessed directly using array_____.

subscript

We can define a matrix as_____array.

Multi dimensional

A_____is an array of characters that can store number of character specified.

String

by Atiq Kundi

Given a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?

. array[2][3] = 6 ;

_____of a variable means the locations within a program from where it can be accessed.

Visibility

Which of the following function call is "call by reference" for the following function prototype? int add (int *);

add(&x);

Which of the following function call is "call by reference" for the following function prototype? float add (float *);

add(&x);

Which of the function call is call by value for the following function prototype?

float add(float);

add(x);

Which of the function call is "call by value" for the following function prototype?

float add(int);

add(x);

Return type of a function that does not return any value must be_.

void

_____will be used for enclosing function statements into a block.

{}

What is the output of the following code if the 2nd case is true

```
switch (var) {
case 'a': cout<<"apple"<<endl; case
'b':cout<<"banana"<<endl; case
'm':cout<<"mango"<<endl; default: cout<<"any
fruit"<<endl;
}
```

banana
mango any

by Attiq Kundi

fruit

When the break statement is encountered in a loop's body, it transfers the control_from the current loop.

Outside

What is the output of the following code if the 3rd case is true

```
switch (var) {
case 'a':cout<<"apple"<<endl; case
'b':cout<<"banana"<<endl; case
'm':cout<<"mango"<<endl; default: cout<<"any
fruit"<<endl;
}
```

mango
any fruit

What is the output of the following code, if the first case is true

```
switch (var) {
case 'a':cout<<"apple"<<endl; case
'b':cout<<"banana"<<endl; case
'm':cout<<"mango"<<endl; default: cout<<"any
fruit"<<endl;
}
```

apple
banana
mango
any fruit

What will be the output of following code segment?

```
for (int i = 2; i<10; i++) { if ( i == 5)
continue; cout<<i<< "," ;
}
```

2,3,4,6,7,8,9

_statement is used to terminate the processing of a particular case and exit from switch structure.

break

What will be the result of the expression j = i++; if initially j = 0 and i = 5?

5

by Attiq Kundi

What will be the result of the expression k = ++m; if initially k = 0 and m = 4?

5

What will be the result of the expression k = ++m; if initially k = 0 and m = 5?

6

How many times the following do-while loop will execute?

int k = 10; do { cout<< "Statements" <<endl; k -= 2; } while(k>0);

6

7

Which of the following loops checks the test condition at the end of the loop?

by Attiq Kundi

Do-While

The operators ++ and -- are used to increment or decrement the value of a variable by_____.

1

How many times the following loop will execute?

```
int j = 3; while(j > 0) { cout<< "Statements" <<endl; j -= 2; }
```

3. 2

A__structure specifies that an action is to be repeated while some condition remains true.

Control

!(x> 3) means in C++ that

x is less than or equal to 3

When the logical operator && combines two expressions then the result will be true only when the both expressions are_.

true

< and > both are_____operators.

Relational

What will be the value of variable "input" if the initial

value of input is 67?

```
if(input >= 50) input = input
+ 1; if(input <= 75) input =
input + 2; else
input = input - 1;
```

3. 70

!(x< 3) means in C++ that

x is greater than or equal to 3

!= operator is used to check whether the operand on the left-hand-side is_____to the operand on the right- hand-side.

Not equal

by Atiq Kundi

When the if statement consists more than one statement then enclosing these statement in curly braces is,

Must

The most suitable data type for number 325.25 is _____.

float

What will be the result of arithmetic expression 6+48/4*3?

42

Which of the following will be the most appropriate data type to store the value 63.547?

Float

In the given expression which operator will be evaluated first? 10 + (6 / 2) - 2 * 3?

3. /

What will be the value of the variable output in the given piece of code?

```
double output = 0;
output = (2 + 2) * 4 + 2 / (4 - 2);
```

17

It is the job of_____to transfer the executable code from hard disk to main memory.

1. interpreter
2. Debugger
3. Linker
4. Loader

In computer systems there are mainly_____type of softwares.

2

_____will explain the function of a program.

Comments

if (a>b && a>c) then the condition will be true only if

Both a>b and a>c are true

by Atiq Kundi

A variable of character data type occupies _____ byte(s) in memory.

1

We must include the header file_____to convert the value of one type into another type using built-in functions.

string.h

A function is a block of statements that can be defined once and used___in the program.

As many times as user wants

Select the correct way to assign the address of first element of array to pointer?

int *ptr = &data;

Consider the following code segment. What will be the output of following code?

```
int addValue (int *a){ int b = (*a)
+ 2; return b;
}
main() { int x
= 6;
cout<<addValue(&x)<<","; cout<<x;
}
```

6,8,6

Here the code is given below. You have to identify the problem in the code.

```
while(i< 10) && (i> 24))
```

the test condition is always false

The correct syntax of do-while loop is_____.

do {statements;} while (condition);

Matrix is defined as_____.

Multi-dimensional array

In programming, comments are used to explain the functioning of the_.

Program

by Atiq Kundi

by Attiq Kundi

Operating System is a type of a/an_____.

system software

From the options given, you need to choose the option which is true for the given code.

```
for (int i = 1; i>0; i++) {
/*loop code*/
}
```

the test condition is always true

Which of the following values are used in C/C++ to represent true and false?

1 and 0

'While' loop may execute_____or more times.

zero

Body of any function is enclosed within_____.

1. { }

What will be the correct syntax for initialization of a pointer ptr with string "programming"?

char *ptr = "programming";

Which one of the given option is not a mode for reading/writing the data from a file?

4. get

Which of the following operators is used to access the value of variable pointed by a pointer?

* operator

In case of single dereferencing, the value of the _____is the address of the_____.

pointer, variable

The remainder (%) operator is a_____operator.

Arithmetic

byAtiq Kundi

CS201

Mid-Term

Quiz by Attiq Kundi

SUBSCRIBE "Knowledge For Us" ON YOU TUBE

100 % CORRECT MCSQ

AND Many MoRe

CS 201

What will be the output of following code? int x = 10;

```
cout<<"x="<<x;
```

x=10

The purpose of using cout<< is to_____.

Display information on the screen

Which of the following data types will be assumed if no data type is specified with constant?

short

When an array element is passed to a function, it is passed by___.

reference

While programming, it is good to provide an easy to understand and easy to use interface; this programming skill is called_____.

usability

_____executes all the lines before error and stops at the line which contains the error.

Intrepreter

Which of the following is the correct syntax to access the value of first element of an array using pointer ptr?

by Attiq Kundi

*ptr[0]

C is a/an_____language.

function oriented

_____of a function is also known as signature of a function.

Declaration

_____are very good tools for code reuse.

functions

If any break statement is missed in switch statement then_.

this may cause a logical error

A 2D array multi[5][10] can be accessed using the array name as **multi, this technique is called_____.

Double dereferencing

In C/C++, the default command line arguments passed to the main function are_ _____.

int argc, char **argv

A record is a group of related_____.

Fields

The microsoft word document (.doc) is a kind of _____.

Random AccessFile

NULL character is used to indicate the_____of string.

End

How many dimensions does n-dimensional array has?

n dimensions

Which of the following function call is "call by reference" for the following function prototype?

func(&num);

The loop which is most suitable to be used when the number of iterations is known is called_____.

for

In C/C++, the string constant is enclosed in_____.

by Atiq Kundi

double quotes " "

In order to get the right most digit of a number, we divide this number by 10 and take_____.

Its remainder

What is the correct syntax to declare an array of size 10 of int data type?

int name[10];

How many bytes of memory are occupied by array 'str'? char str[] = "

11

Suppose that an integer type pointer contains a memory address 0x22f230. What will be the new memory address if we increment this pointer by one?

0x22f234

Which of the following if missing would result in infinite recursion in case of recursive function?

Recursive call

Whenever we use a library function or a predefined object or macro, we need to use a_____.

header file

Switch statement deals with_____type of data.

Both Integer and Character

Both compiler and_____are used to translate program into machine language code.

interpreter

TWAIN stands for_____.

Technology Without An Interesting Name

The parameter passed to isdigit() function is_____.

a character variable

C++ views each file as a sequential stream of _____.

Bytes

Structure is a collection of_____under a single name.

by Atiq Kundi

only variables

The default mode for writing into a file using ofstream object is_.

out

The memory address of the first element of an array is called___.

base address

We want to access array in random order which of the following approach is better?

Pointer

The___structure is a multiple-selection construct which makes the code more efficient and easy to read and understand.

switch

Which of the following is not a reserved word in C/C++?

sum

To access rand(), which library is required to be included in program?

stdlib.h

What is the highest legal index for the following array? int arr[4]

4

Word processor is a type of a/an_____.

application software

Identify the correct option which is used for calling the function float area (int).

area(int num);

The_statement allows us to select from multiple choices based on a set of fixed values for a given expression.

switch

C is widely known as development language of _____operating system.

Unix

To convert the value of one type into another type using built-in functions, we include_____header file.

by Atiq Kundi

stdlib.h

The keyword_____is used to get some value back from a function.

return

The function seekg() takes_____parameter(s).

2

The function write() takes_____as parameter(s).

String and no. of bytes to be written

When the logical operator AND (&&) combines two expressions exp1 and exp2 then the result will be true only _____.

When both exp1 and exp2 are true

Syntax of a union is identical to_____.

structure

Which one of the symbol is used to represent a decision in a flow chart?

Rectangle

In Flow Chart, flow of control is represented by _____.

4. Arrow

There can be_____'default' statement(s) in any switch structure.

2

The condition in loop should be a(n)_____.

Arithmetic Expression

How many nested loops would be required to manipulate n-dimensional array?

2n

Which of the following is not an example of int data type?

-4

We should use_____for clarity and to force the order of evaluation in an expression.

by Atiq Kundi

parenthesis ()

Which of the following is the starting index of an array in C++?

0

The statement x += y can be interpreted as_____.

Adding the value of the x to the value of the y and storing the result in x

Given a 2D array of integers, what would be the correct way of assigning the value 5 to the element at second row and third column?

m[1][2] = 5;

Array is a data structure that stores_____.

Variables

A program statement that invokes a function is called _____.

function call

If a function has been declared but not defined before its function call then it is termed as_____.

by Attiq Kundi

run time error

The compiler of C language is written in _____ language.

C

Which one of the below functions is not included in ctype.h header file?

getdigit(int c)

Which function is used to locate the first occurance of a character in any string?

strlen()

To access the data members of structure,_____is used.

Dot operator

In the following nested For Loop, which loop will run most number of times?

```
for( inti = 0; i< 5; i++)
{

for(int k = 0; k < 5; k++)
{
. . . . .
}
}
```

Depends upon the statements in the inner loop's body

Structure use_____allocation.

___function give the position of the next character to be read from that file.

tellp()

What will be the size of the following character array? char name[] = "Adeel";

5

Function prototype is written,

Before call of that function

by Attiq Kundi

Which one of the following languages has been used to write the compiler of "C" language?

C

A hierarchy of classes which are used to deal with console and disk files are called_____.

Stream classes

____stops execution at the line that contains error(s) in the code.

Interpreter

C++ is a_____language.

High level

How many elements are stored in the following? int matrix [4][5];

20

____is a substitute of multiple if statement.

if. . .elseif statement

if

int sum = 54;
Then the value of the following statement is sum = sum - 3;

3. 51

What will be the correct syntax for declaration of the following statement?

"ptr is a constant pointer to an integer"

const int *myptr;

____operator is used to pass the address of a variable in call by reference method.

&

____data type can operate on modulus operator.

int

Whenever some number is added in an array name, it will jump as many_as the added number.

rows

by Atiq Kundi

Suppose that an integer type pointer contains a memory address 0x22f220. What will be the new memory address if we increment this pointer by one?

0x22f224

____is the pointer which determines the position in a file from where the next read operation occurs.

put

Destructor _____

Takes no arguments and Can be overloaded

The default visibility for the data members of the class is_____.

Private

Which of the following permits function overloading in C++ Both

type and arguments

Once we have defined a symbolic constant value using #define, that value_____during program execution.

Cannot be changed

Encapsulation means _____.

That the data of a class cannot be accessed from outside

The original value remains unchanged in _____

Call by value

Programmer should be very careful about the memory management because it can _____.

cause problems of memory leakage and dangling pointers

The destructor is used to_____.

deallocate memory

by Attiq Kundi

The main advantage of macros is that_____and program runs faster

macros are more efficient

Constructor is special type of function :

which has no return type

Unix operating system was written in C language

C

When accessing a structure member, the identifier to the left of the dot operator is the name of_____.

Structure variable

Constructor has_____.

the same name as of class

For console input and output we use_____.

conio headerfile

We should not use such variable names that are starting with _____ because in C++, there are lots of internal constants and symbolic names that start with it.

upper case alphabets

CS201

Mid-Term

Quiz by Attiq Kundi

SUBSCRIBE " Knowledge For Us " ON YOU TUBE

100 % CORRECT MCSQ

AND Many MoRe

by Attiq Kundi

CS 201

by Attiq Kundi