Professional Online Academy Vu Topper RM

CS201-Introduction To Programming

Update MCQ'S Quiz-3 File

Follow Us on YouTube:
@vutopperrm

For More Help Contact What's app Me!!!
Number's = # 0322-4021365, 0316-4980094

Rizwan Manzoor
Vu Topper RM



بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

The original value remains unchanged in _____.

A. Call by value
B. Call by reference
C. Dynamic Variables
D. Pointers

malloc function returns _____to the _____ from the available memory.

A. void pointer , starting of the chunk of memory allocated from the heap
B. integer pointer, middle of the chunk of memory allocated from the heap
C. void pointer, starting of the chunk of memory allocated from the array
D. NULL pointer, end of the chunk of memory allocated from the stack

Which of the following permits function overloading in C++.

A. Both type and arguments
B. Type only
C. Number of arguments only
D. Number of function names

_____ is a special type of pointer we have to cast it before we use it.

A. float
B. integer
C. void
D. double

Sometimes after allocating memory we need additional space, for this purpose we use _____.

A. reallocation function

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

B. realloc function
C. void pointer
D. calloc function

Question No:1 **(Marks:1)** **Vu-Topper RM**
RAID stands for_____.
Redundant Array of Inexpensive Devices **Page 250**

Question No:2 **(Marks:1)** **Vu-Topper RM**
Which of the following is an example of static memory allocation?
Array

Question No:3 **(Marks:1)** **Vu-Topper RM**
Local variables are stored in an area called _____.
Stack

Question No:4 **(Marks:1)** **Vu-Topper RM**
How many destructors are allowed in a Class?
One

Question No:5 **(Marks:1)** **Vu-Topper RM**
Which one of the following is not a possible state for a pointer?
Point to a type

Question No:6 **(Marks:1)** **Vu-Topper RM**
i+=2 is equivalent to _____.
i=i+2;

Question No:7 **(Marks:1)** **Vu-Topper RM**
To get the memory address of a variable we use ____ .
&

Question No:8 **(Marks:1)** **Vu-Topper RM**

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

_____ operators are the ones that require two operands on both sides of the operator.

Binay

Question No:9 **(Marks:1)** **Vu-Topper RM**

Which of the following is the default mode of the file opening while using the ofstream class?

ios::out

Question No:10 **(Marks:1)** **Vu-Topper RM**

Which of the following is the correct definition of streams?

It is an ordered sequence of bytes

Question No:11 **(Marks:1)** **Vu-Topper RM**

endl is a parameter-less _____ manipulator that inserts the new line besides flushing the buffer.

built-in

Question No:12 **(Marks:1)** **Vu-Topper RM**

Stream operators are heavily overloaded means , they allow to handle int and character data type only.

True

False

Question No:13 **(Marks:1)** **Vu-Topper RM**

In the member initializer list, the data members are initialized,

A. In the order in which they are defined within class
B. None of the given options
C. From right to left
D. From left to right

Question No:14 **(Marks:1)** **Vu-Topper RM**

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

What is the use of function call operator?

A. overloading the parameters
B. overloading the string
C. overloading the methods
D. overloading the objects

Question No:15 (Marks:1) Vu-Topper RM

If text is a pointer of type String then what will be the functionality of following statement? text = new String [5];

A. Creates array of pointers to string
B. Creates array of 5 objects dynamically
C. Creates a string Object
D. Creates array of 5 objects statically

Question No:16 (Marks:1) Vu-Topper RM

Which of the following concept is NOT associated with stream?

A. Source
B. Template
C. Destination
D. State

Question No:17 (Marks:1) Vu-Topper RM

What will happen when the function call operator is overloaded?

A. It will modify the operator to be interpreted
B. It will modify the object
C. It will modify the functions
D. It will not modify the functions

Question No:18 (Marks:1) Vu-Topper RM

What will be the output of following statement?cout << setfill('0') << setw(7) << 128 ;

A. 0128128
B. 0000128

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

C. 0012800
D. 1280000

Question No:19 **(Marks:1)** **Vu-Topper RM**

The life time of the static data member of a class is the life time of the _____.

A. function
B. program
C. destructor
D. constructor

Question No:20 **(Marks:1)** **Vu-Topper RM**

Identify the correct method of adding two strings, s1 and s2.

A. s1+s2
B. s1, s2+
C. s1+s2 and strcat(s1,s2)
D. strcat(s1, s2);

Question No:21 **(Marks:1)** **Vu-Topper RM**

We can delete an array of objects without specifying [] brackets if a class is not doing dynamic memory allocation internally.

True
False

Question No:22 **(Marks:1)** **Vu-Topper RM**

Class is a user defined_____.

A. memory reference
B. none of the given options.
C. value
D. data type

Question No:23 **(Marks:1)** **Vu-Topper RM**

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Header files provide _____ so the program running on one operating system can run without an error on the other system.

A. Accuracy
B. Reliability
C. Portability
D. Accessibility

Question No:24 (Marks:1) Vu-Topper RM

The malloc function takes _____ argument(s).

A. One Page 282 ok
B. Two
C. Four
D. Three

Question No:25 (Marks:1) Vu-Topper RM

_____ is used for input file or for reading from the file.

A. tellp()
B. tellg()
C. seekg() Page 220
D. seekp()

Question No:26 (Marks:1) Vu-Topper RM

To avoid dangling reference, don't return _____.

A. the reference of a static variable from the function
B. the reference of a global variable from the function
C. the reference of a local variable from the function Page 369
D. the reference of a private data member from the function

Question No:27 (Marks:1) Vu-Topper RM

Which is the correct syntax to define a structure named 'student'?

A. structure student{//variables};

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

B. struct student{//variables};
C. struct student(//variables);
D. structure student(//variables);

Question No:28 **(Marks:1)** **Vu-Topper RM**
For converting a void type pointer ptr into integer type, the correct syntax is:
A. *int ptr
B. ptr * int
C. int * ptr
D. (int *) ptr **ok**

Question No:29 **(Marks:1)** **Vu-Topper RM**
To access the data members of structure, _____ is used.
A. Dot operator **Page 231**
B. Logical operator
C. Address operator
D. Dereference operator

Question No:30 **(Marks:1)** **Vu-Topper RM**
_____ for parameters is also done for inline functions.
A. Testing
B. Value checking
C. Syntax checking
D. Automatic type checking **Page 299**

Question No:31 **(Marks:1)** **Vu-Topper RM**
What is the other name for a variable?
A. Identifier
B. Visual
C. Static
D. Constant

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:32 **(Marks:1)** **Vu-Topper RM**

With the use of dynamic allocation of memory, the system resources can be _____.

A. used carelessly
B. used efficiently
C. wasted
D. all of the given options

Question No:33 **(Marks:1)** **Vu-Topper RM**

The object code of our program is combined with the _____.

A. source program
B. with header files
C. object code of the library functions **Page 269**
D. machine code of the operating system

Question No:34 **(Marks:1)** **Vu-Topper RM**

Which one of the following is used to perform bit-wise exclusive OR operation?

A. ||
B. |
C. ^
D. ~

Question No:35 **(Marks:1)** **Vu-Topper RM**

What can the resultant number when you AND two numbers 12 & 8 bit-wise using & operator?

A. 4
B. 12
C. 8
D. 6

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:36 **(Marks:1)** **Vu-Topper RM**

Which one is the correct example of a unary operator?

A. %
B. /
C. - ok
D. ==

Question No:37 **(Marks:1)** **Vu-Topper RM**

Object code is machine code but it is not _____ and _____.

A. faster , efficient
B. tested , compiled
C. compiled ,debugged
D. relocatable , executable ok

Question No:38 **(Marks:1)** **Vu-Topper RM**

The concept of friend function negates the concept of _____.

A. Inheritance
B. Persistence
C. Polymorphism
D. Encapsulation

Question No:39 **(Marks:1)** **Vu-Topper RM**

Constructor is itself a _____ of C++ and _____.

A. class , can be overloaded
B. object, can not be initialized
C. function, can be overloaded Page 315 ok
D. function , cannot be overloaded

Question No:40 **(Marks:1)** **Vu-Topper RM**

public or private keywords can be _____

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

A. written outside the class
B. written only twice in the class declaration
C. written only for once in the class or structure declaration
D. written multiple times in the class or structure declaration ok

Question No:41 (Marks:1) Vu-Topper RM

Windows operating system may itself takes memory from _____.

A. Stack
B. Heap Google
C. List
D. Array

Question No:42 (Marks:1) Vu-Topper RM

The friend keyword provides access _____.

A. to all classes
B. in two directions
C. in one direction only
D. to the data members of the friend class only

Question No:43 (Marks:1) Vu-Topper RM

The function overloading requires_____.

A. A. the argument list to be different. Page 322
B. no arguments
C. the argument list to be the same
D. the arguments of integer type only

Question No:44 (Marks:1) Vu-Topper RM

Initializing the data member within the class is _____.

A. not an error
B. a run time error
C. a syntax error
D. a logical error

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:45 **(Marks:1)** **Vu-Topper RM**

By writing aFile.seekg(15L, ios::cur) we are moving _____.

A. 15 bytes in the forward direction starting from the current position

B. 15 bits in the backward direction starting from the current position

C. 15 bytes in the backward direction starting from the current position

D. 15 bits in the backward direction starting from the previous position

Question No:46 **(Marks:1)** **Vu-Topper RM**

Which is not true regarding structures?

A. a) We can declare arrays of structure

B. c) We can't declare pointers to structure

C. d) Both b & c

D. b) We can take the size of structure

Question No:47 **(Marks:1)** **Vu-Topper RM**

We use dot operator to access the data members of both _____ and _____.

A. arrays, structures

B. none of them

C. unions, arrays

D. unions, structures

Question No:48 **(Marks:1)** **Vu-Topper RM**

The memory allocation in C++ is carried out with the help of _____.

A. NULL pointer

B. + operator

C. new operator **Page 64**

D. dot operator

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:49 **(Marks:1)** **Vu-Topper RM**

a = a + 1; can be written as _____.

A. a + 1;
B. a + a + 1;
C. a + = 1; **Page 14**
D. 1 + a = a;

Question No:50 **(Marks:1)** **Vu-Topper RM**

C++ was developed by _____.

A. Graham Bell
B. Von Nuemann
C. Charles Babbage
D. Bejarne Stroustrup **Google** **ok**

Question No:51 **(Marks:1)** **Vu-Topper RM**

How many bits form a byte?

A. 4
B. 6
C. 2
D. 8 **Google**

Question No:52 **(Marks:1)** **Vu-Topper RM**

The difference between pointers and references is that _____.

A. we can assign references
B. we cannot reassign pointers
C. we can do arithmetic with pointers
D. we cannot do arithmetic with pointers

Question No:53 **(Marks:1)** **Vu-Topper RM**

The_____is the increment Operator in c++.

A. +*
B. --

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

C. ++
D. *+

Question No:54 **(Marks:1)** **Vu-Topper RM**

Constructor has _____.

A. no name
B. return type
C. the same name as of class **Page 50**
D. the same name as data member

Question No:55 **(Marks:1)** **Vu-Topper RM**

We cannot use _____ pointer for storing and reading data from it.

A. Null **ok**
B. Zero
C. Integer
D. Double

Question No:56 **(Marks:1)** **Vu-Topper RM**

The new operator automatically determines the size of memory required to store that object , so it does not need _____.

A. free operator
B. dot operator
C. sizeof operator
D. size off operator

Question No:57 **(Marks:1)** **Vu-Topper RM**

This reference to a variable can be obtained by preceding the identifier of a variable with _____.

A. ^ sign
B. Operator
C. Dot operator

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

D. Ampersand sign &

Question No:58 **(Marks:1)** **Vu-Topper RM**

A class can be declared as a _____ of other class.

A. Part
B. Friend **Page 87**
C. Member
D. member function

Question No:59 **(Marks:1)** **Vu-Topper RM**

The members of a class declared without any keyword are _____ by default

A. Public
B. Private **ok**
C. Constant
D. Protected

Question No:60 **(Marks:1)** **Vu-Topper RM**

Look at the statement given below int & a; and tell what will happen ?

A. Compiler will generate an error: 'a' declared as reference but not initialized
B. Compiler will compile successfully
C. Compiler will show a warning to you
D. Null value will be assigned to a

Question No:61 **(Marks:1)** **Vu-Topper RM**

getche() is a _____ function and defined in _____ header file.

A. built-in function , conio.h
B. user-define function , conio.h
C. built -in function, iostream.h
D. built-in function, stlib.h

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:62 **(Marks:1)** **Vu-Topper RM**

The main advantage of function overloading is that _____.

A. The program becomes more readable

B. The function becomes inline

C. The program becomes portable

D. The program becomes complex

Question No:63 **(Marks:1)** **Vu-Topper RM**

If the request of new operator is not fulfilled due to insufficient memory in the heap _____.

A. free operator returns nothing

B. the new operator returns 1

C. the operator returns 0 **ok**

D. the new operator returns 2

Question No:64 **(Marks:1)** **Vu-Topper RM**

For console input and output we use _____.

A. process.h header file

B. stdlib.h header file

C. conio.h header file **ok**

D. getch.h header file

Question No:65 **(Marks:1)** **Vu-Topper RM**

The operator to free the allocated memory using new operator is _____.

A. free

B. delete

C. del

D. remove

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:66 **(Marks:1)** **Vu-Topper RM**

_____ allow us to have a memory location and use it as int or char interchangeably

A. construct
B. None of the given
C. structures
D. union

Question No:67 **(Marks:1)** **Vu-Topper RM**

A structure is a collection of _____under a single name.

A. Array
B. Pointer
C. Datatype
D. Variables **Page 229**

Question No:68 **(Marks:1)** **Vu-Topper RM**

The memory allocation functions return a chunk of memory with a pointer of type_____.

A. Ptr
B. Void **Page 281**
C. Float
D. Integer

Question No:69 **(Marks:1)** **Vu-Topper RM**

A file opened with the help of _____ can be used for both input and output.

A. Fstream **Page 220**
B. Ofstream
C. Iostream

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

D. Ifstream

Question No:70 **(Marks:1)** **Vu-Topper RM**

Macros are categorized into _____ type(s).

A. One

B. Two **Page 275** **ok**

C. Five

D. Three

Question No:71 **(Marks:1)** **Vu-Topper RM**

All the preprocessors directives starts with _____.

A. -

B. &

C. # **Page 279**

D. $

Question No:72 **(Marks:1)** **Vu-Topper RM**

When we include the header file in the angle brackets the compiler searches for it in _____.

A. All the drives

B. Current folder

C. Current directory **Page 269**

D. Specific directory

Question No:73 **(Marks:1)** **Vu-Topper RM**

For accessing data members we use _____ operator

A. Dot. **ok**

B. Plus+

C. Division /

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

D. multiplication *

Question No:74 **(Marks:1)** **Vu-Topper RM**

The dynamic memory allocation uses _____ whereas static memory allocation uses _____.

A. stack , lists
B. array , stack
C. Heap,stack
D. classes , array

Question No:75 **(Marks:1)** **Vu-Topper RM**

A file opened with _____ is used for input and cannot be used for output.

A. Ifstream **Page 220**
B. Ostream
C. Istream
D. Fstream

Question No:76 **(Marks:1)** **Vu-Topper RM**

The data, contained in the structure, is defined in the _____.

A. None
B. Parenthesis
C. Curly braces **Page 229**
D. Inverted commas

Question No:77 **(Marks:1)** **Vu-Topper RM**

student s[100]; means that 's' is an array of hundred students of type 'student' structure. What will be the correct statement to access the 'name' data element of the fifty sixth student from the array?

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

A. s.name[56];
B. s[55].name;
C. s.name[55];
D. s[56].name;

Question No:78 **(Marks:1)** **Vu-Topper RM**

Which of the following code segment represents a left shift operator?

A. cout<<1;
B. cin >> number ;
C. result = number >> 1 ;
D. result = number << 1 ; **Google**

Question No:79 **(Marks:1)** **Vu-Topper RM**

Array indexes start from _____.

A. 1
B. 0 **Page 266** **ok**
C. 2
D. 3

Question No:80 **(Marks:1)** **Vu-Topper RM**

An instance of a class is called _____.

A. Object **Page 324**
B. Structure
C. Data type
D. Member function

Question No:81 **(Marks:1)** **Vu-Topper RM**

Which header file is required to use file I/O operations?

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

A. <fstream> **Google**

B. <ifstream>

C. <ostream>

D. <iostream>

Question No:82 **(Marks:1)** **Vu-Topper RM**

Name the function whose definition can be substituted at a place where its function call is made _____.

A. inline function **Google**

B. static function

C. friend function

D. volatile function

Question No:83 **(Marks:1)** **Vu-Topper RM**

Default constructor takes _____.

A. no parameters **Page 315**

B. one parameter

C. two parameters

D. character type parameter

Question No:84 **(Marks:1)** **Vu-Topper RM**

_____function gives the position of the next character to be read from that file.

A. Tellp()

B. Tellg() **Page 215**

C. Seekp()

D. Seekg()

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:85 **(Marks:1)** **Vu-Topper RM**

the sizeof operator is used to determine the size of _____.

A. Data

B. Variable

C. Data type **Page 235**

D. None of the given

Question No:86 **(Marks:1)** **Vu-Topper RM**

Shifting the binary numbers is similar to shifting the _____ numbers.

A. Octal

B. Base 7

C. Decimal **Page 252**

D. Hexadecimal

Question No:87 **(Marks:1)** **Vu-Topper RM**

_____function is used to determine the next position to write a character while writing into a file.

A. Tellg()

B. Tellp() **Page 215**

C. Seekp()

D. Seekg()

Question No:88 **(Marks:1)** **Vu-Topper RM**

We have opened a file stream myfile for reading (getting), myfile.tellg () gives us the current get position of the file pointer. It returns a whole number of type_____

A. Int

B. Long **Page 215**

C. Short

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

D. Double

Question No:89 **(Marks:1)** **Vu-Topper RM**

What is the use of ios::trunc mode?

A. To open a file in input mode
B. To open a file in output mode
C. To truncate an existing file to half
D. To truncate an existing file to zero **Google**

Question No:90 **(Marks:1)** **Vu-Topper RM**

Structures use _____ for memory allocation.

A. Heap **Google**
B. Stack
C. Queue
D. Cache

Question No:91 **(Marks:1)** **Vu-Topper RM**

Which of the following is not a file opening mode_____?

A. Ios::in
B. Ios::out
C. Ios::ate
D. ios::truncate

Question No:92 **(Marks:1)** **Vu-Topper RM**

Structures are syntactically defined with the word_____.

A. Struc
B. Struct **Page 229**
C. Structure
D. None of the given

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:93 **(Marks:1)** **Vu-Topper RM**

Which of the following syntax is best used to delete an array of 5 objects named ‘string’ allocated using new operator.

A. Delete string;
B. Delete [] string;
C. Delete string [1];
D. Delete string [5];

Question No:94 **(Marks:1)** **Vu-Topper RM**

Consider the following code segment. Which of the following will be called while executing code at line 2?

String s1,s2;
S1=s2;

A. Default operator
B. Copy constructor
C. Assignment operator
D. Parameterized constructor

Question No:95 **(Marks:1)** **Vu-Topper RM**

free function is available in _____ header file.

A. stdlib.h
B. conio.h
C. string.h
D. iostream.h

Question No:96 **(Marks:1)** **Vu-Topper RM**

C++ offers _____ levels of data access control inside a class

A. Two

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What’s app 03224021365

B. Five
C. Four
D. Three **Google**

Question No:97 **(Marks:1)** **Vu-Topper RM**
The stream-insertion operator is >> and the stream-extraction operator is <<.
True
False

Question No:98 **(Marks:1)** **Vu-Topper RM**
The concept of _____ allows us to separate the interface from the implementation of the class.
A. Pointers
B. Inheritance
C. Polymorphism
D. Encapsulation **Google**

Question No:99 **(Marks:1)** **Vu-Topper RM**
Which of the following is unary operator?
A. I++
B. I--
C. ++i
D. All of the Given

Question No:100 **(Marks:1)** **Vu-Topper RM**
Identify the correct syntax for making a class friend of other class
friend ClassOne
{

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

OtherClass;
private;
//here we write the data members of ClassOne
};
lassOne
{friend OtherClass ;
private:
//here we write the data members of ClassOne
};
class ClassOne
{
friend OtherClass ;
private:
//here we write the data members of ClassOne
};
Friend class ClassOne
{
friend OtherClass ;
private:
//here we write the data members of ClassOne
};

Question No:101 **(Marks:1)** **Vu-Topper RM**

Let suppose
int a, b, c, d, e;
a = b = c = d = e = 42;
This can be interpreted by the complier as:

A. a = (b = (c = (d = (e = 42))));

B. (a = b) = (c = d) = (e = 42);

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

C. a = b = (c = (d = (e = 42)));
D. (a = b = (c = (d = (e = 42))));

Question No:102 **(Marks:1)** **Vu-Topper RM**

We cannot increment _____.

A. Arrays
B. Pointers
C. Variables
D. References **Page 364**

Question No:103 **(Marks:1)** **Vu-Topper RM**

_____ operators are the ones that require only one operator to work.

A. Unit
B. Unary **Page 370**
C. Binary
D. Single

Question No:104 **(Marks:1)** **Vu-Topper RM**

The constructor contains _____.

A. Class **Page 313**
B. Object
C. Return
D. None of these

Question No:105 **(Marks:1)** **Vu-Topper RM**

We can _____references.

A. Reassign **Google**
B. Increment
C. Decrement

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

VuTopper RM

D. None of the given

Question No:106 **(Marks:1)** **Vu-Topper RM**

The destructor is used to _____.

A. create objects
B. allocate memory
C. de-allocate memory **Page 338**
D. allocate static memory

Question No:107 **(Marks:1)** **Vu-Topper RM**

Functions declared with the _____ specifier in a class member list are called friend functions of that class.

A. Friend
B. Public
C. Private
D. Protected

Question No:108 **(Marks:1)** **Vu-Topper RM**

To prevent dangling reference the functions returning reference should be used with _____

A. Arrays
B. local variables
C. global variables only
D. static and global variables

Question No:109 **(Marks:1)** **Vu-Topper RM**

If we want to allocate memory to an array of 5 integers dynamically, the syntax will be _____.

A. iptr= new[5]

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

B. int iptr ; iptr= int [5]

C. int *iptr ; iptr = new int[5] ; ok

D. integer iptr** ; iptr= new int[5]

Question No:110 (Marks:1) Vu-Topper RM

The function will return a reference to the global variable that exists throughout the program and thus there will be no danger of _____.

A. System crash

B. Garbage collection

C. Dangling reference Page 365

D. Wastage of memory

Question No:111 (Marks:1) Vu-Topper RM

If class A is a friend of class B, and class B is a friend of class C. If class A wants class C to be a friend, _____

A. it has to declare, class B as a friend

B. it has to declare, class C as a friend

C. it has to declare , class A as a friend

D. it has to declare, class B and class A as friend classes

Question No:112 (Marks:1) Vu-Topper RM

If we use cin stream to read some value and store it in some integer variable and press some alphabet key instead of numeric keys. then what will happen?

A. Its ASCII code will be stored inside the computer

B. Some error will occur and cin stream will detect this error.

C. Its binary representation will be ignored and the value will be stored

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

D. Its binary representation will be ignored and the character will be stored

Question No:113 **(Marks:1)** **Vu-Topper RM**

Which one of the following is the correct statement about operator overloading?

A. N-arithmetic operators can be overloaded only.

B. Arithmetic operators can be overloaded only.

C. Associativity and precedence of operators do not change.

D. Precedence of operators are changed after overloading.

Question No:114 **(Marks:1)** **Vu-Topper RM**

new operator can be used for _____.

A. dot operator

B. only integer data type

C. only char and integer data types

D. integer, float, char and double data types

Question No:115 **(Marks:1)** **Vu-Topper RM**

Friend classes are used in cases where one class is _____to another class.

A. Independent

B. Encapsulated

C. tightly coupled.

D. loosely coupled.

Question No:116 **(Marks:1)** **Vu-Topper RM**

_____will return the number of bytes reserved for a variable or data type.

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

A. void pointer
B. free operator
C. new operator
D. size of operator ok

Question No:117 (Marks:1) Vu-Topper RM

int &i; It means that i is a _____to an integer.

A. Pointer
B. data type
C. reference Page 358
D. constant pointer

Question No:118 (Marks:1) Vu-Topper RM

What does the following statement mean?int (*fp)(char*)

A. pointer to a pointer
B. function taking a char* argument and returning a pointer to i
C. pointer to an array of chars
D. pointer to function taking a char* argument and returns an int

Question No:119 (Marks:1) Vu-Topper RM

_____data isn't accessible by non-member functions or outside classes

A. Static
B. Public
C. Private
D. Globally declared.

Question No:120 (Marks:1) Vu-Topper RM

If we have a program that writes the output data(numbers) to the disc

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

,and if we collect the output data and write it on the disc in one write operation instead of writing the numbers one by one.In the above situation the area where we will gather the number is called

A. Stack
B. Heap
C. Cache
D. Buffer

Question No:121 (Marks:1) Vu-Topper RM

Default constructor generated by _____does _____for us.

A. classes , initialization
B. compiler , initialization ok
C. compiler, no initialization
D. main program, memory management

Question No:122 (Marks:1) Vu-Topper RM

What is the function of the following statement to delete an array of 5 objects named 'arr' allocated using new operator?
delete arr ;

A. Results into syntax error
B. Do not delete any object
C. Deletes all the objects of array
D. Deletes only one object of array

Question No:123 (Marks:1) Vu-Topper RM

The syntax of declaration of a function that returns the reference to an integer is _____.

A. Int myfunc();

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

B. Int myfunc() &;
C. Int &myfunc() ;
D. Integer &myfunc();

Question No:124 **(Marks:1)** **Vu-Topper RM**

If we do not write our own assignment operator then which of the following problem may occur?

A. Null pointer
B. Memory leak
C. Dangling pointer
D. Unreferenced memory

Question No:125 **(Marks:1)** **Vu-Topper RM**

What is the difference between cout and cerr?

A. Cout is unbuffered output and cerr is a buffered output
B. Cout is not standard output and cerr is a standard output
C. Cout is buffered output and cerr is not a unbuffered output
D. Cout is standard output and cerr is not a standard output

Question No:126 **(Marks:1)** **Vu-Topper RM**

The only operator that the compiler overloads for user define data type by default is

A. Plus (+) operator **Google**
B. Minus (-) operator
C. Equal (==) operator
D. Assignment (=) operator

Question No:127 **(Marks:1)** **Vu-Topper RM**

The friend functions are _____.

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

A. void functions
B. inline functions
C. member of a class
D. not member of a class **Page 523**

Question No:128 **(Marks:1)** **Vu-Topper RM**

The friend function of a class can have access _____.

A. to the private data members
B. to the protected data members
C. to the public data members only
D. to public, private and protected data members **Google**

Question No:129 **(Marks:1)** **Vu-Topper RM**

Let suppose a = b = c
In such situation, it is necessary to return a reference of an object from assignment operator function.

True
False

Question No:130 **(Marks:1)** **Vu-Topper RM**

You cannot overload the _____ operator

A. /
B. +
C. ?;
D. ++

Question No:131 **(Marks:1)** **Vu-Topper RM**

Bugs can occur due to _____

A. default values

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

B. uninitialized data

C. object destruction

D. initialization of a variable

Question No:132 **(Marks:1)** **Vu-Topper RM**

When new operator is overloaded at global level then corresponding built-in new operator will also be visible to whole of the program.

True

False

Question No:133 **(Marks:1)** **Vu-Topper RM**

Care must be taken about the correct _____ of operator while overloading. (Choose the most appropriate).

A. Semantic

B. Complexity

C. None of the given option

D. Both Semantic and Complexity

Question No:134 **(Marks:1)** **Vu-Topper RM**

Ternary operator is shown as_____.

A. lll

B. ?:

C. &&

D. = = =

Question No:135 **(Marks:1)** **Vu-Topper RM**

These functions seekg() and ssekp()requires an argument of type_____ to determine the backward.

A. Int

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

B. Long
C. Short
D. Double

Question No:136 **(Marks:1)** **Vu-Topper RM**

The stream-insertion operator is >> and the stream -extraction operator is <<.

True

False

Question No:137 **(Marks:1)** **Vu-Topper RM**

The return type of the overloading new operator must be?

A. Int pointer
B. Void pointer
C. Object pointer
D. Void (nothing)

Question No:138 **(Marks:1)** **Vu-Topper RM**

Reference is not really an address it is _____.

A. A value
B. A number
C. A synonym
D. An antonym

Question No:139 **(Marks:1)** **Vu-Topper RM**

The reference data types are used as _____ variables without any _____ operator

A. Local, &
B. Global, dot

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

C. Static, deference

D. Ordinary, deference

Question No:140 (Marks:1) Vu-Topper RM

Overloaded member operator function is always called by ___

A. Class

B. Object

C. Compiler

D. Primitive data types

Question No:141 (Marks:1) Vu-Topper RM

Encapsulation means_____.

A. That data becomes public.

B. That the data of a class cannot be accessed from outside.

C. That the data of a class can be accessed from outside.

D. That the can be accessible anywhere within a main program.

Question No:142 (Marks:1) Vu-Topper RM

Memory allocated from heap or free store _____.

A. Can be allocated to classes only

B. Can be returned back to the system automatically

C. Cannot be returned back unless freed explicitly using malloc and realloc

D. Cannot be returned back unless freed explicitly using free and delete operators

Question No:143 (Marks:1) Vu-Topper RM

_____ operators are the ones that require two operators on both sides of the operator.

A. Unary

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

B. Binary

C. Double

D. Two sided

Question No:144 **(Marks:1)** **Vu-Topper RM**

when the compiler overloads the assignment (=) operator by default then

A. Class members are not assigned properly.

B. Compiler does member wise assignment.

C. Compiler does not do member wise assignment.

D. Compiler does not allow default assignment operator.

Question No:145 **(Marks:1)** **Vu-Topper RM**

In C language, the region of memory allocated at runtime is called _____.

A. Stack

B. Heap

C. Free store

D. Available memory

Question No:146 **(Marks:1)** **Vu-Topper RM**

_____is the pointer which determines the position in a file from where the next read operation occurs.

A. Set

B. Put

C. Get

D. Tell

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:147 **(Marks:1)** **Vu-Topper RM**

Once we have defined a symbolic constant value using #defined, the value_____ during program.

A. Varies
B. Becomes zero
C. Can be changed.
D. Cannot be changed.

Question No:148 **(Marks:1)** **Vu-Topper RM**

The function calloc takes two arguments, first argument is the _____ and the second argument is the _____.

A. Size of array, member of bytes.
B. Size of space, member of bytes.
C. Space in terms of string character, size of list.
D. Required space in terms of number. Size of space.

Question No:149 **(Marks:1)** **Vu-Topper RM**

The default visibility for the data members of the class is.

A. Public
B. Private **ok**
C. Protected
D. Accessible outside the class.

Question No:150 **(Marks:1)** **Vu-Topper RM**

symbolic constant PI can be defined as:

A. #defined pi 3.14; **ok**
B. #defined pi 3.14
C. #include pi = 3.14
D. #defined pi = 3.14

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:151 **(Marks:1)** **Vu-Topper RM**

When accessing a structure member, the identifier to the left of the dot operator is the name of _____.

A. Structure data
B. Structure tag
C. Structure member
D. Structure variable

Question No:152 **(Marks:1)** **Vu-Topper RM**

_____operator uses the sign ^.

A. Bit-wise OR
B. NOT operator
C. Exclusive OR **ok**
D. AND operator

Question No:153 **(Marks:1)** **Vu-Topper RM**

We should not use such variable names that are starting with_____ because in C++, then names that start with it.

A. Double underscore
B. Lower case alphabets
C. Upper case alphabets
D. None of the given option

Question No:1 **(Marks:1)** **Vu-Topper RM**

The statement cin.get (); is used to_____.

A. Read a string from file
B. Read a character from file
C. Read a string from keyboard

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

D. Read a character from keyboard **Page 426**

Question No:154 **(Marks:1)** **Vu-Topper RM**

Ostream is a _____ operator.

A. None
B. Member
C. Dependent
D. Standalone

Question No:155 **(Marks:1)** **Vu-Topper RM**

The second parameter of operator function for >> operator must always be passed

A. By value
B. By reference
C. None of the given option
D. Function takes no argument

Question No:156 **(Marks:1)** **Vu-Topper RM**

If text is a pointer of type String, then what will be the functionality of following statement?text = new string [5];

A. Creates a string object
B. Creates array of of pointer to string
C. Creates array of 5 objects statistically
D. Creates array of 5 objects dynamically

Question No:157 **(Marks:1)** **Vu-Topper RM**

When operator function is implemented as member function then return type of function ____.

A. Can be any data type
B. Must be built – in data type

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

C. Must be user defined data type
D. Must be an object of same class

Question No:158 **(Marks:1)** **Vu-Topper RM**

We cannot define friends for the _____ that are already written and not in our control.

A. Classes
B. Functions
C. Destructor
D. Constructors

Question No:159 **(Marks:1)** **Vu-Topper RM**

With user data type variables (Objects) self assignment can produce

A. Link error
B. Syntax error
C. Logical error
D. Run time error

Question No:160 **(Marks:1)** **Vu-Topper RM**

When an operator function is defined as member function for a binary Plus (+) operator then the number of extra arguments it takes is/are.

A. One
B. Five
C. Zero
D. N arguments

Question No:161 **(Marks:1)** **Vu-Topper RM**

The get member function, when passed no arguments, inputs an entire stream and returns it as the value of the function call.?

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

False

True

Question No:162 **(Marks:1)** **Vu-Topper RM**

What will be the output of the following code segment?

Float pi=32.3996;

Cout<<fixed;

Cout<<setprecision(2)<<pi;

A. 32.00

B. 32.39

C. 32.40

D. 32.310

Question No:163 **(Marks:1)** **Vu-Topper RM**

C++ provides member functions, which control the formatting to be performed during stream I/O operations.

True

False

Question No:164 **(Marks:1)** **Vu-Topper RM**

In overloading the assignment (=) operator, which object(s) will call the operator function?

A. Right object of the assignment operator

B. No object will call the operator function

C. Left object of the assignment operator

D. Both objects will call the operator function

Question No:165 **(Marks:1)** **Vu-Topper RM**

The was manipulator can be used with __ stream(s).

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

None of the given option

A. Input
B. Output
C. Both of these
D. None of the these

Question No:166 (Marks:1) Vu-Topper RM

When we use cin stream to read some number from the keyboard and store it in the integer variable, then what will happen?

A. Its to ASCII code will be stored inside the computer
B. Some error will occure and cin stream will detect this error
C. Its binary representation will be ignored and the character will be stored
D. Its binary representation will be ignored and the value will be stored

Question No:167 (Marks:1) Vu-Topper RM

*This is a pointer that always points to

A. A value of data member
B. Current object of the class
C. Current function of the class
D. Current pointer of the class

Question No:168 (Marks:1) Vu-Topper RM

If operator function is non-member function, then object on left side of operator cannot be_____?

A. Built-in data type
B. Object of operator class
C. Object of different class

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

D. Object of member function

Question No:169 **(Marks:1)** **Vu-Topper RM**

What is the purpose of endl stream manipulator?

A. Insert a new line

B. Flush the stream

C. Terminate a string with null

D. Insert a new line and flush the stream

Question No:170 **(Marks:1)** **Vu-Topper RM**

Overloaded assignment operator must be

A. Global function

B. Friend function of class

C. Member function of class

D. Non-member function of class

Question No:171 **(Marks:1)** **Vu-Topper RM**

C++ offers type-safe I/O. The << and >> operators are overloaded to accept data items of specific types.\

False

True

Question No:172 **(Marks:1)** **Vu-Topper RM**

For the joining of two strings in string class, we may use "+" operator, can we use "-" operator the same way for subtracting strings?

A. Yes

B. No

C. Yes along "?" operator only

D. Yes along "+"operator only

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:173 **(Marks:1)** **Vu-Topper RM**

:: is called _____.

A. Bitwise OR

B. Condition operator

C. One's complement operator

D. Scope resolution operator

Question No:174 **(Marks:1)** **Vu-Topper RM**

The stream insertion and extraction operators are not already overloaded for __

A. User- defined data types

B. Built-in data types

C. None of the given option

D. Both built –in and user – defined types

Question No:175 **(Marks:1)** **Vu-Topper RM**

In C++ operators, which of the following operator cannot be overloaded _____.

A. -

B. ?

C. +

D. <<

Question No:176 **(Marks:1)** **Vu-Topper RM**

Automatic variable are created on ____.

A. Heap

B. Stack

C. Free store

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

D. Static storage

Question No:177 **(Marks:1)** **Vu-Topper RM**

When we used eof (end of file) with the file reading than which of the following is a true statement?

A. This is a way to check type of the stream

B. This is a way to check source of the stream

C. This is a way to check state of the stream

D. This is a way to check destination of the stream

Question No:178 **(Marks:1)** **Vu-Topper RM**

Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

A. Class –name operator +();

B. Class –name operator +(int);

C. Class –name operator ++();

D. Class –name operator ++(int);

Question No:179 **(Marks:1)** **Vu-Topper RM**

The first parameter of operator function for << operator _____.

A. Must be object class

B. Must be passed by value

C. Must be passed by reference

D. Can be passed by value or reference

Question No:180 **(Marks:1)** **Vu-Topper RM**

Ostream class is ____ and not under our control.

A. User-defined

B. Built-in

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

C. Both
D. None

Question No:181 **(Marks:1)** **Vu-Topper RM**

Which of the following functionality can be achieved through overloading?

A. We can change associativity of all operator
B. We can change the precedence of same operator
C. We can change the associativity of some operator
D. New operator cannot be defined through operator overloading

Question No:182 **(Marks:1)** **Vu-Topper RM**

The operator function for << (stream insertion) >> and stream extraction must be

A. None of given option
B. Member function of class
C. Non –member function of class
D. Both member and non-member function

Question No:183 **(Marks:1)** **Vu-Topper RM**

Static variable which is defined in a function is initialized ____.

A. None of the above
B. Compile time of program
C. Every time the function call
D. Only once during its life time

Question No:184 **(Marks:1)** **Vu-Topper RM**

Overloaded delete operator function takes parameter of void pointer and returns.

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

A. Void
B. Int pointer
C. Void pointer
D. Object pointer

Question No:185 **(Marks:1)** **Vu-Topper RM**

_____ must be included to use stream manipulator in your code.

A. Conio.h
B. Stdlib.h
C. Iomanip
D. Iostream

Question No:186 **(Marks:1)** **Vu-Topper RM**

Consider the following code, the printed value will be converted into:

```
int n = 10;
cout<<oct<<n;
```

A. base 2
B. base 8
C. base 10
D. decimal number system

Question No:187 **(Marks:1)** **Vu-Topper RM**

Which of the following is normally a destination for cin stream?

A. Mouse
B. Printer
C. Variable
D. Keyboard

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:188 **(Marks:1)** **Vu-Topper RM**

Which of the following is a destination of cout stream?

A. Printer
B. Constant
C. Variable
D. Data type

Question No:189 **(Marks:1)** **Vu-Topper RM**

The return type of the operator function for << operator is ____.

A. Void
B. Class for which we overload operator
C. Reference of ostrem class(istream&)
D. Reference of ostrem class(ostream&)

Question No:190 **(Marks:1)** **Vu-Topper RM**

Static data members of a class can be ____.

A. Public
B. Private
C. Both
D. None

Question No:191 **(Marks:1)** **Vu-Topper RM**

Once the _____ are created, they exist for the life time of the program

A. Local variables
B. Static variables **Page 365**
C. Automatic variables
D. non static variables

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:192 **(Marks:1)** **Vu-Topper RM**

The members of a class declared with the keyword struct are _____by default.

A. Static
B. Public **ok**
C. Private
D. Protected

Question No:193 **(Marks:1)** **Vu-Topper RM**

If the memory in the free store is not sufficient _____.

A. Malloc function returns 0
B. Malloc function returns 1
C. Malloc function returns free space
D. Malloc functions returns NULL pointer

Question No:194 **(Marks:1)** **Vu-Topper RM**

Once an object is declared as a friend, _____.

A. It has access to public members only
B. It has to protected data members only
C. It has no access to data members of the class
D. It has access to all non-public members as if they were public

Question No:195 **(Marks:1)** **Vu-Topper RM**

Reference variables must _____.

A. Contain zero value
B. Contain integer value
C. Be initialized after they are declared
D. Not be initialized after they are declared

Question No:196 **(Marks:1)** **Vu-Topper RM**

What is the sequence of event(s) when allocating memory to an object using new operator?

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

A. Only destructor is called for object
B. Only block of memory is deallocated for object
C. Destructor is called first before deallocating memory
D. Memory is allocated first before calling constructor

Question No:197 **(Marks:1)** **Vu-Topper RM**
The endl and flush are _____
Manipulators

Question No:198 **(Marks:1)** **Vu-Topper RM**
Deleting an array of objects without specifying [] brackets may lead to memory leak.
False
True

Question No:199 **(Marks:1)** **Vu-Topper RM**
A variable which is defined inside a function is called
Automatic variable

Question No:200 **(Marks:1)** **Vu-Topper RM**
_____ variables are defined in the main.
Local

Question No:201 **(Marks:1)** **Vu-Topper RM**
Assignment operator is used to initialize a newly declared object from existing object.
True
False

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:202 **(Marks:1)** **Vu-Topper RM**

When a variable is defined as static in a class then _____.

Only one copy is created for all objects of this class

Question No:203 **(Marks:1)** **Vu-Topper RM**

Within the statement obj1=obj2; obj1 will call the assignment operator function and obj2 will be passed as an argument to function.

True

False

Question No:204 **(Marks:1)** **Vu-Topper RM**

Which of the following is normally a source for cin stream?

Keyboard

Question No:205 **(Marks:1)** **Vu-Topper RM**

When an array of object is created dynamically then there is no way to provide parameterized constructors for array of objects.

True

False

Question No:206 **(Marks:1)** **Vu-Topper RM**

It is possible to return an object from function using this pointer.

True

False

Vu Topper RM

Visit My YouTube Channel For Subjective and More Important Files

For More Help Contact What's app 03224021365

Channel Name = #VuTopperRM

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365