Virtual University

بسم الله الرحمن الرحيم

Mickey ch

CS-201(Introduction to programming)

Mid Term Important Solved Mcq's

By Mickey Ch

80 to 100% Marks

We offers:

- LMS Handling
- Assignments
- Quizes
- GDB
- Mid&Final Term important Notes

We also offers:

- CS 619 Projects

Follow us on youtube:

@mickeych8525

Whatsapp

#0333-6166150

Email:

mickeych96@gmail.com

Learning With Mickey ch

Q NO 01:

If the file is not properly closed in the program, the program _____.

A. Terminate normally

B. Indicate Runtime error

C. Indicate Compile time error

D. Crashes

Q NO 02:

Which of the following header file include string conversion functions?

A. string.h

B. stdlib.h

C. ctype.h

D. sconvert.h

Q NO 03:

The function of cin is

A. To display message

B. To read data from keyboard

C. To display output on the screen

D. To send data to printer

Q NO 04:

Continue statement usually force the immediate_____iteration of the loop .

A. last

B. previous

C. first

D. next

Q NO 05:

Which one of the following is used to perform bit- wise OR operation?

A. ~

B. ^

C. ||

D. |

Q NO 06:

The friend function are --.

A. Not member of class

B. Member of class

C. Inline function

D. Void function

Q NO 07:

The function of calloc takes two arguments, the first argument is the and the second argument is the.....

A. Required space in terms of number , size of space

B. Size of space, number of bytes

C. Space in terms of string character , size of list

D. Size of array, number of bytes

Q NO 08:

With the use of dynamic allocation of memory, the system resource can be --.

A. Wasted

B. Used efficiently

C. Used carelessly

D. All of the above

Q NO 09:

Mickey.ch

Whatsapp#0333-6166150

Learning With Mickey ch

An instance of a class is called --.

A. Structure
B. Data type
C. Member function
D. Object

Q NO 10:

In c language, the region of memory allocated at run time is called --.

A. Stack
B. Heap
C. Free store
D. Available memory

Q NO 11:

Constructor has --.

A. No name
B. The same of the class
C. The same name as data member
D. Return type

Q NO 12:

We should not use sch variable names that are starting with_____because in C++, there are lots of internal constant and symbolic names that star with it.

A. Upper case alphabets
B. Lower case alphabets
C. Double underscore
D. None of the given option

Q NO 13:

For console input and output we use --.

A. Conio.h header file
B. Stdlib.h header file
C. Process.h header file
D. Getch.h header file

Q NO 14:

The exclusive OR operator returns 1 if --.

A. Both input are 1
B. None of the given
C. One in is 1 and other is zero
D. Both input are 0

Q NO 15:

Operating system is a type software.

A. Utility
B. Device driver
C. Application
D. System

Q NO 16:

What will be result of the expression K=++m;If

initially K=0 and m=5?

A. 6
B. 4
C. 0
D. 5

Q NO 17:

eof is used to check for the_____of file when a file is being read.

Mickey ch

Whatsapp#0333-6166150

A. Start
B. End
C. Middle
D. Name

Q NO 18:

Pointers are a special type of_____in which a memory address isstored.

A. variable
B. Location
C. Characters
D. None of the given

Q NO 19:

The string in the array is terminated by a_.

A. zero
B. nil
C. null
D. one

Q NO 20:

Given a two dimensional array of integer, what would be the correct wayof assigning the value 6 to the element at third row and fourth column?

A. array[3][4]=6;
B. array[2][4]=6;
C. array[4][3]=6;
D. array[2][3]=6;

Q NO 21:

Transpose of a matrix means that when we interchange rows andcolumns_.

A. the first row becomes the Last column
B. the first row becomes the first column
C. the Last row becomes the first column
D. the first column becomes the first row

Q NO 22:

We can define a matrix as_____array.

A. Sorted
B. Unsorted
C. Single dimensional
D. Multi dimensional

Q NO 23:

At the desing phase, we try to break up the problem into_____.

A. functional units
B. non-functional units
C. small units
D. None of the given

Q NO 24:

The name of the array is a constant pointer which contains the memoryaddress of the____of the array.

A. first element
B. last element
C. second element
D. none of the given

Q NO 25:

The ASCHI code of null character is_____ .

Mickey ch

A. 000
B. 010
C. 111
D. 110

Q NO 26:

_____contains functions for manipulations of character data.

A. Ctype.h
B. Iostream.h
C. String.h
D. None of the given

Q NO 27:

Each array declaration must provide the information about all these things expec _____.

A. Name of the array
B. Type of data stored in the array
C. The location of the first element to be stored
D. Number of elements of the array

Q NO 28:

dereferencing operator is represented by _____

A. +
B. *
C. –
D. None

Q NO 29:

Following is the declaration of a_____array. int arr[2][2];

A. 1 dimensional
B. 2 dimensional
C. 4 dimensional
D. 3 dimensional

Q NO 30:

A file opened with_____is used for input and cannot be used for output.

A. Ifstream
B. Ostream
C. Istream
D. Fstream

Q NO 31:

Base address is the memory address of_____element of an array.

A. 1st
B. 2nd
C. 3rd
D. 4th

Q NO 32:

At the_____, we try to break up the problem into functional units analysis phase

A. Small units
B. Design phase
C. Functional units
D. None of the given

Q NO 33:

After evaluating the expression X=10+3*4/2-1 the value of x will be

A. 5
B. 10

Mickey ch

C. 15
D. 20

Q NO 34:

9If x is declare as an integer what will be result of the given expression

A. 2
B. 4
C. 6
D. 8

Q NO 35:

Null Character is represented by_____in C++.

A. /0
B. \0
C. \n
D. \t

Q NO 36:

While handling files, one can have _____options.

A. read the file
B. write in some file
C. read and write in the same file
D. All of the given

Q NO 37:

we have opened a file stream myfile for reading(getting), myfile.tellg()gives us the current get position of the file pointer. It returns a whole number of type __.

A. long
B. int
C. short
D. double

Q NO 38:

_____Returns true if c is a letter and false otherwise.

A. int isalpha(int c)
B. int isalnum(int c)
C. int isxdigit(int c)
D. int isdigit(int c)

Q NO 39:

The ASCII code of null character is_____.

A. 000
B. 010
C. 111
D. 110

Q NO 40:

What will be the size of the following character array?char name[]="Adeel";

A. 5
B. 6
C. **4**
D. **7**

Q NO 41:

There is a pointer variable named ptr of type float then address of whichtype of variable the ptr will store in it?

A. int
B. float
C. char

Mickey ch

D. double

Q NO 42:

Whenever some number is added in an array name, it will jump as many _____as the added number.

A) rows
B) value
C) column
D) None of the given

Q NO 43:

A record is a group of related_____.

A. Data
B. Fields
C. Bytes
D. Files

Q NO 44:

A while loop many execute —- or more times

A. 1
B. 0
C. 2
D. 3

Q NO 45:

Array indexes start from—.

A. 0
B. 1
C. 4
D. 8

Q NO 46:

The result of 4%3 will be

A. 0
B. 1
C. 2
D. 3

Q NO 47:

What will be the output of the following codeString grade[3]={“A”,”B”,”C”}; Grade[2]=”F”;Cout<<grade[2];

A. F
B. A
C. C
D. D

Q NO 48:

If y=20 and z=y++ then the value of z will be—-

A. 21
B. 20
C. 19
D. 18

Q NO 49:

A variable of character data type occupies — bytes in memory

A. 0
B. 2
C. 1
D. 3

Q NO 50:

Mickey ch

Learning With Mickey ch

If x=11, and x%=3, than values of x will be

A. 4
B. 2
C. 6
D. 8

Q NO 51:

By default the starting index of an array in C++ is—

A. 0
B. 1
C. 2
D. 3

Q NO 52:

If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout<<statement

A. 3
B. 4
C. 2
D. 1

Q NO 53:

The string in the array is terminated by a_____.

A. Null
B. One
C. Two
D. Five

Q NO 54:

If an array has 50 elements what is allowable range of subscripts?

A. 0-49
B. 1-49
C. 0-50
D. 1-50

Q NO 55:

aFile.seekg(-10L, ios:cur) indicates the file pointer will move 10 bytes inthe____.

A. forward direction
B. backward direction
C. both direction
D. None of the above

Q NO 56:

_____function give the position of the next character to be readfrom that file.

A. tellp()
B. tellg()
C. seekg()
D. seekp()

Q NO 57:

At the design phase, we try to break up the problem into_____.

A. Small units
B. Functional units
C. Non-functional units
D. None of the given

Q NO 58:

When we access a multidimensional array, each array index issurrounded by _.

A. Single quotes "
B. Double quotes

Mickey ch

Whatsapp#0333-6166150

Learning With Mickey ch

C. Brackets []
D. Commas ,,

Q NO 59:
We have opened a file stream myfile for reading (getting), myfile.tellg()gives us the current get position of the file pointer. It returns a whole number of type ___.
A. long
B. int
C. short
D. double

Q NO 60:
The statement cout << yptr will show the_____the yptr points to.
A. Value
B. Variable
C. None of given
D. Memory Address

Q NO 61:
In the case of pointer to pointer or__, the first pointer contains the address of the second pointer, which contains the address of the variable, which contains the desired value.
A. Different
B. Float and double
C. Single dereference
D. Double dereference

Q NO 62:
A structure is a collection of_____under a single name.
A. Array
B. Pointer
C. Datatype
D. Variables

Q NO 63:
What will be the output of following program?Int data[10]=[10,20,30,40,50,60,70,80,90,100];Int*yptr=&data[5];
Co<<++yptr
A. 61
B. 51
C. 60
D. 52

Q NO 64:
What is the other name of the variable?
A. Identifier
B. Visual
C. Static
D. Constant

Q NO 65:
Which of the Following is true about streams?
A. It is a sequence of bytes
B. It is an ordered sequence
C. All bytes can go trough the stream simultaneously
D. Bytes that enters first into the stream will go out at last

Mickey ch

Whatsapp#0333-6166150

A. A &D
B. A only
C. C only
D. A & B

Q NO 66:

When No. of repetition is know then we use the structure to perform repetition tasks.

A. While loop
B. For loop
C. Switch
D. Do while loop

Q NO 67:

Shifting the binary number is similar to shifting the ___ number.

A. Base 7
B. Decimal
C. octal
D. Hexadecimal

Q NO 68:

In do while loop the , condition is checked one execution of loop.

A. Before
B. During
C. At Any time
D. After

Q NO 69:

We can read, write and manipulate the same file using--.

A. Stdio.h
B. Fsteram. h
C. Iomanp.h
D. Iostream.h

Q NO 70:

< , <=, >, >= are called____operators.

A. Arithmetic
B. Conational
C. Logical
D. Relational

Q NO 71:

For breaking complex problem into smaller pieces we use --.

A. Function
B. Loops
C. If/else
D. Break statement

Q NO 72:

In three – dimensional array. We use------- 'for loop(s)' to populate the array.

A. 3
B. 2
C. 1
D. 4

Q NO 73:

a = a +1: can be written as ----------

A. 1 + a = a:
B. a+a+1
C. a+=1
D. a+1

Mickey ch

Learning With Mickey ch

Q NO 74:
If a file is opened with ios: : out mode . then --.
A. We can write in this file
B. Content of file discarded
C. A new file is created
D. File is deleted

Q NO 75:
---------- operator is used to pass the address of variable in call by reference method.
A. &
B. @
C. %
D. +

Q NO 76:
C++ is a ------- language.
A. Machine
B. Low level
C. Assembly language
D. High level

Q NO 77:
By writing a file seekg (15L. ios : : cur) we are moving --.
A. 15 bit in the backward direction starting from the pervious position.
B. 15 bit in the backward direction starting from the current position.
C. 15 bytes in the backward direction starting from the pervious position.
D. 15 bytes in the forward direction starting from the perviousposition.

Q NO 78:
Pointer points to a particular --.
A. Data types
B. Variable
C. Memory address
D. value

Q NO 79:
We can access a global variable--.
A. From anywhere in the program
B. From the main() function only
C. From the function only
D. From the loop only

Q NO 80:
If y= 20 and z = y++. Then the value of z will be--.
A. 22
B. 20
C. 21
D. 19

Q NO 81:
Suppose we have a file with name "my file .txt". What will be the correct syntax of file opening for theinput.
A. myFile. In("myfile. txt". Ios : :open):
B. myFile. open("myfile. txt". Ios : :in):
C. myFile. Input("myfile. txt". Ios : :open):
D. myFile. open("myfile. txt". Ios : :inpt):

Q NO 82:
The structure which can execute zero or more times is called --.
A. For structure

Mickey ch

B. Do- while loop
C. While structure
D. None of the above

Q NO 83:

Which of the following is the correct way to write a compound assignment operator?

A. X + = 4:
B. X+=4:
C. X+==4:
D. None of the above

Q NO 84:

Char name []= "Hello world" : In the above statement. A memory of characters will be allocated.

A. 10
B. 12
C. 13
D. 11

Q NO 85:

This reference to variable can be obtained by preceding the identifier of a variable with --.

A. Dot operator
B. Ampersand sign &
C. ^sign
D. *operator

Q NO 86:

A friend function of a class is a function defined --.

A. Inside that class and that has no access to the member of the class
B. Output that class that right to access public member of the class only
C. Outside that class and that has the right to access all member ofclass.
D. Outside that class and that has the right to access all member of the class

Q NO 87:

Initializing the data member within the class is --.

A. A logical error
B. A run time error
C. A syntax error
D. Not an error

Q NO 88:

Programmer should be very careful about the memory management because it can --.

A. Cause problem of memory leakage and dangling pointers.
B. Creates problem of null pointer
C. Returns void pointers
D. Affects the logic of the program

Q NO 89:

Something after allocating memory we need additional space for this purpose we use

A. Reallocation function
B. Calloc function
C. Realloc function
D. Void pointer

Q NO 90:

The constructor contains --.

A. Return type
B. No return type
C. Objects
D. Classes

Mickey ch

Learning With Mickey ch

Q NO 91:

Encapsulation means -- --.

A. That the data of a class cannot be accessed from outside
B. That the data of a class can be accessed from outside
C. That data becomes public
D. That the data can be accessed anywhere within a main program

Q NO 92:

Following is the declaration of 2D array how many column are declaredfor this array
int arr[3][2];

A. 3
B. 4
C. 2
D. 1

Q NO 93:

In computer system there are mainly — type of software

A. 4
B. 2
C. 6
D. 8

Q NO 94:

What is output of following code?
Int data [10] = {10,20,30,40,50,60,70,80,90,100};
Int*xptr=&data[4]; Int *xptr
=&data [6]; Cout< < xptr+yptr++;?

A. 120
B. 110
C. 115
D. 125

Q NO 95:

For the following statement, how much memory will be allocated to myarray[0]
Char*myarray[] = {“arif”,”sadia”}

A. 5 bytes
B. 4 bytes
C. 3 bytes
D. 1 bytes

Q NO 96:

What will be the output of the following code segment?Char
myName[]=”student ID”; Int n=sizeof(myName);Cout<<n;

A. 10
B. 11
C. 12
D. 15

Q NO 97:

To read command-line arguments, the main() function itself must be given
_____arguments.

A. 2
B. 3
C. 1
D. 4

Q NO 98:

_____are conventional names of the command line parameters of the‘main()’

Mickey ch

Whatsapp#0333-6166150

function.

A. ‘argb’ and ‘argv’
B. ‘argc’ and ‘argv’
C. ‘argc’ and ‘argu’
D. None of Given

Q NO 99:

In C-language the string "AZMAT" is equal to_____.

A. Azmat
B. azmat
C. AZMAT
D. None of the given

Q NO 100:

How many bytes an integer type pointer intPtr will jump in memory ifthe statement below is executed? intPtr += 2 ;

A. 2
B. 4
C. 8
D. 12

Q NO 101:

"multi [3][3]" element can also be accessed by '____'.

A. **(multi+3)+3
B. *(*(multi+3)+3)
C. *(multi+3)
D. None of the given

Q NO 102:

In_____, we try to have a precise problem statement.

A. Analysis
B. Design
C. Coding
D. None of the given

Q NO 103:

Which header file must be included to use the functions tolower() antoupper()?

A. iostream.h
B. conio.h
C. ctype.h
D. stdlib.h

Q NO 104:

The statement cout<< yptr will show the_____yptr points to.

A. Value
B. memory address
C. Variable
D. None of the given

Q NO 105:

_____contains function for manipulations of character data.

A. ctype.h
B. iostream.h
C. string.h
D. None of the given

Q NO 106:

How we declare an array of integer data whose size is 20 with arrayname "count".

A. int count[19];
B. int count[20];

Mickey ch

C. float count[20];
D. int count[21];

Q NO 107:

The parameter passed to isdigit() function is_____variable.

A. Character
B. Boolean
C. Integer
D. Float

Q NO 108:

We must include the header file _____to convert the value of onetype into another type using built-in functions.

A. conio.h
B. stdlib.h
C. string.h
D. iostream.h

Q NO 109:

We can say that a pointer is a variable that hold the_____address.

A. byte code
B. source code
C. memory
D. compiler

Q NO 110:

An object of _____class can be created of saving the currentposition of any opened file before reading from the file.

A. Stream
B. Filepos
C. Streampos
D. Filestream

Q NO 111:

From following; which one is the correct syntax of an array initialize:Array size is 10 and it is of double data type to value 0?

A. arr[10]={0.0};
B. double arr[10]=0.0;
C. double arr[10]={0.0};
D. double arr[]=0.0;

Q NO 112:

Suppose that an integer type contains a memory address 0x22f220. Whatwill be the new memory address if we increment this pointer by one?

A. 0x22f221
B. 0x22f222
C. 0x22f223
D. 0x22f224

Q NO 113:

When we access a multidimensional array, each index is surrounded by__.

A. Single quotes "
B. Double quotes ""
C. Brackets []
D. Commas ,,

Q NO 114:

The statement cout << yptr will show the _____the yptr points to.

A. Value

Mickey ch

B. memory address
C. Variable
D. None of the given

Q NO 115:

_____Returns true if c is a digit and false otherwise.

A. int isalpha(int c)
B. int isalnum(int c)
C. int isxdigit(int c)
D. int isdigit(int c)

Q NO 116:

The increment of a pointer depends on its_____.

A. variable
B. value
C. data type
D. None of the given

Q NO 117:

char name [] ="Hello World"; In the above statement, a memory of_charaters will beallocated.

A. 13
B. 11
C. 12
D. 10

Q NO 118:

These functions seekg() and seekp() requires an argument of type___to let them how many bytes to move forward or backward.

A. int
B. short
C. long
D. double

Q NO 119:

_____are conventional names of command line parameters of the'main()' function.

A. 'argb' and 'argv'
B. 'argc' and 'argv'
C. 'argc' and 'argu'
D. None of the given

Q NO 120:

In Analysis, we try to have a_____.

A. Determined the inputs
B. Break up of problem
C. Precise problem statement
D. None of the given

Q NO 121:

In C++, what will be the highest index of the following array?int array[15];

A. 16
B. 15
C. 14
D. 13

Q NO 122:

To get the value stored at a memory address, we use the_____.

A. refrencing operator
B. dereferencing operator
C. simple operator

Mickey ch

D. None of the given

Q NO 123:

Suppose that an integer type pointer contains a memory address 0x22f220. What will be the new memory address if we increment thispointer by one?

A. 0x22f221
B. 0x22f222
C. 0x22f223
D. 0x22f224

Q NO 124:

We use _____to open a file or stream for extraction.

A. in
B. out
C. app
D. ate

Q NO 125:

_____is the pointer which determines the position in a file fromwhere the next read operation occurs.

A. Set
B. Get
C. Put
D. Tell

Q NO 126:

From the following; hich one is the correct syntax of an arraydeclaration: array size 5 and it is of float data type?

A. float [5] name;
B. name [5] float;
C. float name[5];
D. None of the given options

Q NO 127:

dereferencing operator is represented by_____.

A. *
B. +
C. _
D. None of the given

Q NO 128:

Given a two dimensional array of integers, what would be the correctway of assigning the value 6 to the element at third row and fourth column?

A. array[3][4]=6
B. array[2][4]=6
C. array[4][3]=6
D. array[2][3]=6

Q NO 129:

To manipulate n-dimensional array_nested loops arerequired.

A. n-2
B. n-1
C. n+1
D. **n**

Q NO 130:

By default, the starting index of an array in C++ is_____.

A) 2
B) -1

Mickey ch

C) **0**
D) 1

Q NO 131:

What will be the correct syntax of declaration of the followingstatement?
"ptr is a pointer to const int"

A. int const* ptr
B. int * const ptr
C. const int * ptr
D. const * int ptr

Q NO 132:

What will be the size of following array? int arr[29];

A. 0
B. 30
C. 29
D. 28

Q NO 133:

char **argv can be read as _____.

1. pointer to pointer
2. pointer to char
3. pointer to pointer to char
4. None of the given

Q NO 134:

What will be the size of the array declared as int array[1000];

A. 999
B. 1000
C. **1001**
D. 1002

Q NO 135:

suppose we have int y[10];To access the 4th element of the array we write.

A. y[4];
B. y[3];
C. y[2];
D. None of given

Q NO 136:

All elements of an array must be of_____data type(s).

A. char and int
B. Same
C. Different
D. float and double

Q NO 137:

ofstream is used for_____.

A. Input file stream
B. Output file stream
C. Input and output file stream
D. All of the given

Q NO 138:

Following is the declaration of a array. Int arr[2][2][2]

A. 2 –Dimensional
B. 3 –Dimensional
C. 1 –Dimensional
D. None of the given

Mickey ch

Learning With Mickey ch

Q NO 139:

To get the value stored at a memory address , we use the --.

A. Referencing operator
B. Binary operator
C. dereferencing operator
D. AND(&&) operator

Q NO 140:

In do while loop the condition is checked one execution of loop.

A. During
B. Before
C. At any time
D. After

Q NO 141:

The expression ((a +b)== 10) &&((X + Y)==20) is true only if --.

A. ((a+ b) == 10)is true
B. Both ((a + b) ==10)and ((x +Y) == 20) are true
C. Either ((a + b) == 10) or ((X +Y) == 20) is true
D. ((X + Y) == 20 is true

Q NO 142:

From the following; which one is the correct syntax of an array declaration; array size is 5 and it offloat data type?

A. [5] float name;
B. Float name [5];
C. Name[5]float;
D. Float[5] name;

Q NO 143:

Compiler translates high language program into____language code.

A. Java
B. Machine
C. C
D. C++

Q NO 144:

a ^= b; can be written as

A. a= b^a;
B. a^=a+b
C. a=a^+b;
D. a=a^b;

Q NO 145:

There is a pointer variable named ptr of type float. Which type of variable address can be stored by ptr?

A. Int
B. Char
C. Float
D. double

Q NO 146:

Structure use___for memory allocation

A. Cache
B. Stack
C. Heap
D. Queue

Q NO 147:

Individual characters in a string stored in an array can be accessed directly using array --.

Mickey.ch

Whatsapp#0333-6166150

A. Subscript
B. Script
C. Value
D. Superscript

Q NO 148:

MS word is type of___software

A. Application
B. Device Driver
C. Operating system
D. utility

Q NO 149:

Identify the logical error in the following if condition If ((i<5) &&(i>5))

A. & will be used instead of &&
B. && cannot be used with if condition
C. Condition is always true
D. Condition is always false

Q NO 150:

If int a = 50; then the value of a/=3; will be

A. 18
B. 15
C. 17
D. 16

Q NO 151:

Which is the correct syntax to define a structure named "student"?

A. Struct student(//variable);
B. Struct student{//variable};
C. Structure student(//variable);
D. Structure student{//variable};

Q NO 152:

In C/C++, a variable's name can start with the symbol --.

A. -Underscore
B. +Plus
C. :Colon
D. ;semicolon

Q NO 153:

aFile- seeking (-10L,ios:cur)

A. Both direction
B. None of the given
C. Backward direction
D. Forward direction

Q NO 154:

=operator is used for--.

A. Checking equality
B. Decision making
C. Comparison
D. Assigning values to cariables

Q NO 155:

If function has not been, declared before it is a --.

A. Run time error
B. Logical error
C. Syntax error

Mickey ch

D. Late binding error

Q NO 156:

---------- statement is used to terminate the processing of a particular case and exit from switch structure.

A. Break
B. If
C. Goto
D. continue

Q NO 157:

In the following nested For Loop, which loop will run most number of times?

For (int I = 0 : k : 5 K++)
{
For (int k = 0 : k <: 5: k++)
{
……
}

A. Inner loop
B. Depends upon the statements in the inner in the loop body
C. Outer loop
D. Both loop run equal number of time

Q NO 158:

Structures are syntactically defined with the word --.

A. Struct
B. Struc
C. Structure
D. None of the given

Q NO 159:

What will be the value of the variable output in the given piece of the code? Double output = 0
Out put = (2 + 2)*4+ 2 /(4- 2):

A. 17
B. 11
C. 15
D. 12

Q NO 160:

Which one of the following languages has been used to write the compiler of "C "language?

A. C
B. Basic
C. Fortran
D. Java

Q NO 161:

What will be output of following code segment? For

(intI=2,i< 10: i++){

If (i==5)
Continue: Cout <<i<<".":}

A. 2, 3, 4
B. 2, 3,4,6,7,8,9
C. 4,6,7,8,9
D. 2,3,7,8,9

Mickey ch

Learning With Mickey ch

Q NO 162:

Identify the correct syntax for making a class friend of other class

A. class Class one{friend otherclass

B. friend ClassOne{OtherClass

C. ClassOne{friend otherclass

D. friend class ClassOne{friend otherclass

Q NO 163:

The function will be return a reference to the global variable that exits throughout the promgram and thus there will be no danger of --.

A. Garbage collection

B. Dangling reference

C. Wastage of memory

D. System crash

Q NO 164:

Friend classes are used in cases where one class is to another class

A. Lightly coupled

B. Loosely coupled

C. Independent

D. encapsulted

Q NO 165:

#define CIRCUMFERENCE(X) (2*pl * R) is a

A. user defined function

B. library function

C. definition of a macro

D. utility function

Q NO 166:

Header files provide so the program running on one operating system can run without an error on the other system.

A. Accessibility

B. Reliability

C. Accuracy

D. portability

Q NO 167:

------ will return the number of bytes reserved for a variable or data type.

A. Size of operation

B. Free operator

C. Void pointer

D. New operator

Q NO 168:

Default constructor takes --.

A. One parameter

B. Two parameter

C. No parameter

D. Character type paremeter

Q NO 169:

Void calloc(50,sizeroof(int))will return

A. Char pointer

B. A memory chunk of 50 integers from heap

C. A memory chunk of 50 integers from stack

D. A memory chunk with zero pointer

Q NO 170:

Mickey ch

Whatsapp#0333-6166150

Learning With Mickey ch

We cannot increment --.

A. Pointer
B. Arrays
C. References
D. variables

Q NO 171:

Symbolic constant pI can be defined as:

A. #define PI 3.14;
B. #define PI 3.14
C. #define Pi =3.14
D. #include pi= 3.14

Q NO 172:

Special name which is substituted in code by its definition and as a reslt we get anexpanded code is called

A. Union
B. Directive
C. Macro
D. Array

Q NO 173:

In a class we can have constructor(s).

A. Only one
B. No
C. Two
D. Many

QNO 174:

For accessing data members we use operator

A. plus+
B. multiplication*
C. dot.
D. Division/

Q NO 175:

The memory allocation in C++ is carried out with the help of --.

A. NULL Pointer
B. New operator
C. Dot operator
D. +operator

Q NO 176:

C++ offers --- levels of data access control inside a class.

A. Three
B. Four
C. Two
D. five

Q NO 177:

The object code of our program is combined with the --.

A. Source program
B. Machine code of the operating system
C. Object code of the library functions
D. With header files

Q NO 178:

Initializing the data member with in the class is --.

A. A logical error

Mickey ch

Whatsapp#0333-6166150

B. A run time error
C. A syntax error
D. Not an error

Q NO 179:

Look at the program code and identify the error. 1 #include <iostream.h>
#define PI3.1415926; //Defining PI
main()
{
int radius =5:
cout <<"Area of circle with radius " <<radius "="<<PI*radius * radius;
}

A. It will be compiled successfully and will not generate error
B. It will be compiled and return nothing
C. Error exists in line number 2 semi colon is not allowed definedirective
D. The value of PI cannot be defined in the beginning

Q NO 180:

To prevent dangling reference the function returning reference should be sued with --.
A. Local variables
B. Global variables only
C. Arrays
D. Static and global variables

Q NO 181:

The function will return a reference to the global variable that exits throughout the program and thusthere will be no danger of --.
A. Garbage collection
B. Dangling reference
C. Wastage of memory
D. System crash

Q NO 182:

What will be the output of the given code? #include

<iostearm.h>

Inline int max(int a, int b)
{
if(a>b) return a; return b;
} main()
{
int I x,y;
x= 23; y=45
I = max (x++, y++); Cout<< "x="<<"y="

'/n';

}

A. X 23 y 45
B. X 24 y 46
C. X 22 y 46
D. X 23 y 47

Q NO 183:

The difference b/w pointer and references is that --.

Mickey ch

A. We cannot do arithmetic with pointers
B. We can do arithmetic with pointes
C. We cannot reassign pointers
D. We can assign references

Q NO 184:

If you create a header file of your own and you save it in the "Header file" folder which is located on the current working directory then you must enclose your header file within --.

A. Braces
B. Quotation marks
C. #sign
D. Angle brackets

Q NO 185:

Reference Variables must---.

A. Not be initialized after they are declared
B. Be initialized after they are declared
C. Contain integer value
D. Contain zero vlaue

Q NO 186:

Word processor is

A. Operating system
B. Application software
C. Device driver
D. Utility software

Q NO 187:

Which of the following operator is used to access the value of variable pointed to by a pointer?

A. operator
B. operator
C. && operator
D. & operator

Q NO 188:

Paying attention to detail in designing a program is _____

A. Time consuming
B. Redundant
C. Necessary
D. Somewhat Good

Q NO 189:

The while loop becomes infinite,

A. When the condition is always false
B. When the condition is less than zero
C. When the condition is always true
D. When the condition contains a logical operatoR

Q NO 190:

Which of the following function(s) is/are included in stdlib.h header file

A. double atof(const char *nptr)
B. int atoi(const char *nptr)
C. char *strcpy (char *s1, const char *s2)
D. 1 and 2 only

Q NO 191:

Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

Mickey ch

A. cout << "Hello" + x + "\n";
B. cout << "H" << x << "\n";
C. cout << "H", x, "\n";
D. cout << ("H" & x & "\n");

Q NO 192:

Which of the following is correct way to initialize a variable x of int type with value 10?

A. int x ; x = 10 ;
B. int x = 10 ;
C. int x, x = 10;
D. x = 10 ;

Q NO 193:

Which of the following is used with bit manipulation?

A. Signed integer
B. Un-signed integer
C. Signed double
D. Un-signed double

Q NO 194:

A precise sequence of steps to solve a problem is called

A. Statement
B. Program
C. Utility
D. Routine

Q NO 195:

Initialization of variable at the time of definition is,

A. Must
B. Necessary
C. Good Programming
D. None of the given options

Q NO 196:

In if structure the block of statements is executed only,

A. When the condition is false
B. When it contain arithmetic operators
C. When it contain logical operators
D. When the condition is true

Q NO 197:

Pointer is a variable which store,

A. Data
B. Memory Address
C. Data Type
D. Values

Q NO 198:

Preprocessor program perform its function before _____ phase takes place

A. Editing
B. Linking
C. Compiling
D. Loading

Q NO 199:

Which of the following can not be a variable name?

A. Area

Mickey ch

B. _area
C. 10area
D. area2

Q NO 200:

Which character is inserted at the end of string to indicate the end of string?

A. New
B. line
C. tab
D. null

Mickey ch